Technical Data Sheet
OPUDA'S Weathershield

Product code OPD-WS - Emulsion range - Revision 2026-09

This sheet states the figures used by the product page and the paint calculator on opudapaint.com. Coverage is quoted for one coat on a sound, sealed surface; porous substrates absorb more.

SPECIFICATION

Finish	Textured exterior coating
Coverage	6 m2 per litre, single coat
Recommended coats	2
Touch dry	2 hours
Recoat	6 hours
Full cure	14 days
Thinning	Do not thin. Stir thoroughly; trowel or heavy roller.
VOC / base	Water-based acrylic
Surfaces	Exterior render, facades, boundary walls, parapets
Pack sizes	10 L - 20 L
Guarantee	5 years

PRODUCT CLAIMS (AS PRINTED ON THE PAIL)

- Bridges hairline cracks
- UV and colour stable
- Breathable film
- Rain resistant after 24 hours

APPLICATION

1. Remove efflorescence, treat mould, repair honeycombing.
2. Prime with OPUDA'S Primer, or a bonding agent on chalky render.
3. Coat 1: work from the top of the elevation downwards.
4. Coat 2: after 6 hours. Protect from rain for 24 hours.

LIMITATIONS

Do not apply when the substrate or ambient temperature is below 10 degC, or when relative humidity is above 85%. Do not apply over active damp, mould or efflorescence: correct the cause first. Do not wash the film for 7 days. Colour on a screen cannot guarantee a physical match; approve a painted sample on the actual wall before full application.

GUARANTEE

The guarantee applies to the supplied product when applied in accordance with this sheet, on a sound and correctly prepared substrate, in the specified system. It does not cover failure caused by structural movement, water ingress, inadequate preparation or application outside these instructions.

Digital values are approximations; physical chips are the authority.