Safety Data Sheet
OPUDA'S Weathershield

Product code OPD-WS - Revision 2026-09 - Prepared in the four-part SDS format used in Nigeria.
Read this sheet before use. It does not replace a site-specific risk assessment.

1. IDENTIFICATION

Product as named above. Manufacturer: OPUDA'S PAINT, Lagos, Nigeria. Emergency telephone: 0902 642 4350 (Monday to Saturday, 08:00-18:00 WAT).

2. HAZARDS IDENTIFICATION

Water-based products are not classified as hazardous under GHS. Solvent-based gloss contains flammable solvent: keep away from ignition sources, avoid inhalation of vapour. Wet paint is a mild eye and skin irritant. Sanding dust from cured film may be irritant.

3. COMPOSITION

Acrylic/styrene-acrylic polymer dispersion, titanium dioxide, calcium carbonate, silicate extenders, water, glycol ether coalescent, preservative and anti-fungi additive, defoamer, thickener. Exact formulation is withheld as confidential business information.

4. FIRST AID

Eyes: rinse with clean water for 15 minutes, holding the lids open. Seek medical advice if irritation persists. Skin: wash with soap and water. Inhalation: move to fresh air. Ingestion: do not induce vomiting; rinse mouth and seek medical advice.

5. FIRE FIGHTING

Water-based products are non-flammable; use media appropriate to the surrounding fire. Solvent-based gloss: foam, dry powder or CO2. Do not use a direct water jet on burning solvent.

6. ACCIDENTAL RELEASE

Contain with sand or earth; do not allow to enter drains or watercourses. Collect into a labelled container for disposal. Wash the area with water.

7. HANDLING AND STORAGE

Store between 5 degC and 35 degC, out of direct sunlight, with the lid firmly closed. Protect from frost. Keep out of reach of children. Do not store near food or drink.

8. EXPOSURE CONTROLS

Water-based: general ventilation is adequate. Solvent-based: ensure local exhaust ventilation; wear solvent-resistant gloves and eye protection. Respiratory protection if spraying.

9. PHYSICAL PROPERTIES

Appearance: pigmented liquid. Odour: low (water-based) / solvent (gloss). pH 8-9. Density approximately 1.3-1.5 g/cm3. Solubility: miscible with water before curing.

10. STABILITY AND REACTIVITY

Stable under normal conditions. Protect from freezing; freezing permanently damages the dispersion.

11. TOXICOLOGICAL INFORMATION

Digital values are approximations; physical chips are the authority.

No acute systemic toxicity expected from normal use. Prolonged skin contact may cause dermatitis in sensitised individuals.

12. ECOLOGICAL INFORMATION

Do not allow to enter drains or watercourses. Cured film is inert. Dispose of unused product through an authorised waste contractor.

13. DISPOSAL

Allow small residues to dry in the container and dispose of as household/industrial waste in accordance with local regulations. Do not pour liquid paint down drains.

14. TRANSPORT

Not classified as dangerous goods for transport in the pack sizes supplied, with the exception of solvent-based gloss above the applicable flammable liquid threshold.

15. REGULATORY INFORMATION

Classified in accordance with the GHS as adopted in Nigeria. Safety data sheet prepared in line with the four-part SDS format used in Nigeria.

16. OTHER INFORMATION

This sheet is reviewed annually. The current revision date is printed on the document footer. It does not replace a site-specific risk assessment.

Digital values are approximations; physical chips are the authority.