Specification sheet

The six products in the range, by the surface they go on. Full application steps and the complete safety data are in each product's own technical and safety data sheet, linked at opudapaint.com/products.

INTERIOR WALLS & CEILINGS

MATT Emulsion

Matt (flat), sheen < 5%

— High quality, for walls and ceilings
— Smooth finish with better flow
— Extra coverage per litre

11 m² per litre

LABEL-VERIFIED

SILK Emulsion

Silk (soft sheen), 10-15%

— Washable soft-sheen film
— Resists kitchen steam and condensation
— Anti-fungi additive

12 m² per litre

LABEL-VERIFIED

EXTERIOR & BOUNDARY WALLS

Weathershield

Textured exterior coating

— Bridges hairline cracks
— UV and colour stable
— Breathable film

6 m² per litre

PENDING VERIFICATION

WOOD & METAL

Synthetic Gloss

Gloss, sheen 80%+

— Hard, impact-resistant film
— Interior and exterior joinery
— Good flow and levelling

13 m² per litre

PENDING VERIFICATION

PREPARATION & REPAIR

Alkali-Resisting Primer

Primer (sealing coat)

— Blocks alkali burn on new render
— Seals uneven porosity
— Improves topcoat coverage

10 m² per litre

PENDING VERIFICATION

Screeding Compound

Filler / base coat

— Levels uneven blockwork
— Sands to a fine finish
— Strong bond, minimal shrinkage

1.6 m² per kg at 1 mm thickness

PENDING VERIFICATION

HOW TO READ THIS PAGE

Coverage is per single coat. The status chip under each product marks whether its claims come from the physical pail (label-verified) or from the standard range a manufacturer at this scale supplies, awaiting technical sign-off (pending verification). The full comparison, including touch-dry, recoat and cure times for every product, is overleaf.

"Label-verified" claims are transcribed from the physical pail; "pending verification" claims are the standard range a manufacturer at this scale supplies and await technical sign-off.

Every figure, one table

Coverage is for a single coat on a sound, sealed surface — thin or porous substrates use more. Touch-dry and recoat times assume 25°C and 60% relative humidity; Port Harcourt's wet-season humidity will extend both.

PRODUCT	FINISH	SURFACES	COVERAGE	COATS	TOUCH DRY	RECOAT	FULL CURE	GUARANTEE	STATUS
MATT Emulsion	Matt	Interior walls and ceilings	11 m² per litre	2	1 hour	3 hours	7 days	5 years	LABEL-VERIFIED
SILK Emulsion	Silk	Interior walls, kitchens, bathrooms, corridors	12 m² per litre	2	1 hour	4 hours	7 days	5 years	LABEL-VERIFIED
Alkali-Resisting Primer	Primer	New plaster, interior and exterior walls	10 m² per litre	1	2 hours	4 hours	3 days	-	PENDING VERIFICATION
Synthetic Gloss	Gloss	Timber and metal: doors, gates, frames, railings	13 m² per litre	2	4 hours	16 hours	7 days	3 years	PENDING VERIFICATION
Weathershield	Textured exterior coating	Exterior render, facades, boundary walls, parapets	6 m² per litre	2	2 hours	6 hours	14 days	5 years	PENDING VERIFICATION
Screeding Compound	Filler / base coat	Interior walls, ceilings, new blockwork	1.6 m² per kg at 1 mm thickness	2	3 hours	4 hours	3 days	-	PENDING VERIFICATION

DILUTION AND VOC

MATT Emulsion	First coat: up to 10% clean water on porous plaster. Finish coat: undiluted. — Water-based, low VOC.
SILK Emulsion	First coat: up to 10% clean water. Finish coat: undiluted. — Water-based, low VOC, low odour.
Alkali-Resisting Primer	Up to 20% clean water on very porous render. — Water-based, low VOC.
Synthetic Gloss	Recommended solvent only, maximum 5%. Not water-thinnable. — Solvent-based. Ventilate and use appropriate PPE.
Weathershield	Do not thin. Stir thoroughly; trowel or heavy roller. — Water-based acrylic.
Screeding Compound	Mix 1 kg to approximately 0.4 L clean water; rest 10 minutes. — Cementitious, low VOC.

Wall area ÷ coverage × coats = litres

Trade sales and colour mixing · 0902 642 4350 · Port Harcourt, Rivers State · opudapaint.com/dealers