This module will be imported into every implementation

## EXTENDS Sequences

An ordered event stream of every event that occurs in the system. All the specifications will be written based on it. This is an observability value that you wouldn't have access to in the implementation. We'll only have the API method stubs write to it; no implementation may read from it. This will be enforced with code review

VARIABLE events

Represents every potential user in the system

CONSTANT USERS

Constants that should be set to single model values to allow comparisons.

Only equality comparisons will be made.

CONSTANTS

 $EventsOk \triangleq$ 

SubscriptionFee,

Cancellation Fee,

FailedPaymentFee

 $Fees \triangleq \{SubscriptionFee, CancellationFee, FailedPaymentFee\}$ 

Event Types: Describes everything that can happen in the system

```
\begin{aligned} & \textit{MonthPassEvent} \; \triangleq \; [\textit{type}: \{\; \text{``monthpass''}\}] \\ & \textit{StartSubscriptionEvent} \; \triangleq \; [\textit{type}: \{\; \text{``startsubscription''}\}, \, \textit{user}: \, \textit{USERS}] \\ & \textit{CancelSubscriptionEvent} \; \triangleq \; [\textit{type}: \{\; \text{``cancelsubscription''}\}, \, \textit{user}: \, \textit{USERS}] \\ & \textit{StartTrialEvent} \; \triangleq \; [\textit{type}: \{\; \text{``starttrial''}\}, \, \textit{user}: \, \textit{USERS}] \\ & \textit{CancelTrialEvent} \; \triangleq \; [\textit{type}: \{\; \text{``canceltrial''}\}, \, \textit{user}: \, \textit{USERS}] \\ & \textit{WatchVideoEvent} \; \triangleq \; [\textit{type}: \{\; \text{``watchvideo''}\}, \, \textit{user}: \, \textit{USERS}] \\ & \textit{BillEvent} \; \triangleq \; [\textit{type}: \{\; \text{``bill''}\}, \, \textit{user}: \, \textit{USERS}, \, \textit{fee} \; : \, \textit{Fees}] \\ & \textit{PaymentFailedEvent} \; \triangleq \; [\textit{type}: \{\; \text{``paymentfailed''}\}, \, \textit{user}: \, \textit{USERS}, \, \textit{fee} \; : \, \textit{Fees}] \\ & \textit{Event} \; \triangleq \; \\ & \textit{MonthPassEvent} \; \cup \\ & \textit{StartSubscriptionEvent} \; \cup \\ & \textit{StartTrialEvent} \; \cup \\ & \textit{StartTrialEvent} \; \cup \\ & \textit{CancelTrialEvent} \; \cup \\ & \textit{WatchVideoEvent} \; \cup \\ & \textit{BillEvent} \; \cup \\ & \textit{BillEvent} \; \cup \\ & \textit{PaymentFailedEvent} \end{aligned}
```

## $events \in Seq(Event)$

- \\* Modification History \\* Last modified Fri Jun 17 00:07:38 MST 2022 by elliotswart \\* Created Thu Jun 16 20:19:00 MST 2022 by elliotswart