

Credential Phishing Investigation

Domain: auth-login.pages.dev

Status: **MALICIOUS** Date: May 28, 2026

Prepared by: Jessica Sansaricq

01 — EXECUTIVE SUMMARY

This report documents the investigation of a credential-harvesting campaign hosted on the domain auth-login.pages.dev, which was flagged as malicious by Google Safe Browsing and confirmed active by VirusTotal. The page displayed a login interface with an Arabic-language title, suggesting it may be targeting users in Arabic-speaking regions or impersonating a service popular in those markets.

The site is hosted on Cloudflare's infrastructure — a common tactic used by phishing actors to hide behind legitimate, trusted providers and complicate takedown efforts. Passive DNS analysis of the associated IP addresses revealed dozens of additional suspicious domains sharing the same hosting, indicating this is likely part of a broader, ongoing phishing operation.

02 — TECHNICAL FINDINGS

Infrastructure Details

Field	Value
Domain	auth-login.pages.dev
IP Addresses	172.66.44.83 · 172.66.47.173 · 172.66.45.32
Hosting Provider	Cloudflare, Inc. (AS13335)
Hosting Location	San Francisco, California, United States
VirusTotal Detection	1 / 91 vendors flagged
Google Safe Browsing	MALICIOUS
First Submission (VT)	April 15, 2026
Page Title Observed	Arabic: "Logging in..."
Open Ports	80, 443, 2052, 2053, 2082, 2083, 2086, 2087, 2095, 6443, 8080, 8443, 8880
WHOIS Privacy	Registrant hidden — ownership not publicly available
OTX Threat Pulses	0 active pulses (infrastructure-level indicators only)

Related Suspicious Domains

The following domains share the same Cloudflare infrastructure and exhibit similar suspicious naming patterns:

- ▶ ledger-start-cloud.pages.dev
- ▶ asset-finance-hitsmore.pages.dev
- ▶ ai-gateway-admin-2nc.pages.dev
- ▶ okx-web3-tron-usdt-trc20-000000774.pages.dev
- ▶ help-kraken-co-eng.pages.dev
- ▶ en-live-docs-ledger.pages.dev
- ▶ tacticalcyber-couk.pages.dev

03 — MITRE ATT&CK® MAPPING

Threat Technique Mapping

Technique ID	Technique Name	Tactic	Description
T1566	Phishing	Initial Access	The domain mimics a legitimate login page to trick users into entering credentials, a direct example of phishing used to gain initial access to accounts or systems.
T1598	Phishing for Information	Reconnaissance	The active login form is designed to harvest credentials — usernames, passwords, or session tokens — the hallmark of a spearphishing-for-information campaign.
T1583.001	Acquire Infrastructure: Domains	Resource Development	The threat actor registered a deceptively named subdomain (auth-login.pages.dev) on a trusted platform to lend legitimacy to the phishing site and evade detection.
T1090.002	Proxy: External Proxy	Command & Control	All infrastructure sits behind Cloudflare's reverse proxy, masking the true origin server and making attribution and takedown significantly harder.

04 — RECOMMENDATIONS

Defensive Actions

- 1 Block the Domain at the DNS Layer**
Add auth-login.pages.dev and all related IOC domains to your corporate DNS filtering solution (e.g. Cisco Umbrella, Palo Alto DNS Security) immediately.
- 2 Add IOCs to SIEM Detection Rules**
Ingest the three IP addresses and all related domains as threat indicators for alerting on any internal traffic touching this infrastructure.
- 3 Report the Domain to Cloudflare's Abuse Team**
Submit a phishing abuse report at abuse.cloudflare.com to request takedown. Include the VirusTotal and Google Safe Browsing references for faster processing.
- 4 Train Users to Verify URLs Before Entering Credentials**
Remind staff that legitimate services will never use a subdomain like pages.dev for login pages, and to check the full URL — not just the visible page title or logo.
- 5 Monitor for Credential Exposure**
If any users may have visited this page, prompt mandatory password resets and check for unusual login activity, particularly from new locations or devices.

05 — CONCLUSION

This campaign reflects a low-effort but effective phishing operation that exploits the trusted reputation of Cloudflare's Pages platform to host credential-harvesting pages. The shared infrastructure hosting dozens of similarly suspicious domains — many targeting cryptocurrency and financial services users — points to an opportunistic actor running a scaled phishing kit rather than a targeted, sophisticated threat.

The ease with which free hosting services can be abused underscores the importance of behavioral detection and user awareness training, since perimeter controls alone are insufficient when malicious content is hosted on legitimate, widely-trusted platforms.