
EasyProcess Documentation

Release 0.0.10

ponty

July 05, 2011

CONTENTS

1	Basic usage	2
2	Installation	3
2.1	General	3
2.2	Ubuntu	3
2.3	Uninstall	3
3	Usage	4
3.1	With	5
3.2	Timeout	5
3.3	Logging	5
3.4	Alias	6
3.5	Replacing existing functions	7
4	API	8
5	Development	10
5.1	Tools	10
5.2	Install on ubuntu	10
5.3	Tasks	11
6	Indices and tables	12
	Index	13

EasyProcess

Date July 05, 2011

PDF EasyProcess.pdf

Contents:

EasyProcess is an easy to use python subprocess interface.

Links:

- home: <https://github.com/ponty/EasyProcess>
- documentation: <http://ponty.github.com/EasyProcess>

Features:

- layer on top of subprocess module
- easy to start, stop programs
- easy to get standard output/error, return code of programs
- command can be list or string
- logging
- timeout
- unittests
- crossplatform, development on linux
- global config file with program aliases

Known problems:

- shell is not supported
- pipes are not supported
- large stdout/stderr was not tested, maybe not efficient
- stdout/stderr is set only after the subprocess has finished
- stop() does not kill whole subprocess tree
- Python 3 is not supported

BASIC USAGE

```
>>> from easyprocess import EasyProcess
>>> EasyProcess('echo hello').call().stdout
'hello'
```

INSTALLATION

2.1 General

- install `setuptools` or `pip`
- install the program:

if you have `setuptools` installed:

```
# as root
easy_install EasyProcess
```

if you have `pip` installed:

```
# as root
pip install EasyProcess
```

2.2 Ubuntu

```
sudo apt-get install python-setuptools
sudo easy_install EasyProcess
```

2.3 Uninstall

```
# as root
pip uninstall EasyProcess
```

USAGE

```
>>> from easyprocess import EasyProcess
>>> # Run program, wait for it to complete, get stdout (command is string):
>>> EasyProcess('echo hello').call().stdout
'hello'
>>> # Run program, wait for it to complete, get stdout (command is list):
>>> EasyProcess(['echo', 'hello']).call().stdout
'hello'
>>> # Run program, wait for it to complete, get stderr:
>>> EasyProcess('python --version').call().stderr
'Python 2.6.6'
>>> # Run program, wait for it to complete, get return code:
>>> EasyProcess('python --version').call().return_code
0
>>> # Run program, wait 1 second, stop it, get stdout:
>>> print EasyProcess('ping localhost').start().sleep(1).stop().stdout
PING localhost.localdomain (127.0.0.1) 56(84) bytes of data.
64 bytes from localhost.localdomain (127.0.0.1): icmp_req=1 ttl=64 time=0.027 ms
64 bytes from localhost.localdomain (127.0.0.1): icmp_req=2 ttl=64 time=0.028 ms
>>> # Run program, wait for it to complete, check for errors:
>>> EasyProcess('ls').check()
<Proc cmd_param=ls alias=None cmd=['ls'] (ls) oerror=None returncode=0 stdout="dist
distribute_setup.py
docs
easyprocess
EasyProcess.egg-info
LICENSE.txt
MANIFEST.in
pavement.py
paver-minilib.zip
README.rst
setup.py
tests
TODO" stderr="" timeout=False>
```

Exceptions in check:

```
>>> EasyProcess('bad_command').check()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "easyprocess.py", line 84, in check
    raise EasyProcessCheckError(self)
easyprocess.EasyProcessCheckError: EasyProcess check failed!
OSError: [Errno 2] No such file or directory
cmd: ['bad_command']
```

```

return code:None
stderr:None
>>> EasyProcess('sh -c bad_command').check()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "easyprocess.py", line 84, in check
    raise EasyProcessCheckError(self)
easyprocess.EasyProcessCheckError: EasyProcess check failed!
OSError:None
cmd:['sh', '-c', 'bad_command']
return code:127
stderr:sh: bad_command: not found

```

3.1 With

By using with statement the process is started and stopped automatically:

```

>>> from easyprocess import EasyProcess
>>> with EasyProcess('ping 127.0.0.1') as proc: # start()
...     # communicate with proc
...     pass
... # stopped
...

```

3.2 Timeout

```

>>> from easyprocess import EasyProcess
>>> # Run ping with timeout
>>> print EasyProcess('ping localhost').call(timeout=1).stdout
PING localhost.localdomain (127.0.0.1) 56(84) bytes of data.
64 bytes from localhost.localdomain (127.0.0.1): icmp_req=1 ttl=64 time=0.027 ms
64 bytes from localhost.localdomain (127.0.0.1): icmp_req=2 ttl=64 time=0.028 ms

```

3.3 Logging

Example program:

```

from easyprocess import EasyProcess
import logging

# turn on logging
logging.basicConfig(level=logging.DEBUG)

EasyProcess('echo hello').call()
EasyProcess('python --version').call()
EasyProcess('ping localhost').start().sleep(1).stop()
EasyProcess('python --version').check()
try:
    EasyProcess('bad_command').check()
except Exception, detail:
    print detail

```



```
try:
    EasyProcess('sh -c bad_command').check()
except Exception, detail:
    print detail
```

Output:

```
$ python -m easyprocess.examples.log
DEBUG:easyprocess:param: "echo hello" command: ['echo', 'hello'] ("echo hello")
DEBUG:easyprocess:reading config: /home/titi/.easyprocess.cfg
DEBUG:easyprocess:process was started (pid=19394)
DEBUG:easyprocess:process has ended
DEBUG:easyprocess:return code=0
DEBUG:easyprocess:stdout=hello
DEBUG:easyprocess:stderr=
DEBUG:easyprocess:param: "python --version" command: ['python', '--version'] ("python --version")
DEBUG:easyprocess:process was started (pid=19396)
DEBUG:easyprocess:process has ended
DEBUG:easyprocess:return code=0
DEBUG:easyprocess:stdout=
DEBUG:easyprocess:stderr=Python 2.6.6
DEBUG:easyprocess:param: "ping localhost" command: ['ping', 'localhost'] ("ping localhost")
DEBUG:easyprocess:process was started (pid=19398)
DEBUG:easyprocess:stopping process (pid=19398 cmd=["'ping', 'localhost'"])
DEBUG:easyprocess:process is active -> sending SIGTERM
DEBUG:easyprocess:process has ended
DEBUG:easyprocess:return code=-15
DEBUG:easyprocess:stdout=PING localhost.localdomain (127.0.0.1) 56(84) bytes of data.
64 bytes from localhost.localdomain (127.0.0.1): icmp_req=1 ttl=64 time=0.026 ms
64 bytes from localhost.localdomain (127.0.0.1): icmp_req=2 ttl=64 time=0.029 ms
DEBUG:easyprocess:stderr=
DEBUG:easyprocess:param: "python --version" command: ['python', '--version'] ("python --version")
DEBUG:easyprocess:process was started (pid=19400)
DEBUG:easyprocess:process has ended
DEBUG:easyprocess:return code=0
DEBUG:easyprocess:stdout=
DEBUG:easyprocess:stderr=Python 2.6.6
DEBUG:easyprocess:param: "bad_command" command: ['bad_command'] ("bad_command")
DEBUG:easyprocess:OSError exception:[Errno 2] No such file or directory
DEBUG:easyprocess:param: "sh -c bad_command" command: ['sh', '-c', 'bad_command'] ("sh -c bad_command")
DEBUG:easyprocess:process was started (pid=19403)
DEBUG:easyprocess:process has ended
DEBUG:easyprocess:return code=127
DEBUG:easyprocess:stdout=
DEBUG:easyprocess:stderr=sh: bad_command: not found
start error <Proc cmd_param=bad_command alias=None cmd=['bad_command'] (bad_command) oerror=[Errno 2]
check error, return code is not zero! <Proc cmd_param=sh -c bad_command alias=None cmd=['sh', '-c', 'bad_command'] (sh -c bad_command) oerror=[Errno 2]
```

3.4 Alias

You can define an alias for EasyProcess calls by editing your config file (\$HOME/.easyprocess.cfg) This can be used for:

- testing different version of the same program
- redirect calls

- program path can be defined here. (Installed programs are not in \$PATH on Windows)

start python and print python version:

```
>>> from easyprocess import EasyProcess
>>> EasyProcess('python --version').call().stderr
'Python 2.6.6'
```

edit the config file: \$HOME/.easyprocess.cfg:

```
[link]
python=/usr/bin/python2.7
```

restart python and print python version again:

```
>>> from easyprocess import EasyProcess
>>> EasyProcess('python --version').call().stderr
'Python 2.7.0+'
```

3.5 Replacing existing functions

Replacing `os.system`:

```
retcode = os.system("ls -l")
==>
p = EasyProcess("ls -l").call()
retcode = p.return_code
print p.stdout
```

Replacing `subprocess.call`:

```
retcode = subprocess.call(["ls", "-l"])
==>
p = EasyProcess(["ls", "-l"]).call()
retcode = p.return_code
print p.stdout
```

API

`easyprocess.EasyProcess`

alias of `Proc`

class `easyprocess.Proc` (*cmd, ubuntu_package=None, url=None, max_bytes_to_log=1000, cwd=None*)

simple interface for `subprocess`

shell is not supported (`shell=False`)

call (*timeout=None*)

Run command with arguments. Wait for command to complete.

Return type `self`

check (*return_code=0*)

Run command with arguments. Wait for command to complete. If the exit code was as expected and there is no exception then return, otherwise raise `EasyProcessError`.

Parameters `return_code` – int, expected return code

Return type `self`

check_installed ()

Used for testing if program is installed.

Run command with arguments. Wait for command to complete. If `OSError` raised, then raise `EasyProcessCheckInstalledError` with information about program installation

Parameters `return_code` – int, expected return code

Return type `self`

is_alive ()

poll process (`subprocess.Popen.poll()`)

Return type `bool`

pid

PID (`subprocess.Popen.pid`)

Return type `int`

return_code

`returncode` (`subprocess.Popen.returncode`)

Return type `int`

sendstop ()

Kill process by sending `SIGTERM`. Do not wait for command to complete.

Return type self

sleep (*sec*)
sleeping (same as `time.sleep()`)

Return type self

start ()
start command in background and does not wait for it

Timeout:

- discussion: <http://stackoverflow.com/questions/1191374/subprocess-with-timeout>
- implementation: threading with polling

Return type self

stop ()
Kill process by sending SIGTERM. and wait for command to complete.
same as `sendstop().wait()`

Return type self

wait (*timeout=None*)
Wait for command to complete.

Return type self

wrap (*callable, delay=0*)

returns a function which:

1. start process
2. call callable, save result
3. stop process
4. returns result

similar to `with` statement

Return type

DEVELOPMENT

5.1 Tools

1. `setuptools`
2. `Paver`
3. `nose`
4. `ghp-import`
5. `pyflakes`
6. `pychecker`
7. `paved fork`
8. `Sphinx`
9. `sphinxcontrib-programsscreenshot`
10. `sphinxcontrib-paverutils`
11. `autorun` from `sphinx-contrib` (there is no simple method, you have to download/unpack/setup)

5.2 Install on ubuntu

```
sudo apt-get install python-setuptools
sudo apt-get install python-paver
sudo apt-get install python-nose
sudo easy_install ghp-import
sudo apt-get install pyflakes
sudo apt-get install pychecker
sudo easy_install https://github.com/ponty/paved/zipball/master
sudo apt-get install scrot
sudo apt-get install xvfb
sudo apt-get install xserver-xephyr
sudo apt-get install python-imaging
sudo apt-get install python-sphinx
sudo easy_install sphinxcontrib-programsscreenshot
sudo easy_install sphinxcontrib-programoutput
sudo easy_install sphinxcontrib-paverutils
```

5.3 Tasks

[Paver](#) is used for task management, settings are saved in `pavement.py`. [Sphinx](#) is used to generate documentation.

print [paver](#) settings:

```
paver printoptions
```

clean generated files:

```
paver clean
```

generate documentation under *docs/_build/html*:

```
paver cog pdf html
```

upload documentation to [github](#):

```
paver ghpages
```

run unit tests:

```
paver nose
#or
nosetests --verbose
```

check python code:

```
paver pyflakes
paver pychecker
```

generate python distribution:

```
paver sdist
```

upload python distribution to [PyPI](#):

```
paver upload
```

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

INDEX

C

`call()` (easyprocess.Proc method), 8
`check()` (easyprocess.Proc method), 8
`check_installed()` (easyprocess.Proc method), 8

E

`EasyProcess` (in module easyprocess), 8

I

`is_alive()` (easyprocess.Proc method), 8

P

`pid` (easyprocess.Proc attribute), 8
`Proc` (class in easyprocess), 8

R

`return_code` (easyprocess.Proc attribute), 8

S

`sendstop()` (easyprocess.Proc method), 8
`sleep()` (easyprocess.Proc method), 9
`start()` (easyprocess.Proc method), 9
`stop()` (easyprocess.Proc method), 9

W

`wait()` (easyprocess.Proc method), 9
`wrap()` (easyprocess.Proc method), 9