Cyborg_THM

Enumuration

- # Got a admin directory consisting a website
- # we get three users ,josh,alex
- #we have a /etc dir having a passwd dile apparently having a hash and somename
- # in website we get to download a archive.tar
- # we untar it and it has many differnt conf files but its all gibberish
- # we read the readme file which showed that this was all a backup made by using borgbackup utility
- # we research and see that we can install these backups using borg binary
- # the file we got in /etc dir had a name music Archive which is apparently a directory as stated in website blog
- # we decode the hash and get a password which is squidward\
- # Now we can can install the backup by the command

./borgbinary extract home/field/dev/final archive::music archive

the above given path is the path when we untar the tar archive a directory system wasinstalled. This directoy path is a repo in that borh backup system

we use the password to extract and get alex file system and get his ssh crreds

Now login as alex

#

Nmap

```
PORT STATE SERVICE VERSION
```

22/tcp open ssh OpenSSH 7.2p2 Ubuntu 4ubuntu2.10 (Ubuntu Linux; protocol 2.0)

ssh-hostkey:

2048 db:b2:70:f3:07:ac:32:00:3f:81:b8:d0:3a:89:f3:65 (RSA)

256 68:e6:85:2f:69:65:5b:e7:c6:31:2c:8e:41:67:d7:ba (ECDSA)

256 56:2c:79:92:ca:23:c3:91:49:35:fa:dd:69:7c:ca:ab (ED25519)

80/tcp open http Apache httpd 2.4.18 ((Ubuntu))

|_http-server-header: Apache/2.4.18 (Ubuntu)

| http-title: Apache2 Ubuntu Default Page: It works

Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port

Aggressive OS guesses: Linux 3.1 (95%), Linux 3.2 (95%), AXIS 210A or 211 Network Camera (Linux 2.6.17) (94%), ASUS RT-N56U WAP (Linux 3.4) (93%), Linux 3.16 (93%), Linux 2.6.32 (92%), Linux 2.6.39 - 3.2 (92%), Linux 3.1 - 3.2 (92%), Linux 3.2 - 4.9 (92%), Linux 3.7 - 3.10 (92%)

No exact OS matches for host (test conditions non-ideal).

Network Distance: 4 hops

Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE (using port 80/tcp)

HOP RTT ADDRESS

1 193.64 ms 10.4.0.1

2 ... 3

4 460.29 ms 10.10.104.110

OS and Service detection performed. Please report any incorrect results at $\underline{\text{https://nmap.org/submit/}}$. Nmap done: 1 IP address (1 host up) scanned in 36.73 seconds

22:ssh

http:80

Exploitation

Post Exploitation

- # We see that we can run a backup.sh file as sudo
- # its owned by us but we dont have write access so we chmod it
- # Now e copied bash binary to /tmp and set it as suid bit
- # now we run the backup.sh with sudo and then /tmp/root with -p for privileged mode and get a root shell

LOot

credentials

We get a passwd file withh username an hash music_archive:\$apr1\$BpZ.Q.1m\$F0qqPwHSOG50URuOVQTTn. we decode it and get squidward password

ssh creds

alex:S3cretP@s3

FLAGS

User flag

 $flag{1_hop3_y0u_ke3p_th3_arch1v3s_saf3}$

Root Flag

flag{Than5s_f0r_play1ng_H0p£_y0u_enJ053d}