

# HSDL-4260

High-Power T-1¾ (5mm) AlGaAs Infrared (875nm) Lamp



## Datasheet

### Description


The HSDL-4260 High Power Infrared emitter was designed for applications that require high power, low forward voltage and high speed. It utilizes Aluminum Gallium Arsenide (AlGaAs) LED technology and is optimized for speed and efficiency at emission wavelengths of 875nm. The material used produces high radiant efficiency over a wide range of currents. The emitter is packaged in clear T-1¾ (5mm) package.

### Features

- High Power AlGaAs LED Technology
- 875nm Wavelength
- T-1¾ Package
- Low Cost
- Low Forward Voltage: 1.4V at 20mA
- High Speed: 15ns Rise Times

### Applications

- Industrial Infrared Equipments and applications
- Portable Infrared Instruments
- Consumer Electronics (Optical mouse, Infrared Remote Controllers etc)
- High Speed Infrared Communications (IR LANs, IR Modems, IR Dongles etc)



Part Number	Lead Form	Shipping Option
HSDL-4260	Straight	Bulk

**Absolute Maximum Ratings at 25°C**

Parameter	Symbol	Minimum	Maximum	Unit	Reference
Peak Forward Current	$I_{\text{FPK}}$	-	500	mA	Figure 3 Duty cycle = 20% Pulse Width = 100us
Forward Current	$I_{\text{FDC}}$	-	100	mA	[1]
Power Dissipation	$P_{\text{DISS}}$	-	230	mW	
Reverse Voltage	$V_{\text{R}}$	4	-	V	$I_{\text{R}}=100\mu\text{A}$
Storage Temperature	$T_{\text{S}}$	-40	100	°C	
LED Junction Temperature	$T_{\text{J}}$		110	°C	
Lead Soldering Temperature			260 for 5 sec	°C	

Notes: Derate as shown in Figure 6.

**Recommended Operating Conditions**

Parameter	Symbol	Min	Max	Unit	Reference
Operating Temperature	$T_{\text{O}}$	-40	85	°C	

**Electrical Characteristics at 25°C**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition	Reference
Forward Voltage	$V_{\text{F}}$	-	1.4 1.7	1.9 2.3	V	$I_{\text{FDC}}=20\text{mA}$ $I_{\text{FDC}}=100\text{mA}$	Figure 2
Forward Voltage Temperature Coefficient	$\Delta V/\Delta T$	-	-1.3	-	mV/°C	$I_{\text{FDC}}=100\text{mA}$	Figure 4
Series Resistance	$R_{\text{S}}$	-	4	-	Ohms	$I_{\text{FDC}}=100\text{mA}$	
Diode Capacitance	$C_{\text{O}}$	-	70	-	pF	$V_{\text{bias}}=0\text{V}$ , $f=1\text{MHz}$	
Thermal Resistance, Junction to Ambient	$R\theta_{\text{ja}}$	-	300	-	°C/W		

**Optical Characteristics at 25°C**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition	Reference
Radiant On-Axis Intensity	$I_{\text{E}}$	150	200	-	mW/Sr	$I_{\text{FDC}}=100\text{mA}$	Figure 5
Radiant On-Axis Intensity Temperature Coefficient	$\Delta I_{\text{E}}/\Delta T$	-	-0.36	-	%/°C	$I_{\text{FDC}}=100\text{mA}$	
Viewing Angle	$2\theta_{1/2}$	-	15	-	°		Figure 7
Peak Wavelength	$\lambda_{\text{pk}}$	-	875	-	nm		Figure 1
Peak wavelength Temperature Coefficient	$\Delta \lambda/\Delta T$	-	0.2	-	nm/°C	$I_{\text{FDC}}=100\text{mA}$	
Spectral Width	$\Delta \lambda$		45	-	nm	$I_{\text{FDC}}=20\text{mA}$	Figure 1
Optical Rise and Fall Time	$t_{\text{r}}/t_{\text{f}}$		15	-	ns	$I_{\text{FDC}}=500\text{mA}$ Duty Ratio = 20% Pulse Width=100ns	




Figure 1. Relative Radiant Intensity vs. Wavelength




Figure 2. DC Forward Current vs. Forward Voltage




Figure 3. Peak Forward Current vs. Forward Voltage




Figure 4. Forward Voltage vs. Ambient Temperature




Figure 5. Relative Radiant Intensity vs. DC Forward Current






Figure 6. DC Forward Current vs. Ambient Temperature Derated Based on  $T_{JMAX}=110^{\circ}\text{C}$



**Figure 7. Radiant Intensity vs. Angular Displacement for HSDL-4260**

For company and product information, please go to our web site: [WWW.liteon.com](http://WWW.liteon.com) or <http://optodatabook.liteon.com/databook/databook.aspx>

Data subject to change. Copyright © 2007 Lite-On Technology Corporation. All rights reserved.

**LITEON**®