

Configuration Guide

Configuration is resolved with the following precedence (highest first):

1. **Environment variables** — `OSINT_<KEY>` (uppercased).
2. `config.json` in the project root (or the path in `OSINT_CONFIG`).
3. **Built-in defaults** (`osint_chain/config.py`).

Options

Key	Env var	Default	Description
data_dir	OSINT_DATA_DIR	data	Base directory for all runtime data
evidence_dir	OSINT_EVIDENCE_DIR	data/evidence	Write-once evidence object store
chain_file	OSINT_CHAIN_FILE	data/chain/ chain.jsonl	The append-only blockchain (JSON Lines)
users_file	OSINT_USERS_FILE	data/users.json	User registry
keys_dir	OSINT_KEYS_DIR	data/keys	Per-user Ed25519 private keys (PEM, 0600)
ntp_servers	OSINT_NTP_SERVERS	pool.ntp.org,time.google.com,time.cloudflare.com	Comma-separated NTP servers (tried in order)
ntp_timeout	OSINT_NTP_TIMEOUT	3	NTP query timeout (seconds)
ntp_enabled	OSINT_NTP_ENABLED	true	Disable to always use local clock (offline use)
timestamp_authority	OS- INT_TIMESTAMP_AUTHORITY	pool.ntp.org	Informational default authority label
max_upload_mb	OSINT_MAX_UPLOAD_MB	200	Max upload size per request
jwt_secret	OSINT_JWT_SECRET	(placeholder)	Change in production! HS256 signing key
jwt_expiry_hours	OS- INT_JWT_EXPIRY_HOURS	12	Token lifetime
host	OSINT_HOST	0.0.0.0	API bind address
port	OSINT_PORT	3000	API port

⚠ Ports 1000 and 2200 are reserved on the Abacus VM. Use 3000 (default).

Examples

Custom evidence directory and port via env vars:

```
export OSINT_EVIDENCE_DIR=/secure/evidence
export OSINT_PORT=8080
export OSINT_JWT_SECRET="$(openssl rand -hex 32)"
osint-server
```

Offline / air-gapped (no NTP):

```
export OSINT_NTP_ENABLED=false
osint-server
```

Blocks will record "authority": "local-system-clock" so the reduced trust level is explicit in the audit record.

A separate config file:

```
export OSINT_CONFIG=/etc/osint/config.json
osint-server
```

Production checklist

- [] Set a strong `OSINT_JWT_SECRET` (≥ 32 bytes).
- [] Place `data/` on an encrypted, access-controlled volume.
- [] Restrict `data/keys/` to the service account only.
- [] Put the Flask app behind a production WSGI server (gunicorn/uWSGI) and a TLS-terminating reverse proxy (nginx/Caddy).
- [] Back up / replicate `chain.jsonl` to an append-only or off-host location.
- [] Keep NTP enabled and reachable for trustworthy timestamps.