

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Timing discrepancy infoleak

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
462	Cross-Domain Search Timing
541	Application Fingerprinting
580	System Footprinting

## CWE-209: Generation of Error Message Containing Sensitive Information

**Weakness ID :** 209

**Structure :** Simple

**Abstraction :** Base

### Description

The product generates an error message that includes sensitive information about its environment, users, or associated data.

### Extended Description

The sensitive information may be valuable information on its own (such as a password), or it may be useful for launching other, more serious attacks. The error message may be created in different ways:








- self-generated: the source code explicitly constructs the error message and delivers it
- externally-generated: the external environment, such as a language interpreter, handles the error and constructs its own message, whose contents are not under direct control by the programmer


An attacker may use the contents of error messages to help launch another, more focused attack. For example, an attempt to exploit a path traversal weakness (CWE-22) might yield the full pathname of the installed application. In turn, this could be used to select the proper number of "." sequences to navigate to the targeted file. An attack using SQL injection (CWE-89) might not initially succeed, but an error message could reveal the malformed query, which would expose query logic and possibly even passwords or other sensitive information used within the query.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1576
ChildOf		200	Exposure of Sensitive Information to an Unauthorized Actor	504
ParentOf		210	Self-generated Error Message Containing Sensitive Information	539
ParentOf		211	Externally-Generated Error Message Containing Sensitive Information	541
ParentOf		550	Server-generated Error Message Containing Sensitive Information	1263
PeerOf		1295	Debug Messages Revealing Unnecessary Information	2152
CanFollow		600	Uncaught Exception in Servlet	1343

Nature	Type	ID	Name	Page
CanFollow		756	Missing Custom Error Page	1579



*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		200	Exposure of Sensitive Information to an Unauthorized Actor	504

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	2430

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	2312
MemberOf		389	Error Conditions, Return Values, Status Codes	2322

### Weakness Ordinalities

**Primary :**

**Resultant :**

### Applicable Platforms

**Language :** PHP (*Prevalence = Often*)

**Language :** Java (*Prevalence = Often*)

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data  <i>Often this will either reveal sensitive information which may be used for a later attack or private information stored in the server.</i>	

### Detection Methods

#### Manual Analysis

This weakness generally requires domain-specific interpretation using manual analysis. However, the number of potential error conditions may be too large to cover completely within limited time constraints.

*Effectiveness = High*

#### Automated Analysis

Automated methods may be able to detect certain idioms automatically, such as exposed stack traces or pathnames, but violation of business rules or privacy requirements is not typically feasible.

*Effectiveness = Moderate*

#### Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not

become unstable, crash, or generate incorrect results. Error conditions may be triggered with a stress-test by calling the software simultaneously from a large number of threads or processes, and look for evidence of any unexpected behavior.

*Effectiveness = Moderate*

### Manual Dynamic Analysis

Identify error conditions that are not likely to occur during normal usage and trigger them. For example, run the program under low memory conditions, run with insufficient privileges or permissions, interrupt a transaction before it is completed, or disable connectivity to basic network services such as DNS. Monitor the software for any unexpected behavior. If you trigger an unhandled exception or similar error that was discovered and handled by the application's environment, it may still indicate unexpected conditions that were not handled by the application itself.

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

## Potential Mitigations

### Phase: Implementation

Ensure that error messages only contain minimal details that are useful to the intended audience and no one else. The messages need to strike the balance between being too cryptic (which can confuse users) or being too detailed (which may reveal more than intended). The messages should not reveal the methods that were used to determine the error. Attackers can use detailed information to refine or optimize their original attack, thereby increasing their chances of success. If errors must be captured in some detail, record them in log messages, but consider what could occur if the log messages can be viewed by attackers. Highly sensitive information such as passwords should never be saved to log files. Avoid inconsistent messaging that might accidentally tip off an attacker about internal state, such as whether a user account exists or not.

### Phase: Implementation

Handle exceptions internally and do not display errors containing potentially sensitive information to a user.

### Phase: Implementation

*Strategy = Attack Surface Reduction*

Use naming conventions and strong types to make it easier to spot when sensitive data is being used. When creating structures, objects, or other complex entities, separate the sensitive and non-sensitive data as much as possible.

*Effectiveness = Defense in Depth*

*This makes it easier to spot places in the code where data is being used that is unencrypted.*

### Phase: Implementation

### Phase: Build and Compilation

*Strategy = Compilation or Build Hardening*

Debugging information should not make its way into a production release.

### Phase: Implementation

### Phase: Build and Compilation

*Strategy = Environment Hardening*

Debugging information should not make its way into a production release.

### Phase: System Configuration

Where available, configure the environment to use less verbose error messages. For example, in PHP, disable the `display_errors` setting during configuration, or at runtime using the `error_reporting()` function.

### Phase: System Configuration

Create default error pages or messages that do not leak any information.

## Demonstrative Examples

### Example 1:

In the following example, sensitive information might be printed depending on the exception that occurs.

*Example Language: Java*

*(Bad)*

```
try {
    /.../
}
catch (Exception e) {
    System.out.println(e);
}
```

If an exception related to SQL is handled by the catch, then the output might contain sensitive information such as SQL query structure or private information. If this output is redirected to a web user, this may represent a security problem.

### Example 2:

This code tries to open a database connection, and prints any exceptions that occur.

*Example Language: PHP*

*(Bad)*

```
try {
    openDbConnection();
}
//print exception message that includes exception message and configuration file location
catch (Exception $e) {
    echo 'Caught exception: ', $e->getMessage(), "\n";
    echo 'Check credentials in config file at: ', $Mysql_config_location, "\n";
}
```

If an exception occurs, the printed message exposes the location of the configuration file the script is using. An attacker can use this information to target the configuration file (perhaps exploiting a Path Traversal weakness). If the file can be read, the attacker could gain credentials for accessing the database. The attacker may also be able to replace the file with a malicious one, causing the application to use an arbitrary database.

### Example 3:

The following code generates an error message that leaks the full pathname of the configuration file.

*Example Language: Perl*

*(Bad)*

```
$ConfigDir = "/home/myprog/config";
$username = GetUserInput("username");
# avoid CWE-22, CWE-78, others.
ExitError("Bad hacker!") if ($username !~ /\w+$/);
$file = "$ConfigDir/$username.txt";
```

```

if (! (-e $file)) {
    ExitError("Error: $file does not exist");
}
...

```

If this code is running on a server, such as a web application, then the person making the request should not know what the full pathname of the configuration directory is. By submitting a username that does not produce a \$file that exists, an attacker could get this pathname. It could then be used to exploit path traversal or symbolic link following problems that may exist elsewhere in the application.

#### Example 4:

In the example below, the method `getUserBankAccount` retrieves a bank account object from a database using the supplied username and account number to query the database. If an `SQLException` is raised when querying the database, an error message is created and output to a log file.

Example Language: Java

(Bad)

```

public BankAccount getUserBankAccount(String username, String accountNumber) {
    BankAccount userAccount = null;
    String query = null;
    try {
        if (isAuthorizedUser(username)) {
            query = "SELECT * FROM accounts WHERE owner = "
                + username + " AND accountID = " + accountNumber;
            DatabaseManager dbManager = new DatabaseManager();
            Connection conn = dbManager.getConnection();
            Statement stmt = conn.createStatement();
            ResultSet queryResult = stmt.executeQuery(query);
            userAccount = (BankAccount)queryResult.getObject(accountNumber);
        }
    } catch (SQLException ex) {
        String logMessage = "Unable to retrieve account information from database,\nquery: " + query;
        Logger.getLogger(BankManager.class.getName()).log(Level.SEVERE, logMessage, ex);
    }
    return userAccount;
}

```

The error message that is created includes information about the database query that may contain sensitive information about the database or query logic. In this case, the error message will expose the table name and column names used in the database. This data could be used to simplify other attacks, such as SQL injection (CWE-89) to directly access the database.



#### Observed Examples

Reference	Description
<b>CVE-2008-2049</b>	POP3 server reveals a password in an error message after multiple APOP commands are sent. Might be resultant from another weakness. <a href="https://www.cve.org/CVERecord?id=CVE-2008-2049">https://www.cve.org/CVERecord?id=CVE-2008-2049</a>
<b>CVE-2007-5172</b>	Program reveals password in error message if attacker can trigger certain database errors. <a href="https://www.cve.org/CVERecord?id=CVE-2007-5172">https://www.cve.org/CVERecord?id=CVE-2007-5172</a>
<b>CVE-2008-4638</b>	Composite: application running with high privileges (CWE-250) allows user to specify a restricted file to process, which generates a parsing error that leaks the contents of the file (CWE-209). <a href="https://www.cve.org/CVERecord?id=CVE-2008-4638">https://www.cve.org/CVERecord?id=CVE-2008-4638</a>
<b>CVE-2008-1579</b>	Existence of user names can be determined by requesting a nonexistent blog and reading the error message. <a href="https://www.cve.org/CVERecord?id=CVE-2008-1579">https://www.cve.org/CVERecord?id=CVE-2008-1579</a>

Reference	Description
<b>CVE-2007-1409</b>	Direct request to library file in web application triggers pathname leak in error message. <a href="https://www.cve.org/CVERecord?id=CVE-2007-1409">https://www.cve.org/CVERecord?id=CVE-2007-1409</a>
<b>CVE-2008-3060</b>	Malformed input to login page causes leak of full path when IMAP call fails. <a href="https://www.cve.org/CVERecord?id=CVE-2008-3060">https://www.cve.org/CVERecord?id=CVE-2008-3060</a>
<b>CVE-2005-0603</b>	Malformed regexp syntax leads to information exposure in error message. <a href="https://www.cve.org/CVERecord?id=CVE-2005-0603">https://www.cve.org/CVERecord?id=CVE-2005-0603</a>
<b>CVE-2017-9615</b>	verbose logging stores admin credentials in a world-readable log file <a href="https://www.cve.org/CVERecord?id=CVE-2017-9615">https://www.cve.org/CVERecord?id=CVE-2017-9615</a>
<b>CVE-2018-1999036</b>	SSH password for private key stored in build log <a href="https://www.cve.org/CVERecord?id=CVE-2018-1999036">https://www.cve.org/CVERecord?id=CVE-2018-1999036</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		717	OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling	629	2332
MemberOf		728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	2337
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	2339
MemberOf		751	2009 Top 25 - Insecure Interaction Between Components	750	2352
MemberOf		801	2010 Top 25 - Insecure Interaction Between Components	800	2354
MemberOf		815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	2358
MemberOf		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	2365
MemberOf		867	2011 Top 25 - Weaknesses On the Cusp	900	2372
MemberOf		880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	2379
MemberOf		884	CWE Cross-section	884	2567
MemberOf		933	OWASP Top Ten 2013 Category A5 - Security Misconfiguration	928	2391
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1032	OWASP Top Ten 2017 Category A6 - Security Misconfiguration	1026	2438
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1417	Comprehensive Categorization: Sensitive Information Exposure	1400	2548

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Accidental leaking of sensitive information through error messages
OWASP Top Ten 2007	A6	CWE More Specific	Information Leakage and Improper Error Handling
OWASP Top Ten 2004	A7	CWE More Specific	Improper Error Handling
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	ERR01-J		Do not allow exceptions to expose sensitive information
Software Fault Patterns	SFP23		Exposed Data

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
7	Blind SQL Injection
54	Query System for Information
215	Fuzzing for application mapping
463	Padding Oracle Crypto Attack

### References

- [REF-174]Web Application Security Consortium. "Information Leakage". < <http://projects.webappsec.org/w/page/13246936/Information%20Leakage> >. 2023-04-07.
- [REF-175]Brian Chess and Jacob West. "Secure Programming with Static Analysis". 2007. Addison-Wesley.
- [REF-176]Michael Howard and David LeBlanc. "Writing Secure Code". 1st Edition. 2001 November 3. Microsoft Press.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-179]Johannes Ullrich. "Top 25 Series - Rank 16 - Information Exposure Through an Error Message". 2010 March 7. SANS Software Security Institute. < <http://software-security.sans.org/blog/2010/03/17/top-25-series-rank-16-information-exposure-through-an-error-message> >.
- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.
- [REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-210: Self-generated Error Message Containing Sensitive Information

**Weakness ID :** 210

**Structure :** Simple

**Abstraction :** Base


### Description

The product identifies an error condition and creates its own diagnostic or error messages that contain sensitive information.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		209	Generation of Error Message Containing Sensitive Information	533



*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1016	Limit Exposure	2431

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

### Potential Mitigations

**Phase: Implementation**

**Phase: Build and Compilation**

*Strategy = Compilation or Build Hardening*

Debugging information should not make its way into a production release.

**Phase: Implementation**

**Phase: Build and Compilation**

*Strategy = Environment Hardening*

Debugging information should not make its way into a production release.

### Demonstrative Examples

#### Example 1:

The following code uses custom configuration files for each user in the application. It checks to see if the file exists on the system before attempting to open and use the file. If the configuration file does not exist, then an error is generated, and the application exits.

*Example Language: Perl*

*(Bad)*

```
$uname = GetUserInput("username");
# avoid CWE-22, CWE-78, others.
if ($uname !~ /\w+$/)
{
    ExitError("Bad hacker!");
}
$filename = "/home/myprog/config/" . $uname . ".txt";
if (!(-e $filename))
{
    ExitError("Error: $filename does not exist");
}
```

If this code is running on a server, such as a web application, then the person making the request should not know what the full pathname of the configuration directory is. By submitting a username that is not associated with a configuration file, an attacker could get this pathname from the error message. It could then be used to exploit path traversal, symbolic link following, or other problems that may exist elsewhere in the application.




### Observed Examples

Reference	Description
<b>CVE-2005-1745</b>	Infoleak of sensitive information in error message (physical access required). <a href="https://www.cve.org/CVERecord?id=CVE-2005-1745">https://www.cve.org/CVERecord?id=CVE-2005-1745</a>

### MemberOf Relationships



This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1417	Comprehensive Categorization: Sensitive Information Exposure	1400	2548

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Product-Generated Error Message Infoleak
Software Fault Patterns	SFP23		Exposed Data

### References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

## CWE-211: Externally-Generated Error Message Containing Sensitive Information

**Weakness ID :** 211

**Structure :** Simple

**Abstraction :** Base





### Description

The product performs an operation that triggers an external diagnostic or error message that is not directly generated or controlled by the product, such as an error generated by the programming language interpreter that a software application uses. The error can contain sensitive system information.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		209	Generation of Error Message Containing Sensitive Information	533
ParentOf		535	Exposure of Information Through Shell Error Message	1244
ParentOf		536	Servlet Runtime Error Message Containing Sensitive Information	1245
ParentOf		537	Java Runtime Error Message Containing Sensitive Information	1246

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1016	Limit Exposure	2431

### Weakness Ordinalities

**Resultant :**

**Applicable Platforms**

- Language :** PHP (*Prevalence = Often*)
- Language :** Not Language-Specific (*Prevalence = Undetermined*)

**Common Consequences**

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

**Potential Mitigations**

- Phase: System Configuration**  
Configure the application's environment in a way that prevents errors from being generated. For example, in PHP, disable display\_errors.
- Phase: Implementation**
- Phase: Build and Compilation**  
*Strategy = Compilation or Build Hardening*  
Debugging information should not make its way into a production release.
- Phase: Implementation**
- Phase: Build and Compilation**  
*Strategy = Environment Hardening*  
Debugging information should not make its way into a production release.
- Phase: Implementation**  
Handle exceptions internally and do not display errors containing potentially sensitive information to a user. Create default error pages if necessary.
- Phase: Implementation**  
The best way to prevent this weakness during implementation is to avoid any bugs that could trigger the external error message. This typically happens when the program encounters fatal errors, such as a divide-by-zero. You will not always be able to control the use of error pages, and you might not be using a language that handles exceptions.

**Demonstrative Examples**

**Example 1:**  
The following servlet code does not catch runtime exceptions, meaning that if such an exception were to occur, the container may display potentially dangerous information (such as a full stack trace).

*Example Language: Java* (Bad)

```
public void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    String username = request.getParameter("username");
    // May cause unchecked NullPointerException.
    if (username.length() < 10) {
        ...
    }
}
```

**Example 2:**  
In the following Java example the class InputFileRead enables an input file to be read using a FileReader object. In the constructor of this class a default input file path is set to some directory

on the local file system and the method `setInputFile` must be called to set the name of the input file to be read in the default directory. The method `readInputFile` will create the `FileReader` object and will read the contents of the file. If the method `setInputFile` is not called prior to calling the method `readInputFile` then the `File` object will remain null when initializing the `FileReader` object. A Java `RuntimeException` will be raised, and an error message will be output to the user.

Example Language: Java

(Bad)

```
public class InputFileRead {
    private File readFile = null;
    private FileReader reader = null;
    private String inputFilePath = null;
    private final String DEFAULT_FILE_PATH = "c:\\somedirectory\\";
    public InputFileRead() {
        inputFilePath = DEFAULT_FILE_PATH;
    }
    public void setInputFile(String inputFile) {
        /* Assume appropriate validation / encoding is used and privileges / permissions are preserved */
    }
    public void readInputFile() {
        try {
            reader = new FileReader(readFile);
            ...
        } catch (RuntimeException rex) {
            System.err.println("Error: Cannot open input file in the directory " + inputFilePath);
            System.err.println("Input file has not been set, call setInputFile method before calling readInputFile");
        } catch (FileNotFoundException ex) {...}
    }
}
```

However, the error message output to the user contains information regarding the default directory on the local file system. This information can be exploited and may lead to unauthorized access or use of the system. Any Java `RuntimeExceptions` that are handled should not expose sensitive information to the user.

### Observed Examples



Reference	Description
<b>CVE-2004-1581</b>	chain: product does not protect against direct request of an include file, leading to resultant path disclosure when the include file does not successfully execute. <a href="https://www.cve.org/CVERecord?id=CVE-2004-1581">https://www.cve.org/CVERecord?id=CVE-2004-1581</a>
<b>CVE-2004-1579</b>	Single "" inserted into SQL query leads to invalid SQL query execution, triggering full path disclosure. Possibly resultant from more general SQL injection issue. <a href="https://www.cve.org/CVERecord?id=CVE-2004-1579">https://www.cve.org/CVERecord?id=CVE-2004-1579</a>
<b>CVE-2005-0459</b>	chain: product does not protect against direct request of a library file, leading to resultant path disclosure when the file does not successfully execute. <a href="https://www.cve.org/CVERecord?id=CVE-2005-0459">https://www.cve.org/CVERecord?id=CVE-2005-0459</a>
<b>CVE-2005-0443</b>	invalid parameter triggers a failure to find an include file, leading to infoleak in error message. <a href="https://www.cve.org/CVERecord?id=CVE-2005-0443">https://www.cve.org/CVERecord?id=CVE-2005-0443</a>
<b>CVE-2005-0433</b>	Various invalid requests lead to information leak in verbose error messages describing the failure to instantiate a class, open a configuration file, or execute an undefined function. <a href="https://www.cve.org/CVERecord?id=CVE-2005-0433">https://www.cve.org/CVERecord?id=CVE-2005-0433</a>
<b>CVE-2004-1101</b>	Improper handling of filename request with trailing "/" causes multiple consequences, including information leak in Visual Basic error message. <a href="https://www.cve.org/CVERecord?id=CVE-2004-1101">https://www.cve.org/CVERecord?id=CVE-2004-1101</a>

### Functional Areas

- Error Handling

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1417	Comprehensive Categorization: Sensitive Information Exposure	1400	2548

### Notes

#### Relationship

This is inherently a resultant vulnerability from a weakness within the product or an interaction error.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Product-External Error Message Infoleak

## CWE-212: Improper Removal of Sensitive Information Before Storage or Transfer

**Weakness ID :** 212

**Structure :** Simple

**Abstraction :** Base

### Description

The product stores, transfers, or shares a resource that contains sensitive information, but it does not properly remove that information before the product makes the resource available to unauthorized actors.

### Extended Description

Resources that may contain sensitive data include documents, packets, messages, databases, etc. While this data may be useful to an individual user or small set of users who share the resource, it may need to be removed before the resource can be shared outside of the trusted group. The process of removal is sometimes called cleansing or scrubbing.




For example, a product for editing documents might not remove sensitive data such as reviewer comments or the local pathname where the document is stored. Or, a proxy might not remove an internal IP address from headers before making an outgoing request to an Internet site.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1471

Nature	Type	ID	Name	Page
ParentOf		226	Sensitive Information in Resource Not Removed Before Reuse	562
ParentOf		1258	Exposure of Sensitive System Information Due to Uncleared Debug Information	2071
CanPrecede		201	Insertion of Sensitive Information Into Sent Data	514



*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1471

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	2430

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	2312
MemberOf		452	Initialization and Cleanup Errors	2327

### Weakness Ordinalities

**Primary :**

**Resultant :**

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories Read Application Data  <i>Sensitive data may be exposed to an unauthorized actor in another control sphere. This may have a wide range of secondary consequences which will depend on what data is exposed. One possibility is the exposure of system data allowing an attacker to craft a specific, more effective attack.</i>	

### Potential Mitigations

#### Phase: Requirements

Clearly specify which information should be regarded as private or sensitive, and require that the product offers functionality that allows the user to cleanse the sensitive information from the resource before it is published or exported to other parties.

#### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

**Phase: Implementation**

*Strategy = Attack Surface Reduction*

Use naming conventions and strong types to make it easier to spot when sensitive data is being used. When creating structures, objects, or other complex entities, separate the sensitive and non-sensitive data as much as possible.

*Effectiveness = Defense in Depth*

*This makes it easier to spot places in the code where data is being used that is unencrypted.*

**Phase: Implementation**

Avoid errors related to improper resource shutdown or release (CWE-404), which may leave the sensitive data within the resource if it is in an incomplete state.

**Demonstrative Examples****Example 1:**

This code either generates a public HTML user information page or a JSON response containing the same user information.

*Example Language: PHP*

*(Bad)*

```
// API flag, output JSON if set
$json = $_GET['json']
$username = $_GET['user']
if(!$json)
{
    $record = getUserRecord($username);
    foreach($record as $fieldName => $fieldValue)
    {
        if($fieldName == "email_address") {
            // skip displaying user emails
            continue;
        }
        else{
            writeToHtmlPage($fieldName,$fieldValue);
        }
    }
}
else
{
    $record = getUserRecord($username);
    echo json_encode($record);
}
```

The programmer is careful to not display the user's e-mail address when displaying the public HTML page. However, the e-mail address is not removed from the JSON response, exposing the user's e-mail address.

**Observed Examples**

Reference	Description
<b>CVE-2019-3733</b>	Cryptography library does not clear heap memory before release <a href="https://www.cve.org/CVERecord?id=CVE-2019-3733">https://www.cve.org/CVERecord?id=CVE-2019-3733</a>
<b>CVE-2005-0406</b>	Some image editors modify a JPEG image, but the original EXIF thumbnail image is left intact within the JPEG. (Also an interaction error). <a href="https://www.cve.org/CVERecord?id=CVE-2005-0406">https://www.cve.org/CVERecord?id=CVE-2005-0406</a>
<b>CVE-2002-0704</b>	NAT feature in firewall leaks internal IP addresses in ICMP error messages. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0704">https://www.cve.org/CVERecord?id=CVE-2002-0704</a>

**MemberOf Relationships**

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	2355
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	2372
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf	C	1364	ICS Communications: Zone Boundary Failures	1358	2501
MemberOf	C	1416	Comprehensive Categorization: Resource Lifecycle Management	1400	2545

## Notes

### Relationship

This entry is intended to be different from resultant information leaks, including those that occur from improper buffer initialization and reuse, improper encryption, interaction errors, and multiple interpretation errors. This entry could be regarded as a privacy leak, depending on the type of information that is leaked.

### Relationship

There is a close association between CWE-226 and CWE-212. The difference is partially that of perspective. CWE-226 is geared towards the final stage of the resource lifecycle, in which the resource is deleted, eliminated, expired, or otherwise released for reuse. Technically, this involves a transfer to a different control sphere, in which the original contents of the resource are no longer relevant. CWE-212, however, is intended for sensitive data in resources that are intentionally shared with others, so they are still active. This distinction is useful from the perspective of the CWE research view (CWE-1000).

### Terminology

The terms "cleansing" and "scrubbing" have multiple uses within computing. In information security, these are used for the removal of sensitive data, but they are also used for the modification of incoming/outgoing data so that it conforms to specifications.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Cross-Boundary Cleansing Infoleak

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
168	Windows ::DATA Alternate Data Stream

## CWE-213: Exposure of Sensitive Information Due to Incompatible Policies

**Weakness ID :** 213

**Structure :** Simple

**Abstraction :** Base

### Description

The product's intended functionality exposes information to certain actors in accordance with the developer's security policy, but this information is regarded as sensitive according to the intended security policies of other stakeholders such as the product's administrator, users, or others whose information is being processed.

### Extended Description



When handling information, the developer must consider whether the information is regarded as sensitive by different stakeholders, such as users or administrators. Each stakeholder effectively has its own intended security policy that the product is expected to uphold. When a developer does not treat that information as sensitive, this can introduce a vulnerability that violates the expectations of the product's users.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		200	Exposure of Sensitive Information to an Unauthorized Actor	504

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	2312

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

## Demonstrative Examples

### Example 1:

This code displays some information on a web page.

*Example Language: JSP*

*(Bad)*

```
Social Security Number: <%= ssn %></br>Credit Card Number: <%= ccn %>
```

The code displays a user's credit card and social security numbers, even though they aren't absolutely necessary.

## Observed Examples

Reference	Description
<b>CVE-2002-1725</b>	Script calls phpinfo() <a href="https://www.cve.org/CVERecord?id=CVE-2002-1725">https://www.cve.org/CVERecord?id=CVE-2002-1725</a>
<b>CVE-2004-0033</b>	Script calls phpinfo() <a href="https://www.cve.org/CVERecord?id=CVE-2004-0033">https://www.cve.org/CVERecord?id=CVE-2004-0033</a>
<b>CVE-2003-1181</b>	Script calls phpinfo() <a href="https://www.cve.org/CVERecord?id=CVE-2003-1181">https://www.cve.org/CVERecord?id=CVE-2003-1181</a>
<b>CVE-2004-1422</b>	Script calls phpinfo() <a href="https://www.cve.org/CVERecord?id=CVE-2004-1422">https://www.cve.org/CVERecord?id=CVE-2004-1422</a>
<b>CVE-2004-1590</b>	Script calls phpinfo() <a href="https://www.cve.org/CVERecord?id=CVE-2004-1590">https://www.cve.org/CVERecord?id=CVE-2004-1590</a>
<b>CVE-2003-1038</b>	Product lists DLLs and full pathnames. <a href="https://www.cve.org/CVERecord?id=CVE-2003-1038">https://www.cve.org/CVERecord?id=CVE-2003-1038</a>
<b>CVE-2005-1205</b>	Telnet protocol allows servers to obtain sensitive environment information from clients. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1205">https://www.cve.org/CVERecord?id=CVE-2005-1205</a>

Reference	Description
<b>CVE-2005-0488</b>	Telnet protocol allows servers to obtain sensitive environment information from clients. <a href="https://www.cve.org/CVERecord?id=CVE-2005-0488">https://www.cve.org/CVERecord?id=CVE-2005-0488</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1340	CISQ Data Protection Measures	1340	2590
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1417	Comprehensive Categorization: Sensitive Information Exposure	1400	2548

### Notes

#### Maintenance

This entry is being considered for deprecation. It overlaps many other entries related to information exposures. It might not be essential to preserve this entry, since other key stakeholder policies are covered elsewhere, e.g. personal privacy leaks (CWE-359) and system-level exposures that are important to system administrators (CWE-497).

#### Theoretical

In vulnerability theory terms, this covers cases in which the developer's Intended Policy allows the information to be made available, but the information might be in violation of a Universal Policy in which the product's administrator should have control over which information is considered sensitive and therefore should not be exposed.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Intended information leak

## CWE-214: Invocation of Process Using Visible Sensitive Information

**Weakness ID :** 214

**Structure :** Simple

**Abstraction :** Base

### Description

A process is invoked with sensitive command-line arguments, environment variables, or other elements that can be seen by other processes on the operating system.

### Extended Description



Many operating systems allow a user to list information about processes that are owned by other users. Other users could see information such as command line arguments or environment variable settings. When this data contains sensitive information such as credentials, it might allow other users to launch an attack against the product or related resources.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		497	Exposure of Sensitive System Information to an Unauthorized Control Sphere	1193
PeerOf		526	Cleartext Storage of Sensitive Information in an Environment Variable	1234

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1016	Limit Exposure	2431

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	2312

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

### Demonstrative Examples

#### Example 1:

In the example below, the password for a keystore file is read from a system property.

*Example Language: Java*

*(Bad)*

```
String keystorePass = System.getProperty("javax.net.ssl.keyStorePassword");
if (keystorePass == null) {
    System.err.println("ERROR: Keystore password not specified.");
    System.exit(-1);
}
...
```

If the property is defined on the command line when the program is invoked (using the -D... syntax), the password may be displayed in the OS process list.

### Observed Examples

Reference	Description
<b>CVE-2005-1387</b>	password passed on command line <a href="https://www.cve.org/CVERecord?id=CVE-2005-1387">https://www.cve.org/CVERecord?id=CVE-2005-1387</a>
<b>CVE-2005-2291</b>	password passed on command line <a href="https://www.cve.org/CVERecord?id=CVE-2005-2291">https://www.cve.org/CVERecord?id=CVE-2005-2291</a>
<b>CVE-2001-1565</b>	username/password on command line allows local users to view via "ps" or other process listing programs <a href="https://www.cve.org/CVERecord?id=CVE-2001-1565">https://www.cve.org/CVERecord?id=CVE-2001-1565</a>
<b>CVE-2004-1948</b>	Username/password on command line allows local users to view via "ps" or other process listing programs. <a href="https://www.cve.org/CVERecord?id=CVE-2004-1948">https://www.cve.org/CVERecord?id=CVE-2004-1948</a>
<b>CVE-1999-1270</b>	PGP passphrase provided as command line argument. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1270">https://www.cve.org/CVERecord?id=CVE-1999-1270</a>



Reference	Description
<b>CVE-2004-1058</b>	Kernel race condition allows reading of environment variables of a process that is still spawning. <a href="https://www.cve.org/CVERecord?id=CVE-2004-1058">https://www.cve.org/CVERecord?id=CVE-2004-1058</a>
<b>CVE-2021-32638</b>	Code analysis product passes access tokens as a command-line parameter or through an environment variable, making them visible to other processes via the ps command. <a href="https://www.cve.org/CVERecord?id=CVE-2021-32638">https://www.cve.org/CVERecord?id=CVE-2021-32638</a>

### Affected Resources

- System Process

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1417	Comprehensive Categorization: Sensitive Information Exposure	1400	2548

### Notes

#### Research Gap

Under-studied, especially environment variables.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Process information infoleak to other processes
Software Fault Patterns	SFP23		Exposed Data

## CWE-215: Insertion of Sensitive Information Into Debugging Code

**Weakness ID** : 215

**Structure** : Simple

**Abstraction** : Base

### Description

The product inserts sensitive information into debugging code, which could expose this information if the debugging code is not disabled in production.

### Extended Description

When debugging, it may be necessary to report detailed information to the programmer. However, if the debugging code is not disabled when the product is operating in a production environment, then this sensitive information may be exposed to attackers.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		200	Exposure of Sensitive Information to an Unauthorized Actor	504
CanFollow		489	Active Debug Code	1171

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	2312

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

#### Phase: Implementation

Do not leave debug statements that could be executed in the source code. Ensure that all debug information is eradicated before releasing the software.

#### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

### Demonstrative Examples

#### Example 1:

The following program changes its behavior based on a debug flag.

*Example Language: JSP*

*(Bad)*

```
<% if (Boolean.getBoolean("debugEnabled")) {
    %>
    User account number: <%= acctNo %>
    <%
    } %>
```

The code writes sensitive debug information to the client browser if the "debugEnabled" flag is set to true .

### Observed Examples

Reference	Description
<b>CVE-2004-2268</b>	Password exposed in debug information. <a href="https://www.cve.org/CVERecord?id=CVE-2004-2268">https://www.cve.org/CVERecord?id=CVE-2004-2268</a>
<b>CVE-2002-0918</b>	CGI script includes sensitive information in debug messages when an error is triggered. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0918">https://www.cve.org/CVERecord?id=CVE-2002-0918</a>
<b>CVE-2003-1078</b>	FTP client with debug option enabled shows password to the screen. <a href="https://www.cve.org/CVERecord?id=CVE-2003-1078">https://www.cve.org/CVERecord?id=CVE-2003-1078</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		717	OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling	629	2332
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	2339
MemberOf		933	OWASP Top Ten 2013 Category A5 - Security Misconfiguration	928	2391
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1417	Comprehensive Categorization: Sensitive Information Exposure	1400	2548

### Notes

#### Relationship

This overlaps other categories.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Infoleak Using Debug Information
OWASP Top Ten 2007	A6	CWE More Specific	Information Leakage and Improper Error Handling
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management
Software Fault Patterns	SFP23		Exposed Data

## CWE-219: Storage of File with Sensitive Data Under Web Root

**Weakness ID :** 219

**Structure :** Simple

**Abstraction :** Variant

### Description

The product stores sensitive data under the web document root with insufficient access control, which might make it accessible to untrusted parties.

### Extended Description

Besides public-facing web pages and code, products may store sensitive data, code that is not directly invoked, or other files under the web document root of the web server. If the server is not configured or otherwise used to prevent direct access to those files, then attackers may obtain this sensitive data.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		552	Files or Directories Accessible to External Parties	1265
ParentOf		433	Unparsed Raw Web Content Delivery	1046

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

### Potential Mitigations

**Phase: Implementation**

**Phase: System Configuration**

Avoid storing information under the web root directory.

**Phase: System Configuration**

Access control permissions should be set to prevent reading/writing of sensitive files inside/outside of the web directory.

### Observed Examples


Reference	Description
<b>CVE-2005-1835</b>	Data file under web root. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1835">https://www.cve.org/CVERecord?id=CVE-2005-1835</a>
<b>CVE-2005-2217</b>	Data file under web root. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2217">https://www.cve.org/CVERecord?id=CVE-2005-2217</a>
<b>CVE-2002-1449</b>	Username/password in data file under web root. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1449">https://www.cve.org/CVERecord?id=CVE-2002-1449</a>
<b>CVE-2002-0943</b>	Database file under web root. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0943">https://www.cve.org/CVERecord?id=CVE-2002-0943</a>
<b>CVE-2005-1645</b>	database file under web root. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1645">https://www.cve.org/CVERecord?id=CVE-2005-1645</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	2339
MemberOf		815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	2358
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400



Nature	Type	ID	Name	V	Page
MemberOf		1345	OWASP Top Ten 2021 Category A01:2021 - Broken Access Control	1344	2487
MemberOf		1403	Comprehensive Categorization: Exposed Resource	1400	2528

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Sensitive Data Under Web Root
OWASP Top Ten 2004	A10		CWE More Specific Insecure Configuration Management

## CWE-220: Storage of File With Sensitive Data Under FTP Root

**Weakness ID :** 220

**Structure :** Simple

**Abstraction :** Variant

### Description

The product stores sensitive data under the FTP server root with insufficient access control, which might make it accessible to untrusted parties.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		552	Files or Directories Accessible to External Parties	1265

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Background Details

Various Unix FTP servers require a password file that is under the FTP root, due to use of chroot.

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

### Potential Mitigations

**Phase: Implementation**

**Phase: System Configuration**

Avoid storing information under the FTP root directory.

**Phase: System Configuration**

Access control permissions should be set to prevent reading/writing of sensitive files inside/outside of the FTP directory.

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436
MemberOf	C	1403	Comprehensive Categorization: Exposed Resource	1400	2528

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Sensitive Data Under FTP Root

## CWE-221: Information Loss or Omission

**Weakness ID :** 221

**Structure :** Simple

**Abstraction :** Class

### Description

The product does not record, or improperly records, security-relevant information that leads to an incorrect decision or hampers later analysis.

### Extended Description

This can be resultant, e.g. a buffer overflow might trigger a crash before the product can log the event.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	P	664	Improper Control of a Resource Through its Lifetime	1454
ParentOf	B	222	Truncation of Security-relevant Information	557
ParentOf	B	223	Omission of Security-relevant Information	559
ParentOf	B	224	Obscured Security-relevant Information by Alternate Name	561
ParentOf	B	356	Product UI does not Warn User of Unsafe Actions	879
ParentOf	B	396	Declaration of Catch for Generic Exception	959
ParentOf	B	397	Declaration of Throws for Generic Exception	961
ParentOf	C	451	User Interface (UI) Misrepresentation of Critical Information	1079

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	

### Demonstrative Examples

**Example 1:**

This code logs suspicious multiple login attempts.

Example Language: PHP

(Bad)

```
function login($userName,$password){
    if(authenticate($userName,$password)){
        return True;
    }
    else{
        incrementLoginAttempts($userName);
        if(recentLoginAttempts($userName) > 5){
            writeLog("Failed login attempt by User: " . $userName . " at " + date('r') );
        }
    }
}
```



This code only logs failed login attempts when a certain limit is reached. If an attacker knows this limit, they can stop their attack from being discovered by avoiding the limit.

### Observed Examples

Reference	Description
<b>CVE-2004-2227</b>	Web browser's filename selection dialog only shows the beginning portion of long filenames, which can trick users into launching executables with dangerous extensions. <a href="https://www.cve.org/CVERecord?id=CVE-2004-2227">https://www.cve.org/CVERecord?id=CVE-2004-2227</a>
<b>CVE-2003-0412</b>	application server does not log complete URI of a long request (truncation). <a href="https://www.cve.org/CVERecord?id=CVE-2003-0412">https://www.cve.org/CVERecord?id=CVE-2003-0412</a>
<b>CVE-1999-1029</b>	Login attempts are not recorded if the user disconnects before the maximum number of tries. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1029">https://www.cve.org/CVERecord?id=CVE-1999-1029</a>
<b>CVE-2002-0725</b>	Attacker performs malicious actions on a hard link to a file, obscuring the real target file. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0725">https://www.cve.org/CVERecord?id=CVE-2002-0725</a>
<b>CVE-1999-1055</b>	Product does not warn user when document contains certain dangerous functions or macros. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1055">https://www.cve.org/CVERecord?id=CVE-1999-1055</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		997	SFP Secondary Cluster: Information Loss	888	2418
MemberOf		1416	Comprehensive Categorization: Resource Lifecycle Management	1400	2545

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Information loss or omission

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
81	Web Server Logs Tampering

## CWE-222: Truncation of Security-relevant Information

**Weakness ID** : 222**Structure** : Simple**Abstraction** : Base


## Description

The product truncates the display, recording, or processing of security-relevant information in a way that can obscure the source or nature of an attack.


## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	556

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1210	Audit / Logging Errors	2475

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences





Scope	Impact	Likelihood
Non-Repudiation	Hide Activities  <i>The source of an attack will be difficult or impossible to determine. This can allow attacks to the system to continue without notice.</i>	

## Observed Examples

Reference	Description
<b>CVE-2005-0585</b>	Web browser truncates long sub-domains or paths, facilitating phishing. <a href="https://www.cve.org/CVERecord?id=CVE-2005-0585">https://www.cve.org/CVERecord?id=CVE-2005-0585</a>
<b>CVE-2004-2032</b>	Bypass URL filter via a long URL with a large number of trailing hex-encoded space characters. <a href="https://www.cve.org/CVERecord?id=CVE-2004-2032">https://www.cve.org/CVERecord?id=CVE-2004-2032</a>
<b>CVE-2003-0412</b>	application server does not log complete URI of a long request (truncation). <a href="https://www.cve.org/CVERecord?id=CVE-2003-0412">https://www.cve.org/CVERecord?id=CVE-2003-0412</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		884	CWE Cross-section	884	2567
MemberOf		997	SFP Secondary Cluster: Information Loss	888	2418
MemberOf		1413	Comprehensive Categorization: Protection Mechanism Failure	1400	2542

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Truncation of Security-relevant Information

## CWE-223: Omission of Security-relevant Information

**Weakness ID :** 223

**Structure :** Simple

**Abstraction :** Base



### Description

The product does not record or display information that would be important for identifying the source or nature of an attack, or determining if an action is safe.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	556
ParentOf		778	Insufficient Logging	1638

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1009	Audit	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1210	Audit / Logging Errors	2475

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities  <i>The source of an attack will be difficult or impossible to determine. This can allow attacks to the system to continue without notice.</i>	

### Demonstrative Examples

#### Example 1:

This code logs suspicious multiple login attempts.

*Example Language: PHP*

*(Bad)*

```
function login($userName,$password){
    if(authenticate($userName,$password)){
        return True;
    }
    else{
        incrementLoginAttempts($userName);
        if(recentLoginAttempts($userName) > 5){
```

```

        writeLog("Failed login attempt by User: " . $userName . " at " + date('r') );
    }
}
}

```

This code only logs failed login attempts when a certain limit is reached. If an attacker knows this limit, they can stop their attack from being discovered by avoiding the limit.

### Example 2:

This code prints the contents of a file if a user has permission.

Example Language: PHP

(Bad)

```

function readFile($filename){
    $user = getCurrentUser();
    $realFile = $filename;
    //resolve file if its a symbolic link
    if(is_link($filename)){
        $realFile = readlink($filename);
    }
    if(fileowner($realFile) == $user){
        echo file_get_contents($realFile);
        return;
    }
    else{
        echo 'Access denied';
        writeLog($user . ' attempted to access the file ' . $filename . ' on ' . date('r'));
    }
}
}

```

While the code logs a bad access attempt, it logs the user supplied name for the file, not the canonicalized file name. An attacker can obscure their target by giving the script the name of a link to the file they are attempting to access. Also note this code contains a race condition between the `is_link()` and `readlink()` functions (CWE-363).

### Observed Examples

Reference	Description
<b>CVE-1999-1029</b>	Login attempts are not recorded if the user disconnects before the maximum number of tries. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1029">https://www.cve.org/CVERecord?id=CVE-1999-1029</a>
<b>CVE-2002-1839</b>	Sender's IP address not recorded in outgoing e-mail. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1839">https://www.cve.org/CVERecord?id=CVE-2002-1839</a>
<b>CVE-2000-0542</b>	Failed authentication attempts are not recorded if later attempt succeeds. <a href="https://www.cve.org/CVERecord?id=CVE-2000-0542">https://www.cve.org/CVERecord?id=CVE-2000-0542</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	997	SFP Secondary Cluster: Information Loss	888	2418
MemberOf	C	1036	OWASP Top Ten 2017 Category A10 - Insufficient Logging & Monitoring	1026	2439
MemberOf	C	1355	OWASP Top Ten 2021 Category A09:2021 - Security Logging and Monitoring Failures	1344	2496
MemberOf	C	1413	Comprehensive Categorization: Protection Mechanism Failure	1400	2542

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Omission of Security-relevant Information

## References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

## CWE-224: Obscured Security-relevant Information by Alternate Name

**Weakness ID :** 224

**Structure :** Simple

**Abstraction :** Base


## Description

The product records security-relevant information according to an alternate name of the affected entity, instead of the canonical name.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	556

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1009	Audit	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1210	Audit / Logging Errors	2475

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	
Access Control	Gain Privileges or Assume Identity	

## Demonstrative Examples

### Example 1:

This code prints the contents of a file if a user has permission.

*Example Language: PHP*

*(Bad)*

```
function readFile($filename){
    $user = getCurrentUser();
    $realFile = $filename;
    //resolve file if its a symbolic link
```



```
if(is_link($filename)){
    $realFile = readlink($filename);
}
if(fileowner($realFile) == $user){
    echo file_get_contents($realFile);
    return;
}
else{
    echo 'Access denied';
    writeLog($user . ' attempted to access the file ' . $filename . ' on ' . date('r'));
}
}
```



While the code logs a bad access attempt, it logs the user supplied name for the file, not the canonicalized file name. An attacker can obscure their target by giving the script the name of a link to the file they are attempting to access. Also note this code contains a race condition between the `is_link()` and `readlink()` functions (CWE-363).

### Observed Examples

Reference	Description
<b>CVE-2002-0725</b>	Attacker performs malicious actions on a hard link to a file, obscuring the real target file. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0725">https://www.cve.org/CVERecord?id=CVE-2002-0725</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		997	SFP Secondary Cluster: Information Loss	888	2418
MemberOf		1413	Comprehensive Categorization: Protection Mechanism Failure	1400	2542

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Obscured Security-relevant Information by Alternate Name

### References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

## CWE-226: Sensitive Information in Resource Not Removed Before Reuse

**Weakness ID :** 226

**Structure :** Simple

**Abstraction :** Base

### Description

The product releases a resource such as memory or a file so that it can be made available for reuse, but it does not clear or "zeroize" the information contained in the resource before the product performs a critical state transition or makes the resource available for reuse by other entities.

### Extended Description

When resources are released, they can be made available for reuse. For example, after memory is de-allocated, an operating system may make the memory available to another process, or disk space may be reallocated when a file is deleted. As removing information requires time and additional resources, operating systems do not usually clear the previously written information.

Even when the resource is reused by the same process, this weakness can arise when new data is not as large as the old data, which leaves portions of the old data still available. Equivalent errors can occur in other situations where the length of data is variable but the associated data structure is not. If memory is not cleared after use, the information may be read by less trustworthy parties when the memory is reallocated.

This weakness can apply in hardware, such as when a device or system switches between power, sleep, or debug states during normal operation, or when execution changes to different users or privilege levels.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	B	212	Improper Removal of Sensitive Information Before Storage or Transfer	544
ChildOf	B	459	Incomplete Cleanup	1099
ParentOf	V	244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	591
ParentOf	V	1239	Improper Zeroization of Hardware Register	2022
ParentOf	B	1272	Sensitive Information Uncleared Before Debug/Power State Transition	2104
ParentOf	B	1301	Insufficient or Incomplete Data Removal within Hardware Component	2170
ParentOf	B	1342	Information Exposure through Microarchitectural State after Transient Execution	2250
CanPrecede	B	201	Insertion of Sensitive Information Into Sent Data	514

*Relevant to the view "Hardware Design" (CWE-1194)*

Nature	Type	ID	Name	Page
ParentOf	V	1239	Improper Zeroization of Hardware Register	2022
ParentOf	B	1342	Information Exposure through Microarchitectural State after Transient Execution	2250

### Weakness Ordinalities

**Primary :**

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

**Technology :** Not Technology-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

### Detection Methods

## Manual Analysis

Write a known pattern into each sensitive location. Trigger the release of the resource or cause the desired state transition to occur. Read data back from the sensitive locations. If the reads are successful, and the data is the same as the pattern that was originally written, the test fails and the product needs to be fixed. Note that this test can likely be automated.

*Effectiveness = High*

## Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

#### Phase: Implementation

During critical state transitions, information not needed in the next state should be removed or overwritten with fixed patterns (such as all 0's) or random data, before the transition to the next state.

*Effectiveness = High*

### Phase: Architecture and Design

#### Phase: Implementation

When releasing, de-allocating, or deleting a resource, overwrite its data and relevant metadata with fixed patterns or random data. Be cautious about complex resource types whose underlying representation might be non-contiguous or change at a low level, such as how a file might be split into different chunks on a file system, even though "logical" file positions are contiguous at the application layer. Such resource types might require invocation of special modes or APIs to tell the underlying operating system to perform the necessary clearing, such as SDelete (Secure Delete) on Windows, although the appropriate functionality might not be available at the application layer.

*Effectiveness = High*

## Demonstrative Examples

### Example 1:

This example shows how an attacker can take advantage of an incorrect state transition.

Suppose a device is transitioning from state A to state B. During state A, it can read certain private keys from the hidden fuses that are only accessible in state A but not in state B. The device reads the keys, performs operations using those keys, then transitions to state B, where those private keys should no longer be accessible.

*Example Language:*

*(Bad)*

During the transition from A to B, the device does not scrub the memory.

After the transition to state B, even though the private keys are no longer accessible directly from the fuses in state B, they can be accessed indirectly by reading the memory that contains the private keys.

*Example Language:*

(Good)

For transition from state A to state B, remove information which should not be available once the transition is complete.

### Example 2:

The following code calls `realloc()` on a buffer containing sensitive data:

*Example Language: C*

(Bad)

```
cleartext_buffer = get_secret();...
cleartext_buffer = realloc(cleartext_buffer, 1024);
...
scrub_memory(cleartext_buffer, 1024);
```

There is an attempt to scrub the sensitive data from memory, but `realloc()` is used, so it could return a pointer to a different part of memory. The memory that was originally allocated for `cleartext_buffer` could still contain an uncleared copy of the data.

### Example 3:

The following example code is excerpted from the AES wrapper/interface, `aes0_wrapper`, module of one of the AES engines (AES0) in the Hack@DAC'21 buggy OpenPiton System-on-Chip (SoC). Note that this SoC contains three distinct AES engines. Within this wrapper module, four 32-bit registers are utilized to store the message intended for encryption, referred to as `p_c[i]`. Using the AXI Lite interface, these registers are filled with the 128-bit message to be encrypted.

*Example Language: Verilog*

(Bad)

```
module aes0_wrapper #(...)(...);
...
always @(posedge clk_i)
begin
    if(~(rst_ni && ~rst_1)) //clear p_c[i] at reset
    begin
        start <= 0;
        p_c[0] <= 0;
        p_c[1] <= 0;
        p_c[2] <= 0;
        p_c[3] <= 0;
        ...
    end
    else if(en && we)
    case(address[8:3])
    0:
        start <= reglk_ctrl_i[1] ? start : wdata[0];
    1:
        p_c[3] <= reglk_ctrl_i[3] ? p_c[3] : wdata[31:0];
    2:
        p_c[2] <= reglk_ctrl_i[3] ? p_c[2] : wdata[31:0];
    3:
        p_c[1] <= reglk_ctrl_i[3] ? p_c[1] : wdata[31:0];
    4:
        p_c[0] <= reglk_ctrl_i[3] ? p_c[0] : wdata[31:0];
    ...
    endcase
end // always @ (posedge wb_clk_i)
endmodule
```

The above code snippet [REF-1402] illustrates an instance of a vulnerable implementation of the AES wrapper module, where p\_c[i] registers are cleared at reset. Otherwise, p\_c[i] registers either maintain their old values (if reglk\_ctrl\_i[3] is true) or get filled through the AXI signal wdata. Note that p\_c[i] registers can be read through the AXI Lite interface (not shown in snippet). However, p\_c[i] registers are never cleared after their usage once the AES engine has completed the encryption process of the message. In a multi-user or multi-process environment, not clearing registers may result in the attacker process accessing data left by the victim, leading to data leakage or unintentional information disclosure.

To fix this issue, it is essential to ensure that these internal registers are cleared in a timely manner after their usage, i.e., the encryption process is complete. This is illustrated below by monitoring the assertion of the cipher text valid signal, ct\_valid [REF-1403].

Example Language: Verilog

(Good)

```
module aes0_wrapper #(...)(...);
...
always @(posedge clk_i)
begin
    if(~(rst_ni && ~rst_1)) //clear p_c[i] at reset
    ...
    else if(ct_valid) //encryption process complete, clear p_c[i]
    begin
        p_c[0] <= 0;
        p_c[1] <= 0;
        p_c[2] <= 0;
        p_c[3] <= 0;
    end
    else if(en && we)
        case(address[8:3])
        ...
        endcase
    end // always @ (posedge wb_clk_i)
endmodule
```

## Observed Examples

Reference	Description
<b>CVE-2019-3733</b>	Cryptography library does not clear heap memory before release <a href="https://www.cve.org/CVERecord?id=CVE-2019-3733">https://www.cve.org/CVERecord?id=CVE-2019-3733</a>
<b>CVE-2003-0001</b>	Ethernet NIC drivers do not pad frames with null bytes, leading to infoleak from malformed packets. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0001">https://www.cve.org/CVERecord?id=CVE-2003-0001</a>
<b>CVE-2003-0291</b>	router does not clear information from DHCP packets that have been previously used <a href="https://www.cve.org/CVERecord?id=CVE-2003-0291">https://www.cve.org/CVERecord?id=CVE-2003-0291</a>
<b>CVE-2005-1406</b>	Products do not fully clear memory buffers when less data is stored into the buffer than previous. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1406">https://www.cve.org/CVERecord?id=CVE-2005-1406</a>
<b>CVE-2005-1858</b>	Products do not fully clear memory buffers when less data is stored into the buffer than previous. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1858">https://www.cve.org/CVERecord?id=CVE-2005-1858</a>
<b>CVE-2005-3180</b>	Products do not fully clear memory buffers when less data is stored into the buffer than previous. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3180">https://www.cve.org/CVERecord?id=CVE-2005-3180</a>
<b>CVE-2005-3276</b>	Product does not clear a data structure before writing to part of it, yielding information leak of previously used memory. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3276">https://www.cve.org/CVERecord?id=CVE-2005-3276</a>
<b>CVE-2002-2077</b>	Memory not properly cleared before reuse. <a href="https://www.cve.org/CVERecord?id=CVE-2002-2077">https://www.cve.org/CVERecord?id=CVE-2002-2077</a>

## Functional Areas







- Memory Management
- Networking

## Affected Resources

- Memory

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	2338
MemberOf		742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	2345
MemberOf		876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	2376
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1202	Memory and Storage Issues	1194	2472
MemberOf		1416	Comprehensive Categorization: Resource Lifecycle Management	1400	2545

## Notes

### Relationship

There is a close association between CWE-226 and CWE-212. The difference is partially that of perspective. CWE-226 is geared towards the final stage of the resource lifecycle, in which the resource is deleted, eliminated, expired, or otherwise released for reuse. Technically, this involves a transfer to a different control sphere, in which the original contents of the resource are no longer relevant. CWE-212, however, is intended for sensitive data in resources that are intentionally shared with others, so they are still active. This distinction is useful from the perspective of the CWE research view (CWE-1000).

### Maintenance

This entry needs modification to clarify the differences with CWE-212. The description also combines two problems that are distinct from the CWE research perspective: the inadvertent transfer of information to another sphere, and improper initialization/shutdown. Some of the associated taxonomy mappings reflect these different uses.

### Research Gap

This is frequently found for network packets, but it can also exist in local memory allocation, files, etc.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Sensitive Information Uncleared Before Use
CERT C Secure Coding	MEM03-C		Clear sensitive information stored in reusable resources returned for reuse
Software Fault Patterns	SFP23		Exposed Data

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
37	Retrieve Embedded Sensitive Data

## References

[REF-1402]"aes0\_wrapper.sv". 2021. < [https://github.com/HACK-EVENT/hackatdac21/blob/65d0ffdab7426da4509c98d62e163bcce642f651/piton/design/chip/tile/ariane/src/aes0/aes0\\_wrapper.sv#L84C2-L90C29](https://github.com/HACK-EVENT/hackatdac21/blob/65d0ffdab7426da4509c98d62e163bcce642f651/piton/design/chip/tile/ariane/src/aes0/aes0_wrapper.sv#L84C2-L90C29)> >.2024-02-14.

[REF-1403]"Fix for aes0\_wrapper". 2023 November 9. < [https://github.com/HACK-EVENT/hackatdac21/blob/0034dff6852365a8c4e36590a47ea8b088d725ae/piton/design/chip/tile/ariane/src/aes0/aes0\\_wrapper.sv#L96C1-L102C16](https://github.com/HACK-EVENT/hackatdac21/blob/0034dff6852365a8c4e36590a47ea8b088d725ae/piton/design/chip/tile/ariane/src/aes0/aes0_wrapper.sv#L96C1-L102C16)> >.2024-02-14.

## CWE-228: Improper Handling of Syntactically Invalid Structure

**Weakness ID :** 228

**Structure :** Simple

**Abstraction :** Class

### Description

The product does not handle or incorrectly handles input that is not syntactically well-formed with respect to the associated specification.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	P	703	Improper Check or Handling of Exceptional Conditions	1535
ChildOf	P	707	Improper Neutralization	1546
ParentOf	B	166	Improper Handling of Missing Special Element	423
ParentOf	B	167	Improper Handling of Additional Special Element	425
ParentOf	B	168	Improper Handling of Inconsistent Special Elements	426
ParentOf	B	229	Improper Handling of Values	570
ParentOf	B	233	Improper Handling of Parameters	574
ParentOf	B	237	Improper Handling of Structural Elements	580
ParentOf	B	241	Improper Handling of Unexpected Data Type	584

### Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU)	
	<i>If an input is syntactically invalid, then processing the input could place the system in an unexpected state that could lead to a crash, consume available system resources or other unintended behaviors.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)



Effectiveness = High

## Demonstrative Examples

### Example 1:

This Android application has registered to handle a URL when sent an intent:

Example Language: Java

(Bad)

```
...
IntentFilter filter = new IntentFilter("com.example.URLHandler.openURL");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
...
public class UrlHandlerReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        if("com.example.URLHandler.openURL".equals(intent.getAction())) {
            String URL = intent.getStringExtra("URLToOpen");
            int length = URL.length();
        }
    }
}
```





The application assumes the URL will always be included in the intent. When the URL is not present, the call to `getStringExtra()` will return null, thus causing a null pointer exception when `length()` is called.

## Observed Examples

Reference	Description
<b>CVE-2004-0270</b>	Anti-virus product has assert error when line length is non-numeric. <a href="https://www.cve.org/CVERecord?id=CVE-2004-0270">https://www.cve.org/CVERecord?id=CVE-2004-0270</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	2337
MemberOf		884	CWE Cross-section	884	2567
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

## Notes

### Maintenance

This entry needs more investigation. Public vulnerability research generally focuses on the manipulations that generate invalid structure, instead of the weaknesses that are exploited by those manipulations. For example, a common attack involves making a request that omits a required field, which can trigger a crash in some cases. The crash could be due to a named chain such as CWE-690 (Unchecked Return Value to NULL Pointer Dereference), but public reports rarely cover this aspect of a vulnerability.

### Theoretical

The validity of input could be roughly classified along "syntactic", "semantic", and "lexical" dimensions. If the specification requires that an input value should be delimited with the "[" and "]" square brackets, then any input that does not follow this specification would be syntactically

invalid. If the input between the brackets is expected to be a number, but the letters "aaa" are provided, then the input is syntactically invalid. If the input is a number and enclosed in brackets, but the number is outside of the allowable range, then it is semantically invalid. The inter-relationships between these properties - and their associated weaknesses- need further exploration.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Structure and Validity Problems
OWASP Top Ten 2004	A7	CWE More Specific	Improper Error Handling

## CWE-229: Improper Handling of Values

**Weakness ID :** 229

**Structure :** Simple

**Abstraction :** Base





### Description

The product does not properly handle when the expected number of values for parameters, fields, or arguments is not provided in input, or if those values are undefined.


### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	568
ParentOf		230	Improper Handling of Missing Values	570
ParentOf		231	Improper Handling of Extra Values	572
ParentOf		232	Improper Handling of Undefined Values	573

*Relevant to the view "Software Development" (CWE-699)*




Nature	Type	ID	Name	Page
MemberOf		19	Data Processing Errors	2309

### Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

## CWE-230: Improper Handling of Missing Values

**Weakness ID :** 230  
**Structure :** Simple  
**Abstraction :** Variant


### Description

The product does not handle or incorrectly handles when a parameter, field, or argument name is specified, but the associated value is missing, i.e. it is empty, blank, or null.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		229	Improper Handling of Values	570

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

### Demonstrative Examples

#### Example 1:

This Android application has registered to handle a URL when sent an intent:

*Example Language: Java*

*(Bad)*

```
...
IntentFilter filter = new IntentFilter("com.example.URLHandler.openURL");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
...
public class UrlHandlerReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        if("com.example.URLHandler.openURL".equals(intent.getAction())) {
            String URL = intent.getStringExtra("URLToOpen");
            int length = URL.length();
            ...
        }
    }
}
```

The application assumes the URL will always be included in the intent. When the URL is not present, the call to `getStringExtra()` will return null, thus causing a null pointer exception when `length()` is called.




### Observed Examples

Reference	Description
<b>CVE-2002-0422</b>	Blank Host header triggers resultant infoleak. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0422">https://www.cve.org/CVERecord?id=CVE-2002-0422</a>
<b>CVE-2000-1006</b>	Blank "charset" attribute in MIME header triggers crash. <a href="https://www.cve.org/CVERecord?id=CVE-2000-1006">https://www.cve.org/CVERecord?id=CVE-2000-1006</a>
<b>CVE-2004-1504</b>	Blank parameter causes external error infoleak.

Reference	Description
	<a href="https://www.cve.org/CVERecord?id=CVE-2004-1504">https://www.cve.org/CVERecord?id=CVE-2004-1504</a>
<b>CVE-2005-2053</b>	Blank parameter causes external error infoleak. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2053">https://www.cve.org/CVERecord?id=CVE-2005-2053</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	2365
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Notes

#### Research Gap

Some "crash by port scan" bugs are probably due to this, but lack of diagnosis makes it difficult to be certain.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Value Error
The CERT Oracle Secure Coding Standard for Java (2011)	ERR08-J		Do not catch NullPointerException or any of its ancestors

## CWE-231: Improper Handling of Extra Values

**Weakness ID :** 231

**Structure :** Simple

**Abstraction :** Variant



### Description

The product does not handle or incorrectly handles when more values are provided than expected.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		229	Improper Handling of Values	570
CanPrecede		120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	304

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Scope	Impact	Likelihood
-------	--------	------------

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf	C	1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Notes

#### Relationship

This can overlap buffer overflows.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Extra Value Error

## CWE-232: Improper Handling of Undefined Values

**Weakness ID :** 232

**Structure :** Simple

**Abstraction :** Variant

### Description

The product does not handle or incorrectly handles when a value is not defined or supported for the associated parameter, field, or argument name.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	B	229	Improper Handling of Values	570

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

### Demonstrative Examples

#### Example 1:

In this example, an address parameter is read and trimmed of whitespace.

*Example Language: Java*

*(Bad)*

```
String address = request.getParameter("address");
address = address.trim();
String updateString = "UPDATE shippingInfo SET address='?' WHERE email='cwe@example.com'";
emailAddress = con.prepareStatement(updateString);
```

```
emailAddress.setString(1, address);
```




If the value of the address parameter is null (undefined), the servlet will throw a `NullPointerException` when the `trim()` is attempted.

### Observed Examples

Reference	Description
<b>CVE-2000-1003</b>	Client crash when server returns unknown driver type. <a href="https://www.cve.org/CVERecord?id=CVE-2000-1003">https://www.cve.org/CVERecord?id=CVE-2000-1003</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	2365
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Undefined Value Error
The CERT Oracle Secure Coding Standard for Java (2011)	ERR08-J		Do not catch <code>NullPointerException</code> or any of its ancestors

## CWE-233: Improper Handling of Parameters

**Weakness ID :** 233

**Structure :** Simple

**Abstraction :** Base





### Description

The product does not properly handle when the expected number of parameters, fields, or arguments is not provided in input, or if those parameters are undefined.


### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as `ChildOf`, `ParentOf`, `MemberOf` and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as `PeerOf` and `CanAlsoBe` are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	568
ParentOf		234	Failure to Handle Missing Parameter	576
ParentOf		235	Improper Handling of Extra Parameters	578
ParentOf		236	Improper Handling of Undefined Parameters	579

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		19	Data Processing Errors	2309

## Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

## Detection Methods

### Fuzzing

Fuzz testing (fuzzing) is a powerful technique for generating large numbers of diverse inputs - either randomly or algorithmically - and dynamically invoking the code with those inputs. Even with random inputs, it is often capable of generating unexpected results such as crashes, memory corruption, or resource consumption. Fuzzing effectively produces repeatable test cases that clearly indicate bugs, which helps developers to diagnose the issues.

*Effectiveness = High*

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Demonstrative Examples

### Example 1:

This Android application has registered to handle a URL when sent an intent:

*Example Language: Java*




*(Bad)*

```
...
IntentFilter filter = new IntentFilter("com.example.URLHandler.openURL");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
...
public class UrlHandlerReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        if("com.example.URLHandler.openURL".equals(intent.getAction())) {
            String URL = intent.getStringExtra("URLToOpen");
            int length = URL.length();
        }
    }
}
```

The application assumes the URL will always be included in the intent. When the URL is not present, the call to `getStringExtra()` will return null, thus causing a null pointer exception when `length()` is called.

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532



## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Parameter Problems

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
39	Manipulating Opaque Client-based Data Tokens

## CWE-234: Failure to Handle Missing Parameter

**Weakness ID :** 234

**Structure :** Simple

**Abstraction :** Variant


### Description

If too few arguments are sent to a function, the function will still pop the expected number of arguments from the stack. Potentially, a variable number of arguments could be exhausted in a function as well.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		233	Improper Handling of Parameters	574

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Gain Privileges or Assume Identity	
Availability	<i>There is the potential for arbitrary code execution with privileges of the vulnerable program if function parameter list is exhausted.</i>	
Access Control		
Availability	DoS: Crash, Exit, or Restart	
	<i>Potentially a program could fail if it needs more arguments then are available.</i>	

### Potential Mitigations

#### Phase: Build and Compilation

This issue can be simply combated with the use of proper build process.

#### Phase: Implementation

Forward declare all functions. This is the recommended solution. Properly forward declaration of all used functions will result in a compiler error if too few arguments are sent to a function.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C (Bad)

```
foo_func(one, two);
void foo_func(int one, int two, int three) {
    printf("1) %d\n2) %d\n3) %d\n", one, two, three);
}
```

Example Language: C (Bad)

```
void some_function(int foo, ...) {
    int a[3], i;
    va_list ap;
    va_start(ap, foo);
    for (i = 0; i < sizeof(a) / sizeof(int); i++) a[i] = va_arg(ap, int);
    va_end(ap);
}
int main(int argc, char *argv[]) {
    some_function(17, 42);
}
```

This can be exploited to disclose information with no work whatsoever. In fact, each time this function is run, it will print out the next 4 bytes on the stack after the two numbers sent to it.


Observed Examples

Reference	Description
CVE-2004-0276	Server earlier allows remote attackers to cause a denial of service (crash) via an HTTP request with a sequence of "%" characters and a missing Host field. <a href="https://www.cve.org/CVERecord?id=CVE-2004-0276">https://www.cve.org/CVERecord?id=CVE-2004-0276</a>
CVE-2002-1488	Chat client allows remote malicious IRC servers to cause a denial of service (crash) via a PART message with (1) a missing channel or (2) a channel that the user is not in. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1488">https://www.cve.org/CVERecord?id=CVE-2002-1488</a>
CVE-2002-1169	Proxy allows remote attackers to cause a denial of service (crash) via an HTTP request to helpout.exe with a missing HTTP version numbers. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1169">https://www.cve.org/CVERecord?id=CVE-2002-1169</a>
CVE-2000-0521	Web server allows disclosure of CGI source code via an HTTP request without the version number. <a href="https://www.cve.org/CVERecord?id=CVE-2000-0521">https://www.cve.org/CVERecord?id=CVE-2000-0521</a>
CVE-2001-0590	Application server allows a remote attacker to read the source code to arbitrary 'jsp' files via a malformed URL request which does not end with an HTTP protocol specification. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0590">https://www.cve.org/CVERecord?id=CVE-2001-0590</a>
CVE-2003-0239	Chat software allows remote attackers to cause a denial of service via malformed GIF89a headers that do not contain a GCT (Global Color Table) or an LCT (Local Color Table) after an Image Descriptor. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0239">https://www.cve.org/CVERecord?id=CVE-2003-0239</a>
CVE-2002-1023	Server allows remote attackers to cause a denial of service (crash) via an HTTP GET request without a URI. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1023">https://www.cve.org/CVERecord?id=CVE-2002-1023</a>
CVE-2002-1236	CGI crashes when called without any arguments. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1236">https://www.cve.org/CVERecord?id=CVE-2002-1236</a>
CVE-2003-0422	CGI crashes when called without any arguments. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0422">https://www.cve.org/CVERecord?id=CVE-2003-0422</a>

Reference	Description
<b>CVE-2002-1531</b>	Crash in HTTP request without a Content-Length field. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1531">https://www.cve.org/CVERecord?id=CVE-2002-1531</a>
<b>CVE-2002-1077</b>	Crash in HTTP request without a Content-Length field. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1077">https://www.cve.org/CVERecord?id=CVE-2002-1077</a>
<b>CVE-2002-1358</b>	Empty elements/strings in protocol test suite affect many SSH2 servers/clients. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1358">https://www.cve.org/CVERecord?id=CVE-2002-1358</a>
<b>CVE-2003-0477</b>	FTP server crashes in PORT command without an argument. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0477">https://www.cve.org/CVERecord?id=CVE-2003-0477</a>
<b>CVE-2002-0107</b>	Resultant infoleak in web server via GET requests without HTTP/1.0 version string. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0107">https://www.cve.org/CVERecord?id=CVE-2002-0107</a>
<b>CVE-2002-0596</b>	GET request with empty parameter leads to error message infoleak (path disclosure). <a href="https://www.cve.org/CVERecord?id=CVE-2002-0596">https://www.cve.org/CVERecord?id=CVE-2002-0596</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Notes

#### Maintenance

This entry will be deprecated in a future version of CWE. The term "missing parameter" was used in both PLOVER and CLASP, with completely different meanings. However, data from both taxonomies was merged into this entry. In PLOVER, it was meant to cover malformed inputs that do not contain required parameters, such as a missing parameter in a CGI request. This entry's observed examples and classification came from PLOVER. However, the description, demonstrative example, and other information are derived from CLASP. They are related to an incorrect number of function arguments, which is already covered by CWE-685.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Parameter Error
CLASP			Missing parameter

## CWE-235: Improper Handling of Extra Parameters

**Weakness ID :** 235

**Structure :** Simple

**Abstraction :** Variant

### Description


The product does not handle or incorrectly handles when the number of parameters, fields, or arguments with the same name exceeds the expected amount.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		233	Improper Handling of Parameters	574

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences





Scope	Impact	Likelihood
Integrity	Unexpected State	

### Observed Examples

Reference	Description
<b>CVE-2003-1014</b>	MIE. multiple gateway/security products allow restriction bypass using multiple MIME fields with the same name, which are interpreted differently by clients. <a href="https://www.cve.org/CVERecord?id=CVE-2003-1014">https://www.cve.org/CVERecord?id=CVE-2003-1014</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Notes

#### Relationship

This type of problem has a big role in multiple interpretation vulnerabilities and various HTTP attacks.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Extra Parameter Error

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
460	HTTP Parameter Pollution (HPP)

## CWE-236: Improper Handling of Undefined Parameters

**Weakness ID** : 236

**Structure** : Simple

**Abstraction** : Variant


### Description

The product does not handle or incorrectly handles when a particular parameter, field, or argument name is not defined or supported by the product.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		233	Improper Handling of Parameters	574

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

### Observed Examples

Reference	Description
<b>CVE-2002-1488</b>	Crash in IRC client via PART message from a channel the user is not in. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1488">https://www.cve.org/CVERecord?id=CVE-2002-1488</a>
<b>CVE-2001-0650</b>	Router crash or bad route modification using BGP updates with invalid transitive attribute. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0650">https://www.cve.org/CVERecord?id=CVE-2001-0650</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Undefined Parameter Error

## CWE-237: Improper Handling of Structural Elements

**Weakness ID** : 237

**Structure** : Simple

**Abstraction** : Base


### Description




The product does not handle or incorrectly handles inputs that are related to complex structures.

### Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	568

Nature	Type	ID	Name	Page
ParentOf		238	Improper Handling of Incomplete Structural Elements	581
ParentOf		239	Failure to Handle Incomplete Element	582
ParentOf		240	Improper Handling of Inconsistent Structural Elements	583

*Relevant to the view "Software Development" (CWE-699)*




Nature	Type	ID	Name	Page
MemberOf		19	Data Processing Errors	2309

### Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Element Problems

## CWE-238: Improper Handling of Incomplete Structural Elements

**Weakness ID :** 238

**Structure :** Simple

**Abstraction :** Variant


### Description

The product does not handle or incorrectly handles when a particular structural element is not completely specified.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		237	Improper Handling of Structural Elements	580

### Weakness Ordinalities

**Resultant :**

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Scope	Impact	Likelihood
-------	--------	------------

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf	C	1407	Comprehensive Categorization: Improper Neutralization	1400	2532

## Notes

### Relationship

Can be primary to other problems.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Element Error

## CWE-239: Failure to Handle Incomplete Element

**Weakness ID :** 239

**Structure :** Simple

**Abstraction :** Variant

## Description

The product does not properly handle when a particular element is not completely specified.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	B	237	Improper Handling of Structural Elements	580
PeerOf	C	404	Improper Resource Shutdown or Release	980

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	

## Observed Examples

Reference	Description
<b>CVE-2002-1532</b>	HTTP GET without \r\n\r\n CRLF sequences causes product to wait indefinitely and prevents other users from accessing it. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1532">https://www.cve.org/CVERecord?id=CVE-2002-1532</a>
<b>CVE-2003-0195</b>	Partial request is not timed out. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0195">https://www.cve.org/CVERecord?id=CVE-2003-0195</a>



Reference	Description
<b>CVE-2005-2526</b>	MFV. CPU exhaustion in printer via partial printing request then early termination of connection. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2526">https://www.cve.org/CVERecord?id=CVE-2005-2526</a>
<b>CVE-2002-1906</b>	CPU consumption by sending incomplete HTTP requests and leaving the connections open. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1906">https://www.cve.org/CVERecord?id=CVE-2002-1906</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incomplete Element

## CWE-240: Improper Handling of Inconsistent Structural Elements

**Weakness ID :** 240

**Structure :** Simple

**Abstraction :** Base

### Description

The product does not handle or incorrectly handles when two or more structural elements should be consistent, but are not.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		707	Improper Neutralization	1546
ChildOf		237	Improper Handling of Structural Elements	580
ParentOf		130	Improper Handling of Length Parameter Inconsistency	351

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	

### Demonstrative Examples

**Example 1:**

In the following C/C++ example the method processMessageFromSocket() will get a message from a socket, placed into a buffer, and will parse the contents of the buffer into a structure that contains the message length and the message body. A for loop is used to copy the message body into a local character string which will be passed to another method for processing.

Example Language: C (Bad)

```
int processMessageFromSocket(int socket) {
    int success;
    char buffer[BUFFER_SIZE];
    char message[MESSAGE_SIZE];
    // get message from socket and store into buffer
    //Ignoring possiblity that buffer > BUFFER_SIZE
    if (getMessage(socket, buffer, BUFFER_SIZE) > 0) {
        // place contents of the buffer into message structure
        ExMessage *msg = recastBuffer(buffer);
        // copy message body into string for processing
        int index;
        for (index = 0; index < msg->msgLength; index++) {
            message[index] = msg->msgBody[index];
        }
        message[index] = '\0';
        // process message
        success = processMessage(message);
    }
    return success;
}
```

However, the message length variable from the structure is used as the condition for ending the for loop without validating that the message length variable accurately reflects the length of the message body (CWE-606). This can result in a buffer over-read (CWE-125) by reading from memory beyond the bounds of the buffer if the message length variable indicates a length that is longer than the size of a message body (CWE-130).

Observed Examples

Reference	Description
CVE-2014-0160	Chain: "Heartbleed" bug receives an inconsistent length parameter (CWE-130) enabling an out-of-bounds read (CWE-126), returning memory that could include private cryptographic keys and other sensitive data. <a href="https://www.cve.org/CVERecord?id=CVE-2014-0160">https://www.cve.org/CVERecord?id=CVE-2014-0160</a>
CVE-2009-2299	Web application firewall consumes excessive memory when an HTTP request contains a large Content-Length value but no POST data. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2299">https://www.cve.org/CVERecord?id=CVE-2009-2299</a>

MemberOf Relationships

This MemberOf relationships table shows additional CWE Catgeories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf	C	1407	Comprehensive Categorization: Improper Neutralization	1400	2532

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Inconsistent Elements

CWE-241: Improper Handling of Unexpected Data Type

**Weakness ID :** 241**Structure :** Simple**Abstraction :** Base


### Description

The product does not handle or incorrectly handles when a particular element is not the expected type, e.g. it expects a digit (0-9) but is provided with a letter (A-Z).


### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	568

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		19	Data Processing Errors	2309

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	

### Potential Mitigations

#### Phase: Implementation

*Strategy = Input Validation*

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a list of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs. This is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, denylists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

#### Phase: Implementation

*Strategy = Input Validation*






Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass allowlist validation schemes by introducing dangerous inputs after they have been checked.

### Observed Examples

Reference	Description
<b>CVE-1999-1156</b>	FTP server crash via PORT command with non-numeric character. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1156">https://www.cve.org/CVERecord?id=CVE-1999-1156</a>
<b>CVE-2004-0270</b>	Anti-virus product has assert error when line length is non-numeric. <a href="https://www.cve.org/CVERecord?id=CVE-2004-0270">https://www.cve.org/CVERecord?id=CVE-2004-0270</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	2347
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	2377
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	2417
MemberOf		1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	2459
MemberOf		1407	Comprehensive Categorization: Improper Neutralization	1400	2532

### Notes

#### Research Gap

Probably under-studied.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Wrong Data Type
CERT C Secure Coding	FIO37-C	CWE More Abstract	Do not assume that fgets() or fgetws() returns a nonempty string when successful

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
48	Passing Local Filenames to Functions That Expect a URL

## CWE-242: Use of Inherently Dangerous Function

**Weakness ID** : 242

**Structure** : Simple

**Abstraction** : Base

### Description

The product calls a function that can never be guaranteed to work safely.

### Extended Description

Certain functions behave in dangerous ways regardless of how they are used. Functions in this category were often implemented without taking security concerns into account. The gets() function is unsafe because it does not perform bounds checking on the size of its input. An attacker can easily send arbitrarily-sized input to gets() and overflow the destination buffer. Similarly, the >> operator is unsafe to use when reading into a statically-allocated character array because it does not perform bounds checking on the size of its input. An attacker can easily send arbitrarily-sized input to the >> operator and overflow the destination buffer.


### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1177	Use of Prohibited Code	1972

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1228	API / Function Errors	2482

## Weakness Ordinalities

**Primary :**

## Applicable Platforms

**Language :** C (Prevalence = Undetermined)

**Language :** C++ (Prevalence = Undetermined)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

**Phase: Implementation**

**Phase: Requirements**

Ban the use of dangerous functions. Use their safe equivalent.

**Phase: Testing**

Use grep or static analysis tools to spot usage of dangerous functions.

## Demonstrative Examples

### Example 1:

The code below calls gets() to read information into a buffer.

*Example Language: C*

*(Bad)*

```
char buf[BUFSIZE];
gets(buf);
```

The gets() function in C is inherently unsafe.

### Example 2:

The code below calls the gets() function to read in data from the command line.

Example Language: C

(Bad)

```
char buf[24];
printf("Please enter your name and press <Enter>\n");
gets(buf);
...
}
```






However, gets() is inherently unsafe, because it copies all input from STDIN to the buffer without checking size. This allows the user to provide a string that is larger than the buffer size, resulting in an overflow condition.

### Observed Examples

Reference	Description
<b>CVE-2007-4004</b>	FTP client uses inherently insecure gets() function and is setuid root on some systems, allowing buffer overflow <a href="https://www.cve.org/CVERecord?id=CVE-2007-4004">https://www.cve.org/CVERecord?id=CVE-2007-4004</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		227	7PK - API Abuse	700	2313
MemberOf		748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	2351
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	2420
MemberOf		1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	2463
MemberOf		1412	Comprehensive Categorization: Poor Coding Practices	1400	2538

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Dangerous Functions
CERT C Secure Coding	POS33-C	CWE More Abstract	Do not use vfork()
Software Fault Patterns	SFP3		Use of an improper API

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-194]Herbert Schildt. "Herb Schildt's C++ Programming Cookbook". 2008 April 8. McGraw-Hill Osborne Media.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

## CWE-243: Creation of chroot Jail Without Changing Working Directory

**Weakness ID :** 243

**Structure :** Simple

**Abstraction :** Variant

### Description

The product uses the chroot() system call to create a jail, but does not change the working directory afterward. This does not prevent access to files outside of the jail.



### Extended Description

Improper use of chroot() may allow attackers to escape from the chroot jail. The chroot() function call does not change the process's current working directory, so relative paths may still refer to file system resources outside of the chroot jail after chroot() has been called.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1298
ChildOf		669	Incorrect Resource Transfer Between Spheres	1471

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	2430

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316

### Weakness Ordinalities

**Resultant :**

### Applicable Platforms

**Language :** C (Prevalence = Undetermined)

**Language :** C++ (Prevalence = Undetermined)

**Operating\_System :** Unix (Prevalence = Undetermined)

### Background Details

The chroot() system call allows a process to change its perception of the root directory of the file system. After properly invoking chroot(), a process cannot access any files outside the directory tree defined by the new root directory. Such an environment is called a chroot jail and is commonly used to prevent the possibility that a processes could be subverted and used to access unauthorized files. For instance, many FTP servers run in chroot jails to prevent an attacker who discovers a new vulnerability in the server from being able to download the password file or other sensitive files on the system.

### Likelihood Of Exploit

High

### Common Consequences



Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Demonstrative Examples

### Example 1:

Consider the following source code from a (hypothetical) FTP server:

*Example Language: C*

*(Bad)*

```
chroot("/var/ftpboot");
...
fgets(filename, sizeof(filename), network);
localfile = fopen(filename, "r");
while ((len = fread(buf, 1, sizeof(buf), localfile)) != EOF) {
    fwrite(buf, 1, sizeof(buf), network);
}
fclose(localfile);
```





This code is responsible for reading a filename from the network, opening the corresponding file on the local machine, and sending the contents over the network. This code could be used to implement the FTP GET command. The FTP server calls `chroot()` in its initialization routines in an attempt to prevent access to files outside of `/var/ftpboot`. But because the server does not change the current working directory by calling `chdir("/")`, an attacker could request the file `"../../../../etc/passwd"` and obtain a copy of the system password file.

## Affected Resources

- File or Directory

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		227	7PK - API Abuse	700	2313
MemberOf		979	SFP Secondary Cluster: Failed Chroot Jail	888	2408
MemberOf		1416	Comprehensive Categorization: Resource Lifecycle Management	1400	2545

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Directory Restriction
Software Fault Patterns	SFP17		Failed chroot jail

## References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

## CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection')

**Weakness ID** : 244

**Structure** : Simple

**Abstraction** : Variant

### Description

Using realloc() to resize buffers that store sensitive information can leave the sensitive information exposed to attack, because it is not removed from memory.



### Extended Description

When sensitive data such as a password or an encryption key is not removed from memory, it could be exposed to an attacker using a "heap inspection" attack that reads the sensitive data using memory dumps or other methods. The realloc() function is commonly used to increase the size of a block of allocated memory. This operation often requires copying the contents of the old memory block into a new and larger block. This operation leaves the contents of the original block intact but inaccessible to the program, preventing the program from being able to scrub sensitive data from memory. If an attacker can later examine the contents of a memory dump, the sensitive data could be exposed.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		226	Sensitive Information in Resource Not Removed Before Reuse	562
CanPrecede		669	Incorrect Resource Transfer Between Spheres	1471

### Applicable Platforms

**Language** : C (Prevalence = Undetermined)

**Language** : C++ (Prevalence = Undetermined)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
Other	Other	
<i>Be careful using vfork() and fork() in security sensitive code. The process state will not be cleaned up and will contain traces of data from past use.</i>		

### Demonstrative Examples

#### Example 1:

The following code calls realloc() on a buffer containing sensitive data:

Example Language: C

(Bad)

```
cleartext_buffer = get_secret();...
cleartext_buffer = realloc(cleartext_buffer, 1024);
...
scrub_memory(cleartext_buffer, 1024);
```

There is an attempt to scrub the sensitive data from memory, but `realloc()` is used, so it could return a pointer to a different part of memory. The memory that was originally allocated for `cleartext_buffer` could still contain an uncleared copy of the data.

### Observed Examples

Reference	Description
<b>CVE-2019-3733</b>	Cryptography library does not clear heap memory before release <a href="https://www.cve.org/CVERecord?id=CVE-2019-3733">https://www.cve.org/CVERecord?id=CVE-2019-3733</a>

### Affected Resources

- Memory

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		227	7PK - API Abuse	700	2313
MemberOf		742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	2345
MemberOf		876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	2376
MemberOf		884	CWE Cross-section	884	2567
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1399	Comprehensive Categorization: Memory Safety	1400	2525

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Heap Inspection
CERT C Secure Coding	MEM03-C		Clear sensitive information stored in reusable resources returned for reuse
Software Fault Patterns	SFP23		Exposed Data

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

## CWE-245: J2EE Bad Practices: Direct Management of Connections

**Weakness ID** : 245

**Structure** : Simple

**Abstraction** : Variant

### Description

The J2EE application directly manages connections, instead of using the container's connection management facilities.

### Extended Description

The J2EE standard forbids the direct management of connections. It requires that applications use the container's resource management facilities to obtain connections to resources. Every major web application container provides pooled database connection management as part of its resource management framework. Duplicating this functionality in an application is difficult and error prone, which is part of the reason it is forbidden under the J2EE standard.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		695	Use of Low-Level Functionality	1524

### Weakness Ordinalities

**Primary :**

### Applicable Platforms

**Language :** Java (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Demonstrative Examples

#### Example 1:

In the following example, the class DatabaseConnection opens and manages a connection to a database for a J2EE application. The method openDatabaseConnection opens a connection to the database using a DriverManager to create the Connection object conn to the database specified in the string constant CONNECT\_STRING.

*Example Language: Java*

*(Bad)*

```
public class DatabaseConnection {
    private static final String CONNECT_STRING = "jdbc:mysql://localhost:3306/mysqlpdb";
    private Connection conn = null;
    public DatabaseConnection() {
    }
    public void openDatabaseConnection() {
        try {
            conn = DriverManager.getConnection(CONNECT_STRING);
```

```
    } catch (SQLException ex) {...}
  }
  // Member functions for retrieving database connection and accessing database
  ...
}
```

The use of the DriverManager class to directly manage the connection to the database violates the J2EE restriction against the direct management of connections. The J2EE application should use the web application container's resource management facilities to obtain a connection to the database as shown in the following example.

Example Language:

(Good)

```
public class DatabaseConnection {
    private static final String DB_DATASRC_REF = "jdbc:mysql://localhost:3306/mysqlpdb";
    private Connection conn = null;
    public DatabaseConnection() {
    }
    public void openDatabaseConnection() {
        try {
            InitialContext ctx = new InitialContext();
            DataSource datasource = (DataSource) ctx.lookup(DB_DATASRC_REF);
            conn = datasource.getConnection();
        } catch (NamingException ex) {...}
        } catch (SQLException ex) {...}
    }
    // Member functions for retrieving database connection and accessing database
    ...
}
```

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	2313
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	2420
MemberOf	C	1412	Comprehensive Categorization: Poor Coding Practices	1400	2538

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Bad Practices: getConnection()
Software Fault Patterns	SFP3		Use of an improper API

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

## CWE-246: J2EE Bad Practices: Direct Use of Sockets

Weakness ID : 246

Structure : Simple

Abstraction : Variant

### Description

The J2EE application directly uses sockets instead of using framework method calls.

### Extended Description

The J2EE standard permits the use of sockets only for the purpose of communication with legacy systems when no higher-level protocol is available. Authoring your own communication protocol requires wrestling with difficult security issues.

Without significant scrutiny by a security expert, chances are good that a custom communication protocol will suffer from security problems. Many of the same issues apply to a custom implementation of a standard protocol. While there are usually more resources available that address security concerns related to implementing a standard protocol, these resources are also available to attackers.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		695	Use of Low-Level Functionality	1524

### Weakness Ordinalities

**Resultant :**

### Applicable Platforms

**Language :** Java (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

#### Phase: Architecture and Design

Use framework method calls instead of using sockets directly.

### Demonstrative Examples

#### Example 1:

The following example opens a socket to connect to a remote server.

*Example Language: Java*

*(Bad)*

```
public void doGet(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    // Perform servlet tasks.
```

```
...
// Open a socket to a remote server (bad).
Socket sock = null;
try {
    sock = new Socket(remoteHostname, 3000);
    // Do something with the socket.
    ...
} catch (Exception e) {
    ...
}
}
```

A Socket object is created directly within the Java servlet, which is a dangerous way to manage remote connections.

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Catgeories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	2313
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	2420
MemberOf	C	1412	Comprehensive Categorization: Poor Coding Practices	1400	2538

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Bad Practices: Sockets
Software Fault Patterns	SFP3		Use of an improper API

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

## CWE-248: Uncaught Exception

**Weakness ID :** 248

**Structure :** Simple

**Abstraction :** Base

### Description

An exception is thrown from a function, but it is not caught.

### Extended Description

When an exception is not caught, it may cause the program to crash or expose sensitive information.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*



Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1576
ChildOf		705	Incorrect Control Flow Scoping	1542
ParentOf		600	Uncaught Exception in Servlet	1343

*Relevant to the view "CISQ Quality Measures (2020)" (CWE-1305)*

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1535

*Relevant to the view "CISQ Data Protection Measures" (CWE-1340)*

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1535

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	2322

### Applicable Platforms

**Language** : C++ (Prevalence = Undetermined)

**Language** : Java (Prevalence = Undetermined)

**Language** : C# (Prevalence = Undetermined)

### Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	
Confidentiality	Read Application Data	
	<i>An uncaught exception could cause the system to be placed in a state that could lead to a crash, exposure of sensitive information or other unintended behaviors.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Demonstrative Examples

#### Example 1:

The following example attempts to resolve a hostname.

*Example Language: Java*

*(Bad)*

```
protected void doPost (HttpServletRequest req, HttpServletResponse res) throws IOException {
    String ip = req.getRemoteAddr();
    InetAddress addr = InetAddress.getByName(ip);
    ...
    out.println("hello " + addr.getHostName());
}
```

A DNS lookup failure will cause the Servlet to throw an exception.

### Example 2:

The `_alloca()` function allocates memory on the stack. If an allocation request is too large for the available stack space, `_alloca()` throws an exception. If the exception is not caught, the program will crash, potentially enabling a denial of service attack. `_alloca()` has been deprecated as of Microsoft Visual Studio 2005(R). It has been replaced with the more secure `_alloca_s()`.

### Example 3:

`EnterCriticalSection()` can raise an exception, potentially causing the program to crash. Under operating systems prior to Windows 2000, the `EnterCriticalSection()` function can raise an exception in low memory situations. If the exception is not caught, the program will crash, potentially enabling a denial of service attack.

### Observed Examples

Reference	Description
<b>CVE-2023-41151</b>	SDK for OPC Unified Architecture (OPC UA) server has uncaught exception when a socket is blocked for writing but the server tries to send an error <a href="https://www.cve.org/CVERecord?id=CVE-2023-41151">https://www.cve.org/CVERecord?id=CVE-2023-41151</a>
<b>CVE-2023-21087</b>	Java code in a smartphone OS can encounter a "boot loop" due to an uncaught exception <a href="https://www.cve.org/CVERecord?id=CVE-2023-21087">https://www.cve.org/CVERecord?id=CVE-2023-21087</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	2313
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	2339
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	2365
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	2400
MemberOf	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	2448
MemberOf	C	1181	SEI CERT Perl Coding Standard - Guidelines 03. Expressions (EXP)	1178	2466
MemberOf	C	1410	Comprehensive Categorization: Insufficient Control Flow Management	1400	2536

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Often Misused: Exception Handling
The CERT Oracle Secure Coding Standard for Java (2011)	ERR05-J		Do not let checked exceptions escape from a finally block
The CERT Oracle Secure Coding Standard for Java (2011)	ERR06-J		Do not throw undeclared checked exceptions
SEI CERT Perl Coding Standard	EXP31-PL	Exact	Do not suppress or ignore exceptions
Software Fault Patterns	SFP4		Unchecked Status Condition

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

## CWE-250: Execution with Unnecessary Privileges

**Weakness ID** : 250

**Structure** : Simple

**Abstraction** : Base

### Description

The product performs an operation at a privilege level that is higher than the minimum level required, which creates new weaknesses or amplifies the consequences of other weaknesses.

### Extended Description

New weaknesses can be exposed because running with extra privileges, such as root or Administrator, can disable the normal security checks being performed by the operating system or surrounding environment. Other pre-existing weaknesses can turn into security vulnerabilities if they occur while operating at raised privileges.

Privilege management functions can behave in some less-than-obvious ways, and they have different quirks on different platforms. These inconsistencies are particularly pronounced if you are transitioning from one non-root user to another. Signal handlers and spawned processes run at the privilege of the owning process, so if a process is running as root when a signal fires or a sub-process is executed, the signal handler or sub-process will operate with root privileges.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		657	Violation of Secure Design Principles	1446
ChildOf		269	Improper Privilege Management	646

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	2430

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : Mobile (*Prevalence = Undetermined*)

### Likelihood Of Exploit

Medium

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Gain Privileges or Assume Identity	
Integrity	Execute Unauthorized Code or Commands	
Availability	Read Application Data	
Access Control	DoS: Crash, Exit, or Restart	
<p><i>An attacker will be able to gain access to any resources that are allowed by the extra privileges. Common results include executing code, disabling services, and reading restricted data.</i></p>		

## Detection Methods

### Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

### Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and perform a login. Look for library functions and system calls that indicate when privileges are being raised or dropped. Look for accesses of resources that are restricted to normal users.

### Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Compare binary / bytecode to application permission manifest Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

*Effectiveness = High*

### Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host-based Vulnerability Scanners - Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host Application Interface Scanner

*Effectiveness = SOAR Partial*

### Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

*Effectiveness = High*

### **Automated Static Analysis - Source Code**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

*Effectiveness = SOAR Partial*

### **Automated Static Analysis**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker Permission Manifest Analysis

*Effectiveness = SOAR Partial*

### **Architecture or Design Review**

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

*Effectiveness = High*

## **Potential Mitigations**

### **Phase: Architecture and Design**

#### **Phase: Operation**

*Strategy = Environment Hardening*

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

#### **Phase: Architecture and Design**

*Strategy = Separation of Privilege*

Identify the functionality that requires additional privileges, such as access to privileged operating system resources. Wrap and centralize this functionality if possible, and isolate the privileged code as much as possible from other code [REF-76]. Raise privileges as late as possible, and drop them as soon as possible to avoid CWE-271. Avoid weaknesses such as CWE-288 and CWE-420 by protecting all possible communication channels that could interact with the privileged code, such as a secondary socket that is only intended to be accessed by administrators.

#### **Phase: Architecture and Design**

*Strategy = Attack Surface Reduction*

Identify the functionality that requires additional privileges, such as access to privileged operating system resources. Wrap and centralize this functionality if possible, and isolate the privileged code as much as possible from other code [REF-76]. Raise privileges as late as possible, and drop them as soon as possible to avoid CWE-271. Avoid weaknesses such as CWE-288 and CWE-420 by protecting all possible communication channels that could interact with the privileged code, such as a secondary socket that is only intended to be accessed by administrators.

#### **Phase: Implementation**

Perform extensive input validation for any privileged code that must be exposed to the user and reject anything that does not fit your strict requirements.

#### Phase: Implementation

When dropping privileges, ensure that they have been dropped successfully to avoid CWE-273. As protection mechanisms in the environment get stronger, privilege-dropping calls may fail even if it seems like they would always succeed.

#### Phase: Implementation

If circumstances force you to run with extra privileges, then determine the minimum access level necessary. First identify the different permissions that the software and its users will need to perform their actions, such as file read and write permissions, network socket permissions, and so forth. Then explicitly allow those actions while denying all else [REF-76]. Perform extensive input validation and canonicalization to minimize the chances of introducing a separate vulnerability. This mitigation is much more prone to error than dropping the privileges in the first place.

#### Phase: Operation

#### Phase: System Configuration

*Strategy = Environment Hardening*

Ensure that the software runs properly under the United States Government Configuration Baseline (USGCB) [REF-199] or an equivalent hardening configuration guide, which many organizations use to limit the attack surface and potential risk of deployed software.

### Demonstrative Examples

#### Example 1:

This code temporarily raises the program's privileges to allow creation of a new user folder.

*Example Language: Python*

*(Bad)*

```
def makeNewUserDir(username):
    if invalidUsername(username):
        #avoid CWE-22 and CWE-78
        print('Usernames cannot contain invalid characters')
        return False
    try:
        raisePrivileges()
        os.mkdir('/home/' + username)
        lowerPrivileges()
    except OSError:
        print('Unable to create new user directory for user:' + username)
        return False
    return True
```

While the program only raises its privilege level to create the folder and immediately lowers it again, if the call to `os.mkdir()` throws an exception, the call to `lowerPrivileges()` will not occur. As a result, the program is indefinitely operating in a raised privilege state, possibly allowing further exploitation to occur.

#### Example 2:

The following code calls `chroot()` to restrict the application to a subset of the filesystem below `APP_HOME` in order to prevent an attacker from using the program to gain unauthorized access to files located elsewhere. The code then opens a file specified by the user and processes the contents of the file.

*Example Language: C*

*(Bad)*

```
chroot(APP_HOME);
chdir("/");
```

```
FILE* data = fopen(argv[1], "r+");
...
```

Constraining the process inside the application's home directory before opening any files is a valuable security measure. However, the absence of a call to `setuid()` with some non-zero value means the application is continuing to operate with unnecessary root privileges. Any successful exploit carried out by an attacker against the application can now result in a privilege escalation attack because any malicious operations will be performed with the privileges of the superuser. If the application drops to the privilege level of a non-root user, the potential for damage is substantially reduced.

### Example 3:

This application intends to use a user's location to determine the timezone the user is in:

*Example Language: Java*

*(Bad)*

```
locationClient = new LocationClient(this, this, this);
locationClient.connect();
Location userCurrLocation;
userCurrLocation = locationClient.getLastLocation();
setTimeZone(userCurrLocation);
```

This is unnecessary use of the location API, as this information is already available using the Android Time API. Always be sure there is not another way to obtain needed information before resorting to using the location API.

### Example 4:

This code uses location to determine the user's current US State location.

First the application must declare that it requires the `ACCESS_FINE_LOCATION` permission in the application's manifest.xml:

*Example Language: XML*

*(Bad)*

```
<uses-permission android:name="android.permission.ACCESS_FINE_LOCATION"/>
```

During execution, a call to `getLastLocation()` will return a location based on the application's location permissions. In this case the application has permission for the most accurate location possible:

*Example Language: Java*

*(Bad)*

```
locationClient = new LocationClient(this, this, this);
locationClient.connect();
Location userCurrLocation;
userCurrLocation = locationClient.getLastLocation();
deriveStateFromCoords(userCurrLocation);
```

While the application needs this information, it does not need to use the `ACCESS_FINE_LOCATION` permission, as the `ACCESS_COARSE_LOCATION` permission will be sufficient to identify which US state the user is in.

## Observed Examples









Reference	Description
<b>CVE-2007-4217</b>	FTP client program on a certain OS runs with <code>setuid</code> privileges and has a buffer overflow. Most clients do not need extra privileges, so an overflow is not a vulnerability for those clients. <a href="https://www.cve.org/CVERecord?id=CVE-2007-4217">https://www.cve.org/CVERecord?id=CVE-2007-4217</a>



Reference	Description
<b>CVE-2008-1877</b>	Program runs with privileges and calls another program with the same privileges, which allows read of arbitrary files. <a href="https://www.cve.org/CVERecord?id=CVE-2008-1877">https://www.cve.org/CVERecord?id=CVE-2008-1877</a>
<b>CVE-2007-5159</b>	OS incorrectly installs a program with setuid privileges, allowing users to gain privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2007-5159">https://www.cve.org/CVERecord?id=CVE-2007-5159</a>
<b>CVE-2008-4638</b>	Composite: application running with high privileges (CWE-250) allows user to specify a restricted file to process, which generates a parsing error that leaks the contents of the file (CWE-209). <a href="https://www.cve.org/CVERecord?id=CVE-2008-4638">https://www.cve.org/CVERecord?id=CVE-2008-4638</a>
<b>CVE-2008-0162</b>	Program does not drop privileges before calling another program, allowing code execution. <a href="https://www.cve.org/CVERecord?id=CVE-2008-0162">https://www.cve.org/CVERecord?id=CVE-2008-0162</a>
<b>CVE-2008-0368</b>	setuid root program allows creation of arbitrary files through command line argument. <a href="https://www.cve.org/CVERecord?id=CVE-2008-0368">https://www.cve.org/CVERecord?id=CVE-2008-0368</a>
<b>CVE-2007-3931</b>	Installation script installs some programs as setuid when they shouldn't be. <a href="https://www.cve.org/CVERecord?id=CVE-2007-3931">https://www.cve.org/CVERecord?id=CVE-2007-3931</a>
<b>CVE-2020-3812</b>	mail program runs as root but does not drop its privileges before attempting to access a file. Attacker can use a symlink from their home directory to a directory only readable by root, then determine whether the file exists based on the response. <a href="https://www.cve.org/CVERecord?id=CVE-2020-3812">https://www.cve.org/CVERecord?id=CVE-2020-3812</a>
<b>CVE-2003-0908</b>	Product launches Help functionality while running with raised privileges, allowing command execution using Windows message to access "open file" dialog. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0908">https://www.cve.org/CVERecord?id=CVE-2003-0908</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		227	7PK - API Abuse	700	2313
MemberOf		753	2009 Top 25 - Porous Defenses	750	2353
MemberOf		815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	2358
MemberOf		858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	2368
MemberOf		866	2011 Top 25 - Porous Defenses	900	2372
MemberOf		884	CWE Cross-section	884	2567
MemberOf		901	SFP Primary Cluster: Privilege	888	2386
MemberOf		1418	Comprehensive Categorization: Violation of Secure Design Principles	1400	2549

### Notes

#### Relationship

There is a close association with CWE-653 (Insufficient Separation of Privileges). CWE-653 is about providing separate components for each privilege; CWE-250 is about ensuring that each component has the least amount of privileges possible.

#### Maintenance

CWE-271, CWE-272, and CWE-250 are all closely related and possibly overlapping. CWE-271 is probably better suited as a category. Both CWE-272 and CWE-250 are in active use by the community. The "least privilege" phrase has multiple interpretations.

### Maintenance

The Taxonomy\_Mappings to ISA/IEC 62443 were added in CWE 4.10, but they are still under review and might change in future CWE versions. These draft mappings were performed by members of the "Mapping CWE to 62443" subgroup of the CWE-CAPEC ICS/OT Special Interest Group (SIG), and their work is incomplete as of CWE 4.10. The mappings are included to facilitate discussion and review by the broader ICS/OT community, and they are likely to change in future CWE versions.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms The CERT Oracle Secure Coding Standard for Java (2011)	SER09-J		Often Misused: Privilege Management Minimize privileges before deserializing from a privilege context
ISA/IEC 62443	Part 2-4		Req SP.03.05 BR
ISA/IEC 62443	Part 2-4		Req SP.03.08 BR
ISA/IEC 62443	Part 2-4		Req SP.03.08 RE(1)
ISA/IEC 62443	Part 2-4		Req SP.05.07 BR
ISA/IEC 62443	Part 2-4		Req SP.09.02 RE(4)
ISA/IEC 62443	Part 2-4		Req SP.09.03 BR
ISA/IEC 62443	Part 2-4		Req SP.09.04 BR
ISA/IEC 62443	Part 3-3		Req SR 1.1
ISA/IEC 62443	Part 3-3		Req SR 1.2
ISA/IEC 62443	Part 3-3		Req SR 2.1
ISA/IEC 62443	Part 3-3		Req SR 2.1 RE 1
ISA/IEC 62443	Part 4-1		Req SD-4
ISA/IEC 62443	Part 4-2		Req CCSC 3
ISA/IEC 62443	Part 4-2		Req CR 1.1

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
69	Target Programs with Elevated Privileges
104	Cross Zone Scripting
470	Expanding Control over the Operating System from the Database

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://web.archive.org/web/20211209014121/https://www.cisa.gov/uscert/bsi/articles/knowledge/principles/least-privilege> >.2023-04-07.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-199]NIST. "United States Government Configuration Baseline (USGCB)". < <https://csrc.nist.gov/Projects/United-States-Government-Configuration-Baseline> >.2023-03-28.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

## CWE-252: Unchecked Return Value

**Weakness ID** : 252

**Structure** : Simple

**Abstraction** : Base

### Description

The product does not check the return value from a method or function, which can prevent it from detecting unexpected states and conditions.





### Extended Description

Two common programmer assumptions are "this function call can never fail" and "it doesn't matter if this function call fails". If an attacker can force the function to fail or otherwise return a value that is not expected, then the subsequent program logic could lead to a vulnerability, because the product is not in a state that the programmer assumes. For example, if the program calls a function to drop privileges but does not check the return code to ensure that privileges were successfully dropped, then the program will continue to operate with the higher privileges.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1568
ParentOf		690	Unchecked Return Value to NULL Pointer Dereference	1514
PeerOf		273	Improper Check for Dropped Privileges	660
CanPrecede		476	NULL Pointer Dereference	1132

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1568

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	2322

### Weakness Ordinalities

**Primary** :

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Background Details

Many functions will return some value about the success of their actions. This will alert the program whether or not to handle any errors caused by that function.

### Likelihood Of Exploit

Low

### Common Consequences

Scope	Impact	Likelihood
Availability Integrity	Unexpected State DoS: Crash, Exit, or Restart  <i>An unexpected return value could place the system in a state that could lead to a crash or other unintended behaviors.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

#### Phase: Implementation

Check the results of all functions that return a value and verify that the value is expected.

*Effectiveness = High*

*Checking the return value of the function will typically be sufficient, however beware of race conditions (CWE-362) in a concurrent environment.*

#### Phase: Implementation

Ensure that you account for all possible return values from the function.

#### Phase: Implementation

When designing a function, make sure you return a value or throw an exception in case of an error.

### Demonstrative Examples

#### Example 1:

Consider the following code segment:

*Example Language: C*

*(Bad)*

```
char buf[10], cp_buf[10];
fgets(buf, 10, stdin);
strcpy(cp_buf, buf);
```

The programmer expects that when `fgets()` returns, `buf` will contain a null-terminated string of length 9 or less. But if an I/O error occurs, `fgets()` will not null-terminate `buf`. Furthermore, if the end of the file is reached before any characters are read, `fgets()` returns without writing anything to `buf`. In both of these situations, `fgets()` signals that something unusual has happened by returning `NULL`, but in this code, the warning will not be noticed. The lack of a null terminator in `buf` can result in a buffer overflow in the subsequent call to `strcpy()`.

### Example 2:

In the following example, it is possible to request that memcpy move a much larger segment of memory than assumed:

Example Language: C

(Bad)

```
int returnChunkSize(void *) {
    /* if chunk info is valid, return the size of usable memory,
     * else, return -1 to indicate an error
     */
    ...
}
int main() {
    ...
    memcpy(destBuf, srcBuf, (returnChunkSize(destBuf)-1));
    ...
}
```

If returnChunkSize() happens to encounter an error it will return -1. Notice that the return value is not checked before the memcpy operation (CWE-252), so -1 can be passed as the size argument to memcpy() (CWE-805). Because memcpy() assumes that the value is unsigned, it will be interpreted as MAXINT-1 (CWE-195), and therefore will copy far more memory than is likely available to the destination buffer (CWE-787, CWE-788).

### Example 3:

The following code does not check to see if memory allocation succeeded before attempting to use the pointer returned by malloc().

Example Language: C

(Bad)

```
buf = (char*) malloc(req_size);
strncpy(buf, xfer, req_size);
```

The traditional defense of this coding error is: "If my program runs out of memory, it will fail. It doesn't matter whether I handle the error or allow the program to die with a segmentation fault when it tries to dereference the null pointer." This argument ignores three important considerations:

- Depending upon the type and size of the application, it may be possible to free memory that is being used elsewhere so that execution can continue.
- It is impossible for the program to perform a graceful exit if required. If the program is performing an atomic operation, it can leave the system in an inconsistent state.
- The programmer has lost the opportunity to record diagnostic information. Did the call to malloc() fail because req\_size was too large or because there were too many requests being handled at the same time? Or was it caused by a memory leak that has built up over time? Without handling the error, there is no way to know.

### Example 4:

The following examples read a file into a byte array.

Example Language: C#

(Bad)

```
char[] byteArray = new char[1024];
for (IEnumerator i=users.GetEnumerator(); i.MoveNext(); i.Current()) {
    String userName = (String) i.Current();
    String pFileName = PFILE_ROOT + "/" + userName;
    StreamReader sr = new StreamReader(pFileName);
    sr.Read(byteArray,0,1024);//the file is always 1k bytes
    sr.Close();
    processPFile(userName, byteArray);
}
```

*Example Language: Java**(Bad)*

```
FileInputStream fis;
byte[] byteArray = new byte[1024];
for (Iterator i=users.iterator(); i.hasNext();) {
    String userName = (String) i.next();
    String pFileName = PFILE_ROOT + "/" + userName;
    FileInputStream fis = new FileInputStream(pFileName);
    fis.read(byteArray); // the file is always 1k bytes
    fis.close();
    processPFile(userName, byteArray);
}
```

The code loops through a set of users, reading a private data file for each user. The programmer assumes that the files are always 1 kilobyte in size and therefore ignores the return value from `Read()`. If an attacker can create a smaller file, the program will recycle the remainder of the data from the previous user and treat it as though it belongs to the attacker.

**Example 5:**

The following code does not check to see if the string returned by `getParameter()` is null before calling the member function `compareTo()`, potentially causing a NULL dereference.

*Example Language: Java**(Bad)*

```
String itemName = request.getParameter(ITEM_NAME);
if (itemName.compareTo(IMPORTANT_ITEM) == 0) {
    ...
}
...
```

The following code does not check to see if the string returned by the `Item` property is null before calling the member function `Equals()`, potentially causing a NULL dereference.

*Example Language: Java**(Bad)*

```
String itemName = request.Item(ITEM_NAME);
if (itemName.Equals(IMPORTANT_ITEM)) {
    ...
}
...
```

The traditional defense of this coding error is: "I know the requested value will always exist because.... If it does not exist, the program cannot perform the desired behavior so it doesn't matter whether I handle the error or allow the program to die dereferencing a null value." But attackers are skilled at finding unexpected paths through programs, particularly when exceptions are involved.

**Example 6:**

The following code shows a system property that is set to null and later dereferenced by a programmer who mistakenly assumes it will always be defined.

*Example Language: Java**(Bad)*

```
System.clearProperty("os.name");
...
String os = System.getProperty("os.name");
if (os.equalsIgnoreCase("Windows 95")) System.out.println("Not supported");
```

The traditional defense of this coding error is: "I know the requested value will always exist because.... If it does not exist, the program cannot perform the desired behavior so it doesn't matter whether I handle the error or allow the program to die dereferencing a null value." But attackers are skilled at finding unexpected paths through programs, particularly when exceptions are involved.

**Example 7:**

The following VB.NET code does not check to make sure that it has read 50 bytes from myfile.txt. This can cause DoDangerousOperation() to operate on an unexpected value.

Example Language: C#

(Bad)

```
Dim MyFile As New FileStream("myfile.txt", FileMode.Open, FileAccess.Read, FileShare.Read)
Dim MyArray(50) As Byte
MyFile.Read(MyArray, 0, 50)
DoDangerousOperation(MyArray(20))
```

In .NET, it is not uncommon for programmers to misunderstand Read() and related methods that are part of many System.IO classes. The stream and reader classes do not consider it to be unusual or exceptional if only a small amount of data becomes available. These classes simply add the small amount of data to the return buffer, and set the return value to the number of bytes or characters read. There is no guarantee that the amount of data returned is equal to the amount of data requested.

#### Example 8:

It is not uncommon for Java programmers to misunderstand read() and related methods that are part of many java.io classes. Most errors and unusual events in Java result in an exception being thrown. But the stream and reader classes do not consider it unusual or exceptional if only a small amount of data becomes available. These classes simply add the small amount of data to the return buffer, and set the return value to the number of bytes or characters read. There is no guarantee that the amount of data returned is equal to the amount of data requested. This behavior makes it important for programmers to examine the return value from read() and other IO methods to ensure that they receive the amount of data they expect.

#### Example 9:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(Bad)

```
void host_lookup(char *user_supplied_addr){
    struct hostent *hp;
    in_addr_t *addr;
    char hostname[64];
    in_addr_t inet_addr(const char *cp);
    /*routine that ensures user_supplied_addr is in the right format for conversion */
    validate_addr_form(user_supplied_addr);
    addr = inet_addr(user_supplied_addr);
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);
    strcpy(hostname, hp->h_name);
}
```

If an attacker provides an address that appears to be well-formed, but the address does not resolve to a hostname, then the call to gethostbyaddr() will return NULL. Since the code does not check the return value from gethostbyaddr (CWE-252), a NULL pointer dereference (CWE-476) would then occur in the call to strcpy().

Note that this code is also vulnerable to a buffer overflow (CWE-119).

#### Example 10:

The following function attempts to acquire a lock in order to perform operations on a shared resource.

Example Language: C

(Bad)

```
void f(pthread_mutex_t *mutex) {
    pthread_mutex_lock(mutex);
    /* access shared resource */
}
```



```
pthread_mutex_unlock(mutex);
}
```

However, the code does not check the value returned by `pthread_mutex_lock()` for errors. If `pthread_mutex_lock()` cannot acquire the mutex for any reason, the function may introduce a race condition into the program and result in undefined behavior.

In order to avoid data races, correctly written programs must check the result of thread synchronization functions and appropriately handle all errors, either by attempting to recover from them or reporting them to higher levels.

Example Language: C

(Good)

```
int f(pthread_mutex_t *mutex) {
    int result;
    result = pthread_mutex_lock(mutex);
    if (0 != result)
        return result;
    /* access shared resource */
    return pthread_mutex_unlock(mutex);
}
```

## Observed Examples

Reference	Description
<b>CVE-2020-17533</b>	Chain: unchecked return value (CWE-252) of some functions for policy enforcement leads to authorization bypass (CWE-862) <a href="https://www.cve.org/CVERecord?id=CVE-2020-17533">https://www.cve.org/CVERecord?id=CVE-2020-17533</a>
<b>CVE-2020-6078</b>	Chain: The return value of a function returning a pointer is not checked for success (CWE-252) resulting in the later use of an uninitialized variable (CWE-456) and a null pointer dereference (CWE-476) <a href="https://www.cve.org/CVERecord?id=CVE-2020-6078">https://www.cve.org/CVERecord?id=CVE-2020-6078</a>
<b>CVE-2019-15900</b>	Chain: <code>sscanf()</code> call is used to check if a username and group exists, but the return value of <code>sscanf()</code> call is not checked (CWE-252), causing an uninitialized variable to be checked (CWE-457), returning success to allow authorization bypass for executing a privileged (CWE-863). <a href="https://www.cve.org/CVERecord?id=CVE-2019-15900">https://www.cve.org/CVERecord?id=CVE-2019-15900</a>
<b>CVE-2007-3798</b>	Unchecked return value leads to resultant integer overflow and code execution. <a href="https://www.cve.org/CVERecord?id=CVE-2007-3798">https://www.cve.org/CVERecord?id=CVE-2007-3798</a>
<b>CVE-2006-4447</b>	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. <a href="https://www.cve.org/CVERecord?id=CVE-2006-4447">https://www.cve.org/CVERecord?id=CVE-2006-4447</a>
<b>CVE-2006-2916</b>	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. <a href="https://www.cve.org/CVERecord?id=CVE-2006-2916">https://www.cve.org/CVERecord?id=CVE-2006-2916</a>
<b>CVE-2008-5183</b>	chain: unchecked return value can lead to NULL dereference <a href="https://www.cve.org/CVERecord?id=CVE-2008-5183">https://www.cve.org/CVERecord?id=CVE-2008-5183</a>
<b>CVE-2010-0211</b>	chain: unchecked return value (CWE-252) leads to free of invalid, uninitialized pointer (CWE-824). <a href="https://www.cve.org/CVERecord?id=CVE-2010-0211">https://www.cve.org/CVERecord?id=CVE-2010-0211</a>
<b>CVE-2017-6964</b>	Linux-based device mapper encryption program does not check the return value of <code>setuid</code> and <code>setgid</code> allowing attackers to execute code with unintended privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2017-6964">https://www.cve.org/CVERecord?id=CVE-2017-6964</a>

Reference	Description
<b>CVE-2002-1372</b>	Chain: Return values of file/socket operations are not checked (CWE-252), allowing resultant consumption of file descriptors (CWE-772). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1372">https://www.cve.org/CVERecord?id=CVE-2002-1372</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	2313
MemberOf	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	2337
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	2345
MemberOf	C	847	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP)	844	2363
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	2376
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	2400
MemberOf	C	1129	CISQ Quality Measures (2016) - Reliability	1128	2440
MemberOf	C	1131	CISQ Quality Measures (2016) - Security	1128	2442
MemberOf	C	1136	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP)	1133	2445
MemberOf	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1154	2461
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	2463
MemberOf	C	1181	SEI CERT Perl Coding Standard - Guidelines 03. Expressions (EXP)	1178	2466
MemberOf	C	1306	CISQ Quality Measures - Reliability	1305	2483
MemberOf	C	1308	CISQ Quality Measures - Security	1305	2485
MemberOf	C	1405	Comprehensive Categorization: Improper Check or Handling of Exceptional Conditions	1400	2531

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Unchecked Return Value
CLASP			Ignored function return value
OWASP Top Ten 2004	A7	CWE More Specific	Improper Error Handling
CERT C Secure Coding	ERR33-C	Imprecise	Detect and handle standard library errors
CERT C Secure Coding	POS54-C	Imprecise	Detect and handle POSIX library errors
The CERT Oracle Secure Coding Standard for Java (2011)	EXP00-J		Do not ignore values returned by methods
SEI CERT Perl Coding Standard	EXP32-PL	Exact	Do not ignore function return values
Software Fault Patterns	SFP4		Unchecked Status Condition

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCSM	ASCSM-CWE-252-resource		
OMG ASCRM	ASCRM-CWE-252-data		
OMG ASCRM	ASCRM-CWE-252-resource		

## References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

## CWE-253: Incorrect Check of Function Return Value

**Weakness ID** : 253

**Structure** : Simple

**Abstraction** : Base

### Description

The product incorrectly checks a return value from a function, which prevents it from detecting errors or exceptional conditions.


### Extended Description

Important and common functions will return some value about the success of its actions. This will alert the program whether or not to handle any errors caused by that function.


### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1568
ChildOf		573	Improper Following of Specification by Caller	1298

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	2322

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

Low

## Common Consequences

Scope	Impact	Likelihood
Availability	Unexpected State	
Integrity	DoS: Crash, Exit, or Restart	
	<i>An unexpected return value could place the system in a state that could lead to a crash or other unintended behaviors.</i>	

## Potential Mitigations

### Phase: Architecture and Design

*Strategy = Language Selection*

Use a language or compiler that uses exceptions and requires the catching of those exceptions.

### Phase: Implementation

Properly check all functions which return a value.

### Phase: Implementation

When designing any function make sure you return a value or throw an exception in case of an error.

## Demonstrative Examples

### Example 1:

This code attempts to allocate memory for 4 integers and checks if the allocation succeeds.

*Example Language: C*

*(Bad)*

```
tmp = malloc(sizeof(int) * 4);
if (tmp < 0 ) {
    perror("Failure");
    //should have checked if the call returned 0
}
```

The code assumes that only a negative return value would indicate an error, but malloc() may return a null pointer when there is an error. The value of tmp could then be equal to 0, and the error would be missed.

## Observed Examples

Reference	Description
<b>CVE-2023-49286</b>	Chain: function in web caching proxy does not correctly check a return value (CWE-253) leading to a reachable assertion (CWE-617) <a href="https://www.cve.org/CVERecord?id=CVE-2023-49286">https://www.cve.org/CVERecord?id=CVE-2023-49286</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	2400
MemberOf	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1154	2461
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	2463
MemberOf	C	1412	Comprehensive Categorization: Poor Coding Practices	1400	2538

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Misinterpreted function return value
Software Fault Patterns	SFP4		Unchecked Status Condition
CERT C Secure Coding	ERR33-C	Imprecise	Detect and handle standard library errors
CERT C Secure Coding	POS54-C	Imprecise	Detect and handle POSIX library errors

## References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-256: Plaintext Storage of a Password

**Weakness ID** : 256

**Structure** : Simple

**Abstraction** : Base

## Description

Storing a password in plaintext may result in a system compromise.

## Extended Description

Password management issues occur when a password is stored in plaintext in an application's properties, configuration file, or memory. Storing a plaintext password in a configuration file allows anyone who can read the file access to the password-protected resource. In some contexts, even storage of a plaintext password in memory is considered a security risk if the password is not cleared immediately after it is used.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	C	522	Insufficiently Protected Credentials	1225

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management Errors	2315

## Weakness Ordinalities

**Primary :**

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

**Technology :** ICS/OT (*Prevalence = Undetermined*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

Avoid storing passwords in easily accessible locations.

### Phase: Architecture and Design

Consider storing cryptographic hashes of passwords as an alternative to storing in plaintext.

A programmer might attempt to remedy the password management problem by obscuring the password with an encoding function, such as base 64 encoding, but this effort does not adequately protect the password because the encoding can be detected and decoded easily.

*Effectiveness = None*

## Demonstrative Examples

### Example 1:

The following code reads a password from a properties file and uses the password to connect to a database.

*Example Language: Java*

*(Bad)*

```
...
Properties prop = new Properties();
prop.load(new FileInputStream("config.properties"));
String password = prop.getProperty("password");
```

```
DriverManager.getConnection(url, usr, password);  
...
```

This code will run successfully, but anyone who has access to config.properties can read the value of password. If a devious employee has access to this information, they can use it to break into the system.

**Example 2:**

The following code reads a password from the registry and uses the password to create a new network credential.

*Example Language: Java*

*(Bad)*

```
...  
String password = regKey.GetValue(passKey).toString();  
NetworkCredential netCred = new NetworkCredential(username,password,domain);  
...
```

This code will run successfully, but anyone who has access to the registry key used to store the password can read the value of password. If a devious employee has access to this information, they can use it to break into the system

**Example 3:**

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in cleartext.

This Java example shows a properties file with a cleartext username / password pair.

*Example Language: Java*

*(Bad)*

```
# Java Web App ResourceBundle properties file  
...  
webapp ldap.username=secretUsername  
webapp ldap.password=secretPassword  
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in cleartext.

*Example Language: ASP.NET*

*(Bad)*

```
...  
<connectionStrings>  
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"  
    providerName="System.Data.Odbc" />  
</connectionStrings>  
...
```

Username and password information should not be included in a configuration file or a properties file in cleartext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information.

**Example 4:**

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.



At least one OT product stored a password in plaintext.

### Observed Examples

Reference	Description
<b>CVE-2022-30275</b>	Remote Terminal Unit (RTU) uses a driver that relies on a password stored in plaintext. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30275">https://www.cve.org/CVERecord?id=CVE-2022-30275</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		254	7PK - Security Features	700	2314
MemberOf		930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	2389
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	2436
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management
Software Fault Patterns	SFP23		Exposed Data
ISA/IEC 62443	Part 4-2		Req CR 1.5
ISA/IEC 62443	Part 3-3		Req SR 1.5

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

[REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.

## CWE-257: Storing Passwords in a Recoverable Format

**Weakness ID** : 257

**Structure** : Simple

**Abstraction** : Base

### Description

The storage of passwords in a recoverable format makes them subject to password reuse attacks by malicious users. In fact, it should be noted that recoverable encrypted passwords provide no significant benefit over plaintext passwords since they are subject not only to reuse by malicious attackers but also by malicious insiders. If a system administrator can recover a password directly,

or use a brute force search on the available information, the administrator can use the password on other accounts.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		522	Insufficiently Protected Credentials	1225
PeerOf		259	Use of Hard-coded Password	623
PeerOf		259	Use of Hard-coded Password	623
PeerOf		798	Use of Hard-coded Credentials	1690

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management Errors	2315

## Weakness Ordinalities

**Primary :**

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Gain Privileges or Assume Identity	
Access Control	<i>User's passwords may be revealed.</i>	
Access Control	Gain Privileges or Assume Identity	
	<i>Revealed passwords may be reused elsewhere to impersonate the users in question.</i>	

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

Use strong, non-reversible encryption to protect stored passwords.

## Demonstrative Examples

### Example 1:

Both of these examples verify a password by comparing it to a stored compressed version.

Example Language: C

(Bad)

```
int VerifyAdmin(char *password) {
    if (strcmp(compress(password), compressed_password)) {
        printf("Incorrect Password!\n");
        return(0);
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

Example Language: Java

(Bad)

```
int VerifyAdmin(String password) {
    if (passwd.Equals(compress(password), compressed_password)) {
        return(0);
    }
    //Diagnostic Mode
    return(1);
}
```

Because a compression algorithm is used instead of a one way hashing algorithm, an attacker can recover compressed passwords stored in the database.

### Example 2:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in cleartext.

This Java example shows a properties file with a cleartext username / password pair.

Example Language: Java

(Bad)

```
# Java Web App ResourceBundle properties file
...
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in cleartext.

Example Language: ASP.NET

(Bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in cleartext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information.

## Observed Examples

Reference	Description
<b>CVE-2022-30018</b>	A messaging platform serializes all elements of User/Group objects, making private information available to adversaries <a href="https://www.cve.org/CVERecord?id=CVE-2022-30018">https://www.cve.org/CVERecord?id=CVE-2022-30018</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Maintenance

The meaning of this entry needs to be investigated more closely, especially with respect to what is meant by "recoverable."

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Storing passwords in a recoverable format
Software Fault Patterns	SFP23		Exposed Data

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
49	Password Brute Forcing

### References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-258: Empty Password in Configuration File

**Weakness ID :** 258

**Structure :** Simple

**Abstraction :** Variant

### Description

Using an empty string as a password is insecure.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		521	Weak Password Requirements	1223
ChildOf		260	Password in Configuration File	629

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

## Weakness Ordinalities

**Primary :**

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

## Potential Mitigations

### Phase: System Configuration

Passwords should be at least eight characters long -- the longer the better. Avoid passwords that are in any way similar to other passwords you have. Avoid using words that may be found in a dictionary, names book, on a map, etc. Consider incorporating numbers and/or punctuation into your password. If you do use common words, consider replacing letters in that word with numbers and punctuation. However, do not use "similar-looking" punctuation. For example, it is not a good idea to change cat to c@t, ca+, (@+, or anything similar. Finally, it is never appropriate to use an empty string as a password.

## Demonstrative Examples

### Example 1:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but the password is provided as an empty string.

This Java example shows a properties file with an empty password string.

*Example Language: Java*

*(Bad)*

```
# Java Web App ResourceBundle properties file
...
webapp ldap.username=secretUsername
webapp ldap.password=
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database and the password is provided as an empty string.

*Example Language: ASP.NET*

*(Bad)*

```
...
<connectionStrings>
<add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=; dbalias=uDB;"
providerName="System.Data.Odbc" />
</connectionStrings>
...
```




An empty string should never be used as a password as this can allow unauthorized access to the application. Username and password information should not be included in a configuration file or a properties file in clear text. If possible, encrypt this information and avoid CWE-260 and CWE-13.

### Observed Examples

Reference	Description
<b>CVE-2022-26117</b>	Network access control (NAC) product has a configuration file with an empty password <a href="https://www.cve.org/CVERecord?id=CVE-2022-26117">https://www.cve.org/CVERecord?id=CVE-2022-26117</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		254	7PK - Security Features	700	2314
MemberOf		950	SFP Secondary Cluster: Hardcoded Sensitive Data	888	2396
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management: Empty Password in Configuration File

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

## CWE-259: Use of Hard-coded Password

**Weakness ID** : 259

**Structure** : Simple

**Abstraction** : Variant

### Description

The product contains a hard-coded password, which it uses for its own inbound authentication or for outbound communication to external components.

### Extended Description

A hard-coded password typically leads to a significant authentication failure that can be difficult for the system administrator to detect. Once detected, it can be difficult to fix, so the administrator may be forced into disabling the product entirely. There are two main variations:

Inbound: the product contains an authentication mechanism that checks for a hard-coded password.

Outbound: the product connects to another system or component, and it contains hard-coded password for connecting to that component.






In the Inbound variant, a default administration account is created, and a simple password is hard-coded into the product and associated with that account. This hard-coded password is the same for each installation of the product, and it usually cannot be changed or disabled by system administrators without manually modifying the program, or otherwise patching the product. If the password is ever discovered or published (a common occurrence on the Internet), then anybody with knowledge of this password can access the product. Finally, since all installations of the product will have the same password, even across different organizations, this enables massive attacks such as worms to take place.

The Outbound variant applies to front-end systems that authenticate with a back-end service. The back-end service may require a fixed password which can be easily discovered. The programmer may simply hard-code those back-end credentials into the front-end product. Any user of that program may be able to extract the password. Client-side systems with hard-coded passwords pose even more of a threat, since the extraction of a password from a binary is usually very simple.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		798	Use of Hard-coded Credentials	1690
PeerOf		257	Storing Passwords in a Recoverable Format	618
PeerOf		321	Use of Hard-coded Cryptographic Key	785
PeerOf		257	Storing Passwords in a Recoverable Format	618
CanFollow		656	Reliance on Security Through Obscurity	1444

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "CISQ Quality Measures (2020)" (CWE-1305)*

Nature	Type	ID	Name	Page
ChildOf		798	Use of Hard-coded Credentials	1690

*Relevant to the view "CISQ Data Protection Measures" (CWE-1340)*

Nature	Type	ID	Name	Page
ChildOf		798	Use of Hard-coded Credentials	1690

## Weakness Ordinalities

**Primary :**

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

**Technology :** ICS/OT (*Prevalence = Undetermined*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	



Scope	Impact	Likelihood
	<i>If hard-coded passwords are used, it is almost certain that malicious users will gain access through the account in question.</i>	

## Detection Methods

### Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

### Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as *truss* (Solaris) and *strace* (Linux); system activity monitors such as *FileMon*, *RegMon*, *Process Monitor*, and other *Sysinternals* utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and perform a login. Using disassembled code, look at the associated instructions and see if any of them appear to be comparing the input to a fixed string or value.

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

For outbound authentication: store passwords outside of the code in a strongly-protected, encrypted configuration file or database that is protected from access by all outsiders, including other local users on the same system. Properly protect the key (CWE-320). If you cannot use encryption to protect the file, then make sure that the permissions are as restrictive as possible.

### Phase: Architecture and Design

For inbound authentication: Rather than hard-code a default username and password for first time logins, utilize a "first login" mode that requires the user to enter a unique strong password.

### Phase: Architecture and Design

Perform access control checks and limit which entities can access the feature that requires the hard-coded password. For example, a feature might only be enabled through the system console instead of through a network connection.

### Phase: Architecture and Design

For inbound authentication: apply strong one-way hashes to your passwords and store those hashes in a configuration file or database with appropriate access control. That way, theft of the file/database still requires the attacker to try to crack the password. When receiving an incoming password during authentication, take the hash of the password and compare it to the hash that you have saved. Use randomly assigned salts for each separate hash that you generate. This increases the amount of computation that an attacker needs to conduct a brute-force attack, possibly limiting the effectiveness of the rainbow table method.

**Phase: Architecture and Design**

For front-end to back-end connections: Three solutions are possible, although none are complete. The first suggestion involves the use of generated passwords which are changed automatically and must be entered at given time intervals by a system administrator. These passwords will be held in memory and only be valid for the time intervals. Next, the passwords used should be limited at the back end to only performing actions valid for the front end, as opposed to having full access. Finally, the messages sent should be tagged and checksummed with time sensitive values so as to prevent replay style attacks.

**Demonstrative Examples****Example 1:**

The following code uses a hard-coded password to connect to a database:

*Example Language: Java*

*(Bad)*

```
...
DriverManager.getConnection(url, "scott", "tiger");
...
```

This is an example of an external hard-coded password on the client-side of a connection. This code will run successfully, but anyone who has access to it will have access to the password. Once the program has shipped, there is no going back from the database user "scott" with a password of "tiger" unless the program is patched. A devious employee with access to this information can use it to break into the system. Even worse, if attackers have access to the bytecode for application, they can use the `javap -c` command to access the disassembled code, which will contain the values of the passwords used. The result of this operation might look something like the following for the example above:

*Example Language:*

*(Attack)*

```
javap -c ConnMngr.class
22: ldc #36; //String jdbc:mysql://ixne.com/rxsql
24: ldc #38; //String scott
26: ldc #17; //String tiger
```

**Example 2:**

The following code is an example of an internal hard-coded password in the back-end:

*Example Language: C*

*(Bad)*

```
int VerifyAdmin(char *password) {
    if (strcmp(password, "Mew!")) {
        printf("Incorrect Password!\n");
        return(0);
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

*Example Language: Java*

*(Bad)*

```
int VerifyAdmin(String password) {
    if (!password.equals("Mew!")) {
        return(0);
    }
    //Diagnostic Mode
    return(1);
}
```

Every instance of this program can be placed into diagnostic mode with the same password. Even worse is the fact that if this program is distributed as a binary-only distribution, it is very difficult to change that password or disable this "functionality."

### Example 3:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in cleartext.

This Java example shows a properties file with a cleartext username / password pair.

Example Language: Java

(Bad)

```
# Java Web App ResourceBundle properties file
...
webapp ldap.username=secretUsername
webapp ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in cleartext.

Example Language: ASP.NET

(Bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in cleartext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information.

### Example 4:

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.

Multiple vendors used hard-coded credentials in their OT products.

## Observed Examples

Reference	Description
<b>CVE-2022-29964</b>	Distributed Control System (DCS) has hard-coded passwords for local shell access <a href="https://www.cve.org/CVERecord?id=CVE-2022-29964">https://www.cve.org/CVERecord?id=CVE-2022-29964</a>
<b>CVE-2021-37555</b>	Telnet service for IoT feeder for dogs and cats has hard-coded password [REF-1288] <a href="https://www.cve.org/CVERecord?id=CVE-2021-37555">https://www.cve.org/CVERecord?id=CVE-2021-37555</a>
<b>CVE-2021-35033</b>	Firmware for a WiFi router uses a hard-coded password for a BusyBox shell, allowing bypass of authentication through the UART port <a href="https://www.cve.org/CVERecord?id=CVE-2021-35033">https://www.cve.org/CVERecord?id=CVE-2021-35033</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	2314
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	2335
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	2353
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	2370
MemberOf	C	950	SFP Secondary Cluster: Hardcoded Sensitive Data	888	2396
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	2453
MemberOf	C	1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

## Notes

### Maintenance

This entry could be split into multiple variants: an inbound variant (as seen in the second demonstrative example) and an outbound variant (as seen in the first demonstrative example). These variants are likely to have different consequences, detectability, etc. More importantly, from a vulnerability theory perspective, they could be characterized as different behaviors.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management: Hard-Coded Password
CLASP			Use of hard-coded password
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management
The CERT Oracle Secure Coding Standard for Java (2011)	MSC03-J		Never hard code sensitive information
Software Fault Patterns	SFP33		Hardcoded sensitive data

## References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.

[REF-1288]Julia Lokrantz. "Ethical hacking of a Smart Automatic Feed Dispenser". 2021 June 7. < <http://kth.diva-portal.org/smash/get/diva2:1561552/FULLTEXT01.pdf> >.

[REF-1304]ICS-CERT. "ICS Alert (ICS-ALERT-13-164-01): Medical Devices Hard-Coded Passwords". 2013 June 3. < <https://www.cisa.gov/news-events/ics-alerts/ics-alert-13-164-01> >.2023-04-07.

## CWE-260: Password in Configuration File

**Weakness ID :** 260  
**Structure :** Simple  
**Abstraction :** Base

### Description

The product stores a password in a configuration file that might be accessible to actors who do not know the password.

### Extended Description

This can result in compromise of the system for which the password is used. An attacker could gain access to this file and learn the stored password or worse yet, change the password to one of their choosing.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		522	Insufficiently Protected Credentials	1225
ParentOf		13	ASP.NET Misconfiguration: Password in Configuration File	13
ParentOf		258	Empty Password in Configuration File	621
ParentOf		555	J2EE Misconfiguration: Plaintext Password in Configuration File	1270

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management Errors	2315

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

**Phase: Architecture and Design**

Avoid storing passwords in easily accessible locations.

**Phase: Architecture and Design**

Consider storing cryptographic hashes of passwords as an alternative to storing in plaintext.

**Demonstrative Examples****Example 1:**

Below is a snippet from a Java properties file.

*Example Language: Java*

*(Bad)*

```
webapp ldap.username = secretUsername
webapp ldap.password = secretPassword
```

Because the LDAP credentials are stored in plaintext, anyone with access to the file can gain access to the resource.

**Example 2:**

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in cleartext.

This Java example shows a properties file with a cleartext username / password pair.

*Example Language: Java*

*(Bad)*

```
# Java Web App ResourceBundle properties file
...
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in cleartext.

*Example Language: ASP.NET*

*(Bad)*

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in cleartext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information.

**Observed Examples**

Reference	Description
<b>CVE-2022-38665</b>	A continuous delivery pipeline management tool stores an unencrypted password in a configuration file. <a href="https://www.cve.org/CVERecord?id=CVE-2022-38665">https://www.cve.org/CVERecord?id=CVE-2022-38665</a>

**Affected Resources**

- File or Directory

**MemberOf Relationships**

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	Page	Page
MemberOf		254	7PK - Security Features	700	2314
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1349	OWASP Top Ten 2021 Category A05:2021 - Security Misconfiguration	1344	2493
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management: Password in Configuration File

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

## CWE-261: Weak Encoding for Password

**Weakness ID :** 261

**Structure :** Simple

**Abstraction :** Base

### Description

Obscuring a password with a trivial encoding does not protect the password.

### Extended Description

Password management issues occur when a password is stored in plaintext in an application's properties or configuration file. A programmer can attempt to remedy the password management problem by obscuring the password with an encoding function, such as base 64 encoding, but this effort does not adequately protect the password.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*



Nature	Type	ID	Name	Page
ChildOf		522	Insufficiently Protected Credentials	1225

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*



Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management Errors	2315
MemberOf		310	Cryptographic Issues	2318

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

#### Potential Mitigations

Passwords should be encrypted with keys that are at least 128 bits in length for adequate security.

### Demonstrative Examples

#### Example 1:

The following code reads a password from a properties file and uses the password to connect to a database.

*Example Language: Java*

*(Bad)*

```
...
Properties prop = new Properties();
prop.load(new FileInputStream("config.properties"));
String password = Base64.decode(prop.getProperty("password"));
DriverManager.getConnection(url, usr, password);
...
```

This code will run successfully, but anyone with access to config.properties can read the value of password and easily determine that the value has been base 64 encoded. If a devious employee has access to this information, they can use it to break into the system.

#### Example 2:

The following code reads a password from the registry and uses the password to create a new network credential.

*Example Language: C#*

*(Bad)*

```
...
string value = regKey.GetValue(passKey).ToString();
byte[] decVal = Convert.FromBase64String(value);
NetworkCredential netCred = new NetworkCredential(username, decVal.toString(), domain);
...
```

This code will run successfully, but anyone who has access to the registry key used to store the password can read the value of password. If a devious employee has access to this information, they can use it to break into the system.

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		254	7PK - Security Features	700	2314
MemberOf		729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	2338
MemberOf		959	SFP Secondary Cluster: Weak Cryptography	888	2398
MemberOf		1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Other

The "crypt" family of functions uses weak cryptographic algorithms and should be avoided. It may be present in some projects for compatibility.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management: Weak Cryptography
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
55	Rainbow Table Password Cracking

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

## CWE-262: Not Using Password Aging

**Weakness ID :** 262  
**Structure :** Simple  
**Abstraction :** Base

### Description

The product does not have a mechanism in place for managing password aging.

### Extended Description




Password aging (or password rotation) is a policy that forces users to change their passwords after a defined time period passes, such as every 30 or 90 days. Without mechanisms such as aging, users might not change their passwords in a timely manner.

Note that while password aging was once considered an important security feature, it has since fallen out of favor by many, because it is not as effective against modern threats compared to other mechanisms such as slow hashes. In addition, forcing frequent changes can unintentionally encourage users to select less-secure passwords. However, password aging is still in use due to factors such as compliance requirements, e.g., Payment Card Industry Data Security Standard (PCI DSS).

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1390	Weak Authentication	2267
PeerOf		309	Use of Password System for Primary Authentication	754
PeerOf		324	Use of a Key Past its Expiration Date	792

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management Errors	2315

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

Low

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>As passwords age, the probability that they are compromised grows.</i>	

## Potential Mitigations

### Phase: Architecture and Design

As part of a product's design, require users to change their passwords regularly and avoid reusing previous passwords.

### Phase: Implementation

Developers might disable clipboard paste operations into password fields as a way to discourage users from pasting a password into a clipboard. However, this might encourage users to choose less-secure passwords that are easier to type, and it can reduce the usability of password managers [REF-1294].

*Effectiveness = Discouraged Common Practice*

## Demonstrative Examples

### Example 1:

A system does not enforce the changing of passwords every certain period.

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	951	SFP Secondary Cluster: Insecure Authentication Policy	888	2396
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Not allowing password aging

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
16	Dictionary-based Password Attack
49	Password Brute Forcing
55	Rainbow Table Password Cracking
70	Try Common or Default Usernames and Passwords
509	Kerberoasting
555	Remote Services with Stolen Credentials
560	Use of Known Domain Credentials
561	Windows Admin Shares with Stolen Credentials
565	Password Spraying
600	Credential Stuffing
652	Use of Known Kerberos Credentials
653	Use of Known Operating System Credentials

## References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-1305]Kurt Seifried and other members of the CWE-Research mailing list. "Discussion Thread: Time to retire CWE-262 and CWE-263". 2021 December 3. < <https://www.mail-archive.com/cwe-research-list@mitre.org/msg00018.html> >.2022-10-11.

[REF-1289]Lance Spitzner. "Time for Password Expiration to Die". 2021 June 7. < <https://www.sans.org/blog/time-for-password-expiration-to-die/> >.

[REF-1290]Lorrie Cranor. "Time to rethink mandatory password changes". 2016 March 2. < <https://www.ftc.gov/policy/advocacy-research/tech-at-ftc/2016/03/time-rethink-mandatory-password-changes> >.

[REF-1291]Eugene Spafford. "Security Myths and Passwords". 2006 April 9. < <https://www.cerias.purdue.edu/site/blog/post/password-change-myths/> >.

[REF-1292]National Cyber Security Centre. "Password administration for system owners". 2018 November 9. < <https://www.ncsc.gov.uk/collection/passwords> >.2023-04-07.

[REF-1293]NIST. "Digital Identity Guidelines: Authentication and Lifecycle Management(SP 800-63B)". 2017 June. < <https://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-63b.pdf> >.2023-04-07.

[REF-1294]National Cyber Security Centre. "Let them paste passwords". 2017 January 2. < <https://www.ncsc.gov.uk/blog-post/let-them-paste-passwords> >.2023-04-07.

## CWE-263: Password Aging with Long Expiration

**Weakness ID** : 263

**Structure** : Simple

**Abstraction** : Base

### Description

The product supports password aging, but the expiration period is too long.

### Extended Description

Password aging (or password rotation) is a policy that forces users to change their passwords after a defined time period passes, such as every 30 or 90 days. A long expiration provides more time for attackers to conduct password cracking before users are forced to change to a new password.

Note that while password aging was once considered an important security feature, it has since fallen out of favor by many, because it is not as effective against modern threats compared to other mechanisms such as slow hashes. In addition, forcing frequent changes can unintentionally encourage users to select less-secure passwords. However, password aging is still in use due to factors such as compliance requirements, e.g., Payment Card Industry Data Security Standard (PCI DSS).

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1390	Weak Authentication	2267

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management Errors	2315

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

Low

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Scope	Impact	Likelihood
	As passwords age, the probability that they are compromised grows.	

### Potential Mitigations

#### Phase: Architecture and Design

Ensure that password aging is limited so that there is a defined maximum age for passwords. Note that if the expiration window is too short, it can cause users to generate poor or predictable passwords.

#### Phase: Architecture and Design

Ensure that the user is notified several times leading up to the password expiration.

#### Phase: Architecture and Design

Create mechanisms to prevent users from reusing passwords or creating similar passwords.

#### Phase: Implementation

Developers might disable clipboard paste operations into password fields as a way to discourage users from pasting a password into a clipboard. However, this might encourage users to choose less-secure passwords that are easier to type, and it can reduce the usability of password managers [REF-1294].

*Effectiveness = Discouraged Common Practice*





### Demonstrative Examples

#### Example 1:

A system requires the changing of passwords every five years.

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		884	CWE Cross-section	884	2567
MemberOf		951	SFP Secondary Cluster: Insecure Authentication Policy	888	2396
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Allowing password aging

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
16	Dictionary-based Password Attack
49	Password Brute Forcing
55	Rainbow Table Password Cracking
70	Try Common or Default Usernames and Passwords
509	Kerberoasting
555	Remote Services with Stolen Credentials
560	Use of Known Domain Credentials
561	Windows Admin Shares with Stolen Credentials
565	Password Spraying
600	Credential Stuffing
652	Use of Known Kerberos Credentials
653	Use of Known Operating System Credentials

## References

- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.
- [REF-1305]Kurt Seifried and other members of the CWE-Research mailing list. "Discussion Thread: Time to retire CWE-262 and CWE-263". 2021 December 3. < <https://www.mail-archive.com/cwe-research-list@mitre.org/msg00018.html> >.2022-10-11.
- [REF-1289]Lance Spitzner. "Time for Password Expiration to Die". 2021 June 7. < <https://www.sans.org/blog/time-for-password-expiration-to-die/> >.
- [REF-1290]Lorrie Cranor. "Time to rethink mandatory password changes". 2016 March 2. < <https://www.ftc.gov/policy/advocacy-research/tech-at-ftc/2016/03/time-rethink-mandatory-password-changes> >.
- [REF-1291]Eugene Spafford. "Security Myths and Passwords". 2006 April 9. < <https://www.cerias.purdue.edu/site/blog/post/password-change-myths/> >.
- [REF-1292]National Cyber Security Centre. "Password administration for system owners". 2018 November 9. < <https://www.ncsc.gov.uk/collection/passwords> >.2023-04-07.
- [REF-1293]NIST. "Digital Identity Guidelines: Authentication and Lifecycle Management(SP 800-63B)". 2017 June. < <https://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-63b.pdf> >.2023-04-07.
- [REF-1294]National Cyber Security Centre. "Let them paste passwords". 2017 January 2. < <https://www.ncsc.gov.uk/blog-post/let-them-paste-passwords> >.2023-04-07.

## CWE-266: Incorrect Privilege Assignment

**Weakness ID** : 266

**Structure** : Simple

**Abstraction** : Base







### Description

A product incorrectly assigns a privilege to a particular actor, creating an unintended sphere of control for that actor.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	646
ParentOf		9	J2EE Misconfiguration: Weak Access Permissions for EJB Methods	8
ParentOf		520	.NET Misconfiguration: Use of Impersonation	1222
ParentOf		556	ASP.NET Misconfiguration: Use of Identity Impersonation	1271
ParentOf		1022	Use of Web Link to Untrusted Target with window.opener Access	1862
CanAlsoBe		286	Incorrect User Management	691

*Relevant to the view "Architectural Concepts" (CWE-1008)*



Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316

## Weakness Ordinalities

**Resultant :**

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  <i>A user can access restricted functionality and/or sensitive information that may include administrative functionality and user accounts.</i>	

## Potential Mitigations

**Phase: Architecture and Design**

**Phase: Operation**

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

**Phase: Architecture and Design**

**Phase: Operation**

*Strategy = Environment Hardening*

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

## Demonstrative Examples

### Example 1:

The following example demonstrates the weakness.

*Example Language: C*

*(Bad)*

```
setuid(0);
/* do some stuff */
setuid(getuid());
```

### Example 2:

The following example demonstrates the weakness.

*Example Language: Java*

*(Bad)*

```
AccessController.doPrivileged(new PrivilegedAction() {
    public Object run() {
        // privileged code goes here, for example:
        System.loadLibrary("awt");
        return null;
        // nothing to return
    }
});
```

```
}
```

### Example 3:

This application sends a special intent with a flag that allows the receiving application to read a data file for backup purposes.

Example Language: Java

(Bad)

```
Intent intent = new Intent();
intent.setAction("com.example.BackupUserData");
intent.setData(file_uri);
intent.addFlags(FLAG_GRANT_READ_URI_PERMISSION);
sendBroadcast(intent);
```

Example Language: Java

(Attack)

```
public class CallReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        Uri userData = intent.getData();
        stealUserData(userData);
    }
}
```

Any malicious application can register to receive this intent. Because of the FLAG\_GRANT\_READ\_URI\_PERMISSION included with the intent, the malicious receiver code can read the user's data.

### Observed Examples





Reference	Description
<b>CVE-1999-1193</b>	untrusted user placed in unix "wheel" group <a href="https://www.cve.org/CVERecord?id=CVE-1999-1193">https://www.cve.org/CVERecord?id=CVE-1999-1193</a>
<b>CVE-2005-2741</b>	Product allows users to grant themselves certain rights that can be used to escalate privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2741">https://www.cve.org/CVERecord?id=CVE-2005-2741</a>
<b>CVE-2005-2496</b>	Product uses group ID of a user instead of the group, causing it to run with different privileges. This is resultant from some other unknown issue. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2496">https://www.cve.org/CVERecord?id=CVE-2005-2496</a>
<b>CVE-2004-0274</b>	Product mistakenly assigns a particular status to an entity, leading to increased privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2004-0274">https://www.cve.org/CVERecord?id=CVE-2004-0274</a>

### Affected Resources

- System Process

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	2335
MemberOf		859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	2369
MemberOf		884	CWE Cross-section	884	2567
MemberOf		901	SFP Primary Cluster: Privilege	888	2386

Nature	Type	ID	Name	V	Page
MemberOf		1149	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC)	1133	2452
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incorrect Privilege Assignment
The CERT Oracle Secure Coding Standard for Java (2011)	SEC00-J		Do not allow privileged blocks to leak sensitive information across a trust boundary
The CERT Oracle Secure Coding Standard for Java (2011)	SEC01-J		Do not allow tainted variables in privileged blocks

### References

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://web.archive.org/web/20211209014121/https://www.cisa.gov/uscert/bsi/articles/knowledge/principles/least-privilege> >.2023-04-07.

## CWE-267: Privilege Defined With Unsafe Actions

**Weakness ID** : 267

**Structure** : Simple

**Abstraction** : Base

### Description

A particular privilege, role, capability, or right can be used to perform unsafe actions that were not intended, even when it is assigned to the correct entity.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	646
ParentOf		623	Unsafe ActiveX Control Marked Safe For Scripting	1389

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  <i>A user can access restricted functionality and/or sensitive information that may include administrative functionality and user accounts.</i>	

### Potential Mitigations

#### Phase: Architecture and Design

#### Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

#### Phase: Architecture and Design

#### Phase: Operation

*Strategy = Environment Hardening*

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

### Demonstrative Examples

#### Example 1:

This code intends to allow only Administrators to print debug information about a system.

*Example Language: Java*

*(Bad)*

```
public enum Roles {
    ADMIN, USER, GUEST
}

public void printDebugInfo(User requestingUser){
    if(isAuthenticated(requestingUser)){
        switch(requestingUser.role){
            case GUEST:
                System.out.println("You are not authorized to perform this command");
                break;
            default:
                System.out.println(currentDebugState());
                break;
        }
    }
    else{
        System.out.println("You must be logged in to perform this command");
    }
}
```

While the intention was to only allow Administrators to print the debug information, the code as written only excludes those with the role of "GUEST". Someone with the role of "ADMIN" or "USER" will be allowed access, which goes against the original intent. An attacker may be able to use this debug information to craft an attack on the system.





### Observed Examples

Reference	Description
<b>CVE-2002-1981</b>	Roles have access to dangerous procedures (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1981">https://www.cve.org/CVERecord?id=CVE-2002-1981</a>
<b>CVE-2002-1671</b>	Untrusted object/method gets access to clipboard (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1671">https://www.cve.org/CVERecord?id=CVE-2002-1671</a>

Reference	Description
<b>CVE-2004-2204</b>	Gain privileges using functions/tags that should be restricted (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2004-2204">https://www.cve.org/CVERecord?id=CVE-2004-2204</a>
<b>CVE-2000-0315</b>	Traceroute program allows unprivileged users to modify source address of packet (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2000-0315">https://www.cve.org/CVERecord?id=CVE-2000-0315</a>
<b>CVE-2004-0380</b>	Bypass domain restrictions using a particular file that references unsafe URI schemes (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2004-0380">https://www.cve.org/CVERecord?id=CVE-2004-0380</a>
<b>CVE-2002-1154</b>	Script does not restrict access to an update command, leading to resultant disk consumption and filled error logs (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1154">https://www.cve.org/CVERecord?id=CVE-2002-1154</a>
<b>CVE-2002-1145</b>	"public" database user can use stored procedure to modify data controlled by the database owner (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1145">https://www.cve.org/CVERecord?id=CVE-2002-1145</a>
<b>CVE-2000-0506</b>	User with capability can prevent setuid program from dropping privileges (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2000-0506">https://www.cve.org/CVERecord?id=CVE-2000-0506</a>
<b>CVE-2002-2042</b>	Allows attachment to and modification of privileged processes (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2002-2042">https://www.cve.org/CVERecord?id=CVE-2002-2042</a>
<b>CVE-2000-1212</b>	User with privilege can edit raw underlying object using unprotected method (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2000-1212">https://www.cve.org/CVERecord?id=CVE-2000-1212</a>
<b>CVE-2005-1742</b>	Inappropriate actions allowed by a particular role (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2005-1742">https://www.cve.org/CVERecord?id=CVE-2005-1742</a>
<b>CVE-2001-1480</b>	Untrusted entity allowed to access the system clipboard (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2001-1480">https://www.cve.org/CVERecord?id=CVE-2001-1480</a>
<b>CVE-2001-1551</b>	Extra Linux capability allows bypass of system-specified restriction (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2001-1551">https://www.cve.org/CVERecord?id=CVE-2001-1551</a>
<b>CVE-2001-1166</b>	User with debugging rights can read entire process (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2001-1166">https://www.cve.org/CVERecord?id=CVE-2001-1166</a>
<b>CVE-2005-1816</b>	Non-root admins can add themselves or others to the root admin group (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2005-1816">https://www.cve.org/CVERecord?id=CVE-2005-1816</a>
<b>CVE-2005-2173</b>	Users can change certain properties of objects to perform otherwise unauthorized actions (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2005-2173">https://www.cve.org/CVERecord?id=CVE-2005-2173</a>
<b>CVE-2005-2027</b>	Certain debugging commands not restricted to just the administrator, allowing registry modification and infoleak (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2005-2027">https://www.cve.org/CVERecord?id=CVE-2005-2027</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		884	CWE Cross-section	884	2567
MemberOf		901	SFP Primary Cluster: Privilege	888	2386
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

## Notes

### Maintenance

Note: there are 2 separate sub-categories here: - privilege incorrectly allows entities to perform certain actions - object is incorrectly accessible to entities with a given privilege

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unsafe Privilege

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
58	Restful Privilege Elevation
634	Probe Audio and Video Peripherals
637	Collect Data from Clipboard
643	Identify Shared Files/Directories on System
648	Collect Data from Screen Capture

## References

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://web.archive.org/web/20211209014121/https://www.cisa.gov/uscert/bsi/articles/knowledge/principles/least-privilege> >.2023-04-07.

## CWE-268: Privilege Chaining

**Weakness ID** : 268

**Structure** : Simple

**Abstraction** : Base

### Description

Two distinct privileges, roles, capabilities, or rights can be combined in a way that allows an entity to perform unsafe actions that would not be allowed without that combination.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	646

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316

### Weakness Ordinalities

**Primary** :

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  <i>A user can be given or gain access rights of another user. This can give the user unauthorized access to sensitive information including the access information of another user.</i>	

## Potential Mitigations

### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

### Phase: Architecture and Design

#### Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

### Phase: Architecture and Design

#### Phase: Operation

*Strategy = Environment Hardening*

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

## Demonstrative Examples

### Example 1:

This code allows someone with the role of "ADMIN" or "OPERATOR" to reset a user's password. The role of "OPERATOR" is intended to have less privileges than an "ADMIN", but still be able to help users with small issues such as forgotten passwords.

*Example Language: Java*

*(Bad)*

```
public enum Roles {
    ADMIN, OPERATOR, USER, GUEST
}

public void resetPassword(User requestingUser, User user, String password) {
    if (isAuthenticated(requestingUser)) {
        switch (requestingUser.role) {
            case GUEST:
                System.out.println("You are not authorized to perform this command");
                break;
            case USER:
                System.out.println("You are not authorized to perform this command");
                break;
            default:
                setPassword(user, password);
                break;
        }
    }
}
```



```

    }
    else{
        System.out.println("You must be logged in to perform this command");
    }
}

```

This code does not check the role of the user whose password is being reset. It is possible for an Operator to gain Admin privileges by resetting the password of an Admin account and taking control of that account.

### Observed Examples

Reference	Description
<b>CVE-2005-1736</b>	Chaining of user rights. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1736">https://www.cve.org/CVERecord?id=CVE-2005-1736</a>
<b>CVE-2002-1772</b>	Gain certain rights via privilege chaining in alternate channel. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1772">https://www.cve.org/CVERecord?id=CVE-2002-1772</a>
<b>CVE-2005-1973</b>	Application is allowed to assign extra permissions to itself. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1973">https://www.cve.org/CVERecord?id=CVE-2005-1973</a>
<b>CVE-2003-0640</b>	"operator" user can overwrite usernames and passwords to gain admin privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0640">https://www.cve.org/CVERecord?id=CVE-2003-0640</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	2335
MemberOf		884	CWE Cross-section	884	2567
MemberOf		901	SFP Primary Cluster: Privilege	888	2386
MemberOf		1364	ICS Communications: Zone Boundary Failures	1358	2501
MemberOf		1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Relationship

There is some conceptual overlap with Unsafe Privilege.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege Chaining

### References

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://web.archive.org/web/20211209014121/https://www.cisa.gov/uscert/bsi/articles/knowledge/principles/least-privilege> >.2023-04-07.

## CWE-269: Improper Privilege Management

**Weakness ID** : 269

**Structure** : Simple

**Abstraction** : Class

## Description

The product does not properly assign, modify, track, or check privileges for an actor, creating an unintended sphere of control for that actor.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	P	284	Improper Access Control	680
ParentOf	B	250	Execution with Unnecessary Privileges	599
ParentOf	B	266	Incorrect Privilege Assignment	638
ParentOf	B	267	Privilege Defined With Unsafe Actions	641
ParentOf	B	268	Privilege Chaining	644
ParentOf	B	270	Privilege Context Switching Error	651
ParentOf	C	271	Privilege Dropping / Lowering Errors	653
ParentOf	B	274	Improper Handling of Insufficient Privileges	663
ParentOf	B	648	Incorrect Use of Privileged APIs	1428

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	2425

## Weakness Ordinalities

**Primary :**

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

Medium

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

**Phase: Architecture and Design**

**Phase: Operation**

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Follow the principle of least privilege when assigning access rights to entities in a software system.

### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

## Demonstrative Examples

### Example 1:

This code temporarily raises the program's privileges to allow creation of a new user folder.

*Example Language: Python*

*(Bad)*

```
def makeNewUserDir(username):
    if invalidUsername(username):
        #avoid CWE-22 and CWE-78
        print('Usernames cannot contain invalid characters')
        return False
    try:
        raisePrivileges()
        os.mkdir('/home/' + username)
        lowerPrivileges()
    except OSError:
        print('Unable to create new user directory for user:' + username)
        return False
    return True
```

While the program only raises its privilege level to create the folder and immediately lowers it again, if the call to `os.mkdir()` throws an exception, the call to `lowerPrivileges()` will not occur. As a result, the program is indefinitely operating in a raised privilege state, possibly allowing further exploitation to occur.

### Example 2:

The following example demonstrates the weakness.

*Example Language: C*

*(Bad)*

```
seteuid(0);
/* do some stuff */
seteuid(getuid());
```

### Example 3:

The following example demonstrates the weakness.

*Example Language: Java*

*(Bad)*

```
AccessController.doPrivileged(new PrivilegedAction() {
    public Object run() {
        // privileged code goes here, for example:
        System.loadLibrary("awt");
        return null;
        // nothing to return
    }
})
```

**Example 4:**

This code intends to allow only Administrators to print debug information about a system.

Example Language: Java

(Bad)

```
public enum Roles {
    ADMIN, USER, GUEST
}
public void printDebugInfo(User requestingUser){
    if(isAuthenticated(requestingUser)){
        switch(requestingUser.role){
            case GUEST:
                System.out.println("You are not authorized to perform this command");
                break;
            default:
                System.out.println(currentDebugState());
                break;
        }
    }
    else{
        System.out.println("You must be logged in to perform this command");
    }
}
```

While the intention was to only allow Administrators to print the debug information, the code as written only excludes those with the role of "GUEST". Someone with the role of "ADMIN" or "USER" will be allowed access, which goes against the original intent. An attacker may be able to use this debug information to craft an attack on the system.

**Example 5:**

This code allows someone with the role of "ADMIN" or "OPERATOR" to reset a user's password. The role of "OPERATOR" is intended to have less privileges than an "ADMIN", but still be able to help users with small issues such as forgotten passwords.

Example Language: Java

(Bad)

```
public enum Roles {
    ADMIN, OPERATOR, USER, GUEST
}
public void resetPassword(User requestingUser, User user, String password){
    if(isAuthenticated(requestingUser)){
        switch(requestingUser.role){
            case GUEST:
                System.out.println("You are not authorized to perform this command");
                break;
            case USER:
                System.out.println("You are not authorized to perform this command");
                break;
            default:
                setPassword(user,password);
                break;
        }
    }
    else{
        System.out.println("You must be logged in to perform this command");
    }
}
```




This code does not check the role of the user whose password is being reset. It is possible for an Operator to gain Admin privileges by resetting the password of an Admin account and taking control of that account.

**Observed Examples**

Reference	Description
<b>CVE-2001-1555</b>	Terminal privileges are not reset when a user logs out. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1555">https://www.cve.org/CVERecord?id=CVE-2001-1555</a>
<b>CVE-2001-1514</b>	Does not properly pass security context to child processes in certain cases, allows privilege escalation. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1514">https://www.cve.org/CVERecord?id=CVE-2001-1514</a>
<b>CVE-2001-0128</b>	Does not properly compute roles. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0128">https://www.cve.org/CVERecord?id=CVE-2001-0128</a>
<b>CVE-1999-1193</b>	untrusted user placed in unix "wheel" group <a href="https://www.cve.org/CVERecord?id=CVE-1999-1193">https://www.cve.org/CVERecord?id=CVE-1999-1193</a>
<b>CVE-2005-2741</b>	Product allows users to grant themselves certain rights that can be used to escalate privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2741">https://www.cve.org/CVERecord?id=CVE-2005-2741</a>
<b>CVE-2005-2496</b>	Product uses group ID of a user instead of the group, causing it to run with different privileges. This is resultant from some other unknown issue. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2496">https://www.cve.org/CVERecord?id=CVE-2005-2496</a>
<b>CVE-2004-0274</b>	Product mistakenly assigns a particular status to an entity, leading to increased privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2004-0274">https://www.cve.org/CVERecord?id=CVE-2004-0274</a>
<b>CVE-2007-4217</b>	FTP client program on a certain OS runs with setuid privileges and has a buffer overflow. Most clients do not need extra privileges, so an overflow is not a vulnerability for those clients. <a href="https://www.cve.org/CVERecord?id=CVE-2007-4217">https://www.cve.org/CVERecord?id=CVE-2007-4217</a>
<b>CVE-2007-5159</b>	OS incorrectly installs a program with setuid privileges, allowing users to gain privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2007-5159">https://www.cve.org/CVERecord?id=CVE-2007-5159</a>
<b>CVE-2008-4638</b>	Composite: application running with high privileges (CWE-250) allows user to specify a restricted file to process, which generates a parsing error that leaks the contents of the file (CWE-209). <a href="https://www.cve.org/CVERecord?id=CVE-2008-4638">https://www.cve.org/CVERecord?id=CVE-2008-4638</a>
<b>CVE-2007-3931</b>	Installation script installs some programs as setuid when they shouldn't be. <a href="https://www.cve.org/CVERecord?id=CVE-2007-3931">https://www.cve.org/CVERecord?id=CVE-2007-3931</a>
<b>CVE-2002-1981</b>	Roles have access to dangerous procedures (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1981">https://www.cve.org/CVERecord?id=CVE-2002-1981</a>
<b>CVE-2002-1671</b>	Untrusted object/method gets access to clipboard (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1671">https://www.cve.org/CVERecord?id=CVE-2002-1671</a>
<b>CVE-2000-0315</b>	Traceroute program allows unprivileged users to modify source address of packet (Accessible entities). <a href="https://www.cve.org/CVERecord?id=CVE-2000-0315">https://www.cve.org/CVERecord?id=CVE-2000-0315</a>
<b>CVE-2000-0506</b>	User with capability can prevent setuid program from dropping privileges (Unsafe privileged actions). <a href="https://www.cve.org/CVERecord?id=CVE-2000-0506">https://www.cve.org/CVERecord?id=CVE-2000-0506</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		901	SFP Primary Cluster: Privilege	888	2386
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	2576
MemberOf		1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	2587

Nature	Type	ID	Name	V	Page
MemberOf	C	1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf	V	1350	Weaknesses in the 2020 CWE Top 25 Most Dangerous Software Weaknesses	1350	2594
MemberOf	C	1364	ICS Communications: Zone Boundary Failures	1358	2501
MemberOf	C	1365	ICS Communications: Unreliability	1358	2502
MemberOf	C	1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf	C	1373	ICS Engineering (Construction/Deployment): Trust Model Problems	1358	2510
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519
MemberOf	V	1425	Weaknesses in the 2023 CWE Top 25 Most Dangerous Software Weaknesses	1425	2600

## Notes

### Maintenance

The relationships between privileges, permissions, and actors (e.g. users and groups) need further refinement within the Research view. One complication is that these concepts apply to two different pillars, related to control of resources (CWE-664) and protection mechanism failures (CWE-693).

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege Management Error
ISA/IEC 62443	Part 2-4		Req SP.03.08 BR
ISA/IEC 62443	Part 3-2		Req CR 3.1
ISA/IEC 62443	Part 3-3		Req SR 1.2
ISA/IEC 62443	Part 3-3		Req SR 2.1
ISA/IEC 62443	Part 4-1		Req SD-3
ISA/IEC 62443	Part 4-1		Req SD-4
ISA/IEC 62443	Part 4-1		Req SI-1
ISA/IEC 62443	Part 4-2		Req CR 1.1
ISA/IEC 62443	Part 4-2		Req CR 2.1

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
58	Restful Privilege Elevation
122	Privilege Abuse
233	Privilege Escalation

## References

- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.
- [REF-1287]MITRE. "Supplemental Details - 2022 CWE Top 25". 2022 June 8. < [https://cwe.mitre.org/top25/archive/2022/2022\\_cwe\\_top25\\_supplemental.html#problematicMappingDetails](https://cwe.mitre.org/top25/archive/2022/2022_cwe_top25_supplemental.html#problematicMappingDetails) >.

## CWE-270: Privilege Context Switching Error

Weakness ID : 270

**Structure** : Simple  
**Abstraction** : Base

## Description

The product does not properly manage privileges while it is switching between different contexts that have different privileges or spheres of control.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	646

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  A user can assume the identity of another user with separate privileges in another context. This will give the user unauthorized access that may allow them to acquire the access information of other users.	

## Potential Mitigations

### Phase: Architecture and Design

#### Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

### Phase: Architecture and Design

#### Phase: Operation

*Strategy = Environment Hardening*

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

### Phase: Architecture and Design

*Strategy = Separation of Privilege*







Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

### Observed Examples

Reference	Description
<b>CVE-2002-1688</b>	Web browser cross domain problem when user hits "back" button. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1688">https://www.cve.org/CVERecord?id=CVE-2002-1688</a>
<b>CVE-2003-1026</b>	Web browser cross domain problem when user hits "back" button. <a href="https://www.cve.org/CVERecord?id=CVE-2003-1026">https://www.cve.org/CVERecord?id=CVE-2003-1026</a>
<b>CVE-2002-1770</b>	Cross-domain issue - third party product passes code to web browser, which executes it in unsafe zone. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1770">https://www.cve.org/CVERecord?id=CVE-2002-1770</a>
<b>CVE-2005-2263</b>	Run callback in different security context after it has been changed from untrusted to trusted. * note that "context switch before actions are completed" is one type of problem that happens frequently, espec. in browsers. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2263">https://www.cve.org/CVERecord?id=CVE-2005-2263</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		884	CWE Cross-section	884	2567
MemberOf		901	SFP Primary Cluster: Privilege	888	2386
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Research Gap

This concept needs more study.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege Context Switching Error

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
17	Using Malicious Files
30	Hijacking a Privileged Thread of Execution
35	Leverage Executable Code in Non-Executable Files

### References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://web.archive.org/web/20211209014121/https://www.cisa.gov/uscert/bsi/articles/knowledge/principles/least-privilege> >.2023-04-07.

## CWE-271: Privilege Dropping / Lowering Errors

**Weakness ID** : 271  
**Structure** : Simple  
**Abstraction** : Class

## Description

The product does not drop privileges before passing control of a resource to an actor that does not have those privileges.


## Extended Description

In some contexts, a system executing with elevated permissions will hand off a process/file/etc. to another process or user. If the privileges of an entity are not reduced, then elevated privileges are spread throughout a system and possibly to an attacker.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	646
ParentOf		272	Least Privilege Violation	656
ParentOf		273	Improper Check for Dropped Privileges	660
PeerOf		274	Improper Handling of Insufficient Privileges	663

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

## Weakness Ordinalities

**Primary :**

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>If privileges are not dropped, neither are access rights of the user. Often these rights can be prevented from being dropped.</i>	
Access Control Non-Repudiation	Gain Privileges or Assume Identity Hide Activities <i>If privileges are not dropped, in some cases the system may record actions as the user which is being impersonated rather than the impersonator.</i>	

## Potential Mitigations

**Phase: Architecture and Design**

*Strategy = Separation of Privilege*

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and

reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

#### Phase: Architecture and Design

#### Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

#### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

### Demonstrative Examples

#### Example 1:

The following code calls `chroot()` to restrict the application to a subset of the filesystem below `APP_HOME` in order to prevent an attacker from using the program to gain unauthorized access to files located elsewhere. The code then opens a file specified by the user and processes the contents of the file.

*Example Language: C*

*(Bad)*

```
chroot(APP_HOME);
chdir("/");
FILE* data = fopen(argv[1], "r+");
...
```

Constraining the process inside the application's home directory before opening any files is a valuable security measure. However, the absence of a call to `setuid()` with some non-zero value means the application is continuing to operate with unnecessary root privileges. Any successful exploit carried out by an attacker against the application can now result in a privilege escalation attack because any malicious operations will be performed with the privileges of the superuser. If the application drops to the privilege level of a non-root user, the potential for damage is substantially reduced.

### Observed Examples

Reference	Description
<b>CVE-2000-1213</b>	Program does not drop privileges after acquiring the raw socket. <a href="https://www.cve.org/CVERecord?id=CVE-2000-1213">https://www.cve.org/CVERecord?id=CVE-2000-1213</a>
<b>CVE-2001-0559</b>	Setuid program does not drop privileges after a parsing error occurs, then calls another program to handle the error. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0559">https://www.cve.org/CVERecord?id=CVE-2001-0559</a>
<b>CVE-2001-0787</b>	Does not drop privileges in related groups when lowering privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0787">https://www.cve.org/CVERecord?id=CVE-2001-0787</a>
<b>CVE-2002-0080</b>	Does not drop privileges in related groups when lowering privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0080">https://www.cve.org/CVERecord?id=CVE-2002-0080</a>
<b>CVE-2001-1029</b>	Does not drop privileges before determining access to certain files. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1029">https://www.cve.org/CVERecord?id=CVE-2001-1029</a>
<b>CVE-1999-0813</b>	Finger daemon does not drop privileges when executing programs on behalf of the user being fingered. <a href="https://www.cve.org/CVERecord?id=CVE-1999-0813">https://www.cve.org/CVERecord?id=CVE-1999-0813</a>
<b>CVE-1999-1326</b>	FTP server does not drop privileges if a connection is aborted during file transfer. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1326">https://www.cve.org/CVERecord?id=CVE-1999-1326</a>
<b>CVE-2000-0172</b>	Program only uses <code>seteuid</code> to drop privileges.

Reference	Description
	<a href="https://www.cve.org/CVERecord?id=CVE-2000-0172">https://www.cve.org/CVERecord?id=CVE-2000-0172</a>
<b>CVE-2004-2504</b>	Windows program running as SYSTEM does not drop privileges before executing other programs (many others like this, especially involving the Help facility).
	<a href="https://www.cve.org/CVERecord?id=CVE-2004-2504">https://www.cve.org/CVERecord?id=CVE-2004-2504</a>
<b>CVE-2004-0213</b>	Utility Manager launches winhlp32.exe while running with raised privileges, which allows local users to gain system privileges.
	<a href="https://www.cve.org/CVERecord?id=CVE-2004-0213">https://www.cve.org/CVERecord?id=CVE-2004-0213</a>
<b>CVE-2004-0806</b>	Setuid program does not drop privileges before executing program specified in an environment variable.
	<a href="https://www.cve.org/CVERecord?id=CVE-2004-0806">https://www.cve.org/CVERecord?id=CVE-2004-0806</a>
<b>CVE-2004-0828</b>	Setuid program does not drop privileges before processing file specified on command line.
	<a href="https://www.cve.org/CVERecord?id=CVE-2004-0828">https://www.cve.org/CVERecord?id=CVE-2004-0828</a>
<b>CVE-2004-2070</b>	Service on Windows does not drop privileges before using "view file" option, allowing code execution.
	<a href="https://www.cve.org/CVERecord?id=CVE-2004-2070">https://www.cve.org/CVERecord?id=CVE-2004-2070</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	901	SFP Primary Cluster: Privilege	888	2386
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Maintenance

CWE-271, CWE-272, and CWE-250 are all closely related and possibly overlapping. CWE-271 is probably better suited as a category.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege Dropping / Lowering Errors

### References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

## CWE-272: Least Privilege Violation

**Weakness ID :** 272

**Structure :** Simple

**Abstraction :** Base

### Description

The elevated privilege level required to perform operations such as chroot() should be dropped immediately after the operation is performed.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		271	Privilege Dropping / Lowering Errors	653

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316

### Weakness Ordinalities

**Primary :**

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control Confidentiality	Gain Privileges or Assume Identity Read Application Data Read Files or Directories  <i>An attacker may be able to access resources with the elevated privilege that could not be accessed with the attacker's original privileges. This is particularly likely in conjunction with another flaw, such as a buffer overflow.</i>	

### Detection Methods

#### Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Compare binary / bytecode to application permission manifest

*Effectiveness = SOAR Partial*

#### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host-based Vulnerability Scanners - Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria

*Effectiveness = SOAR Partial*

#### Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

*Effectiveness = High*

#### Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

*Effectiveness = SOAR Partial*

### Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Permission Manifest Analysis

*Effectiveness = SOAR Partial*

### Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

#### Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Follow the principle of least privilege when assigning access rights to entities in a software system.

### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

## Demonstrative Examples

### Example 1:

The following example demonstrates the weakness.

*Example Language: C*

*(Bad)*

```
setuid(0);  
// Do some important stuff  
setuid(old_uid);  
// Do some non privileged stuff.
```

### Example 2:

The following example demonstrates the weakness.

*Example Language: Java*

*(Bad)*

```
AccessController.doPrivileged(new PrivilegedAction() {  
    public Object run() {  
        // privileged code goes here, for example:
```

```
System.loadLibrary("awt");
return null;
// nothing to return
}
```

### Example 3:

The following code calls `chroot()` to restrict the application to a subset of the filesystem below `APP_HOME` in order to prevent an attacker from using the program to gain unauthorized access to files located elsewhere. The code then opens a file specified by the user and processes the contents of the file.

Example Language: C

(Bad)

```
chroot(APP_HOME);
chdir("/");
FILE* data = fopen(argv[1], "r+");
...
```

Constraining the process inside the application's home directory before opening any files is a valuable security measure. However, the absence of a call to `setuid()` with some non-zero value means the application is continuing to operate with unnecessary root privileges. Any successful exploit carried out by an attacker against the application can now result in a privilege escalation attack because any malicious operations will be performed with the privileges of the superuser. If the application drops to the privilege level of a non-root user, the potential for damage is substantially reduced.

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	2314
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	2351
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	2369
MemberOf	C	901	SFP Primary Cluster: Privilege	888	2386
MemberOf	C	1149	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC)	1133	2452
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Maintenance

CWE-271, CWE-272, and CWE-250 are all closely related and possibly overlapping. CWE-271 is probably better suited as a category.

#### Other

If system privileges are not dropped when it is reasonable to do so, this is not a vulnerability by itself. According to the principle of least privilege, access should be allowed only when it is absolutely necessary to the function of a given system, and only for the minimal necessary amount of time. Any further allowance of privilege widens the window of time during which a successful exploitation of the system will provide an attacker with that same privilege. If at all possible, limit the allowance of system privilege to small, simple sections of code that may be called atomically. When a program calls a privileged function, such as `chroot()`, it must first



acquire root privilege. As soon as the privileged operation has completed, the program should drop root privilege and return to the privilege level of the invoking user.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Least Privilege Violation
CLASP			Failure to drop privileges when reasonable
CERT C Secure Coding	POS02-C		Follow the principle of least privilege
The CERT Oracle Secure Coding Standard for Java (2011)	SEC00-J		Do not allow privileged blocks to leak sensitive information across a trust boundary
The CERT Oracle Secure Coding Standard for Java (2011)	SEC01-J		Do not allow tainted variables in privileged blocks
Software Fault Patterns	SFP36		Privilege

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
17	Using Malicious Files
35	Leverage Executable Code in Non-Executable Files
76	Manipulating Web Input to File System Calls

### References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

## CWE-273: Improper Check for Dropped Privileges

**Weakness ID :** 273

**Structure :** Simple

**Abstraction :** Base

### Description

The product attempts to drop privileges but does not check or incorrectly checks to see if the drop succeeded.


### Extended Description

If the drop fails, the product will continue to run with the raised privileges, which might provide additional access to unprivileged users.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		271	Privilege Dropping / Lowering Errors	653
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1568

Nature	Type	ID	Name	Page
PeerOf	B	252	Unchecked Return Value	606

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf	G	754	Improper Check for Unusual or Exceptional Conditions	1568

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf	C	265	Privilege Issues	2316

### Weakness Ordinalities

**Primary :**

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Background Details

In Windows based environments that have access control, impersonation is used so that access checks can be performed on a client identity by a server with higher privileges. By impersonating the client, the server is restricted to client-level security -- although in different threads it may have much higher privileges.

### Likelihood Of Exploit

Medium

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>If privileges are not dropped, neither are access rights of the user. Often these rights can be prevented from being dropped.</i>	
Access Control Non-Repudiation	Gain Privileges or Assume Identity Hide Activities <i>If privileges are not dropped, in some cases the system may record actions as the user which is being impersonated rather than the impersonator.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

Phase: Implementation

Check the results of all functions that return a value and verify that the value is expected.

Effectiveness = High

Checking the return value of the function will typically be sufficient, however beware of race conditions (CWE-362) in a concurrent environment.

Phase: Implementation

In Windows, make sure that the process token has the SeImpersonatePrivilege(Microsoft Server 2003). Code that relies on impersonation for security must ensure that the impersonation succeeded, i.e., that a proper privilege demotion happened.

Demonstrative Examples

Example 1:

This code attempts to take on the privileges of a user before creating a file, thus avoiding performing the action with unnecessarily high privileges:

Example Language: C++ (Bad)

```
bool DoSecureStuff(HANDLE hPipe) {
    bool fDataWritten = false;
    ImpersonateNamedPipeClient(hPipe);
    HANDLE hFile = CreateFile(...);
    ...
    RevertToSelf()
    ...
}
```

The call to ImpersonateNamedPipeClient may fail, but the return value is not checked. If the call fails, the code may execute with higher privileges than intended. In this case, an attacker could exploit this behavior to write a file to a location that the attacker does not have access to.

Observed Examples

Reference	Description
CVE-2006-4447	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. <a href="https://www.cve.org/CVERecord?id=CVE-2006-4447">https://www.cve.org/CVERecord?id=CVE-2006-4447</a>
CVE-2006-2916	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. <a href="https://www.cve.org/CVERecord?id=CVE-2006-2916">https://www.cve.org/CVERecord?id=CVE-2006-2916</a>

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	2351
MemberOf		884	CWE Cross-section	884	2567
MemberOf		962	SFP Secondary Cluster: Unchecked Status Condition	888	2400
MemberOf		1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	2463
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to check whether privileges were dropped successfully
CERT C Secure Coding	POS37-C	Exact	Ensure that privilege relinquishment is successful
Software Fault Patterns	SFP4		Unchecked Status Condition

### References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-274: Improper Handling of Insufficient Privileges

**Weakness ID :** 274

**Structure :** Simple

**Abstraction :** Base

### Description

The product does not handle or incorrectly handles when it has insufficient privileges to perform an operation, leading to resultant weaknesses.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	646
ChildOf		755	Improper Handling of Exceptional Conditions	1576
PeerOf		271	Privilege Dropping / Lowering Errors	653
CanAlsoBe		280	Improper Handling of Insufficient Permissions or Privileges	672

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316

### Weakness Ordinalities

Primary :

### Applicable Platforms

Language : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Other	Other Alter Execution Logic	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Observed Examples

Reference	Description
<b>CVE-2001-1564</b>	System limits are not properly enforced after privileges are dropped. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1564">https://www.cve.org/CVERecord?id=CVE-2001-1564</a>
<b>CVE-2005-3286</b>	Firewall crashes when it can't read a critical memory block that was protected by a malicious process. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3286">https://www.cve.org/CVERecord?id=CVE-2005-3286</a>
<b>CVE-2005-1641</b>	Does not give admin sufficient privileges to overcome otherwise legitimate user actions. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1641">https://www.cve.org/CVERecord?id=CVE-2005-1641</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		901	SFP Primary Cluster: Privilege	888	2386
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Maintenance

CWE-280 and CWE-274 are too similar. It is likely that CWE-274 will be deprecated in the future.

#### Relationship

Overlaps dropped privileges, insufficient permissions.

#### Theoretical

This has a layering relationship with Unchecked Error Condition and Unchecked Return Value.

#### Theoretical

Within the context of vulnerability theory, privileges and permissions are two sides of the same coin. Privileges are associated with actors, and permissions are associated with resources. To perform access control, at some point the product makes a decision about whether the actor (and the privileges that have been assigned to that actor) is allowed to access the resource (based on the permissions that have been specified for that resource).

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insufficient privileges

## CWE-276: Incorrect Default Permissions

**Weakness ID :** 276

**Structure :** Simple

**Abstraction :** Base

### Description

During installation, installed file permissions are set to allow anyone to modify those files.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1551

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1551

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	2317

### Weakness Ordinalities

**Primary :**

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

**Technology :** Not Technology-Specific (*Prevalence = Undetermined*)

**Technology :** ICS/OT (*Prevalence = Undetermined*)

### Likelihood Of Exploit

Medium

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

## Detection Methods

### Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Inter-application Flow Analysis

*Effectiveness = SOAR Partial*

### Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host-based Vulnerability Scanners - Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria Web Application Scanner Web Services Scanner Database Scanners

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Host Application Interface Scanner Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer Automated Monitored Execution Forced Path Execution

*Effectiveness = High*

### Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

*Effectiveness = High*

### Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

*Effectiveness = SOAR Partial*

### Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

*Effectiveness = SOAR Partial*

### Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

*Effectiveness = High*

## Potential Mitigations



**Phase: Architecture and Design****Phase: Operation**

The architecture needs to access and modification attributes for files to only those users who actually require those actions.

**Phase: Architecture and Design**

*Strategy = Separation of Privilege*









Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.






**Observed Examples**

Reference	Description
<b>CVE-2005-1941</b>	Executables installed world-writable. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1941">https://www.cve.org/CVERecord?id=CVE-2005-1941</a>
<b>CVE-2002-1713</b>	Home directories installed world-readable. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1713">https://www.cve.org/CVERecord?id=CVE-2002-1713</a>
<b>CVE-2001-1550</b>	World-writable log files allow information loss; world-readable file has cleartext passwords. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1550">https://www.cve.org/CVERecord?id=CVE-2001-1550</a>
<b>CVE-2002-1711</b>	World-readable directory. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1711">https://www.cve.org/CVERecord?id=CVE-2002-1711</a>
<b>CVE-2002-1844</b>	Windows product uses insecure permissions when installing on Solaris (genesis: port error). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1844">https://www.cve.org/CVERecord?id=CVE-2002-1844</a>
<b>CVE-2001-0497</b>	Insecure permissions for a shared secret key file. Overlaps cryptographic problem. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0497">https://www.cve.org/CVERecord?id=CVE-2001-0497</a>
<b>CVE-1999-0426</b>	Default permissions of a device allow IP spoofing. <a href="https://www.cve.org/CVERecord?id=CVE-1999-0426">https://www.cve.org/CVERecord?id=CVE-1999-0426</a>

**MemberOf Relationships**

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	2347
MemberOf		857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	2368
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	2377
MemberOf		946	SFP Secondary Cluster: Insecure Resource Permissions	888	2394
MemberOf		1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	2450
MemberOf		1198	Privilege Separation and Access Control Issues	1194	2470
MemberOf		1337	Weaknesses in the 2021 CWE Top 25 Most Dangerous Software Weaknesses	1337	2589

Nature	Type	ID	Name	V	Page
MemberOf		1345	OWASP Top Ten 2021 Category A01:2021 - Broken Access Control	1344	2487
MemberOf		1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf		1376	ICS Engineering (Construction/Deployment): Security Gaps in Commissioning	1358	2512
MemberOf		1387	Weaknesses in the 2022 CWE Top 25 Most Dangerous Software Weaknesses	1387	2597
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519
MemberOf		1425	Weaknesses in the 2023 CWE Top 25 Most Dangerous Software Weaknesses	1425	2600

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure Default Permissions
CERT C Secure Coding	FIO06-C		Create files with appropriate access permissions
The CERT Oracle Secure Coding Standard for Java (2011)	FIO01-J		Create files with appropriate access permission
ISA/IEC 62443	Part 2-4		Req SP.03.08
ISA/IEC 62443	Part 4-2		Req CR 2.1

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
1	Accessing Functionality Not Properly Constrained by ACLs
81	Web Server Logs Tampering
127	Directory Indexing

### References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

## CWE-277: Insecure Inherited Permissions

**Weakness ID :** 277

**Structure :** Simple

**Abstraction :** Variant

### Description

A product defines a set of insecure permissions that are inherited by objects that are created by the program.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1551

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	2317

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

### Potential Mitigations

**Phase: Architecture and Design**

**Phase: Operation**

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

**Phase: Architecture and Design**

*Strategy = Separation of Privilege*




Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

### Observed Examples

Reference	Description
<b>CVE-2005-1841</b>	User's umask is used when creating temp files. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1841">https://www.cve.org/CVERecord?id=CVE-2005-1841</a>
<b>CVE-2002-1786</b>	Insecure umask for core dumps [is the umask preserved or assigned?]. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1786">https://www.cve.org/CVERecord?id=CVE-2002-1786</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		946	SFP Secondary Cluster: Insecure Resource Permissions	888	2394
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure inherited permissions

## CWE-278: Insecure Preserved Inherited Permissions

**Weakness ID :** 278

**Structure** : Simple**Abstraction** : Variant

## Description

A product inherits a set of insecure permissions for an object, e.g. when copying from an archive file, without user awareness or involvement.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1551

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	2317

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

## Potential Mitigations

### Phase: Architecture and Design

### Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

### Phase: Architecture and Design

*Strategy = Separation of Privilege*



Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

## Observed Examples

Reference	Description
<b>CVE-2005-1724</b>	Does not obey specified permissions when exporting. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1724">https://www.cve.org/CVERecord?id=CVE-2005-1724</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		946	SFP Secondary Cluster: Insecure Resource Permissions	888	2394
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure preserved inherited permissions

## CWE-279: Incorrect Execution-Assigned Permissions

**Weakness ID :** 279

**Structure :** Simple

**Abstraction :** Variant

### Description

While it is executing, the product sets the permissions of an object in a way that violates the intended permissions that have been specified by the user.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1551

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	2317

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

### Potential Mitigations

**Phase: Architecture and Design**

**Phase: Operation**

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

**Phase: Architecture and Design**

*Strategy = Separation of Privilege*







Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

### Observed Examples

Reference	Description
<b>CVE-2002-0265</b>	Log files opened read/write. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0265">https://www.cve.org/CVERecord?id=CVE-2002-0265</a>
<b>CVE-2003-0876</b>	Log files opened read/write. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0876">https://www.cve.org/CVERecord?id=CVE-2003-0876</a>
<b>CVE-2002-1694</b>	Log files opened read/write. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1694">https://www.cve.org/CVERecord?id=CVE-2002-1694</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	2347
MemberOf		857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	2368
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	2377
MemberOf		946	SFP Secondary Cluster: Insecure Resource Permissions	888	2394
MemberOf		1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	2450
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure execution-assigned permissions
CERT C Secure Coding	FIO06-C		Create files with appropriate access permissions
The CERT Oracle Secure Coding Standard for Java (2011)	FIO01-J		Create files with appropriate access permission

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
81	Web Server Logs Tampering

## CWE-280: Improper Handling of Insufficient Permissions or Privileges

Weakness ID : 280

Structure : Simple

Abstraction : Base



### Description

The product does not handle or incorrectly handles when it has insufficient privileges to access resources or functionality as specified by their permissions. This may cause it to follow unexpected code paths that may leave the product in an invalid state.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1576
PeerOf		636	Not Failing Securely ('Failing Open')	1401

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		265	Privilege Issues	2316
MemberOf		275	Permission Issues	2317

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Other	Other Alter Execution Logic	

## Potential Mitigations

### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

### Phase: Implementation

Always check to see if you have successfully accessed a resource or system functionality, and use proper error handling if it is unsuccessful. Do this even when you are operating in a highly privileged mode, because errors or environmental conditions might still cause a failure. For example, environments with highly granular permissions/privilege models, such as Windows or Linux capabilities, can cause unexpected failures.

## Observed Examples




Reference	Description
<b>CVE-2003-0501</b>	Special file system allows attackers to prevent ownership/permission change of certain entries by opening the entries before calling a setuid program. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0501">https://www.cve.org/CVERecord?id=CVE-2003-0501</a>



Reference	Description
<b>CVE-2004-0148</b>	FTP server places a user in the root directory when the user's permissions prevent access to the their own home directory. <a href="https://www.cve.org/CVERecord?id=CVE-2004-0148">https://www.cve.org/CVERecord?id=CVE-2004-0148</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		962	SFP Secondary Cluster: Unchecked Status Condition	888	2400
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Maintenance

CWE-280 and CWE-274 are too similar. It is likely that CWE-274 will be deprecated in the future.

#### Relationship

This can be both primary and resultant. When primary, it can expose a variety of weaknesses because a resource might not have the expected state, and subsequent operations might fail. It is often resultant from Unchecked Error Condition (CWE-391).

#### Theoretical

Within the context of vulnerability theory, privileges and permissions are two sides of the same coin. Privileges are associated with actors, and permissions are associated with resources. To perform access control, at some point the software makes a decision about whether the actor (and the privileges that have been assigned to that actor) is allowed to access the resource (based on the permissions that have been specified for that resource).

#### Research Gap

This type of issue is under-studied, since researchers often concentrate on whether an object has too many permissions, instead of not enough. These weaknesses are likely to appear in environments with fine-grained models for permissions and privileges, which can include operating systems and other large-scale software packages. However, even highly simplistic permission/privilege models are likely to contain these issues if the developer has not considered the possibility of access failure.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Fails poorly due to insufficient permissions
WASC	17		Improper Filesystem Permissions
Software Fault Patterns	SFP4		Unchecked Status Condition

## CWE-281: Improper Preservation of Permissions

**Weakness ID** : 281

**Structure** : Simple

**Abstraction** : Base

### Description

The product does not preserve permissions or incorrectly preserves permissions when copying, restoring, or sharing objects, which can cause them to have less restrictive permissions than intended.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1551

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1551

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	2317

## Weakness Ordinalities

**Resultant :** This is resultant from errors that prevent the permissions from being preserved.

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

## Observed Examples

Reference	Description
<b>CVE-2002-2323</b>	Incorrect ACLs used when restoring backups from directories that use symbolic links. <a href="https://www.cve.org/CVERecord?id=CVE-2002-2323">https://www.cve.org/CVERecord?id=CVE-2002-2323</a>
<b>CVE-2001-1515</b>	Automatic modification of permissions inherited from another file system. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1515">https://www.cve.org/CVERecord?id=CVE-2001-1515</a>
<b>CVE-2005-1920</b>	Permissions on backup file are created with defaults, possibly less secure than original file. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1920">https://www.cve.org/CVERecord?id=CVE-2005-1920</a>
<b>CVE-2001-0195</b>	File is made world-readable when being cloned. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0195">https://www.cve.org/CVERecord?id=CVE-2001-0195</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	<b>C</b>	946	SFP Secondary Cluster: Insecure Resource Permissions	888	2394
MemberOf	<b>C</b>	1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Permission preservation failure

## CWE-282: Improper Ownership Management

**Weakness ID :** 282

**Structure :** Simple

**Abstraction :** Class

### Description

The product assigns the wrong ownership, or does not properly verify the ownership, of an object or resource.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	<b> P </b>	284	Improper Access Control	680
ParentOf	<b>B</b>	283	Unverified Ownership	678
ParentOf	<b>B</b>	708	Incorrect Ownership Assignment	1548

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf	<b>C</b>	1011	Authorize Actors	2425

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

**Phase: Architecture and Design****Phase: Operation**

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

**Demonstrative Examples****Example 1:**

This function is part of a privileged program that takes input from users with potentially lower privileges.

Example Language: Python

(Bad)

```
def killProcess(processID):  
    os.kill(processID, signal.SIGKILL)
```

This code does not confirm that the process to be killed is owned by the requesting user, thus allowing an attacker to kill arbitrary processes.

This function remedies the problem by checking the owner of the process before killing it:

Example Language: Python

(Good)

```
def killProcess(processID):  
    user = getCurrentUser()  
    #Check process owner against requesting user  
    if getProcessOwner(processID) == user:  
        os.kill(processID, signal.SIGKILL)  
        return  
    else:  
        print("You cannot kill a process you don't own")  
        return
```

**Observed Examples**



Reference	Description
<b>CVE-1999-1125</b>	Program runs setuid root but relies on a configuration file owned by a non-root user. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1125">https://www.cve.org/CVERecord?id=CVE-1999-1125</a>

**Affected Resources**

- File or Directory

**MemberOf Relationships**

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		944	SFP Secondary Cluster: Access Management	888	2393
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

**Notes****Maintenance**

The relationships between privileges, permissions, and actors (e.g. users and groups) need further refinement within the Research view. One complication is that these concepts apply to two different pillars, related to control of resources (CWE-664) and protection mechanism failures (CWE-693).

**Taxonomy Mappings**

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Ownership errors

#### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
17	Using Malicious Files
35	Leverage Executable Code in Non-Executable Files

## CWE-283: Unverified Ownership

**Weakness ID :** 283

**Structure :** Simple

**Abstraction :** Base

### Description

The product does not properly verify that a critical resource is owned by the proper entity.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		282	Improper Ownership Management	676

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		840	Business Logic Errors	2360

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  <i>An attacker could gain unauthorized access to system resources.</i>	

### Potential Mitigations

**Phase: Architecture and Design**

**Phase: Operation**

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

**Phase: Architecture and Design**

*Strategy = Separation of Privilege*

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

## Demonstrative Examples

### Example 1:

This function is part of a privileged program that takes input from users with potentially lower privileges.

Example Language: Python

(Bad)

```
def killProcess(processID):
    os.kill(processID, signal.SIGKILL)
```

This code does not confirm that the process to be killed is owned by the requesting user, thus allowing an attacker to kill arbitrary processes.

This function remedies the problem by checking the owner of the process before killing it:

Example Language: Python

(Good)






```
def killProcess(processID):
    user = getCurrentUser()
    #Check process owner against requesting user
    if getProcessOwner(processID) == user:
        os.kill(processID, signal.SIGKILL)
        return
    else:
        print("You cannot kill a process you don't own")
        return
```

## Observed Examples

Reference	Description
<b>CVE-2001-0178</b>	Program does not verify the owner of a UNIX socket that is used for sending a password. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0178">https://www.cve.org/CVERecord?id=CVE-2001-0178</a>
<b>CVE-2004-2012</b>	Owner of special device not checked, allowing root. <a href="https://www.cve.org/CVERecord?id=CVE-2004-2012">https://www.cve.org/CVERecord?id=CVE-2004-2012</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	2335
MemberOf		884	CWE Cross-section	884	2567
MemberOf		944	SFP Secondary Cluster: Access Management	888	2393
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

## Notes

### Relationship

This overlaps insufficient comparison, verification errors, permissions, and privileges.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unverified Ownership

## CWE-284: Improper Access Control

**Weakness ID** : 284  
**Structure** : Simple  
**Abstraction** : Pillar

### Description

The product does not restrict or incorrectly restricts access to a resource from an unauthorized actor.

### Extended Description

Access control involves the use of several protection mechanisms such as:

- Authentication (proving the identity of an actor)
- Authorization (ensuring that a given actor can access a resource), and
- Accountability (tracking of activities that were performed)

When any mechanism is not applied or otherwise fails, attackers can compromise the security of the product by gaining privileges, reading sensitive information, executing commands, evading detection, etc.













There are two distinct behaviors that can introduce access control weaknesses:

- Specification: incorrect privileges, permissions, ownership, etc. are explicitly specified for either the user or the resource (for example, setting a password file to be world-writable, or giving administrator capabilities to a guest user). This action could be performed by the program or the administrator.
- Enforcement: the mechanism contains errors that prevent it from properly enforcing the specified access control requirements (e.g., allowing the user to specify their own privileges, or allowing a syntactically-incorrect ACL to produce insecure settings). This problem occurs within the program itself, in that it does not actually enforce the intended security policy that the administrator specifies.






























### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
MemberOf		1000	Research Concepts	2575
ParentOf		269	Improper Privilege Management	646
ParentOf		282	Improper Ownership Management	676
ParentOf		285	Improper Authorization	684
ParentOf		286	Incorrect User Management	691
ParentOf		287	Improper Authentication	692
ParentOf		346	Origin Validation Error	853
ParentOf		749	Exposed Dangerous Method or Function	1564
ParentOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1827
ParentOf		1191	On-Chip Debug and Test Interface With Improper Access Control	1980
ParentOf		1220	Insufficient Granularity of Access Control	1992
ParentOf		1224	Improper Restriction of Write-Once Bit Fields	2003








Nature	Type	ID	Name	Page
ParentOf		1231	Improper Prevention of Lock Bit Modification	2007
ParentOf		1233	Security-Sensitive Hardware Controls with Missing Lock Bit Protection	2012
ParentOf		1242	Inclusion of Undocumented Features or Chicken Bits	2033
ParentOf		1252	CPU Hardware Not Configured to Support Exclusivity of Write and Execute Operations	2056
ParentOf		1257	Improper Access Control Applied to Mirrored or Aliased Memory Regions	2068
ParentOf		1259	Improper Restriction of Security Token Assignment	2073
ParentOf		1260	Improper Handling of Overlap Between Protected Memory Ranges	2075
ParentOf		1262	Improper Access Control for Register Interface	2081
ParentOf		1263	Improper Physical Access Control	2085
ParentOf		1267	Policy Uses Obsolete Encoding	2093
ParentOf		1268	Policy Privileges are not Assigned Consistently Between Control and Data Agents	2095
ParentOf		1270	Generation of Incorrect Security Tokens	2100
ParentOf		1274	Improper Access Control for Volatile Memory Containing Boot Code	2108
ParentOf		1276	Hardware Child Block Incorrectly Connected to Parent System	2113
ParentOf		1280	Access Control Check Implemented After Asset is Accessed	2122
ParentOf		1283	Mutable Attestation or Measurement Reporting Data	2128
ParentOf		1290	Incorrect Decoding of Security Identifiers	2142
ParentOf		1292	Incorrect Conversion of Security Identifiers	2147
ParentOf		1294	Insecure Security Identifier Mechanism	2150
ParentOf		1296	Incorrect Chaining or Granularity of Debug Components	2153
ParentOf		1304	Improperly Preserved Integrity of Hardware Configuration State During a Power Save/Restore Operation	2176
ParentOf		1311	Improper Translation of Security Attributes by Fabric Bridge	2182
ParentOf		1312	Missing Protection for Mirrored Regions in On-Chip Fabric Firewall	2184
ParentOf		1313	Hardware Allows Activation of Test or Debug Logic at Runtime	2185
ParentOf		1315	Improper Setting of Bus Controlling Capability in Fabric End-point	2190
ParentOf		1316	Fabric-Address Map Allows Programming of Unwarranted Overlaps of Protected and Unprotected Ranges	2192
ParentOf		1317	Improper Access Control in Fabric Bridge	2194
ParentOf		1320	Improper Protection for Outbound Error Messages and Alert Signals	2202
ParentOf		1323	Improper Management of Sensitive Trace Data	2208
ParentOf		1334	Unauthorized Error Injection Can Degrade Hardware Redundancy	2234

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

*Relevant to the view "CISQ Data Protection Measures" (CWE-1340)*

Nature	Type	ID	Name	Page
ParentOf		285	Improper Authorization	684

Nature	Type	ID	Name	Page
ParentOf		287	Improper Authentication	692
ParentOf		288	Authentication Bypass Using an Alternate Path or Channel	700
ParentOf		639	Authorization Bypass Through User-Controlled Key	1406
ParentOf		862	Missing Authorization	1780
ParentOf		863	Incorrect Authorization	1787

### Applicable Platforms

**Technology** : Not Technology-Specific (*Prevalence = Undetermined*)

**Technology** : ICS/OT (*Prevalence = Undetermined*)

### Alternate Terms

**Authorization** : The terms "access control" and "authorization" are often used interchangeably, although many people have distinct definitions. The CWE usage of "access control" is intended as a general term for the various mechanisms that restrict which users can access which resources, and "authorization" is more narrowly defined. It is unlikely that there will be community consensus on the use of these terms.

### Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

### Potential Mitigations

#### Phase: Architecture and Design

#### Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

#### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

### Observed Examples

Reference	Description
<b>CVE-2022-24985</b>	A form hosting website only checks the session authentication status for a single form, making it possible to bypass authentication when there are multiple forms <a href="https://www.cve.org/CVERecord?id=CVE-2022-24985">https://www.cve.org/CVERecord?id=CVE-2022-24985</a>
<b>CVE-2022-29238</b>	Access-control setting in web-based document collaboration tool is not properly implemented by the code, which prevents listing hidden directories but does not prevent direct requests to files in those directories. <a href="https://www.cve.org/CVERecord?id=CVE-2022-29238">https://www.cve.org/CVERecord?id=CVE-2022-29238</a>
<b>CVE-2022-23607</b>	Python-based HTTP library did not scope cookies to a particular domain such that "supercookies" could be sent to any domain on redirect <a href="https://www.cve.org/CVERecord?id=CVE-2022-23607">https://www.cve.org/CVERecord?id=CVE-2022-23607</a>
<b>CVE-2021-21972</b>	Chain: Cloud computing virtualization platform does not require authentication for upload of a tar format file (CWE-306), then uses .. path traversal sequences










Reference	Description
	(CWE-23) in the file to access unexpected files, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2021-21972">https://www.cve.org/CVERecord?id=CVE-2021-21972</a>
<b>CVE-2021-37415</b>	IT management product does not perform authentication for some REST API requests, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2021-37415">https://www.cve.org/CVERecord?id=CVE-2021-37415</a>
<b>CVE-2021-35033</b>	Firmware for a WiFi router uses a hard-coded password for a BusyBox shell, allowing bypass of authentication through the UART port <a href="https://www.cve.org/CVERecord?id=CVE-2021-35033">https://www.cve.org/CVERecord?id=CVE-2021-35033</a>
<b>CVE-2020-10263</b>	Bluetooth speaker does not require authentication for the debug functionality on the UART port, allowing root shell access <a href="https://www.cve.org/CVERecord?id=CVE-2020-10263">https://www.cve.org/CVERecord?id=CVE-2020-10263</a>
<b>CVE-2020-13927</b>	Default setting in workflow management product allows all API requests without authentication, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2020-13927">https://www.cve.org/CVERecord?id=CVE-2020-13927</a>
<b>CVE-2010-4624</b>	Bulletin board applies restrictions on number of images during post creation, but does not enforce this on editing. <a href="https://www.cve.org/CVERecord?id=CVE-2010-4624">https://www.cve.org/CVERecord?id=CVE-2010-4624</a>

### Affected Resources

- File or Directory

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		254	7PK - Security Features	700	2314
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	2335
MemberOf		944	SFP Secondary Cluster: Access Management	888	2393
MemberOf		1031	OWASP Top Ten 2017 Category A5 - Broken Access Control	1026	2437
MemberOf		1340	CISQ Data Protection Measures	1340	2590
MemberOf		1345	OWASP Top Ten 2021 Category A01:2021 - Broken Access Control	1344	2487
MemberOf		1369	ICS Supply Chain: IT/OT Convergence/Expansion	1358	2506
MemberOf		1372	ICS Supply Chain: OT Counterfeit and Malicious Corruption	1358	2509
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Maintenance

This entry needs more work. Possible sub-categories include: Trusted group includes undesired entities (partially covered by CWE-286) Group can perform undesired actions ACL parse error does not fail closed

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Access Control List (ACL) errors
WASC	2		Insufficient Authorization
7 Pernicious Kingdoms			Missing Access Control

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
19	Embedding Scripts within Scripts
441	Malicious Logic Insertion
478	Modification of Windows Service Configuration
479	Malicious Root Certificate
502	Intent Spoof
503	WebView Exposure
536	Data Injected During Configuration
546	Incomplete Data Deletion in a Multi-Tenant Environment
550	Install New Service
551	Modify Existing Service
552	Install Rootkit
556	Replace File Extension Handlers
558	Replace Trusted Executable
562	Modify Shared File
563	Add Malicious File to Shared Webroot
564	Run Software at Logon
578	Disable Security Software

## References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-1287]MITRE. "Supplemental Details - 2022 CWE Top 25". 2022 June 8. < [https://cwe.mitre.org/top25/archive/2022/2022\\_cwe\\_top25\\_supplemental.html#problematicMappingDetails](https://cwe.mitre.org/top25/archive/2022/2022_cwe_top25_supplemental.html#problematicMappingDetails) >.

## CWE-285: Improper Authorization

**Weakness ID :** 285

**Structure :** Simple

**Abstraction :** Class

### Description

The product does not perform or incorrectly performs an authorization check when an actor attempts to access a resource or perform an action.

### Extended Description

Assuming a user with a given identity, authorization is the process of determining whether that user can access a given resource, based on the user's privileges and any permissions or other access-control specifications that apply to the resource.

When access control checks are not applied consistently - or not at all - users are able to access data or perform actions that they should not be allowed to perform. This can lead to a wide range of problems, including information exposures, denial of service, and arbitrary code execution.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	P	284	Improper Access Control	680
ParentOf	B	552	Files or Directories Accessible to External Parties	1265
ParentOf	C	732	Incorrect Permission Assignment for Critical Resource	1551
ParentOf	C	862	Missing Authorization	1780
ParentOf	C	863	Incorrect Authorization	1787
ParentOf	V	926	Improper Export of Android Application Components	1833
ParentOf	V	927	Use of Implicit Intent for Sensitive Communication	1836
ParentOf	B	1230	Exposure of Sensitive Information Through Metadata	2006
ParentOf	B	1256	Improper Restriction of Software Interfaces to Hardware Features	2065
ParentOf	B	1297	Unprotected Confidential Information on Device is Accessible by OSAT Vendors	2156
ParentOf	B	1328	Security Version Number Mutable to Older Versions	2217

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	2425

*Relevant to the view "CISQ Data Protection Measures" (CWE-1340)*

Nature	Type	ID	Name	Page
ChildOf	P	284	Improper Access Control	680

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : Web Server (*Prevalence = Often*)

**Technology** : Database Server (*Prevalence = Often*)

### Background Details

An access control list (ACL) represents who/what has permissions to a given object. Different operating systems implement (ACLs) in different ways. In UNIX, there are three types of permissions: read, write, and execute. Users are divided into three classes for file access: owner, group owner, and all other users where each class has a separate set of rights. In Windows NT, there are four basic types of permissions for files: "No access", "Read access", "Change access", and "Full control". Windows NT extends the concept of three types of users in UNIX to include a list of users and groups along with their associated permissions. A user can create an object (file) and assign specified permissions to that object.

### Alternate Terms

**AuthZ** : "AuthZ" is typically used as an abbreviation of "authorization" within the web application security community. It is distinct from "AuthN" (or, sometimes, "AuthC") which is an abbreviation of "authentication." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Scope	Impact	Likelihood
Integrity	Read Files or Directories	<p>An attacker could read sensitive data, either by reading the data directly from a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to read the data.</p>
	Modify Application Data Modify Files or Directories	
Access Control	Gain Privileges or Assume Identity	<p>An attacker could gain privileges by modifying or reading critical data directly, or by accessing insufficiently-protected, privileged functionality.</p>

## Detection Methods

### Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authorization. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authorization libraries. Generally, automated static analysis tools have difficulty detecting custom authorization schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an authorization check; an automated technique that detects the absence of authorization may report false positives.

*Effectiveness = Limited*

### Automated Dynamic Analysis

Automated dynamic analysis may find many or all possible interfaces that do not require authorization, but manual analysis is required to determine if the lack of authorization violates business logic

### Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of custom authorization mechanisms.

*Effectiveness = Moderate*

*These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules. However, manual efforts might not achieve desired code coverage within limited time constraints.*

### Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners



*Effectiveness = SOAR Partial*

### **Dynamic Analysis with Manual Results Interpretation**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host Application Interface Scanner Fuzz Tester Framework-based Fuzzer Forced Path Execution Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

*Effectiveness = SOAR Partial*

### **Manual Static Analysis - Source Code**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

*Effectiveness = SOAR Partial*

### **Automated Static Analysis - Source Code**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

*Effectiveness = SOAR Partial*

### **Architecture or Design Review**

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

*Effectiveness = High*

## **Potential Mitigations**

### **Phase: Architecture and Design**

Divide the product into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully mapping roles with data and functionality. Use role-based access control (RBAC) to enforce the roles at the appropriate boundaries. Note that this approach may not protect against horizontal authorization, i.e., it will not protect a user from attacking others with the same role.

### **Phase: Architecture and Design**

Ensure that you perform access control checks related to your business logic. These checks may be different than the access control checks that you apply to more generic resources such as files, connections, processes, memory, and database records. For example, a database may restrict access for medical records to a specific database user, but each record might only be intended to be accessible to the patient and the patient's doctor.

### **Phase: Architecture and Design**

*Strategy = Libraries or Frameworks*

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using authorization frameworks such as the JAAS Authorization Framework [REF-233] and the OWASP ESAPI Access Control feature [REF-45].

### **Phase: Architecture and Design**

For web applications, make sure that the access control mechanism is enforced correctly at the server side on every page. Users should not be able to access any unauthorized functionality or information by simply requesting direct access to that page. One way to do this is to ensure that all pages containing sensitive information are not cached, and that all such pages restrict access



to requests that are accompanied by an active and authenticated session token associated with a user who has the required permissions to access that page.

### Phase: System Configuration

#### Phase: Installation

Use the access control capabilities of your operating system and server environment and define your access control lists accordingly. Use a "default deny" policy when defining these ACLs.

### Demonstrative Examples

#### Example 1:

This function runs an arbitrary SQL query on a given database, returning the result of the query.

*Example Language: PHP*

*(Bad)*

```
function runEmployeeQuery($dbName, $name){
    mysql_select_db($dbName,$globalDbHandle) or die("Could not open Database ".$dbName);
    //Use a prepared statement to avoid CWE-89
    $preparedStatement = $globalDbHandle->prepare('SELECT * FROM employees WHERE name = :name');
    $preparedStatement->execute(array(':name' => $name));
    return $preparedStatement->fetchAll();
}
//.../
$employeeRecord = runEmployeeQuery('EmployeeDB',$_GET['EmployeeName']);
```

While this code is careful to avoid SQL Injection, the function does not confirm the user sending the query is authorized to do so. An attacker may be able to obtain sensitive employee information from the database.

#### Example 2:

The following program could be part of a bulletin board system that allows users to send private messages to each other. This program intends to authenticate the user before deciding whether a private message should be displayed. Assume that `LookupMessageObject()` ensures that the `$id` argument is numeric, constructs a filename based on that id, and reads the message details from that file. Also assume that the program stores all private messages for all users in the same directory.

*Example Language: Perl*

*(Bad)*

```
sub DisplayPrivateMessage {
    my($id) = @_;
    my $Message = LookupMessageObject($id);
    print "From: " . encodeHTML($Message->{from}) . "<br>\n";
    print "Subject: " . encodeHTML($Message->{subject}) . "\n";
    print "<hr>\n";
    print "Body: " . encodeHTML($Message->{body}) . "\n";
}
my $q = new CGI;
# For purposes of this example, assume that CWE-309 and
# CWE-523 do not apply.
if (!AuthenticateUser($q->param('username'), $q->param('password'))) {
    ExitError("invalid username or password");
}
my $id = $q->param('id');
DisplayPrivateMessage($id);
```

While the program properly exits if authentication fails, it does not ensure that the message is addressed to the user. As a result, an authenticated attacker could provide any arbitrary identifier and read private messages that were intended for other users.

One way to avoid this problem would be to ensure that the "to" field in the message object matches the username of the authenticated user.

## Observed Examples

Reference	Description
<b>CVE-2022-24730</b>	Go-based continuous deployment product does not check that a user has certain privileges to update or create an app, allowing adversaries to read sensitive repository information <a href="https://www.cve.org/CVERecord?id=CVE-2022-24730">https://www.cve.org/CVERecord?id=CVE-2022-24730</a>
<b>CVE-2009-3168</b>	Web application does not restrict access to admin scripts, allowing authenticated users to reset administrative passwords. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3168">https://www.cve.org/CVERecord?id=CVE-2009-3168</a>
<b>CVE-2009-2960</b>	Web application does not restrict access to admin scripts, allowing authenticated users to modify passwords of other users. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2960">https://www.cve.org/CVERecord?id=CVE-2009-2960</a>
<b>CVE-2009-3597</b>	Web application stores database file under the web root with insufficient access control (CWE-219), allowing direct request. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3597">https://www.cve.org/CVERecord?id=CVE-2009-3597</a>
<b>CVE-2009-2282</b>	Terminal server does not check authorization for guest access. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2282">https://www.cve.org/CVERecord?id=CVE-2009-2282</a>
<b>CVE-2009-3230</b>	Database server does not use appropriate privileges for certain sensitive operations. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3230">https://www.cve.org/CVERecord?id=CVE-2009-3230</a>
<b>CVE-2009-2213</b>	Gateway uses default "Allow" configuration for its authorization settings. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2213">https://www.cve.org/CVERecord?id=CVE-2009-2213</a>
<b>CVE-2009-0034</b>	Chain: product does not properly interpret a configuration option for a system group, allowing users to gain privileges. <a href="https://www.cve.org/CVERecord?id=CVE-2009-0034">https://www.cve.org/CVERecord?id=CVE-2009-0034</a>
<b>CVE-2008-6123</b>	Chain: SNMP product does not properly parse a configuration option for which hosts are allowed to connect, allowing unauthorized IP addresses to connect. <a href="https://www.cve.org/CVERecord?id=CVE-2008-6123">https://www.cve.org/CVERecord?id=CVE-2008-6123</a>
<b>CVE-2008-5027</b>	System monitoring software allows users to bypass authorization by creating custom forms. <a href="https://www.cve.org/CVERecord?id=CVE-2008-5027">https://www.cve.org/CVERecord?id=CVE-2008-5027</a>
<b>CVE-2008-7109</b>	Chain: reliance on client-side security (CWE-602) allows attackers to bypass authorization using a custom client. <a href="https://www.cve.org/CVERecord?id=CVE-2008-7109">https://www.cve.org/CVERecord?id=CVE-2008-7109</a>
<b>CVE-2008-3424</b>	Chain: product does not properly handle wildcards in an authorization policy list, allowing unintended access. <a href="https://www.cve.org/CVERecord?id=CVE-2008-3424">https://www.cve.org/CVERecord?id=CVE-2008-3424</a>
<b>CVE-2009-3781</b>	Content management system does not check access permissions for private files, allowing others to view those files. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3781">https://www.cve.org/CVERecord?id=CVE-2009-3781</a>
<b>CVE-2008-4577</b>	ACL-based protection mechanism treats negative access rights as if they are positive, allowing bypass of intended restrictions. <a href="https://www.cve.org/CVERecord?id=CVE-2008-4577">https://www.cve.org/CVERecord?id=CVE-2008-4577</a>
<b>CVE-2008-6548</b>	Product does not check the ACL of a page accessed using an "include" directive, allowing attackers to read unauthorized files. <a href="https://www.cve.org/CVERecord?id=CVE-2008-6548">https://www.cve.org/CVERecord?id=CVE-2008-6548</a>
<b>CVE-2007-2925</b>	Default ACL list for a DNS server does not set certain ACLs, allowing unauthorized DNS queries. <a href="https://www.cve.org/CVERecord?id=CVE-2007-2925">https://www.cve.org/CVERecord?id=CVE-2007-2925</a>
<b>CVE-2006-6679</b>	Product relies on the X-Forwarded-For HTTP header for authorization, allowing unintended access by spoofing the header. <a href="https://www.cve.org/CVERecord?id=CVE-2006-6679">https://www.cve.org/CVERecord?id=CVE-2006-6679</a>
<b>CVE-2005-3623</b>	OS kernel does not check for a certain privilege before setting ACLs for files. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3623">https://www.cve.org/CVERecord?id=CVE-2005-3623</a>

Reference	Description
<b>CVE-2005-2801</b>	Chain: file-system code performs an incorrect comparison (CWE-697), preventing default ACLs from being properly applied. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2801">https://www.cve.org/CVERecord?id=CVE-2005-2801</a>
<b>CVE-2001-1155</b>	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1155">https://www.cve.org/CVERecord?id=CVE-2001-1155</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	2314
MemberOf	C	721	OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access	629	2333
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	2335
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	2353
MemberOf	C	803	2010 Top 25 - Porous Defenses	800	2355
MemberOf	C	817	OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access	809	2359
MemberOf	C	935	OWASP Top Ten 2013 Category A7 - Missing Function Level Access Control	928	2392
MemberOf	C	945	SFP Secondary Cluster: Insecure Resource Access	888	2394
MemberOf	C	1031	OWASP Top Ten 2017 Category A5 - Broken Access Control	1026	2437
MemberOf	C	1345	OWASP Top Ten 2021 Category A01:2021 - Broken Access Control	1344	2487
MemberOf	C	1382	ICS Operations (& Maintenance): Emerging Energy Technologies	1358	2517
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Missing Access Control
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control
Software Fault Patterns	SFP35		Insecure resource access

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
1	Accessing Functionality Not Properly Constrained by ACLs
5	Blue Boxing
13	Subverting Environment Variable Values
17	Using Malicious Files
39	Manipulating Opaque Client-based Data Tokens
45	Buffer Overflow via Symbolic Links
51	Poison Web Service Registry
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)
76	Manipulating Web Input to File System Calls

CAPEC-ID	Attack Pattern Name
77	Manipulating User-Controlled Variables
87	Forceful Browsing
104	Cross Zone Scripting
127	Directory Indexing
402	Bypassing ATA Password Security
647	Collect Data from Registries
668	Key Negotiation of Bluetooth Attack (KNOB)

## References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". NIST Workshop on Software Security Assurance Tools Techniques and Metrics. 2005 November 7. NIST. < [https://samate.nist.gov/SSATTM\\_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf](https://samate.nist.gov/SSATTM_Content/papers/Seven%20Pernicious%20Kingdoms%20-%20Taxonomy%20of%20Sw%20Security%20Errors%20-%20Tsipenyuk%20-%20Chess%20-%20McGraw.pdf) >.

[REF-229]NIST. "Role Based Access Control and Role Based Security". < <https://csrc.nist.gov/projects/role-based-access-control> >.2023-04-07.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-231]Frank Kim. "Top 25 Series - Rank 5 - Improper Access Control (Authorization)". 2010 March 4. SANS Software Security Institute. < <https://www.sans.org/blog/top-25-series-rank-5-improper-access-control-authorization/> >.2023-04-07.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

[REF-233]Rahul Bhattacharjee. "Authentication using JAAS". < <https://javaranch.com/journal/2008/04/authentication-using-JAAS.html> >.2023-04-07.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

## CWE-286: Incorrect User Management

**Weakness ID** : 286

**Structure** : Simple

**Abstraction** : Class

### Description

The product does not properly manage a user within its environment.

### Extended Description

Users can be assigned to the wrong group (class) of permissions resulting in unintended access rights to sensitive objects.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	I	284	Improper Access Control	680
ParentOf	E	842	Placement of User into Incorrect Group	1775

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	2425

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

## Observed Examples

Reference	Description
<b>CVE-2022-36109</b>	Containerization product does not record a user's supplementary group ID, allowing bypass of group restrictions. <a href="https://www.cve.org/CVERecord?id=CVE-2022-36109">https://www.cve.org/CVERecord?id=CVE-2022-36109</a>
<b>CVE-1999-1193</b>	Operating system assigns user to privileged wheel group, allowing the user to gain root privileges. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1193">https://www.cve.org/CVERecord?id=CVE-1999-1193</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	944	SFP Secondary Cluster: Access Management	888	2393
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

## Notes

### Maintenance

The relationships between privileges, permissions, and actors (e.g. users and groups) need further refinement within the Research view. One complication is that these concepts apply to two different pillars, related to control of resources (CWE-664) and protection mechanism failures (CWE-693).

### Maintenance

This item needs more work. Possible sub-categories include: user in wrong group, and user with insecure profile or "configuration". It also might be better expressed as a category than a weakness.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			User management errors

## CWE-287: Improper Authentication

**Weakness ID** : 287

**Structure** : Simple

**Abstraction** : Class

## Description

When an actor claims to have a given identity, the product does not prove or insufficiently proves that the claim is correct.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	P	284	Improper Access Control	680
ParentOf	B	295	Improper Certificate Validation	714
ParentOf	B	306	Missing Authentication for Critical Function	741
ParentOf	B	645	Overly Restrictive Account Lockout Mechanism	1423
ParentOf	C	1390	Weak Authentication	2267
CanFollow	B	613	Insufficient Session Expiration	1371

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ParentOf	B	290	Authentication Bypass by Spoofing	705
ParentOf	B	294	Authentication Bypass by Capture-replay	712
ParentOf	B	295	Improper Certificate Validation	714
ParentOf	B	306	Missing Authentication for Critical Function	741
ParentOf	B	307	Improper Restriction of Excessive Authentication Attempts	747
ParentOf	B	521	Weak Password Requirements	1223
ParentOf	C	522	Insufficiently Protected Credentials	1225
ParentOf	B	640	Weak Password Recovery Mechanism for Forgotten Password	1409
ParentOf	B	798	Use of Hard-coded Credentials	1690

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf	C	1010	Authenticate Actors	2424

*Relevant to the view "CISQ Data Protection Measures" (CWE-1340)*

Nature	Type	ID	Name	Page
ChildOf	P	284	Improper Access Control	680

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : ICS/OT (*Prevalence = Often*)

## Alternate Terms

**authentication** : An alternate term is "authentification", which appears to be most commonly used by people from non-English-speaking countries.

**AuthN** : "AuthN" is typically used as an abbreviation of "authentication" within the web application security community. It is also distinct from "AuthZ," which is an abbreviation of "authorization." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.



**AuthC** : "AuthC" is used as an abbreviation of "authentication," but it appears to be used less frequently than "AuthN."

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Integrity	Read Application Data	
Confidentiality	Gain Privileges or Assume Identity	
Availability	Execute Unauthorized Code or Commands	
Access Control	<i>This weakness can lead to the exposure of resources or functionality to unintended actors, possibly providing attackers with sensitive information or even execute arbitrary code.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis is useful for detecting certain types of authentication. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authentication libraries. Generally, automated static analysis tools have difficulty detecting custom authentication schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an established identity; an automated technique that detects the absence of authentication may report false positives.

*Effectiveness = Limited*

#### Manual Static Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Manual static analysis is useful for evaluating the correctness of custom authentication mechanisms.

*Effectiveness = High*

*These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.*

#### Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

*Effectiveness = SOAR Partial*

#### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

*Effectiveness = SOAR Partial*

#### Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

*Effectiveness = SOAR Partial*

#### Manual Static Analysis - Source Code



According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Manual Source Code Review (not inspections)

*Effectiveness = SOAR Partial*

### Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

*Effectiveness = SOAR Partial*

### Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

*Effectiveness = SOAR Partial*

### Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

*Strategy = Libraries or Frameworks*

Use an authentication framework or library such as the OWASP ESAPI Authentication feature.

## Demonstrative Examples

### Example 1:

The following code intends to ensure that the user is already logged in. If not, the code performs authentication with the user-provided username and password. If successful, it sets the loggedin and user cookies to "remember" that the user has already logged in. Finally, the code performs administrator tasks if the logged-in user has the "Administrator" username, as recorded in the user cookie.

*Example Language: Perl*

*(Bad)*

```
my $q = new CGI;
if ($q->cookie('loggedin') ne "true") {
    if (! AuthenticateUser($q->param('username'), $q->param('password'))) {
        ExitError("Error: you need to log in first");
    }
    else {
        # Set loggedin and user cookies.
        $q->cookie(
            -name => 'loggedin',
            -value => 'true'
        );
        $q->cookie(
            -name => 'user',
            -value => $q->param('username')
        );
    }
}
if ($q->cookie('user') eq "Administrator") {
    DoAdministratorTasks();
}
```

Unfortunately, this code can be bypassed. The attacker can set the cookies independently so that the code does not check the username and password. The attacker could do this with an HTTP request containing headers such as:

Example Language:

(Attack)

```
GET /cgi-bin/vulnerable.cgi HTTP/1.1
Cookie: user=Administrator
Cookie: loggedin=true
[body of request]
```

By setting the loggedin cookie to "true", the attacker bypasses the entire authentication check. By using the "Administrator" value in the user cookie, the attacker also gains privileges to administer the software.

### Example 2:

In January 2009, an attacker was able to gain administrator access to a Twitter server because the server did not restrict the number of login attempts [REF-236]. The attacker targeted a member of Twitter's support team and was able to successfully guess the member's password using a brute force attack by guessing a large number of common words. After gaining access as the member of the support staff, the attacker used the administrator panel to gain access to 33 accounts that belonged to celebrities and politicians. Ultimately, fake Twitter messages were sent that appeared to come from the compromised accounts.

### Example 3:

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.

Multiple vendors did not use any authentication or used client-side authentication for critical functionality in their OT products.

## Observed Examples

Reference	Description
<b>CVE-2022-35248</b>	Chat application skips validation when Central Authentication Service (CAS) is enabled, effectively removing the second factor from two-factor authentication <a href="https://www.cve.org/CVERecord?id=CVE-2022-35248">https://www.cve.org/CVERecord?id=CVE-2022-35248</a>
<b>CVE-2022-36436</b>	Python-based authentication proxy does not enforce password authentication during the initial handshake, allowing the client to bypass authentication by specifying a 'None' authentication type. <a href="https://www.cve.org/CVERecord?id=CVE-2022-36436">https://www.cve.org/CVERecord?id=CVE-2022-36436</a>
<b>CVE-2022-30034</b>	Chain: Web UI for a Python RPC framework does not use regex anchors to validate user login emails (CWE-777), potentially allowing bypass of OAuth (CWE-1390). <a href="https://www.cve.org/CVERecord?id=CVE-2022-30034">https://www.cve.org/CVERecord?id=CVE-2022-30034</a>
<b>CVE-2022-29951</b>	TCP-based protocol in Programmable Logic Controller (PLC) has no authentication. <a href="https://www.cve.org/CVERecord?id=CVE-2022-29951">https://www.cve.org/CVERecord?id=CVE-2022-29951</a>
<b>CVE-2022-29952</b>	Condition Monitor uses a protocol that does not require authentication. <a href="https://www.cve.org/CVERecord?id=CVE-2022-29952">https://www.cve.org/CVERecord?id=CVE-2022-29952</a>
<b>CVE-2022-30313</b>	Safety Instrumented System uses proprietary TCP protocols with no authentication. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30313">https://www.cve.org/CVERecord?id=CVE-2022-30313</a>
<b>CVE-2022-30317</b>	Distributed Control System (DCS) uses a protocol that has no authentication.

Reference	Description
	<a href="https://www.cve.org/CVERecord?id=CVE-2022-30317">https://www.cve.org/CVERecord?id=CVE-2022-30317</a>
<b>CVE-2022-33139</b>	SCADA system only uses client-side authentication, allowing adversaries to impersonate other users. <a href="https://www.cve.org/CVERecord?id=CVE-2022-33139">https://www.cve.org/CVERecord?id=CVE-2022-33139</a>
<b>CVE-2021-3116</b>	Chain: Python-based HTTP Proxy server uses the wrong boolean operators (CWE-480) causing an incorrect comparison (CWE-697) that identifies an authN failure if all three conditions are met instead of only one, allowing bypass of the proxy authentication (CWE-1390) <a href="https://www.cve.org/CVERecord?id=CVE-2021-3116">https://www.cve.org/CVERecord?id=CVE-2021-3116</a>
<b>CVE-2021-21972</b>	Chain: Cloud computing virtualization platform does not require authentication for upload of a tar format file (CWE-306), then uses .. path traversal sequences (CWE-23) in the file to access unexpected files, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2021-21972">https://www.cve.org/CVERecord?id=CVE-2021-21972</a>
<b>CVE-2021-37415</b>	IT management product does not perform authentication for some REST API requests, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2021-37415">https://www.cve.org/CVERecord?id=CVE-2021-37415</a>
<b>CVE-2021-35033</b>	Firmware for a WiFi router uses a hard-coded password for a BusyBox shell, allowing bypass of authentication through the UART port <a href="https://www.cve.org/CVERecord?id=CVE-2021-35033">https://www.cve.org/CVERecord?id=CVE-2021-35033</a>
<b>CVE-2020-10263</b>	Bluetooth speaker does not require authentication for the debug functionality on the UART port, allowing root shell access <a href="https://www.cve.org/CVERecord?id=CVE-2020-10263">https://www.cve.org/CVERecord?id=CVE-2020-10263</a>
<b>CVE-2020-13927</b>	Default setting in workflow management product allows all API requests without authentication, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2020-13927">https://www.cve.org/CVERecord?id=CVE-2020-13927</a>
<b>CVE-2021-35395</b>	Stack-based buffer overflows in SFK for wifi chipset used for IoT/embedded devices, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2021-35395">https://www.cve.org/CVERecord?id=CVE-2021-35395</a>
<b>CVE-2021-34523</b>	Mail server does not properly check an access token before executing a Powershell command, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2021-34523">https://www.cve.org/CVERecord?id=CVE-2021-34523</a>
<b>CVE-2020-12812</b>	Chain: user is not prompted for a second authentication factor (CWE-287) when changing the case of their username (CWE-178), as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2020-12812">https://www.cve.org/CVERecord?id=CVE-2020-12812</a>
<b>CVE-2020-10148</b>	Authentication bypass by appending specific parameters and values to a URI, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2020-10148">https://www.cve.org/CVERecord?id=CVE-2020-10148</a>
<b>CVE-2020-0688</b>	Mail server does not generate a unique key during installation, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2020-0688">https://www.cve.org/CVERecord?id=CVE-2020-0688</a>
<b>CVE-2017-14623</b>	LDAP Go package allows authentication bypass using an empty password, causing an unauthenticated LDAP bind <a href="https://www.cve.org/CVERecord?id=CVE-2017-14623">https://www.cve.org/CVERecord?id=CVE-2017-14623</a>
<b>CVE-2009-3421</b>	login script for guestbook allows bypassing authentication by setting a "login_ok" parameter to 1. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3421">https://www.cve.org/CVERecord?id=CVE-2009-3421</a>
<b>CVE-2009-2382</b>	admin script allows authentication bypass by setting a cookie value to "LOGGEDIN". <a href="https://www.cve.org/CVERecord?id=CVE-2009-2382">https://www.cve.org/CVERecord?id=CVE-2009-2382</a>
<b>CVE-2009-1048</b>	VOIP product allows authentication bypass using 127.0.0.1 in the Host header. <a href="https://www.cve.org/CVERecord?id=CVE-2009-1048">https://www.cve.org/CVERecord?id=CVE-2009-1048</a>

Reference	Description
<b>CVE-2009-2213</b>	product uses default "Allow" action, instead of default deny, leading to authentication bypass. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2213">https://www.cve.org/CVERecord?id=CVE-2009-2213</a>
<b>CVE-2009-2168</b>	chain: redirect without exit (CWE-698) leads to resultant authentication bypass. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2168">https://www.cve.org/CVERecord?id=CVE-2009-2168</a>
<b>CVE-2009-3107</b>	product does not restrict access to a listening port for a critical service, allowing authentication to be bypassed. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3107">https://www.cve.org/CVERecord?id=CVE-2009-3107</a>
<b>CVE-2009-1596</b>	product does not properly implement a security-related configuration setting, allowing authentication bypass. <a href="https://www.cve.org/CVERecord?id=CVE-2009-1596">https://www.cve.org/CVERecord?id=CVE-2009-1596</a>
<b>CVE-2009-2422</b>	authentication routine returns "nil" instead of "false" in some situations, allowing authentication bypass using an invalid username. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2422">https://www.cve.org/CVERecord?id=CVE-2009-2422</a>
<b>CVE-2009-3232</b>	authentication update script does not properly handle when admin does not select any authentication modules, allowing authentication bypass. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3232">https://www.cve.org/CVERecord?id=CVE-2009-3232</a>
<b>CVE-2009-3231</b>	use of LDAP authentication with anonymous binds causes empty password to result in successful authentication <a href="https://www.cve.org/CVERecord?id=CVE-2009-3231">https://www.cve.org/CVERecord?id=CVE-2009-3231</a>
<b>CVE-2005-3435</b>	product authentication succeeds if user-provided MD5 hash matches the hash in its database; this can be subjected to replay attacks. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3435">https://www.cve.org/CVERecord?id=CVE-2005-3435</a>
<b>CVE-2005-0408</b>	chain: product generates predictable MD5 hashes using a constant value combined with username, allowing authentication bypass. <a href="https://www.cve.org/CVERecord?id=CVE-2005-0408">https://www.cve.org/CVERecord?id=CVE-2005-0408</a>

## Functional Areas

- Authentication

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	2552
MemberOf	C	718	OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management	629	2332
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	2335
MemberOf	C	812	OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management	809	2357
MemberOf	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	2389
MemberOf	C	947	SFP Secondary Cluster: Authentication Bypass	888	2394
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	2576
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	2436
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	2587
MemberOf	V	1337	Weaknesses in the 2021 CWE Top 25 Most Dangerous Software Weaknesses	1337	2589

Nature	Type	ID	Name	V	Page
MemberOf	V	1350	Weaknesses in the 2020 CWE Top 25 Most Dangerous Software Weaknesses	1350	2594
MemberOf	C	1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf	C	1364	ICS Communications: Zone Boundary Failures	1358	2501
MemberOf	C	1368	ICS Dependencies (& Architecture): External Digital Systems	1358	2505
MemberOf	V	1387	Weaknesses in the 2022 CWE Top 25 Most Dangerous Software Weaknesses	1387	2597
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519
MemberOf	V	1425	Weaknesses in the 2023 CWE Top 25 Most Dangerous Software Weaknesses	1425	2600

## Notes

### Relationship

This can be resultant from SQL injection vulnerabilities and other issues.

### Maintenance

The Taxonomy\_Mappings to ISA/IEC 62443 were added in CWE 4.10, but they are still under review and might change in future CWE versions. These draft mappings were performed by members of the "Mapping CWE to 62443" subgroup of the CWE-CAPEC ICS/OT Special Interest Group (SIG), and their work is incomplete as of CWE 4.10. The mappings are included to facilitate discussion and review by the broader ICS/OT community, and they are likely to change in future CWE versions.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Error
OWASP Top Ten 2007	A7	CWE More Specific	Broken Authentication and Session Management
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management
WASC	1		Insufficient Authentication
ISA/IEC 62443	Part 3-3		Req SR 1.1
ISA/IEC 62443	Part 3-3		Req SR 1.2
ISA/IEC 62443	Part 4-2		Req CR 1.1
ISA/IEC 62443	Part 4-2		Req CR 1.2

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
22	Exploiting Trust in Client
57	Utilizing REST's Trust in the System Resource to Obtain Sensitive Data
94	Adversary in the Middle (AiTM)
114	Authentication Abuse
115	Authentication Bypass
151	Identity Spoofing
194	Fake the Source of Data
593	Session Hijacking
633	Token Impersonation
650	Upload a Web Shell to a Web Server

## References

[REF-236]Kim Zetter. "Weak Password Brings 'Happiness' to Twitter Hacker". 2009 January 9. < <https://www.wired.com/2009/01/professed-twitt/> >.2023-04-07.

[REF-237]OWASP. "Top 10 2007-Broken Authentication and Session Management". 2007. < [http://www.owasp.org/index.php/Top\\_10\\_2007-A7](http://www.owasp.org/index.php/Top_10_2007-A7) >.

[REF-238]OWASP. "Guide to Authentication". < [http://www.owasp.org/index.php/Guide\\_to\\_Authentication](http://www.owasp.org/index.php/Guide_to_Authentication) >.

[REF-239]Microsoft. "Authentication". < [http://msdn.microsoft.com/en-us/library/aa374735\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/aa374735(VS.85).aspx) >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.

## CWE-288: Authentication Bypass Using an Alternate Path or Channel

**Weakness ID** : 288

**Structure** : Simple

**Abstraction** : Base





### Description

A product requires authentication, but the product has an alternate path or channel that does not require authentication.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		306	Missing Authentication for Critical Function	741
ParentOf		425	Direct Request ('Forced Browsing')	1025
ParentOf		1299	Missing Protection Mechanism for Alternate Hardware Interface	2162
PeerOf		420	Unprotected Alternate Channel	1018

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "CISQ Data Protection Measures" (CWE-1340)*

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	680

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences



Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Funnel all access through a single choke point to simplify how users can access a resource. For every access, perform a check to determine if the user has permissions to access the resource.

Demonstrative Examples

Example 1:

Register SECURE\_ME is located at address 0xF00. A mirror of this register called COPY\_OF\_SECURE\_ME is at location 0x800F00. The register SECURE\_ME is protected from malicious agents and only allows access to select, while COPY\_OF\_SECURE\_ME is not.

Access control is implemented using an allowlist (as indicated by acl\_oh\_allowlist). The identity of the initiator of the transaction is indicated by the one hot input, incoming\_id. This is checked against the acl\_oh\_allowlist (which contains a list of initiators that are allowed to access the asset).

Though this example is shown in Verilog, it will apply to VHDL as well.

Example Language: Verilog

(Informative)

```
module foo_bar(data_out, data_in, incoming_id, address, clk, rst_n);
output [31:0] data_out;
input [31:0] data_in, incoming_id, address;
input clk, rst_n;
wire write_auth, addr_auth;
reg [31:0] data_out, acl_oh_allowlist, q;
assign write_auth = | (incoming_id & acl_oh_allowlist) ? 1 : 0;
always @*
    acl_oh_allowlist <= 32'h8312;
assign addr_auth = (address == 32'hF00) ? 1 : 0;
always @ (posedge clk or negedge rst_n)
    if (!rst_n)
        begin
            q <= 32'h0;
            data_out <= 32'h0;
        end
    else
        begin
            q <= (addr_auth & write_auth) ? data_in : q;
            data_out <= q;
        end
    end
end
endmodule
```

Example Language: Verilog

(Bad)

```
assign addr_auth = (address == 32'hF00) ? 1 : 0;
```

The bugged line of code is repeated in the Bad example above. Weakness arises from the fact that the SECURE\_ME register can be modified by writing to the shadow register COPY\_OF\_SECURE\_ME, the address of COPY\_OF\_SECURE\_ME should also be included in the check. That buggy line of code should instead be replaced as shown in the Good Code Snippet below.

Example Language: Verilog

(Good)

```
assign addr_auth = (address == 32'hF00 || address == 32'h800F00) ? 1 : 0;
```



## Observed Examples

Reference	Description
<b>CVE-2000-1179</b>	Router allows remote attackers to read system logs without authentication by directly connecting to the login screen and typing certain control characters. <a href="https://www.cve.org/CVERecord?id=CVE-2000-1179">https://www.cve.org/CVERecord?id=CVE-2000-1179</a>
<b>CVE-1999-1454</b>	Attackers with physical access to the machine may bypass the password prompt by pressing the ESC (Escape) key. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1454">https://www.cve.org/CVERecord?id=CVE-1999-1454</a>
<b>CVE-1999-1077</b>	OS allows local attackers to bypass the password protection of idled sessions via the programmer's switch or CMD-PWR keyboard sequence, which brings up a debugger that the attacker can use to disable the lock. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1077">https://www.cve.org/CVERecord?id=CVE-1999-1077</a>
<b>CVE-2003-0304</b>	Direct request of installation file allows attacker to create administrator accounts. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0304">https://www.cve.org/CVERecord?id=CVE-2003-0304</a>
<b>CVE-2002-0870</b>	Attackers may gain additional privileges by directly requesting the web management URL. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0870">https://www.cve.org/CVERecord?id=CVE-2002-0870</a>
<b>CVE-2002-0066</b>	Bypass authentication via direct request to named pipe. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0066">https://www.cve.org/CVERecord?id=CVE-2002-0066</a>
<b>CVE-2003-1035</b>	User can avoid lockouts by using an API instead of the GUI to conduct brute force password guessing. <a href="https://www.cve.org/CVERecord?id=CVE-2003-1035">https://www.cve.org/CVERecord?id=CVE-2003-1035</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		721	OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access	629	2333
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	2394
MemberOf		1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf		1364	ICS Communications: Zone Boundary Failures	1358	2501
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

## Notes

## Relationship

overlaps Unprotected Alternate Channel

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Bypass by Alternate Path/Channel
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
127	Directory Indexing
665	Exploitation of Thunderbolt Protection Flaws

## CWE-289: Authentication Bypass by Alternate Name

**Weakness ID :** 289

**Structure :** Simple

**Abstraction :** Base






### Description

The product performs authentication based on the name of a resource being accessed, or the name of the actor performing the access, but it does not properly check all possible names for that resource or actor.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1390	Weak Authentication	2267
CanFollow		46	Path Equivalence: 'filename ' (Trailing Space)	96
CanFollow		52	Path Equivalence: '/multiple/trailing/slash/'	103
CanFollow		173	Improper Handling of Alternate Encoding	435
CanFollow		178	Improper Handling of Case Sensitivity	445

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

### Potential Mitigations

#### Phase: Architecture and Design

*Strategy = Input Validation*

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

#### Phase: Implementation

*Strategy = Input Validation*

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a list of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input

is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs. This is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, denylists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

### Phase: Implementation

*Strategy = Input Validation*





Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass allowlist validation schemes by introducing dangerous inputs after they have been checked.

### Observed Examples

Reference	Description
<b>CVE-2003-0317</b>	Protection mechanism that restricts URL access can be bypassed using URL encoding. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0317">https://www.cve.org/CVERecord?id=CVE-2003-0317</a>
<b>CVE-2004-0847</b>	Bypass of authentication for files using "\" (backslash) or "%5C" (encoded backslash). <a href="https://www.cve.org/CVERecord?id=CVE-2004-0847">https://www.cve.org/CVERecord?id=CVE-2004-0847</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	2362
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	2394
MemberOf		1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	2444
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Relationship

Overlaps equivalent encodings, canonicalization, authorization, multiple trailing slash, trailing space, mixed case, and other equivalence issues.

#### Theoretical

Alternate names are useful in data driven manipulation attacks, not just for authentication.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication bypass by alternate name
The CERT Oracle Secure Coding Standard for Java (2011)	IDS01-J	CWE More Specific	Normalize strings before validating them
SEI CERT Oracle Coding Standard for Java	IDS01-J	CWE More Specific	Normalize strings before validating them

## CWE-290: Authentication Bypass by Spoofing

**Weakness ID :** 290  
**Structure :** Simple  
**Abstraction :** Base






### Description

This attack-focused weakness is caused by incorrectly implemented authentication schemes that are subject to spoofing attacks.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1390	Weak Authentication	2267
ParentOf		291	Reliance on IP Address for Authentication	708
ParentOf		293	Using Referer Field for Authentication	710
ParentOf		350	Reliance on Reverse DNS Resolution for a Security-Critical Action	863
PeerOf		602	Client-Side Enforcement of Server-Side Security	1350

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	692

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity  <i>This weakness can allow an attacker to access resources which are not otherwise accessible without proper authentication.</i>	

### Demonstrative Examples

#### Example 1:

The following code authenticates users.

*Example Language: Java*

*(Bad)*

```
String sourceIP = request.getRemoteAddr();
if (sourceIP != null && sourceIP.equals(APPROVED_IP)) {
    authenticated = true;
}
```

The authentication mechanism implemented relies on an IP address for source validation. If an attacker is able to spoof the IP, they may be able to bypass the authentication mechanism.

### Example 2:

Both of these examples check if a request is from a trusted address before responding to the request.

*Example Language: C*

*(Bad)*

```
sd = socket(AF_INET, SOCK_DGRAM, 0);
serv.sin_family = AF_INET;
serv.sin_addr.s_addr = htonl(INADDR_ANY);
servr.sin_port = htons(1008);
bind(sd, (struct sockaddr *) & serv, sizeof(serv));
while (1) {
    memset(msg, 0x0, MAX_MSG);
    clien = sizeof(cli);
    if (inet_ntoa(cli.sin_addr) == getTrustedAddress()) {
        n = recvfrom(sd, msg, MAX_MSG, 0, (struct sockaddr *) & cli, & clien);
    }
}
```

*Example Language: Java*

*(Bad)*

```
while(true) {
    DatagramPacket rp = new DatagramPacket(rData, rData.length);
    outSock.receive(rp);
    String in = new String(p.getData(), 0, rp.getLength());
    InetAddress clientIPAddress = rp.getAddress();
    int port = rp.getPort();
    if (isTrustedAddress(clientIPAddress) & secretKey.equals(in)) {
        out = secret.getBytes();
        DatagramPacket sp = new DatagramPacket(out, out.length, IPAddress, port); outSock.send(sp);
    }
}
```

The code only verifies the address as stored in the request packet. An attacker can spoof this address, thus impersonating a trusted client.

### Example 3:

The following code samples use a DNS lookup in order to decide whether or not an inbound request is from a trusted host. If an attacker can poison the DNS cache, they can gain trusted status.

*Example Language: C*

*(Bad)*

```
struct hostent *hp; struct in_addr myaddr;
char* tHost = "trustme.example.com";
myaddr.s_addr = inet_addr(ip_addr_string);
hp = gethostbyaddr((char *) &myaddr, sizeof(struct in_addr), AF_INET);
if (hp && !strncmp(hp->h_name, tHost, sizeof(tHost))) {
    trusted = true;
} else {
    trusted = false;
}
```

*Example Language: Java*

*(Bad)*

```
String ip = request.getRemoteAddr();
InetAddress addr = InetAddress.getByName(ip);
if (addr.getCanonicalHostName().endsWith("trustme.com")) {
    trusted = true;
}
```

Example Language: C#

(Bad)

```
IPAddress hostIPAddress = IPAddress.Parse(RemoteIpAddress);
IPHostEntry hostInfo = Dns.GetHostByAddress(hostIPAddress);
if (hostInfo.HostName.EndsWith("trustme.com")) {
    trusted = true;
}
```

IP addresses are more reliable than DNS names, but they can also be spoofed. Attackers can easily forge the source IP address of the packets they send, but response packets will return to the forged IP address. To see the response packets, the attacker has to sniff the traffic between the victim machine and the forged IP address. In order to accomplish the required sniffing, attackers typically attempt to locate themselves on the same subnet as the victim machine. Attackers may be able to circumvent this requirement by using source routing, but source routing is disabled across much of the Internet today. In summary, IP address verification can be a useful part of an authentication scheme, but it should not be the single factor required for authentication.

### Observed Examples

Reference	Description
<b>CVE-2022-30319</b>	S-bus functionality in a home automation product performs access control using an IP allowlist, which can be bypassed by a forged IP address. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30319">https://www.cve.org/CVERecord?id=CVE-2022-30319</a>
<b>CVE-2009-1048</b>	VOIP product allows authentication bypass using 127.0.0.1 in the Host header. <a href="https://www.cve.org/CVERecord?id=CVE-2009-1048">https://www.cve.org/CVERecord?id=CVE-2009-1048</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	956	SFP Secondary Cluster: Channel Attack	888	2397
MemberOf	C	1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf	C	1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Relationship

This can be resultant from insufficient verification.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication bypass by spoofing

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Identifiers
22	Exploiting Trust in Client
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)
94	Adversary in the Middle (AiTM)
459	Creating a Rogue Certification Authority Certificate
461	Web Services API Signature Forgery Leveraging Hash Function Extension Weakness
473	Signature Spoof

**CAPEC-ID    Attack Pattern Name**

476	Signature Spoofing by Misrepresentation
667	Bluetooth Impersonation AttackS (BIAS)

**References**

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

**CWE-291: Reliance on IP Address for Authentication****Weakness ID** : 291**Structure** : Simple**Abstraction** : Variant**Description**

The product uses an IP address for authentication.




**Extended Description**

IP addresses can be easily spoofed. Attackers can forge the source IP address of the packets they send, but response packets will return to the forged IP address. To see the response packets, the attacker has to sniff the traffic between the victim machine and the forged IP address. In order to accomplish the required sniffing, attackers typically attempt to locate themselves on the same subnet as the victim machine. Attackers may be able to circumvent this requirement by using source routing, but source routing is disabled across much of the Internet today. In summary, IP address verification can be a useful part of an authentication scheme, but it should not be the single factor required for authentication.

**Relationships**

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		471	Modification of Assumed-Immutable Data (MAID)	1121
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1827
ChildOf		290	Authentication Bypass by Spoofing	705

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

**Weakness Ordinalities**

**Resultant** :

**Applicable Platforms**

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Likelihood Of Exploit**

High

**Common Consequences**



Scope	Impact	Likelihood
Access Control	Hide Activities	
Non-Repudiation	Gain Privileges or Assume Identity	
	<i>Malicious users can fake authentication information, impersonating any IP address.</i>	

## Potential Mitigations

### Phase: Architecture and Design

Use other means of identity verification that cannot be simply spoofed. Possibilities include a username/password or certificate.

## Demonstrative Examples

### Example 1:

Both of these examples check if a request is from a trusted address before responding to the request.

Example Language: C

(Bad)

```
sd = socket(AF_INET, SOCK_DGRAM, 0);
serv.sin_family = AF_INET;
serv.sin_addr.s_addr = htonl(INADDR_ANY);
servr.sin_port = htons(1008);
bind(sd, (struct sockaddr *) & serv, sizeof(serv));
while (1) {
    memset(msg, 0x0, MAX_MSG);
    clien = sizeof(cli);
    if (inet_ntoa(cli.sin_addr) == getTrustedAddress()) {
        n = recvfrom(sd, msg, MAX_MSG, 0, (struct sockaddr *) & cli, &clien);
    }
}
```

Example Language: Java

(Bad)

```
while(true) {
    DatagramPacket rp=new DatagramPacket(rData,rData.length);
    outSock.receive(rp);
    String in = new String(p.getData(),0, rp.getLength());
    InetAddress clientIPAddress = rp.getAddress();
    int port = rp.getPort();
    if (isTrustedAddress(clientIPAddress) & secretKey.equals(in)) {
        out = secret.getBytes();
        DatagramPacket sp =new DatagramPacket(out,out.length, IPAddress, port); outSock.send(sp);
    }
}
```

The code only verifies the address as stored in the request packet. An attacker can spoof this address, thus impersonating a trusted client.

## Observed Examples

Reference	Description
<b>CVE-2022-30319</b>	S-bus functionality in a home automation product performs access control using an IP allowlist, which can be bypassed by a forged IP address. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30319">https://www.cve.org/CVERecord?id=CVE-2022-30319</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Trusting self-reported IP address

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
4	Using Alternative IP Address Encodings

### References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

[REF-1371]"IP address spoofing". 2006 April 7. Wikipedia. < [https://en.wikipedia.org/wiki/IP\\_address\\_spoofing](https://en.wikipedia.org/wiki/IP_address_spoofing) >.2023-10-21.

## CWE-293: Using Referer Field for Authentication

**Weakness ID :** 293

**Structure :** Simple

**Abstraction :** Variant

### Description

The referer field in HTTP requests can be easily modified and, as such, is not a valid means of message integrity checking.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	B	290	Authentication Bypass by Spoofing	705

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf	C	1010	Authenticate Actors	2424

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Background Details

The referer field in HTML requests can be simply modified by malicious users, rendering it useless as a means of checking the validity of the request in question.

### Alternate Terms

**referrer :** While the proper spelling might be regarded as "referrer," the HTTP RFCs and their implementations use "referer," so this is regarded as the correct spelling.

### Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  <i>Actions, which may not be authorized otherwise, can be carried out as if they were validated by the server referred to.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

Potential Mitigations

Phase: Architecture and Design

In order to usefully check if a given action is authorized, some means of strong authentication and method protection must be used. Use other means of authorization that cannot be simply spoofed. Possibilities include a username/password or certificate.

Demonstrative Examples

Example 1:

The following code samples check a packet's referer in order to decide whether or not an inbound request is from a trusted host.

Example Language: C++ (Bad)

```
String trustedReferer = "http://www.example.com/"
while(true){
    n = read(newsock, buffer, BUFSIZE);
    requestPacket = processPacket(buffer, n);
    if (requestPacket.referer == trustedReferer){
        openNewSecureSession(requestPacket);
    }
}
```



Example Language: Java (Bad)

```
boolean processConnectionRequest(HttpServletRequest request){
    String referer = request.getHeader("referer")
    String trustedReferer = "http://www.example.com/"
    if(referer.equals(trustedReferer)){
        openPrivilegedConnection(request);
        return true;
    }
    else{
        sendPrivilegeError(request);
        return false;
    }
}
```

These examples check if a request is from a trusted referer before responding to a request, but the code only verifies the referer name as stored in the request packet. An attacker can spoof the referer, thus impersonating a trusted client.

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	2395
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using referrer field for authentication
Software Fault Patterns	SFP29		Faulty endpoint authentication

## References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-294: Authentication Bypass by Capture-replay

**Weakness ID** : 294

**Structure** : Simple

**Abstraction** : Base

## Description

A capture-replay flaw exists when the design of the product makes it possible for a malicious user to sniff network traffic and bypass authentication by replaying it to the server in question to the same effect as the original message (or with minor changes).

## Extended Description

Capture-replay attacks are common and can be difficult to defeat without cryptography. They are a subset of network injection attacks that rely on observing previously-sent valid commands, then changing them slightly if necessary and resending the same commands to the server.


## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1390	Weak Authentication	2267

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	692

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf	<span style="color: red;">C</span>	1211	Authentication Errors	2475

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  <i>Messages sent with a capture-relay attack allow access to resources which are not otherwise accessible without proper authentication.</i>	

### Potential Mitigations

#### Phase: Architecture and Design

Utilize some sequence or time stamping functionality along with a checksum which takes this into account in order to ensure that messages can be parsed only once.

#### Phase: Architecture and Design

Since any attacker who can listen to traffic can see sequence numbers, it is necessary to sign messages with some kind of cryptography to ensure that sequence numbers are not simply doctored along with content.

### Observed Examples

Reference	Description
<b>CVE-2005-3435</b>	product authentication succeeds if user-provided MD5 hash matches the hash in its database; this can be subjected to replay attacks. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3435">https://www.cve.org/CVERecord?id=CVE-2005-3435</a>
<b>CVE-2007-4961</b>	Chain: cleartext transmission of the MD5 hash of password (CWE-319) enables attacks against a server that is susceptible to replay (CWE-294). <a href="https://www.cve.org/CVERecord?id=CVE-2007-4961">https://www.cve.org/CVERecord?id=CVE-2007-4961</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<span style="color: red;">V</span>	Page
MemberOf	<span style="color: red;">V</span>	884	CWE Cross-section	884	2567
MemberOf	<span style="color: red;">C</span>	956	SFP Secondary Cluster: Channel Attack	888	2397
MemberOf	<span style="color: red;">C</span>	1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf	<span style="color: red;">C</span>	1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication bypass by replay
CLASP			Capture-replay

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
60	Reusing Session IDs (aka Session Replay)
94	Adversary in the Middle (AiTM)
102	Session Sidejacking
509	Kerberoasting
555	Remote Services with Stolen Credentials
561	Windows Admin Shares with Stolen Credentials
644	Use of Captured Hashes (Pass The Hash)
645	Use of Captured Tickets (Pass The Ticket)
652	Use of Known Kerberos Credentials
701	Browser in the Middle (BiTM)

## References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-295: Improper Certificate Validation

**Weakness ID :** 295

**Structure :** Simple

**Abstraction :** Base

## Description

The product does not validate, or incorrectly validates, a certificate.









## Extended Description

When a certificate is invalid or malicious, it might allow an attacker to spoof a trusted entity by interfering in the communication path between the host and client. The product might connect to a malicious host while believing it is a trusted host, or the product might be deceived into accepting spoofed data that appears to originate from a trusted host.


## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	692
ParentOf		296	Improper Following of a Certificate's Chain of Trust	719
ParentOf		297	Improper Validation of Certificate with Host Mismatch	722
ParentOf		298	Improper Validation of Certificate Expiration	726
ParentOf		299	Improper Check for Certificate Revocation	727
ParentOf		599	Missing Validation of OpenSSL Certificate	1341
PeerOf		322	Key Exchange without Entity Authentication	788
PeerOf		322	Key Exchange without Entity Authentication	788


*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	692

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	2429

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : Mobile (*Prevalence = Undetermined*)

### Background Details

A certificate is a token that associates an identity (principal) to a cryptographic key. Certificates can be used to check if a public key belongs to the assumed owner.

### Common Consequences

Scope	Impact	Likelihood
Integrity	Bypass Protection Mechanism	
Authentication	Gain Privileges or Assume Identity	

### Detection Methods

#### Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis  
Binary Weakness Analysis - including disassembler + source code weakness analysis

*Effectiveness = SOAR Partial*

#### Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

*Effectiveness = SOAR Partial*

#### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner

*Effectiveness = SOAR Partial*

#### Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Man-in-the-middle attack tool

*Effectiveness = High*

#### Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

*Effectiveness = High*

#### Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer



*Effectiveness = SOAR Partial*

### Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

*Effectiveness = High*

### Potential Mitigations

#### Phase: Architecture and Design

#### Phase: Implementation

Certificates should be carefully managed and checked to assure that data are encrypted with the intended owner's public key.

#### Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the hostname.

### Demonstrative Examples

#### Example 1:

This code checks the certificate of a connected peer.

*Example Language: C*

*(Bad)*

```
if ((cert = SSL_get_peer_certificate(ssl)) && host)
    foo=SSL_get_verify_result(ssl);
if ((X509_V_OK==foo) || X509_V_ERR_SELF_SIGNED_CERT_IN_CHAIN==foo))
    // certificate looks good, host can be trusted
```

In this case, because the certificate is self-signed, there was no external authority that could prove the identity of the host. The program could be communicating with a different system that is spoofing the host, e.g. by poisoning the DNS cache or using an Adversary-in-the-Middle (AITM) attack to modify the traffic from server to client.

#### Example 2:

The following OpenSSL code obtains a certificate and verifies it.

*Example Language: C*

*(Bad)*

```
cert = SSL_get_peer_certificate(ssl);
if (cert && (SSL_get_verify_result(ssl)==X509_V_OK)) {
    // do secret things
}
```

Even though the "verify" step returns X509\_V\_OK, this step does not include checking the Common Name against the name of the host. That is, there is no guarantee that the certificate is for the desired host. The SSL connection could have been established with a malicious host that provided a valid certificate.

#### Example 3:

The following OpenSSL code ensures that there is a certificate and allows the use of expired certificates.

*Example Language: C*

*(Bad)*

```
if (cert = SSL_get_peer_certificate(ssl)) {
    foo=SSL_get_verify_result(ssl);
    if ((X509_V_OK==foo) || (X509_V_ERR_CERT_HAS_EXPIRED==foo))
        //do stuff
```

If the call to `SSL_get_verify_result()` returns `X509_V_ERR_CERT_HAS_EXPIRED`, this means that the certificate has expired. As time goes on, there is an increasing chance for attackers to compromise the certificate.

#### Example 4:

The following OpenSSL code ensures that there is a certificate before continuing execution.

Example Language: C

(Bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {  
    // got a certificate, do secret things
```

Because this code does not use `SSL_get_verify_results()` to check the certificate, it could accept certificates that have been revoked (`X509_V_ERR_CERT_REVOKED`). The software could be communicating with a malicious host.

#### Example 5:

The following OpenSSL code ensures that the host has a certificate.

Example Language: C

(Bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {  
    // got certificate, host can be trusted  
    //foo=SSL_get_verify_result(ssl);  
    //if (X509_V_OK==foo) ...  
}
```

Note that the code does not call `SSL_get_verify_result(ssl)`, which effectively disables the validation step that checks the certificate.







### Observed Examples

Reference	Description
<b>CVE-2019-12496</b>	A Go framework for robotics, drones, and IoT devices skips verification of root CA certificates by default. <a href="https://www.cve.org/CVERecord?id=CVE-2019-12496">https://www.cve.org/CVERecord?id=CVE-2019-12496</a>
<b>CVE-2014-1266</b>	chain: incorrect "goto" in Apple SSL product bypasses certificate validation, allowing Adversary-in-the-Middle (AITM) attack (Apple "goto fail" bug). CWE-705 (Incorrect Control Flow Scoping) -> CWE-561 (Dead Code) -> CWE-295 (Improper Certificate Validation) -> CWE-393 (Return of Wrong Status Code) -> CWE-300 (Channel Accessible by Non-Endpoint). <a href="https://www.cve.org/CVERecord?id=CVE-2014-1266">https://www.cve.org/CVERecord?id=CVE-2014-1266</a>
<b>CVE-2021-22909</b>	Chain: router's firmware update procedure uses curl with "-k" (insecure) option that disables certificate validation (CWE-295), allowing adversary-in-the-middle (AITM) compromise with a malicious firmware image (CWE-494). <a href="https://www.cve.org/CVERecord?id=CVE-2021-22909">https://www.cve.org/CVERecord?id=CVE-2021-22909</a>
<b>CVE-2008-4989</b>	Verification function trusts certificate chains in which the last certificate is self-signed. <a href="https://www.cve.org/CVERecord?id=CVE-2008-4989">https://www.cve.org/CVERecord?id=CVE-2008-4989</a>
<b>CVE-2012-5821</b>	Web browser uses a TLS-related function incorrectly, preventing it from verifying that a server's certificate is signed by a trusted certification authority (CA) <a href="https://www.cve.org/CVERecord?id=CVE-2012-5821">https://www.cve.org/CVERecord?id=CVE-2012-5821</a>
<b>CVE-2009-3046</b>	Web browser does not check if any intermediate certificates are revoked. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3046">https://www.cve.org/CVERecord?id=CVE-2009-3046</a>
<b>CVE-2011-0199</b>	Operating system does not check Certificate Revocation List (CRL) in some cases, allowing spoofing using a revoked certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2011-0199">https://www.cve.org/CVERecord?id=CVE-2011-0199</a>

Reference	Description
<b>CVE-2012-5810</b>	Mobile banking application does not verify hostname, leading to financial loss. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5810">https://www.cve.org/CVERecord?id=CVE-2012-5810</a>
<b>CVE-2012-3446</b>	Cloud-support library written in Python uses incorrect regular expression when matching hostname. <a href="https://www.cve.org/CVERecord?id=CVE-2012-3446">https://www.cve.org/CVERecord?id=CVE-2012-3446</a>
<b>CVE-2009-2408</b>	Web browser does not correctly handle '\0' character (NUL) in Common Name, allowing spoofing of https sites. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2408">https://www.cve.org/CVERecord?id=CVE-2009-2408</a>
<b>CVE-2012-2993</b>	Smartphone device does not verify hostname, allowing spoofing of mail services. <a href="https://www.cve.org/CVERecord?id=CVE-2012-2993">https://www.cve.org/CVERecord?id=CVE-2012-2993</a>
<b>CVE-2012-5822</b>	Application uses third-party library that does not validate hostname. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5822">https://www.cve.org/CVERecord?id=CVE-2012-5822</a>
<b>CVE-2012-5819</b>	Cloud storage management application does not validate hostname. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5819">https://www.cve.org/CVERecord?id=CVE-2012-5819</a>
<b>CVE-2012-5817</b>	Java library uses JSSE SSLSocket and SSLEngine classes, which do not verify the hostname. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5817">https://www.cve.org/CVERecord?id=CVE-2012-5817</a>
<b>CVE-2010-1378</b>	chain: incorrect calculation allows attackers to bypass certificate checks. <a href="https://www.cve.org/CVERecord?id=CVE-2010-1378">https://www.cve.org/CVERecord?id=CVE-2010-1378</a>
<b>CVE-2005-3170</b>	LDAP client accepts certificates even if they are not from a trusted CA. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3170">https://www.cve.org/CVERecord?id=CVE-2005-3170</a>
<b>CVE-2009-0265</b>	chain: DNS server does not correctly check return value from the OpenSSL EVP_VerifyFinal function allows bypass of validation of the certificate chain. <a href="https://www.cve.org/CVERecord?id=CVE-2009-0265">https://www.cve.org/CVERecord?id=CVE-2009-0265</a>
<b>CVE-2003-1229</b>	chain: product checks if client is trusted when it intended to check if the server is trusted, allowing validation of signed code. <a href="https://www.cve.org/CVERecord?id=CVE-2003-1229">https://www.cve.org/CVERecord?id=CVE-2003-1229</a>
<b>CVE-2002-0862</b>	Cryptographic API, as used in web browsers, mail clients, and other software, does not properly validate Basic Constraints. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0862">https://www.cve.org/CVERecord?id=CVE-2002-0862</a>
<b>CVE-2009-1358</b>	chain: OS package manager does not check properly check the return value, allowing bypass using a revoked certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2009-1358">https://www.cve.org/CVERecord?id=CVE-2009-1358</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	2339
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436
MemberOf		1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	2587
MemberOf		1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf		1382	ICS Operations (& Maintenance): Emerging Energy Technologies	1358	2517
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
459	Creating a Rogue Certification Authority Certificate
475	Signature Spoofing by Improper Validation

### References

[REF-243]Sascha Fahl, Marian Harbach, Thomas Muders, Matthew Smith and Lars Baumgärtner, Bernd Freisleben. "Why Eve and Mallory Love Android: An Analysis of Android SSL (In)Security". 2012 October 6. < <http://www2.dcsec.uni-hannover.de/files/android/p50-fahl.pdf> >.

[REF-244]M. Bishop. "Computer Security: Art and Science". 2003. Addison-Wesley.

## CWE-296: Improper Following of a Certificate's Chain of Trust

**Weakness ID :** 296

**Structure :** Simple

**Abstraction :** Base

### Description

The product does not follow, or incorrectly follows, the chain of trust for a certificate back to a trusted root certificate, resulting in incorrect trust of any resource that is associated with that certificate.

### Extended Description

If a system does not follow the chain of trust of a certificate to a root server, the certificate loses all usefulness as a metric of trust. Essentially, the trust gained from a certificate is derived from a chain of trust -- with a reputable trusted entity at the end of that list. The end user must trust that reputable source, and this reputable source must vouch for the resource in question through the medium of the certificate.

In some cases, this trust traverses several entities who vouch for one another. The entity trusted by the end user is at one end of this trust chain, while the certificate-wielding resource is at the other end of the chain. If the user receives a certificate at the end of one of these trust chains and then proceeds to check only that the first link in the chain, no real trust has been derived, since the entire chain must be traversed back to a trusted source to verify the certificate.

There are several ways in which the chain of trust might be broken, including but not limited to:

- Any certificate in the chain is self-signed, unless it the root.
- Not every intermediate certificate is checked, starting from the original certificate all the way up to the root certificate.
- An intermediate, CA-signed certificate does not have the expected Basic Constraints or other important extensions.
- The root certificate has been compromised or authorized to the wrong party.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1298
ChildOf		295	Improper Certificate Validation	714
PeerOf		370	Missing Check for Certificate Revocation after Initial Check	917

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	2429

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

Low

## Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities <i>Exploitation of this flaw can lead to the trust of data that may have originated with a spoofed source.</i>	
Integrity	Gain Privileges or Assume Identity	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	<i>Data, requests, or actions taken by the attacking entity can be carried out as a spoofed benign entity.</i>	
Access Control		

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

Ensure that proper certificate checking is included in the system design.

### Phase: Implementation

Understand, and properly implement all checks necessary to ensure the integrity of certificate trust integrity.

### Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the full chain of trust.

## Demonstrative Examples

### Example 1:

This code checks the certificate of a connected peer.

*Example Language: C*

*(Bad)*

```
if ((cert = SSL_get_peer_certificate(ssl)) && host)
```

```
foo=SSL_get_verify_result(ssl);
if ((X509_V_OK==foo) || X509_V_ERR_SELF_SIGNED_CERT_IN_CHAIN==foo))
    // certificate looks good, host can be trusted
```








In this case, because the certificate is self-signed, there was no external authority that could prove the identity of the host. The program could be communicating with a different system that is spoofing the host, e.g. by poisoning the DNS cache or using an Adversary-in-the-Middle (AITM) attack to modify the traffic from server to client.

### Observed Examples

Reference	Description
<b>CVE-2016-2402</b>	Server allows bypass of certificate pinning by sending a chain of trust that includes a trusted CA that is not pinned. <a href="https://www.cve.org/CVERecord?id=CVE-2016-2402">https://www.cve.org/CVERecord?id=CVE-2016-2402</a>
<b>CVE-2008-4989</b>	Verification function trusts certificate chains in which the last certificate is self-signed. <a href="https://www.cve.org/CVERecord?id=CVE-2008-4989">https://www.cve.org/CVERecord?id=CVE-2008-4989</a>
<b>CVE-2012-5821</b>	Chain: Web browser uses a TLS-related function incorrectly, preventing it from verifying that a server's certificate is signed by a trusted certification authority (CA). <a href="https://www.cve.org/CVERecord?id=CVE-2012-5821">https://www.cve.org/CVERecord?id=CVE-2012-5821</a>
<b>CVE-2009-3046</b>	Web browser does not check if any intermediate certificates are revoked. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3046">https://www.cve.org/CVERecord?id=CVE-2009-3046</a>
<b>CVE-2009-0265</b>	chain: DNS server does not correctly check return value from the OpenSSL EVP_VerifyFinal function allows bypass of validation of the certificate chain. <a href="https://www.cve.org/CVERecord?id=CVE-2009-0265">https://www.cve.org/CVERecord?id=CVE-2009-0265</a>
<b>CVE-2009-0124</b>	chain: incorrect check of return value from the OpenSSL EVP_VerifyFinal function allows bypass of validation of the certificate chain. <a href="https://www.cve.org/CVERecord?id=CVE-2009-0124">https://www.cve.org/CVERecord?id=CVE-2009-0124</a>
<b>CVE-2002-0970</b>	File-transfer software does not validate Basic Constraints of an intermediate CA-signed certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0970">https://www.cve.org/CVERecord?id=CVE-2002-0970</a>
<b>CVE-2002-0862</b>	Cryptographic API, as used in web browsers, mail clients, and other software, does not properly validate Basic Constraints. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0862">https://www.cve.org/CVERecord?id=CVE-2002-0862</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	2335
MemberOf		884	CWE Cross-section	884	2567
MemberOf		948	SFP Secondary Cluster: Digital Certificate	888	2395
MemberOf		1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf		1382	ICS Operations (& Maintenance): Emerging Energy Technologies	1358	2517
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings



Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to follow chain of trust in certificate validation

## References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

[REF-245]Martin Georgiev, Subodh Iyengar, Suman Jana, Rishita Anubhai, Dan Boneh and Vitaly Shmatikov. "The Most Dangerous Code in the World: Validating SSL Certificates in Non-Browser Software". 2012 October 5. < [http://www.cs.utexas.edu/~shmat/shmat\\_ccs12.pdf](http://www.cs.utexas.edu/~shmat/shmat_ccs12.pdf) >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

## CWE-297: Improper Validation of Certificate with Host Mismatch

**Weakness ID** : 297

**Structure** : Simple

**Abstraction** : Variant

## Description

The product communicates with a host that provides a certificate, but the product does not properly ensure that the certificate is actually associated with that host.

## Extended Description

Even if a certificate is well-formed, signed, and follows the chain of trust, it may simply be a valid certificate for a different site than the site that the product is interacting with. If the certificate's host-specific data is not properly checked - such as the Common Name (CN) in the Subject or the Subject Alternative Name (SAN) extension of an X.509 certificate - it may be possible for a redirection or spoofing attack to allow a malicious host with a valid certificate to provide data, impersonating a trusted host. In order to ensure data integrity, the certificate must be valid and it must pertain to the site that is being accessed.

Even if the product attempts to check the hostname, it is still possible to incorrectly check the hostname. For example, attackers could create a certificate with a name that begins with a trusted name followed by a NUL byte, which could cause some string-based comparisons to only examine the portion that contains the trusted name.

This weakness can occur even when the product uses Certificate Pinning, if the product does not verify the hostname at the time a certificate is pinned.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		295	Improper Certificate Validation	714
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1827
PeerOf		370	Missing Check for Certificate Revocation after Initial Check	917

*Relevant to the view "Architectural Concepts" (CWE-1008)*



Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	2429

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : Mobile (*Prevalence = Undetermined*)

**Technology** : Not Technology-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  <i>The data read from the system vouched for by the certificate may not be from the expected system.</i>	
Authentication Other	Other  <i>Trust afforded to the system in question - based on the malicious certificate - may allow for spoofing or redirection attacks.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

#### Dynamic Analysis with Manual Results Interpretation

Set up an untrusted endpoint (e.g. a server) with which the product will connect. Create a test certificate that uses an invalid hostname but is signed by a trusted CA and provide this certificate from the untrusted endpoint. If the product performs any operations instead of disconnecting and reporting an error, then this indicates that the hostname is not being checked and the test certificate has been accepted.

#### Black Box

When Certificate Pinning is being used in a mobile application, consider using a tool such as Spinner [REF-955]. This methodology might be extensible to other technologies.

### Potential Mitigations

#### Phase: Architecture and Design

Fully check the hostname of the certificate and provide the user with adequate information about the nature of the problem and how to proceed.

#### Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the hostname.

### Demonstrative Examples

#### Example 1:

The following OpenSSL code obtains a certificate and verifies it.

Example Language: C

(Bad)

```
cert = SSL_get_peer_certificate(ssl);
if (cert && (SSL_get_verify_result(ssl) == X509_V_OK)) {
    // do secret things
}
```

Even though the "verify" step returns X509\_V\_OK, this step does not include checking the Common Name against the name of the host. That is, there is no guarantee that the certificate is for the desired host. The SSL connection could have been established with a malicious host that provided a valid certificate.




### Observed Examples

Reference	Description
<b>CVE-2012-5810</b>	Mobile banking application does not verify hostname, leading to financial loss. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5810">https://www.cve.org/CVERecord?id=CVE-2012-5810</a>
<b>CVE-2012-5811</b>	Mobile application for printing documents does not verify hostname, allowing attackers to read sensitive documents. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5811">https://www.cve.org/CVERecord?id=CVE-2012-5811</a>
<b>CVE-2012-5807</b>	Software for electronic checking does not verify hostname, leading to financial loss. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5807">https://www.cve.org/CVERecord?id=CVE-2012-5807</a>
<b>CVE-2012-3446</b>	Cloud-support library written in Python uses incorrect regular expression when matching hostname. <a href="https://www.cve.org/CVERecord?id=CVE-2012-3446">https://www.cve.org/CVERecord?id=CVE-2012-3446</a>
<b>CVE-2009-2408</b>	Web browser does not correctly handle '\0' character (NUL) in Common Name, allowing spoofing of https sites. <a href="https://www.cve.org/CVERecord?id=CVE-2009-2408">https://www.cve.org/CVERecord?id=CVE-2009-2408</a>
<b>CVE-2012-0867</b>	Database program truncates the Common Name during hostname verification, allowing spoofing. <a href="https://www.cve.org/CVERecord?id=CVE-2012-0867">https://www.cve.org/CVERecord?id=CVE-2012-0867</a>
<b>CVE-2010-2074</b>	Incorrect handling of '\0' character (NUL) in hostname verification allows spoofing. <a href="https://www.cve.org/CVERecord?id=CVE-2010-2074">https://www.cve.org/CVERecord?id=CVE-2010-2074</a>
<b>CVE-2009-4565</b>	Mail server's incorrect handling of '\0' character (NUL) in hostname verification allows spoofing. <a href="https://www.cve.org/CVERecord?id=CVE-2009-4565">https://www.cve.org/CVERecord?id=CVE-2009-4565</a>
<b>CVE-2009-3767</b>	LDAP server's incorrect handling of '\0' character (NUL) in hostname verification allows spoofing. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3767">https://www.cve.org/CVERecord?id=CVE-2009-3767</a>
<b>CVE-2012-5806</b>	Payment processing module does not verify hostname when connecting to PayPal using PHP fsockopen function. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5806">https://www.cve.org/CVERecord?id=CVE-2012-5806</a>
<b>CVE-2012-2993</b>	Smartphone device does not verify hostname, allowing spoofing of mail services. <a href="https://www.cve.org/CVERecord?id=CVE-2012-2993">https://www.cve.org/CVERecord?id=CVE-2012-2993</a>
<b>CVE-2012-5804</b>	E-commerce module does not verify hostname when connecting to payment site. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5804">https://www.cve.org/CVERecord?id=CVE-2012-5804</a>
<b>CVE-2012-5824</b>	Chat application does not validate hostname, leading to loss of privacy. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5824">https://www.cve.org/CVERecord?id=CVE-2012-5824</a>
<b>CVE-2012-5822</b>	Application uses third-party library that does not validate hostname. <a href="https://www.cve.org/CVERecord?id=CVE-2012-5822">https://www.cve.org/CVERecord?id=CVE-2012-5822</a>
<b>CVE-2012-5819</b>	Cloud storage management application does not validate hostname.

Reference	Description
<b>CVE-2012-5817</b>	<a href="https://www.cve.org/CVERecord?id=CVE-2012-5819">https://www.cve.org/CVERecord?id=CVE-2012-5819</a> Java library uses JSSE SSLSocket and SSLEngine classes, which do not verify the hostname.
<b>CVE-2012-5784</b>	<a href="https://www.cve.org/CVERecord?id=CVE-2012-5817">https://www.cve.org/CVERecord?id=CVE-2012-5817</a> SOAP platform does not verify the hostname.
<b>CVE-2012-5782</b>	<a href="https://www.cve.org/CVERecord?id=CVE-2012-5784">https://www.cve.org/CVERecord?id=CVE-2012-5784</a> PHP library for payments does not verify the hostname.
<b>CVE-2012-5780</b>	<a href="https://www.cve.org/CVERecord?id=CVE-2012-5782">https://www.cve.org/CVERecord?id=CVE-2012-5782</a> Merchant SDK for payments does not verify the hostname.
<b>CVE-2003-0355</b>	<a href="https://www.cve.org/CVERecord?id=CVE-2012-5780">https://www.cve.org/CVERecord?id=CVE-2012-5780</a> Web browser does not validate Common Name, allowing spoofing of https sites.
	<a href="https://www.cve.org/CVERecord?id=CVE-2003-0355">https://www.cve.org/CVERecord?id=CVE-2003-0355</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		948	SFP Secondary Cluster: Digital Certificate	888	2395
MemberOf		1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to validate host-specific certificate data

### References

- [REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.
- [REF-245]Martin Georgiev, Subodh Iyengar, Suman Jana, Rishita Anubhai, Dan Boneh and Vitaly Shmatikov. "The Most Dangerous Code in the World: Validating SSL Certificates in Non-Browser Software". 2012 October 5. < [http://www.cs.utexas.edu/~shmat/shmat\\_ccs12.pdf](http://www.cs.utexas.edu/~shmat/shmat_ccs12.pdf) >.
- [REF-243]Sascha Fahl, Marian Harbach, Thomas Muders, Matthew Smith and Lars Baumgärtner, Bernd Freisleben. "Why Eve and Mallory Love Android: An Analysis of Android SSL (In)Security". 2012 October 6. < <http://www2.dcsec.uni-hannover.de/files/android/p50-fahl.pdf> >.
- [REF-249]Kenneth Ballard. "Secure programming with the OpenSSL API, Part 2: Secure handshake". 2005 May 3. < [https://developer.ibm.com/tutorials/l-openssl/?mhsrc=ibmsearch\\_a&mhq=secure%20programming%20with%20the%20openssl%20API](https://developer.ibm.com/tutorials/l-openssl/?mhsrc=ibmsearch_a&mhq=secure%20programming%20with%20the%20openssl%20API) >.2023-04-07.
- [REF-250]Eric Rescorla. "An Introduction to OpenSSL Programming (Part I)". 2001 October 5. < <https://www.linuxjournal.com/article/4822> >.2023-04-07.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-955]Chris McMahon Stone, Tom Chothia and Flavio D. Garcia. "Spinner: Semi-Automatic Detection of Pinning without Hostname Verification". < <http://www.cs.bham.ac.uk/~garcia/publications/spinner.pdf> >.2018-01-16.

## CWE-298: Improper Validation of Certificate Expiration

**Weakness ID :** 298

**Structure :** Simple

**Abstraction :** Variant

### Description

A certificate expiration is not validated or is incorrectly validated, so trust may be assigned to certificates that have been abandoned due to age.





### Extended Description

When the expiration of a certificate is not taken into account, no trust has necessarily been conveyed through it. Therefore, the validity of the certificate cannot be verified and all benefit of the certificate is lost.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		672	Operation on a Resource after Expiration or Release	1479
ChildOf		295	Improper Certificate Validation	714
PeerOf		324	Use of a Key Past its Expiration Date	792
PeerOf		370	Missing Check for Certificate Revocation after Initial Check	917

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	2429

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

Low

### Common Consequences

Scope	Impact	Likelihood
Integrity Other	Other <i>The data read from the system vouched for by the expired certificate may be flawed due to malicious spoofing.</i>	
Authentication Other	Other <i>Trust afforded to the system in question - based on the expired certificate - may allow for spoofing attacks.</i>	

### Potential Mitigations

#### Phase: Architecture and Design

Check for expired certificates and provide the user with adequate information about the nature of the problem and how to proceed.

#### Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the expiration.

## Demonstrative Examples

### Example 1:

The following OpenSSL code ensures that there is a certificate and allows the use of expired certificates.

Example Language: C




(Bad)

```
if (cert = SSL_get_peer(certificate(ssl)) {
    foo=SSL_get_verify_result(ssl);
    if ((X509_V_OK==foo) || (X509_V_ERR_CERT_HAS_EXPIRED==foo))
        //do stuff
```

If the call to `SSL_get_verify_result()` returns `X509_V_ERR_CERT_HAS_EXPIRED`, this means that the certificate has expired. As time goes on, there is an increasing chance for attackers to compromise the certificate.

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	2335
MemberOf		948	SFP Secondary Cluster: Digital Certificate	888	2395
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to validate certificate expiration

## References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

## CWE-299: Improper Check for Certificate Revocation

**Weakness ID :** 299

**Structure :** Simple

**Abstraction :** Base

### Description

The product does not check or incorrectly checks the revocation status of a certificate, which may cause it to use a certificate that has been compromised.

### Extended Description

An improper check for certificate revocation is a far more serious flaw than related certificate failures. This is because the use of any revoked certificate is almost certainly malicious. The most common reason for certificate revocation is compromise of the system in question, with the result that no legitimate servers will be using a revoked certificate, unless they are sorely out of sync.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	980
ChildOf		295	Improper Certificate Validation	714
ParentOf		370	Missing Check for Certificate Revocation after Initial Check	917

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	2429

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

Medium

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>Trust may be assigned to an entity who is not who it claims to be.</i>	
Integrity Other	Other <i>Data from an untrusted (and possibly malicious) source may be integrated.</i>	
Confidentiality	Read Application Data <i>Data may be disclosed to an entity impersonating a trusted entity, resulting in information disclosure.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

#### Phase: Architecture and Design

Ensure that certificates are checked for revoked status.

#### Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the revoked status.

### Demonstrative Examples

#### Example 1:



The following OpenSSL code ensures that there is a certificate before continuing execution.

Example Language: C

(Bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {
    // got a certificate, do secret things
}
```

Because this code does not use `SSL_get_verify_results()` to check the certificate, it could accept certificates that have been revoked (`X509_V_ERR_CERT_REVOKED`). The product could be communicating with a malicious host.

### Observed Examples

Reference	Description
<b>CVE-2011-2014</b>	LDAP-over-SSL implementation does not check Certificate Revocation List (CRL), allowing spoofing using a revoked certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2011-2014">https://www.cve.org/CVERecord?id=CVE-2011-2014</a>
<b>CVE-2011-0199</b>	Operating system does not check Certificate Revocation List (CRL) in some cases, allowing spoofing using a revoked certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2011-0199">https://www.cve.org/CVERecord?id=CVE-2011-0199</a>
<b>CVE-2010-5185</b>	Antivirus product does not check whether certificates from signed executables have been revoked. <a href="https://www.cve.org/CVERecord?id=CVE-2010-5185">https://www.cve.org/CVERecord?id=CVE-2010-5185</a>
<b>CVE-2009-3046</b>	Web browser does not check if any intermediate certificates are revoked. <a href="https://www.cve.org/CVERecord?id=CVE-2009-3046">https://www.cve.org/CVERecord?id=CVE-2009-3046</a>
<b>CVE-2009-0161</b>	chain: Ruby module for OCSP misinterprets a response, preventing detection of a revoked certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2009-0161">https://www.cve.org/CVERecord?id=CVE-2009-0161</a>
<b>CVE-2011-2701</b>	chain: incorrect parsing of replies from OCSP responders allows bypass using a revoked certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2011-2701">https://www.cve.org/CVERecord?id=CVE-2011-2701</a>
<b>CVE-2011-0935</b>	Router can permanently cache certain public keys, which would allow bypass if the certificate is later revoked. <a href="https://www.cve.org/CVERecord?id=CVE-2011-0935">https://www.cve.org/CVERecord?id=CVE-2011-0935</a>
<b>CVE-2009-1358</b>	chain: OS package manager does not properly check the return value, allowing bypass using a revoked certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2009-1358">https://www.cve.org/CVERecord?id=CVE-2009-1358</a>
<b>CVE-2009-0642</b>	chain: language interpreter does not properly check the return value from an OCSP function, allowing bypass using a revoked certificate. <a href="https://www.cve.org/CVERecord?id=CVE-2009-0642">https://www.cve.org/CVERecord?id=CVE-2009-0642</a>
<b>CVE-2008-4679</b>	chain: web service component does not call the expected method, which prevents a check for revoked certificates. <a href="https://www.cve.org/CVERecord?id=CVE-2008-4679">https://www.cve.org/CVERecord?id=CVE-2008-4679</a>
<b>CVE-2006-4410</b>	Certificate revocation list not searched for certain certificates. <a href="https://www.cve.org/CVERecord?id=CVE-2006-4410">https://www.cve.org/CVERecord?id=CVE-2006-4410</a>
<b>CVE-2006-4409</b>	Product cannot access certificate revocation list when an HTTP proxy is being used. <a href="https://www.cve.org/CVERecord?id=CVE-2006-4409">https://www.cve.org/CVERecord?id=CVE-2006-4409</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	948	SFP Secondary Cluster: Digital Certificate	888	2395



Nature	Type	ID	Name	V	Page
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to check for certificate revocation

### References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

## CWE-300: Channel Accessible by Non-Endpoint

**Weakness ID :** 300

**Structure :** Simple

**Abstraction :** Class

### Description

The product does not adequately verify the identity of actors at both ends of a communication channel, or does not adequately ensure the integrity of the channel, in a way that allows the channel to be accessed or influenced by an actor that is not an endpoint.




### Extended Description

In order to establish secure communication between two parties, it is often important to adequately verify the identity of entities at each end of the communication channel. Inadequate or inconsistent verification may result in insufficient or incorrect identification of either communicating entity. This can have negative consequences such as misplaced trust in the entity at the other end of the channel. An attacker can leverage this by interposing between the communicating entities and masquerading as the original entity. In the absence of sufficient verification of identity, such an attacker can eavesdrop and potentially modify the communication between the original entities.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1827
PeerOf		602	Client-Side Enforcement of Server-Side Security	1350
PeerOf		603	Use of Client-Side Authentication	1354

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	2425

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Alternate Terms

**Adversary-in-the-Middle / AITM :**

**Man-in-the-Middle / MITM :**

**Person-in-the-Middle / PITM :**

**Monkey-in-the-Middle :**

**Monster-in-the-Middle :**

**On-path attack :**

**Interception attack :**

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	
Access Control	Gain Privileges or Assume Identity	
	<i>An attacker could pose as one of the entities and read or possibly modify the communication.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

#### Phase: Implementation

Always fully authenticate both ends of any communications channel.

#### Phase: Architecture and Design

Adhere to the principle of complete mediation.

#### Phase: Implementation

A certificate binds an identity to a cryptographic key to authenticate a communicating party. Often, the certificate takes the encrypted form of the hash of the identity of the subject, the public key, and information such as time of issue or expiration using the issuer's private key. The certificate can be validated by deciphering the certificate with the issuer's public key. See also X.509 certificate signature chains and the PGP certification structure.

### Demonstrative Examples

#### Example 1:

In the Java snippet below, data is sent over an unencrypted channel to a remote server.

*Example Language: Java*

*(Bad)*

```
Socket sock;  
PrintWriter out;  
try {  
    sock = new Socket(REMOTE_HOST, REMOTE_PORT);  
    out = new PrintWriter(echoSocket.getOutputStream(), true);  
    // Write data to remote host via socket output stream.  
    ...  
}
```

}

By eavesdropping on the communication channel or posing as the endpoint, an attacker would be able to read all of the transmitted data.

### Observed Examples

Reference	Description
<b>CVE-2014-1266</b>	chain: incorrect "goto" in Apple SSL product bypasses certificate validation, allowing Adversary-in-the-Middle (AiTM) attack (Apple "goto fail" bug). CWE-705 (Incorrect Control Flow Scoping) -> CWE-561 (Dead Code) -> CWE-295 (Improper Certificate Validation) -> CWE-393 (Return of Wrong Status Code) -> CWE-300 (Channel Accessible by Non-Endpoint). <a href="https://www.cve.org/CVERecord?id=CVE-2014-1266">https://www.cve.org/CVERecord?id=CVE-2014-1266</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	2369
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	956	SFP Secondary Cluster: Channel Attack	888	2397
MemberOf	C	1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Maintenance

The summary identifies multiple distinct possibilities, suggesting that this is a category that must be broken into more specific weaknesses.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Man-in-the-middle (MITM)
WASC	32		Routing Detour
The CERT Oracle Secure Coding Standard for Java (2011)	SEC06-J		Do not rely on the default automatic signature verification provided by URLClassLoader and java.util.jar

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
57	Utilizing REST's Trust in the System Resource to Obtain Sensitive Data
94	Adversary in the Middle (AiTM)
466	Leveraging Active Adversary in the Middle Attacks to Bypass Same Origin Policy
589	DNS Blocking
590	IP Address Blocking
612	WiFi MAC Address Tracking
613	WiFi SSID Tracking
615	Evil Twin Wi-Fi Attack
662	Adversary in the Browser (AiTB)

### References

[REF-244]M. Bishop. "Computer Security: Art and Science". 2003. Addison-Wesley.

## CWE-301: Reflection Attack in an Authentication Protocol

**Weakness ID :** 301

**Structure :** Simple

**Abstraction :** Base

### Description

Simple authentication protocols are subject to reflection attacks if a malicious user can use the target machine to impersonate a trusted user.

### Extended Description



A mutual authentication protocol requires each party to respond to a random challenge by the other party by encrypting it with a pre-shared key. Often, however, such protocols employ the same pre-shared key for communication with a number of different entities. A malicious user or an attacker can easily compromise this protocol without possessing the correct key by employing a reflection attack on the protocol.

Reflection attacks capitalize on mutual authentication schemes in order to trick the target into revealing the secret shared between it and another valid user. In a basic mutual-authentication scheme, a secret is known to both the valid user and the server; this allows them to authenticate. In order that they may verify this shared secret without sending it plainly over the wire, they utilize a Diffie-Hellman-style scheme in which they each pick a value, then request the hash of that value as keyed by the shared secret. In a reflection attack, the attacker claims to be a valid user and requests the hash of a random value from the server. When the server returns this value and requests its own value to be hashed, the attacker opens another connection to the server. This time, the hash requested by the attacker is the value which the server requested in the first connection. When the server returns this hashed value, it is used in the first connection, authenticating the attacker successfully as the impersonated valid user.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1390	Weak Authentication	2267
PeerOf		327	Use of a Broken or Risky Cryptographic Algorithm	799

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

Medium

**Common Consequences**

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity  <i>The primary result of reflection attacks is successful authentication with a target machine -- as an impersonated user.</i>	

**Potential Mitigations****Phase: Architecture and Design**

Use different keys for the initiator and responder or of a different type of challenge for the initiator and responder.

**Phase: Architecture and Design**

Let the initiator prove its identity before proceeding.

**Demonstrative Examples****Example 1:**

The following example demonstrates the weakness.

Example Language: C

(Bad)

```
unsigned char *simple_digest(char *alg,char *buf,unsigned int len, int *olen) {
    const EVP_MD *m;
    EVP_MD_CTX ctx;
    unsigned char *ret;
    OpenSSL_add_all_digests();
    if (!(m = EVP_get_digestbyname(alg))) return NULL;
    if (!(ret = (unsigned char*)malloc(EVP_MAX_MD_SIZE))) return NULL;
    EVP_DigestInit(&ctx, m);
    EVP_DigestUpdate(&ctx,buf,len);
    EVP_DigestFinal(&ctx,ret,olen);
    return ret;
}

unsigned char *generate_password_and_cmd(char *password_and_cmd) {
    simple_digest("sha1",password,strlen(password_and_cmd)
    ...
    );
}
```

Example Language: Java

(Bad)





```
String command = new String("some cmd to execute & the password")
MessageDigest encer =
MessageDigest.getInstance("SHA");
encer.update(command.getBytes("UTF-8"));
byte[] digest = encer.digest();
```

**Observed Examples**

Reference	Description
<b>CVE-2005-3435</b>	product authentication succeeds if user-provided MD5 hash matches the hash in its database; this can be subjected to replay attacks. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3435">https://www.cve.org/CVERecord?id=CVE-2005-3435</a>

**MemberOf Relationships**

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		718	OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management	629	2332
MemberOf		884	CWE Cross-section	884	2567
MemberOf		956	SFP Secondary Cluster: Channel Attack	888	2397
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

## Notes

### Maintenance

The term "reflection" is used in multiple ways within CWE and the community, so its usage should be reviewed.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Reflection attack in an auth protocol
OWASP Top Ten 2007	A7	CWE More Specific	Broken Authentication and Session Management

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
90	Reflection Attack in Authentication Protocol

## References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

## CWE-302: Authentication Bypass by Assumed-Immutable Data

**Weakness ID :** 302

**Structure :** Simple

**Abstraction :** Base



## Description

The authentication scheme or implementation uses key data elements that are assumed to be immutable, but can be controlled or modified by the attacker.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		807	Reliance on Untrusted Inputs in a Security Decision	1714
ChildOf		1390	Weak Authentication	2267

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

### Potential Mitigations

**Phase: Architecture and Design**

**Phase: Operation**

**Phase: Implementation**

Implement proper protection for immutable data (e.g. environment variable, hidden form fields, etc.)

### Demonstrative Examples

#### Example 1:

In the following example, an "authenticated" cookie is used to determine whether or not a user should be granted access to a system.

*Example Language: Java*

*(Bad)*

```
boolean authenticated = new Boolean(getCookieValue("authenticated")).booleanValue();
if (authenticated) {
    ...
}
```

Modifying the value of a cookie on the client-side is trivial, but many developers assume that cookies are essentially immutable.






### Observed Examples

Reference	Description
<b>CVE-2002-0367</b>	DebPloit <a href="https://www.cve.org/CVERecord?id=CVE-2002-0367">https://www.cve.org/CVERecord?id=CVE-2002-0367</a>
<b>CVE-2004-0261</b>	Web auth <a href="https://www.cve.org/CVERecord?id=CVE-2004-0261">https://www.cve.org/CVERecord?id=CVE-2004-0261</a>
<b>CVE-2002-1730</b>	Authentication bypass by setting certain cookies to "true". <a href="https://www.cve.org/CVERecord?id=CVE-2002-1730">https://www.cve.org/CVERecord?id=CVE-2002-1730</a>
<b>CVE-2002-1734</b>	Authentication bypass by setting certain cookies to "true". <a href="https://www.cve.org/CVERecord?id=CVE-2002-1734">https://www.cve.org/CVERecord?id=CVE-2002-1734</a>
<b>CVE-2002-2064</b>	Admin access by setting a cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2002-2064">https://www.cve.org/CVERecord?id=CVE-2002-2064</a>
<b>CVE-2002-2054</b>	Gain privileges by setting cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2002-2054">https://www.cve.org/CVERecord?id=CVE-2002-2054</a>
<b>CVE-2004-1611</b>	Product trusts authentication information in cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2004-1611">https://www.cve.org/CVERecord?id=CVE-2004-1611</a>
<b>CVE-2005-1708</b>	Authentication bypass by setting admin-testing variable to true. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1708">https://www.cve.org/CVERecord?id=CVE-2005-1708</a>
<b>CVE-2005-1787</b>	Bypass auth and gain privileges by setting a variable. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1787">https://www.cve.org/CVERecord?id=CVE-2005-1787</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.



Nature	Type	ID	Name	V	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	2335
MemberOf		859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	2369
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	2395
MemberOf		1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Bypass via Assumed-Immutable Data
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
The CERT Oracle Secure Coding Standard for Java (2011)	SEC02-J		Do not base security checks on untrusted sources

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
10	Buffer Overflow via Environment Variables
13	Subverting Environment Variable Values
21	Exploitation of Trusted Identifiers
31	Accessing/Intercepting/Modifying HTTP Cookies
39	Manipulating Opaque Client-based Data Tokens
45	Buffer Overflow via Symbolic Links
77	Manipulating User-Controlled Variables
274	HTTP Verb Tampering

## CWE-303: Incorrect Implementation of Authentication Algorithm

**Weakness ID :** 303

**Structure :** Simple

**Abstraction :** Base

### Description

The requirements for the product dictate the use of an established authentication algorithm, but the implementation of the algorithm is incorrect.


### Extended Description

This incorrect implementation may allow authentication to be bypassed.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1390	Weak Authentication	2267
ParentOf		304	Missing Critical Step in Authentication	738

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences




Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

### Observed Examples

Reference	Description
<b>CVE-2003-0750</b>	Conditional should have been an 'or' not an 'and'. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0750">https://www.cve.org/CVERecord?id=CVE-2003-0750</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	2394
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Logic Error

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
90	Reflection Attack in Authentication Protocol

## CWE-304: Missing Critical Step in Authentication

**Weakness ID** : 304

**Structure** : Simple

**Abstraction** : Base

### Description

The product implements an authentication technique, but it skips a step that weakens the technique.



### Extended Description

Authentication techniques should follow the algorithms that define them exactly, otherwise authentication can be bypassed or more easily subjected to brute force attacks.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1298
ChildOf		303	Incorrect Implementation of Authentication Algorithm	737

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

**Applicable Platforms**

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Common Consequences**

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Integrity	Gain Privileges or Assume Identity	
Confidentiality	Read Application Data	
	Execute Unauthorized Code or Commands	
	<i>This weakness can lead to the exposure of resources or functionality to unintended actors, possibly providing attackers with sensitive information or allowing attackers to execute arbitrary code.</i>	

**Detection Methods****Automated Static Analysis**

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)






*Effectiveness = High*

**Observed Examples**

Reference	Description
<b>CVE-2004-2163</b>	Shared secret not verified in a RADIUS response packet, allowing authentication bypass by spoofing server replies. <a href="https://www.cve.org/CVERecord?id=CVE-2004-2163">https://www.cve.org/CVERecord?id=CVE-2004-2163</a>
<b>CVE-2005-3327</b>	Chain: Authentication bypass by skipping the first startup step as required by the protocol. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3327">https://www.cve.org/CVERecord?id=CVE-2005-3327</a>

**MemberOf Relationships**

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	2335
MemberOf		884	CWE Cross-section	884	2567
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	2394
MemberOf		1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494

Nature	Type	ID	Name	V	Page
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Critical Step in Authentication

## CWE-305: Authentication Bypass by Primary Weakness

**Weakness ID :** 305

**Structure :** Simple

**Abstraction :** Base

### Description

The authentication algorithm is sound, but the implemented mechanism can be bypassed as the result of a separate weakness that is primary to the authentication error.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		1390	Weak Authentication	2267

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	



### Observed Examples

Reference	Description
<b>CVE-2002-1374</b>	The provided password is only compared against the first character of the real password. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1374">https://www.cve.org/CVERecord?id=CVE-2002-1374</a>
<b>CVE-2000-0979</b>	The password is not properly checked, which allows remote attackers to bypass access controls by sending a 1-byte password that matches the first character of the real password. <a href="https://www.cve.org/CVERecord?id=CVE-2000-0979">https://www.cve.org/CVERecord?id=CVE-2000-0979</a>
<b>CVE-2001-0088</b>	Chain: Forum software does not properly initialize an array, which inadvertently sets the password to a single character, allowing remote attackers to easily guess the password and gain administrative privileges.

Reference	Description
	<a href="https://www.cve.org/CVERecord?id=CVE-2001-0088">https://www.cve.org/CVERecord?id=CVE-2001-0088</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	2394
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Notes

#### Relationship

Most "authentication bypass" errors are resultant, not primary.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Bypass by Primary Weakness

## CWE-306: Missing Authentication for Critical Function

**Weakness ID :** 306

**Structure :** Simple

**Abstraction :** Base

### Description

The product does not perform any authentication for functionality that requires a provable user identity or consumes a significant amount of resources.




### Extended Description

As data is migrated to the cloud, if access does not require authentication, it can be easier for attackers to access the data from anywhere on the Internet.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	692
ParentOf		288	Authentication Bypass Using an Alternate Path or Channel	700
ParentOf		322	Key Exchange without Entity Authentication	788


*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	692

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : Cloud Computing (*Prevalence = Undetermined*)

**Technology** : ICS/OT (*Prevalence = Often*)

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
Other	Other	
	<p><i>Exposing critical functionality essentially provides an attacker with the privilege level of that functionality. The consequences will depend on the associated functionality, but they can range from reading or modifying sensitive data, access to administrative or other privileged functionality, or possibly even execution of arbitrary code.</i></p>	

### Detection Methods

#### Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of custom authentication mechanisms.

#### Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authentication. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authentication libraries. Generally, automated static analysis tools have difficulty detecting custom authentication schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an established identity; an automated technique that detects the absence of authentication may report false positives.

*Effectiveness = Limited*

#### Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

*Effectiveness = SOAR Partial*

#### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

*Effectiveness = SOAR Partial*

**Dynamic Analysis with Manual Results Interpretation**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host Application Interface Scanner Fuzz Tester Framework-based Fuzzer

*Effectiveness = SOAR Partial*

**Manual Static Analysis - Source Code**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

*Effectiveness = SOAR Partial*

**Automated Static Analysis - Source Code**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

*Effectiveness = SOAR Partial*

**Architecture or Design Review**

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

*Effectiveness = High*

**Potential Mitigations****Phase: Architecture and Design**

Divide the software into anonymous, normal, privileged, and administrative areas. Identify which of these areas require a proven user identity, and use a centralized authentication capability. Identify all potential communication channels, or other means of interaction with the software, to ensure that all channels are appropriately protected. Developers sometimes perform authentication at the primary channel, but open up a secondary channel that is assumed to be private. For example, a login mechanism may be listening on one network port, but after successful authentication, it may open up a second port where it waits for the connection, but avoids authentication because it assumes that only the authenticated party will connect to the port. In general, if the software or protocol allows a single session or user state to persist across multiple connections or channels, authentication and appropriate credential management need to be used throughout.

**Phase: Architecture and Design**

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

**Phase: Architecture and Design**

Where possible, avoid implementing custom authentication routines and consider using authentication capabilities as provided by the surrounding framework, operating system, or environment. These may make it easier to provide a clear separation between authentication tasks and authorization tasks. In environments such as the World Wide Web, the line between authentication and authorization is sometimes blurred. If custom authentication routines are required instead of those provided by the server, then these routines must be applied to every single page, since these pages could be requested directly.

**Phase: Architecture and Design**



*Strategy = Libraries or Frameworks*

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using libraries with authentication capabilities such as OpenSSL or the ESAPI Authenticator [REF-45].

**Phase: Implementation**

**Phase: System Configuration**

**Phase: Operation**

When storing data in the cloud (e.g., S3 buckets, Azure blobs, Google Cloud Storage, etc.), use the provider's controls to require strong authentication for users who should be allowed to access the data [REF-1297] [REF-1298] [REF-1302].

## Demonstrative Examples

### Example 1:

In the following Java example the method `createBankAccount` is used to create a `BankAccount` object for a bank management application.

*Example Language: Java*

*(Bad)*

```
public BankAccount createBankAccount(String accountNumber, String accountType,
String accountName, String accountSSN, double balance) {
    BankAccount account = new BankAccount();
    account.setAccountNumber(accountNumber);
    account.setAccountType(accountType);
    account.setAccountOwnerName(accountName);
    account.setAccountOwnerSSN(accountSSN);
    account.setBalance(balance);
    return account;
}
```

However, there is no authentication mechanism to ensure that the user creating this bank account object has the authority to create new bank accounts. Some authentication mechanisms should be used to verify that the user has the authority to create bank account objects.

The following Java code includes a boolean variable and method for authenticating a user. If the user has not been authenticated then the `createBankAccount` will not create the bank account object.

*Example Language: Java*

*(Good)*

```
private boolean isUserAuthentic = false;
// authenticate user,
// if user is authenticated then set variable to true
// otherwise set variable to false
public boolean authenticateUser(String username, String password) {
    ...
}
public BankAccount createNewBankAccount(String accountNumber, String accountType,
String accountName, String accountSSN, double balance) {
    BankAccount account = null;
    if (isUserAuthentic) {
        account = new BankAccount();
        account.setAccountNumber(accountNumber);
        account.setAccountType(accountType);
        account.setAccountOwnerName(accountName);
        account.setAccountOwnerSSN(accountSSN);
        account.setBalance(balance);
    }
    return account;
}
```

### Example 2:

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.

Multiple vendors did not use any authentication for critical functionality in their OT products.

### Example 3:

In 2021, a web site operated by PeopleGIS stored data of US municipalities in Amazon Web Service (AWS) Simple Storage Service (S3) buckets.

*Example Language: Other*

*(Bad)*

A security researcher found 86 S3 buckets that could be accessed without authentication (CWE-306) and stored data unencrypted (CWE-312). These buckets exposed over 1000 GB of data and 1.6 million files including physical addresses, phone numbers, tax documents, pictures of driver's license IDs, etc. [REF-1296] [REF-1295]

While it was not publicly disclosed how the data was protected after discovery, multiple options could have been considered.

*Example Language: Other*

*(Good)*

The sensitive information could have been protected by ensuring that the buckets did not have public read access, e.g., by enabling the s3-account-level-public-access-blocks-periodic rule to Block Public Access. In addition, the data could have been encrypted at rest using the appropriate S3 settings, e.g., by enabling server-side encryption using the s3-bucket-server-side-encryption-enabled setting. Other settings are available to further prevent bucket data from being leaked. [REF-1297]















## Observed Examples

Reference	Description
<b>CVE-2022-31260</b>	Chain: a digital asset management program has an undisclosed backdoor in the legacy version of a PHP script (CWE-912) that could allow an unauthenticated user to export metadata (CWE-306) <a href="https://www.cve.org/CVERecord?id=CVE-2022-31260">https://www.cve.org/CVERecord?id=CVE-2022-31260</a>
<b>CVE-2022-29951</b>	TCP-based protocol in Programmable Logic Controller (PLC) has no authentication. <a href="https://www.cve.org/CVERecord?id=CVE-2022-29951">https://www.cve.org/CVERecord?id=CVE-2022-29951</a>
<b>CVE-2022-29952</b>	Condition Monitor firmware uses a protocol that does not require authentication. <a href="https://www.cve.org/CVERecord?id=CVE-2022-29952">https://www.cve.org/CVERecord?id=CVE-2022-29952</a>
<b>CVE-2022-30276</b>	SCADA-based protocol for bridging WAN and LAN traffic has no authentication. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30276">https://www.cve.org/CVERecord?id=CVE-2022-30276</a>
<b>CVE-2022-30313</b>	Safety Instrumented System uses proprietary TCP protocols with no authentication. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30313">https://www.cve.org/CVERecord?id=CVE-2022-30313</a>
<b>CVE-2022-30317</b>	Distributed Control System (DCS) uses a protocol that has no authentication. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30317">https://www.cve.org/CVERecord?id=CVE-2022-30317</a>
<b>CVE-2021-21972</b>	Chain: Cloud computing virtualization platform does not require authentication for upload of a tar format file (CWE-306), then uses .. path traversal sequences (CWE-23) in the file to access unexpected files, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2021-21972">https://www.cve.org/CVERecord?id=CVE-2021-21972</a>

Reference	Description
<b>CVE-2020-10263</b>	Bluetooth speaker does not require authentication for the debug functionality on the UART port, allowing root shell access <a href="https://www.cve.org/CVERecord?id=CVE-2020-10263">https://www.cve.org/CVERecord?id=CVE-2020-10263</a>
<b>CVE-2021-23147</b>	WiFi router does not require authentication for its UART port, allowing adversaries with physical access to execute commands as root <a href="https://www.cve.org/CVERecord?id=CVE-2021-23147">https://www.cve.org/CVERecord?id=CVE-2021-23147</a>
<b>CVE-2021-37415</b>	IT management product does not perform authentication for some REST API requests, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2021-37415">https://www.cve.org/CVERecord?id=CVE-2021-37415</a>
<b>CVE-2020-13927</b>	Default setting in workflow management product allows all API requests without authentication, as exploited in the wild per CISA KEV. <a href="https://www.cve.org/CVERecord?id=CVE-2020-13927">https://www.cve.org/CVERecord?id=CVE-2020-13927</a>
<b>CVE-2002-1810</b>	MFV. Access TFTP server without authentication and obtain configuration file with sensitive plaintext information. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1810">https://www.cve.org/CVERecord?id=CVE-2002-1810</a>
<b>CVE-2008-6827</b>	Agent software running at privileges does not authenticate incoming requests over an unprotected channel, allowing a Shatter" attack. <a href="https://www.cve.org/CVERecord?id=CVE-2008-6827">https://www.cve.org/CVERecord?id=CVE-2008-6827</a>
<b>CVE-2004-0213</b>	Product enforces restrictions through a GUI but not through privileged APIs. <a href="https://www.cve.org/CVERecord?id=CVE-2004-0213">https://www.cve.org/CVERecord?id=CVE-2004-0213</a>
<b>CVE-2020-15483</b>	monitor device allows access to physical UART debug port without authentication <a href="https://www.cve.org/CVERecord?id=CVE-2020-15483">https://www.cve.org/CVERecord?id=CVE-2020-15483</a>
<b>CVE-2019-9201</b>	Programmable Logic Controller (PLC) does not have an authentication feature on its communication protocols. <a href="https://www.cve.org/CVERecord?id=CVE-2019-9201">https://www.cve.org/CVERecord?id=CVE-2019-9201</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		803	2010 Top 25 - Porous Defenses	800	2355
MemberOf		812	OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management	809	2357
MemberOf		866	2011 Top 25 - Porous Defenses	900	2372
MemberOf		884	CWE Cross-section	884	2567
MemberOf		952	SFP Secondary Cluster: Missing Authentication	888	2396
MemberOf		1337	Weaknesses in the 2021 CWE Top 25 Most Dangerous Software Weaknesses	1337	2589
MemberOf		1350	Weaknesses in the 2020 CWE Top 25 Most Dangerous Software Weaknesses	1350	2594
MemberOf		1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf		1364	ICS Communications: Zone Boundary Failures	1358	2501
MemberOf		1365	ICS Communications: Unreliability	1358	2502
MemberOf		1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf		1368	ICS Dependencies (& Architecture): External Digital Systems	1358	2505
MemberOf		1387	Weaknesses in the 2022 CWE Top 25 Most Dangerous Software Weaknesses	1387	2597
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

Nature	Type	ID	Name	V	Page
MemberOf	V	1425	Weaknesses in the 2023 CWE Top 25 Most Dangerous Software Weaknesses	1425	2600

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			No Authentication for Critical Function
Software Fault Patterns	SFP31		Missing authentication
ISA/IEC 62443	Part 4-2		Req CR 1.1
ISA/IEC 62443	Part 4-2		Req CR 1.2
ISA/IEC 62443	Part 4-2		Req CR 2.1
ISA/IEC 62443	Part 4-1		Req SR-2
ISA/IEC 62443	Part 4-1		Req SVV-3

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
12	Choosing Message Identifier
36	Using Unpublished Interfaces or Functionality
62	Cross Site Request Forgery
166	Force the System to Reset Values
216	Communication Channel Manipulation

### References

- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.
- [REF-257]Frank Kim. "Top 25 Series - Rank 19 - Missing Authentication for Critical Function". 2010 February 3. SANS Software Security Institute. < <https://www.sans.org/blog/top-25-series-rank-19-missing-authentication-for-critical-function/> >.2023-04-07.
- [REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.
- [REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.
- [REF-1295]WizCase. "Over 80 US Municipalities' Sensitive Information, Including Resident's Personal Data, Left Vulnerable in Massive Data Breach". 2021 July 0. < <https://www.wizcase.com/blog/us-municipality-breach-report/> >.
- [REF-1296]Jonathan Greig. "1,000 GB of local government data exposed by Massachusetts software company". 2021 July 2. < <https://www.zdnet.com/article/1000-gb-of-local-government-data-exposed-by-massachusetts-software-company/> >.
- [REF-1297]Amazon. "AWS Foundational Security Best Practices controls". 2022. < <https://docs.aws.amazon.com/securityhub/latest/userguide/securityhub-controls-reference.html> >.2023-04-07.
- [REF-1298]Microsoft. "Authentication and authorization in Azure App Service and Azure Functions". 2021 November 3. < <https://learn.microsoft.com/en-us/azure/app-service/overview-authentication-authorization> >.2022-10-11.
- [REF-1302]Google Cloud. "Authentication and authorization use cases". 2022 October 1. < <https://cloud.google.com/docs/authentication/use-cases> >.2022-10-11.

## CWE-307: Improper Restriction of Excessive Authentication Attempts

Weakness ID : 307

**Structure** : Simple  
**Abstraction** : Base

## Description

The product does not implement sufficient measures to prevent multiple failed authentication attempts within a short time frame, making it more susceptible to brute force attacks.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		799	Improper Control of Interaction Frequency	1699
ChildOf		1390	Weak Authentication	2267


*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	692

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism  <i>An attacker could perform an arbitrary number of authentication attempts using different passwords, and eventually gain access to the targeted account.</i>	

## Detection Methods

### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Web Application Scanner Web Services Scanner Database Scanners Cost effective for partial coverage: Host-based Vulnerability Scanners - Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria

*Effectiveness = High*

### Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Fuzz Tester Framework-based Fuzzer Cost effective for partial coverage: Forced Path Execution

*Effectiveness = High*

### Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

*Effectiveness = High*

### Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

*Effectiveness = SOAR Partial*

### Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

*Effectiveness = SOAR Partial*

### Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

Common protection mechanisms include: Disconnecting the user after a small number of failed attempts Implementing a timeout Locking out a targeted account Requiring a computational task on the user's part.

### Phase: Architecture and Design

*Strategy = Libraries or Frameworks*

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Consider using libraries with authentication capabilities such as OpenSSL or the ESAPI Authenticator. [REF-45]

## Demonstrative Examples

### Example 1:

In January 2009, an attacker was able to gain administrator access to a Twitter server because the server did not restrict the number of login attempts [REF-236]. The attacker targeted a member of Twitter's support team and was able to successfully guess the member's password using a brute force attack by guessing a large number of common words. After gaining access as the member of the support staff, the attacker used the administrator panel to gain access to 33 accounts that belonged to celebrities and politicians. Ultimately, fake Twitter messages were sent that appeared to come from the compromised accounts.

### Example 2:

The following code, extracted from a servlet's doPost() method, performs an authentication lookup every time the servlet is invoked.

*Example Language: Java*

*(Bad)*

```
String username = request.getParameter("username");
String password = request.getParameter("password");
int authResult = authenticateUser(username, password);
```



However, the software makes no attempt to restrict excessive authentication attempts.

### Example 3:

This code attempts to limit the number of login attempts by causing the process to sleep before completing the authentication.

Example Language: PHP

(Bad)

```
$username = $_POST['username'];
$password = $_POST['password'];
sleep(2000);
$isAuthenticated = authenticateUser($username, $password);
```

However, there is no limit on parallel connections, so this does not increase the amount of time an attacker needs to complete an attack.

### Example 4:

In the following C/C++ example the validateUser method opens a socket connection, reads a username and password from the socket and attempts to authenticate the username and password.

Example Language: C

(Bad)

```
int validateUser(char *host, int port)
{
    int socket = openSocketConnection(host, port);
    if (socket < 0) {
        printf("Unable to open socket connection");
        return(FAIL);
    }
    int isValidUser = 0;
    char username[USERNAME_SIZE];
    char password[PASSWORD_SIZE];
    while (isValidUser == 0) {
        if (getNextMessage(socket, username, USERNAME_SIZE) > 0) {
            if (getNextMessage(socket, password, PASSWORD_SIZE) > 0) {
                isValidUser = AuthenticateUser(username, password);
            }
        }
    }
    return(SUCCESS);
}
```

The validateUser method will continuously check for a valid username and password without any restriction on the number of authentication attempts made. The method should limit the number of authentication attempts made to prevent brute force attacks as in the following example code.

Example Language: C

(Good)

```
int validateUser(char *host, int port)
{
    ...
    int count = 0;
    while ((isValidUser == 0) && (count < MAX_ATTEMPTS)) {
        if (getNextMessage(socket, username, USERNAME_SIZE) > 0) {
            if (getNextMessage(socket, password, PASSWORD_SIZE) > 0) {
                isValidUser = AuthenticateUser(username, password);
            }
        }
        count++;
    }
    if (isValidUser) {
        return(SUCCESS);
    }
}
```



```

else {
    return(FAIL);
}
}

```

### Example 5:









Consider this example from a real-world attack against the iPhone [REF-1218]. An attacker can use brute force methods; each time there is a failed guess, the attacker quickly cuts the power before the failed entry is recorded, effectively bypassing the intended limit on the number of failed authentication attempts. Note that this attack requires removal of the cell phone battery and connecting directly to the phone's power source, and the brute force attack is still time-consuming.

### Observed Examples

Reference	Description
<b>CVE-2019-0039</b>	the REST API for a network OS has a high limit for number of connections, allowing brute force password guessing <a href="https://www.cve.org/CVERecord?id=CVE-2019-0039">https://www.cve.org/CVERecord?id=CVE-2019-0039</a>
<b>CVE-1999-1152</b>	Product does not disconnect or timeout after multiple failed logins. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1152">https://www.cve.org/CVERecord?id=CVE-1999-1152</a>
<b>CVE-2001-1291</b>	Product does not disconnect or timeout after multiple failed logins. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1291">https://www.cve.org/CVERecord?id=CVE-2001-1291</a>
<b>CVE-2001-0395</b>	Product does not disconnect or timeout after multiple failed logins. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0395">https://www.cve.org/CVERecord?id=CVE-2001-0395</a>
<b>CVE-2001-1339</b>	Product does not disconnect or timeout after multiple failed logins. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1339">https://www.cve.org/CVERecord?id=CVE-2001-1339</a>
<b>CVE-2002-0628</b>	Product does not disconnect or timeout after multiple failed logins. <a href="https://www.cve.org/CVERecord?id=CVE-2002-0628">https://www.cve.org/CVERecord?id=CVE-2002-0628</a>
<b>CVE-1999-1324</b>	User accounts not disabled when they exceed a threshold; possibly a resultant problem. <a href="https://www.cve.org/CVERecord?id=CVE-1999-1324">https://www.cve.org/CVERecord?id=CVE-1999-1324</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	2335
MemberOf		808	2010 Top 25 - Weaknesses On the Cusp	800	2355
MemberOf		812	OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management	809	2357
MemberOf		866	2011 Top 25 - Porous Defenses	900	2372
MemberOf		884	CWE Cross-section	884	2567
MemberOf		955	SFP Secondary Cluster: Unrestricted Authentication	888	2397
MemberOf		1353	OWASP Top Ten 2021 Category A07:2021 - Identification and Authentication Failures	1344	2494
MemberOf		1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER	AUTHENT.MULTFAIL		Multiple Failed Authentication Attempts not Prevented
Software Fault Patterns	SFP34		Unrestricted authentication

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
16	Dictionary-based Password Attack
49	Password Brute Forcing
560	Use of Known Domain Credentials
565	Password Spraying
600	Credential Stuffing
652	Use of Known Kerberos Credentials
653	Use of Known Operating System Credentials

## References

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

[REF-236]Kim Zetter. "Weak Password Brings 'Happiness' to Twitter Hacker". 2009 January 9. < <https://www.wired.com/2009/01/professed-twitt/> >.2023-04-07.

[REF-1218]Graham Cluley. "This Black Box Can Brute Force Crack iPhone PIN Passcodes". The Mac Security Blog. 2015 March 6. < <https://www.intego.com/mac-security-blog/iphone-pin-passcode/> >.

## CWE-308: Use of Single-factor Authentication

**Weakness ID :** 308

**Structure :** Simple

**Abstraction :** Base

## Description

The use of single-factor authentication can lead to unnecessary risk of compromise when compared with the benefits of a dual-factor authentication scheme.





## Extended Description

While the use of multiple authentication schemes is simply piling on more complexity on top of authentication, it is inestimably valuable to have such measures of redundancy. The use of weak, reused, and common passwords is rampant on the internet. Without the added protection of multiple authentication schemes, a single mistake can result in the compromise of an account. For this reason, if multiple schemes are possible and also easy to use, they should be implemented and required.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		654	Reliance on a Single Factor in a Security Decision	1439
ChildOf		1390	Weak Authentication	2267
PeerOf		309	Use of Password System for Primary Authentication	754
PeerOf		309	Use of Password System for Primary Authentication	754

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism  <i>If the secret in a single-factor authentication scheme gets compromised, full authentication is possible.</i>	

### Potential Mitigations

#### Phase: Architecture and Design

Use multiple independent authentication schemes, which ensures that -- if one of the methods is compromised -- the system itself is still likely safe from compromise.

### Demonstrative Examples

#### Example 1:

In both of these examples, a user is logged in if their given password matches a stored password:

*Example Language: C*

*(Bad)*

```

unsigned char *check_passwd(char *plaintext) {
    ctext = simple_digest("sha1",plaintext,strlen(plaintext), ... );
    //Login if hash matches stored hash
    if (equal(ctext, secret_password())) {
        login_user();
    }
}

```

*Example Language: Java*

*(Bad)*

```

String plainText = new String(plainTextIn);
MessageDigest encer = MessageDigest.getInstance("SHA");
encer.update(plainTextIn);
byte[] digest = password.digest();
//Login if hash matches stored hash
if (equal(digest,secret_password())) {
    login_user();
}

```

This code relies exclusively on a password mechanism (CWE-309) using only one factor of authentication (CWE-308). If an attacker can steal or guess a user's password, they are given full access to their account. Note this code also uses SHA-1, which is a weak hash (CWE-328). It also does not use a salt (CWE-759).

### Observed Examples

Reference	Description
<b>CVE-2022-35248</b>	Chat application skips validation when Central Authentication Service (CAS) is enabled, effectively removing the second factor from two-factor authentication <a href="https://www.cve.org/CVERecord?id=CVE-2022-35248">https://www.cve.org/CVERecord?id=CVE-2022-35248</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	947	SFP Secondary Cluster: Authentication Bypass	888	2394
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	2436
MemberOf	C	1368	ICS Dependencies (& Architecture): External Digital Systems	1358	2505
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using single-factor authentication

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
16	Dictionary-based Password Attack
49	Password Brute Forcing
55	Rainbow Table Password Cracking
70	Try Common or Default Usernames and Passwords
509	Kerberoasting
555	Remote Services with Stolen Credentials
560	Use of Known Domain Credentials
561	Windows Admin Shares with Stolen Credentials
565	Password Spraying
600	Credential Stuffing
644	Use of Captured Hashes (Pass The Hash)
645	Use of Captured Tickets (Pass The Ticket)
652	Use of Known Kerberos Credentials
653	Use of Known Operating System Credentials

### References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-309: Use of Password System for Primary Authentication

**Weakness ID :** 309

**Structure :** Simple

**Abstraction :** Base






### Description

The use of password systems as the primary means of authentication may be subject to several flaws or shortcomings, each reducing the effectiveness of the mechanism.


### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		654	Reliance on a Single Factor in a Security Decision	1439
ChildOf		1390	Weak Authentication	2267
PeerOf		308	Use of Single-factor Authentication	752
PeerOf		262	Not Using Password Aging	633
PeerOf		308	Use of Single-factor Authentication	752

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Background Details

Password systems are the simplest and most ubiquitous authentication mechanisms. However, they are subject to such well known attacks, and such frequent compromise that their use in the most simple implementation is not practical.

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity  <i>A password authentication mechanism error will almost always result in attackers being authorized as valid users.</i>	

### Potential Mitigations

#### Phase: Architecture and Design

In order to protect password systems from compromise, the following should be noted: Passwords should be stored safely to prevent insider attack and to ensure that -- if a system is compromised -- the passwords are not retrievable. Due to password reuse, this information may be useful in the compromise of other systems these users work with. In order to protect these passwords, they should be stored encrypted, in a non-reversible state, such that the original text password cannot be extracted from the stored value. Password aging should be strictly enforced to ensure that passwords do not remain unchanged for long periods of time. The longer a password remains in use, the higher the probability that it has been compromised. For this reason, passwords should require refreshing periodically, and users should be informed of the risk of passwords which remain in use for too long. Password strength should be enforced intelligently. Rather than restrict passwords to specific content, or specific length, users should be encouraged to use upper and lower case letters, numbers, and symbols in their passwords. The system should also ensure that no passwords are derived from dictionary words.

#### Phase: Architecture and Design

Use a zero-knowledge password protocol, such as SRP.

#### Phase: Architecture and Design

Ensure that passwords are stored safely and are not reversible.

#### Phase: Architecture and Design

Implement password aging functionality that requires passwords be changed after a certain point.

**Phase: Architecture and Design**

Use a mechanism for determining the strength of a password and notify the user of weak password use.

**Phase: Architecture and Design**

Inform the user of why password protections are in place, how they work to protect data integrity, and why it is important to heed their warnings.

**Demonstrative Examples****Example 1:**

In both of these examples, a user is logged in if their given password matches a stored password:

Example Language: C

(Bad)

```
unsigned char *check_passwd(char *plaintext) {
    ctext = simple_digest("sha1",plaintext,strlen(plaintext), ... );
    //Login if hash matches stored hash
    if (equal(ctext, secret_password())) {
        login_user();
    }
}
```

Example Language: Java

(Bad)

```
String plainText = new String(plainTextIn);
MessageDigest encer = MessageDigest.getInstance("SHA");
encer.update(plainTextIn);
byte[] digest = password.digest();
//Login if hash matches stored hash
if (equal(digest,secret_password())) {
    login_user();
}
```

This code relies exclusively on a password mechanism (CWE-309) using only one factor of authentication (CWE-308). If an attacker can steal or guess a user's password, they are given full access to their account. Note this code also uses SHA-1, which is a weak hash (CWE-328). It also does not use a salt (CWE-759).

**MemberOf Relationships**

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	2335
MemberOf	C	947	SFP Secondary Cluster: Authentication Bypass	888	2394
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

**Taxonomy Mappings**

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using password systems
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management

**Related Attack Patterns**

CAPEC-ID	Attack Pattern Name
16	Dictionary-based Password Attack

CAPEC-ID	Attack Pattern Name
49	Password Brute Forcing
55	Rainbow Table Password Cracking
70	Try Common or Default Usernames and Passwords
509	Kerberoasting
555	Remote Services with Stolen Credentials
560	Use of Known Domain Credentials
561	Windows Admin Shares with Stolen Credentials
565	Password Spraying
600	Credential Stuffing
652	Use of Known Kerberos Credentials
653	Use of Known Operating System Credentials

## References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-311: Missing Encryption of Sensitive Data

**Weakness ID** : 311

**Structure** : Simple

**Abstraction** : Class

## Description

The product does not encrypt sensitive or critical information before storage or transmission.





## Extended Description

The lack of proper data encryption passes up the guarantees of confidentiality, integrity, and accountability that properly implemented encryption conveys.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1520
ParentOf		312	Cleartext Storage of Sensitive Information	764
ParentOf		319	Cleartext Transmission of Sensitive Information	779
PeerOf		327	Use of a Broken or Risky Cryptographic Algorithm	799

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ParentOf		312	Cleartext Storage of Sensitive Information	764
ParentOf		319	Cleartext Transmission of Sensitive Information	779

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

## Applicable Platforms



**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data  <i>If the application does not use a secure channel, such as SSL, to exchange sensitive information, it is possible for an attacker with access to the network traffic to sniff packets from the connection and uncover the data. This attack is not technically difficult, but does require physical access to some portion of the network over which the sensitive data travels. This access is usually somewhere near where the user is connected to the network (such as a colleague on the company network) but can be anywhere along the path from the user to the end server.</i>	
Confidentiality Integrity	Modify Application Data  <i>Omitting the use of encryption in any program which transfers data over a network of any kind should be considered on par with delivering the data sent to each user on the local networks of both the sender and receiver. Worse, this omission allows for the injection of data into a stream of communication between two parties -- with no means for the victims to separate valid data from invalid. In this day of widespread network attacks and password collection sniffers, it is an unnecessary risk to omit encryption from the design of any system which might benefit from it.</i>	

## Detection Methods

### Manual Analysis

The characterization of sensitive data often requires domain-specific understanding, so manual methods are useful. However, manual efforts might not achieve desired code coverage within limited time constraints. Black box methods may produce artifacts (e.g. stored data or unencrypted network transfer) that require manual evaluation.

*Effectiveness = High*

### Automated Analysis

Automated measurement of the entropy of an input/output source may indicate the use or lack of encryption, but human analysis is still required to distinguish intentionally-unencrypted data (e.g. metadata) from sensitive data.

### Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective:  
 Network Sniffer Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer  
 Automated Monitored Execution Man-in-the-middle attack tool

*Effectiveness = High*

### Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective:  
 Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review  
 (not inspections)

*Effectiveness = High*

### Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

*Effectiveness = SOAR Partial*

### Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective:  
 Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal  
 Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

*Effectiveness = High*

## Potential Mitigations

### Phase: Requirements

Clearly specify which data or resources are valuable enough that they should be protected by encryption. Require that any transmission or storage of this data/resource should use well-vetted encryption algorithms.

### Phase: Architecture and Design

Ensure that encryption is properly integrated into the system design, including but not necessarily limited to: Encryption that is needed to store or transmit private data of the users of the system  
 Encryption that is needed to protect the system itself from unauthorized disclosure or tampering  
 Identify the separate needs and contexts for encryption: One-way (i.e., only the user or recipient needs to have the key). This can be achieved using public key cryptography, or other techniques in which the encrypting party (i.e., the product) does not need to have access to a private key.  
 Two-way (i.e., the encryption can be automatically performed on behalf of a user, but the key must be available so that the plaintext can be automatically recoverable by that user). This requires storage of the private key in a format that is recoverable only by the user (or perhaps by the operating system) in a way that cannot be recovered by others. Using threat modeling or other techniques, assume that data can be compromised through a separate vulnerability or weakness, and determine where encryption will be most effective. Ensure that data that should be private is not being inadvertently exposed using weaknesses such as insecure permissions (CWE-732). [REF-7]

### Phase: Architecture and Design

*Strategy = Libraries or Frameworks*

When there is a need to store or transmit sensitive data, use strong, up-to-date cryptographic algorithms to encrypt that data. Select a well-vetted algorithm that is currently considered to be strong by experts in the field, and use well-tested implementations. As with all cryptographic mechanisms, the source code should be available for analysis. For example, US government systems require FIPS 140-2 certification. Do not develop custom or private cryptographic

algorithms. They will likely be exposed to attacks that are well-understood by cryptographers. Reverse engineering techniques are mature. If the algorithm can be compromised if attackers find out how it works, then it is especially weak. Periodically ensure that the cryptography has not become obsolete. Some older algorithms, once thought to require a billion years of computing time, can now be broken in days or hours. This includes MD4, MD5, SHA1, DES, and other algorithms that were once regarded as strong. [REF-267]

### Phase: Architecture and Design

*Strategy = Separation of Privilege*

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design, and the compartmentalization allows for and reinforces privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide the appropriate time to use privileges and the time to drop privileges.

### Phase: Implementation

#### Phase: Architecture and Design

When using industry-approved techniques, use them correctly. Don't cut corners by skipping resource-intensive steps (CWE-325). These steps are often essential for preventing common attacks.

#### Phase: Implementation

*Strategy = Attack Surface Reduction*

Use naming conventions and strong types to make it easier to spot when sensitive data is being used. When creating structures, objects, or other complex entities, separate the sensitive and non-sensitive data as much as possible.

*Effectiveness = Defense in Depth*

*This makes it easier to spot places in the code where data is being used that is unencrypted.*

### Demonstrative Examples

#### Example 1:

This code writes a user's login information to a cookie so the user does not have to login again later.

*Example Language: PHP*

*(Bad)*

```
function persistLogin($username, $password){
    $data = array("username" => $username, "password"=> $password);
    setcookie ("userdata", $data);
}
```

The code stores the user's username and password in plaintext in a cookie on the user's machine. This exposes the user's login information if their computer is compromised by an attacker. Even if the user's machine is not compromised, this weakness combined with cross-site scripting (CWE-79) could allow an attacker to remotely copy the cookie.

Also note this example code also exhibits Plaintext Storage in a Cookie (CWE-315).

#### Example 2:

The following code attempts to establish a connection, read in a password, then store it to a buffer.

*Example Language: C*

*(Bad)*

```
server.sin_family = AF_INET; hp = gethostbyname(argv[1]);
if (hp==NULL) error("Unknown host");
```

```

memcpy( (char *)&server.sin_addr,(char *)hp->h_addr,hp->h_length);
if (argc < 3) port = 80;
else port = (unsigned short)atoi(argv[3]);
server.sin_port = htons(port);
if (connect(sock, (struct sockaddr *)&server, sizeof server) < 0) error("Connecting");
...
while ((n=read(sock,buffer,BUFSIZE-1))!=-1) {
    write(dfd,password_buffer,n);
    ...
}

```

While successful, the program does not encrypt the data before writing it to a buffer, possibly exposing it to unauthorized actors.

### Example 3:

The following code attempts to establish a connection to a site to communicate sensitive information.

Example Language: Java

(Bad)

```

try {
    URL u = new URL("http://www.secret.example.org/");
    HttpURLConnection hu = (HttpURLConnection) u.openConnection();
    hu.setRequestMethod("PUT");
    hu.connect();
    OutputStream os = hu.getOutputStream();
    hu.disconnect();
}
catch (IOException e) {
    //...
}

```

Though a connection is successfully made, the connection is unencrypted and it is possible that all sensitive data sent to or received from the server will be read by unintended actors.














### Observed Examples

Reference	Description
<b>CVE-2009-2272</b>	password and username stored in cleartext in a cookie <a href="https://www.cve.org/CVERecord?id=CVE-2009-2272">https://www.cve.org/CVERecord?id=CVE-2009-2272</a>
<b>CVE-2009-1466</b>	password stored in cleartext in a file with insecure permissions <a href="https://www.cve.org/CVERecord?id=CVE-2009-1466">https://www.cve.org/CVERecord?id=CVE-2009-1466</a>
<b>CVE-2009-0152</b>	chat program disables SSL in some circumstances even when the user says to use SSL. <a href="https://www.cve.org/CVERecord?id=CVE-2009-0152">https://www.cve.org/CVERecord?id=CVE-2009-0152</a>
<b>CVE-2009-1603</b>	Chain: product uses an incorrect public exponent when generating an RSA key, which effectively disables the encryption <a href="https://www.cve.org/CVERecord?id=CVE-2009-1603">https://www.cve.org/CVERecord?id=CVE-2009-1603</a>
<b>CVE-2009-0964</b>	storage of unencrypted passwords in a database <a href="https://www.cve.org/CVERecord?id=CVE-2009-0964">https://www.cve.org/CVERecord?id=CVE-2009-0964</a>
<b>CVE-2008-6157</b>	storage of unencrypted passwords in a database <a href="https://www.cve.org/CVERecord?id=CVE-2008-6157">https://www.cve.org/CVERecord?id=CVE-2008-6157</a>
<b>CVE-2008-6828</b>	product stores a password in cleartext in memory <a href="https://www.cve.org/CVERecord?id=CVE-2008-6828">https://www.cve.org/CVERecord?id=CVE-2008-6828</a>
<b>CVE-2008-1567</b>	storage of a secret key in cleartext in a temporary file <a href="https://www.cve.org/CVERecord?id=CVE-2008-1567">https://www.cve.org/CVERecord?id=CVE-2008-1567</a>
<b>CVE-2008-0174</b>	SCADA product uses HTTP Basic Authentication, which is not encrypted <a href="https://www.cve.org/CVERecord?id=CVE-2008-0174">https://www.cve.org/CVERecord?id=CVE-2008-0174</a>
<b>CVE-2007-5778</b>	login credentials stored unencrypted in a registry key <a href="https://www.cve.org/CVERecord?id=CVE-2007-5778">https://www.cve.org/CVERecord?id=CVE-2007-5778</a>
<b>CVE-2002-1949</b>	Passwords transmitted in cleartext.

Reference	Description
	<a href="https://www.cve.org/CVERecord?id=CVE-2002-1949">https://www.cve.org/CVERecord?id=CVE-2002-1949</a>
<b>CVE-2008-4122</b>	Chain: Use of HTTPS cookie without "secure" flag causes it to be transmitted across unencrypted HTTP. <a href="https://www.cve.org/CVERecord?id=CVE-2008-4122">https://www.cve.org/CVERecord?id=CVE-2008-4122</a>
<b>CVE-2008-3289</b>	Product sends password hash in cleartext in violation of intended policy. <a href="https://www.cve.org/CVERecord?id=CVE-2008-3289">https://www.cve.org/CVERecord?id=CVE-2008-3289</a>
<b>CVE-2008-4390</b>	Remote management feature sends sensitive information including passwords in cleartext. <a href="https://www.cve.org/CVERecord?id=CVE-2008-4390">https://www.cve.org/CVERecord?id=CVE-2008-4390</a>
<b>CVE-2007-5626</b>	Backup routine sends password in cleartext in email. <a href="https://www.cve.org/CVERecord?id=CVE-2007-5626">https://www.cve.org/CVERecord?id=CVE-2007-5626</a>
<b>CVE-2004-1852</b>	Product transmits Blowfish encryption key in cleartext. <a href="https://www.cve.org/CVERecord?id=CVE-2004-1852">https://www.cve.org/CVERecord?id=CVE-2004-1852</a>
<b>CVE-2008-0374</b>	Printer sends configuration information, including administrative password, in cleartext. <a href="https://www.cve.org/CVERecord?id=CVE-2008-0374">https://www.cve.org/CVERecord?id=CVE-2008-0374</a>
<b>CVE-2007-4961</b>	Chain: cleartext transmission of the MD5 hash of password enables attacks against a server that is susceptible to replay (CWE-294). <a href="https://www.cve.org/CVERecord?id=CVE-2007-4961">https://www.cve.org/CVERecord?id=CVE-2007-4961</a>
<b>CVE-2007-4786</b>	Product sends passwords in cleartext to a log server. <a href="https://www.cve.org/CVERecord?id=CVE-2007-4786">https://www.cve.org/CVERecord?id=CVE-2007-4786</a>
<b>CVE-2005-3140</b>	Product sends file with cleartext passwords in e-mail message intended for diagnostic purposes. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3140">https://www.cve.org/CVERecord?id=CVE-2005-3140</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	629	2333
MemberOf		720	OWASP Top Ten 2007 Category A9 - Insecure Communications	629	2333
MemberOf		729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	2338
MemberOf		803	2010 Top 25 - Porous Defenses	800	2355
MemberOf		816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	809	2359
MemberOf		818	OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection	809	2359
MemberOf		861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	2370
MemberOf		866	2011 Top 25 - Porous Defenses	900	2372
MemberOf		930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	2389
MemberOf		934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	2391
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	2576
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436

Nature	Type	ID	Name	V	Page
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	2453
MemberOf	V	1340	CISQ Data Protection Measures	1340	2590
MemberOf	C	1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf	C	1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf	C	1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Relationship

There is an overlapping relationship between insecure storage of sensitive information (CWE-922) and missing encryption of sensitive information (CWE-311). Encryption is often used to prevent an attacker from reading the sensitive data. However, encryption does not prevent the attacker from erasing or overwriting the data.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to encrypt data
OWASP Top Ten 2007	A8	CWE More Specific	Insecure Cryptographic Storage
OWASP Top Ten 2007	A9	CWE More Specific	Insecure Communications
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage
WASC	4		Insufficient Transport Layer Protection
The CERT Oracle Secure Coding Standard for Java (2011)	MSC00-J		Use SSLSocket rather than Socket for secure data exchange
Software Fault Patterns	SFP23		Exposed Data
ISA/IEC 62443	Part 3-3		Req SR 4.1
ISA/IEC 62443	Part 3-3		Req SR 4.3
ISA/IEC 62443	Part 4-2		Req CR 4.1
ISA/IEC 62443	Part 4-2		Req CR 7.3
ISA/IEC 62443	Part 4-2		Req CR 1.5

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
31	Accessing/Intercepting/Modifying HTTP Cookies
37	Retrieve Embedded Sensitive Data
65	Sniff Application Code
157	Sniffing Attacks
158	Sniffing Network Traffic
204	Lifting Sensitive Data Embedded in Cache
383	Harvesting Information via API Event Monitoring
384	Application API Message Manipulation via Man-in-the-Middle
385	Transaction or Event Tampering via Application API Manipulation
386	Application API Navigation Remapping
387	Navigation Remapping To Propagate Malicious Content
388	Application API Button Hijacking
477	Signature Spoofing by Mixing Signed and Unsigned Content
609	Cellular Traffic Intercept

## References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.



[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-265]Frank Kim. "Top 25 Series - Rank 10 - Missing Encryption of Sensitive Data". 2010 February 6. SANS Software Security Institute. < <https://www.sans.org/blog/top-25-series-rank-10-missing-encryption-of-sensitive-data/> >.2023-04-07.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <https://csrc.nist.gov/csrc/media/publications/fips/140/2/final/documents/fips1402.pdf> >.2023-04-07.

## CWE-312: Cleartext Storage of Sensitive Information

**Weakness ID** : 312

**Structure** : Simple

**Abstraction** : Base

### Description

The product stores sensitive information in cleartext within a resource that might be accessible to another control sphere.

### Extended Description

Because the information is stored in cleartext (i.e., unencrypted), attackers could potentially read it. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.









When organizations adopt cloud services, it can be easier for attackers to access the data from anywhere on the Internet.

In some systems/environments such as cloud, the use of "double encryption" (at both the software and hardware layer) might be required, and the developer might be solely responsible for both layers, instead of shared responsibility with the administrator of the broader system/environment.


### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		922	Insecure Storage of Sensitive Information	1825
ChildOf		311	Missing Encryption of Sensitive Data	757
ParentOf		313	Cleartext Storage in a File or on Disk	770
ParentOf		314	Cleartext Storage in the Registry	772
ParentOf		315	Cleartext Storage of Sensitive Information in a Cookie	774
ParentOf		316	Cleartext Storage of Sensitive Information in Memory	775
ParentOf		317	Cleartext Storage of Sensitive Information in GUI	777
ParentOf		318	Cleartext Storage of Sensitive Information in Executable	778



Nature	Type	ID	Name	Page
ParentOf		526	Cleartext Storage of Sensitive Information in an Environment Variable	1234

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		311	Missing Encryption of Sensitive Data	757

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	2312

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : Cloud Computing (*Prevalence = Undetermined*)

**Technology** : ICS/OT (*Prevalence = Undetermined*)

**Technology** : Mobile (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>An attacker with access to the system could read sensitive information stored in cleartext.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

**Phase: Implementation**

**Phase: System Configuration**

**Phase: Operation**

When storing data in the cloud (e.g., S3 buckets, Azure blobs, Google Cloud Storage, etc.), use the provider's controls to encrypt the data at rest. [REF-1297] [REF-1299] [REF-1301]

### Demonstrative Examples

#### Example 1:

The following code excerpt stores a plaintext user account ID in a browser cookie.

*Example Language: Java**(Bad)*

```
response.addCookie( new Cookie("userAccountID", acctID);
```

Because the account ID is in plaintext, the user's account information is exposed if their computer is compromised by an attacker.

**Example 2:**

This code writes a user's login information to a cookie so the user does not have to login again later.

*Example Language: PHP**(Bad)*

```
function persistLogin($username, $password){
    $data = array("username" => $username, "password"=> $password);
    setcookie ("userdata", $data);
}
```

The code stores the user's username and password in plaintext in a cookie on the user's machine. This exposes the user's login information if their computer is compromised by an attacker. Even if the user's machine is not compromised, this weakness combined with cross-site scripting (CWE-79) could allow an attacker to remotely copy the cookie.

Also note this example code also exhibits Plaintext Storage in a Cookie (CWE-315).

**Example 3:**

The following code attempts to establish a connection, read in a password, then store it to a buffer.

*Example Language: C**(Bad)*

```
server.sin_family = AF_INET; hp = gethostbyname(argv[1]);
if (hp==NULL) error("Unknown host");
memcpy( (char *)&server.sin_addr,(char *)hp->h_addr,hp->h_length);
if (argc < 3) port = 80;
else port = (unsigned short)atoi(argv[3]);
server.sin_port = htons(port);
if (connect(sock, (struct sockaddr *)&server, sizeof server) < 0) error("Connecting");
...
while ((n=read(sock,buffer,BUFSIZE-1))!=1) {
    write(dfd,password_buffer,n);
    ...
}
```

While successful, the program does not encrypt the data before writing it to a buffer, possibly exposing it to unauthorized actors.

**Example 4:**

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in cleartext.

This Java example shows a properties file with a cleartext username / password pair.

*Example Language: Java**(Bad)*

```
# Java Web App ResourceBundle properties file
...
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in cleartext.

Example Language: ASP.NET

(Bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in cleartext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information.

#### Example 5:

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.

At least one OT product stored a password in plaintext.

#### Example 6:

In 2021, a web site operated by PeopleGIS stored data of US municipalities in Amazon Web Service (AWS) Simple Storage Service (S3) buckets.

Example Language: Other

(Bad)

A security researcher found 86 S3 buckets that could be accessed without authentication (CWE-306) and stored data unencrypted (CWE-312). These buckets exposed over 1000 GB of data and 1.6 million files including physical addresses, phone numbers, tax documents, pictures of driver's license IDs, etc. [REF-1296] [REF-1295]

While it was not publicly disclosed how the data was protected after discovery, multiple options could have been considered.

Example Language: Other

(Good)

The sensitive information could have been protected by ensuring that the buckets did not have public read access, e.g., by enabling the s3-account-level-public-access-blocks-periodic rule to Block Public Access. In addition, the data could have been encrypted at rest using the appropriate S3 settings, e.g., by enabling server-side encryption using the s3-bucket-server-side-encryption-enabled setting. Other settings are available to further prevent bucket data from being leaked. [REF-1297]

#### Example 7:

Consider the following PowerShell command examples for encryption scopes of Azure storage objects. In the first example, an encryption scope is set for the storage account.

Example Language: Shell

(Bad)

```
New-AzStorageEncryptionScope -ResourceGroupName "MyResourceGroup" -AccountName "MyStorageAccount" -
EncryptionScopeName testscope -StorageEncryption
```

The result (edited and formatted for readability) might be:

Example Language: Other

(Bad)

```
ResourceGroupName: MyResourceGroup, StorageAccountName: MyStorageAccount
```

However, the empty string under `RequireInfrastructureEncryption` indicates this service was not enabled at the time of creation, because the `-RequireInfrastructureEncryption` argument was not specified in the command.

Including the `-RequireInfrastructureEncryption` argument addresses the issue:

*Example Language: Shell*

*(Good)*

```
New-AzStorageEncryptionScope -ResourceGroupName "MyResourceGroup" -AccountName "MyStorageAccount" -
EncryptionScopeName testscope -StorageEncryption -RequireInfrastructureEncryption
```

This produces the report:

*Example Language: Other*

*(Result)*

```
ResourceGroupName: MyResourceGroup, StorageAccountName: MyStorageAccount
```

In a scenario where both software and hardware layer encryption is required ("double encryption"), Azure's infrastructure encryption setting can be enabled via the CLI or Portal. An important note is that infrastructure hardware encryption cannot be enabled or disabled after a blob is created. Furthermore, the default value for infrastructure encryption is disabled in blob creations.











### Observed Examples

Reference	Description
<b>CVE-2022-30275</b>	Remote Terminal Unit (RTU) uses a driver that relies on a password stored in plaintext. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30275">https://www.cve.org/CVERecord?id=CVE-2022-30275</a>
<b>CVE-2009-2272</b>	password and username stored in cleartext in a cookie <a href="https://www.cve.org/CVERecord?id=CVE-2009-2272">https://www.cve.org/CVERecord?id=CVE-2009-2272</a>
<b>CVE-2009-1466</b>	password stored in cleartext in a file with insecure permissions <a href="https://www.cve.org/CVERecord?id=CVE-2009-1466">https://www.cve.org/CVERecord?id=CVE-2009-1466</a>
<b>CVE-2009-0152</b>	chat program disables SSL in some circumstances even when the user says to use SSL. <a href="https://www.cve.org/CVERecord?id=CVE-2009-0152">https://www.cve.org/CVERecord?id=CVE-2009-0152</a>
<b>CVE-2009-1603</b>	Chain: product uses an incorrect public exponent when generating an RSA key, which effectively disables the encryption <a href="https://www.cve.org/CVERecord?id=CVE-2009-1603">https://www.cve.org/CVERecord?id=CVE-2009-1603</a>
<b>CVE-2009-0964</b>	storage of unencrypted passwords in a database <a href="https://www.cve.org/CVERecord?id=CVE-2009-0964">https://www.cve.org/CVERecord?id=CVE-2009-0964</a>
<b>CVE-2008-6157</b>	storage of unencrypted passwords in a database <a href="https://www.cve.org/CVERecord?id=CVE-2008-6157">https://www.cve.org/CVERecord?id=CVE-2008-6157</a>
<b>CVE-2008-6828</b>	product stores a password in cleartext in memory <a href="https://www.cve.org/CVERecord?id=CVE-2008-6828">https://www.cve.org/CVERecord?id=CVE-2008-6828</a>
<b>CVE-2008-1567</b>	storage of a secret key in cleartext in a temporary file <a href="https://www.cve.org/CVERecord?id=CVE-2008-1567">https://www.cve.org/CVERecord?id=CVE-2008-1567</a>
<b>CVE-2008-0174</b>	SCADA product uses HTTP Basic Authentication, which is not encrypted <a href="https://www.cve.org/CVERecord?id=CVE-2008-0174">https://www.cve.org/CVERecord?id=CVE-2008-0174</a>
<b>CVE-2007-5778</b>	login credentials stored unencrypted in a registry key <a href="https://www.cve.org/CVERecord?id=CVE-2007-5778">https://www.cve.org/CVERecord?id=CVE-2007-5778</a>
<b>CVE-2001-1481</b>	Plaintext credentials in world-readable file. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1481">https://www.cve.org/CVERecord?id=CVE-2001-1481</a>
<b>CVE-2005-1828</b>	Password in cleartext in config file. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1828">https://www.cve.org/CVERecord?id=CVE-2005-1828</a>
<b>CVE-2005-2209</b>	Password in cleartext in config file. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2209">https://www.cve.org/CVERecord?id=CVE-2005-2209</a>

Reference	Description
<b>CVE-2002-1696</b>	Decrypted copy of a message written to disk given a combination of options and when user replies to an encrypted message. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1696">https://www.cve.org/CVERecord?id=CVE-2002-1696</a>
<b>CVE-2004-2397</b>	Plaintext storage of private key and passphrase in log file when user imports the key. <a href="https://www.cve.org/CVERecord?id=CVE-2004-2397">https://www.cve.org/CVERecord?id=CVE-2004-2397</a>
<b>CVE-2002-1800</b>	Admin password in plaintext in a cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1800">https://www.cve.org/CVERecord?id=CVE-2002-1800</a>
<b>CVE-2001-1537</b>	Default configuration has cleartext usernames/passwords in cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1537">https://www.cve.org/CVERecord?id=CVE-2001-1537</a>
<b>CVE-2001-1536</b>	Usernames/passwords in cleartext in cookies. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1536">https://www.cve.org/CVERecord?id=CVE-2001-1536</a>
<b>CVE-2005-2160</b>	Authentication information stored in cleartext in a cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2160">https://www.cve.org/CVERecord?id=CVE-2005-2160</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	809	2359
MemberOf		884	CWE Cross-section	884	2567
MemberOf		934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	2391
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf		1368	ICS Dependencies (& Architecture): External Digital Systems	1358	2505
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

### Notes

#### Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage of Sensitive Information
Software Fault Patterns	SFP23		Exposed Data
ISA/IEC 62443	Part 4-2		Req CR 4.1 a)
ISA/IEC 62443	Part 3-3		Req SR 4.1

### Related Attack Patterns

**CAPEC-ID    Attack Pattern Name**

37            Retrieve Embedded Sensitive Data

**References**

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-172]Chris Wysopal. "Mobile App Top 10 List". 2010 December 3. < <https://www.veracode.com/blog/2010/12/mobile-app-top-10-list> >.2023-04-07.

[REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.

[REF-1295]WizCase. "Over 80 US Municipalities' Sensitive Information, Including Resident's Personal Data, Left Vulnerable in Massive Data Breach". 2021 July 0. < <https://www.wizcase.com/blog/us-municipality-breach-report/> >.

[REF-1296]Jonathan Greig. "1,000 GB of local government data exposed by Massachusetts software company". 2021 July 2. < <https://www.zdnet.com/article/1000-gb-of-local-government-data-exposed-by-massachusetts-software-company/> >.

[REF-1297]Amazon. "AWS Foundational Security Best Practices controls". 2022. < <https://docs.aws.amazon.com/securityhub/latest/userguide/securityhub-controls-reference.html> >.2023-04-07.

[REF-1299]Microsoft. "Azure encryption overview". 2022 August 8. < <https://learn.microsoft.com/en-us/azure/security/fundamentals/encryption-overview> >.2022-10-11.

[REF-1301]Google Cloud. "Default encryption at rest". 2022 October 1. < <https://cloud.google.com/docs/security/encryption/default-encryption> >.2022-10-11.

[REF-1307]Center for Internet Security. "CIS Microsoft Azure Foundations Benchmark version 1.5.0". 2022 August 6. < <https://www.cisecurity.org/benchmark/azure> >.2023-01-19.

[REF-1310]Microsoft. "Enable infrastructure encryption for double encryption of data". 2022 July 4. < <https://learn.microsoft.com/en-us/azure/storage/common/infrastructure-encryption-enable> >.2023-01-24.

**CWE-313: Cleartext Storage in a File or on Disk****Weakness ID :** 313**Structure :** Simple**Abstraction :** Variant**Description**

The product stores sensitive information in cleartext in a file, or on disk.

**Extended Description**

The sensitive information could be read by attackers with access to the file, or with physical or administrator access to the raw disk. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

**Relationships**

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	764

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Demonstrative Examples

### Example 1:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in cleartext.

This Java example shows a properties file with a cleartext username / password pair.

*Example Language: Java*

*(Bad)*

```
# Java Web App ResourceBundle properties file
...
webapp ldap.username=secretUsername
webapp ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in cleartext.

*Example Language: ASP.NET*

*(Bad)*

```
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```



Username and password information should not be included in a configuration file or a properties file in cleartext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information.

### Observed Examples

Reference	Description
<b>CVE-2001-1481</b>	Cleartext credentials in world-readable file. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1481">https://www.cve.org/CVERecord?id=CVE-2001-1481</a>
<b>CVE-2005-1828</b>	Password in cleartext in config file. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1828">https://www.cve.org/CVERecord?id=CVE-2005-1828</a>
<b>CVE-2005-2209</b>	Password in cleartext in config file. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2209">https://www.cve.org/CVERecord?id=CVE-2005-2209</a>
<b>CVE-2002-1696</b>	Decrypted copy of a message written to disk given a combination of options and when user replies to an encrypted message. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1696">https://www.cve.org/CVERecord?id=CVE-2002-1696</a>
<b>CVE-2004-2397</b>	Cleartext storage of private key and passphrase in log file when user imports the key. <a href="https://www.cve.org/CVERecord?id=CVE-2004-2397">https://www.cve.org/CVERecord?id=CVE-2004-2397</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf	C	1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf	C	1402	Comprehensive Categorization: Encryption	1400	2527

### Notes

#### Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in File or on Disk
Software Fault Patterns	SFP23		Exposed Data

## CWE-314: Cleartext Storage in the Registry

**Weakness ID :** 314

**Structure :** Simple

**Abstraction :** Variant

### Description

The product stores sensitive information in cleartext in the registry.

### Extended Description

Attackers can read the information by accessing the registry key. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	764

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences




Scope	Impact	Likelihood
Confidentiality	Read Application Data	

## Observed Examples

Reference	Description
<b>CVE-2005-2227</b>	Cleartext passwords in registry key. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2227">https://www.cve.org/CVERecord?id=CVE-2005-2227</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in Registry
Software Fault Patterns	SFP23		Exposed Data

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
37	Retrieve Embedded Sensitive Data

## CWE-315: Cleartext Storage of Sensitive Information in a Cookie

**Weakness ID** : 315

**Structure** : Simple

**Abstraction** : Variant

### Description

The product stores sensitive information in cleartext in a cookie.


### Extended Description

Attackers can use widely-available tools to view the cookie and read the sensitive information. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	764

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Demonstrative Examples

#### Example 1:

The following code excerpt stores a plaintext user account ID in a browser cookie.

*Example Language: Java*

*(Bad)*

```
response.addCookie( new Cookie("userAccountID", acctID);
```




Because the account ID is in plaintext, the user's account information is exposed if their computer is compromised by an attacker.

## Observed Examples

Reference	Description
<b>CVE-2002-1800</b>	Admin password in cleartext in a cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1800">https://www.cve.org/CVERecord?id=CVE-2002-1800</a>
<b>CVE-2001-1537</b>	Default configuration has cleartext usernames/passwords in cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1537">https://www.cve.org/CVERecord?id=CVE-2001-1537</a>
<b>CVE-2001-1536</b>	Usernames/passwords in cleartext in cookies. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1536">https://www.cve.org/CVERecord?id=CVE-2001-1536</a>
<b>CVE-2005-2160</b>	Authentication information stored in cleartext in a cookie. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2160">https://www.cve.org/CVERecord?id=CVE-2005-2160</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1349	OWASP Top Ten 2021 Category A05:2021 - Security Misconfiguration	1344	2493
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in Cookie
Software Fault Patterns	SFP23		Exposed Data

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
31	Accessing/Intercepting/Modifying HTTP Cookies
37	Retrieve Embedded Sensitive Data
39	Manipulating Opaque Client-based Data Tokens
74	Manipulating State

## CWE-316: Cleartext Storage of Sensitive Information in Memory

**Weakness ID** : 316

**Structure** : Simple

**Abstraction** : Variant

### Description

The product stores sensitive information in cleartext in memory.

### Extended Description


The sensitive memory might be saved to disk, stored in a core dump, or remain uncleared if the product crashes, or if the programmer does not properly clear the memory before freeing it.

It could be argued that such problems are usually only exploitable by those with administrator privileges. However, swapping could cause the memory to be written to disk and leave it accessible to physical attack afterwards. Core dump files might have insecure permissions or be stored in archive files that are accessible to untrusted people. Or, uncleared sensitive memory might be inadvertently exposed to attackers due to another weakness.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	764

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	

## Observed Examples





Reference	Description
<b>CVE-2001-1517</b>	Sensitive authentication information in cleartext in memory. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1517">https://www.cve.org/CVERecord?id=CVE-2001-1517</a>
<b>CVE-2001-0984</b>	Password protector leaves passwords in memory when window is minimized, even when "clear password when minimized" is set. <a href="https://www.cve.org/CVERecord?id=CVE-2001-0984">https://www.cve.org/CVERecord?id=CVE-2001-0984</a>
<b>CVE-2003-0291</b>	SSH client does not clear credentials from memory. <a href="https://www.cve.org/CVERecord?id=CVE-2003-0291">https://www.cve.org/CVERecord?id=CVE-2003-0291</a>

## Affected Resources

- Memory

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1348	OWASP Top Ten 2021 Category A04:2021 - Insecure Design	1344	2491
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Relationship

This could be a resultant weakness, e.g. if the compiler removes code that was intended to wipe memory.

## Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in Memory
Software Fault Patterns	SFP23		Exposed Data

## CWE-317: Cleartext Storage of Sensitive Information in GUI

**Weakness ID :** 317

**Structure :** Simple

**Abstraction :** Variant

## Description

The product stores sensitive information in cleartext within the GUI.

## Extended Description

An attacker can often obtain data from a GUI, even if hidden, by using an API to directly access GUI objects such as windows and menus. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	764

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

**Operating\_System :** Windows (*Prevalence = Sometimes*)

## Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory Read Application Data	



## Observed Examples

Reference	Description
<b>CVE-2002-1848</b>	Unencrypted passwords stored in GUI dialog may allow local users to access the passwords.

Reference	Description
	<a href="https://www.cve.org/CVERecord?id=CVE-2002-1848">https://www.cve.org/CVERecord?id=CVE-2002-1848</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

### Notes

#### Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in GUI
Software Fault Patterns	SFP23		Exposed Data

## CWE-318: Cleartext Storage of Sensitive Information in Executable

**Weakness ID :** 318

**Structure :** Simple

**Abstraction :** Variant

### Description

The product stores sensitive information in cleartext in an executable.

### Extended Description

Attackers can reverse engineer binary code to obtain secret data. This is especially easy when the cleartext is plain ASCII. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	764

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)



## Common Consequences



Scope	Impact	Likelihood
Confidentiality	Read Application Data	

## Observed Examples

Reference	Description
<b>CVE-2005-1794</b>	Product stores RSA private key in a DLL and uses it to sign a certificate, allowing spoofing of servers and Adversary-in-the-Middle (AIM) attacks. <a href="https://www.cve.org/CVERecord?id=CVE-2005-1794">https://www.cve.org/CVERecord?id=CVE-2005-1794</a>
<b>CVE-2001-1527</b>	administration passwords in cleartext in executable <a href="https://www.cve.org/CVERecord?id=CVE-2001-1527">https://www.cve.org/CVERecord?id=CVE-2001-1527</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in Executable

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
37	Retrieve Embedded Sensitive Data
65	Sniff Application Code

## CWE-319: Cleartext Transmission of Sensitive Information

**Weakness ID :** 319

**Structure :** Simple

**Abstraction :** Base

### Description

The product transmits sensitive or security-critical data in cleartext in a communication channel that can be sniffed by unauthorized actors.

### Extended Description

Many communication channels can be "sniffed" (monitored) by adversaries during data transmission. For example, in networking, packets can traverse many intermediary nodes from the source to the destination, whether across the internet, an internal network, the cloud, etc. Some actors might have privileged access to a network interface or any link along the channel, such as

a router, but they might not be authorized to collect the underlying data. As a result, network traffic could be sniffed by adversaries, spilling security-critical data.




Applicable communication channels are not limited to software products. Applicable channels include hardware-specific technologies such as internal hardware networks and external debug channels, supporting remote JTAG debugging. When mitigations are not applied to combat adversaries within the product's threat model, this weakness significantly lowers the difficulty of exploitation by such adversaries.

When full communications are recorded or logged, such as with a packet dump, an adversary could attempt to obtain the dump long after the transmission has occurred and try to "sniff" the cleartext from the recorded communications in the dump itself. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.


## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		311	Missing Encryption of Sensitive Data	757
ParentOf		5	J2EE Misconfiguration: Data Transmission Without Encryption	1
ParentOf		614	Sensitive Cookie in HTTPS Session Without 'Secure' Attribute	1373

*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ChildOf		311	Missing Encryption of Sensitive Data	757

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	2312

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : Cloud Computing (*Prevalence = Undetermined*)

**Technology** : Mobile (*Prevalence = Undetermined*)

**Technology** : ICS/OT (*Prevalence = Often*)

**Technology** : System on Chip (*Prevalence = Undetermined*)

**Technology** : Test/Debug Hardware (*Prevalence = Often*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Integrity	Read Application Data	
Confidentiality	Modify Files or Directories	
	<i>Anyone can read the information by gaining access to the channel being used for communication.</i>	

## Detection Methods

### Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process, trigger the feature that sends the data, and look for the presence or absence of common cryptographic functions in the call tree. Monitor the network and determine if the data packets contain readable commands. Tools exist for detecting if certain encodings are in use. If the traffic contains high entropy, this might indicate the usage of encryption.

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

Before transmitting, encrypt the data using reliable, confidentiality-protecting cryptographic protocols.

### Phase: Implementation

When using web applications with SSL, use SSL for the entire session from login to logout, not just for the initial login page.

### Phase: Implementation

When designing hardware platforms, ensure that approved encryption algorithms (such as those recommended by NIST) protect paths from security critical data to trusted user applications.

### Phase: Testing

Use tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

### Phase: Operation

Configure servers to use encrypted channels for communication, which may include SSL or other secure protocols.

## Demonstrative Examples

### Example 1:

The following code attempts to establish a connection to a site to communicate sensitive information.

*Example Language: Java*

*(Bad)*

```
try {
    URL u = new URL("http://www.secret.example.org/");
    HttpURLConnection hu = (HttpURLConnection) u.openConnection();
    hu.setRequestMethod("PUT");
    hu.connect();
    OutputStream os = hu.getOutputStream();
    hu.disconnect();
}
catch (IOException e) {
    //...
}
```

Though a connection is successfully made, the connection is unencrypted and it is possible that all sensitive data sent to or received from the server will be read by unintended actors.

### Example 2:

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.

Multiple vendors used cleartext transmission of sensitive information in their OT products.

### Example 3:

A TAP accessible register is read/written by a JTAG based tool, for internal use by authorized users. However, an adversary can connect a probing device and collect the values from the unencrypted channel connecting the JTAG interface to the authorized user, if no additional protections are employed.

### Example 4:

The following Azure CLI command lists the properties of a particular storage account:

*Example Language: Shell*

*(Informative)*

```
az storage account show -g {ResourceGroupName} -n {StorageAccountName}
```

The JSON result might be:

*Example Language: JSON*

*(Bad)*

```
{
  "name": "{StorageAccountName}",
  "enableHttpsTrafficOnly": false,
  "type": "Microsoft.Storage/storageAccounts"
}
```

The enableHttpsTrafficOnly value is set to false, because the default setting for Secure transfer is set to Disabled. This allows cloud storage resources to successfully connect and transfer data without the use of encryption (e.g., HTTP, SMB 2.1, SMB 3.0, etc.).

Azure's storage accounts can be configured to only accept requests from secure connections made over HTTPS. The secure transfer setting can be enabled using Azure's Portal (GUI) or programmatically by setting the enableHttpsTrafficOnly property to True on the storage account, such as:

Example Language: Shell

(Good)

```
az storage account update -g {ResourceGroupName} -n {StorageAccountName} --https-only true
```

The change can be confirmed from the result by verifying that the enableHttpsTrafficOnly value is true:

Example Language: JSON

(Good)

```
{
  "name": "{StorageAccountName}",
  "enableHttpsTrafficOnly": true,
  "type": "Microsoft.Storage/storageAccounts"
}
```

Note: to enable secure transfer using Azure's Portal instead of the command line:














1. Open the Create storage account pane in the Azure portal.
2. In the Advanced page, select the Enable secure transfer checkbox.

### Observed Examples

Reference	Description
<b>CVE-2022-29519</b>	Programmable Logic Controller (PLC) sends sensitive information in plaintext, including passwords and session tokens. <a href="https://www.cve.org/CVERecord?id=CVE-2022-29519">https://www.cve.org/CVERecord?id=CVE-2022-29519</a>
<b>CVE-2022-30312</b>	Building Controller uses a protocol that transmits authentication credentials in plaintext. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30312">https://www.cve.org/CVERecord?id=CVE-2022-30312</a>
<b>CVE-2022-31204</b>	Programmable Logic Controller (PLC) sends password in plaintext. <a href="https://www.cve.org/CVERecord?id=CVE-2022-31204">https://www.cve.org/CVERecord?id=CVE-2022-31204</a>
<b>CVE-2002-1949</b>	Passwords transmitted in cleartext. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1949">https://www.cve.org/CVERecord?id=CVE-2002-1949</a>
<b>CVE-2008-4122</b>	Chain: Use of HTTPS cookie without "secure" flag causes it to be transmitted across unencrypted HTTP. <a href="https://www.cve.org/CVERecord?id=CVE-2008-4122">https://www.cve.org/CVERecord?id=CVE-2008-4122</a>
<b>CVE-2008-3289</b>	Product sends password hash in cleartext in violation of intended policy. <a href="https://www.cve.org/CVERecord?id=CVE-2008-3289">https://www.cve.org/CVERecord?id=CVE-2008-3289</a>
<b>CVE-2008-4390</b>	Remote management feature sends sensitive information including passwords in cleartext. <a href="https://www.cve.org/CVERecord?id=CVE-2008-4390">https://www.cve.org/CVERecord?id=CVE-2008-4390</a>
<b>CVE-2007-5626</b>	Backup routine sends password in cleartext in email. <a href="https://www.cve.org/CVERecord?id=CVE-2007-5626">https://www.cve.org/CVERecord?id=CVE-2007-5626</a>
<b>CVE-2004-1852</b>	Product transmits Blowfish encryption key in cleartext. <a href="https://www.cve.org/CVERecord?id=CVE-2004-1852">https://www.cve.org/CVERecord?id=CVE-2004-1852</a>
<b>CVE-2008-0374</b>	Printer sends configuration information, including administrative password, in cleartext. <a href="https://www.cve.org/CVERecord?id=CVE-2008-0374">https://www.cve.org/CVERecord?id=CVE-2008-0374</a>
<b>CVE-2007-4961</b>	Chain: cleartext transmission of the MD5 hash of password enables attacks against a server that is susceptible to replay (CWE-294). <a href="https://www.cve.org/CVERecord?id=CVE-2007-4961">https://www.cve.org/CVERecord?id=CVE-2007-4961</a>
<b>CVE-2007-4786</b>	Product sends passwords in cleartext to a log server. <a href="https://www.cve.org/CVERecord?id=CVE-2007-4786">https://www.cve.org/CVERecord?id=CVE-2007-4786</a>
<b>CVE-2005-3140</b>	Product sends file with cleartext passwords in e-mail message intended for diagnostic purposes. <a href="https://www.cve.org/CVERecord?id=CVE-2005-3140">https://www.cve.org/CVERecord?id=CVE-2005-3140</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		751	2009 Top 25 - Insecure Interaction Between Components	750	2352
MemberOf		818	OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection	809	2359
MemberOf		858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	2368
MemberOf		859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	2369
MemberOf		884	CWE Cross-section	884	2567
MemberOf		934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	2391
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	2400
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436
MemberOf		1148	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)	1133	2451
MemberOf		1207	Debug and Test Problems	1194	2474
MemberOf		1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf		1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Maintenance

The Taxonomy\_Mappings to ISA/IEC 62443 were added in CWE 4.10, but they are still under review and might change in future CWE versions. These draft mappings were performed by members of the "Mapping CWE to 62443" subgroup of the CWE-CAPEC ICS/OT Special Interest Group (SIG), and their work is incomplete as of CWE 4.10. The mappings are included to facilitate discussion and review by the broader ICS/OT community, and they are likely to change in future CWE versions.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Transmission of Sensitive Information
The CERT Oracle Secure Coding Standard for Java (2011)	SEC06-J		Do not rely on the default automatic signature verification provided by URLClassLoader and java.util.jar
The CERT Oracle Secure Coding Standard for Java (2011)	SER02-J		Sign then seal sensitive objects before sending them outside a trust boundary
Software Fault Patterns	SFP23		Exposed Data
ISA/IEC 62443	Part 3-3		Req SR 4.1
ISA/IEC 62443	Part 4-2		Req CR 4.1B

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
65	Sniff Application Code
102	Session Sidejacking



CAPEC-ID	Attack Pattern Name
117	Interception
383	Harvesting Information via API Event Monitoring
477	Signature Spoofing by Mixing Signed and Unsigned Content

## References

[REF-271]OWASP. "Top 10 2007-Insecure Communications". 2007. < [http://www.owasp.org/index.php/Top\\_10\\_2007-A9](http://www.owasp.org/index.php/Top_10_2007-A9) >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-172]Chris Wysopal. "Mobile App Top 10 List". 2010 December 3. < <https://www.veracode.com/blog/2010/12/mobile-app-top-10-list> >.2023-04-07.

[REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.

[REF-1307]Center for Internet Security. "CIS Microsoft Azure Foundations Benchmark version 1.5.0". 2022 August 6. < <https://www.cisecurity.org/benchmark/azure> >.2023-01-19.

[REF-1309]Microsoft. "Require secure transfer to ensure secure connections". 2022 July 4. < <https://learn.microsoft.com/en-us/azure/storage/common/storage-require-secure-transfer> >.2023-01-24.

## CWE-321: Use of Hard-coded Cryptographic Key

**Weakness ID** : 321

**Structure** : Simple

**Abstraction** : Variant





### Description

The use of a hard-coded cryptographic key significantly increases the possibility that encrypted data may be recovered.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		798	Use of Hard-coded Credentials	1690
PeerOf		259	Use of Hard-coded Password	623
PeerOf		1291	Public Key Re-Use for Signing both Debug and Production Code	2145
CanFollow		656	Reliance on Security Through Obscurity	1444

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428



Relevant to the view "CISQ Quality Measures (2020)" (CWE-1305)

Nature	Type	ID	Name	Page
ChildOf		798	Use of Hard-coded Credentials	1690

Relevant to the view "CISQ Data Protection Measures" (CWE-1340)

Nature	Type	ID	Name	Page
ChildOf		798	Use of Hard-coded Credentials	1690

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : ICS/OT (*Prevalence = Undetermined*)

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity  <i>If hard-coded cryptographic keys are used, it is almost certain that malicious users will gain access through the account in question.</i>	

### Detection Methods

#### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

### Potential Mitigations

#### Phase: Architecture and Design

Prevention schemes mirror that of hard-coded password storage.

### Demonstrative Examples

#### Example 1:

The following code examples attempt to verify a password using a hard-coded cryptographic key.

Example Language: C

(Bad)

```
int VerifyAdmin(char *password) {
    if (strcmp(password,"68af404b513073584c4b6f22b6c63e6b")) {
        printf("Incorrect Password!\n");
        return(0);
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

Example Language: Java

(Bad)

```
public boolean VerifyAdmin(String password) {
    if (password.equals("68af404b513073584c4b6f22b6c63e6b")) {
```

```
System.out.println("Entering Diagnostic Mode...");
return true;
}
System.out.println("Incorrect Password!");
return false;
```

Example Language: C#

(Bad)

```
int VerifyAdmin(String password) {
    if (password.Equals("68af404b513073584c4b6f22b6c63e6b")) {
        Console.WriteLine("Entering Diagnostic Mode...");
        return(1);
    }
    Console.WriteLine("Incorrect Password!");
    return(0);
}
```

The cryptographic key is within a hard-coded string value that is compared to the password. It is likely that an attacker will be able to read the key and compromise the system.

### Example 2:

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.







Multiple vendors used hard-coded keys for critical functionality in their OT products.

### Observed Examples

Reference	Description
<b>CVE-2022-29960</b>	Engineering Workstation uses hard-coded cryptographic keys that could allow for unauthorized filesystem access and privilege escalation <a href="https://www.cve.org/CVERecord?id=CVE-2022-29960">https://www.cve.org/CVERecord?id=CVE-2022-29960</a>
<b>CVE-2022-30271</b>	Remote Terminal Unit (RTU) uses a hard-coded SSH private key that is likely to be used by default. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30271">https://www.cve.org/CVERecord?id=CVE-2022-30271</a>
<b>CVE-2020-10884</b>	WiFi router service has a hard-coded encryption key, allowing root access <a href="https://www.cve.org/CVERecord?id=CVE-2020-10884">https://www.cve.org/CVERecord?id=CVE-2020-10884</a>
<b>CVE-2014-2198</b>	Communications / collaboration product has a hardcoded SSH private key, allowing access to root account <a href="https://www.cve.org/CVERecord?id=CVE-2014-2198">https://www.cve.org/CVERecord?id=CVE-2014-2198</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	629	2333
MemberOf		720	OWASP Top Ten 2007 Category A9 - Insecure Communications	629	2333
MemberOf		729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	2338
MemberOf		950	SFP Secondary Cluster: Hardcoded Sensitive Data	888	2396
MemberOf		1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488

Nature	Type	ID	Name	V	Page
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

## Notes

### Other

The main difference between the use of hard-coded passwords and the use of hard-coded cryptographic keys is the false sense of security that the former conveys. Many people believe that simply hashing a hard-coded password before storage will protect the information from malicious users. However, many hashes are reversible (or at least vulnerable to brute force attacks) -- and further, many authentication protocols simply request the hash itself, making it no better than a password.

### Maintenance

The Taxonomy\_Mappings to ISA/IEC 62443 were added in CWE 4.10, but they are still under review and might change in future CWE versions. These draft mappings were performed by members of the "Mapping CWE to 62443" subgroup of the CWE-CAPEC ICS/OT Special Interest Group (SIG), and their work is incomplete as of CWE 4.10. The mappings are included to facilitate discussion and review by the broader ICS/OT community, and they are likely to change in future CWE versions.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Use of hard-coded cryptographic key
OWASP Top Ten 2007	A8	CWE More Specific	Insecure Cryptographic Storage
OWASP Top Ten 2007	A9	CWE More Specific	Insecure Communications
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage
Software Fault Patterns	SFP33		Hardcoded sensitive data
ISA/IEC 62443	Part 2-4		Req SP.03.10 RE(1)
ISA/IEC 62443	Part 2-4		Req SP.03.10 RE(3)
ISA/IEC 62443	Part 3-3		Req SR 1.5
ISA/IEC 62443	Part 3-3		Req SR 4.3
ISA/IEC 62443	Part 4-1		Req SD-1
ISA/IEC 62443	Part 4-2		Req SR 4.3
ISA/IEC 62443	Part 4-2		Req CR 7.3

## References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

[REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.

## CWE-322: Key Exchange without Entity Authentication

**Weakness ID :** 322

**Structure :** Simple

**Abstraction :** Base

## Description

The product performs a key exchange with an actor without verifying the identity of that actor.

## Extended Description





Performing a key exchange will preserve the integrity of the information sent between two entities, but this will not guarantee that the entities are who they claim they are. This may enable an

attacker to impersonate an actor by modifying traffic between the two entities. Typically, this involves a victim client that contacts a malicious server that is impersonating a trusted server. If the client skips authentication or ignores an authentication failure, the malicious server may request authentication information from the user. The malicious server can then use this authentication information to log in to the trusted server using the victim's credentials, sniff traffic between the victim and trusted server, etc.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.





### Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		306	Missing Authentication for Critical Function	741
PeerOf		295	Improper Certificate Validation	714
PeerOf		295	Improper Certificate Validation	714
CanPrecede		923	Improper Restriction of Communication Channel to Intended Endpoints	1827

### Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	2424

### Relevant to the view "Software Development" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1211	Authentication Errors	2475
MemberOf		1214	Data Integrity Issues	2477
MemberOf		320	Key Management Errors	2319
MemberOf		417	Communication Channel Errors	2325

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Likelihood Of Exploit

High

## Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>No authentication takes place in this process, bypassing an assumed protection of encryption.</i>	
Confidentiality	Read Application Data <i>The encrypted communication between a user and a trusted host may be subject to sniffing by any actor in the communication path.</i>	

## Potential Mitigations

### Phase: Architecture and Design

Ensure that proper authentication is included in the system design.

### Phase: Implementation

Understand and properly implement all checks necessary to ensure the identity of entities involved in encrypted communications.

### Demonstrative Examples

#### Example 1:

Many systems have used Diffie-Hellman key exchange without authenticating the entities exchanging keys, allowing attackers to influence communications by redirecting or interfering with the communication path. Many people using SSL/TLS skip the authentication (often unknowingly).

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	2398
MemberOf	C	1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf	C	1396	Comprehensive Categorization: Access Control	1400	2519

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Key exchange without entity authentication

### References

- [REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

## CWE-323: Reusing a Nonce, Key Pair in Encryption

**Weakness ID :** 323

**Structure :** Simple

**Abstraction :** Base

### Description

Nonces should be used for the present occasion and only once.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	E	344	Use of Invariant Value in Dynamically Changing Context	849

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		320	Key Management Errors	2319

### Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

### Background Details

Nonces are often bundled with a key in a communication exchange to produce a new session key for each exchange.

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity  <i>Potentially a replay attack, in which an attacker could send the same data twice, could be crafted if nonces are allowed to be reused. This could allow a user to send a message which masquerades as a valid message from a valid user.</i>	

### Potential Mitigations

#### Phase: Implementation

Refuse to reuse nonce values.

#### Phase: Implementation

Use techniques such as requiring incrementing, time based and/or challenge response to assure uniqueness of nonces.

### Demonstrative Examples

#### Example 1:

This code takes a password, concatenates it with a nonce, then encrypts it before sending over a network:

*Example Language: C*

*(Bad)*

```
void encryptAndSendPassword(char *password){
    char *nonce = "bad";
    ...
    char *data = (unsigned char*)malloc(20);
    int para_size = strlen(nonce) + strlen(password);
    char *paragraph = (char*)malloc(para_size);
    SHA1((const unsigned char*)paragraph,parsize,(unsigned char*)data);
    sendEncryptedData(data)
}
```

Because the nonce used is always the same, an attacker can impersonate a trusted party by intercepting and resending the encrypted password. This attack avoids the need to learn the unencrypted password.

#### Example 2:

This code sends a command to a remote server, using an encrypted password and nonce to prove the command is from a trusted party:

Example Language: C++

(Bad)

```
String command = new String("some command to execute");
MessageDigest nonce = MessageDigest.getInstance("SHA");
nonce.update(String.valueOf("bad nonce"));
byte[] nonce = nonce.digest();
MessageDigest password = MessageDigest.getInstance("SHA");
password.update(nonce + "secretPassword");
byte[] digest = password.digest();
sendCommand(digest, command)
```

Once again the nonce used is always the same. An attacker may be able to replay previous legitimate commands or execute new arbitrary commands.

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	2398
MemberOf	C	1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf	C	1414	Comprehensive Categorization: Randomness	1400	2543

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Reusing a nonce, key pair in encryption

### References

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-324: Use of a Key Past its Expiration Date

**Weakness ID :** 324

**Structure :** Simple

**Abstraction :** Base

### Description

The product uses a cryptographic key or password past its expiration date, which diminishes its safety significantly by increasing the timing window for cracking attacks against that key.

### Extended Description

While the expiration of keys does not necessarily ensure that they are compromised, it is a significant concern that keys which remain in use for prolonged periods of time have a decreasing probability of integrity. For this reason, it is important to replace keys within a period of time proportional to their strength.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to



similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		672	Operation on a Resource after Expiration or Release	1479
PeerOf		298	Improper Validation of Certificate Expiration	726
PeerOf		262	Not Using Password Aging	633

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management Errors	2315
MemberOf		310	Cryptographic Issues	2318
MemberOf		320	Key Management Errors	2319

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

### Likelihood Of Exploit

Low

### Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity  <i>The cryptographic key in question may be compromised, providing a malicious user with a method for authenticating as the victim.</i>	

### Potential Mitigations

#### Phase: Architecture and Design

Adequate consideration should be put in to the user interface in order to notify users previous to the key's expiration, to explain the importance of new key generation and to walk users through the process as painlessly as possible.

### Demonstrative Examples

#### Example 1:

The following code attempts to verify that a certificate is valid.

*Example Language: C*

*(Bad)*

```
if (cert = SSL_get_peer_certificate(ssl)) {
    foo=SSL_get_verify_result(ssl);
    if ((X509_V_OK==foo) || (X509_V_ERRCERT_NOT_YET_VALID==foo))
        //do stuff
}
```




The code checks if the certificate is not yet valid, but it fails to check if a certificate is past its expiration date, thus treating expired certificates as valid.

### Observed Examples

Reference	Description
<b>CVE-2021-33020</b>	Picture Archiving and Communication System (PACS) system for hospitals uses a cryptographic key or password past its expiration date <a href="https://www.cve.org/CVERecord?id=CVE-2021-33020">https://www.cve.org/CVERecord?id=CVE-2021-33020</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		959	SFP Secondary Cluster: Weak Cryptography	888	2398
MemberOf		1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using a key past its expiration date

### References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

## CWE-325: Missing Cryptographic Step

**Weakness ID** : 325

**Structure** : Simple

**Abstraction** : Base



### Description

The product does not implement a required step in a cryptographic algorithm, resulting in weaker encryption than advertised by the algorithm.

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1298
PeerOf		358	Improperly Implemented Security Check for Standard	881

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	2318

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : Not Technology-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Confidentiality	Read Application Data	
Integrity	Modify Application Data	
Accountability	Hide Activities	
Non-Repudiation		

## Demonstrative Examples

### Example 1:

The example code is taken from the HMAC engine inside the buggy OpenPiton SoC of HACK@DAC'21 [REF-1358]. HMAC is a message authentication code (MAC) that uses both a hash and a secret crypto key. The HMAC engine in HACK@DAC SoC uses the SHA-256 module for the calculation of the HMAC for 512 bits messages.

*Example Language: Verilog*

*(Bad)*

```
logic [511:0] bigData;
...
hmac hmac(
    .clk_i(clk_i),
    .rst_ni(rst_ni && ~rst_4),
    .init_i(startHash && ~startHash_r),
    .key_i(key),
    .ikey_hash_i(ikey_hash),
    .okey_hash_i(okey_hash),
    .key_hash_bypass_i(key_hash_bypass),
    .message_i(bigData),
    .hash_o(hash),
    .ready_o(ready),
    .hash_valid_o(hashValid)
```

However, this HMAC engine cannot handle messages that are longer than 512 bits. Moreover, a complete HMAC will contain an iterate hash function that breaks up a message into blocks of a fixed size and iterates over them with a compression function (e.g., SHA-256). Therefore, the implementation of the HMAC in OpenPiton SoC is incomplete. Such HMAC engines will not be used in real-world applications as the messages will usually be longer than 512 bits. For instance, OpenTitan offers a comprehensive HMAC implementation that utilizes a FIFO for temporarily storing the truncated message, as detailed in [REF-1359].

To mitigate this, implement the iterative function to break up a message into blocks of a fixed size.

## Observed Examples











Reference	Description
<b>CVE-2001-1585</b>	Missing challenge-response step allows authentication bypass using public key. <a href="https://www.cve.org/CVERecord?id=CVE-2001-1585">https://www.cve.org/CVERecord?id=CVE-2001-1585</a>

## Functional Areas

- Cryptography

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	629	2333
MemberOf		720	OWASP Top Ten 2007 Category A9 - Insecure Communications	629	2333
MemberOf		884	CWE Cross-section	884	2567
MemberOf		934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	2391
MemberOf		958	SFP Secondary Cluster: Broken Cryptography	888	2398
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436
MemberOf		1205	Security Primitives and Cryptography Issues	1194	2473
MemberOf		1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf		1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Relationship

Overlaps incomplete/missing security check.

### Relationship

Can be resultant.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Required Cryptographic Step
OWASP Top Ten 2007	A8	CWE More Specific	Insecure Cryptographic Storage
OWASP Top Ten 2007	A9	CWE More Specific	Insecure Communications

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
68	Subvert Code-signing Facilities

## References

[REF-1358]"hmac\_wrapper.sv". 2021. < [https://github.com/HACK-EVENT/hackatdac21/blob/main/piton/design/chip/tile/ariane/src/hmac/hmac\\_wrapper.sv#L41](https://github.com/HACK-EVENT/hackatdac21/blob/main/piton/design/chip/tile/ariane/src/hmac/hmac_wrapper.sv#L41) >.2023-07-15.

[REF-1359]"HMAC HWIP Technical Specification". 2023. < <https://opentitan.org/book/hw/ip/hmac/> >.2023-10-05.

## CWE-326: Inadequate Encryption Strength

**Weakness ID** : 326

**Structure** : Simple

**Abstraction** : Class

## Description

The product stores or transmits sensitive data using an encryption scheme that is theoretically sound, but is not strong enough for the level of protection required.

## Extended Description

A weak encryption scheme can be subjected to brute force attacks that have a reasonable chance of succeeding using current attack methods and resources.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf	P	693	Protection Mechanism Failure	1520
ParentOf	Ⓔ	328	Use of Weak Hash	806

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf	Ⓒ	1013	Encrypt Data	2428

## Applicable Platforms

**Language :** Not Language-Specific (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Access Control Confidentiality	Bypass Protection Mechanism Read Application Data  <i>An attacker may be able to decrypt the data using brute force attacks.</i>	

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

Use an encryption scheme that is currently considered to be strong by experts in the field.











## Observed Examples

Reference	Description
<b>CVE-2001-1546</b>	Weak encryption <a href="https://www.cve.org/CVERecord?id=CVE-2001-1546">https://www.cve.org/CVERecord?id=CVE-2001-1546</a>
<b>CVE-2004-2172</b>	Weak encryption (chosen plaintext attack) <a href="https://www.cve.org/CVERecord?id=CVE-2004-2172">https://www.cve.org/CVERecord?id=CVE-2004-2172</a>
<b>CVE-2002-1682</b>	Weak encryption <a href="https://www.cve.org/CVERecord?id=CVE-2002-1682">https://www.cve.org/CVERecord?id=CVE-2002-1682</a>
<b>CVE-2002-1697</b>	Weak encryption produces same ciphertext from the same plaintext blocks. <a href="https://www.cve.org/CVERecord?id=CVE-2002-1697">https://www.cve.org/CVERecord?id=CVE-2002-1697</a>
<b>CVE-2002-1739</b>	Weak encryption

Reference	Description
	<a href="https://www.cve.org/CVERecord?id=CVE-2002-1739">https://www.cve.org/CVERecord?id=CVE-2002-1739</a>
<b>CVE-2005-2281</b>	Weak encryption scheme <a href="https://www.cve.org/CVERecord?id=CVE-2005-2281">https://www.cve.org/CVERecord?id=CVE-2005-2281</a>
<b>CVE-2002-1872</b>	Weak encryption (XOR) <a href="https://www.cve.org/CVERecord?id=CVE-2002-1872">https://www.cve.org/CVERecord?id=CVE-2002-1872</a>
<b>CVE-2002-1910</b>	Weak encryption (reversible algorithm). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1910">https://www.cve.org/CVERecord?id=CVE-2002-1910</a>
<b>CVE-2002-1946</b>	Weak encryption (one-to-one mapping). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1946">https://www.cve.org/CVERecord?id=CVE-2002-1946</a>
<b>CVE-2002-1975</b>	Encryption error uses fixed salt, simplifying brute force / dictionary attacks (overlaps randomness). <a href="https://www.cve.org/CVERecord?id=CVE-2002-1975">https://www.cve.org/CVERecord?id=CVE-2002-1975</a>

### MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	629	2333
MemberOf		720	OWASP Top Ten 2007 Category A9 - Insecure Communications	629	2333
MemberOf		729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	2338
MemberOf		816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	809	2359
MemberOf		934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	2391
MemberOf		959	SFP Secondary Cluster: Weak Cryptography	888	2398
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	2576
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436
MemberOf		1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Weak Encryption
OWASP Top Ten 2007	A8	CWE More Specific	Insecure Cryptographic Storage
OWASP Top Ten 2007	A9	CWE More Specific	Insecure Communications
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
20	Encryption Brute Forcing
112	Brute Force
192	Protocol Analysis

### References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

## CWE-327: Use of a Broken or Risky Cryptographic Algorithm

**Weakness ID** : 327

**Structure** : Simple

**Abstraction** : Class

### Description

The product uses a broken or risky cryptographic algorithm or protocol.

### Extended Description

Cryptographic algorithms are the methods by which data is scrambled to prevent observation or influence by unauthorized actors. Insecure cryptography can be exploited to expose sensitive information, modify data in unexpected ways, spoof identities of other users or devices, or other impacts.

It is very difficult to produce a secure algorithm, and even high-profile algorithms by accomplished cryptographic experts have been broken. Well-known techniques exist to break or weaken various kinds of cryptography. Accordingly, there are a small number of well-understood and heavily studied algorithms that should be used by most products. Using a non-standard or known-insecure algorithm is dangerous because a determined adversary may be able to break the algorithm and compromise whatever data has been protected.








Since the state of cryptography advances so rapidly, it is common for an algorithm to be considered "unsafe" even if it was once thought to be strong. This can happen when new attacks are discovered, or if computing power increases so much that the cryptographic algorithm no longer provides the amount of protection that was originally thought.

For a number of reasons, this weakness is even more challenging to manage with hardware deployment of cryptographic algorithms as opposed to software implementation. First, if a flaw is discovered with hardware-implemented cryptography, the flaw cannot be fixed in most cases without a recall of the product, because hardware is not easily replaceable like software. Second, because the hardware product is expected to work for years, the adversary's computing power will only increase over time.

### Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1520
ParentOf		328	Use of Weak Hash	806
ParentOf		780	Use of RSA Algorithm without OAEP	1644
ParentOf		1240	Use of a Cryptographic Primitive with a Risky Implementation	2025
PeerOf		311	Missing Encryption of Sensitive Data	757
PeerOf		301	Reflection Attack in an Authentication Protocol	733
CanFollow		208	Observable Timing Discrepancy	529



*Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)*

Nature	Type	ID	Name	Page
ParentOf		916	Use of Password Hash With Insufficient Computational Effort	1813

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Language** : Verilog (*Prevalence = Undetermined*)

**Language** : VHDL (*Prevalence = Undetermined*)

**Technology** : Not Technology-Specific (*Prevalence = Undetermined*)

**Technology** : ICS/OT (*Prevalence = Undetermined*)

### Likelihood Of Exploit

High

### Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>The confidentiality of sensitive data may be compromised by the use of a broken or risky cryptographic algorithm.</i>	
Integrity	Modify Application Data <i>The integrity of sensitive data may be compromised by the use of a broken or risky cryptographic algorithm.</i>	
Accountability Non-Repudiation	Hide Activities <i>If the cryptographic algorithm is used to ensure the identity of the source of the data (such as digital signatures), then a broken algorithm will compromise this scheme and the source of the data cannot be proven.</i>	

### Detection Methods

#### Automated Analysis

Automated methods may be useful for recognizing commonly-used libraries or features that have become obsolete.

*Effectiveness = Moderate*

*False negatives may occur if the tool is not aware of the cryptographic libraries in use, or if custom cryptography is being used.*

#### Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

#### Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness

analysis Binary Weakness Analysis - including disassembler + source code weakness analysis  
Binary / Bytecode simple extractor - strings, ELF readers, etc.

*Effectiveness = SOAR Partial*

### Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

*Effectiveness = SOAR Partial*

### Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Man-in-the-middle attack tool Cost effective for partial coverage: Framework-based Fuzzer Automated Monitored Execution Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

*Effectiveness = High*

### Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

*Effectiveness = High*

### Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

*Effectiveness = High*

### Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

*Effectiveness = SOAR Partial*

### Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

*Strategy = Libraries or Frameworks*

When there is a need to store or transmit sensitive data, use strong, up-to-date cryptographic algorithms to encrypt that data. Select a well-vetted algorithm that is currently considered to be strong by experts in the field, and use well-tested implementations. As with all cryptographic mechanisms, the source code should be available for analysis. For example, US government systems require FIPS 140-2 certification [REF-1192]. Do not develop custom or private

cryptographic algorithms. They will likely be exposed to attacks that are well-understood by cryptographers. Reverse engineering techniques are mature. If the algorithm can be compromised if attackers find out how it works, then it is especially weak. Periodically ensure that the cryptography has not become obsolete. Some older algorithms, once thought to require a billion years of computing time, can now be broken in days or hours. This includes MD4, MD5, SHA1, DES, and other algorithms that were once regarded as strong. [REF-267]

### Phase: Architecture and Design

Ensure that the design allows one cryptographic algorithm to be replaced with another in the next generation or version. Where possible, use wrappers to make the interfaces uniform. This will make it easier to upgrade to stronger algorithms. With hardware, design the product at the Intellectual Property (IP) level so that one cryptographic algorithm can be replaced with another in the next generation of the hardware product.

*Effectiveness = Defense in Depth*

### Phase: Architecture and Design

Carefully manage and protect cryptographic keys (see CWE-320). If the keys can be guessed or stolen, then the strength of the cryptography itself is irrelevant.

### Phase: Architecture and Design

*Strategy = Libraries or Frameworks*

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Industry-standard implementations will save development time and may be more likely to avoid errors that can occur during implementation of cryptographic algorithms. Consider the ESAPI Encryption feature.

### Phase: Implementation

### Phase: Architecture and Design

When using industry-approved techniques, use them correctly. Don't cut corners by skipping resource-intensive steps (CWE-325). These steps are often essential for preventing common attacks.

## Demonstrative Examples

### Example 1:

These code examples use the Data Encryption Standard (DES).

*Example Language: C*

*(Bad)*

```
EVP_des_ecb();
```

*Example Language: Java*

*(Bad)*

```
Cipher des=Cipher.getInstance("DES...");
des.initEncrypt(key2);
```

*Example Language: PHP*

*(Bad)*

```
function encryptPassword($password){
    $iv_size = mcrypt_get_iv_size(MCRYPT_DES, MCRYPT_MODE_ECB);
    $iv = mcrypt_create_iv($iv_size, MCRYPT_RAND);
    $key = "This is a password encryption key";
    $encryptedPassword = mcrypt_encrypt(MCRYPT_DES, $key, $password, MCRYPT_MODE_ECB, $iv);
    return $encryptedPassword;
}
```

Once considered a strong algorithm, DES now regarded as insufficient for many applications. It has been replaced by Advanced Encryption Standard (AES).

**Example 2:**

Suppose a chip manufacturer decides to implement a hashing scheme for verifying integrity property of certain bitstream, and it chooses to implement a SHA1 hardware accelerator for to implement the scheme.

*Example Language: Other*

*(Bad)*

The manufacturer chooses a SHA1 hardware accelerator for to implement the scheme because it already has a working SHA1 Intellectual Property (IP) that the manufacturer had created and used earlier, so this reuse of IP saves design cost.

However, SHA1 was theoretically broken in 2005 and practically broken in 2017 at a cost of \$110K. This means an attacker with access to cloud-rented computing power will now be able to provide a malicious bitstream with the same hash value, thereby defeating the purpose for which the hash was used.

This issue could have been avoided with better design.

*Example Language: Other*

*(Good)*

The manufacturer could have chosen a cryptographic solution that is recommended by the wide security community (including standard-setting bodies like NIST) and is not expected to be broken (or even better, weakened) within the reasonable life expectancy of the hardware product. In this case, the architects could have used SHA-2 or SHA-3, even if it meant that such choice would cost extra.

**Example 3:**

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.

Multiple OT products used weak cryptography.

**Observed Examples**

Reference	Description
<b>CVE-2022-30273</b>	SCADA-based protocol supports a legacy encryption mode that uses Tiny Encryption Algorithm (TEA) in ECB mode, which leaks patterns in messages and cannot protect integrity <a href="https://www.cve.org/CVERecord?id=CVE-2022-30273">https://www.cve.org/CVERecord?id=CVE-2022-30273</a>
<b>CVE-2022-30320</b>	Programmable Logic Controller (PLC) uses a protocol with a cryptographically insecure hashing algorithm for passwords. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30320">https://www.cve.org/CVERecord?id=CVE-2022-30320</a>
<b>CVE-2008-3775</b>	Product uses "ROT-25" to obfuscate the password in the registry. <a href="https://www.cve.org/CVERecord?id=CVE-2008-3775">https://www.cve.org/CVERecord?id=CVE-2008-3775</a>
<b>CVE-2007-4150</b>	product only uses "XOR" to obfuscate sensitive data <a href="https://www.cve.org/CVERecord?id=CVE-2007-4150">https://www.cve.org/CVERecord?id=CVE-2007-4150</a>
<b>CVE-2007-5460</b>	product only uses "XOR" and a fixed key to obfuscate sensitive data <a href="https://www.cve.org/CVERecord?id=CVE-2007-5460">https://www.cve.org/CVERecord?id=CVE-2007-5460</a>
<b>CVE-2005-4860</b>	Product substitutes characters with other characters in a fixed way, and also leaves certain input characters unchanged. <a href="https://www.cve.org/CVERecord?id=CVE-2005-4860">https://www.cve.org/CVERecord?id=CVE-2005-4860</a>
<b>CVE-2002-2058</b>	Attackers can infer private IP addresses by dividing each octet by the MD5 hash of '20'. <a href="https://www.cve.org/CVERecord?id=CVE-2002-2058">https://www.cve.org/CVERecord?id=CVE-2002-2058</a>
<b>CVE-2008-3188</b>	Product uses DES when MD5 has been specified in the configuration, resulting in weaker-than-expected password hashes.

Reference	Description
	<a href="https://www.cve.org/CVERecord?id=CVE-2008-3188">https://www.cve.org/CVERecord?id=CVE-2008-3188</a>
<b>CVE-2005-2946</b>	Default configuration of product uses MD5 instead of stronger algorithms that are available, simplifying forgery of certificates. <a href="https://www.cve.org/CVERecord?id=CVE-2005-2946">https://www.cve.org/CVERecord?id=CVE-2005-2946</a>
<b>CVE-2007-6013</b>	Product uses the hash of a hash for authentication, allowing attackers to gain privileges if they can obtain the original hash. <a href="https://www.cve.org/CVERecord?id=CVE-2007-6013">https://www.cve.org/CVERecord?id=CVE-2007-6013</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	2338
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	2353
MemberOf	C	803	2010 Top 25 - Porous Defenses	800	2355
MemberOf	C	816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	809	2359
MemberOf	C	866	2011 Top 25 - Porous Defenses	900	2372
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	2381
MemberOf	V	884	CWE Cross-section	884	2567
MemberOf	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	2391
MemberOf	C	958	SFP Secondary Cluster: Broken Cryptography	888	2398
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	2576
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436
MemberOf	C	1131	CISQ Quality Measures (2016) - Security	1128	2442
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	2453
MemberOf	C	1170	SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)	1154	2463
MemberOf	C	1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf	C	1366	ICS Communications: Frail Security in Protocols	1358	2503
MemberOf	C	1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Maintenance

Since CWE 4.4, various cryptography-related entries, including CWE-327 and CWE-1240, have been slated for extensive research, analysis, and community consultation to define consistent terminology, improve relationships, and reduce overlap or duplication. As of CWE 4.6, this work is still ongoing.

### Maintenance

The Taxonomy\_Mappings to ISA/IEC 62443 were added in CWE 4.10, but they are still under review and might change in future CWE versions. These draft mappings were performed by members of the "Mapping CWE to 62443" subgroup of the CWE-CAPEC ICS/OT Special Interest Group (SIG), and their work is incomplete as of CWE 4.10. The mappings are included to

facilitate discussion and review by the broader ICS/OT community, and they are likely to change in future CWE versions.

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using a broken or risky cryptographic algorithm
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage
CERT C Secure Coding	MSC30-C	CWE More Abstract	Do not use the rand() function for generating pseudorandom numbers
CERT C Secure Coding	MSC32-C	CWE More Abstract	Properly seed pseudorandom number generators
The CERT Oracle Secure Coding Standard for Java (2011)	MSC02-J		Generate strong random numbers
OMG ASCSM	ASCSM-CWE-327		
ISA/IEC 62443	Part 3-3		Req SR 4.3
ISA/IEC 62443	Part 4-2		Req CR 4.3

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name
20	Encryption Brute Forcing
97	Cryptanalysis
459	Creating a Rogue Certification Authority Certificate
473	Signature Spoof
475	Signature Spoofing by Improper Validation
608	Cryptanalysis of Cellular Encryption
614	Rooting SIM Cards

### References

- [REF-280]Bruce Schneier. "Applied Cryptography". 1996. John Wiley & Sons. < <https://www.schneier.com/books/applied-cryptography> >.2023-04-07.
- [REF-281]Alfred J. Menezes, Paul C. van Oorschot and Scott A. Vanstone. "Handbook of Applied Cryptography". 1996 October. < <https://cacr.uwaterloo.ca/hac/> >.2023-04-07.
- [REF-282]C Matthew Curtin. "Avoiding bogus encryption products: Snake Oil FAQ". 1998 April 0. < <http://www.faqs.org/faqs/cryptography-faq/snake-oil/> >.
- [REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <https://csrc.nist.gov/csrc/media/publications/fips/140/2/final/documents/fips1402.pdf> >.2023-04-07.
- [REF-284]Paul F. Roberts. "Microsoft Scraps Old Encryption in New Code". 2005 September 5. < <https://www.eweek.com/security/microsoft-scraps-old-encryption-in-new-code/> >.2023-04-07.
- [REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-287]Johannes Ullrich. "Top 25 Series - Rank 24 - Use of a Broken or Risky Cryptographic Algorithm". 2010 March 5. SANS Software Security Institute. < <https://www.sans.org/blog/top-25-series-use-of-a-broken-or-risky-cryptographic-algorithm/> >.2023-04-07.



[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

[REF-18]Secure Software, Inc.. "The CLASP Application Security Process". 2005. < <https://cwe.mitre.org/documents/sources/TheCLASPApplicationSecurityProcess.pdf> >.

[REF-1192]Information Technology Laboratory, National Institute of Standards and Technology. "FIPS PUB 140-3: SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2019 March 2. < <https://csrc.nist.gov/publications/detail/fips/140/3/final> >.

[REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.

## CWE-328: Use of Weak Hash

**Weakness ID** : 328

**Structure** : Simple

**Abstraction** : Base

### Description

The product uses an algorithm that produces a digest (output value) that does not meet security expectations for a hash function that allows an adversary to reasonably determine the original input (preimage attack), find another input that can produce the same hash (2nd preimage attack), or find multiple inputs that evaluate to the same hash (birthday attack).

### Extended Description

A hash function is defined as an algorithm that maps arbitrarily sized data into a fixed-sized digest (output) such that the following properties hold:

1. The algorithm is not invertible (also called "one-way" or "not reversible")
2. The algorithm is deterministic; the same input produces the same digest every time

Building on this definition, a cryptographic hash function must also ensure that a malicious actor cannot leverage the hash function to have a reasonable chance of success at determining any of the following:

1. the original input (preimage attack), given only the digest
2. another input that can produce the same digest (2nd preimage attack), given the original input
3. a set of two or more inputs that evaluate to the same digest (birthday attack), given the actor can arbitrarily choose the inputs to be hashed and can do so a reasonable amount of times

What is regarded as "reasonable" varies by context and threat model, but in general, "reasonable" could cover any attack that is more efficient than brute force (i.e., on average, attempting half of all possible combinations). Note that some attacks might be more efficient than brute force but are still not regarded as achievable in the real world.

Any algorithm that does not meet the above conditions will generally be considered weak for general use in hashing.

In addition to algorithmic weaknesses, a hash function can be made weak by using the hash in a security context that breaks its security guarantees. For example, using a hash function without a salt for storing passwords (that are sufficiently short) could enable an adversary to create a






"rainbow table" [REF-637] to recover the password under certain conditions; this attack works against such hash functions as MD5, SHA-1, and SHA-2.

## Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		326	Inadequate Encryption Strength	796
ChildOf		327	Use of a Broken or Risky Cryptographic Algorithm	799
ParentOf		916	Use of Password Hash With Insufficient Computational Effort	1813

*Relevant to the view "Architectural Concepts" (CWE-1008)*

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	2428

*Relevant to the view "Software Development" (CWE-699)*

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	2318

## Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)

**Technology** : ICS/OT (*Prevalence = Undetermined*)

## Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

## Detection Methods

### Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

## Potential Mitigations

### Phase: Architecture and Design

Use an adaptive hash function that can be configured to change the amount of computational effort needed to compute the hash, such as the number of iterations ("stretching") or the amount of memory required. Some hash functions perform salting automatically. These functions can significantly increase the overhead for a brute force attack compared to intentionally-fast functions such as MD5. For example, rainbow table attacks can become infeasible due to the high computing overhead. Finally, since computing power gets faster and cheaper over time, the technique can be reconfigured to increase the workload without forcing an entire replacement of the algorithm in use. Some hash functions that have one or more of these desired properties include bcrypt [REF-291], scrypt [REF-292], and PBKDF2 [REF-293]. While there is active

debate about which of these is the most effective, they are all stronger than using salts with hash functions with very little computing overhead. Note that using these functions can have an impact on performance, so they require special consideration to avoid denial-of-service attacks. However, their configurability provides finer control over how much CPU and memory is used, so it could be adjusted to suit the environment's needs.

*Effectiveness = High*

## Demonstrative Examples

### Example 1:

In both of these examples, a user is logged in if their given password matches a stored password:

*Example Language: C*

*(Bad)*

```
unsigned char *check_passwd(char *plaintext) {
    ctext = simple_digest("sha1",plaintext,strlen(plaintext), ... );
    //Login if hash matches stored hash
    if (equal(ctext, secret_password())) {
        login_user();
    }
}
```

*Example Language: Java*

*(Bad)*

```
String plainText = new String(plainTextIn);
MessageDigest encer = MessageDigest.getInstance("SHA");
encer.update(plainTextIn);
byte[] digest = password.digest();
//Login if hash matches stored hash
if (equal(digest,secret_password())) {
    login_user();
}
```

This code relies exclusively on a password mechanism (CWE-309) using only one factor of authentication (CWE-308). If an attacker can steal or guess a user's password, they are given full access to their account. Note this code also uses SHA-1, which is a weak hash (CWE-328). It also does not use a salt (CWE-759).

### Example 2:

In 2022, the OT:ICEFALL study examined products by 10 different Operational Technology (OT) vendors. The researchers reported 56 vulnerabilities and said that the products were "insecure by design" [REF-1283]. If exploited, these vulnerabilities often allowed adversaries to change how the products operated, ranging from denial of service to changing the code that the products executed. Since these products were often used in industries such as power, electrical, water, and others, there could even be safety implications.

At least one OT product used weak hashes.

### Example 3:

The example code below is taken from the JTAG access control mechanism of the Hack@DAC'21 buggy OpenPiton SoC [REF-1360]. Access to JTAG allows users to access sensitive information in the system. Hence, access to JTAG is controlled using cryptographic authentication of the users. In this example (see the vulnerable code source), the password checker uses HMAC-SHA256 for authentication. It takes a 512-bit secret message from the user, hashes it using HMAC, and compares its output with the expected output to determine the authenticity of the user.

*Example Language: Verilog*

*(Bad)*

```
...
logic [31:0] data_d, data_q
logic [512-1:0] pass_data;
```

```
...
Write: begin
...
    if (pass_mode) begin
        pass_data = { {60{8'h00}}, data_d};
        state_d = PassChk;
        pass_mode = 1'b0;
    ...
    end
...

```

The vulnerable code shows an incorrect implementation of the HMAC authentication where it only uses the least significant 32 bits of the secret message for the authentication (the remaining 480 bits are hard coded as zeros). As a result, the system is susceptible to brute-force attacks where the attacker only needs to determine 32 bits of the secret message instead of 512 bits, weakening the cryptographic protocol.

To mitigate, remove the zero padding and use all 512 bits of the secret message for HMAC authentication [REF-1361].

*Example Language: Verilog*

*(Good)*

```
...
logic [512-1:0] data_d, data_q
logic [512-1:0] pass_data;
...
Write: begin
...
    if (pass_mode) begin
        pass_data = data_d;
        state_d = PassChk;
        pass_mode = 1'b0;
    ...
    end
...





```

## Observed Examples

Reference	Description
<b>CVE-2022-30320</b>	Programmable Logic Controller (PLC) uses a protocol with a cryptographically insecure hashing algorithm for passwords. <a href="https://www.cve.org/CVERecord?id=CVE-2022-30320">https://www.cve.org/CVERecord?id=CVE-2022-30320</a>
<b>CVE-2005-4900</b>	SHA-1 algorithm is not collision-resistant. <a href="https://www.cve.org/CVERecord?id=CVE-2005-4900">https://www.cve.org/CVERecord?id=CVE-2005-4900</a>
<b>CVE-2020-25685</b>	DNS product uses a weak hash (CRC32 or SHA-1) of the query name, allowing attacker to forge responses by computing domain names with the same hash. <a href="https://www.cve.org/CVERecord?id=CVE-2020-25685">https://www.cve.org/CVERecord?id=CVE-2020-25685</a>
<b>CVE-2012-6707</b>	blogging product uses MD5-based algorithm for passwords. <a href="https://www.cve.org/CVERecord?id=CVE-2012-6707">https://www.cve.org/CVERecord?id=CVE-2012-6707</a>
<b>CVE-2019-14855</b>	forging of certificate signatures using SHA-1 collisions. <a href="https://www.cve.org/CVERecord?id=CVE-2019-14855">https://www.cve.org/CVERecord?id=CVE-2019-14855</a>
<b>CVE-2017-15999</b>	mobile app for backup sends SHA-1 hash of password in cleartext. <a href="https://www.cve.org/CVERecord?id=CVE-2017-15999">https://www.cve.org/CVERecord?id=CVE-2017-15999</a>
<b>CVE-2006-4068</b>	Hard-coded hashed values for username and password contained in client-side script, allowing brute-force offline attacks. <a href="https://www.cve.org/CVERecord?id=CVE-2006-4068">https://www.cve.org/CVERecord?id=CVE-2006-4068</a>

## MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	2391
MemberOf		958	SFP Secondary Cluster: Broken Cryptography	888	2398
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	2436
MemberOf		1346	OWASP Top Ten 2021 Category A02:2021 - Cryptographic Failures	1344	2488
MemberOf		1402	Comprehensive Categorization: Encryption	1400	2527

## Notes

### Maintenance

Since CWE 4.4, various cryptography-related entries including CWE-328 have been slated for extensive research, analysis, and community consultation to define consistent terminology, improve relationships, and reduce overlap or duplication. As of CWE 4.6, this work is still ongoing.

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Reversible One-Way Hash

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name
68	Subvert Code-signing Facilities
461	Web Services API Signature Forgery Leveraging Hash Function Extension Weakness

## References

- [REF-289]Alexander Sotirov et al.. "MD5 considered harmful today". < <http://www.phreedom.org/research/rogue-ca/> >.2023-04-07.
- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.
- [REF-291]Johnny Shelley. "bcrypt". < <http://bcrypt.sourceforge.net/> >.
- [REF-292]Colin Percival. "Tarsnap - The script key derivation function and encryption utility". < <http://www.tarsnap.com/scrypt.html> >.
- [REF-293]B. Kaliski. "RFC2898 - PKCS #5: Password-Based Cryptography Specification Version 2.0". 2000. < <https://www.rfc-editor.org/rfc/rfc2898> >.2023-04-07.
- [REF-294]Coda Hale. "How To Safely Store A Password". 2010 January 1. < <https://codahale.com/how-to-safely-store-a-password/> >.2023-04-07.
- [REF-295]Brian Krebs. "How Companies Can Beef Up Password Security (interview with Thomas H. Ptacek)". 2012 June 1. < <https://krebsonsecurity.com/2012/06/how-companies-can-beef-up-password-security/> >.2023-04-07.
- [REF-296]Solar Designer. "Password security: past, present, future". 2012. < <https://www.openwall.com/presentations/PHDays2012-Password-Security/> >.2023-04-07.
- [REF-297]Troy Hunt. "Our password hashing has no clothes". 2012 June 6. < <https://www.troyhunt.com/our-password-hashing-has-no-clothes/> >.2023-04-07.

[REF-298]Joshbw. "Should we really use bcrypt/scrypt?". 2012 June 8. < <https://web.archive.org/web/20120629144851/http://www.analyticalengine.net/2012/06/should-we-really-use-bcryptscrypt/> >.2023-04-07.

[REF-637]"Rainbow table". 2009 March 3. Wikipedia. < [https://en.wikipedia.org/wiki/Rainbow\\_table](https://en.wikipedia.org/wiki/Rainbow_table) >.2023-04-07.

[REF-1243]Bruce Schneier. "Cryptanalysis of SHA-1". 2005 February 8. < [https://www.schneier.com/blog/archives/2005/02/cryptanalysis\\_o.html](https://www.schneier.com/blog/archives/2005/02/cryptanalysis_o.html) >.2021-10-25.

[REF-1244]Dan Goodin. "At death's door for years, widely used SHA1 function is now dead". 2017 February 3. Ars Technica. < <https://arstechnica.com/information-technology/2017/02/at-deaths-door-for-years-widely-used-sha1-function-is-now-dead/> >.2021-10-25.

[REF-1283]Forescout Vedere Labs. "OT:ICEFALL: The legacy of "insecure by design" and its implications for certifications and risk management". 2022 June 0. < <https://www.forescout.com/resources/ot-icefall-report/> >.

[REF-1360]"dmi\_jtag.sv". 2021. < [https://github.com/HACK-EVENT/hackatdac21/blob/71103971e8204de6a61afc17d3653292517d32bf/piton/design/chip/tile/ariane/src/riscv-dbg/src/dmi\\_jtag.sv#L82](https://github.com/HACK-EVENT/hackatdac21/blob/71103971e8204de6a61afc17d3653292517d32bf/piton/design/chip/tile/ariane/src/riscv-dbg/src/dmi_jtag.sv#L82) >.2023-07-15.

[REF-1361]"fix cwe\_1205 in dmi\_jtag.sv". 2021. < [https://github.com/HACK-EVENT/hackatdac21/blob/c4f4b832218b50c406dbf9f425d3b654117c1355/piton/design/chip/tile/ariane/src/riscv-dbg/src/dmi\\_jtag.sv#L82](https://github.com/HACK-EVENT/hackatdac21/blob/c4f4b832218b50c406dbf9f425d3b654117c1355/piton/design/chip/tile/ariane/src/riscv-dbg/src/dmi_jtag.sv#L82) >.2023-07-22.

## CWE-329: Generation of Predictable IV with CBC Mode

**Weakness ID** : 329

**Structure** : Simple

**Abstraction** : Variant

### Description

The product generates and uses a predictable initialization Vector (IV) with Cipher Block Chaining (CBC) Mode, which causes algorithms to be susceptible to dictionary attacks when they are encrypted under the same key.



### Extended Description

CBC mode eliminates a weakness of Electronic Code Book (ECB) mode by allowing identical plaintext blocks to be encrypted to different ciphertext blocks. This is possible by the XOR-ing of an IV with the initial plaintext block so that every plaintext block in the chain is XOR'd with a different value before encryption. If IVs are reused, then identical plaintexts would be encrypted to identical ciphertexts. However, even if IVs are not identical but are predictable, then they still break the security of CBC mode against Chosen Plaintext Attacks (CPA).

### Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

*Relevant to the view "Research Concepts" (CWE-1000)*

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1298
ChildOf		1204	Generation of Weak Initialization Vector (IV)	1987

### Applicable Platforms

**Language** : Not Language-Specific (*Prevalence = Undetermined*)  
**Technology** : ICS/OT (*Prevalence = Undetermined*)

Background Details

CBC mode is a commonly used mode of operation for a block cipher. It works by XOR-ing an IV with the initial block of a plaintext prior to encryption and then XOR-ing each successive block of plaintext with the previous block of ciphertext before encryption.

$$C_0 = IV$$

$$C_i = E_k\{M_i \text{ XOR } C_{i-1}\}$$

When used properly, CBC mode provides security against chosen plaintext attacks. Having an unpredictable IV is a crucial underpinning of this. See [REF-1171].

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
	<i>If the IV is not properly initialized, data that is encrypted can be compromised and leak information.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis, commonly referred to as Static Application Security Testing (SAST), can find some instances of this weakness by analyzing source code (or binary/compiled code) without having to execute it. Typically, this is done by building a model of data flow and control flow, then searching for potentially-vulnerable patterns that connect "sources" (origins of input) with "sinks" (destinations where the data interacts with external components, a lower layer such as the OS, etc.)

*Effectiveness = High*

Potential Mitigations

Phase: Implementation

NIST recommends two methods of generating unpredictable IVs for CBC mode [REF-1172]. The first is to generate the IV randomly. The second method is to encrypt a nonce with the same key and cipher to be used to encrypt the plaintext. In this case the nonce must be unique but can be predictable, since the block cipher will act as a pseudo random permutation.

Demonstrative Examples

Example 1:

In the following examples, CBC mode is used when encrypting data:

*Example Language: C* *(Bad)*

```
EVP_CIPHER_CTX ctx;
char key[EVP_MAX_KEY_LENGTH];
char iv[EVP_MAX_IV_LENGTH];
RAND_bytes(key, b);
memset(iv,0,EVP_MAX_IV_LENGTH);
EVP_EncryptInit(&ctx,EVP_bf_cbc(), key,iv);
```