


Cybersource®



ISV - Oracle Commerce Cloud Gateway User Installation Guide

December 2023



Contents

1.	Introduction.....	4
1.1.	Cybersource Configuration	5
1.2.	Generating API Keys in Business Center	5
1.3.	Oracle Commerce Cloud Configuration	6
1.3.1.	Payment Gateway Installation Details.....	6
1.3.2.	SSE (server-extension) installation details.....	8
1.3.3.	Plugin installation details	9
2.	Version History.....	10
3.	Configuration Details.....	12
3.1.	General Settings.....	12
3.2.	Fraud Management Settings.....	14
3.2.1.	Enabling Payer Authentication	14
3.2.2.	Enabling Strong Customer Authentication	16
3.2.3.	Enabling Device fingerprint.....	17
3.2.4.	Advanced Fraud Screening with Decision Manager	18
4.	Reporting.....	18
4.1.	Reporting configuration	18
5.	Shipping Region.....	19
6.	Placing order from Storefront.....	20
6.1.	Placing an order from storefront using Credit Card	20
7.	Oracle Commerce Cloud Storefront Cancel an order	25
8.	Apple Pay Configuration.....	29
8.1.	Create a Merchant ID.....	29
8.2.	Create Payment Processing Certificate.....	31
8.3.	Domain Validation.....	32
8.4.	Create Merchant Identity Certificate.....	34
9.	Network Tokenization	37
10.	Support.....	38
11.	Abbreviations	39

Copyright:

© 2023 Cybersource Corporation. All rights reserved. Cybersource Corporation (including its subsidiaries, "Cybersource") furnishes this document and the software and/or code described in this document under the applicable agreement between the reader of this document ("You") and Cybersource ("Agreement"). You may use this document and/or software and/or code only in accordance with the terms of the Agreement, except as expressly set forth in the Agreement, the information contained in this document is subject to change without notice and therefore should not be interpreted in any way as a guarantee or warranty by Cybersource. Cybersource assumes no responsibility or liability for any errors that may appear in this document. The copyrighted software and/or code that accompanies this document is licensed to you for use only in strict accordance with the Agreement. You should read the Agreement carefully before using the software and/or code. Except as permitted by the Agreement, you may not reproduce any part of this document, store this document in a retrieval system or transmit this document in any form or by any means, electronic, mechanical, recording or otherwise without the prior written consent of Cybersource.

Network Capability: By accepting this document, you acknowledge and accept that you are responsible for and assume liability for the functionality, maintenance and availability of your software and network. At all times, it is your responsibility to ensure the accuracy, technical sufficiency and functionality of your software, network, plug-ins, configurations, applications, code, application program interfaces (APIs), software development kits and all other technology ("Your Network"). You are responsible for Your Network's ability to use and/or access the Cybersource network, any Cybersource API and receive the benefit of Cybersource's services. You are responsible for all costs, fees, expenses and liabilities associated with Your Network's ability to access and interface with the Cybersource network and receive the benefit of Cybersource's services. Cybersource will not be responsible or liable for loss or costs associated with or that results from Your Network's inability to connect to or process transactions on the Cybersource network.

Release: December 2023

Version: 23.3.0

1. Introduction

This document contains the details of configuring the ISV OCC payment plugin in Oracle Commerce Cloud. The configuration steps are related to Payment Acceptance, Payment Security, Fraud Management, Order Management and Commerce services for Credit Card, Google Pay and Apple Pay Payment Methods.

The purpose of this manual is to guide a user to configure and to use the ISV OCC payment plugin for the Oracle Commerce Cloud platform. The Oracle Commerce Cloud platform includes the following Cybersource payment management capabilities.

Credit Cards (Flex Microform)

- a) Payment Acceptance
 - Authorization
 - Sale (Authorization & Settlement)
- b) Payment Security
 - Tokenization -Create Payment Token for New Payment Methods
 - Tokenization - Make a Payment Using a Stored Token
 - Network Token Updates
- c) Fraud Management
 - Payer Authentication
 - Strong Customer Authentication
 - Decision Manager with Device Fingerprint
 - Advanced Fraud Screening with Decision Manager
- d) Order Management
 - Capture
 - Refund
 - Void (Authorization Reversal)
- e) Commerce service
 - On-demand conversion
 - Daily conversion

Google Pay

- a) Payment Acceptance
 - Authorization
- b) Fraud Management
 - Decision Manager with Device Fingerprint
 - Advanced Fraud Screening with Decision Manager
- c) Order Management
 - Capture
 - Refund
 - Void (Authorization Reversal)
- d) Commerce service
 - On-demand conversion

- Daily conversion

Apple Pay

- a) Payment Acceptance
 - Authorization
- b) Fraud Management
 - Decision Manager with Device Fingerprint
 - Advanced Fraud Screening with Decision Manager
- c) Order Management
 - Capture
 - Refund
 - Void (Authorization Reversal)
- d) Commerce service
 - On-demand conversion
 - Daily conversion

Note:

- Saved Card feature is supported only during checkout
- Services triggered using OMS will not be updated in OCC

1.1. Cybersource Configuration

To use the Cybersource services, the Merchant needs to procure an account from Cybersource. The Merchant will be provided with the Merchant key ID and Shared secret key. This Merchant key ID and Shared secret key should be configured in Oracle Commerce Cloud to enable the integration between Cybersource and Oracle Commerce Cloud.

A Cybersource account can be created from [Cybersource.com](#). For more information on creating an account, Merchant can contact the Cybersource Customer support.

Key features of the Oracle Commerce Cloud and Cybersource Official Payment Add-on Integration:

- Enable the users to accept and manage payments in Oracle Commerce Cloud.
- Enable hassle-free, completely secure, PCI Compliant, Fraud management enabled - end to end payment transaction for Credit Card, Google Pay and Apple Pay Payment Methods.
- Supports Tokenization which eliminates electronic CHD from being stored in the Merchant environment thereby reduces the scope of Payment Card Industry (PCI) compliance considerations.

1.2. Generating API Keys in Business Center

This section provides the detailed steps to generate API Keys (Merchant key ID and Shared secret key) required to configure in the Oracle Commerce Cloud Back Office.

Oracle Commerce Cloud – ISV Gateway User Installation Guide

Step 1: Go to [Cybersource.com](#) and then login to business center. Click on “Key Management” in “Payment Configuration” Tab.

Step 2: Click on “Generate Key” button.

Step 3: Select “REST - Shared Secret” and click on “Generate Key”.

Step 4: A Shared secret key will be generated.

Step 5: Go to “Key Management”, note the Key ID displayed. These keys can be used in Oracle Commerce Cloud Back Office Payment Settings for the MID in which these keys are generated.

1.3. Oracle Commerce Cloud Configuration

This section provides the plugin installation steps to enable integration between Oracle Commerce Cloud and Cybersource.

1.3.1. Payment Gateway Installation Details

The steps to install the plugin from Oracle Commerce Cloud Admin are:

1.3.1.1. Create an extension ID

To upload an extension into Commerce Cloud, you must generate an ID for the extension and update the same in packages/payment-gateway/ext.json file

To create an extension ID:

- Log into Commerce Cloud.
- Navigate to Settings -> Extensions -> Developer tab.
- Click on Generate ID button.
- Enter a name for the extension and click Save.
- Copy and update the generated extension ID

1.3.1.2. Upload Extension

Before uploading the extension, zip up all the files within your packages/payment-gateway directory excluding settings.json. This is the file you upload to Commerce Cloud to make the extension available for use.

Step 1: In the “Settings” tab on the left panel.

Oracle Commerce Cloud – ISV Gateway User Installation Guide

The screenshot shows the Oracle Commerce Cloud Back Office Dashboard. On the left is a dark sidebar with various icons. The main area has a header 'Commerce' and a sub-header 'Dashboard'. It displays 'Totals for yesterday' with 8 Orders, \$830.00 (USD) Gross Revenue, and 16 Visits. Below this is a 'Trend over last 7 days' chart showing a slight upward trend from 8 to 9. To the right is a 'Resources' sidebar with links to 'How Do I?', 'Videos and Tutorials', and 'Version 22.3.1'.

Figure 1: Oracle Commerce Cloud Back Office Dashboard

Step 2: In settings, click on “Extension” button.

The screenshot shows the Oracle Commerce Cloud Settings page. The left sidebar lists various settings categories. The 'Extensions' button at the bottom of the sidebar is highlighted with a red box. The main content area shows sections for 'Payment Types' (with logos for VISA, MasterCard, American Express, Discover, Diners Club, Elo, and CartaSi) and 'Billing Countries' (with a dropdown for 'Default Billing Country' set to 'No Selection'). A note states: 'The storefront will only accept payments from these countries. If none selected, you cannot accept payments.' Another note states: 'Preselected in the billing address form during checkout, though shoppers can change it. The country must be a selected billing country. Otherwise, no country is preselected at checkout.' At the bottom right are 'Cancel' and 'Save' buttons.

Figure 2: Extension button

Step 3: Click the Upload Extension button and select the extension zip file from your local file system.




Figure 3: Upload Extension

Once the module is installed, head back to the Oracle Commerce Cloud Admin settings to configure it.

1.3.2. SSE (server-extension) installation details

Configure production settings in the following file packages/server-extension/config/app.prod.json:

- cache.service.ttl.secs - Default caching TTL, can be zero value
- cache.gatewaysettings.ttl.secs - Caching TTL for gateway settings call (see packages/serverextension/src/middlewares/gatewaySettings.ts). You might want to use TTL value '1' while testing SSE so that changes in gateway settings performed in OCC Admin become immediately available to SSE and Payment Widget respectively
- crypto.service.key - Random key which is used to encrypt data so that it is not tampered in UI
- partner.developerId - Leave the value as is
- partner.solutionId - Leave the value as is
- logging.webhook.http - Enable webhook request/response logging
- logging.api.error - Enable logging for errors
- logging.api.access - Enable logging for incoming requests
- payments.secret.key - Webhook secret key (SHA512)

1.3.3. Plugin installation details

- Copy the contents from `cybersource-plugins-oraclecxcommerce/plugins` into the `plugins` directory of your storefront (OSF workspace) code.

Copy plugins/actions into your storefront code and export the actions in the index and meta files: `plugins/actions/index.js`

```
export * from '@oracle-cx-commerce/actions';

export const flexMicroformAction = () => import('./flex-microform-action');
export const applePayValidationAction = () => import('./apple-pay-validation-action');
export const getPayerAuthSetupAction = () => import('./get-payer-auth-setup-action');
```

`plugins/actions/meta.js`

```
export * from '@oracle-cx-commerce/actions/meta';
|
export {flexMicroformAction} from './flex-microform-action/meta';
export {applePayValidationAction} from './apple-pay-validation-action/meta';
export {getPayerAuthSetupAction} from './get-payer-auth-setup-action/meta';
```

Copy plugins/components into your storefront code and export the components in the index and meta files: `plugins/components/index.js`

```
export * from '@oracle-cx-commerce/react-widgets';
export const IsvPaymentMethod = () => import('./isv-payment-method/index');
export const IsvCheckoutContinueToReviewOrderButton = () => import('./isv-checkout-continue-to-review-order-button');
export const IsvCheckoutPlaceOrderButton = () => import('./isv-checkout-place-order-button');
```

`plugins/components/meta.js`

```
export * from '@oracle-cx-commerce/react-widgets/meta';
export {default as IsvPaymentMethod} from './isv-payment-method/meta';
export {default as IsvCheckoutContinueToReviewOrderButton} from './isv-checkout-continue-to-review-order-button/meta';
export {default as IsvCheckoutPlaceOrderButton} from './isv-checkout-place-order-button/meta';
```

Copy plugins/endpoints into your storefront code and export the endpoints in the index and meta files: `plugins/endpoints/index.js`

```
export * from '@oracle-cx-commerce/endpoints';
export * from '@oracle-cx-commerce/oce-endpoints';
export const flexMicroformEndpoint = () => import('./flex-microform-endpoint');
export const paymentMethodConfigEndpoint = () => import('./payment-method-config-endpoint');
export const applePayValidationEndpoint = () => import('./apple-pay-validation-endpoint');
export const payerAuthSetupEndpoint = () => import('./payer-auth-setup-endpoint');
```

`plugins/endpoints/meta.js`

```
export * from '@oracle-cx-commerce/endpoints/meta';
export * from '@oracle-cx-commerce/oce-endpoints';
export {default as flexMicroformEndpoint} from './flex-microform-endpoint/meta';
export {default as paymentMethodConfigEndpoint} from './payment-method-config-endpoint/meta';
export {default as applePayValidationEndpoint} from './apple-pay-validation-endpoint/meta';
export {default as payerAuthSetupEndpoint} from './payer-auth-setup-endpoint/meta';
```

Copy plugins/selectors into your storefront code and export the selector in the index file: `plugins/selectors/index.js`

```
export * from './flex-microform-selector';
export * from './payment-method-config-selector';

```

Copy plugins/fetchers into your storefront code and export the fetchers in the hook, index and meta files:
plugins/fetchers/hooks.js

```
export {default as useFlexMicroformFetcher} from './flex-microform-fetcher/hook';
export {default as usePaymentMethodConfigFetcher} from './payment-method-config-fetcher';
```

plugins/fetchers/index.js

```
export {default as flexMicroformFetcher} from './flex-microform-fetcher';
export {default as paymentMethodConfigFetcher} from './payment-method-config-fetcher';
```

plugins/fetchers/meta.js

```
export {default as flexMicroformFetcher} from './flex-microform-fetcher/meta';
export {default as paymentMethodConfigFetcher} from './payment-method-config-fetcher/meta';
```

Note: Install jwt-decode package by running '**yarn add jwt-decode -W**'

- Deploy with the following command:

```
yarn occ deploy
```

2. Version History

This section gives details on the release notes of the ISV OCC Gateway.

Version 23.3.0

1. Network Tokenization
2. Flex Microform upgrade
3. Cybersource rest client and other dependencies upgrade
4. Updated the user guide
5. Addressed Checkmark issues

Compatible with latest OSF: v5.0.0

OCC Version: v23.08.01

Version 23.2.0

1. Allow merchants to configure when to enforce Strong Consumer Authentication.
2. Module compatible with latest Oracle 23C upgrade.

Compatible with OSF: v5.0.0

OCC Version: v23.08.01

Version 23.1.0

1. Payer Authentication from Hybrid model to direct connection API
2. Included custom properties in the request
3. Addressed Checkmarx issues
4. Updated the user guide with support items

Note: Local instance doesn't support Payer Authentication with saved card due to product limitation.

Compatible with OSF: v4.4.0

OCC Version: v23.1.1.1

Version 22.1.0

1. Implemented Payment Acceptance, Fraud Management and Payment Security Services for Credit Card, Google Pay and Apple Pay for OSF framework.
2. Security and vulnerability issues, Checkmarx issue and
3. Handled promise rejection with error logs
4. Request - response logs for webhook and API calls

Compatible with OSF: 3.7

3. Configuration Details

This section provides the details about the steps for configuring the extension with Merchant Details, Payment Method enabling for Credit Card, Google Pay and Apple Pay

3.1. General Settings

Step 1: Go to OCC Admin -> Settings ->Payment Processing and then click on “Payment Gateways”.

The screenshot shows the Oracle Commerce Cloud Admin interface. On the left, there is a dark sidebar with various navigation options like Dashboard, Catalog, Marketing, Design, Media, Search, Accounts, Settings (which is currently selected), User Management, Reports, Service Operations, and Changes. Below the sidebar, there are buttons for 'Save to workset #default' and 'NV'. The main content area has a header 'Commerce' and a dropdown 'Commerce Cloud Site'. Below the header, there are tabs for 'Setup', 'Payment Types', and 'Payment Gateways' (which is highlighted with a red border). The 'Payment Gateways' tab leads to a sub-page with a 'Service Type' dropdown set to 'No Selection'. At the bottom right of the main content area are 'Cancel' and 'Save' buttons.

Figure 4: Payment Gateways

Step 2: Under Payment Gateways, select the Service Type “ISV OCC Gateway” and enable the Payment Gateway

The screenshot shows the same Oracle Commerce Cloud Admin interface as Figure 4, but with the 'Service Type' dropdown expanded. The dropdown menu lists several options: 'No Selection', 'CyberSource', 'In Store Payment', 'PayPal', and 'ISV OCC Gateway'. The 'ISV OCC Gateway' option is highlighted with a red box. The rest of the interface is identical to Figure 4, including the sidebar, header, and bottom buttons.

Figure 5: ISV OCC Gateways

Step 3: Under ISV OCC Gateway, enter the details for Preview, StoreFront and Agent Configurations

Figure 6: Preview Configuration

Section	Description
Merchant ID	Enter the Merchant ID details
Key id	Enter the Merchant Key ID
Secret key	Enter the Merchant Secret Key
Key alias	Key Alias (in case authentication type = jwt)
Key pass	Key Pass (in case authentication type = jwt)
Key file name	Key File Name (in case authentication type = jwt)
Authentication type	Choose the authentication type from the drop down
Environment	PSP REST API environment to send requests to
Google Pay Gateway	To retrieve payment and customer information from a payment gateway that's supported by the Google Pay API. Gateway's identifier, which is issued by Google
Google Pay Gateway merchant ID	To retrieve payment and customer information from a payment gateway that's supported by the Google Pay API. Your gateway account ID, which is provided by the gateway

Google Pay Merchant ID	A Google merchant identifier issued after registration with the Google Pay Business Console. Required when Payments Client is initialized with an environment property of PRODUCTION. See Request production access for more information about the approval process and how to obtain a Google merchant identifier
Google Pay Merchant Name	Merchant name encoded as UTF-8. Merchant name is rendered in the payment sheet. In TEST environment, or if a merchant isn't recognized, a "Pay Unverified Merchant" message is displayed in the payment sheet
Google Pay Supported Networks	Google Pay Supported networks
Apple Pay Merchant ID	Apple Pay Merchant ID
Apple Pay initiative context	Fully qualified domain name associated with your Apple Pay Merchant Identity Certificate
Apple Pay supported network	Apple Pay Supported Networks
Apple Pay display name	Apple Pay Display Name

Table 1: Configuration Fields

Step 4: Save changes

Step 5: Go back to the 'Payment Types' type

Step 6: Select supported credit card types from the list [Possible card types: VISA, MASTERCARD, AMEX, DISCOVER, DINERSCLUB, JCB, CARTESBANCAIRES, MAESTRO, CARNET, CUP]

Step 7: Save and publish the changes

3.2. Fraud Management Settings

3.2.1. Enabling Payer Authentication

Step 1: Login to OCC Admin dashboard and click on Settings.

Oracle Commerce Cloud – ISV Gateway User Installation Guide




Figure 7: Enabling Payer Authentication

Step 2: Go to Settings -> Payment Processing and then click on “Payment Gateways”.




Figure 8: Payment Gateways

Step 3: Under Payment Gateways, select the Service Type “ISV OCC Gateway”. Select the Credit Card Payer Authentication Enabled checkbox. Save the changes.




Figure 9: Enabling Payer Authentication

Note: Local Instance doesn't support Payer Authentication with saved cards

3.2.2. Enabling Strong Customer Authentication

When payer authentication is enabled, if a transaction gets declined with the reason as Strong Customer Authentication required, then another request will be sent from Oracle Commerce Cloud automatically for the same order and the customer will be 3DS challenged

This section covers information on how to enable a Strong Customer Authentication Service. Under Payment Gateways -> “ISV OCC Gateway”, select the Enforce Strong Customer Authentication checkbox to enable the Strong Customer Authentication. Save the changes.

The screenshot shows a configuration page for an ISV Gateway. On the left is a vertical toolbar with icons for Home, Commerce, Reports, Data, Analytics, and Help. The main panel has a title 'Commerce' and contains several configuration fields:

- Key File Name (in case authentication type = jwt) (required)**: A text input field containing 'keyFileName'.
- Authentication Type (required)**: A dropdown menu set to 'http_signature'.
- Environment (required)**: A text input field containing 'environment'.
- Credit Card Payer Authentication Enabled**: A checked checkbox with a tooltip indicating it enables Payer Authentication (3D Secure).
- Enforce SCA for Saving Card**: A checked checkbox with a tooltip indicating it enforces Strong Customer Authentication when saving a card.
- Network Token Updates**: An unchecked checkbox with a tooltip indicating it subscribes to Network Token life cycle updates.
- Sale Enabled**: An unchecked checkbox with a tooltip indicating it authorizes and takes payment at the same time for a particular payment mode.
- Card**: An unchecked checkbox.

Figure 10: Enabling Strong Customer Authentication

Note: The “Enforce SCA for Saving Card” setting will be only available if “Payer Authentication” is enabled

3.2.3. Enabling Device fingerprint

This section covers information on how to enable Device Fingerprint Service.

Under Payment Gateways -> “ISV OCC Gateway”, select the Device Fingerprint Enabled checkbox to enable the Device Fingerprint and enter the details for Device Fingerprint URL & Device Fingerprint Organization Id. Save the changes.

The screenshot shows a configuration page for the Device Fingerprint service. On the left is a vertical toolbar with icons for Home, Commerce, Reports, Data, Analytics, and Help. The main panel has a title 'Commerce' and contains several configuration fields:

- DM Decision Skip**: A group of checkboxes for 'Card', 'Apple Pay', and 'Google Pay' with a tooltip indicating they skip the decision manager step.
- Daily Report Name (required)**: A text input field containing 'dailyReportName'.
- Device Fingerprint URL (required)**: A text input field containing 'https://h.online-metrix.net/fp/tags'.
- Device Fingerprint Organization Id (required)**: A text input field containing 'deviceFingerprintOrgId'.
- Device Fingerprint Enabled**: A checked checkbox.

At the bottom right are 'Cancel' and 'Save' buttons.

Figure 11: Enabling Device fingerprint

3.2.4. Advanced Fraud Screening with Decision Manager

This section provides information on Configuring Decision Manager Services in OCC.

Under Payment Gateways -> “ISV OCC Gateway”, uncheck the DM Decision Skip to enable Decision Manager for the desired Payment Service.




Figure 12: DM Decision Skip

4. Reporting

This section covers the details of the Reports imported from Cybersource to Oracle Commerce Cloud. Following Reports are generated in Cybersource and are imported in Oracle Commerce Cloud:

1. On-demand conversion
2. Daily conversion

4.1. Reporting configuration

This section covers the configuration to be made for Reporting:

The types of Reports supported are:

1. **On-demand conversion:** Daily transaction level report that provides details related to each individual transaction.
2. **Daily conversion:** Report that can be scheduled for daily execution which returns conversion report for a given date.

In settings, give the daily report name as **ConversionDetailReport_Daily_Classic**

Oracle Commerce Cloud – ISV Gateway User Installation Guide




Figure 13: Enter the Daily Report Name

5. Shipping Region

This section covers the details about changing the Shipping Region in OCC Admin

Step 1: Under Settings -> Shipping Methods, click on New Shipping Region




Figure 14: Shipping methods

Step 2: Enter the display name as per your preference and select the shipping country and save




Figure 15: New Shipping Region

6. Placing order from Storefront

6.1. Placing an order from storefront using Credit Card

Step 1: Open the Oracle Commerce Cloud Storefront

The screenshot shows the Oracle Commerce Cloud StoreFront interface. At the top, there is a search bar with placeholder text 'I'm searching for...' and a magnifying glass icon. To the right of the search bar are links for 'Commerce Cloud Site' and a user profile icon. Below the search bar, there is a category 'Clothing' and a note 'Viewing 1-2 of 2'. On the left, there are filters for 'Category' (set to 'Clothing (2)') and 'Price Range' (\$50.00 - \$60.00 and \$80.00 - \$90.00). The main content area displays two products: 't-shirt' and 'sweat shirt'. Each product has a blue square thumbnail, a price of '\$50.00' or '\$80.00', and a red crossed-out price of '\$100.00'. There is also a note 'Now: \$80.00' for the sweat shirt. A dropdown menu 'Best Match' is visible on the right.

Figure 16: Oracle Commerce Cloud StoreFront

Step 2: Add an item in to cart

Oracle Commerce Cloud – ISV Gateway User Installation Guide




Figure 17: Oracle Commerce Cloud Add to Cart

Step 3: After adding an item to cart, click on “Checkout” option.




Figure 18: Oracle Commerce Cloud Checkout

Step 4: Click on “Checkout as Guest”

Oracle Commerce Cloud – ISV Gateway User Installation Guide




Figure 19: Oracle Commerce Cloud Checkout as Guest

Step 5: Fill in the Shipping details.

A screenshot of the Shipping address input form. The page title is 'Checkout'. It shows three steps: 1 SHIPPING, 2 PAYMENT, and 3 REVIEW. The 'SHIPPING' step is active. It has fields for First Name, Last Name, Country (United States), ZIP Code, State (Alabama), Street Address, Town/City, and Phone Number (optional). To the right, there's an 'Order Summary' table:

Subtotal	\$100.00	
Shipping	Free	\$0.00
Tax		
Total	\$100.00	

At the bottom, there's a 'Continue' button and a footer with links for Help, Customer Services, Contact Us, Shipping Information, Returns & Refunds, and social media icons.

Figure 20: Shipping address

Step 6: Select the desired shipping option & click “Continue to Payment”

Oracle Commerce Cloud – ISV Gateway User Installation Guide

The screenshot shows the 'Checkout' process at step 1: SHIPPING. On the left, there's a section for 'Home Delivery' with an item detail for a 't-shirt' priced at \$50.00, quantity 2, and total \$100.00. It includes a 'Remove Item' link. Below this is a 'Ship to' section with an address for 'Ann Babu' at '1295 Charleston Road, Mountain View CA 94043 US'. There's an 'Edit Address' link. Under 'Shipping Options', the radio button for 'Shipping Cost: \$6.00' is selected. At the bottom is a blue 'Continue to Payment' button, which is highlighted with a red border.

Figure 21: Continue to Payment

Step 7: Select the required Payment method and enter the necessary details. For Credit Card, click on Continue to Review Order button and respective buttons for Google Pay & Apple Pay.

The screenshot shows the 'PAYMENT' step. It starts with a radio button for 'Credit Card' which is selected. Below it are fields for 'Card Number' (with icons for VISA, Mastercard, and American Express), 'Expiry Date (MM/YY)', and 'CVV Number'. There's also a field for 'Name on Card'. Further down is a 'Billing Address' section with the address '1295 Charleston Road, Mountain View ABE 94043 GB'. An 'Edit Address' link is provided. At the bottom, there are buttons for 'Google Pay' and '+ Apply a Promo Code'. The 'Continue to Review Order' button is highlighted with a blue background and white text. To its right is a 'Back to Previous' button. On the right side, there's an 'Order Summary' table:

Order Summary	
Subtotal	\$100.00
Shipping	\$6.00
Tax	\$0.00
Total	\$106.00

Order Summary

Order Summary	
Subtotal	\$100.00
Shipping	\$6.00
Tax	\$0.00
Total	\$106.00

Figure 22.1: Credit Card Payment Method

Oracle Commerce Cloud – ISV Gateway User Installation Guide




Figure 22.2: Google Pay Payment Method




Figure 22.3: Apple Pay Payment Method

Step 8: Enter the email address, click on “Place Order” button

Oracle Commerce Cloud – ISV Gateway User Installation Guide

The screenshot shows the 'Checkout' process. The 'REVIEW ORDER' section includes 'Contact Information' (Email Address: test@gmail.com) and 'Shipping Details' (Home Delivery, Item: t-shirt, Price: \$50.00, Quantity: 1, Total: \$50.00). The 'Order Summary' table shows Subtotal (\$50.00), Shipping (\$6.00), Tax (\$0.00), and Total (\$56.00). The 'Place Order' button is highlighted with a red box. The 'Payment Details' section shows a VISA card (last four digits: 1111, Expiry Date: 05/2025) and Billing Address (1235 Charleston Road, Mountain View CA 94043 US). The footer includes links for Help, Customer Services, Contact Us, Shipping Information, Returns & Refunds, and social media icons (Facebook, Instagram, Twitter, Pinterest).

Figure 23: Place Order

The screenshot shows the 'Thank you for your order' page. It displays a message: 'Your order has been submitted. A confirmation email with your order details has been sent to your email address.' The Order Number is e60142. Below this, there's a section for creating an account with fields for First Name (Ann), Last Name (Babu), Email Address (test@gmail.com), and a checkbox for 'I want to get email updates.' A 'Create an Account' button is highlighted with a blue bar. Below it is a 'Continue Shopping' button. The footer includes links for Help, Customer Services, Contact Us, Shipping Information, Returns & Refunds, and social media icons.

Figure 24: Order placed

7. Oracle Commerce Cloud Storefront Cancel an order

The Customer can cancel the order from Oracle Commerce Cloud.

Step 1: Click on “Agent Console Settings” and then “Remorse Period”.

Oracle Commerce Cloud – ISV Gateway User Installation Guide

The screenshot shows the Oracle Commerce Cloud interface. On the left, there's a sidebar with various navigation options like Dashboard, Catalog, Marketing, Design, Media, Search, Accounts, Settings, User Management, Reports, and Service Operations. Below these are sections for Changes (with a save button) and Agent Console Settings. The main content area is titled 'Agent Console Settings' and has tabs for Announcements, Quick Links, Price Override, Remorse Period (which is highlighted with a red box), and Extended Remorse Period. Under the Remorse Period tab, there's a section for 'Announcements' which says 'No Announcements have been created.' and 'Click the New Announcement button to start.' A 'New Announcement' button is visible on the right. The rest of the page lists other settings like Shipping Methods, Payment Processing, etc.

Figure 25: Remorse Period

Step 2: Specify the Time for Remorse Period and save.

This screenshot shows the same interface as Figure 25, but with a modal dialog box open over the 'Remorse Period' section. The dialog is titled 'Remorse Period' and contains a checkbox labeled 'Enable Remorse Period'. Below it is a section titled 'Specify Time For Remorse Period:' with two input fields: 'Hours' (set to 0) and 'Minutes' (set to 15). The entire 'Specify Time For Remorse Period:' section is highlighted with a red box. At the bottom right of the dialog are 'Cancel' and 'Save' buttons.

Figure 26: Enable Remorse Period

Step 3: Login into user account and select Order History from the profile

Oracle Commerce Cloud – ISV Gateway User Installation Guide




Figure 27: Order History

Step 4: Click on the order to be cancelled




Figure 28: Orders page

Step 5: Click on “Cancel This Order” button

Oracle Commerce Cloud – ISV Gateway User Installation Guide

LATEST PROMOTIONS AND OFFERS

I'm searching for...

Commerce Cloud Site

Clothing

« Back | Your Account / Order History / Order Details

Order Details

Order Number: 060209
Order Date: 9/26/2022
Creation Date: 9/26/2022
Order Status: Submitted to fulfillment
Number of items: 2
Order Total: \$106.00

Shipping Details

Home Delivery

Item Details	Item Price	Quantity	Total
t-shirt	\$50.00	2	\$100.00

Order Summary

Subtotal	\$100.00
Shipping	\$6.00
Tax	\$0.00
Total	\$106.00

Copy Order

Cancel This Order

Figure 29: Cancel This order

Step 6: Select the reason for the cancellation & click on “Submit Cancellation”

LATEST PROMOTIONS AND OFFERS

I'm searching for...

Commerce Cloud Site

Clothing

Your Account / Order History / Cancel Order

Cancel Order

Item Details Item Price Quantity Total

t-shirt	\$50.00	2	\$100.00
---------	---------	---	----------

No longer needed

Help Customer Services Contact Us Shipping Information Returns & Refunds

Copyright © 2020 Oracle. All rights reserved.

Figure 30: Submit cancellation

Step 7: The Order Cancellation screen.




Figure 31: Order Canceled successfully

8. Apple Pay Configuration

In order to use Apple Pay there are few assumptions and prerequisites one should take into consideration.

- You must have an Apple Developer Account.
- All pages that incorporate Apple Pay must be served over HTTPS.
- Your website must comply with the Apple Pay guidelines. [Click here](#) for more information.
- Your website must have HTTPS mode enabled. [Click here](#) to know more about server requirements

In order to configure Apple Pay added in the ISV OCC Gateway plugin, you need to perform the following actions:

1. Register an Apple Pay Merchant ID
2. Validate your Store domain in Apple Pay.
3. Create a Payment Processing Certificate.
4. Create a Merchant Identity Certificate.

8.1. Create a Merchant ID

[Click here](#) to visit Apple's official article

1. Go to [Certificates, Identifiers & Profiles](#) page.
2. Select Identifiers from the sidebar. Click the "+" button.
3. Find and select the Merchant IDs from the list.

Oracle Commerce Cloud – ISV Gateway User Installation Guide

Apple Developer

Certificates, Identifiers & Profiles

< All Identifiers

Register a new identifier

App IDs
Register an App ID to enable your app, app extensions, or App Clip to access available services and identify your app in a provisioning profile. You can enable app services when you create an App ID or modify these settings later.

Services IDs
For each website that uses Sign in with Apple, register a services identifier (Services ID), configure your domain and return URL, and create an associated private key.

Pass Type IDs
Register a pass type identifier (Pass Type ID) for each kind of pass you create (i.e. gift cards). Registering your Pass Type IDs lets you generate Apple-issued certificates which are used to digitally sign and send updates to your passes, and allow your passes to be recognized by Wallet.

Website Push IDs
Register a Website Push Identifier (Website Push ID). Registering your Website Push IDs lets you generate Apple-issued certificates which are used to digitally sign and send push notifications from your website to macOS.

iCloud Containers
Registering your iCloud Container lets you use the iCloud Storage APIs to enable your apps to store data and documents in iCloud, keeping your apps up to date automatically.

App Groups
Registering your App Group allows access to group containers that are shared among multiple related apps, and allows certain additional interprocess communication between the apps.

Merchant IDs
Register your Merchant Identifiers (Merchant IDs) to enable your apps to process transactions for physical goods and services to be used outside of your apps. Generate a Apple Pay Payment Processing certificate for each registered Merchant ID to validate transactions initiated within your app.

Media IDs
Register a media identifier (Media ID) for each app that uses the Apple Music API or ShazamKit. Then create an associated private key.

Maps IDs
For each website that uses MapKit JS, register a Maps identifier (Maps ID) then create an associated private key.

[Continue](#)

Figure 32: Register a New Identifier Page

4. Fill in the Description and the Identifier field values. Record the value of the Identifier as it is required in the following configuration process. Click the Continue button.

Apple Developer

Certificates, Identifiers & Profiles

< All Identifiers

Register a Merchant ID

Description

You cannot use special characters such as @, &, *, ^, ", ~, -.

Identifier

We recommend using a reverse-domain name style string (i.e., com.domainname.appname).

[Back](#) [Continue](#)

Figure 33: Register a Merchant ID Page

5. Click the Register button to finish the Merchant ID creation process.

Apple Developer

Certificates, Identifiers & Profiles

< All Identifiers

Register a Merchant ID

Description

Identifier

[Back](#) [Register](#)

Figure 34: Finishing a New Merchant ID Registration Page

8.2. Create Payment Processing Certificate

A Payment Processing certificate is used to establish secure communication between Apple Pay and Cybersource.

1. Log in to your Cybersource Enterprise Business Center account.
2. On the left navigation panel go to “Payment Configuration” > “Digital Payment Solutions” .
3. Click “Configure” button near “Apple Pay”.
4. Enter the value of your Apple Pay Merchant ID in the Apple Merchant ID field.

The screenshot shows the 'Apple Pay Registration' page. At the top, there's a header bar with a close button ('X') and a 'Help' link. Below the header, the first step is titled 'Step 1: Generate the Certificate Signing Request'. It contains instructions about what a CSR is and how to use it. A text input field is labeled 'Apple Merchant ID' with a placeholder value. Below the input field is a blue button labeled 'GENERATE NEW CERTIFICATE SIGNING REQUEST'.

Step 2: Submit the CSR to Apple
Submit the CSR to Apple to get the required Apple Pay Certificate. [Learn more about the submission process.](#)

Step 3: Generate Transaction Security Key
Complete this step if you use the SDK. When using the SDK, each transaction request originating from your iOS application must include a unique signature.

At least one CyberSource SOAP Toolkit API transaction security key exists. If you do not want to reuse an existing key, [generate a new transaction security key here.](#)

Important - To use Apple Pay, your processor must support payment network tokenization.

Figure 35: EBC Apple Pay Registration Page

5. Click Generate New Certificate Signing Request button.
6. Save the generated CSR on your disk.
7. Go to [Certificates, Identifiers & Profiles](#) page on your Apple Developer portal.
8. Select Identifiers from the sidebar.
9. Select your Merchant ID from the list.
10. Under Apple Pay Payment Processing Certificate click the Create Certificate button.
11. Select the CSR file you have downloaded from EBC in the previous step.

Oracle Commerce Cloud – ISV Gateway User Installation Guide




Figure 36: Uploading Payment Processing Certificate Request

12. Click Continue button.
13. Click Download button.




Figure 37: Downloading Payment Processing Certificate Request

8.3. Domain Validation

1. Go to [Certificates, Identifiers & Profiles](#) page on your Apple Developer portal.
2. Select your Merchant ID from the list.
3. Click Add Domain button under Merchant Domains.

Oracle Commerce Cloud – ISV Gateway User Installation Guide

The screenshot shows the 'Edit or Configure Merchant ID' section of the Apple Developer portal. It includes fields for 'Name' (Cybersource Test Merchant ID) and 'Identifier' (merchant.com.test.cyberosource), with a note about special character restrictions. A 'Save' button is visible. Below this, the 'Apple Pay Payment Processing Certificate' section is shown, featuring a certificate entry for merchant.com.test.cyberosource, type Apple Pay Payment Processing, and expiration on Jul 23, 2023. Buttons for 'Revoke' and 'Download' are present. A link to 'Create an additional certificate' is also provided. The 'Apple Pay Payment Processing on the Web' section follows, with a note about web domain verification and a 'Create Certificate' button. Finally, the 'Merchant Domains' section is shown with a 'Add Domain' button.

Figure 38: Configure Apple Pay Merchant ID Page.

4. Enter your Admin domain name into the field.

The screenshot shows the 'Register' section of the Apple Developer portal. It prompts users to enter their domain name for web-based Apple Pay processing. A text input field contains 'https://[REDACTED]', and a 'Save' button is located to the right. The top navigation bar shows the user's name (Krishna Salem) and ID (94C658DZ5A).

Figure 39: Domain Registration Page.

5. Click Save button.
6. Download the validation file and save on your disk.

The screenshot shows the 'Certificates, Identifiers & Profiles' section of the Apple Developer portal. Under the 'Verify' tab, it displays instructions for domain verification. It includes a download link for a domain association file and an 'Ok' button to finish the process.

Figure 40: Domain Verification Page

7. The [Upload an Apple Pay merchant identity certificate](#) guide can be used in order to setup Apple Pay for testing in the sandbox environment. `yarn occ` CLI tool has a command for your convenience which can upload domain association file for you:

```
yarn occ upload-apple-domain-association -u ${OCC_ADMIN_HOST} -k  
${APPLICATION_KEY} <appledeveloper-merchantid-domain-association>
```

Where

- `APPLICATION_KEY` - Application Key created in Settings -> Web APIs -> Registered Applications
 - `OCC_ADMIN_HOST` - your OCC specific environment, e.g. `asbx80c1dev-admin-{env}.oraclecloud.com`
 - `apple-developer-merchantid-domain-association` - domain association file downloaded from ApplePay dev account
8. When you verify domain make sure it is accessible from ApplePay network. OCC Admin (e.g. `https://asbx80c1dev-admin-{env}.oraclecloud.com/thirdparty/.well-known/apple-developer-merchantiddomain-association`) is often protected by basic authentication which might fail the domain verification process. You can use [updateBasicAuthConfiguration](#) to update your storefront access control settings by removing basic authentication or whitelisting [Apple Pay IP Range](#).
 9. Click the Ok button to finish the Domain Validation process.

8.4. Create Merchant Identity Certificate

Merchant Identity certificate is used to authenticate your sessions on Apple Pay servers. The certificate and its private key files must be uploaded to your server and full paths to these files must be entered in Cybersource Official add-on settings.

1. Go to [Certificates, Identifiers & Profiles](#) page on your Apple Developer portal.
2. Select your Merchant ID from the list.

Oracle Commerce Cloud – ISV Gateway User Installation Guide

3. Generate your CSR following [Apple Developer Help article](#).
4. Click Create Certificate under Apple Pay Merchant Identity Certificate.

Apple Pay Payment Processing on the Web

To configure Apple Pay Payment Processing on the web for this merchant ID, you must register and verify the domains that will process transactions. You must also create a Apple Pay Merchant Identity, which authenticates your web sessions with the Apple Pay Payment Processing servers.

Incorporation of Apple Pay Payment Processing into your website is subject to these [Apple Pay Payment Processing Web Merchant Terms and Conditions](#) and [Acceptable Use Guidelines](#). Failure to comply with any of these Terms and Conditions or guidelines may result in deactivation of Apple Pay Payment Processing transactions on your website.

Merchant Domains

Domain: www.qa.prestashop.cybsplugin.com

Status: **Verified**

Verification Expires: Aug 3, 2021

[Remove](#)

[Verify](#)

Add a domain for use with this Merchant ID.

[Add Domain](#)

Apple Pay Merchant Identity Certificate

Create an Apple Pay Merchant Identity Certificate for this Merchant ID.

[Create Certificate](#)

Figure 41: Create Merchant Identity Certificate Page.

5. Upload the CSR and click Continue.

apple developer

Certificates, Identifiers & Profiles

[All Certificates](#)

Create a New Certificate

[Back](#)

[Continue](#)

Certificate Type

Apple Pay Merchant Identity Certificate

Upload a Certificate Signing Request

To manually generate a Certificate, you need a Certificate Signing Request (CSR) file from your Mac.
[Learn more >](#)

[Choose File](#)

CertificateSigningRequest.certSigningRequest

Figure 42: Create a New Merchant Identity Certificate Page.

6. Click the Download button and save the Certificate on your disk.

apple developer

Certificates, Identifiers & Profiles

[All Certificates](#)

Download Your Certificate

[Revoke](#)

[Download](#)

Certificate Details

Certificate Name:
merchant.com.test.cyberosource
Expiration Date:
2023/07/23

Certificate Type:
Apple Pay Merchant Identity
Created By

Download your certificate to your Mac, then double click the .cer file to install in Keychain Access. Make sure to save a backup copy of your private and public keys somewhere secure.

Figure 43: Download Merchant Identity Certificate Page.

Oracle Commerce Cloud – ISV Gateway User Installation Guide

7. Convert the Certificate into PEM format.

```
openssl x509 -inform der -in merchant_id.cer -out merchant_id.pem
```

8. Install the certificate by double clicking on it. Certificate will be available under Keychain Access.



Figure 44: Certificates Under Keychain Access.

9. Right click on the private key file and export as merchant_id.p12
10. Convert your private key into KEY format.

```
openssl pkcs12 -in merchant_id.p12 -out merchant_id.key -nodes
```

11. Identity certificate file is located in packages/server-extension/certs/applePayIdentityCert.pem. Private key file is located in packages/server-extension/certs/applePayIdentityKey.key. **Please make sure you update the file with identity certificate downloaded from your Apple dev account.**

The screenshot shows the Oracle Commerce interface for payment processing. The left sidebar has a navigation menu with icons for Home, Commerce, Catalog, Reports, Data, Search, Configuration, and Help. The main content area is titled 'Commerce' and contains several input fields for Apple Pay configuration:

- 'Apple Pay Merchant Id (required)': Input field containing 'applePayMerchantId'.
- 'Apple Pay Initiative (required)': Input field containing 'web'. A tooltip explains: 'A predefined value that identifies the e-commerce application making the request. For Apple Pay on the web use "web"'.
- 'Apple Pay Initiative Context (required)': Input field containing 'applePayInitiativeContextId'. A tooltip explains: 'Fully qualified domain name associated with your Apple Pay Merchant Identity Certificate'.
- 'Apple Pay Display Name (required)': Input field containing 'applePayDisplayName'.
- 'Apple Pay Supported Networks (required)': Input field containing 'visa,masterCard,amex,discover'. A tooltip explains: 'Comma separated list of networks. e.g: "visa,masterCard,amex,discover"'.

Figure 45: ISV OCC Gateway Payment Processing Page.

9. Network Tokenization

A Network Token is a network scheme generated token, that represents customer card information for secure transactions that references a customer's actual PAN.

Before a MID can be enabled for Network Tokenization, it must be provisioned with a Token Requestor ID (TRID) for each card scheme.

Plug-in would need to subscribe to the necessary webhook notifications and ingest them for changes to the card. Subscription is created automatically when Authorization is processed, while the Webhook Subscription feature is enabled in the Backoffice configuration.

The following Token updates are processed in Oracle Commerce Cloud:

- Expiry month
- Expiry year
- Card suffix

This section covers information on how to enable a Network Tokenization Service. Under Payment Gateways -> “ISV OCC Gateway”, select the Network Token Updates checkbox to enable the Network Tokenization. Save the changes.




Figure 46: Enabling Network Tokenization

10. Support

If you require support with this software, please contact GlobalPartnerSolutionsCS@visa.com and provide the following details:

- Summary of the issue
- Steps to reproduce the issue
- Oracle Commerce Cloud Platform version: You can find Oracle Commerce Cloud Platform Version in Oracle Commerce Cloud Backoffice dashboard.




Figure 47: ISV OCC Gateway Payment Processing Page.

- Plugin/ Extension version: Under Settings->Extension, find the version of the installed ISV Payment Gateway extension.




Figure 48: ISV OCC Gateway Extension Page.

- Cybersource Merchant ID: Under Settings->Payment Processing, Select the ISV OCC Payment from the Service Type dropdown, find the Merchant Id.




Figure 49: ISV OCC Gateway Payment Processing Page.

- Order ID/ Merchant Reference Number: Order ID can be found in Order Confirmation Page or Order History.
- Configuration screenshots: Please provide screenshots of ISV OCC Gateway Configurations.
- Log file and other relevant data: Download the **debug** and **error** logs from Oracle Commerce Cloud using `getExtensionServerLogs` admin endpoint.

11. Abbreviations

This section covers the full form of all the abbreviations used in the document.

Abbreviation	Full Form
MID	Merchant ID
EBC	Enterprise Business Center
Org ID	Organization ID
API	Application Programming Interface
PCI	Payment Card Industry

Table 2: Abbreviations