

CyberTracker XlsForm Reference Manual

Overview

CyberTracker is a universal data collection application which runs on mobile devices. One of the supported formats is [XlsForm](#).

XlsForm has an [extension mechanism](#) which allows users to activate CyberTracker behavior without affecting the semantics of the form.

This reference manual describes the CyberTracker extensions. Note that XlsForms are simply an Excel files and the extensions are columns in the worksheets.

There are three kinds of customization:

- Views, e.g. grid styles for single and multi-select lists
- Behaviors, e.g. GPS track logs and save targets
- Developer code, e.g. a new widget

Backend

CyberTracker supports [ODK Central](#), [KoBoToolbox](#) and [Survey123](#).

The CyberTracker extensions do not affect the semantics of the form and are transparent to backends. It is possible to use the same form to collect data across platforms (web, ODKCollect, etc) with a single form. In this scenario, CyberTracker would be chosen as a way to meet the needs of specific field workers.

Limitations

While CyberTracker supports most of the commonly used XlsForm features, it is not as mature as the existing data collection tools like ODK Collect, Kobo Collect and Survey123. Users should prefer to use those tools for mission critical projects.

TABLE OF CONTENTS

- [Initial setup](#)
 - [namespace \(required\)](#)
 - [version \(recommended\)](#)
- [Settings](#)
 - [immersive](#)
 - [wizardMode](#)
 - [summary](#)
 - [colors](#)
 - [esriLocationServiceUrl](#)
 - [sendLocationInterval](#)
- [Header](#)
 - [text](#)
 - [topText](#)
 - [button](#)
 - [homeIcon](#)
 - [cancelIcon](#)
 - [confirmIcon](#)
 - [hideHome](#)
 - [hidden](#)
 - [qml](#)
 - [qmlBase64](#)
 - [qmlFile](#)
- [Content](#)
 - [frameWidth](#)
 - [style](#)
 - [padding](#)
 - [columns](#)
 - [lines](#)
 - [border](#)

- [borderWidth](#)
- [fontSize](#)
- [fontBold](#)
- [itemHeight](#)
- [qml](#)
- [qmlBase64](#)
- [qmlFile](#)
- [Footer](#)
 - [buttons](#)
 - [home button](#)
 - [back button](#)
 - [next button](#)
 - [save button](#)
 - [nextOrSave button](#)
 - [index button](#)
 - [options button](#)
 - [map button](#)
 - [Custom button icons](#)
 - [buttonColor](#)
 - [hidden](#)
 - [qml](#)
 - [qmlBase64](#)
 - [qmlFile](#)
- [Save](#)
 - [snapLocation](#)
 - [targets](#)
 - [track](#)
- [Miscellaneous](#)
 - [fixCount](#)
 - [track file format](#)
- [Frequently Asked Questions](#)

- Which backends support XlsForm?
- Are CyberTracker extensions visible to other tools?

Initial setup

The following columns on the `settings` sheet are needed to begin using the CyberTracker extensions.

namespace (required)

The `ct` namespace tells other XlsForm tools to ignore columns starting with `bind::ct:`.

title		version	namespaces	
My Form		2022101001	ct="http://cybertracker.org/xforms"	
◀ ▶	survey	choices	settings	○

version (recommended)

The version field is used to track form versions over time. While not strictly required, it is a best practice to keep this field up to date. The [XlsForm specification](#) recommends the convention of 'yyyymmddrr'. For example, 2022021501 is the 1st revision from Feb 15th, 2022.

Settings

immersive

Setting this to ☐ yes causes the UI to use the wizard exclusively, i.e. there is no **Home** page. Default is ☐ no.

title	bind::ct:immersive
My Form	yes
<div><div>◀ ▶</div><div>survey</div><div>choices</div><div>settings</div><div><input type="radio"/></div></div>	

In the table below, the user context is always within a sighting and each page typically holds one question. Pressing the **options** button (highlighted in the first image) navigates to a new page which shows the current sighting on one tab and all sightings on the other. The user can edit previous sightings, but when editing is complete, the wizard will revert to the original sighting.

<div><div>🏠</div><div>Question 1</div></div> <div><div>Rhino</div><div>Lion</div><div>Buffalo</div><div>Leopard</div><div>Elephant</div><div>Giraffe</div></div> <div><div>←</div><div><div>📄</div></div><div>→</div></div>	<div><div>←</div><div>Current sighting</div><div>⚙️</div></div> <div><div>Introduction</div><div>Question 1 Lion</div><div>Question 3</div><div>Question 4</div><div>Question 5</div><div>Question 6</div><div>Question 7</div><div>Question 8</div><div>Question 9</div></div> <div><div><div>📄</div></div><div><div>📄</div></div></div>	<div><div>←</div><div>Saved sightings</div><div>⚙️</div></div> <div><div>Lion Tue 2022/12/13 19:19:56</div><div>Leopard Tue 2022/12/13 19:20:10</div></div> <div><div><div>📄</div></div><div><div>Submit</div></div><div><div>📄</div></div></div>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


wizardMode

If the ☐ immersive column is missing or set to ☐ no, then the UI reverts to *non-immersive* mode. In this case, there is a **Home** page which shows all sightings. The user returns to this page after saving a sighting.


--	--

title	bind::ct:wizardMode
My Form	yes
◀ ▶	survey choices settings ○

If `wizardMode` is set to `no`, then all questions show on a single page. This mode is recommended when wanting to show all sighting data at once and is the most conventional.



If `wizardMode` is set to `yes`, then each question will appear on its own page with **Back** and **Next** toolbar buttons to navigate between questions. The user will still return to the **Home** page between sightings. `wizardMode` appears on the **Settings** page as **Page mode**.



summary

The summary attribute specifies which fields to use as the summary of a sighting on the **Home** page. For example:

type	name	label
text	f_initial_text	Initial note
select_one animal	f_animal	Animal
select_multiple behavior	f_behavior	Behavior
text	f_final_text	Final note

◀ ▶

survey

choices

settings

○

The following setting will ensure that the summary only uses the `f_animal` and `f_behavior` questions.

title	bind::ct:summary
My Form	f_animal f_behavior


◀ ▶

survey

choices


settings

○



colors

The colors attribute specifies the color scheme used on the form. It follows the [Material Design](#) system:



title	bind::ct:colors.primary	bind::ct:colors.accent
My Form	#6200EE	green
◀ ▶	survey	choices settings ○

The following color fields are supported:

- primary
- accent
- foreground
- background
- darkPrimary
- darkAccent
- darkForeground
- darkBackground

Colors prefixed with 'dark' will be used when dark mode is activated. If dark colors are not provided, then 'primary' and 'accent' colors will be used, but 'foreground' and 'background' colors will be ignored.

Colors can also be provided as a JSON object:

title		bind::ct:colors	
My Form		{ "primary": "#6200EE", "accent": "green" }	
◀ ▶	survey	choices	settings ○


esriLocationServiceUrl

When using Survey123, CyberTracker supports uploading locations and tracks to a hosted feature service. In this case, the feature service is specified in the

`bind::ct:esriLocationServiceUrl` column:

title		bind::ct:esriLocationServiceUrl	
My Form		https://services6.arcgis.com/.../FeatureServer	
◀ ▶	survey	choices	settings ○

The feature service should be created using the CyberTracker Desktop Simulator (see [Download page](#)). There is an option off the **Tools** menu called **Create ArcGIS location service**. This tool will automatically create and configure a hosted service which is compatible with CyberTracker:



Create ArcGIS location service ×

Create an ArcGIS Online hosted feature service which will receive location track data from Survey123 projects.

User name

demo.cybertracker

Password

●●●●●●●●

Service name

Location service demo

Service description

The service description

Click 'START' to create service

START

After clicking **Start**, the tool will display the following:

Success - service created

Create a column named 'bind::ct:esriLocationServiceUrl' in the 'settings' sheet of the XlsForm and set it to the content below. Republish and install or update the form in CyberTracker.

title	namespaces	bind::ct:esriLocationServiceUrl
My Form	ct="http://cybertracker.org/xforms"	https://services6.arcgis.com/...
◀ ▶	survey	choices settings +

https://services6.arcgis.com/[redacted]/arcgis/rest/services/
Location_service_demo/FeatureServer

COPY TO CLIPBOARD

The feature service contains three layers: **Tracks** (point layer), **Last Known Locations** (point layer) and **Track Lines** (Polyline layer).

If this service is not specified, then tracks are placed in a `file` type question of the sighting. See [Tracks](#).

sendLocationInterval

If using Survey123, CyberTracker can send the current location at regular intervals - separately from tracks. The value is in seconds and is user configurable via the form Settings menu on the device. This specifies the default value.

`bind::ct:esriLocationServiceUrl` must be configured.

title		bind::ct:sendLocationInterval		
My Form		30		
◀ ▶	survey	choices	settings	<input type="radio"/>

Header

The header object supports custom header attributes. If no header object is specified, then the default header is used. By default, the header title is taken from the question label.

text

Custom header text.

type	name	bind::ct:header.text
select_one animal	Animal	Custom question text
<div><div><div>◀▶</div><div>survey</div><div>choices</div><div>settings</div><div>○</div></div></div>		

🏠

Custom question text

Rhino

Lion

Buffalo

Leopard

Elephant

Giraffe

←


📄

→

topText

Custom smaller text above main title.

type	name	bind::ct:header.topText
select_one animal	animal	Custom top text



button


Type of the button in the top-right corner. Valid values are:

- empty - by default no button is shown
- track - the current state of the GPS track system
- battery - the current state and level of the battery

type	name	bind::ct:header.button
select_one animal	animal	track
◀▶	survey	choices settings ○

Tapping on the button will provide more information, e.g. the track frequency or the battery level.


--	--	--



homelcon

Override the home icon with a custom icon.


type	name	bind::ct:header.homelcon
select_one animal	animal	my_home_icon.svg
<div><div>◀▶</div><div>survey</div><div>choices</div><div>settings</div><div>○</div></div>		



cancellcon

When editing a sighting in `immersive` mode, the system puts a **Cancel** button in the top left corner. Clicking this button will discard any edits. This property overrides the default icon used.


type	name	bind::ct:header.cancelIcon
select_one animal	animal	my_edit_cancel_icon.svg
<div><div><div>◀▶</div><div>survey</div><div>choices</div><div>settings</div><div>○</div></div></div>		




confirmIcon

When editing a sighting in `immersive` mode, the system puts a **Confirm** button in the top right corner. Clicking this button will accept edits made to the sighting. This property overrides the default icon used.

type	name	bind::ct:header.confirmIcon
select_one animal	animal	my_edit_confirm_icon.svg
<div><div><div>◀▶</div><div>survey</div><div>choices</div><div>settings</div><div>○</div></div></div>		





hideHome


If ☐ yes then the home button is hidden. Default is ☐ no.


type	name	bind::ct:header.hideHome
select_one animal	animal	yes
<div><div>◀▶</div><div><div>survey</div><div>choices</div><div>settings</div></div><div><input type="radio"/></div></div>		

hidden

If ☐ yes then the header is hidden. Default is ☐ no.

type	name	bind::ct:header.hidden
select_one animal	animal	no
<div><div>◀▶</div><div><div>survey</div><div>choices</div><div>settings</div></div><div><input type="radio"/></div></div>		





qml


A **QML** fragment to use instead of the built-in header. See Developer section. For example:


type	name	bind::ct:header.qml
select_one animal	animal	qml fragment
<div><div>◀ ▶</div><div><div>survey</div><div>choices</div><div>settings</div></div><div><input type="radio"/></div></div>		

To set the header to a blue rectangle, replace `qml fragment` above with the following:

```
import QtQuick 2.15

Rectangle {
    color: "blue"
    height: 64
}
```





qmlBase64

Base64 encoded QML (see **qml** above).

qmlFile

Name of a QML file which exists alongside other project files. This is not supported on ODK or KoBoToolbox, but can be used in Survey123.

Content


The content section is the middle part of the screen between the header and footer. By default it automatically selects a control for the question type, e.g. a date selector for a date question. By specifying a custom content object, more styles are available. This is especially useful for customizing lists.

frameWidth

Frame width around the content area of the page. Default is 16.

type	name	bind::ct:content.frameWidth
select_one animal	animal	0
<div><div>◀▶</div><div><div>survey</div><div>choices</div><div>settings</div></div><div><div></div></div></div>		

In this case, `frameWidth` was set to `0` in the second image.



style

The visual appearance of the question.

type	name	bind::ct:content.style
------	------	------------------------


select_one animal	animal	IconOnly
◀ ▶	survey	choices settings ○


For **select_one** questions


- (not specified)
- IconOnly
- TextOnly
- TextBesideIcon
- TextUnderIcon


Single select
Default view


Search


 Alouatta caraya


 Alouatta guariba

 Alouatta macconelli





 Alouatta palliata





 Alouatta seniculus





 Aotus azarae





 Aotus vociferans





Single select
IconOnly style























Single select
TextOnly style

Alouatta caraya

Alouatta guariba

Alouatta macconelli

Alouatta palliata

Alouatta seniculus

Aotus azarae

Aotus vociferans



Ateles geoffroyi



Ateles hybridus brunneus



Ateles paniscus 2



...



Single select
TextBesideIcon style



Alouatta caraya  Alouatta guariba 



Alouatta macc...  Alouatta palliata 



Alouatta senic...  Aotus azarae 



Aotus vociferans  Ateles geoffroyi 



Ateles hybridu...  Ateles paniscu... 

Ateles paniscus  Avahi laniger 


Brachyteles ar...  Brachyteles ar... 


Cebus apella  Cercocobus agi... 


Cercopithecid...  Cercopithecus ... 


Cercopithecus ...  Cercopithecus ... 


Single select
TextUnderIcon style


 Alouatta car...


 Alouatta gua...


 Alouatta ma...


 Alouatta pall...


 Alouatta sen...


 Aotus azarae


 Aotus vocifer...


 Ateles geoffr...


 Ateles hybrid...


 Ateles panis...


 Ateles panis...


 Avahi laniger


 Brachyteles ...

 Brachyteles ...

 Cebus apella

 Cercopithecus ...

 Cercopithecus ...


 Cercopithecus ...


For **select_multiple** questions:


- (not specified)
- IconInlay
- IconOnly
- TextOnly
- TextBesideIcon


Multiple select
Default view


Search


 Afropavo congensis ☒

 Alectrurus tricolor ☐

 Amazona amazonica ☐

 Amazona autumnalis ☒

 Amazona vinacea ☐


 Anthracoceros albirostris ☐


←


📄


→


Multiple select
IconInlay style






































































←


📄


→


Multiple select
IconOnly style
















































































←

📄

→

Multiple select
TextOnly style

☒ Afropavo congensis

☐ Alectrurus tricolor

☐ Amazona amazonica

☐ Amazona autumnalis

☒ Amazona vinacea

☐ Anthracoceros albirostris

☐ Aratinga solstitialis

☒ Ara ararauna

☐ Ardea humbloti

☐ Bangsia aureocincta


☐ ...


←


📄


→


Multiple select
TextBesideIcon style


☒ Afropavo congensis 


☐ Alectrurus tricolor 


☐ Amazona amazonica 

☒ Amazona autumnalis 

☐ Amazona vinacea 

☒ Anthracoceros albirostris 

☐ Aratinga solstitialis 

☐ Ara ararauna 


←

📄




→

For **range** questions:

type	name	parameters	bind::ct:content.style	bind::ct:content.c
range	animal_count	start=1 end=100 step=1	Grid	5
◀ ▶	survey	choices settings ○		

Range
Grid style, 5 columns

1	2	3	4	5
6	7	8	9	10
11	12	13	14	15
16	17	18	19	20
21	22	23	24	25
26	27	28	29	30
31	32	33	34	35
36	37	38	39	40
41	42	43	44	45
46	47	48	49	50
51	52	53	54	55
56	57	58	59	60
61	62	63	64	65



Ignored for other question types.


padding

The padding space between grid items. Requires `style` to be set.

type	name	bind::ct:content.padding
select_one animal	animal	8
<div><div><div><div>◀▶</div><div>survey</div></div><div>choices</div><div>settings</div><div><input type="radio"/></div></div></div>		

Padding values are 0, 4 and 8.

Single select
IconOnly style




←

📄

→

Single select
IconOnly style




←

📄

→

Single select
IconOnly style



←

📄

→

columns

Number of columns for grids. Requires `style` to be set. Defaults to 2.

type	name	bind::ct:content.style	bind::ct:content.columns
select_one animal	animal	Grid	4
<div><div>◀▶</div><div><div>survey</div><div>choices</div><div>settings</div></div><div><input type="radio"/></div></div>			

For example, column values below are `3`, `5` and `10`.

Range
Grid style, columns

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18
19	20	21
22	23	24
25	26	27
28	29	30
31	32	33
34	35	36
37	38	39

←

📄

⬇️

Range
Grid style, columns

1	2	3	4	5
6	7	8	9	10
11	12	13	14	15
16	17	18	19	20
21	22	23	24	25
26	27	28	29	30
31	32	33	34	35
36	37	38	39	40
41	42	43	44	45
46	47	48	49	50

←

📄

⬇️

Range
Grid style, columns

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
71	72	73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88	89	90
91	92	93	94	95	96	97	98	99	100

←

📄


⬇️

lines

Show lines between cells for grids. Requires `style` to be set. Defaults to true.

type	name	bind::ct:content.style	bind::ct:content.lines
select_one animal	animal	IconOnly	no
◀ ▶	survey	choices settings ○	

lines value below is yes and no.




border

Show border around the outside of a grid. Requires style to be set. Defaults to no if frameWidth is 0, yes otherwise.

type	name	bind::ct:content.style	bind::ct:content.border
select_one animal	animal	IconOnly	yes
◀ ▶	survey	choices settings ○	

Border value is yes and no.







borderWidth

Border width for grid lines. Requires `style` to be set. Defaults to 2.

type	name	bind::ct:content.style	bind::ct:content.borderWidth
select_one animal	animal	IconOnly	2
◀ ▶	survey	choices settings ○	

borderWidth value is 2 and 4.






fontSize

Size text font size. Requires `style` to be set. Defaults to 16. Note that the font is subject to scaling according to the **Font size** in the main Settings page.

type	name	bind::ct:content.style	bind::ct:content.fontSize
select_one animal	animal	IconOnly	14
<div><div>◀ ▶</div><div>survey</div><div>choices</div><div>settings</div><div><input type="radio"/></div></div>			

`fontSize` values are `12`, `14` and `16`.



fontBold

Set font to bold. Requires `style` to be set. Defaults to false.

type	name	bind::ct:content.style	bind::ct:content.fontBold
select_one animal	animal	IconOnly	yes
<div><div>◀▶</div><div>survey</div><div>choices</div><div>settings</div><div><input type="radio"/></div></div>			

itemHeight

Set height of individual items. Requires `style` to be set. Defaults to 48.

type	name	bind::ct:content.style	bind::ct:content.itemHeight
select_one animal	animal	IconOnly	48
<div><div>◀▶</div><div>survey</div><div>choices</div><div>settings</div><div><input type="radio"/></div></div>			

`itemHeight` values are `48`, `64` and `128`.

Single select
Custom frame

◀

📄

→

Single select
Custom frame

◀

📄

→

Single select
Custom frame

◀

📄

→

qml

A **QML** fragment to use instead of the built-in content. See Developer section. For example:

type	name	bind::ct:content.qml
------	------	----------------------


integer	animal_count	qml fragment
◀ ▶	survey	choices settings ○

To set the content to a blue rectangle, replace `qml fragment` above with the following:

```
import QtQuick 2.15
import QtQuick.Controls 2.15

Rectangle {
    color: "blue"
    Button {
        anchors.centerIn: parent
        text: "Click me"
        onClicked: parent.color = "red"
    }
}
```

In the example, the content is blue, then changes to red when the button is clicked.



qmlBase64

Base64 encoded QML (see **qml** above).

qmlFile

Name of a QML file which exists alongside other project files. This is not supported on

ODK or KoBoToolbox, but can be used in Survey123.


Footer

The footer object supports custom control buttons, e.g. home, back, next, save, etc. If no footer object is specified, then the default control is used.

buttons

`buttons` is text which specifies which buttons should be shown on the footer toolbar.

type	name	bind::ct:footer.buttons
select_one	animal	back next index save map
<div><div><div>◀▶</div><div>survey</div><div>choices</div><div>settings</div><div>○</div></div></div>		



home button

The `home` button returns to the **Home** page. In `immersive` mode, this returns to the Projects page, otherwise it returns to the project home page.

back button

The `back` button navigates to the prior question on the form. If the wizard is at the start of the form, the back button is hidden.

next button

The `next` button navigates to the next question on the form. If there is no next question, then the next button is hidden.

save button


The `save` button will attempt to save the current sighting. If the sighting has invalid data, then the **Index page** will be shown with invalid fields highlighted.

nextOrSave button

The `nextOrSave` button will show as a `next` button unless there are no more questions, in which case it will become a `save` button.

index button


The `index` button displays a list of all the form questions. Selecting a question will navigate the wizard to it directly. A jump-to-last button on the top right of the header will jump to the next required question. If all required questions are filled in, then it jumps to the last question.



options button


The `options` button is only available in `immersive` mode. In non-immersive mode, it becomes the `index` button (see above).

The `options` button shows an options page with two tabs: current sighting and saved sightings:



map button

The `map` button opens the map dialog.



Custom button icons

The button icons can be overridden with custom ones. To do this, create columns with the name of the button followed by `Icon`. For example:

- homelcon
- backlcon
- nextlcon
- savelcon
- indexlcon
- optionslcon
- maplcon

type	name	bind::ct:footer.maplcon
select_one	animal	my_custom_map_icon.svg
◀ ▶ survey choices settings ○		

buttonColor

Override the default button color with a custom one. This applies to all buttons.

type	name	bind::ct:footer.buttonColor
select_one animal	animal	#6200EE
◀ ▶ survey choices settings ○		

hidden

If ☐ yes then the footer is hidden. Default is ☐ no.

type	name	bind::ct:footer.hidden
select_one animal	animal	no
◀ ▶ survey choices settings ○		

qml

A [QML](#) fragment to use instead of the built-in footer. See Developer section. For example:

type	name	bind::ct:footer.qml
integer	animal_count	qml fragment

To set the footer to a blue rectangle, replace `qml fragment` above with the following:

```
import QtQuick 2.15

Rectangle {
    color: "blue"
    height: 64
}
```



qmlBase64

Base64 encoded QML (see **qml** above).

qmlFile

Name of a QML file which exists alongside other project files. This is not supported on ODK or KoBoToolbox, but can be used in Survey123.

Save

When the user presses the **Save** button, this triggers the save behavior.

snapLocation

Setting `snapLocation` to the name of a `geopoint` question will create a popup to acquire the GPS location. This feature is only active when `wizardMode` is enabled.

type	name	label
geopoint	f_location	Location
select_one animal	f_animal	Animal
text	f_note	Note
<div><div>◀ ▶</div><div>survey</div><div>choices</div><div>settings</div><div><input type="radio"/></div></div>		

title	bind::ct:save.snapLocation
My form	f_location
<div><div>◀ ▶</div><div>survey</div><div>choices</div><div>settings</div><div><input type="radio"/></div></div>	

In this example, the user flow will be:

Animal

Rhino

Elephant

Lion

Leopard

Buffalo

→


Note

Test note

←

↓

←



0

10

20

30

50

100

targets

In the example below, the user will be presented with a popup containing the choices **Restart** or **Another**. After the sighting is saved, a new sighting will be created starting at the targeted question. All prior question data will be replicated into the new sighting.

This value must be a valid JSON array.

type	name	label
select_one animal	f_animal	Animal
select_multiple behavior	f_behavior	Behavior
text	f_note	Note
<div><div>◀ ▶</div><div><div>survey</div><div>choices</div><div>settings</div><div>○</div></div></div>		

restart and another are taken from the choices sheet in the saveTargets list name.


list_name	name	label
saveTarget	restart	Restart
saveTarget	another	Another
<div><div>◀ ▶</div><div><div>survey</div><div>choices</div><div>settings</div><div>○</div></div></div>		

Note that question is the name of the targeted question in the survey table. If the question is not relevant, then this choice will be hidden.

title	bind::ct:save.targets
My form	[{ "choice": "restart", "question": "f_animal"}, { "choice": "another", "question": "f_behavior"}]
<div><div>◀ ▶</div><div><div>survey</div><div>choices</div><div>settings</div><div>○</div></div></div>	

Note that if immersive is set to false, then the target list will automatically contain the **home** button. This option will save and return to the **Home** page without automatically creating a new sighting.

--	--	--



track

In the example below, there is a `select_one` question called `f_track` with choices `start`, `stop` and `nochange`. When the user presses **Save**, the track timer is adjusted depending on which choice was selected. The values in `updateIntervalSeconds` and `distanceFilterMeters` are the new track settings.

This value must be a valid JSON array.

type	name	label
file	f_track_file	
select_one track_items	f_track	Configure track
text	f_note	Note
<div> <div>◀ ▶</div> <div>survey</div> <div>choices</div> <div>settings</div> <div>○</div> </div>		

list_name	name	label
track_items	start	Start
track_items	stop	Stop
track_items	nochange	No change
<div> <div>◀ ▶</div> <div>survey</div> <div>choices</div> <div>settings</div> <div>○</div> </div>		

title	bind::ct:save.trackFile	bind::ct:save.track
		[{"condition": "selected(\${f_track}, 'start')",

My form	f_track_file	"updateIntervalSeconds": 5, "distanceFilterMeters": 10 , { "condition": "selected(\${f_track},'stop')", "updateIntervalSeconds": 0, "snapTrack": true }}
◀ ▶	survey	choices settings ○




`condition` is an XlsForm expression which activates this option if matched, e.g. `${start_stop}='start'`. Check out the [ODK Form Logic documentation](#).




`updateIntervalSeconds` is the number of seconds between GPS readings. Set to 0 to disable the track timer.

`distanceFilterMeters` is the minimum distance between readings in meters. This is optional and by default no distance filter is used.

`snapTrack` causes the system to snapshot all the track points (since prior snap).

If using Survey123 and `esriLocationServiceUrl` is specified, then the track data will be sent to the [feature service](#). Otherwise, a track file will be created and added to a `file` type question in the form. The question selected must be of type `file` and should have a `trackFileFormat` column specified.



Miscellaneous

fixCount

For `geopoint` question types, the number of skipped readings before a fix is taken. The default value is 4. Some GPS devices return old readings before real readings. To overcome this, setting the `fixCount` will cause the system to require several readings before the final location is taken.

type	name	parameters
geopoint	f_location	fixCount=4
◀ ▶	survey	choices settings ○

track file format

When the user presses **Save** and creates a track file, it is stored in a `file` field specified in the `settings` sheet in the `bind::ct:save.trackFile` column.

By default the format of the track is zipped geojson, but this can be changed by using the `format` parameter of the question itself. Supported values are `geojson` and `kmz` (not supported on Survey123).

Survey123 users should prefer to use a location service - see [esriLocationServiceUrl](#). If a location service is specified, this question should be removed.

type	name	appearance	parameters
file	f_track_file	hidden	format=kmz
◀ ▶	survey	choices settings ○	

title	bind::ct:save.trackFile
My form	f_track_file
◀ ▶	survey choices settings ○

Frequently Asked Questions

Which backends support XlsForm?

CyberTracker supports [ODK Central](#), [KoBoToolbox](#) and [Survey123](#).

Are CyberTracker extensions visible to other tools?

XlsForm extensions support custom columns by using the `namespaces` value in the `settings` sheet. Columns prefixed with `bind::ct:` are only used by CyberTracker and are ignored (but preserved) by other tools.