

# Comments to the Naive Rete python code

YKY, general.intelligence@gmail.com

September 30, 2019

**WME** = working memory element.

**Alpha** network: performs the “decision tree” tests.

**Alpha memory** = AM. Store sets of WMEs, ie, *instantiations*.

**Beta** network: checks consistency of **variable bindings** between conditions.

Beta memories store sets of **tokens**, each token representing a sequence of WMEs — specifically, a sequence of  $k$  WMEs, satisfying the first  $k$  conditions (with consistent variable bindings) of some production.

**Production** node = **p-node** = firing of an action.

**ncc** = negated conjunctive conditions. Tests for the absence of a certain combination of WMEs.

**Activation** means passing a new WME down the rete network.

**Left** activation = activation of some node from another node in the **beta** network

**Right** activation = activation of some node from the **alpha** network

**Tokens** = conjunctions of WMEs. It's stored as a tree with each node holding 1 new WME and its parent.

Token has **join\_results** which is specifically for *negative* nodes. Negative nodes are just like ordinary join nodes, but instead of propagating the results of the join down the network, it stores them in the “results” memory in each token. A token is thus propagated down the network if and only if its local result memory is *empty*, since this indicates the absence of any such WME in working memory.

The **join\_results** store NegativeJoinResults. Each NJR has a WME and its owner which is a token.

WMEs also have a field to store NJRs. This is for handling WME *removal*.

## 1 Bug re: remove(x) but x not in list

Seems that `wme.negative_join_results` does not contain enough NJRs for removal. The fix is “`pop()`”.

## 2 Bug re ncc\_results: token.owner = None

`token.node = NCC Partner node`

`token.owner = None`                      { the token whose local memory this result resides }

Solution: condition “else” not handled correctly in NCC partner left-activation.

## 3 Bug: `child.amem.successors.remove(child)`, child not in list

Currently solution is to comment out this part of the code. (For some unknown reason this part is not implemented by the NaiveRete author).

## 4 Fixing the within-condition variable-binding problem

Starts with:

```
self.alpha_root.activation(wme) (1)
```

in `network.py`.