

# On AGI architecture

December 19, 2019 mid-term report

YKY

Independent researcher, Hong Kong

*generic.intelligence@gmail.com*

# Table of contents

- 3 AGI
- 4 No free lunch (NFL)
- 5
- 7
- 9 Topos
- 10 (permutation invariance)


Hello friends 😊

I have made some intermediate progress recently, which I share below.  
I am also looking for collaborators.

# The simplest AGI architecture

- ▶ The simplest AGI architecture consists of a single recurrent loop:

rewrite / update / transition function =  $F$




(1)

- ▶ It operates under reinforcement learning, maximizing rewards by the Bellman optimality condition
- ▶ The transition function  $F$  can be implemented by a neural network
- ▶ According to No Free Lunch theorem, problem with this architecture is lack of inductive bias, learning is too slow

## Some musings on No Free Lunch (NFL)


- ▶ According to NFL, there is no such things as “good” or “bad” inductive bias
- ▶ As long as it accelerates learning, and still accomodates AGI, it is good bias:




- ▶ For example, the neural network  $F$  can be made **sparse** while preserving deepness
- ▶ Yet, I proposed earlier to use logic as bias. Is that redundant? 🤔

## “Double loop” architecture


- Assume **working memory** consists of disparate propositions ( $\bullet$ ), residing in an inner loop. As this loop is iterated, the propositions are condensed into the hidden state. Hence the “double-loop” architecture




- This same architecture may be shared by the human brain, as its structure is simple and thus could have been evolved
- As far as I know, BERT also contains an implicit recurrence, where words in a sentence are condensed into a hidden state, from which target words are generated one by one
- So it seems that if we modify BERT to be a “double loop”, we can get an AGI:



► Diagram (3) is a bit inaccurate, here is a more detailed diagram:



► In contrast, one can use a **symmetric NN** to make the architecture even simpler:



► But it's not easy to decide whether (5) or (6) learns faster 🤔

# Connection between reinforcement learning & quantum mechanics

- ▶ The optimal condition for reinforcement learning is the **Bellman** equation:

$$\boxed{\text{Bellman}} \quad S_t(x) = \max_u \{L(x, u) + \gamma S_{t+1}(x)\} \quad (7)$$

- ▶ The differential version of Bellman equation is the **Hamilton-Jacobi** equation in classical analytic mechanics (This has been recognized in 1970's by Kalman, Pontryagin and others):

$$\boxed{\text{Hamilton-Jacobi}} \quad \frac{\partial S(x, t)}{\partial t} = -H \quad (8)$$

- ▶ The Hamiltonian  $H$  arises when trying to maximize the Lagrangian  $L$  using Lagrangian multipliers. Such multipliers have the interpretation of **momentum**.

$$L = \text{KE} - \text{PE} \quad , \quad H = \text{KE} + \text{PE} \quad (9)$$

where KE = kinetic energy, PE = potential energy.

- ▶ Up to now, we changed a **discrete** equation to a continuous **differential** equation, but that has not yielded any advantage

- ▶ Recently I independently discovered an exact way to go from the classical Hamilton-Jacobi equation to the Schrödinger equation via the substitution  $\Psi = e^{-i\hbar S}$ :

$$\boxed{\text{Hamilton-Jacobi}} \quad \frac{\partial S}{\partial t} = -H \quad \Rightarrow \quad i\hbar \frac{\partial \Psi}{\partial t} = H\Psi \quad \boxed{\text{Schrödinger}} \quad (10)$$

- ▶ We have always been told in textbooks that such a process of **quantization** can only be achieved heuristically, but some friend informed me that [Field 2010] has derived this result.
- ▶ From the perspective of AI, this means that **solving the reinforcement learning problem is equivalent to solving the Schrödinger equation in Hilbert space!**
- ▶ Moreover, the Schrödinger equation can be transformed into the **diffusion** / heat equation via the introduction of **imaginary time**:

$$\boxed{\text{wave eqn.}} \quad \frac{\partial \Psi}{\partial t} + i\Delta\Psi = 0 \quad \Leftrightarrow \quad \frac{\partial u}{\partial t} + \Delta u = 0 \quad \boxed{\text{heat eqn.}} \quad (11)$$

- ▶ Yet, if this is to be applicable to AGI, we need to **discretize** the state space (which becomes a graph), and use the discrete Laplacian  $\Delta$  or discrete Schrödinger operator to act on graphs
- ▶ Impressive as it may sound, this may be of low practical value 😞



# Topos theory

A topos is a category in which one can “do logic”. The idea originated in 1950’s when Lawvere tried to re-formulate the foundation of mathematics / set theory in the new language of category theory.

In a topos, 3 operations are allowed between objects:



- ▶ Cartesian product  $A \times B$  (corresponding to  $A \wedge B$  in propositional logic)
- ▶ exponentiation  $A \rightarrow B = B^A$  (corresponding to  $A \Rightarrow B$  in propositional logic)
- ▶ subobject classifier  $A \hookrightarrow B$  (corresponding to the subset notion  $A \subseteq B$ )

The significance of topos theory is that it distills which mathematical structures are able to carry on logic operations, e.g. relation graphs, algebras, etc.

In my theory, the neural network  $F$  implements  $U \xrightarrow{F} V$  which is the exponentiation  $V^U$ , where  $U, V$  are vector spaces. This requires, at least, to embed the structure of  $A \times B$  into vector space. However  $A \times B = B \times A$  is commutative, which led me to consider Abelian group theory....

# Permutation invariance

- ▶ Recently a nice idea has been proposed to embed Word2Vec into Poincaré disc / hyperbolic space [Nickel and Kiela 2017]
- ▶ Can we similarly embed logic structures (as vectors) into hyperbolic space?
- ▶ Cayley graph of the free group  $F_2$  is a **tree**, but Cayley graph of the **Abelian** free group is **grid-like**:



(12)

- ▶ Generally, the free group  $F_n$ 's Cayley graph can be embedded into the (planar) hyperbolic disc, but the Abelianization of  $F_n = F_n^{\text{Ab}} \cong \mathbb{Z}^n = \mathbb{Z} \times \dots \mathbb{Z}$  is a  **$n$ -dimensional** grid, which seems impossible to embed on a plane.
- ▶ Even considering representation theory, all irreducible representations of Abelian groups are 1-dimensional. The representation of  $F_n^{\text{Ab}}$  is precisely the direct sum of  $n$  copies of dim-1 representations. Useless!

- ▶ Seems that  $\mathbb{Z}^n$  cannot be embedded into lower dimensions, unless we use some kind of **fractal** structure. However, fractals are exactly the realm that is out-of-reach of the universal approximating power of neural networks!
- ▶ Another strategy is to create **symmetric** neural networks whose output is invariant when the input is permuted. This could be achieved by “weight-sharing”.
- ▶ For this to work, the activation function must be **polynomials**.
- ▶ A drawback of this approach is when # layers grow, # constraints also grow exponentially, making it hard to build deep (many-layer) networks
- ▶ An advantage is that the resulting NN is very sparse in terms of # weights. This is a form of inductive bias.
- ▶ As of this writing, I am yet exploring another approach that is inspired by Google’s BERT. More on this later.

Field, JH (2010). “Derivation of the Schrödinger equation from the Hamilton-Jacobi equation in Feynman’s path integral formulation of quantum mechanics”. In: *European Journal of Physics*.

Nickel, Maximillian and Douwe Kiela (2017). “Poincaré embeddings for learning hierarchical representations”. In: *Advances in neural information processing systems*, pp. 6338–6347.

Thanks for watching 😊