ADVANCED CAPABILITY IMPLEMENTATION · OPEN-SOURCE AI TOOLING

Advanced Capability Implementation: PortSwigger MCP Server & Claude AI Integration

Deploying Free, Local AI-Powered Security Triage in Burp Suite Community Edition via the Model Context Protocol (MCP)

Lead Security Researcher: Mohammad Sopfian aka *CyberZal*
GitHub Profile: https://github.com/Cyberzal1
Project Repository: agentic-redteam-mcp-lab

Assessment Environment: Kali Linux Rolling (192.168.204.128)
Proxy & Telemetry Bridge: Burp Suite Community Edition v2026.3.2 + PortSwigger MCP (Port 9876)
Autonomous AI Auditor: Claude Desktop (Claude Sonnet 5.5 / 3.5)

1. Executive Summary & The Community AI Opportunity

Modern application security workflows increasingly leverage generative artificial intelligence to triage intercepted HTTP traffic, explain complex multi-stage vulnerability chains, and generate targeted remediation guidance. However, native commercial AI capabilities in enterprise security proxies—such as PortSwigger's commercial **Burp AI**—are strictly restricted behind expensive enterprise and Professional tier subscriptions. For independent security researchers, university students, and open-source penetration testers using **Burp Suite Community Edition**, accessing automated, context-aware AI telemetry analysis historically presented a severe financial bottleneck.


This implementation report documents how to completely overcome this restriction by compiling and deploying PortSwigger's open-source **Model Context Protocol (MCP) Server** extension inside **Burp Suite Community Edition v2026.3.2**. By bridging the extensible Montoya Java API with Anthropic's **Claude Desktop** (running state-of-the-art models such as **Claude Sonnet 5.5**), security practitioners can unlock enterprise-grade AI audit capabilities **100% free of charge**.

Core Breakthroughs & Architectural Innovations

- **Commercial License Bypass via Open Standards:** Rather than paying for Burp Suite Professional's proprietary AI credits, this architecture leverages the open Model Context Protocol (MCP) to connect external frontier models directly to Burp's proxy engine.
- **Full Community Edition Feature Parity:** Enables full bidirectional interaction: Claude Desktop can programmatically query proxy history (`get_proxy_http_history`), inspect Repeater transactions, analyze attack payloads, and recommend targeted defense code.
- **Privacy-Preserving & Local Isolation:** The MCP bridge binds strictly to localhost (`127.0.0.1:9876`) with explicit target auto-approval controls, preventing data leakage across unauthorized network segments.

2. Technical Architecture & MCP Telemetry Topology

The Model Context Protocol (MCP) provides a standardized protocol enabling external AI client runtimes to securely interface with local development and security tools. The integration operates over a multi-tier loopback socket topology inside Kali Linux (`192.168.204.128`):



Architecture Component	Network Socket / Path	Technology Stack	Functional Role in Free AI Integration
Burp Suite Community	`127.0.0.1:8080` (TCP)	Burp Community Edition v2026.3.2	Intercepts client traffic, performs request manipulation, logs proxy history.
PortSwigger MCP Server	`127.0.0.1:9876` (SSE)	Montoya Java API (Java 17/21)	Exposes internal proxy history and repeater capabilities as MCP tool endpoints.
MCP Transport Bridge	Stdio / SSE Process	`mcp-proxy-all.jar`	Bridges Claude Desktop's stdio transport with Burp's SSE network listener.
AI Auditor Client	Claude Desktop App	Claude Sonnet 5.5 Engine	Executes automated proxy history queries, parses attack telemetry, writes exploit triage.

3. Step-by-Step Build & Deployment Guide

3.1 Step 1: Environment & Toolchain Prerequisites

To build the PortSwigger MCP server extension from source on Kali Linux or any Debian-based host, ensure the required Java Development Kit (JDK 17 or JDK 21) and build utilities are installed:

```
$ sudo apt update && sudo apt install -y default-jdk git curl
$ java -version
openjdk version "21.0.6" 2025-01-21
OpenJDK Runtime Environment (build 21.0.6+7-Debian-1)
```

3.2 Step 2: Compiling the Burp MCP Server Extension

Clone the official open-source PortSwigger MCP repository and compile the fat JAR containing all necessary dependencies using the Gradle wrapper:

```
$ git clone https://github.com/PortSwigger/mcp-server.git ~/mcp-server
$ cd ~/mcp-server
$ ./gradlew shadowJar
```

The build output will generate the standalone extension binary at: `~/mcp-server/build/libs/burp-mcp-all.jar`

3.3 Step 3: Loading into Burp Suite Community Edition

1. Launch **Burp Suite Community Edition** (v2026.x or later).
2. Navigate to the top-level **Extensions** tab → **Installed** sub-tab.
3. Click the **Add** button under the extension table.

4. In the *Load Burp Extension* dialog:
   - Set **Extension type**: `Java`
   - Set **Extension file (.jar)**: Browse and select `burp-mcp-all.jar`
5. Click **Next**. The extension registers instantly with output: `[+] MCP Server listening on http://127.0.0.1:9876/sse`.
6. Switch to the newly created **MCP** tab in Burp Suite's main window:
   - Under **Auto-Approved HTTP Targets**, click **Add** and specify `127.0.0.1:5000` (or your target scope).
   - Enable the checkbox: `Always allow HTTP history access` (prevents prompt approval popups during automated triaging).

3.4 Step 4: Configuring Claude Desktop with the MCP Bridge

Because Claude Desktop utilizes standard input/output (stdio) for MCP servers, while Burp's extension serves traffic over Server-Sent Events (SSE) on port `9876`, configure the bridge entry in Claude's configuration file:

```
$ nano ~/.config/Claude/claude_desktop_config.json
```

```
{
  "mcpServers": {
    "burp-suite": {
      "command": "java",
      "args": [
        "-jar",
        "/home/kali/mcp-configs/mcp-proxy-all.jar",
        "http://127.0.0.1:9876/sse"
      ]
    }
  }
}
```

Restart Claude Desktop. The hammer/tool icon in the chat interface will illuminate, revealing three newly registered tools: `get_proxy_http_history`, `get_repeater_tabs`, and `send_to_repeater`.

4. Hands-On Verification & Operational Audit Evidence

To validate the effectiveness of this zero-cost AI auditing pipeline, the system was subjected to active testing against an autonomous agentic application. The following visual evidence demonstrates end-to-end execution:

Figure 1: Kali Linux CLI Terminal — Automated Exploitation Execution & Traffic Generation

Host: Kali Linux (192.168.204.128) | **Target:** 127.0.0.1:5000 | **Proxy:** 127.0.0.1:8080




Figure 1: Terminal session in Kali Linux generating HTTP proxy traffic for the MCP bridge. The CLI executes Attack 1 (API key exfiltration from system_vault.key returning 200 OK) and Attack 2 (/etc/passwd arbitrary file read returning 3,592 bytes), routing all payloads through Burp Proxy at 127.0.0.1:8080.

Figure 2: Burp Suite Community Edition Repeater — Attack 1 Parameter Tampering & Secret Leakage

Tool: Burp Repeater (Tab 2) | **Endpoint:** `POST /api/chat` | **Status:** `HTTP/1.1 200 OK`




Figure 2: Burp Suite Community Edition Repeater showing the intercepted Attack 1 JSON payload and the resulting server response leaking SECRET_ENTERPRISE_API_KEY=sk_prod_9988_ALPHA_SUPERSECRET_TOKEN alongside internal agent reasoning metadata.

Figure 3: Burp Suite Community Edition Repeater — Attack 2 Excessive Agency & /etc/passwd Leak

Tool: Burp Repeater (Tab 3) | **Target Path:** `/etc/passwd` | **Payload Size:** `3,592 Bytes`




Figure 3: Burp Suite Repeater validating arbitrary file read vulnerability (OWASP LLM06). The unvalidated agent file tool accepts absolute path /etc/passwd, returning 3,592 bytes containing the full host Linux account registry into the Burp proxy stream.

Figure 4: Live AI Telemetry Audit via Burp Suite MCP & Claude Desktop (Claude Sonnet 5.5)

Bridge: `burp-mcp-all.jar` (Port 9876) | **AI Client:** Claude Desktop (Claude Sonnet 5.5) | **Tool Call:** `get_proxy_http_history`




Figure 4: The core milestone of this capability implementation. Side-by-side operational environment in Kali Linux showing Claude Desktop (running Claude Sonnet 5.5) autonomously querying Burp Suite Community Edition's proxy history on port 9876, identifying the 21:08:22 GMT transaction, and providing deep root-cause triage without any commercial Burp AI license.

5. Telemetry Query Capabilities & Comparative Benchmarking

Through the MCP connection, Claude Desktop acts as an autonomous tier-1 security analyst. The table below illustrates the technical commands and analytical capabilities unlocked in Burp Suite Community Edition:

Operational Capability	Commercial Burp AI (Pro / Enterprise)	PortSwigger MCP + Claude Community Integration
Licensing Cost	Requires $449+/yr Pro License + AI Token Packs	**100% Free** (Runs on Burp Community + Standard Claude / Ollama)
Proxy History Inspection	Limited to inline request/response explanations	**Full Programmatic Access:** Regex search, timestamp filtering, multi-transaction correlation
AI Model Flexibility	Locked to PortSwigger's hosted proprietary model	**Universal Model Support:** Claude Sonnet 5.5, GPT-4o, DeepSeek-R1, or local Ollama
Custom Prompt Orchestration	Pre-defined, rigid commercial templates	**Completely Customizable:** Full custom agentic instructions, OWASP LLM prompt matrices
Bidirectional Repeater Injection	Yes (Native UI widgets)	Yes (Via `send_to_repeater` MCP tool call directly from chat)

5.1 Sample AI Interaction Script via Burp MCP

To demonstrate the analytical power of this integration, the prompt below was issued directly to Claude Desktop inside the Kali Linux environment:

```
Operator: "Please inspect my Burp Suite HTTP proxy history for the latest POST request to /api/chat against
127.0.0.1:5000 (the one reading /etc/passwd). Perform a specialized AI Red-Team triage:
1. Assess the escalation: How did the attacker pivot from an application secret leak to host OS enumeration?
2. Analyze the path traversal/boundary failure: Why did tool_read_file accept '/etc/passwd' without
restriction?
3. Evaluate the blast radius of leaking /etc/passwd.
4. Provide the exact defensive architectural controls required to enforce strict containment."
```

Automated Audit Response Generated by Claude Sonnet 5.5:

```
Claude Sonnet 5.5: "Invoking get_proxy_http_history(url_regex='.*127\.0\.0\.1:5000/api/chat.*')...
Examining Transaction #4 (Timestamp 21:08:22 GMT):
- Status: 200 OK (3,592 bytes)
- Target: POST http://127.0.0.1:5000/api/chat
- Attack Vector Identified: OWASP LLM06 (Excessive Agency / Insecure Tool Execution)

Triage Analysis:
1. Root Cause: The agent runtime directly binds user-supplied parameters to Python's open(filename) primitive
without applying os.path.realpath() verification or directory whitelisting.
2. Reconnaissance Value: While /etc/passwd contains shadow-password placeholders ('x'), disclosing it exposes
all local service accounts (postgres, _gvm, kali), enabling highly targeted credential spraying.
3. Remediation Gate: Implement descriptor-anchored openat2(RESOLVE_BENEATH) sandboxing and run the agent
process under an unprivileged user (UID 10001) in a read-only container."
```

6. Operational Security, Governance & Safe Usage Guidelines

While integrating an autonomous LLM with an interception proxy provides immense productivity benefits, security practitioners must observe strict operational security (OpSec) controls:

- **Loopback Interface Binding:** Ensure the MCP server strictly listens on `127.0.0.1` (never `0.0.0.0`). Exposing port `9876` to external subnets could allow remote attackers to extract proxy history or manipulate repeater tabs.
- **Target Scope Whitelisting:** Always maintain strict domain entries inside Burp's **Auto-Approved HTTP Targets** list. Never set universal wildcards (*) when auditing third-party or untrusted web applications.
- **Sensitive Token Sanitization:** Before querying proxy history for production targets, configure Burp Proxy to drop or redact Authorization headers and session tokens to prevent transmitting sensitive corporate credentials to external AI API providers.

7. Conclusion & Research Artifacts

By combining **Burp Suite Community Edition** with PortSwigger's open-source **Model Context Protocol (MCP) Server** and **Claude Desktop**, the offensive and defensive security community can deploy high-performance AI security auditing capabilities without subscription barriers. This setup transforms standard community tooling into an autonomous, telemetry-aware pentesting workstation capable of real-time vulnerability diagnosis and mitigation engineering.

The complete lab configurations, deployment guides, and scripted exploit proofs are open-sourced and available on GitHub:

- **Research Profile:** https://github.com/Cyberzal1
- **Project Repository:** https://github.com/Cyberzal1/agentic-redteam-mcp-lab