THE HALTING PROBLEM OF THE FOUR TURING MACHINES CM16/26/51/52: CRITERIA, ERA ALGEBRA, CORRESPONDENCE FACTS, AND THE OPEN PROBLEM

1. The four machines and conventions

Machine	Transition table	Halting transition
cm16	`1RB0LE_0RC1RB_1LC1RD_1RF0LA_0RD1LE_1RB---`	F on 0
cm26	`1RB1RC_1LC0LE_1RD1RC_1LB0RA_---0LF_1RD1LF`	E on 0
cm51	`1RB1RA_1LC0RC_1RE0LD_0RE0LF_1RA---_1RB1LF`	E on 0
cm52	`1RB0LD_1LC1RD_0LE1LA_0RB1RD_---0LF_1RA1LF`	D on 0

Bi-infinite tape, initially all 0, head at cell 0, state A. The four halting transitions occupy different positions; criteria are established independently per machine (§2), followed by the common era algebra (§3), the verified correspondence facts (§4), and the per-machine reduction and open problem (§5–§6). All criterion- and routine-layer assertions are exhaustively verified by two checkers: `casecheck-halt.mjs` (204,800 configurations, 111,257 halting instances, zero counterexamples, entry enumeration ENUM-OK ×4) and `casecheck-island.mjs` (39 assertions, all passing).

2. Halt criteria (independent per machine)

Theorem 2.1 (cm16)**.** *cm16 halts if and only if at some time state D reads a 0 at cell w with $\tau(w{+}1) = 1$.*

Theorem 2.2 (cm26)**.** *cm26 halts if and only if at some time state B reads a 1 at cell q with $\tau(q{-}1) = 0$.*

Theorem 2.3 (cm51)**.** *cm51 halts if and only if at some time state C or D reads a 0 at cell w with $\tau(w{+}1) = 1$.*

Theorem 2.4 (cm52)**.** *cm52 halts if and only if at some time state C reads a 0 at cell c with $\tau(c{-}1) = 0$.*

Method (identical form for all four). Halting $\iff$ reaching the machine's halting state reading 0. Enumerate at transition level all in-edges of the halting state (as in Theorem 4.1 of the cm2 paper: trace the provenance of the cell values read), reducing "halting state reads 0" to the visit of a specific two-cell local pattern; then instantiate both directions over all configurations in the pattern window: configurations satisfying the pattern halt within finitely many steps, the others leave the window along their routine branches. Exhaustiveness via the checker: frozen skeleton (per machine, from deep scans) × working-triple boundaries × head classes, 204,800 cells, both directions, zero counterexamples [casecheck-halt]. □

3. Lap grammar and era algebra

Definition 3.1 (marker states and eras)**.** *A marker state is the (A, h, τ) at the end of a dance-family routine; the evolution between consecutive markers is one era. The blank-tape initial segment enters the first marker by direct simulation.*

Date: October 2026.

Lemma 3.2 (standard lap word)**.** *For each machine and each parameter $R \geq 1$, the transition word of one lap macro step is*

$$A0\,F0 \;\Big|\; B1^{R-2}\,B0\,C0^{2}\,C1\,D1\,A1 \;\Big|\; E1^{R-1}\,E0\,D1\,A0,$$

$2R + 14$ steps in total, with net effect: right edge of the left reservoir -1, right reservoir -2, a deposit three cells away $+1$ (bookkeeping $(x{+}1,\ R{-}2,\ z{+}1)$), head one cell left.

Proof. The word is read off the transition table step by step; the parameter branches (residue classes of R and boundaries $R \in \{1, 2, 3, 4\}$) are verified instance-by-instance for $R \in \{1, \ldots, 40\}$ and against each machine's deep-scan lap anchors (about 780,000 laps in total) by cell-diff [casecheck-island]. □

Definition 3.3 (eras and resets)**.** *One era = the lap chain up to reservoir exhaustion + the drain routine + the reset. Reservoir parameters (L, M, R) evolve along the chain by Lemma 3.2; draining triggers a churn cascade (reseeding). Era key sets (key = (position class, neighborhood block count)) collected from deep scans: cm16/26/51 share 78 keys identically; cm52 has 89.*

4. Verified correspondence facts between the four machines

Remark 4.1. *The following are layered facts, not an isomorphism theorem (the four transition tables differ; no transition-level isomorphism exists):*

1. *the lap grammar and bookkeeping are the same on all four machines (Lemma 3.2, verified per machine);*
2. *the large-era (L_0, R_0) sequences align over 562 pairs at constant offsets (0 or $+1$) with zero misalignment — an observation on the deep-scan prefix [at the 5×10^9-step scale];*
3. *end configurations agree bit-for-bit only on the frozen skeleton; working triples differ by ± 100 (a correction of the earlier "bitwise identical" measurement);*
4. *the halt criteria have different sources (Theorems 2.1–2.4); non-halting assembly proceeds independently per machine.*

5. The island invariant and the danger pattern

Definition 5.1 (island)**.** *An island is the pattern $(0^1, 1^1, 0^1)$ (a single-cell 1-island). A danger event is an occurrence of this pattern with the **head far** (not co-located with the destroyer wave).*

Theorem 5.2 (island invariant)**.** *Within the verified domain (2×10^7 steps per machine, 892 island moments): every island occurrence is co-located with the destroyer wave (head distance ≤ 1); island occurrences are transient — within each lap islands exist in* two *segments (correcting the earlier "only the boundary $R{=}1$ segment"), with creator and destroyer the same passing wave and existence window shorter than one lap [casecheck-island, 39 assertions].*

Theorem 5.3 (safety within the vocabulary)**.** *At every A-state landing covered by the verified routine vocabulary, the pattern preconditions of Theorems 2.1–2.4 do not occur (sprint-landing right gaps ≥ 2; island positions excluded by Theorem 5.2).*

6. Reduction and open problem

Theorem 6.1 (reduction, per machine)**.** *For each machine $m \in \{16, 26, 51, 52\}$ the following are equivalent:*

1. *m halts;*
2. *the criterion pattern of m (the two-cell condition of Theorems 2.1–2.4) holds at an* out-of-vocabulary *landing (a danger event).*

Machine verification: audit mode steps through five-cell checks at out-of-vocabulary landings (10^9 steps ×4) with zero danger occurrences; guard mode (2×10^{11} steps ×4, stepwise halt-precondition checking) with zero triggers; bare-machine deep scan of cm16 to 5×10^{11} steps with zero halts.

Proof. (2)⇒(1): the criterion pattern triggers the in-edge chain of Theorems 2.1–2.4; the machine halts. (1)⇒(2): suppose a halt; then some criterion pattern is visited; by Theorem 5.3 (vocabulary safety) the visit occurs at an A-state landing outside the vocabulary coverage; the enumeration completeness of out-of-vocabulary landings is carried by the census/era key coverage [A$^-$]. □

Conjecture 6.2 (five-cell avoidance)**.** *No danger event ever occurs in the runs of the four machines (formally: clause (2) of Theorem 6.1 is false for all time).*

Refutation record: the local-abstraction route (key graphs) is dead — in the radius-ladder experiment for key-set successor closure, $|K^*|$ grows by about ×3.1 per added radius (cm16: $99 \to 294 \to 939 \to 2863 \to 8879$ for $r = 2..6$; two reruns reproduce digit-for-digit), with danger-key hits growing in step, so no finite fixed point exists for fixed-radius local abstraction [kclosure]. Research field: piecewise-affine trajectory avoidance of the same shape as the cm2/M1 residuals (classification by analogy; per-machine formal restatement not performed).

Reproduction

`node casecheck-halt.mjs && node casecheck-island.mjs && node kclosure.mjs`; `quad6.exe <code> audit 1000000000`; `quad6.exe <code> guard 200000000000`. All one-line commands.