

Forensic Write-Up

Distributed SSH Brute-Force, Unauthorized Access, XMRig/C3Pool Cryptojacking, and Post-Compromise Abuse

Host: `csb-internet`

Case focus:	SSH brute-force activity, successful authentication events, file deployment, XMRig/C3Pool cryptomining artifacts, persistence, wallet/pool correlation, and external corroboration.
Primary evidence:	Linux authentication and system logs, filesystem timestamps, miner configuration files, payload archive contents, shell scripts, malware hash review, wallet/pool screenshots, and public IP reputation screenshots provided by the user.
Date of report:	April 19, 2026

Analytical note. This report is based on host artifacts and screenshots supplied by the user. Where an exact transfer command or complete terminal history was not recovered, the report states that limitation explicitly. Attribution to a specific real-world actor is not claimed; instead, the report focuses on observable evidence and defensible forensic conclusions.

Contents

1	Executive Summary	4
2	Scope, Methodology, and Evidence Sources	5
2.1	Scope	5
2.2	Methodology	5
2.3	Important Limitation	6
3	Host Context and High-Level Findings	7
3.1	Observed Themes	7
3.2	Core Conclusion	7
4	Detailed Findings	8
4.1	Distributed SSH Brute-Force and Password Spraying	8
4.2	Successful Authentication from Public IP Addresses	8
4.3	Post-Authentication Account Abuse	9
4.4	Miner Payload Deployment and File Artifacts	9
4.5	Suspicious Persistence under <code>jenkins</code>	9
4.6	Recovered Miner Execution Logic	10
4.7	Pool and Wallet Configuration	10
4.8	Malware Hash and External Corroboration	11
5	Consolidated Timeline	12
6	Indicators of Compromise	13
6.1	Network and Identity Indicators	13
6.2	File and Host Indicators	13
7	MITRE ATT&CK-Oriented Interpretation	14
8	Conclusion and Recommended Actions	15

8.1 Conclusion	15
8.2 Immediate Incident Response Recommendations	15
A Selected Log and Artifact Excerpts	17
B Investigation Commands Used to Derive Evidence	19
C Screenshot Evidence	21

List of Figures

C.1	VirusTotal screenshot provided by the user showing the recovered miner sample hash flagged by multiple engines with miner-related detections.	22
C.2	Community screenshot provided by the user showing additional discussion and references for the same sample hash.	22
C.3	Social-media screenshot provided by the user that associates the recovered XMR wallet with <code>c3pool</code> . This is corroborative evidence, not definitive actor attribution.	23
C.4	C3Pool dashboard screenshot provided by the user showing activity for the same XMR wallet recovered from the malware configuration.	23
C.5	IP2Location screenshot provided by the user for public IP <code>196.251.70.231</code>	24
C.6	AbuseIPDB screenshot provided by the user for public IP <code>196.251.70.231</code> , showing repeated abuse reporting.	24
C.7	AbuseIPDB summary screenshot provided by the user for public IP <code>196.251.117.207</code> .	25
C.8	AbuseIPDB detail screenshot provided by the user for public IP <code>196.251.117.207</code> .	25
C.9	AbuseIPDB screenshot provided by the user for public IP <code>5.228.54.184</code> , showing SSH brute-force and scanning reports.	26
C.10	AbuseIPDB screenshot provided by the user for public IP <code>46.101.9.55</code> , showing a very high abuse confidence in the user-provided screenshot.	26

1 Executive Summary

The evidence supports a high-confidence conclusion that host `csb-internet` suffered a compromise that progressed from distributed SSH brute-force and credential abuse to the deployment of an unauthorized XMRig-based Monero mining toolkit configured for C3Pool. The investigation also identified persistence artifacts, account abuse, password changes, privilege escalation, and signs that the host may have been used as a pivot or scanning node after compromise.

The strongest internal artifacts are the payload archive `/home/ubuntu/miner.zip`, its later materialization into multiple `c3pool` directories under both `ubuntu` and `jenkins`, a miner wrapper script that launches `/home/ubuntu/c3pool/xmrig`, and a background configuration that points to `auto.c3pool.org:80` with a specific XMR wallet and a host tag of `csb-internet`. The payload was not isolated to a single user profile; suspicious persistence artifacts were also present under `/home/jenkins/.ecs-92d9/`, including `update`, `autorun`, and multiple executables.

The compromise narrative is additionally reinforced by external corroboration. The recovered `xmrig` binary hash was detected by VirusTotal as malicious with miner-related labels, the XMR wallet found inside the malware configuration matched a social-media report referencing `c3pool`, and the corresponding C3Pool dashboard screenshot showed activity associated with that same wallet. Public IP addresses that successfully authenticated to the host also showed elevated abuse indicators in the screenshots provided by the user.

2 Scope, Methodology, and Evidence Sources

2.1 Scope

This report covers the following investigative questions:

1. Was the host subjected to SSH brute-force or password spraying?
2. Did any public IP addresses successfully authenticate after brute-force activity?
3. What post-authentication actions were performed on the host?
4. Was malware or a miner payload transferred to the system?
5. How was the miner configured, and which wallet and pool were used?
6. Is there evidence of persistence or multi-account deployment?
7. Do external screenshots corroborate the host evidence?

2.2 Methodology

The write-up was built from user-supplied terminal output and screenshots. The investigation followed a host-centric workflow:

- authentication log review to identify brute-force patterns, successful logins, and session timing;
- account management review to identify user creation, password changes, and privilege changes;
- filesystem review to identify new or modified files around the compromise windows;
- artifact inspection of `miner.zip`, `miner.sh`, and `config_background.json`;
- correlation of internal host artifacts with VirusTotal, wallet screenshots, C3Pool dashboard evidence, and IP reputation screenshots.

2.3 Important Limitation

The exact command used to transfer `miner.zip` onto the host was not recovered from the available system logs. No direct `curl`, `wget`, or unambiguous `scp/sftp` transfer record was recovered in the narrowed log windows. Nevertheless, the presence of `miner.zip` on disk, the subsequent `c3pool` deployment, and the later miner configuration provide strong evidence that file transfer and installation occurred.

3 Host Context and High-Level Findings

3.1 Observed Themes

Five themes recur throughout the evidence:

1. **Distributed SSH attack pressure.** Multiple public IP addresses repeatedly attempted SSH authentication, especially against `root`.
2. **Successful public logins.** Several public IP addresses successfully authenticated to accounts including `ubuntu`, `jenkins`, `admin`, and `root`.
3. **Post-compromise account abuse.** The host showed account creation, password changes, and privilege changes.
4. **Cryptomining payload deployment.** A miner archive was recovered from disk and later deployed under more than one user account.
5. **Pool and wallet correlation.** Internal configuration, malware hash results, a social-media wallet report, and a pool dashboard all aligned around the same XMR wallet and C3Pool usage.

3.2 Core Conclusion

Based on the evidence reviewed, the most defensible conclusion is that `csb-internet` was compromised and used for unauthorized Monero mining via XMRig and C3Pool, with evidence of persistence and post-compromise privilege abuse.

4 Detailed Findings

4.1 Distributed SSH Brute-Force and Password Spraying

The logs show repeated distributed SSH activity from many public IP addresses. The most visible repeated attackers in the recovered excerpts include 47.239.90.224 and 8.222.230.39, which generated repeated failed password attempts against `root`. In parallel, the host generated many `sshd ... error: connect_to ... failed` messages to external addresses and alternative SSH ports, a pattern that is inconsistent with ordinary inbound login noise and is more consistent with pivoting or scanning through an active SSH context.

An important analytical nuance is that the host did not merely receive failed login attempts. Successful logins occurred amidst the failed traffic, which strongly suggests that at least some credentials were compromised or reused successfully by remote operators.

4.2 Successful Authentication from Public IP Addresses

The evidence contains multiple successful SSH logins from public IP addresses. Representative examples include:

- 83.222.191.18 successfully authenticated to `ubuntu` and `jenkins` multiple times on 2025-05-07, and later again to `ubuntu` on 2025-05-10.
- 196.251.117.207 successfully authenticated to `ubuntu` on 2025-05-07, and later correlated closely with a successful `admin` session that was followed by an `admin` password change.
- 196.251.70.231 successfully authenticated to `root` on 2025-05-15, and that session was followed within seconds by a successful `root` password change.
- 185.53.197.29 successfully authenticated to `ubuntu` shortly after the `miner.zip` artifact appeared on disk on 2025-05-08.
- Earlier successful `jenkins` logins were also recorded from 5.228.54.184 and 46.101.9.55.

These sessions are analytically significant because they bridge the gap between opportunistic scanning and actual host access.

4.3 Post-Authentication Account Abuse

After successful access, the host showed signs of account manipulation and privilege abuse:

- `viewer` was created as a new user on 2025-05-09 and assigned a home directory.
- `jenkins` was added to the `csb` group.
- `admin` executed `usermod -aG docker admin`, after which the logs confirmed that `admin` was added to the `docker` group.
- Password changes were recorded for `ubuntu`, `jenkins`, `root`, and `admin`.

Adding `admin` to the `docker` group is particularly important because, in practice, membership in `docker` can be close to root-equivalent on Linux hosts.

4.4 Miner Payload Deployment and File Artifacts

The filesystem evidence is particularly strong. The investigation recovered a 9.5 MB archive at:

```
/home/ubuntu/miner.zip
```

The file timestamp placed it on disk on 2025-05-08 06:13:55 UTC. The archive contents include `miner.sh`, `lib/sminer`, and numerous hidden support files and directories, which is consistent with a packaged cryptomining toolkit rather than a benign archive.

Later artifacts show that the payload was materialized into a working `c3pool` structure for `ubuntu`:

```
/home/ubuntu/c3pool/config.json  
/home/ubuntu/c3pool/config_background.json  
/home/ubuntu/c3pool/miner.sh
```

The same miner structure also appeared under `jenkins`:

```
/home/jenkins/c3pool/config.json  
/home/jenkins/c3pool/config_background.json  
/home/jenkins/c3pool/miner.sh
```

This indicates that the miner was not left in a single user profile; it was propagated or reinstalled under another account, increasing resilience and persistence.

4.5 Suspicious Persistence under `jenkins`

Another strong finding is the hidden directory:

```
/home/jenkins/.ecs-92d9/
```

This directory contained multiple suspicious components, including:

- `update` (POSIX shell script),
- `autorun` (POSIX shell script),
- `run`, `run32`, `run64`,
- `h32`, `h64`,
- `cfg`, `dir`, `cron`, and `pid`.

The file set and naming scheme strongly suggest a persistence or update bundle. Although the exact family for this bundle was not independently identified from the available evidence, its coexistence with the miner deployment under `jenkins` materially increases confidence in post-compromise persistence.

4.6 Recovered Miner Execution Logic

The recovered `miner.sh` wrapper script is concise but informative. Its logic checks whether `xmrig` is already running and, if not, launches:

```
/home/ubuntu/c3pool/xmrig
```

The script uses `nice` to execute the binary and refuses to start a second instance if an existing miner process is detected. This behavior is operationally consistent with a miner deployment intended to remain stable in the background.

4.7 Pool and Wallet Configuration

The strongest configuration-level evidence comes from `config_background.json`. The recovered file shows the following operational parameters:

- pool URL: `auto.c3pool.org:80`
- wallet: `4B7vD4PrcGdES1grKPBH5jbsh4SgknSzkFFRHxWMqux7bJrieQoawCiFnd36wKTPtAUXJLeQBZWKRKza7qJaQscx2kCCrZo`
- password / rig tag: `csb-internet`
- log file: `/home/ubuntu/c3pool/xmrig.log`
- background mode: `enabled`

These settings are not generic placeholders; they show a real wallet, a real pool, and a host-specific string in the pool password field.

4.8 Malware Hash and External Corroboration

The `xmrig` binary recovered on the host had SHA-256:

```
e00e9f9d8d3ea668fbc88ed25a9eeffb5b9d8d86a993ff78482500e99ae64351e
```

According to the user-provided VirusTotal screenshot, this sample was flagged by many engines and associated with miner-related detections. A community screenshot provided by the user also showed discussion and links for the same sample hash.

Separately, the user supplied a social-media screenshot that displayed the same XMR wallet and identified the pool as `c3pool`. Finally, the user supplied a C3Pool dashboard screenshot for that same wallet, showing live pool information and mining-related records. These screenshots do not establish a specific real-world identity for the attacker, but they do strongly corroborate the host configuration and the conclusion that the wallet was genuinely used in C3Pool activity.

5 Consolidated Timeline

Time (UTC)	Event Type	Forensic Interpretation
2025-05-07 12:04	Successful login	<code>jenkins</code> authenticated from 5.228.54.184 and 46.101.9.55, indicating that successful public access occurred before later payload deployment.
2025-05-07 13:02–13:14	Brute-force + successful access	Repeated <code>root</code> brute-force from 47.239.90.224 occurred alongside successful <code>ubuntu/jenkins</code> logins from 83.222.191.18 and successful <code>ubuntu</code> access from 196.251.117.207.
2025-05-08 06:13:55	File deployment	<code>/home/ubuntu/miner.zip</code> appeared on disk under user <code>ubuntu</code> .
2025-05-08 06:17:57	Successful login	<code>ubuntu</code> authenticated successfully from 185.53.197.29.
2025-05-09 02:27	Account creation	<code>viewer</code> account created and provisioned.
2025-05-10 12:41	Successful login + suspicious outbound errors	<code>ubuntu</code> authenticated again from 83.222.191.18 while <code>sshd</code> also emitted numerous outbound <code>connect_to</code> failures, suggesting host misuse beyond simple inbound attacks.
2025-05-10 23:52	Miner deployment milestone	<code>/home/ubuntu/c3pool/miner.sh</code> was present, indicating that the miner had been deployed or staged in the <code>c3pool</code> directory.
2025-05-13 22:16	Password change	<code>jenkins</code> password changed.
2025-05-14 00:48–00:57	Persistence and multi-account miner deployment	<code>/home/jenkins/.ecs-92d9/</code> artifacts and <code>/home/jenkins/c3pool/</code> configuration files appeared.
2025-05-14 07:09	Privilege abuse	After a successful <code>admin</code> session, <code>admin</code> was added to the <code>docker</code> group.
2025-05-15 07:17–07:18	Root-level compromise marker	Successful <code>root</code> login from 196.251.70.231 was followed almost immediately by <code>password changed for root</code> .
2025-05-15 13:01	Admin credential abuse	Successful <code>admin</code> login from 196.251.117.207 was followed by <code>password changed for admin</code> .

6 Indicators of Compromise

6.1 Network and Identity Indicators

Indicator	Value / Notes
Host	csb-internet
Pool URL	auto.c3pool.org:80
Wallet	4B7vD4PrGdES1grKPBH5jbsh4SgknSzkFFRHxWMqux7bJrieQoawCiFnd36wKTPtAUXJLeQBZWKRKza7qJaQscx2kCCrZo
Pool password / tag	csb-internet
Successful public IPs of interest	83.222.191.18, 196.251.117.207, 196.251.70.231, 185.53.197.29, 5.228.54.184, 46.101.9.55
Suspicious outbound behavior	sshd ... error: connect_to ... failed to many SSH-related ports; later also SMTP-related ports in other excerpts

6.2 File and Host Indicators

Indicator	Value / Notes
Archive	/home/ubuntu/miner.zip
Ubuntu miner path	/home/ubuntu/c3pool/
Jenkins miner path	/home/jenkins/c3pool/
Persistence bundle	/home/jenkins/.ecs-92d9/
Binary hash sha256	e00e9f9d8d3ea668fbc88ed25a9eefb5b9d8d86a993ff78482500e99ae64351e
Scripts	miner.sh, update, autorun, run
Configuration files	config.json, config_background.json, .cfg, .pools

7 MITRE ATT&CK-Oriented Interpretation

The observed evidence maps naturally to several ATT&CK ideas:

- **T1110 – Brute Force:** repeated SSH password attacks against `root` and other accounts.
- **T1078 – Valid Accounts:** successful SSH authentication to `ubuntu`, `jenkins`, `admin`, and `root`.
- **T1098 – Account Manipulation:** creation of `viewer`, password changes, and group modifications.
- **T1068 / Privilege escalation by administrative misuse:** addition of `admin` to the `docker` group and later root-level changes.
- **T1053 – Scheduled Task / Job:** cron-linked persistence indicators and repeated scheduled activity.
- **T1105 – Ingress Tool Transfer:** the host received `miner.zip`, although the exact transfer command was not recovered.
- **T1496 – Resource Hijacking:** unauthorized use of host resources for Monero mining.

8 Conclusion and Recommended Actions

8.1 Conclusion

The evidence supports a high-confidence finding that the host was used for unauthorized Monero mining via XMRig and C3Pool after successful SSH access from suspicious public IP addresses. The compromise progressed beyond mere login abuse: it included account changes, persistence artifacts, multi-account deployment of the miner toolkit, and password changes for privileged users.

The most important evidentiary chain is:

1. repeated distributed SSH brute-force and password spraying;
2. successful public logins to multiple accounts;
3. appearance of `/home/ubuntu/miner.zip`;
4. later deployment of working `c3pool` structures under `ubuntu` and `jenkins`;
5. recovery of a miner wrapper script that launches `xmrig`;
6. recovery of `config_background.json` pointing to `auto.c3pool.org:80` with a concrete XMR wallet and `csb-internet` tag;
7. external corroboration from VirusTotal, wallet screenshots, and the C3Pool dashboard.

8.2 Immediate Incident Response Recommendations

- isolate or rebuild the host rather than attempting piecemeal cleanup;
- rotate all credentials associated with `ubuntu`, `jenkins`, `admin`, `root`, and any SSH keys created after the compromise window;
- remove unauthorized users and group memberships, especially `viewer` and any unexpected `docker` membership;
- preserve the payload archive, miner binaries, and hidden persistence directories as evidence;
- review cron jobs, systemd units, `authorized_keys`, and all startup locations for residual persistence;

- review outbound network activity and pool traffic for other affected hosts or reused wallets.

A Selected Log and Artifact Excerpts

A.1 Successful access and concurrent brute-force

```
2025-05-07T13:02:27 Failed password for root from 47.239.90.224
2025-05-07T13:02:37 Accepted password for ubuntu from 83.222.191.18
2025-05-07T13:04:29 Accepted password for jenkins from 83.222.191.18
2025-05-07T13:14:15 Accepted password for ubuntu from 196.251.117.207
```

A.2 Miner archive and deployment artifacts

```
2025-05-08 06:13:55 /home/ubuntu/miner.zip
2025-05-10 23:52:21 /home/ubuntu/c3pool/miner.sh
2025-05-14 00:48:24 /home/jenkins/c3pool/config.json
2025-05-14 00:48:24 /home/jenkins/c3pool/miner.sh
2025-05-14 00:57:23 /home/jenkins/c3pool/config_background.json
```

A.3 Privilege abuse and password changes

```
2025-05-14T07:09:53 sudo: admin ... COMMAND=/usr/sbin/usermod -aG docker admin
2025-05-14T07:09:54 usermod: add 'admin' to group 'docker'
2025-05-15T07:18:13 passwd: password changed for root
2025-05-15T13:01:46 passwd: password changed for admin
```

A.4 Recovered miner launcher

```
#!/bin/bash
if ! pidof xmrig >/dev/null; then
    nice /home/ubuntu/c3pool/xmrig $*
else
    echo "Monero miner is already running in the background."
fi
```

A.5 Recovered configuration summary

```
"log-file": "/home/ubuntu/c3pool/xmrig.log",
"pools": [{
  "url": "auto.c3pool.org:80",
  "user": "4B7vD4PrcGdES1grKPBH5jbsh4SgknSzkFFRHxWMqux7bJrieQoawCiFnd",
  " 36wKTPtAUXJLeQBZWKRKza7qJaQscx2kCCrZo",
  "pass": "csb-internet"
}]
```

B Investigation Commands Used to Derive Evidence

This appendix records the principal shell commands used during the investigation to identify brute-force activity, successful authentication, file deployment, miner configuration, and persistence. The commands below reflect the investigative workflow used by the user to derive the evidence discussed in this report.

B.1 Review successful SSH authentication and session openings

```
sudo zgrep -hEi 'Accepted password|Accepted publickey|session opened for user admin|session
opened for user ubuntu|session opened for user root' auth.log*

sudo zgrep -hEi 'Accepted|session opened|sudo:' auth.log* | grep '2025-05-14T07:0'
sudo zgrep -hEi 'Accepted|session opened|sudo:' auth.log* | grep '2025-05-15T07:1'
sudo zgrep -hEi 'Accepted|session opened|sudo:' auth.log* | grep '2025-05-15T13:0'
```

B.2 Narrow timeline windows around compromise events

```
sudo zgrep -ahE '2025-05-07T13:0|2025-05-07T13:1|2025-05-09T02:2|2025-05-14T07:0|2025-05-15T07
:1|2025-05-15T13:0' \
auth.log* syslog* kern.log* cloud-init.log* cloud-init-output.log* \
| grep -Ei 'sshd|sudo|su:|passwd|chpasswd|useradd|adduser|usermod|groupadd|gpasswd|curl|wget|
scp|sftp|ftp|rsync|git|python|perl|bash -c|sh -c|base64|openssl|chmod|chattr|nohup|screen|
tmux|crontab|CRON|systemd|service|xmrig|c3pool|tcron'

sudo zgrep -ahE '2025-05-08T06:1[23]|2025-05-08T06:14|2025-05-08T06:15' auth.log* syslog* \
| grep -Ei 'Accepted|session opened|subsystem|sftp|scp|sshd'
```

B.3 Search shell history for miner- and transfer-related commands

```
sudo grep -RHiE 'curl|wget|scp|sftp|ftp|rsync|git clone|python|perl|bash -c|sh -c|base64|
openssl|chmod \+x|nohup|screen|tmux|systemctl|service|crontab|docker|xmrig|c3pool|tcron' \
/root/.bash_history /home/*/.bash_history 2>/dev/null
```

B.4 Locate artifact files created during the compromise window

```
sudo find /tmp /var/tmp /dev/shm /run /opt /home /root \  
-type f -newermt '2025-05-07 13:00:00' ! -newermt '2025-05-15 13:10:00' \  
-printf '%TY-%Tm-%Td %TT %u %g %m %p\n' 2>/dev/null | sort  
  
sudo find /home/ubuntu /home/jenkins -maxdepth 3 -type f \( -name "miner.zip" -o -name "miner.  
sh" -o -name "config*.json" -o -path "*/.ecs-92d9/*" \) -exec ls -lah {} \; -exec file {} \  
\;
```

B.5 Inspect recovered payloads and miner configuration

```
sudo unzip -l /home/ubuntu/miner.zip  
sudo cat /home/ubuntu/c3pool/miner.sh  
sudo cat /home/ubuntu/c3pool/config_background.json  
sha256sum /home/ubuntu/c3pool/xmrig
```

B.6 Representative pivots used after artifact discovery

```
ps aux | grep xmrig  
pidof xmrig  
systemctl status xmrig  
crontab -l  
crontab -u ubuntu -l  
grep -rn "xmrig" /  
grep -rn "xmrig" /var/log/syslog
```

C Screenshot Evidence




Figure C.1: VirusTotal screenshot provided by the user showing the recovered miner sample hash flagged by multiple engines with miner-related detections.




Figure C.2: Community screenshot provided by the user showing additional discussion and references for the same sample hash.




Figure C.3: Social-media screenshot provided by the user that associates the recovered XMR wallet with c3pool. This is corroborative evidence, not definitive actor attribution.




Figure C.4: C3Pool dashboard screenshot provided by the user showing activity for the same XMR wallet recovered from the malware configuration.

The screenshot displays the IP2Location website interface. The top navigation bar includes links for Home, Solutions, Products, Pricing, Resources, Log In, and a shopping cart icon. The main content area is divided into two sections: Geolocation Data and Proxy Data.

Geolocation Data
The geolocation data uses IP2Location DB26 geolocation database.

Permalink	https://www.ip2location.com/196.251.70.231
IP Address	196.251.70.231
Country	Netherlands (Kingdom of the) [NL]
Region	Noord-Holland
City	Amsterdam
Coordinates of City	52.378500, 4.899980 (52°22'43"N 4°53'60"E)
ISP	Internet Security Cheapyhost
Local Time	19 Apr, 2026 06:23 AM (UTC +02:00)
Domain	cheapy.host
Net Speed	(T1) Data Center/Transit
IDD & Area Code	(31) 020
ZIP Code	1000
Weather Station	Amsterdam (NLXX0002)

Proxy Data
The proxy data uses IP2Proxy PX12 proxy database.

IP Address	196.251.70.231
Anonymous Proxy	No
Proxy Country	Netherlands (Kingdom of the) [NL]
Proxy Region	Noord-Holland
Proxy City	Amsterdam
Proxy ISP	Internet Security Cheapyhost
Proxy Domain	cheapy.host
Proxy Usage Type	(DCH) Data Center/Web Hosting/Transit
Proxy Type	DCH
Proxy ASN	-
Threat	-
Last Seen	-

Figure C.5: IP2Location screenshot provided by the user for public IP 196.251.70.231.

The screenshot displays the AbuseIPDB website interface. The top navigation bar includes links for Report IP, Bulk Checker, Bulk Reporter, Pricing, Integrations, Docs, IP Utilities, Contact, and More. The main content area shows the City (Amsterdam, North Holland) and a summary of IP abuse reports for the IP 196.251.70.231.

IP Abuse Reports for 196.251.70.231:

This IP address has been reported a total of **3,665** times from 106 distinct sources. 196.251.70.231 was first reported on April 16th 2025, and the most recent report was **6 months ago**.
Old Reports: The most recent abuse report for this IP address is from **6 months ago**. It is possible that this IP is no longer involved in abusive activities.

Reporter	IoA Timestamp (UTC)	Comment	Categories
✓ Anonymous	2025-10-07 16:30:50 (6 months ago)	Failed login attempt detected by Fail2Ban in ssh jail	Brute-Force
+ nNordic	2025-08-26 18:00:41 (7 months ago)	Connection attempt blocked by IDS/IPS from IP 196.25 1.70.231/32	Hacking
+ nNordic	2025-08-26 05:29:51 (7 months ago)	Connection attempt blocked by IDS/IPS from IP 196.25 1.70.231/32	Hacking
+ nNordic	2025-08-25 07:02:13 (7 months ago)	Connection attempt blocked by IDS/IPS from IP 196.25 1.70.231/32	Hacking
+ nNordic	2025-08-24 18:49:03 (7 months ago)	Connection attempt blocked by IDS/IPS from IP 196.25 1.70.231/32	Hacking
+ nNordic	2025-08-24 14:27:19	Connection attempt blocked by IDS/IPS from IP 196.25	Hacking

Figure C.6: AbuseIPDB screenshot provided by the user for public IP 196.251.70.231, showing repeated abuse reporting.




Figure C.7: AbuseIPDB summary screenshot provided by the user for public IP 196.251.117.207.




Figure C.8: AbuseIPDB detail screenshot provided by the user for public IP 196.251.117.207.

The screenshot shows the AbuseIPDB interface for IP 5.228.54.184. The header indicates 'IP Abuse Reports for 5.228.54.184:'. Below this, a summary states: 'This IP address has been reported a total of 1,910 times from 304 distinct sources. 5.228.54.184 was first reported on March 27th 2025, and the most recent report was 8 months ago. Old Reports: The most recent abuse report for this IP address is from 8 months ago. It is possible that this IP is no longer involved in abusive activities.'

Reporter	IoA Timestamp (UTC)	Comment	Categories
bigscouts.com	2025-08-10 03:56:37 (8 months ago)	5.228.54.184 (RU/Russia/broadband-5-228-54-184.ip.moscow.ru.ru), 5 distributed sshd attacks on accou ...	Brute-Force, SSH
jetron	2025-08-06 07:54:00 (8 months ago)	unauthorized login attempt @ mailgarant.jetron.com	Brute-Force
SirHiltonBradley	2025-08-02 17:17:21 (8 months ago)	2025-07-04T04:09:09.653907-07:00 dc sshd[1371503]: Invalid user web from 5.228.54.184 port 59880 202 ...	Hacking, Brute-Force, SSH
rtbh.com.tr	2025-07-29 20:07:56 (8 months ago)	list.rtbh.com.tr report: tcp/0	Brute-Force
Parth Maniar	2025-07-29 17:52:38 (8 months ago)	This IP address carried out 17 port scanning attempts on 28-07-2025. For more information or to repo ...	Port Scan, SSH
Parth Maniar	2025-07-29 10:04:40 (8 months ago)	This IP address carried out 4 SSH credential attack (attempts) on 28-07-2025. For more information o ...	Brute-Force, SSH
ThreatBook.io	2025-07-28 22:45:12 (8 months ago)	ThreatBook Intelligence: Zombie,Dynamic IP more details on https://threatbook.io/ip/5.228.54.184	SSH

Figure C.9: AbuseIPDB screenshot provided by the user for public IP 5.228.54.184, showing SSH brute-force and scanning reports.

The screenshot shows the AbuseIPDB interface for IP 46.101.9.55. The header indicates 'AbuseIPDB » 46.101.9.55'. Below this, a search bar contains the IP address and a 'CHECK' button. The main content area displays: '46.101.9.55 was found in our database! This IP was reported 6,857 times. Confidence of Abuse is 100%:'. A red progress bar shows 100% confidence.

ISP	DigitalOcean, LLC
Usage Type	Data Center/Web Hosting/Transit
ASN	AS14061
Domain Name	digitalocean.com
Country	United Kingdom of Great Britain and Northern Ireland
City	London, England

IP info including ISP, Usage Type, and Location provided by IPInfo. Updated weekly.

Figure C.10: AbuseIPDB screenshot provided by the user for public IP 46.101.9.55, showing a very high abuse confidence in the user-provided screenshot.