

PLATINUM Inverter 13000 TL, 16000 TL, 19000 TL, 22000 TL

Technical Data

14 Technical Data

Input characteristics	13000 TL	16000 TL	19000 TL	22000 TL
Maximum PV power	14,700 Wp	18,000 Wp	21,300 Wp	24,300 Wp
Maximum DC power	12,900 W	15,900 W	18,900 W	21,600 W
PV-voltage range, MPPT	351 – 710 V	349 – 710 V	350 – 710 V	351 – 710 V
Maximum DC voltage	880 V			
Maximum input current	3 x 13.0 A	3 x 16.0 A	3 x 18.5 A	3 x 21.0 A
Number of string inputs	6	6	9	9
Number of MPP trackers	3			
DC section switch device	DC disconnect, integrated in the appliance			
Reverse battery protection	yes			
Output characteristics				
Nominal AC power rating	11,250 W	13,800 W	16,550 W	18,900 W
Nominal AC-intensity	3 x 16.3 A	3 x 20.0 A	3 x 23.9 A	3 x 27.4 A
Maximum AC power	12,360 W	15,000 W	18,000 W	20,700 W
Maximum AC intensity	3 x 17.9 A	3 x 21.7 A	3 x 26.1 A	3 x 30.0 A
Feed operation starts at	7 W	7 W	7 W	8 W
Mains output voltage range	3 x 230 V (+/-20%) feeding on three phases			
Internal consumption at night	below 6 W			
Mains frequency	47.5 Hz – 52.2 Hz			
Short-circuit proof	yes			
Interfaces				
DC input	DC plug, Multicontact MC3, MC4, Tyco			
AC output	Spring clamp connectors			
PLATINUM network	EIA 485, 2x RJ45 Western Modular add. plug connector with terminal screws			
Service interface	EIA 232, SubD 9-pole socket			
Potential-free contact	Change-over contact, maximum 24 V _{AC} /2 A, plug connector with terminal screws			
Appliance data				
Maximum degree of efficiency	97.3%	97.4%	97.7%	98.0%
European efficiency	96.8%	96.8%	97.3%	97.6%
Weight	81 kg	84 kg	87 kg	87 kg

PLATINUM Inverter 13000 TL, 16000 TL, 19000 TL, 22000 TL

Technical Data

Input characteristics	13000 TL	16000 TL	19000 TL	22000 TL
Dimensions	H 743 mm x W 972 mm x D 262 mm			
Working temperature range	-20 °C to +60 °C			
Maximum temperature during nominal power	+45 °C			
Storage temperature	-20 °C to +80 °C			
Maximum air humidity	95%			
Degree of protection (except digital interface)	IP65 according to DIN EN 60529			
Optical display	Full graphic 170 x 76 pixels			
Integrated datalogger	Storage capacity sufficient for 30 yrs operating time			
Circuit concept	Transformerless, DIVE, RAC-MPP, ENS according to VDE 0126-1-1			

Technical data apply to maximum height above MSL of 2,000 m.

Note