[Number System] 2's Comp. conversion

Positive Numbers
- Comp = original (补码=原码)
- Original = comp (原码=补码)

Negative Numbers
- **Comp = reverse(abs(original)) + 1** (补码=正数的反码+1)
- **Original = -reverse(comp-1)** (原码=补码-1/反转/再加负号)

Negative Numbers
1. 统一加减法：减法可以转换为加法来处理。
2. 简化溢出处理：正负溢出方式相同，简化溢出的检测逻辑。
3. 避免两个零：假若不用补码，则 0000_2, 1000_2 都代表 0

Overflow detection
- Positive + Positive = Negative
- Negative + Negative = Positive

Multiplication

1. Left-shift multiplicand B
2. Right shift multiplier Q (so each time we can take Q[0])
3. A (product) = A + B * Q[0]

Floating Point Notation

- Significand: Normalized to start with 1 ($\pm 1.bbbb \dots b \times 2^E$)
- **Bias = 2^(k-1),** k is the number of bits of the "biased exponent"
- Bias Exponent: **Biased exponent $= E + bias$**

Decimal Fraction -> Binary Float Point:

$-29.21875 \rightarrow$ 32-bit IEEE floating-point

$(29)_{10} = 2 \cdot 14 \dots\dots 1$
$14 = 2 \cdot 7 \dots\dots 0$ $0.21875 \times 2 = 0.4375\ (0)$
$7 = 2 \cdot 3 \dots\dots 1$ $0.4375 \times 2 = 0.875\ (0)$
$3 = 2 \cdot 1 \dots\dots 1$ $0.875 \times 2 = 1.75\ (1)$
$1 = 2 \cdot 0 \dots\dots 1$ $0.75 \times 2 = 1.5\ (1)$
$= (11101)_2$ $0.5 \times 2 = 1.0\ (1)$

Therefore $-29.21875 = -11101.0011 = -1.11010011 \times 2^4$

Normalize: -1.11010011×2^4

Bias exponent: $4 + (2^{5-1}) = (19)_{10} = (10011)_2$

IEEE Floating Point Representation:

IEEE Float Point = 1 01111111 11010011000000000000000

MIPS

	Instruction	RTL	Notes
00	sll $rd, $rt, shamt	R[$rd] ← R[$rt] << shamt	
02	srl $rd, $rt, shamt	R[$rd] ← R[$rt] >> shamt	Unsigned right shift
03	sra $rd, $rt, shamt	R[$rd] ← R[$rt] >> shamt	Signed right shift
04	sllv $rd, $rt, $rs	R[$rd] ← R[$rt] << R[$rs]	
06	srlv $rd, $rt, $rs	R[$rd] ← R[$rt] >> R[$rs]	Unsigned right shift
07	srav $rd, $rt, $rs	R[$rd] ← R[$rt] >> R[$rs]	Signed right shift
08	jr $rs	PC ← R[$rs]	R[$rs] must be a multiple of 4
09	jalr $rd, $rs	tmp ← R[$rs] R[$rd] ← PC + 8 PC ← tmp	R[$rs] must be a multiple of 4;
09	jalr $rs	(special form of "jalr $rd, $rs" where $rd = 31, implicitly)	
12	syscall	System Call	
16	mfhi $rd	R[$rd] ← HI	
17	mthi $rs	HI ← R[$rs]	
18	mflo $rd	R[$rd] ← LO	
19	mtlo $rs	LO ← R[$rs]	
24	mult $rs, $rt	{HI, LO} ← R[$rs] * R[$rt]	Signed multiplication
25	multu $rs, $rt	{HI, LO} ← R[$rs] * R[$rt]	Unsigned multiplication
26	div $rs, $rt	LO ← R[$rs] / R[$rt] HI ← R[$rs] % R[$rt]	Signed division
27	divu $rs, $rt	LO ← R[$rs] / R[$rt] HI ← R[$rs] % R[$rt]	Unsigned division
32	add $rd, $rs, $rt	R[$rd] ← R[$rs] + R[$rt]	Exception on signed overflow
33	addu $rd, $rs, $rt	R[$rd] ← R[$rs] + R[$rt]	
34	sub $rd, $rs, $rt	R[$rd] ← R[$rs] − R[$rt]	Exception on signed overflow
35	subu $rd, $rs, $rt	R[$rd] ← R[$rs] − R[$rt]	
36	and $rd, $rs, $rt	R[$rd] ← R[$rs] & R[$rt]	
37	or $rd, $rs, $rt	R[$rd] ← R[$rs]	R[$rt]	
38	xor $rd, $rs, $rt	R[$rd] ← R[$rs] ^ R[$rt]	
39	nor $rd, $rs, $rt	R[$rd] ← !(R[$rs] | R[$rt])	
42	slt $rd, $rs, $rt	R[$rd] ← R[$rs] < R[$rt]	Signed comparison
43	sltu $rd, $rs, $rt	R[$rd] ← R[$rs] < R[$rt]	Unsigned comparison

---

Type	31 26	25 21	20 16	15 11	10 06	05 00
R–Type	opcode	$rs	$rt	$rd	shamt	funct
I–Type	opcode	$rs	$rt	imm		
J–Type	opcode	address				

	Instruction	RTL
02	j address	PC ← {(PC + 4)[31:28], address, 00}
03	jal address	R[31] ← PC + 8 PC ← {(PC + 4)[31:28], address, 00}

Register Number	Conventional Name	Usage
$0	$zero	Hard-wired to 0
$1	$at	Reserved for pseudo-instructions
$2 - $3	$v0, $v1	Return values from functions
$4 - $7	$a0 - $a3	Arguments to functions - not preserved by subprograms
$8 - $15	$t0 - $t7	Temporary data, not preserved by subprograms
$16 - $23	$s0 - $s7	Saved registers, preserved by subprograms
$24 - $25	$t8 - $t9	More temporary registers, not preserved by subprograms
$26 - $27	$k0 - $k1	Reserved for kernel. Do not use.
$28	$gp	Global Area Pointer (base of global data segment)
$29	$sp	Stack Pointer
$30	$fp	Frame Pointer
$31	$ra	Return Address

J-type instructions
- Only 26bits address
- [leftmost 4 bits of PC] + [26bit address] + [00, 2 zeros]

I-type instructions
- The immediate value "imm" only have 16 bits
- Zero extend leftwards to extend it to 32 bits

R-type instructions
- $rs = $rt + $rd. 5 Bit each register (since we have 32 in total)
- Shamt used in shift function

MIPS Instruction Cautions & Notes

Bit-wise operations
- ORI: Must be **non-negative** (2's comp. meaningless after zero extend). ORI with zero can load **non-negative** constant to register
- ANDI: **sign irrelevant** (AND with zero padding always be 0). Good for clearing registers.
- XORI: **sign irrelevant**. Good for flipping specific bits of a register (by setting some bits of the immediate value to 1)
- NOR: equivalent to **NOT** (anything NOR 0, flips its bit)
- SLL: implement **No-Op** (sll $0, $0, 0)
- SRL: must be **non-negative** (due to zero padding on the left)
- SRA: **sign extend** left (extend with leftmost bit)

Arithmetic operations
- ADDU: **NOT unsigned**. It means **overflow is ignored**
- ADD: **overflow is detected**
- ADDIU: overflow ignore, **sign extended**
- Same for SUBU / SUB (overflow ignored / detected)
- MULTU: multiply unsigned (no overflow check)
- MULT: multiply signed (no overflow check)
- MFHI D: move 'hi' register -> 'D' register
- MFLO D: move 'lo' register -> 'D' register
- DIVU: division for unsigned. **Remainder -> hi ; Quotient -> lo**

Memory Access Operations
- LW $1, imm($2): $1 <- RAM [$2 + SignExtend(imm)]
- SW $1, imm($2):   RAM[$2 + SignExtend(imm)] <- $1
- LUI $1, imm: copy imm to upper 16bits of $1
- ORI $1, $0, imm: copy imm to lower 16bits of $1
- .data Directive: Declare variables & constants. Data section start at 0x10000000.
- .word Directive: Allocates a 4Bytes. (.data 69 / .data 1, 2, 3, 4)

Control Flow Operations
- J / JAL, PC + 4 before jump, thus need Branch Delay SLot

Name	Instruction	Operation	Notes
Branch on =	beq $rs, $rt, imm	if(R[$rs] = R[$rt])PC ← PC + 4 + SignExt$_{18}$({imm,00})	
Branch on ! =	bne $rs, $rt, imm	if(R[$rs] ≠ R[$rt])PC ← PC + 4 + SignExt$_{18}$({imm,00})	
Branch on ≤ 0	blez $rs, imm	if(R[$rs] ≤ 0)PC ← PC + 4 + SignExt$_{18}$({imm,00})	Signed comparison
Branch on > 0	bgtz $rs, imm	if(R[$rs] > 0)PC ← PC + 4 + SignExt$_{18}$({imm,00})	Signed comparison
Branch on < 0	bltz $rs, imm	if(R[$rs] < 0)PC ← PC + 4 + SignExt$_{18}$({imm,00})	Signed Comparison
Branch on ≥ 0	bgez $rs, imm	if(R[$rs] ≥ 0)PC ← PC + 4 + SignExt$_{18}$({imm,00})	Signed Comparison
Set less than	slt $rd, $rs, $rt	R[$rd] ← R[$rs] < R[$rt]	Signed comparison
Set < unsigned	sltu $rd, $rs, $rt	R[$rd] ← R[$rs] < R[$rt]	Unsigned comparison
Set < immediate	slti $rt, $rs, imm	R[$rt] ← R[$rs] < SignExt$_{16}$(imm)	Signed comparison
Set < unsigned	sltiu $rt, $rs, imm	R[$rt] ← R[$rs] < SignExt$_{16}$(imm)	Unsigned comparison

Subroutine
- $ra (return address) <- PC + 8
- $sp (stack pointer): points to stack top (smallest address)
- Stack push: subu $sp, $sp, 4 -> sw $t0, ($sp) --- ($sp) equiv 0($sp)
- Stack pop: lw $t0, ($sp) -> addu $sp, $sp, 4

Boolean Algebra

Number of Possible Switching Functions: 2^{2^N} (N input variables)

Commutative Laws	A + B = B + A	A.B = B.A
Associative Laws	A + (B + C) = (A + B) + C	A.(B.C) = (A.B).C
Distributive Laws	A.(B + C) = (A.B) + (A.C) (A + B).(A + C) = A + B.C	A + (B.C) = (A + B).(A + C)
Tautology/Idempotent Laws	A.A = A	A + A = A
Tautology/Identity Laws	1.A = A	0 + A = A
Tautology/Null Laws	0.A = 0	1 + A = 1
Tautology/Inverse Laws	A.Ā = 0	A + Ā = 1
Absorption Laws	A.(A + B) = A A + A.B = A	A + (A.B) = A A + Ā.B = A + B
De Morgan's Laws	$\overline{(A.B)} = \bar{A} + \bar{B}$	$\overline{(A + B)} = \bar{A}.\bar{B}$

Boolean Function Duality **(Right Side of Above Table)**
- Replace AND with OR ; Replace OR with AND
- Replace constant 1 with 0 ; Replace 0 with 1
- New function has exact opposite output.

Combinational Logic

Multiplexer (MUX) **reduce wire usage**   **Demultiplexer (DeMUX)**

Control Inputs

A	B	F
0	0	D_0
0	1	D_1
1	0	D_2
1	1	D_3

$F_0 = D\,\bar{A}\,\bar{B}$ $F_2 = D\,A\,\bar{B}$
$F_1 = D\,\bar{A}\,B$ $F_3 = D\,A\,B$

D	A	B	F_0	F_1	F_2	F_3
0	0	0	0	0	0	0
0	0	1	0	0	0	0
0	1	0	0	0	0	0
0	1	1	0	0	0	0
1	0	0	1	0	0	0
1	0	1	0	1	0	0
1	1	0	0	0	1	0
1	1	1	0	0	0	1

Karnaugh Map (K-Map)
- Bit order: 00 01 11 10 (both row and column)
- Group biggest blocks of 1s.
- "X" or "don't care" don't necessarily need to be circled. Only circle them when it simplifies things

Minterm: Product term in SOP form $\sum(m_i, m_j, \dots)$
Maxterm: Sum term in POS form $\prod(M_i, M_j, \dots)$

Quine-McKluskey tables
- Idea: if 2 minterms differ **only in one position**, can be simplified
- AB + AB' = A(B + B') = A

Procedure
1. Group minterms according to **the number of 1's**
2. Check adjacent groups for simplification (group 1 & 2, 2 & 3 …)
3. Merge minterms only differ by one position. Denote the differing position with '-' (canceled)
4. Repeated terms can be cancelled

Group Name	Min terms	W	X	Y	Z
GB1	2,6	0	-	1	0
	2,10	-	0	1	0
	8,9	1	0	0	-
	8,10	1	0	-	0
GB2	6,14	-	1	1	0
	9,11	1	0	-	1
	10,11	1	0	1	-
	10,14	1	-	1	0
GB3	11,15	1	-	1	1
	14,15	1	1	1	-

Group Name	Min terms	W	X	Y	Z
GB1	2,6,10,14	-	-	1	0
	2,10,6,14	-	-	1	0
GB2	8,9,10,11	1	0	-	-
	8,10,9,11	1	0	-	-
	10,11,14,15	1	-	1	-
	10,14,11,15	1	-	1	-

5. Repeat 1~5, Until Can't merge. Now we get **prime implicant**: a minterm that cannot be further simplified with other minterms

**Prime Implicant Table:** each prime implicant covers some minterms

Min terms / Prime Implicants	2	6	8	9	10	11	14	15
YZ'	1	1			1		1	
WX'			1	1	1	1		
WY					1	1	1	1

上面表格中如有 minterm **仅被 1 个 prime implicant 覆盖**，那么这个 prime implicant 是 **essential prime implicant**

Sequential Circuit
- Not only dependent on current (comb. circuits) but also past behavior (i.e., storage element / memory)
- Output (next state) = current input + current state.
- Flip-flops: **bistable** device (two stable states – doesn't change without external input). Outputs: $Q, \bar{Q}$ complements each other.

SR Flipflops

S	R	Q_{n+1}
0	0	Q_n
0	1	0
1	0	1
1	1	–

Edge Triggered (or Clocked) S-R Flip-Flop

(a) positive edge-triggered   (b) negative edge-triggered

D Flip-Flop

| D	Q_{n+1}
0	0
1	1

Characteristic table

JK Flip-Flop

- Unlike SR Flip-Flop (which can't take S=1, R=1 as input)
- JK Flip-Flop allows all combination of input (including 1 1)
- Output tick between 1, 0 each clock cycle when J=1 K=1

J	K	Q_{n+1}
0	0	Q_n
0	1	0
1	0	1
1	1	$\overline{Q_n}$

Characteristic table

8-bit Parallel Registers

Counter (register whose value incr. by 1 every tick)

- For counter with N flip flops, the value ranges from $0 \sim 2^N - 1$
- Asynchronous counter: state of the FF will NOT change same time
- Synchronous counter: state of the FF changes at the same time

Ripple Counter


Finite State Machine

Definition

> **Finite State Machine (FSM):** abstract model to describe real world systems
> - States: represent different situation of the system
> - FSM models **state changes** (external input → external output relation)

$$FSM = (S, I, O, \pi)$$

- S: the finite set of states
- I: the finite set of external inputs
- O: the finite set of external outputs
- π: state transition function:
  - Define the **relations** among input, output, current state, next state.
 - **Complete:** for any $\{S_t, I_t\}$, $\{S_{t+1}, I_{t+1}\}$ can be determined

Mealy Machine

- Output and state depends on both current state and input

Moore Machine

- Output only depends on current state

- **Registers = Memory Component**
- **Comb. logic = State transition Function**

FSM Model -> Circuit

- Model the problem using FSM
- Construct **excitation table** of the circuit

Columns:
- Q: current state
- X: Input
- Q_{next}: next state
- Input to Flip-Flop

Basically:
- FSM -> State table
- FF -> FF ExTable
- **Circuit table = FF ExTable + State Table**

- K-map simplification: All pairs of **(State Q) vs (Flip-Flop Input)**

CHARACTERISTIC EQUATION	EXCITATION TABLE			
	Q	$Q_{(next)}$	S	R
$Q_{(next)} = S + R'Q$	0	0	0	X
$SR = 0$	0	1	1	0
	1	0	0	1
	1	1	X	0
	Q	$Q_{(next)}$	J	K
$Q_{(next)} = JQ' + K'Q$	0	0	0	X
	0	1	1	X
	1	0	X	1
	1	1	X	0
	Q	$Q_{(next)}$		D
$Q_{(next)} = D$	0	0		0
	0	1		1
	1	0		0
	1	1		1
	Q	$Q_{(next)}$		T
$Q_{(next)} = TQ' + T'Q$	0	0		0
	0	1		1
	1	0		1
	1	1		0

Cache Mapping

Mapping Function

> **Intuition:**
> - $\because C \ll M$ (significantly more memory blocks than cachelines)
> - $\therefore$ Use mapping function to map "blocks → cacheline"
> - line $= f(\text{block})$

Direct Mapping

- **Explanation:** Multiple blocks of memory mapped to one fixed cacheline
- **Mapping Rule:**
  - Q blocks mapped to 1 cacheline.
  - $Q = \frac{M}{C}$
- **Selecting cacheline:**
  - index $=$ block address $\mod C$
- **Cons:** low hit ratio if accesses clusters

Associative Mapping

- **Explanation:** Any block can map to any cacheline
- **Mapping Rule:**
  - If there's spare lines, map there
  - Search tags through cached blocks sequentially or in parallel.
- **Cons:** Checking tags is complex

Cache Performance

- Miss Rate = 1 − Hit Rate (*% of mem accesses not found in cache*)
- Hit Time = Time to deliver word from cache -> memory
- Miss Penalty = extra time needed (to access memory) due to miss

Memory Address

Block Address		Block Offset
Tag	Index	

- **Block Offset:** index of each word within the block.
- **Index:** indicates which cacheline
- **Tag:** unique identifier of blocks mapped to same cacheline (blocks of same cacheline have *different tags*)

Calculations:
- N bit address -> 2^n **addressable words**
- K words per block -> $M = 2^n / K$ **blocks**
- **Offset**: $\log_2(K)$ bits --- **log (Block Size) bits**
- **Index**: $\log_2(C)$ bits --- **log (Num. of Cacheline) bits**
- **Tag:** $n - \log_2(K) - \log_2(C)$ --- Total Length of Address – Length of Offset – Length of Index

Memory Access Logic

- Row Access: 11 lines + RAS -> select 2048 rows
- Col Access: 11 lines + CAS -> select 2048 columns
- Read/write: controlled by WE / OE pins.

Error Detection and Correction

- Codeword = original data + parity bits
- D_min = minimum hamming distance among codewords
- **Max Detectable Error: D_min – 1 bits**
- **Max Correctable Error: Floor ((D_min – 1) / 2) bits**

Contiguous Memory Allocation

Fixed Partition
- Memory divided into one or more fixed-sized pattern

Variable Parition
- Division not fixed size (process allocated **just enough** memory), thus no internal fragmentation

Fragmentation

- Internal: unused space **within** partition (fixed partition only)
- External: enough total space, but non-contiguous
- Solution: compaction (defragmentation)

Memory Type	Category	Erasure	Write Mechanism	Volatility
Random-access memory (RAM)	Read-write memory	Electrically, byte-level	Electrically	Volatile
Read-only memory (ROM)	Read-only memory	Not possible	Masks	Nonvolatile
Programmable ROM (PROM)				
Erasable PROM (EPROM)		UV light, chip-level	Electrically	
Electrically Erasable PROM (EEPROM)	Read-mostly memory	Electrically, byte-level		
Flash memory		Electrically, block-level		

Non-Contiguous Memory Allocation

Paging
- **Page Table:** translate page -> Frames
- **Page:** logical memory divided into fixed-size blocks (process view)
- **Frame:** physical mem divided into fixed-size blocks (actual)
- **Virtual Address = { Page Number, Page Offset }**
- Page Offset has $\log_2$(page & frame size)

Segmentation
- Program divided into variable-szied segments
- **Virtual Address = { Segment Number, Segment Offset }**

- **Segment Table :**
- Base Address : Physical starting address of the segment
- Segment Limit: Length of that segment
- Physical Address = Base Address + Segment Offset

Magnetic Disk
- Constant Angular Velocity (CAV) – **LEFT**
- Multiple Zoned Recording -- **RIGHT**

- Access Must Specify: Cylinder, Head, Sector, Transfer Size, Memory Address

- **Access Delay = Seek Time + Rotational Delay**
- **Format of a Track** [Sector] [Sector] [Sector] …
- **Format of Sector** [gap] [ID field] [gap] [Data Field] [gap]
- **ID Field:** [Synth Byte] [Track] [Head] [Sector] [CRC]

Solid-State Drive (SSD)
- Erase entire block before write
- Write data in new space then garbage collect 'deleted' space

I/O Modules - Function
- **Control and Timing**: Proc request; I/OM check & return device status; transfer data if device ready
- **Processor Communication: Command** (control bus, CPU -> I/OM), **Data** (data bus), **Status** (BUSY, READY, error conditions)
- **Device Communication: I/O -> devices.** Unique address for each device (depending on Memory Mapped I/O or Isolated I/O)
- **Data Buffering:** I/OM buffers data to handle different transfer rates
- **Error Detection:** soft error (parity bit) OR hard error (paper jam)

I/O Modules – Technique
Programmed I/O (PIO): I/O Device -> CPU -> RAM
- CPU -> IOM **sends command**
- IOM perform action, sets **status register** when finished
- **Pooling:** CPU periodically checks status register to check completion

**Interrupt-Driven I/O:** I/O Device -> CPU -> RAM
- Same as PIO. Except after command send, CPU **continue other work**
- IOM perform action, **interrupt** CPU when ready
- CPU save state (register, PC, etc), process interrupt, restore state.

Direct Memory Access (DMA): I/O device -> DMA -> RAM
- CPU tells DMA what to do (e.g., device addr, memory loc, words)
- DMA transfer entire block of data. Interrupt CPU when finished.
- **Cycle Stealing:** DMA *steals* some cycles from CPU. CPU slowed.

- **Single bus, detached DMA.** Use bus twice
- CPU suspend twice

- **Single bus, integrated DMA.** Use bus once
- CPU suspend once

- **Separate I/O Bus.**
- CPU suspended once
- Use Bus once