

Cynthia Liu

April 7, 2024

# 1 Revision History

Date	Version	Notes
Mar. 8, 2024 April. 5, 2024	0 0.1	Initial Release Edit according to feedback from peer review and Dr. Smith

# 2 Symbols, Abbreviations and Acronyms

See SRS Documentation at SRS.

[Also add any additional symbols, abbreviations or acronyms —SS]

# Contents

1	Rev	ision l	History					
2	Symbols, Abbreviations and Acronyms							
3	Introduction							
4	Notation							
5	Mo	dule D	Decomposition					
6	MIS	S of Co	ontrol Module					
	6.1	Modu	ıle					
	6.2							
	6.3		X					
		6.3.1	Exported Constants					
		6.3.2	Exported Access Programs					
	6.4	Semar	$rac{1}{ ext{ntics}}$					
		6.4.1	State Variables					
		6.4.2	Environment Variables					
		6.4.3	Assumptions					
		6.4.4	Access Routine Semantics					
		6.4.5	Local Functions					
7	MIS	S of In	aput Module					
	7.1	Modu	<u>lle </u>					
	7.2	Uses						
	7.3	Syntax	x					
		7.3.1	Exported Constants					
		7.3.2	Exported Access Programs					
	7.4	Semar	$\operatorname{ntics}$					
		7.4.1	State Variables					
		7.4.2	Environment Variables					
		7.4.3	Assumptions					
		7.4.4	Access Routine Semantics					
		7.4.5	Local Functions					
3	MIS	S of Da	ata Searching Module					
	8.1	Modu	<u>lle </u>					
	8.2	Uses						
	8.3	Syntax	x					
		8.3.1	Exported Constants					
		8.3.2	Exported Access Programs					

	8.4	Seman	tics						 									7
		8.4.1	State Variables						 									7
		8.4.2	Environment Variables						 									7
		8.4.3	Assumptions						 									7
		8.4.4	Access Routine Semantics						 									8
		8.4.5	Local Functions						 									8
9	MIS	of Ou	tput Visualization Mod	ule	<u>,</u>													9
	9.1		e						 									9
	9.2																	9
	9.3	Syntax							 									9
		9.3.1	Exported Constants															9
		9.3.2	Exported Access Programs						 									9
	9.4	Seman	•															9
		9.4.1	State Variables						 									9
		9.4.2	Environment Variables						 									9
		9.4.3	Assumptions															9
		9.4.4	Access Routine Semantics						 									9
		9.4.5	Local Functions						 									10
10	MIS	of Da	ata Model Reading Mod	ule	<u>.</u>													11
			e						 									11
																		11
			΄															11
		•	Exported Constants															11
			Exported Access Programs															11
	10.4		tics															11
			State Variables															11
		10.4.2	Environment Variables						 									12
		10.4.3	Assumptions						 									12
			Access Routine Semantics															12
			Local Functions															12
11	MIS	of Co	onstant Module															13
			e															13
																		13
			·															13
	11.0		Exported Constants															13
			Exported Access Programs															13
	11 4		tics															13
			State Variables															13
			Environment Variables															13
			Assumptions															14
		11.7.0	7100umpuomo	•		•	•	 •	 	•	 •	 •	•	•	•	•	•	17

	11.4.4 Access Routine Semantics	14
	11.4.5 Local Functions	14
19 MTS	of Deicing Salts Calculation Module	15
		15 15
	Module	
	Uses	15
12.3	Syntax	15
	12.3.1 Exported Constants	15
10.4	12.3.2 Exported Access Programs	15
12.4	Semantics	15
	12.4.1 State Variables	15
	12.4.2 Environment Variables	15
	12.4.3 Assumptions	15
	12.4.4 Access Routine Semantics	15
	12.4.5 Local Functions	16
13 MIS	of Melted Water Thickness Module	17
	Module	17
	Uses	17
	Syntax	17
10.0	13.3.1 Exported Constants	17
	13.3.2 Exported Access Programs	17
19 /	Semantics	17
15.4	13.4.1 State Variables	$\frac{17}{17}$
	13.4.2 Environment Variables	$\frac{17}{17}$
	13.4.3 Assumptions	17
	13.4.4 Access Routine Semantics	17
	13.4.5 Local Functions	18
14 MIS	of Single Water SAS Calculation Module	19
14.1	Module	19
14.2	Uses	19
14.3	Syntax	19
	14.3.1 Exported Constants	19
	14.3.2 Exported Access Programs	19
14.4	Semantics	19
	14.4.1 State Variables	19
	14.4.2 Environment Variables	19
	14.4.3 Assumptions	19
	14.4.4 Access Routine Semantics	19
	14.4.5 Local Functions	20
	14.4.6 Local Functions	20
	TIME DOOM I UIIOUOIID	4

15 MI	S of Single Chloride Ions SAS Calculation Module	<b>2</b> 1
15.	1 Module	2
15.5	2 Uses	2
15.	3 Syntax	2
	15.3.1 Exported Constants	2
	15.3.2 Exported Access Programs	2
15.4	4 Semantics	2
	15.4.1 State Variables	2
	15.4.2 Environment Variables	2
	15.4.3 Assumptions	2
	15.4.4 Access Routine Semantics	22
	15.4.5 Local Functions	
	10.4.0 Local I uncolons	22
16 MI	S of All Chloride Ions SAS Calculation Module	23
16.	1 Module	23
16.5	2 Uses	23
16.	3 Syntax	23
	16.3.1 Exported Constants	23
	16.3.2 Exported Access Programs	23
16.4	4 Semantics	23
	16.4.1 State Variables	23
	16.4.2 Environment Variables	23
	16.4.3 Assumptions	23
	16.4.4 Access Routine Semantics	2
	16.4.5 Local Functions	
	S of Deicing Salts Deposition Calculation Module	25
	1 Module	
17.5	2 Uses	
17.3	3 Syntax	2!
	17.3.1 Exported Constants	2!
	17.3.2 Exported Access Programs	2!
17.4	4 Semantics	2!
	17.4.1 State Variables	2!
	17.4.2 Environment Variables	2!
	17.4.3 Assumptions	2!
	17.4.4 Access Routine Semantics	25
	17.4.5 Local Functions	26
10 N/II	S of Chlorida Eurocaura Databasa Comenation Madela	O.
	S of Chloride Exposure Database Generation Module	27
	1 Module	27
	2 Uses	2'
1.0	A . AVIII AV	

	18.3.1	Exported Constants
	18.3.2	Exported Access Programs
18.4	Seman	${ m tics}$
	18.4.1	State Variables
	18.4.2	Environment Variables
	18.4.3	Assumptions
	18.4.4	Access Routine Semantics
	18 4 5	Local Functions 2

# 3 Introduction

The following document details the Module Interface Specifications for Bridge Corrosion which investigate how climate, traffic might impact corrosion-induced damage for reinforced concrete bridges by influencing the chloride exposure.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at here.

# 4 Notation

The structure of the MIS for modules comes from [HoffmanAndStrooper1995], with the addition that template modules have been adapted from [GhezziEtAl2003]. The mathematical notation comes from Chapter 3 of [HoffmanAndStrooper1995]. For instance, the symbol := is used for a multiple assignment statement and conditional rules follow the form  $(c_1 \Rightarrow r_1|c_2 \Rightarrow r_2|...|c_n \Rightarrow r_n)$ .

The following table summarizes the primitive data types used by BC.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	$\mathbb{Z}$	a number without a fractional component in $(-\infty, \infty)$
natural number	N	a number without a fractional component in $[1, \infty)$
real	$\mathbb{R}$	any number in $(-\infty, \infty)$
empty	Ø	when the input is empty or the variable does not exist
GeoDataFrame	GeoDataFrame	todo

The specification of BC uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, BC uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

# 5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding Module	
Behaviour-Hiding Module	Input Module Control Module Data Searching Module Output Visualization Module Data Model Reading Module Constant Module Deicing Salts Calculation Module Melted Water Thickness Calculation Module Single Water SAS Calculation Module Single Chloride Ions SAS Calculation Module All Chloride Ions SAS Calculation Module Deicing Salts Deposition Calculation Module Chloride Exposure Database Generation Module
Software Decision Module	File I/O Module Plotting Module
<u> </u>	

Table 1: Module Hierarchy

# 6 MIS of Control Module

This module provides the main program and the GUI of the software. It is related to R1 and R2 in the SRS.

# 6.1 Module

main

# 6.2 Uses

- Input Module (Section 7)
- Data Searching Module (Section 8)
- Output Visualization Module (Section 9)

# 6.3 Syntax

# 6.3.1 Exported Constants

None

# 6.3.2 Exported Access Programs

Name	In	Out	Exceptions
main	-	-	_

# 6.4 Semantics

#### 6.4.1 State Variables

None

#### 6.4.2 Environment Variables

None

# 6.4.3 Assumptions

# 6.4.4 Access Routine Semantics

main():

- transition: Control and execute the other modules as follow:
  - Get and verify the input from user. (Section 7)
  - Search the corresponding data in Data Searching Module if the input is valid. (Section 8)
  - Visualize the resulting data by using Output Visualization Module. (Section 9)
- $\bullet$  output: out := None
- exception: exc := None

# 6.4.5 Local Functions

# 7 MIS of Input Module

This module get the input from user and verify if it is within the physical and software constraints, it is related to R1 in SRS.

# 7.1 Module

 $input\_check$ 

# 7.2 Uses

None

# 7.3 Syntax

# 7.3.1 Exported Constants

None

# 7.3.2 Exported Access Programs

Name	In	Out	Exceptions
read_geoinfo	filename: String	-	FileNotFoundError
$convert\_longitude$	long: String	long: $\mathbb{R}$	ValueError
$convert\_latitude$	lat: String	lat: $\mathbb{R}$	ValueError
$is\_within\_ontario$	long: $\mathbb{R}$ , lat: $\mathbb{R}$	Boolean	Input Out of Ontario Error

# 7.4 Semantics

#### 7.4.1 State Variables

- lon:  $\mathbb{R}$  # longitude get from user.
- $\bullet$  lat:  $\mathbb R$  # latitude get from user.
- boundary: GeoDataFrame # the data read from geojson file

# 7.4.2 Environment Variables

- Keyboard: takes input from the keyboard by typing.
- File: the geojson file that contain the shape of Ontario.

#### 7.4.3 Assumptions

This module use the open source geojson file that contain the Ontario boundary, by drawing polygons with the vertex coordinate. The coordinates for those vertexes are assumed to be reliable.

# 7.4.4 Access Routine Semantics

# read\_geoinfo(filename):

- transition: access the data from geojson file
- exception: exc := FileNotFoundError: ∄ filename

# $convert\_longitude(long)$ :

- output: out := long:  $\mathbb{R}$
- exception: exc := ValueError:  $\neg isNumeric(long)$

#### **convert\_latitude**(long):

- output: out := lat:  $\mathbb{R}$
- exception: exc := ValueError:  $\neg isNumeric(lat)$

#### is\_within\_ontario(long, lat):

- output: out := Boolean
- exception: exc := InputOutofOntarioError:  $\neg((long, lat) \in Ontario)$

#### 7.4.5 Local Functions

#### isNumeric(e):

• output: out := Boolean # check if the input e is a string of float

# InputOutofOntarioError:

 $\bullet$  output: out := Exception # raise this exception if the input is out of Ontario

# 8 MIS of Data Searching Module

This module finds the data needed in the database, it is related to R2 in SRS.

# 8.1 Module

search

# 8.2 Uses

Input Module (Section 7), Chloride Exposure Database Generation Module (Section 18)

# 8.3 Syntax

#### 8.3.1 Exported Constants

None

# 8.3.2 Exported Access Programs

Name	In	Out	Exceptions
read_file	filename: String	data: sequence of $\mathbb{R}$	FileNotFoundError
$find\_closest$	long: $\mathbb{R}$ , lat: $\mathbb{R}$	index: $\mathbb{N}$	-
search	long: $\mathbb{R}$ , lat: $\mathbb{R}$	result: sequence of $\mathbb R$	-

#### 8.4 Semantics

#### 8.4.1 State Variables

- $\bullet$  data: sequence of  $\mathbb R$  # the sequence of all data read from chloride exposure database
- ullet result: sequence of  $\mathbb R$  # the sequence of predicted chloride exposure data that the user want

#### 8.4.2 Environment Variables

• File: the database file that contain the yearly chloride exposure data within Ontario.

#### 8.4.3 Assumptions

All locations within Ontario, if it is not on water, must contain valid data.

#### 8.4.4 Access Routine Semantics

# read\_file(filename):

- ullet output: out := data # sequence of  $\mathbb R$  read from the file
- exception: exc := FileNotFoundError =  $\nexists$  filename

 $find\_closest(long, lat)$ : If the input coordinate is not the exact one in database, find the grid that it belongs to and return the index of center coordinate.

• output: out := index:  $\mathbb{N}$ 

# $\mathbf{search}(long, lat)$ :

- output: out := result = search(find\_closest(long, lat)) # sequence of  $\mathbb{R}$ , the chloride exposure result
- exception: exc := None

#### 8.4.5 Local Functions

# 9 MIS of Output Visualization Module

This module provides the visualization of the resulting chloride exposure trend, it is related to R2 and R3 in SRS.

# 9.1 Module

visualization

#### 9.2 Uses

Data Searching Module (Section 8)

# 9.3 Syntax

# 9.3.1 Exported Constants

None

# 9.3.2 Exported Access Programs

Name	In	Out	Exceptions
draw	result: sequence of $\mathbb{R}$	-	-

#### 9.4 Semantics

#### 9.4.1 State Variables

None

#### 9.4.2 Environment Variables

Screen: The graphs are displayed on the screen.

#### 9.4.3 Assumptions

None

#### 9.4.4 Access Routine Semantics

#### draw(result):

- transition: display the graphs using the result from Data Searching Module.
- output: out := None
- exception: exc := None

# 9.4.5 Local Functions

# 10 MIS of Data Model Reading Module

This module loads the climate and traffic data from the external file and store it in the data format that could be used for calculation.

#### 10.1 Module

calculation\_loadT

#### 10.2 Uses

None

# 10.3 Syntax

# 10.3.1 Exported Constants

None

#### 10.3.2 Exported Access Programs

Name	In	Out	Exceptions
new calculation_load	filename: String	$calculation\_loadT$	FileNotFoundError

#### 10.4 Semantics

A data structure designed to store the data from climate and traffic model.

#### 10.4.1 State Variables

- long: sequence of  $\mathbb{R}$  # longitude get from climate and traffic model
- lat: sequence of  $\mathbb{R}$  # latitude get from climate and traffic model
- AADT: sequence of  $\mathbb{R}$  # annual average daily traffic per lane
- $\bullet$  AADTT: sequence of  $\mathbb R$  # annual average daily truck traffic per lane
- t1: sequence of  $\mathbb{R}$  # number of days with snowfall
- $\bullet$  h\_total: sequence of  $\mathbb R$  # the total snowfall during a winter season
- t2: sequence of  $\mathbb{R}$  # number of days with snow melting

# 10.4.2 Environment Variables

File: the file with all climate model data and traffic model data

# 10.4.3 Assumptions

None

# 10.4.4 Access Routine Semantics

# $calculation\_load:$

• transition: Read and store the data from the climate model and traffic model file

 $\bullet$  output: out := self

 $\bullet$ exception: exc := FileNotFoundError =  $\nexists$  filename

# 10.4.5 Local Functions

# 11 MIS of Constant Module

This module stores the constants used for calculation.

# 11.1 Module

constantT

# 11.2 Uses

None

# 11.3 Syntax

# 11.3.1 Exported Constants

Name	Value	Note
salt_application_rate	0.07	salt application rate
$W_{-lane}$	3.75	lane width
$V\_speed$	100	heavy vehicle speed
b	0.56	tire width
K	0.75	ratio of the tire width that is not a groove to the tire width
h_film	0.0001	depth of the water film picked up in each rotation
$water\_density$	997	density of water
V	62.1371	truck speed
$chloride\_ratio$	0.61	molar mass ratio of chloride ions over deicing salts
d	3.5	distance between road edge and nearby bridge structure
$ldv_ratio$	6	ratio of chloride ions sprayed and splashed by trucks over
		light-duty vehicles

# 11.3.2 Exported Access Programs

None

# 11.4 Semantics

# 11.4.1 State Variables

None

#### 11.4.2 Environment Variables

# 11.4.3 Assumptions

None

# 11.4.4 Access Routine Semantics

None

# 11.4.5 Local Functions

# 12 MIS of Deicing Salts Calculation Module

This module provides the calculation for the quantity of deicing salts applied per day with snowfall

#### 12.1 Module

calculation\_step1

# 12.2 Uses

Constant Module (Section 11), Data Model Reading Module (Section 10)

# 12.3 Syntax

# 12.3.1 Exported Constants

None

# 12.3.2 Exported Access Programs

Name	In		Out	Exceptions
calculate_step1	h_total:	sequence of $\mathbb{R}$ ,	$M_{-app}$ : sequence of $\mathbb{R}$	-
	t1: seque	ence of $\mathbb{R}$		

# 12.4 Semantics

#### 12.4.1 State Variables

None

#### 12.4.2 Environment Variables

None

# 12.4.3 Assumptions

None

#### 12.4.4 Access Routine Semantics

calculate\_step1( $h_-total, t1$ ):

• transition: None

- output: out :=  $\frac{salt\_application\_rate*h\_total}{(W\_lane*t1)}$ , where salt\\_application\\_rate and W\\_lane are constant value get from Constant Module, h\_total and t1 are read from Data Model Reading Module
- $\bullet$  exception: exc := None

# 12.4.5 Local Functions

# 13 MIS of Melted Water Thickness Module

This module provides the calculation for the daily water film thickness on the road

# 13.1 Module

calculation\_step2

# 13.2 Uses

Data Model Reading Module (Section 10)

# 13.3 Syntax

# 13.3.1 Exported Constants

None

#### 13.3.2 Exported Access Programs

Name	In	Out	Exceptions
calculate_step2	h_total: sequence of $\mathbb{R}$ ,	h_app: sequence of $\mathbb{R}$	_
	t2: sequence of $\mathbb{R}$		

# 13.4 Semantics

#### 13.4.1 State Variables

None

#### 13.4.2 Environment Variables

None

# 13.4.3 Assumptions

None

#### 13.4.4 Access Routine Semantics

calculate\_step2(h\_total, t2):

- transition: None
- ullet output: out :=  $\frac{h\_total}{t2}$ , where h\\_total and t1 are read from Data Model Reading Module
- exception: exc := None

# 13.4.5 Local Functions

# 14 MIS of Single Water SAS Calculation Module

This module determine water sprayed and splashed by one truck using a (CFD)-based analytical model, taking into account of the four primary mechanisms of vehicle spray and splash: capillary adhesion, tread pickup, bow wave, and side wave.

#### 14.1 Module

calculation\_step3

# 14.2 Uses

Constant Module (Section 11), Melted Water Thickness Module (Section 13)

# 14.3 Syntax

#### 14.3.1 Exported Constants

None

#### 14.3.2 Exported Access Programs

Name	In	Out	Exceptions
calculate_step3	h_app: sequence of $\mathbb{R}$	SD_total: sequence of $\mathbb{R}$	-

# 14.4 Semantics

#### 14.4.1 State Variables

None

#### 14.4.2 Environment Variables

None

#### 14.4.3 Assumptions

None

#### 14.4.4 Access Routine Semantics

calculate\_step3( $h_app$ ):

• transition: None

- output: out :=  $SD_{CA} + SD_{TP} + SD_{BW} + SD_{SW} \#$  the mass of water per unit air volume kicked up by each passing truck is the sum of the four mechanisms, calculated by the local functions below.
- $\bullet$  exception: exc := None

#### 14.4.5 Local Functions

 $V_{speed}$ , b, K,  $h_{film}$ ,  $\rho_{water}$ , V' are constants read from Constant Module. **mass\_flow\_rate**( $h\_app$ ):

- transition: None
- output: out :=

$$\begin{cases} MR_{CA} = V_{speed} \times b \times K \times h_{film} \times \rho_{water} & \text{for } CA \\ MR_{TP} = V_{speed} \times b \times (1 - K) \times h_{app} \times \rho_{water} & \text{for } TP \\ MR_{BW} = MR_{SW} = 0.5 \times V_{speed} \times b \times \\ (h_{app} - K \times h_{film} - (1 - K) \times h_{app}) \times \rho_{water} & \text{for } BW \text{ } and \text{ } SW \end{cases}$$

• exception: exc := None

 $\mathbf{spray\_density}(\mathit{MR}_{\mathit{CA}}, \mathit{MR}_{\mathit{TP}}, \mathit{MR}_{\mathit{BW}}, \mathit{MR}_{\mathit{SW}})$ :

- transition: None
- output: out :=

$$\begin{cases} SD_{CA} = (-2.69 \times 10^{-5} \times V' + 2.43 \times 10^{-3}) \times MR_{CA} & \text{for } CA \\ SD_{TP} = (1.16 \times 10^{-5} \times V' - 5.25 \times 10^{-5}) \times MR_{TP} & \text{for } TP \\ SD_{BW} = (2.67 \times 10^{-5} \times V' - 4.71 \times 10^{-4}) \times MR_{BW} & \text{for } BW \\ SD_{SW} = (1.65 \times 10^{-5} \times V' - 3.99 \times 10^{-4}) \times MR_{SW} & \text{for } SW \end{cases}$$

• exception: exc := None

#### 14.4.6 Local Functions

# 15 MIS of Single Chloride Ions SAS Calculation Module

This module determines the chloride ions sprayed and splashed by one truck.

# 15.1 Module

 $calculation\_step4$ 

# 15.2 Uses

Deicing Salts Calculation Module (Section 12), Single Water SAS Calculation Module (Section 14)

# 15.3 Syntax

# 15.3.1 Exported Constants

None

# 15.3.2 Exported Access Programs

Name	In	Out	Exceptions
calculate_step4	$M_{-app}$ : sequence of $\mathbb{R}$ ,	$SD_{totalCl}$ : sequence of $\mathbb{R}$	-
	h_app: sequence of $\mathbb{R}$ ,		
	SD_total: sequence of $\mathbb{R}$		

# 15.4 Semantics

#### 15.4.1 State Variables

None

#### 15.4.2 Environment Variables

None

# 15.4.3 Assumptions

#### 15.4.4 Access Routine Semantics

 ${\bf calculate\_step4} (M\_app, h\_app, SD\_total) :$ 

- transition: None
- output: out :=  $SD\_total * salt\_water\_ratio(M\_app, h\_app) * chloride\_ratio,$  where chloride\\_ratio is a constant read from Constant Module.
- $\bullet$  exception: exc := None

#### 15.4.5 Local Functions

 $salt\_water\_ratio(M\_app, h\_app)$ :

- transition: None
- output: out :=  $\frac{M\_app}{h\_app*water\_density}$  where water\\_density is a constant read from Constant Module.
- exception: exc := None

# 16 MIS of All Chloride Ions SAS Calculation Module

This module determines chloride ions sprayed and splashed by all vehicles in one winter season

# 16.1 Module

calculation\_step5

# 16.2 Uses

Constant Module (Section 11), Data Model Reading Module (Section 10), Single Water SAS Calculation Module (Section 14)

# 16.3 Syntax

#### 16.3.1 Exported Constants

None

# 16.3.2 Exported Access Programs

Name	In	Out	Exceptions
calculate_step5	SD_totalCl: sequence of	C_s_air: sequence of $\mathbb{R}$	-
	$\mathbb{R}$ , t2: sequence of $\mathbb{R}$ ,		
	AADT: sequence of $\mathbb{R}$ ,		
	AADTT: sequence of $\mathbb{R}$		
${\bf update AADT}$	AADT: sequence of $\mathbb{R}$	AADT: sequence of $\mathbb{R}$	-
updateAADT	$\Gamma$ AADTT: sequence of $\mathbb R$	AADTT: sequence of $\mathbb{R}$	-

#### 16.4 Semantics

#### 16.4.1 State Variables

None

#### 16.4.2 Environment Variables

None

#### 16.4.3 Assumptions

The AADT and AADTT are assumed to have 2% increase rate every year

#### 16.4.4 Access Routine Semantics

calculate\_step5( $M\_app, h\_app, SD\_total, t2, AADT, AADTT$ ):

- transition: None
- output: out :=  $(\frac{SD\_totalCl}{ldv\_ratio} * (updateAADT(AADT) updateAADTT(AADTT)) + SD\_totalCl * AADTT) * t2$ , where ldv\\_ratio is a constant read from Constant Module.
- exception: exc := None

# updateAADT(AADT):

- transition: None
- $\bullet$  output: out := AADT # calculate the AADT for future year, assuming a 2% annual increase rate
- exception: exc := None

# updateAADTT(AADTT):

- transition: None
- $\bullet\,$  output: out := AADTT # calculate the AADTT for future year, assuming a 2% annual increase rate
- exception: exc := None

#### 16.4.5 Local Functions

# 17 MIS of Deicing Salts Deposition Calculation Module

This module determine the deposition of chloride ions on the surface of the bridge substructure

# 17.1 Module

calculation\_step6

# 17.2 Uses

Constant Module (Section 11), All Chloride Ions SAS Calculation Module (Section 16)

# 17.3 Syntax

# 17.3.1 Exported Constants

None

#### 17.3.2 Exported Access Programs

Name	In	Out	Exceptions
calculate_step	6 C_s_air: sequence of $\mathbb{R}$	results: sequence of $\mathbb{R}$	-

# 17.4 Semantics

# 17.4.1 State Variables

None

# 17.4.2 Environment Variables

None

# 17.4.3 Assumptions

None

# 17.4.4 Access Routine Semantics

calculate\_step6( $C\_s\_air$ ):

• transition: None

- output: out :=  $C\_s\_air * 0.015 * e^{-0.05*d} + C\_s\_air * 0.985 * e^{-0.5*d}$ , where d is a constant read from Constant Module, 0.015 and 0.985 being the coefficient of the formula.
- $\bullet$  exception: exc := None

# 17.4.5 Local Functions

# 18 MIS of Chloride Exposure Database Generation Module

This module performs the calculation process(calculation\_load to calculation\_step6) to generate the database, it is related to the R2, R3 in SRS.

# 18.1 Module

calculate

#### 18.2 Uses

Data Model Reading Module (Section 10), Constant Module (Section 11), Deicing Salts Calculation Module (Section 12), Melted Water Thickness Module (Section 13), Single Water SAS Calculation Module (Section 14), Single Chloride Ions SAS Calculation Module (Section 15), All Chloride Ions SAS Calculation Module (Section 16), Deicing Salts Deposition Calculation Module (Section 17)

# 18.3 Syntax

#### 18.3.1 Exported Constants

None

18.3.2 Exported Access Programs

Name	In	Out	Exceptions
calculate	AADT: sequence of $\mathbb{R}$ ,	result: sequence of $\mathbb{R}$	DataMissingError,
	AADTT: sequence of $\mathbb{R}$ ,		DataInvalidError
	t1: sequence of $\mathbb{R}$ , $h_{total}$ :		
	sequence of $\mathbb{R}$ , t2: se-		
	quence of $\mathbb{R}$		
savefile	long: sequence of $\mathbb{R}$ , lat:	file: String	-
	sequence of $\mathbb{R}$ , results:		
	sequence of $\mathbb{R}$		

#### 18.4 Semantics

# 18.4.1 State Variables

None

#### 18.4.2 Environment Variables

File: the result of calculation will be stored in an output csv file.

#### 18.4.3 Assumptions

The map of Ontario is divided into multiple 25km \* 25km grid (as mentioned in SRS) and the coordinates are the center of those grids. The locations inside each grid are consider to have same chloride exposure rate.

#### 18.4.4 Access Routine Semantics

calculate( $AADT, AADTT, t1, h_{total}, t2$ ):

- transition: use all the formulas from calculate\_step1 to calculate\_step6, conclude the final result
- output: out := result # Sequence of  $\mathbb{R}$
- exception: exc:=

Expression	Exception
$\exists e \in [AADT, AADTT, h_{total}, t1, t2], e = \emptyset$	DataMissingError
$(\exists i \in [0 AADT  - 1], AADTT[i] > AADT[i]) \lor (\neg(t1, t2 \in (0, 365)))$	DataInvalidError

# savefile(long, lat, results):

- transition: Save the longitude, latitude and the corresponding results for each grid to a csv file, which is the prediction of chloride exposure rate. The file has a row label as coordinate and a column label as year.
- output: out := file
- exception: exc := None

#### 18.4.5 Local Functions