DNS, codecs, and the default voice

Keep practitioner numbers in their own column.

Sources and go deeper

Technical requirements PDF. vendor. https://documentation-be.five9.com/bundle/five9-technical-requirements/raw/resource/enus/five9-technical-requirements.pdf. last checked 2026-10.
SIP trunk options chapter. vendor. https://documentation.five9.com/bundle/technical-reqs/page/technical-reqs/SIP-trunk-options/_ch-five9-sip-trunk-options.htm. last checked 2026-10.
RFC 3261. rfc. https://www.rfc-editor.org/rfc/rfc3261. last checked 2026-10.
RFC 4733. rfc. https://www.rfc-editor.org/rfc/rfc4733. last checked 2026-10.
RFC 3550, RTP. rfc. https://www.rfc-editor.org/rfc/rfc3550. last checked 2026-10.
RFC 3551, RTP profile for audio and video. rfc. https://www.rfc-editor.org/rfc/rfc3551. last checked 2026-10.
ITU-T G.711. standard. https://www.itu.int/rec/T-REC-G.711. last checked 2026-10.
RFC 1035, domain names. rfc. https://www.rfc-editor.org/rfc/rfc1035. last checked 2026-10.
RFC 2782, DNS SRV. rfc. https://www.rfc-editor.org/rfc/rfc2782. last checked 2026-10.
confirm. A 20 ms packet time is a practitioner note about Cisco gateways, not a figure quoted from the Five9 technical requirements in this lab.. last checked 2026-10.