Headsets, and the call that only fails one way Worked example

Use the debug order on a fictional one-way call.
Path
NAT
Headset
You named a layer before you named a vendor ticket.

Sources and go deeper
Technical requirements PDF. vendor. https://documentation-be.five9.com/bundle/five9-technical-requirements/raw/resource/enus/five9-technical-requirements.pdf. last checked 2026-10.
RFC 3261, SIP: Session Initiation Protocol. rfc. https://www.rfc-editor.org/rfc/rfc3261. last checked 2026-10.
RFC 3550, RTP. rfc. https://www.rfc-editor.org/rfc/rfc3550. last checked 2026-10.
RFC 3551, RTP profile for audio and video. rfc. https://www.rfc-editor.org/rfc/rfc3551. last checked 2026-10.
ITU-T G.711. standard. https://www.itu.int/rec/T-REC-G.711. last checked 2026-10.
RFC 8446, TLS 1.3. rfc. https://www.rfc-editor.org/rfc/rfc8446. last checked 2026-10.
RFC 1918, private internet addresses. rfc. https://www.rfc-editor.org/rfc/rfc1918. last checked 2026-10.
RFC 4787, NAT behavior for UDP. rfc. https://www.rfc-editor.org/rfc/rfc4787. last checked 2026-10.