NAT, idle timers, and split tunnels Learn it in 5 minutes

NAT and PAT are acceptable. Double NAT is not. UDP bindings that idle out cause one-way audio. The requirements use a 30 second UDP idle timeout as the planning number, and they tell you to send keepalives when the binding is shorter.
On a VPN, translate RFC 1918 space to a public address the far side can route. Do not exclude Five9 domains from a split tunnel and then wonder why signaling dies. Do not restrict SIP or RTP between sites.

Sources and go deeper
Technical requirements PDF. vendor. https://documentation-be.five9.com/bundle/five9-technical-requirements/raw/resource/enus/five9-technical-requirements.pdf. last checked 2026-10.
RFC 1918. rfc. https://www.rfc-editor.org/rfc/rfc1918. last checked 2026-10.
RFC 3261. rfc. https://www.rfc-editor.org/rfc/rfc3261. last checked 2026-10.
RFC 3550, RTP. rfc. https://www.rfc-editor.org/rfc/rfc3550. last checked 2026-10.
RFC 3551, RTP profile for audio and video. rfc. https://www.rfc-editor.org/rfc/rfc3551. last checked 2026-10.
ITU-T G.711. standard. https://www.itu.int/rec/T-REC-G.711. last checked 2026-10.
RFC 768, User Datagram Protocol. rfc. https://www.rfc-editor.org/rfc/rfc768. last checked 2026-10.
RFC 4787, NAT behavior for UDP. rfc. https://www.rfc-editor.org/rfc/rfc4787. last checked 2026-10.