80 TCP Outbound: HTTP for sign-in, reporting, and support pages.
443 TCP Outbound: HTTPS for sign-in, reporting, and support.
1024-65535 UDP Outbound: RTP between Five9 applications. Without a stateful firewall, allow the return path. WebRTC also sends STUN on these ports.
2200-2300 TCP Outbound: Encrypted Java RMI on the community softphone table. Java Agent and Supervisor desktops left the customer portal after 1 August 2026. Confirm whether your site still launches Java admin.
5060-5067 UDP Outbound: SIP for the agent application.
5080 UDP Outbound: SIP signaling on the Five9 SIP proxy.
5081 TCP Outbound: SIP over TLS on the Five9 SIP proxy.
8000-8015 UDP Outbound: Source ports the article lists for desktop RTP.
8080/8081 TCP Outbound: Network assessment at quality.five9.com.
8083 TCP Local: Five9 Softphone Service. The article says to keep other processes off it, and to open it on the host firewall when VDI needs it.
8843 TCP Outbound: HTTPS download of Five9 applications and API.
8880 TCP Outbound: HTTP download of Five9 applications.
443 TCP Outbound: Supervisor PC to WEM cloud, application access.
4443 TCP Outbound: Supervisor or admin workstation to the VO cloud for the Interaction Analytics UI.

CYPHER0X9 Five9 Lab. Independent study. Not affiliated with Five9.
https://cyphermonkeylabs.com
https://linktr.ee/cyphermonkey
https://github.com/cipher0x9/five9-lab-free-university-mesmerizing
MIT code, CC BY-NC-SA content. Trademarks belong to their owners.