448 CARDS

Flashcard deck

FOUNDATIONS AND HOW TO READ A CALL · 1

SIP

Application signaling for sessions. The base specification is RFC 3261.

RFC 3261

FOUNDATIONS AND HOW TO READ A CALL · 2

SDP

Describes media. Offer/answer is RFC 3264.

RFC 3264

FOUNDATIONS AND HOW TO READ A CALL · 3

RTP

Carries the media packets after the answer names the port.

RFC 3550

FOUNDATIONS AND HOW TO READ A CALL · 4

100 Trying

Hop-by-hop provisional. A stateful proxy generates it and does not relay one.

RFC 3261 §16

FOUNDATIONS AND HOW TO READ A CALL · 5

5060

Default port for SIP over UDP and SIP over TCP.

RFC 3261 §18

FOUNDATIONS AND HOW TO READ A CALL · 6

5061

Default port for SIP over TLS.

RFC 3261 §18

FOUNDATIONS AND HOW TO READ A CALL · 7

Content-Length

On a stream transport, this is how the parser finds the end of the message.

RFC 3261 §7

FOUNDATIONS AND HOW TO READ A CALL · 8

WS / WSS

WebSocket transport tokens from RFC 7118. The SIP methods do not change.

RFC 7118

FOUNDATIONS AND HOW TO READ A CALL · 9

tel:+15551212

A global telephone URI. The scheme is RFC 3966.

RFC 3966

FOUNDATIONS AND HOW TO READ A CALL · 10

user=phone

The sip user part should be read as a phone number.

RFC 3261

FOUNDATIONS AND HOW TO READ A CALL · 11

E.164

The ITU-T numbering plan. The URI citation in this course is RFC 3966.

RFC 3966

FOUNDATIONS AND HOW TO READ A CALL · 12

Request-URI

Where this hop sends the request. Retargeting changes it and leaves To in place.

RFC 3261 §8

FOUNDATIONS AND HOW TO READ A CALL · 13

Standards Track

The status of RFC 3261. It is the base specification.

RFC 3261

FOUNDATIONS AND HOW TO READ A CALL · 14

Section 20

Header field catalog, including the compact names defined there.

RFC 3261 §20

FOUNDATIONS AND HOW TO READ A CALL · 15

Section 21

Response code catalog.

RFC 3261 §21

FOUNDATIONS AND HOW TO READ A CALL · 16

Section 25

ABNF. Use it when a message looks almost right.

RFC 3261 §25

FOUNDATIONS AND HOW TO READ A CALL · 17

RFC 5411

Informational hitchhiker's guide. A map, not the base spec.

RFC 5411

FOUNDATIONS AND HOW TO READ A CALL · 18

RFC 3262

PRACK and reliable provisional responses.

RFC 3262

FOUNDATIONS AND HOW TO READ A CALL · 19

RFC 4028

Session timers. Not a substitute chapter inside 5411.

RFC 4028

FOUNDATIONS AND HOW TO READ A CALL · 20

RFC 6026

Corrects INVITE 2xx transaction handling after 3261.

RFC 6026

FOUNDATIONS AND HOW TO READ A CALL · 21

IETF Trust

Legal provisions for IETF documents. Read them before copying protocol text.

IETF Trust Legal Provisions

FOUNDATIONS AND HOW TO READ A CALL · 22

Opus

RFC 6716, plus the Opus license page and the IETF IPR disclosures.

RFC 6716

FOUNDATIONS AND HOW TO READ A CALL · 23

G.711

ITU-T recommendation for PCMU and PCMA. Not an IETF RFC.

ITU-T G.711

FOUNDATIONS AND HOW TO READ A CALL · 24

G.729

ITU-T recommendation. Verify patent status. Do not state an expiry date.

ITU-T G.729

FOUNDATIONS AND HOW TO READ A CALL · 25

z9hG4bK

Magic cookie at the start of a branch parameter.

RFC 3261 §8.1.1.7

FOUNDATIONS AND HOW TO READ A CALL · 26

Max-Forwards: 70

The value a UAC SHOULD put on a request it originates.

RFC 3261 §8.1.1.6

FOUNDATIONS AND HOW TO READ A CALL · 27

No To tag

An initial request is outside a dialog, so To has no tag.

RFC 3261 §12

FOUNDATIONS AND HOW TO READ A CALL · 28

RFC 5737

Documentation IPv4 ranges used for the examples in this course.

RFC 5737

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 29

UAC

Creates a request. Defined with the rest of the user-agent rules.

RFC 3261 §8

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 30

Stateful proxy

Transaction state, own Via branch, own 100 Trying.

RFC 3261 §16

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 31

Redirect

3xx and a Contact, then it is out of the call.

RFC 3261

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 32

B2BUA

UAS plus UAC. Expect a second dialog. See RFC 7092.

RFC 7092

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 33

INVITE / ACK / BYE

Set up, complete the handshake, and end a confirmed dialog.

RFC 3261

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 34

CANCEL

Abandon an unanswered INVITE. It is not BYE.

RFC 3261

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 35

401 vs 407

UAS or registrar challenge versus proxy challenge.

RFC 3261 §22

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 36

1xx

Provisional. The transaction is still waiting for a final response.

RFC 3261 §21

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 37

v / f / t / i

Via, From, To, Call-ID.

RFC 3261 §20

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 38

m / l / c / k

Contact, Content-Length, Content-Type, Supported.

RFC 3261 §20

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 39

o and u

Event and Allow-Events. RFC 6665.

RFC 6665

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 40

r and b

Refer-To and Referred-By. RFC 3515.

RFC 3515

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 41

Branch

Transaction identifier. Cookie z9hG4bK plus a unique token.

RFC 3261 §8.1.1.7

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 42

Retransmission

Same message, same branch, sent again by the transaction timer.

RFC 3261 §17

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 43

2xx ACK

New transaction, new branch, end to end. CSeq number matches the INVITE.

RFC 6026

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 44

Timer B

INVITE transaction timeout, 64 times T1. No ACK is generated.

RFC 3261 §17

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 45

Call-ID + tags

The dialog id. Both tags are required once the dialog exists.

RFC 3261 §12

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 46

Early

Provisional response with a To tag. Not confirmed yet.

RFC 3261 §12

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 47

Confirmed

A 2xx to INVITE. BYE is now the teardown.

RFC 3261 §13

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 48

CSeq

Increments for new in-dialog requests. ACK and CANCEL keep the INVITE number.

RFC 3261 §8

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 49

T1 = 500 ms

Default RTT estimate. Timer A starts here on UDP.

RFC 3261 §17

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 50

64*T1

Timer B for INVITE and Timer F for non-INVITE.

RFC 3261 §17

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 51

T2 = 4 s, T4 = 5 s

Retransmit cap, and how long a message may remain in the network.

RFC 3261 §17

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 52

Timer C

Proxy timer for an unanswered INVITE. More than 3 minutes.

RFC 3261 §16

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 53

Via transport

UDP, TCP, TLS, WS, or WSS for this hop.

RFC 3261 §18

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 54

received / rport

Response address and, with RFC 3581, the source port.

RFC 3581

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 55

session protocol sipv2

Dial-peer command that selects SIP for that peer.

Cisco CUBE basic SIP configuration

SIP CORE: MESSAGES, TRANSACTIONS, DIALOGS · 56

ip address trusted list

Sources allowed to present SIP. See the toll-fraud guidance.

Cisco CME toll-fraud prevention

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 57

Non-2xx ACK

Same branch as that hop's INVITE. Generated by the client transaction.

RFC 3261 §17

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 58

2xx ACK

New branch, dialog route set, end to end.

RFC 6026

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 59

CSeq: 1 ACK

Same number as the INVITE. The method token changes to ACK.

RFC 3261 §8

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 60

603 then ACK

Forward the 603. ACK it on this hop. Do not relay the ACK.

RFC 3261 §16

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 61

Record-Route

Inserted by a proxy that must see later requests in the dialog.

RFC 3261 §16

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 62

lr

Required on that URI. It selects loose routing.

RFC 3261 §16

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 63

UAC reverses

Response Record-Route, reversed, becomes the caller's route set.

RFC 3261 §12

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 64

Contact

The remote target. It becomes the mid-dialog Request-URI.

RFC 3261 §12

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 65

Supported: 100rel

The UAC can do reliable provisionals.

RFC 3262

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 66

RSeq

Identifies the reliable provisional.

RFC 3262

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 67

RAck

RSeq, then the CSeq number and method being acknowledged.

RFC 3262

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 68

PRACK

A new transaction. Its success response is 200 OK, not ACK.

RFC 3262

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 69

UPDATE

Session refresh or change. Own transaction. RFC 3311.

RFC 3311

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 70

No ACK

200 OK finishes UPDATE. ACK is reserved for INVITE.

RFC 3311

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 71

Early dialog

UPDATE can run before the first INVITE completes.

RFC 3311

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 72

RFC 6141

Read this before changing the remote target.

RFC 6141

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 73

Session-Expires

Seconds until the session must be refreshed, plus an optional refresher.

RFC 4028

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 74

Min-SE

Minimum interval. Never below 90 seconds.

RFC 4028

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 75

422

Session Interval Too Small. Retry with the Min-SE from the response.

RFC 4028

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 76

refresher

uac or uas. That side sends re-INVITE or UPDATE.

RFC 4028

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 77

CANCEL

Same branch as the unanswered INVITE. CSeq number unchanged.

RFC 3261

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 78

487

Final response to the INVITE that was cancelled. Then ACK.

RFC 3261 §21

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 79

BYE

Ends a confirmed dialog. Higher CSeq. Both tags.

RFC 3261 §12

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 80

re-INVITE

Mid-dialog INVITE. See RFC 6141 if Contact changes the target.

RFC 6141

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 81

Refer-To

The request the recipient should send. Compact form r.

RFC 3515

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 82

202 Accepted

REFER was accepted. Watch NOTIFY for the real result.

RFC 3515

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 83

Replaces

call-id, to-tag, from-tag of the dialog to take over.

RFC 3891

CALL FLOWS THAT OPERATORS ACTUALLY TRACE · 84

sipfrag

A status line in the NOTIFY body, such as SIP/2.0 200 OK.

RFC 3515

REGISTRATION, DNS, AND ROUTING · 85

To on REGISTER

The address-of-record being bound.

RFC 3261 §10

REGISTRATION, DNS, AND ROUTING · 86

Contact

The binding: where requests for that address-of-record can go.

RFC 3261 §10

REGISTRATION, DNS, AND ROUTING · 87

423

Interval Too Brief. Read Min-Expires and retry.

RFC 3261 §21

REGISTRATION, DNS, AND ROUTING · 88

Contact: *

With Expires: 0, removes all bindings for the address-of-record.

RFC 3261 §10

REGISTRATION, DNS, AND ROUTING · 89

NAPTR

Selects the SIP service, such as SIP+D2U or SIP+D2T.

RFC 3263

REGISTRATION, DNS, AND ROUTING · 90

SRV

Host and port for the selected service.

RFC 3263

REGISTRATION, DNS, AND ROUTING · 91

A / AAAA

Addresses for the SRV target.

RFC 3263

REGISTRATION, DNS, AND ROUTING · 92

Numeric IP

No domain lookup. Send to that address.

RFC 3263

REGISTRATION, DNS, AND ROUTING · 93

lr

Loose routing. Pop Route, keep the Request-URI.

RFC 3261 §16

REGISTRATION, DNS, AND ROUTING · 94

Max-Forwards

Starts at 70. Decremented by each proxy.

RFC 3261 §8.1.1.6

REGISTRATION, DNS, AND ROUTING · 95

483

Too Many Hops. The request arrived with Max-Forwards 0.

RFC 3261 §21

REGISTRATION, DNS, AND ROUTING · 96

482

Loop Detected from a Via loop, not from the hop budget.

RFC 3261 §16

REGISTRATION, DNS, AND ROUTING · 97

reg-id

Identifies one flow. A new value is a new flow.

RFC 5626

REGISTRATION, DNS, AND ROUTING · 98

+sip.instance

URN for the UA instance, stable across flows.

RFC 5626

REGISTRATION, DNS, AND ROUTING · 99

CRLF keepalive

Double CRLF on connection-oriented transports. Single CRLF answers.

RFC 5626

REGISTRATION, DNS, AND ROUTING · 100

STUN keepalive

The UDP keepalive in the outbound specification.

RFC 5626

REGISTRATION, DNS, AND ROUTING · 101

Path

Inbound vector stored with the binding. RFC 3327.

RFC 3327

REGISTRATION, DNS, AND ROUTING · 102

Service-Route

Outbound preloaded route from the registrar. RFC 3608.

RFC 3608

REGISTRATION, DNS, AND ROUTING · 103

lr on Path

The edge URI is loose-routed, same as Record-Route.

RFC 3327

REGISTRATION, DNS, AND ROUTING · 104

Preloaded Route

The UA puts Service-Route into Route on a new INVITE.

RFC 3608

REGISTRATION, DNS, AND ROUTING · 105

pub-gruu

Stable URI for one UA instance.

RFC 5627

REGISTRATION, DNS, AND ROUTING · 106

temp-gruu

Instance URI that hides the address-of-record.

RFC 5627

REGISTRATION, DNS, AND ROUTING · 107

+sip.instance

The URN the registrar binds to those GRUUs.

RFC 5627

REGISTRATION, DNS, AND ROUTING · 108

gr

URI parameter that marks a GRUU.

RFC 5627

REGISTRATION, DNS, AND ROUTING · 109

Fork

One incoming INVITE, one client transaction per target.

RFC 3261 §16

REGISTRATION, DNS, AND ROUTING · 110

Early dialog

A To tag on a provisional response. One per branch.

RFC 3261 §12

REGISTRATION, DNS, AND ROUTING · 111

Multiple 200 OK

Forward each. The UAC ACKs each and may BYE the extras.

RFC 3261 §13

REGISTRATION, DNS, AND ROUTING · 112

6xx

Cancel the other pending branches. Do not start new ones.

RFC 3261 §16

SDP AND OFFER/ANSWER · 113

RFC 8866

Current SDP. It obsoletes RFC 4566. Trust the RFC Editor status banner.

RFC 8866

SDP AND OFFER/ANSWER · 114

c=

Connection address where media should be sent.

RFC 8866

SDP AND OFFER/ANSWER · 115

m=

One media stream: type, port, protocol, and payload types.

RFC 8866

SDP AND OFFER/ANSWER · 116

a=

An attribute. After m=, it belongs to that stream.

RFC 8866

SDP AND OFFER/ANSWER · 117

Same count

The answer has exactly as many m-lines as the offer.

RFC 3264

SDP AND OFFER/ANSWER · 118

Same order

Line n in the answer answers line n in the offer.

RFC 3264

SDP AND OFFER/ANSWER · 119

Port 0

Rejects that stream and keeps its position.

RFC 3264

SDP AND OFFER/ANSWER · 120

RFC 6337

Usage examples and the pitfalls of rebuilding SDP.

RFC 6337

SDP AND OFFER/ANSWER · 121

Encoding name

Match opus to opus even when the payload type numbers differ.

RFC 3264

SDP AND OFFER/ANSWER · 122

0 / 8 / 9 / 18

PCMU/8000, PCMA/8000, G722/8000, G729/8000.

RFC 3551

SDP AND OFFER/ANSWER · 123

G722/8000

RTP clock is 8000. Audio sample rate is 16 kHz.

RFC 3551

SDP AND OFFER/ANSWER · 124

fmtp

Parameters for one payload type. Do not guess unknown ones.

RFC 8866

SDP AND OFFER/ANSWER · 125

sendrecv

Send and receive. The usual active call.

RFC 3264

SDP AND OFFER/ANSWER · 126

sendonly

Send, and do not receive. A common hold.

RFC 3264

SDP AND OFFER/ANSWER · 127

recvonly

Receive only. The usual answer to sendonly.

RFC 3264

SDP AND OFFER/ANSWER · 128

inactive

Neither direction. Also a common hold.

RFC 3264

SDP AND OFFER/ANSWER · 129

m=audio 0

Rejects that audio stream. Keep proto and a format.

RFC 3264

SDP AND OFFER/ANSWER · 130

Same index

A rejected line is still answered in its original position.

RFC 3264

SDP AND OFFER/ANSWER · 131

No common codec

Port 0 on that m-line, not a deleted body.

RFC 3264

SDP AND OFFER/ANSWER · 132

Offer port 0

The answer port is also 0.

RFC 3264

SDP AND OFFER/ANSWER · 133

183 + SDP

Usual early-media pattern. Not true of every 183.

RFC 3960

SDP AND OFFER/ANSWER · 134

180

Ringing. Local ringback when this message has no SDP.

RFC 3261 §21

SDP AND OFFER/ANSWER · 135

100rel

Makes a provisional response reliable. PRACK it.

RFC 3262

SDP AND OFFER/ANSWER · 136

Two bodies

Compare 183 SDP with the 200 OK SDP before you lock the port.

RFC 6337

SDP AND OFFER/ANSWER · 137

RFC 6337

Offer/answer usage and the mistakes to stop repeating.

RFC 6337

SDP AND OFFER/ANSWER · 138

sess-version

Increase it when the SDP changes.

RFC 8866

SDP AND OFFER/ANSWER · 139

Delayed offer

No SDP in the INVITE. Offer in the reliable response. Answer in the ACK.

RFC 3264

SDP AND OFFER/ANSWER · 140

Do not rebuild

Edit m-lines in place. Do not drop, swap, or renumber them.

RFC 6337

RTP, CODECS, AND DTMF · 141

V=2

RTP version is 2.

RFC 3550

RTP, CODECS, AND DTMF · 142

Sequence

Plus one for every packet from that source.

RFC 3550

RTP, CODECS, AND DTMF · 143

Timestamp

Media clock. 20 ms of G.711 or G.722 steps by 160.

RFC 3550

RTP, CODECS, AND DTMF · 144

SSRC

32-bit source id chosen by the sender.

RFC 3550

RTP, CODECS, AND DTMF · 145

PT 0

PCMU/8000, static.

RFC 3551

RTP, CODECS, AND DTMF · 146

PT 8

PCMA/8000, static. Not the same as PCMU.

RFC 3551

RTP, CODECS, AND DTMF · 147

PT 9

G722/8000. Sample rate is still 16 kHz.

RFC 3551

RTP, CODECS, AND DTMF · 148

PT 18

G729/8000, static.

RFC 3551

RTP, CODECS, AND DTMF · 149

G.711

PCMU/8000 and PCMA/8000. Read ITU-T G.711. They are not interchangeable.

ITU-T G.711

RTP, CODECS, AND DTMF · 150

G.729

rtpmap G729/8000, static PT 18. Read ITU-T G.729. This course states no licensing result.

ITU-T G.729

RTP, CODECS, AND DTMF · 151

Opus

RFC 6716. Read the RFC and the license.

RFC 6716

RTP, CODECS, AND DTMF · 152

IPR

Check IETF IPR disclosures. This course states no legal result.

IETF IPR disclosures

RTP, CODECS, AND DTMF · 153

SR

Sender report. Used when this participant has sent RTP.

RFC 3550

RTP, CODECS, AND DTMF · 154

RR

Receiver report. Fraction lost, cumulative loss, jitter.

RFC 3550

RTP, CODECS, AND DTMF · 155

Port pair

RTP on an even port, RTCP on the next higher port, by default.

RFC 3550

RTP, CODECS, AND DTMF · 156

Not SIP

200 OK does not carry fraction lost.

RFC 3550

RTP, CODECS, AND DTMF · 157

RFC 4733

telephone-event. Obsoletes RFC 2833. Trust the status banner.

RFC 4733

RTP, CODECS, AND DTMF · 158

Events 0-15

DTMF. Event 16 is flash.

RFC 4733

RTP, CODECS, AND DTMF · 159

Dynamic PT

Match the name telephone-event in SDP.

RFC 4733

RTP, CODECS, AND DTMF · 160

Not INFO

RFC 6086 is a method. application/dtmf-relay is a vendor body.

RFC 6086

RTP, CODECS, AND DTMF · 161

a=ptime:20

20 ms of media per packet. SDP, not RTP.

RFC 8866

RTP, CODECS, AND DTMF · 162

50 and 160

G.711 at 20 ms: 50 packets/s, 160 payload bytes, plus headers.

RFC 3551

RTP, CODECS, AND DTMF · 163

EF

Voice service class in RFC 4594.

RFC 4594

RTP, CODECS, AND DTMF · 164

RFC 3246

Defines the EF per-hop behavior. No router config in this lesson.

RFC 3246

RTP, CODECS, AND DTMF · 165

200 OK

Offer/answer finished. It does not prove both RTP directions.

RFC 3264

RTP, CODECS, AND DTMF · 166

sendonly answer

Answerer sends, does not receive. One-way by negotiation.

RFC 3264

RTP, CODECS, AND DTMF · 167

c= and port

The destination you must capture.

RFC 8866

RTP, CODECS, AND DTMF · 168

SR from one side

The other side is not sending, according to RTCP.

RFC 3550

TLS, SRTP, IDENTITY, AND ABUSE · 169

401

From the UAS. Challenge is WWW-Authenticate. Retry with Authorization.

RFC 3261 §22

TLS, SRTP, IDENTITY, AND ABUSE · 170

407

From the proxy. Challenge is Proxy-Authenticate. Retry with Proxy-Authorization.

RFC 3261 §22

TLS, SRTP, IDENTITY, AND ABUSE · 171

RFC 7616

HTTP digest algorithms. Read the algorithm parameter.

RFC 7616

TLS, SRTP, IDENTITY, AND ABUSE · 172

Stop here

Identify the header. Do not compute a digest in this lesson.

RFC 3261 §22

TLS, SRTP, IDENTITY, AND ABUSE · 173

RFC 3261 §18

SIP over TLS. Same methods. Via transport TLS.

RFC 3261 §18

TLS, SRTP, IDENTITY, AND ABUSE · 174

5061

Usual TLS port in RFC 3261.

RFC 3261 §18

TLS, SRTP, IDENTITY, AND ABUSE · 175

RFC 5922

The certificate must identify the SIP domain.

RFC 5922

TLS, SRTP, IDENTITY, AND ABUSE · 176

Not SRTP

TLS on SIP does not select the media keying method.

RFC 3261 §18

TLS, SRTP, IDENTITY, AND ABUSE · 177

RFC 3711

SRTP. Protects RTP. Profile RTP/SAVP.

RFC 3711

TLS, SRTP, IDENTITY, AND ABUSE · 178

RFC 4568

SDES. a=crypto in SDP. Protect the signaling.

RFC 4568

TLS, SRTP, IDENTITY, AND ABUSE · 179

RFC 5764

DTLS-SRTP. Keys from DTLS. Fingerprint in SDP.

RFC 5764

TLS, SRTP, IDENTITY, AND ABUSE · 180

Per leg

Do not assume two peers share one keying method.

RFC 5764

TLS, SRTP, IDENTITY, AND ABUSE · 181

RFC 3323

Privacy header. id withholds a network-asserted identity.

RFC 3323

TLS, SRTP, IDENTITY, AND ABUSE · 182

PPI

P-Preferred-Identity. A hint from the UA inside the trust domain.

RFC 3325

TLS, SRTP, IDENTITY, AND ABUSE · 183

PAI

P-Asserted-Identity. Trusted networks only. Not a signature.

RFC 3325

TLS, SRTP, IDENTITY, AND ABUSE · 184

Strip

Remove PAI and PPI when the request leaves the trust domain.

RFC 3325

TLS, SRTP, IDENTITY, AND ABUSE · 185

RFC 8224

STIR. Identity header in SIP.

RFC 8224

TLS, SRTP, IDENTITY, AND ABUSE · 186

RFC 8225

PASSporT.

RFC 8225

TLS, SRTP, IDENTITY, AND ABUSE · 187

RFC 8226

Certificates for STIR.

RFC 8226

TLS, SRTP, IDENTITY, AND ABUSE · 188

Levels A/B/C

ATIS SHAKEN. Confirm the current ATIS document. See also the FCC page.

FCC call authentication

TLS, SRTP, IDENTITY, AND ABUSE · 189

Scanning

Unsolicited SIP from addresses you did not provision. Close the exposure.

RFC 3261 §22

TLS, SRTP, IDENTITY, AND ABUSE · 190

Hijack

Unexpected Contact on an address-of-record. Authenticate REGISTER.

RFC 3261 §10

TLS, SRTP, IDENTITY, AND ABUSE · 191

Toll fraud

Unauthorized calls that run up charges. Authorize the source.

Cisco CME toll-fraud prevention

TLS, SRTP, IDENTITY, AND ABUSE · 192

FCC page

Call authentication is not a substitute for outbound authorization.

FCC call authentication

TLS, SRTP, IDENTITY, AND ABUSE · 193

Allow list

Named peers only. See the CME toll-fraud guide for trusted sources.

Cisco CME toll-fraud prevention

TLS, SRTP, IDENTITY, AND ABUSE · 194

Digest

401 uses Authorization. 407 uses Proxy-Authorization.

RFC 3261 §22

TLS, SRTP, IDENTITY, AND ABUSE · 195

RFC 5922

Certificate name equals the SIP domain.

RFC 5922

TLS, SRTP, IDENTITY, AND ABUSE · 196

Per-leg SRTP

Do not copy keying from one peer to another.

RFC 3711

NAT, ICE, AND THE ALG PROBLEM · 197

Embedded

Via, Contact, and SDP c= carry addresses NAT does not rewrite.

RFC 3261

NAT, ICE, AND THE ALG PROBLEM · 198

c=

Media destination. A private value is non-routable on the public Internet.

RFC 8866

NAT, ICE, AND THE ALG PROBLEM · 199

200 OK

Signaling can succeed while RTP still cannot go where c= points.

RFC 3264

NAT, ICE, AND THE ALG PROBLEM · 200

RFC 5737

203.0.113.10 and the other lab addresses are documentation ranges.

RFC 5737

NAT, ICE, AND THE ALG PROBLEM · 201

RFC 3581

rport. Symmetric SIP response routing.

RFC 3581

NAT, ICE, AND THE ALG PROBLEM · 202

received

Source address the server saw.

RFC 3581

NAT, ICE, AND THE ALG PROBLEM · 203

rport value

Source port the server saw.

RFC 3581

NAT, ICE, AND THE ALG PROBLEM · 204

Not SDP

rport does not rewrite c=.

RFC 3581

NAT, ICE, AND THE ALG PROBLEM · 205

RFC 8489

Current STUN. Obsoletes RFC 5389. Trust the status banner.

RFC 8489

NAT, ICE, AND THE ALG PROBLEM · 206

Binding

Request that asks what address the server sees.

RFC 8489

NAT, ICE, AND THE ALG PROBLEM · 207

XOR-MAPPED-ADDRESS

The reflexive address in the success response.

RFC 8489

NAT, ICE, AND THE ALG PROBLEM · 208

Not SIP

A STUN server does not store a SIP Contact.

RFC 8489

NAT, ICE, AND THE ALG PROBLEM · 209

RFC 8656

Current TURN. Obsoletes RFC 5766. Trust the status banner.

RFC 8656

NAT, ICE, AND THE ALG PROBLEM · 210

Allocate

Reserves a relayed transport address.

RFC 8656

NAT, ICE, AND THE ALG PROBLEM · 211

Relay

Peers send media to the relay. TURN forwards it.

RFC 8656

NAT, ICE, AND THE ALG PROBLEM · 212

Not SIP

Allocate is not REGISTER and not an SDP rewrite.

RFC 8656

NAT, ICE, AND THE ALG PROBLEM · 213

RFC 8445

Current ICE. Obsoletes RFC 5245. Trust the status banner.

RFC 8445

NAT, ICE, AND THE ALG PROBLEM · 214

host

Local interface.

RFC 8445

NAT, ICE, AND THE ALG PROBLEM · 215

srflx / relay

STUN reflexive address, and TURN relay.

RFC 8489

NAT, ICE, AND THE ALG PROBLEM · 216

prflx

Discovered during a connectivity check.

RFC 8445

NAT, ICE, AND THE ALG PROBLEM · 217

ALG

In-path SIP and SDP rewrite. Often corrupts the call.

RFC 8866

NAT, ICE, AND THE ALG PROBLEM · 218

Length

If Content-Length does not match the body, the edit is corrupt.

RFC 3261

NAT, ICE, AND THE ALG PROBLEM · 219

TLS

The ALG cannot rewrite what it cannot see.

RFC 3261 §18

NAT, ICE, AND THE ALG PROBLEM · 220

Disable it

Turn the ALG off. Do not stack a second hidden editor.

RFC 3261

NAT, ICE, AND THE ALG PROBLEM · 221

Latch

Learn the remote RTP address from the first packet instead of trusting c=.

RFC 5853

NAT, ICE, AND THE ALG PROBLEM · 222

RFC 5853

SBC requirements. Not an IETF algorithm for latching.

RFC 5853

NAT, ICE, AND THE ALG PROBLEM · 223

Authenticated

Latch only after signaling is accepted, and only toward the expected side.

RFC 3261 §22

NAT, ICE, AND THE ALG PROBLEM · 224

ICE

RFC 8445 is the specified candidate check when both ends use it.

RFC 8445

SESSION BORDER CONTROLLERS · 225

RFC 5853

Informational requirements from SBC deployments. Not an SBC protocol.

RFC 5853

SESSION BORDER CONTROLLERS · 226

No SBC method

INVITE and OPTIONS stay as RFC 3261 defined them.

RFC 3261

SESSION BORDER CONTROLLERS · 227

Datasheet

Session and transcode limits are platform-specific.

RFC 5853

SESSION BORDER CONTROLLERS · 228

B2BUA

The usual SIP role behind an SBC. Taxonomy is RFC 7092.

RFC 7092

SESSION BORDER CONTROLLERS · 229

B2BUA

UAS plus UAC. Two dialogs for one call.

RFC 7092

SESSION BORDER CONTROLLERS · 230

Pure proxy

Forwards the request and adds Via.

RFC 3261 §16

SESSION BORDER CONTROLLERS · 231

Call-ID

Often different on the two legs of an SBC.

RFC 7092

SESSION BORDER CONTROLLERS · 232

RFC 3261

Defines the B2BUA as UAS concatenated with UAC.

RFC 3261

SESSION BORDER CONTROLLERS · 233

Via

Identifies the previous SIP hop. Hide the internal one.

RFC 3261

SESSION BORDER CONTROLLERS · 234

Contact

Dialog target. An SBC usually substitutes its own.

RFC 7092

SESSION BORDER CONTROLLERS · 235

c=

SDP connection address. Anchoring rewrites it.

RFC 3264

SESSION BORDER CONTROLLERS · 236

User-Agent

A common topology leak. Stripping it is a product rule.

RFC 5853

SESSION BORDER CONTROLLERS · 237

Anchor

RTP terminates on the SBC. SDP c= names the SBC.

RFC 3550

SESSION BORDER CONTROLLERS · 238

Bypass

SIP through the SBC. Media between endpoints.

RFC 3264

SESSION BORDER CONTROLLERS · 239

Transcode

Decode and encode. Capacity is on the datasheet.

RFC 5853

SESSION BORDER CONTROLLERS · 240

telephone-event

RFC 4733 DTMF in RTP.

RFC 4733

SESSION BORDER CONTROLLERS · 241

OPTIONS

Capability and liveness request. RFC 3261.

RFC 3261 §11

SESSION BORDER CONTROLLERS · 242

CSeq method

Must match the start line. OPTIONS stays OPTIONS.

RFC 3261 §8

SESSION BORDER CONTROLLERS · 243

200 OK

The peer answered. The call is a later transaction.

RFC 3261 §21

SESSION BORDER CONTROLLERS · 244

Interval

Configured on the product. Not an RFC constant.

RFC 5853

SESSION BORDER CONTROLLERS · 245

Admission

Refuse new work when the configured budget is exhausted.

RFC 5853

SESSION BORDER CONTROLLERS · 246

503

Service Unavailable. Confirm the product’s actual code.

RFC 3261 §21

SESSION BORDER CONTROLLERS · 247

Datasheet

The only source for this platform’s session limit.

RFC 5853

SESSION BORDER CONTROLLERS · 248

No CPS formula

Do not invent calls-per-second math.

RFC 5853

SESSION BORDER CONTROLLERS · 249

Active

The unit currently processing the dialogs.

RFC 5853

SESSION BORDER CONTROLLERS · 250

Standby

Ready to take the role. Not a SIP method.

RFC 5853

SESSION BORDER CONTROLLERS · 251

No timer here

Do not invent a failover interval.

RFC 5853

SESSION BORDER CONTROLLERS · 252

Dialog state

A B2BUA holds it. Survival is a product question.

RFC 7092

CISCO CUBE, CUCM, AND UNITY CONNECTION · 253

CUBE

Cisco Unified Border Element. An IOS XE B2BUA.

Cisco CUBE basic SIP configuration

CISCO CUBE, CUCM, AND UNITY CONNECTION · 254

IOS XE

The operating system whose voice stack CUBE uses.

Cisco CUBE basic SIP configuration

CISCO CUBE, CUCM, AND UNITY CONNECTION · 255

SIP profiles

Header modifications. Guide for 17.6 and later.

Cisco CUBE SIP profiles (IOS XE 17.6+)

CISCO CUBE, CUCM, AND UNITY CONNECTION · 256

B2BUA

The role RFC 7092 taxonomizes.

RFC 7092

CISCO CUBE, CUCM, AND UNITY CONNECTION · 257

dial-peer voice N voip

Creates the VoIP dial peer numbered N.

Cisco CUBE basic SIP configuration

CISCO CUBE, CUCM, AND UNITY CONNECTION · 258

session protocol sipv2

This dial peer speaks SIP.

Cisco CUBE basic SIP configuration

CISCO CUBE, CUCM, AND UNITY CONNECTION · 259

session target ipv4:

The next-hop IPv4 address.

Cisco CUBE basic SIP configuration

CISCO CUBE, CUCM, AND UNITY CONNECTION · 260

192.0.2.40

Carrier address in this synthetic.

RFC 5737

CISCO CUBE, CUCM, AND UNITY CONNECTION · 261

sip-profiles

voice class sip-profiles N holds the rules.

Cisco CUBE SIP profiles (IOS XE 17.6+)

CISCO CUBE, CUCM, AND UNITY CONNECTION · 262

remove

request INVITE sip-header Diversion remove.

Cisco CUBE SIP profiles (IOS XE 17.6+)

CISCO CUBE, CUCM, AND UNITY CONNECTION · 263

After 15.4

Inbound profile support, per the use-case technote.

Cisco SIP profile use cases

CISCO CUBE, CUCM, AND UNITY CONNECTION · 264

CSA tester

Try the profile before loading it.

Cisco Collaboration Solutions Analyzer

CISCO CUBE, CUCM, AND UNITY CONNECTION · 265

Delayed offer

INVITE without SDP. Offer comes later.

RFC 3264

CISCO CUBE, CUCM, AND UNITY CONNECTION · 266

Early offer

The INVITE already contains the offer.

RFC 3264

CISCO CUBE, CUCM, AND UNITY CONNECTION · 267

early-offer forced

Dial-peer command that forces an outbound offer.

Cisco CUBE basic SIP configuration

CISCO CUBE, CUCM, AND UNITY CONNECTION · 268

ACK answer

Used when the offer arrived in the 200 OK.

RFC 3264

CISCO CUBE, CUCM, AND UNITY CONNECTION · 269

SIP trunk

CUCM's adjacency to CUBE or another peer.

Cisco Unified Communications Manager

CISCO CUBE, CUCM, AND UNITY CONNECTION · 270

CUCM SIP profile

Not voice class sip-profiles.

Cisco Unified Communications Manager

CISCO CUBE, CUCM, AND UNITY CONNECTION · 271

Lua

Normalization scripts exist. Open the admin guide.

Cisco Unified Communications Manager

CISCO CUBE, CUCM, AND UNITY CONNECTION · 272

MTP required

Confirm the guide for that version before checking it.

Cisco Unified Communications Manager

CISCO CUBE, CUCM, AND UNITY CONNECTION · 273

SIP integration

The documented Unity Connection path. Open your version’s guide.

Cisco Unity Connection

CISCO CUBE, CUCM, AND UNITY CONNECTION · 274

Diversion

RFC 5806 redirecting number. Reason unconditional in the lab.

RFC 5806

CISCO CUBE, CUCM, AND UNITY CONNECTION · 275

History-Info

RFC 7044. Use it if the guide asks for it.

RFC 7044

CISCO CUBE, CUCM, AND UNITY CONNECTION · 276

Not SCCP-by-guess

Do not invent SCCP as the current default.

Cisco Unity Connection

CISCO CUBE, CUCM, AND UNITY CONNECTION · 277

debug ccsip messages

Shows sent and received SIP.

Cisco CUBE basic SIP configuration

CISCO CUBE, CUCM, AND UNITY CONNECTION · 278

sip-profiles debug

debug ccsip feature sip-profiles.

Cisco CUBE SIP profiles (IOS XE 17.6+)

CISCO CUBE, CUCM, AND UNITY CONNECTION · 279

CSA

SIP Profile Tester in Collaboration Solutions Analyzer.

Cisco Collaboration Solutions Analyzer

CISCO CUBE, CUCM, AND UNITY CONNECTION · 280

Sent / Received

Direction markers around each SIP message.

Cisco CUBE basic SIP configuration

ORACLE, RIBBON, AND AUDIOCODES · 281

realm

Routing and policy context on the Oracle SBC.

Oracle Communications SBC documentation

ORACLE, RIBBON, AND AUDIOCODES · 282

session-agent

Named next hop.

Oracle Communications SBC documentation

ORACLE, RIBBON, AND AUDIOCODES · 283

in-manipulationid

Which sip-manipulation runs on arrival.

Oracle SBC HMR configuration (10.1)

ORACLE, RIBBON, AND AUDIOCODES · 284

out-manipulationid

Which sip-manipulation runs on the way out.

Oracle SBC HMR configuration (10.1)

ORACLE, RIBBON, AND AUDIOCODES · 285

header-rule

One rule inside a sip-manipulation.

Oracle SBC HMR configuration (10.1)

ORACLE, RIBBON, AND AUDIOCODES · 286

delete

Removes the named header. Lab rule strip-server.

Oracle SBC HMR fundamentals (10.1)

ORACLE, RIBBON, AND AUDIOCODES · 287

store

Keeps a value for a later rule. Run it first.

Oracle SBC HMR fundamentals (10.1)

ORACLE, RIBBON, AND AUDIOCODES · 288

reject

An HMR action. Read the release guide for the status.

Oracle SBC HMR fundamentals (10.1)

ORACLE, RIBBON, AND AUDIOCODES · 289

SWe Edge

Edge product. Family includes SBC 1000 and SBC 2000.

Ribbon SBC SWe Edge

ORACLE, RIBBON, AND AUDIOCODES · 290

SBC Core

A separate family.

Ribbon SBC SWe Edge

ORACLE, RIBBON, AND AUDIOCODES · 291

ACS snapshot

5110, 5210, 5400, 7000, and SWe for that validation.

Ribbon documentation portal

ORACLE, RIBBON, AND AUDIOCODES · 292

No invented CLI

Admin guides live on the documentation portal.

Ribbon documentation portal

ORACLE, RIBBON, AND AUDIOCODES · 293

Action Subject

Which header or element the rule touches.

AudioCodes SIP message manipulation (7.6)

ORACLE, RIBBON, AND AUDIOCODES · 294

Action Type

Add, Remove, Modify, prefix, suffix, or Normalize.

AudioCodes manipulation syntax 7.6

ORACLE, RIBBON, AND AUDIOCODES · 295

IP group

Inbound or outbound assignment of the set.

AudioCodes SIP message manipulation (7.6)

ORACLE, RIBBON, AND AUDIOCODES · 296

Release menu

The clicks change. Use the 7.6 manual you are running.

AudioCodes SIP message manipulation (7.6)

ORACLE, RIBBON, AND AUDIOCODES · 297

CUBE line

request INVITE sip-header NAME remove.

Cisco CUBE SIP profiles (IOS XE 17.6+)

ORACLE, RIBBON, AND AUDIOCODES · 298

Oracle block

header-rule, header-name, action delete.

Oracle SBC HMR fundamentals (10.1)

ORACLE, RIBBON, AND AUDIOCODES · 299

AudioCodes row

Action Type Remove on an IP group.

AudioCodes SIP message manipulation (7.6)

ORACLE, RIBBON, AND AUDIOCODES · 300

Do not paste across

Each grammar is parsed by its own product.

Oracle SBC HMR configuration (10.1)

ORACLE, RIBBON, AND AUDIOCODES · 301

PAI

P-Asserted-Identity, RFC 3325.

RFC 3325

ORACLE, RIBBON, AND AUDIOCODES · 302

Privacy

RFC 3323. id asks the network to withhold identity.

RFC 3323

ORACLE, RIBBON, AND AUDIOCODES · 303

Diversion

RFC 5806 redirecting header.

RFC 5806

ORACLE, RIBBON, AND AUDIOCODES · 304

History-Info

RFC 7044. Map it only as the interop guide says.

RFC 7044

ORACLE, RIBBON, AND AUDIOCODES · 305

RFC 5922

SIP domain certificates.

RFC 5922

ORACLE, RIBBON, AND AUDIOCODES · 306

Teams Contact

FQDN. An IP draws 403.

Direct Routing SIP protocol

ORACLE, RIBBON, AND AUDIOCODES · 307

Teams wildcard

CN or SAN wildcards are supported for Direct Routing.

Plan Direct Routing

ORACLE, RIBBON, AND AUDIOCODES · 308

Webex LGW wildcard

Not supported for Local Gateway.

Get started with Local Gateway

CLOUD VOICE AND CCAAS SIP · 309

pstnhub

sip, sip2, and sip3.pstnhub.microsoft.com.

Direct Routing SIP protocol

CLOUD VOICE AND CCAAS SIP · 310

5061

Direct Routing signaling port.

Direct Routing SIP protocol

CLOUD VOICE AND CCAAS SIP · 311

Verified domain

Not a name ending in onmicrosoft.com.

Plan Direct Routing

CLOUD VOICE AND CCAAS SIP · 312

No RFC 5923

The SIP proxy does not support connection aliasing.

Direct Routing definitions and RFCs

CLOUD VOICE AND CCAAS SIP · 313

OPTIONS 200

Marks the Direct Routing SBC healthy.

Direct Routing OPTIONS and TLS

CLOUD VOICE AND CCAAS SIP · 314

CSeq

Method token matches the request. OPTIONS, not INVITE.

RFC 3261 §8

CLOUD VOICE AND CCAAS SIP · 315

Table cell

Checked 2026-10-14: CSeq: 1 INVITE. Do not copy it.

Direct Routing SIP protocol

CLOUD VOICE AND CCAAS SIP · 316

SRTP

Media processors use SRTP. RFC 3711.

RFC 3711

CLOUD VOICE AND CCAAS SIP · 317

SIP TLS

Signaling from an IOS XE Local Gateway to Webex.

Local Gateway on IOS XE

CLOUD VOICE AND CCAAS SIP · 318

SRTP

Media for that IOS XE Local Gateway.

Local Gateway on IOS XE

CLOUD VOICE AND CCAAS SIP · 319

Certificate trunk

How a third-party SBC is supported.

Webex Calling trunks and dial plans

CLOUD VOICE AND CCAAS SIP · 320

ByoPSTN

Bring your own PSTN. Not Cloud Connected PSTN.

Get started with Local Gateway

CLOUD VOICE AND CCAAS SIP · 321

Cisco Calling Plan

One of the three organization-article choices.

Configure Webex Calling PSTN

CLOUD VOICE AND CCAAS SIP · 322

Cloud Connected PSTN

A cloud partner through Webex. Not the Local Gateway.

Configure Webex Calling PSTN

CLOUD VOICE AND CCAAS SIP · 323

Local Gateway

Premises-based PSTN. One connection on the location.

Get started with Local Gateway

CLOUD VOICE AND CCAAS SIP · 324

ByoPSTN

Bring your own PSTN.

Get started with Local Gateway

CLOUD VOICE AND CCAAS SIP · 325

Managed PSTN

Ordinary Connect calls. No customer SIP trunk required.

Amazon Connect telephony

CLOUD VOICE AND CCAAS SIP · 326

SIPREC

External voice into the analytics connector.

Connect conversational analytics connector

CLOUD VOICE AND CCAAS SIP · 327

Voice Connector

Chime SDK SIP trunking service.

Amazon Chime SDK Voice Connector

CLOUD VOICE AND CCAAS SIP · 328

Not a bridge

Carrier through Voice Connector into Connect needs specialist approval.

Voice Connector and Connect

CLOUD VOICE AND CCAAS SIP · 329

BYO SIP

Your ITSP or gateway connects to Five9 SBCs.

Five9 BYO SIP trunking

CLOUD VOICE AND CCAAS SIP · 330

Entitled groups

Self-service exists for entitled BYO SIP trunk groups.

Five9 BYO SIP trunking

CLOUD VOICE AND CCAAS SIP · 331

Termination URI

Must appear in the Request-URI or Twilio drops the request.

Twilio trunk troubleshooting

CLOUD VOICE AND CCAAS SIP · 332

sip not sips

Origination URLs use sip. sips is not supported.

Twilio Elastic SIP Trunking API

CLOUD VOICE AND CCAAS SIP · 333

BYOC Cloud

Public internet SIP. RTP crosses the internet.

Genesys BYOC Cloud overview

CLOUD VOICE AND CCAAS SIP · 334

BYOC Premises

Customer-managed Edge. Hybrid media is allowed.

BYOC Cloud with BYOC Premises

CLOUD VOICE AND CCAAS SIP · 335

December 1, 2026

Genesys Hardware Solution only.

About BYOC Premises

CLOUD VOICE AND CCAAS SIP · 336

CXone ports

5060 and 5061, plus dynamic RTP/SRTP.

NiCE CXone ports

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 337

Call-ID

Same value for the dialog. A B2BUA may use a new one on the other leg.

RFC 3261 §8

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 338

CSeq

Integer plus method. The ACK for an INVITE keeps the INVITE's number.

RFC 3261 §8

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 339

Via branch

Transaction hop id. Look for the z9hG4bK cookie.

RFC 3261 §17

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 340

2xx ACK

End to end. New branch. RFC 6026 corrects the transaction rules around it.

RFC 6026

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 341

180

Ringing. Provisional alerting.

RFC 3261 §21

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 342

183

Session Progress. Provisional, often where early media shows up.

RFC 3261 §21

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 343

487

Request Terminated. The INVITE's answer after CANCEL.

RFC 3261 §21

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 344

606

Not Acceptable. Global. 488 is only this UA.

RFC 3261 §21

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 345

sip

Display filter for SIP packets. Field names live on the SIP reference page.

Wireshark SIP display filter reference

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 346

rtp

Display filter for RTP packets. Field names live on the RTP reference page.

Wireshark RTP display filter reference

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 347

sip.Method

Safe display field for the SIP method.

Wireshark SIP display filter reference

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 348

Confirm CSeq

sip.CSeq.method is common. Confirm it on the SIP display-filter reference.

Wireshark SIP display filter reference

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 349

ccsip messages

IOS voice debug that prints SIP send and receive.

Cisco CUBE basic SIP configuration

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 350

ccapi inout

IOS voice debug of the call-control API. Not a SIP RFC.

Cisco CUBE basic SIP configuration

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 351

Sent / Received

Direction on the debug. The SIP start line comes after it.

RFC 3261

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 352

Synthetic

Lab output in this track is synthetic. Customer logs stay out.

RFC 3261

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 353

488

Not Acceptable Here. This UA. Often codec or SDP.

RFC 3261 §21

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 354

422

Session Interval Too Small. RFC 4028. Read Min-SE.

RFC 4028

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 355

telephone-event

RFC 4733. Offer it on purpose if you need DTMF.

RFC 4733

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 356

Offer/answer

The answer is a subset. No shared audio codec tends to 488.

RFC 3264

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 357

Name mismatch

Handshake fails. No SIP status from the peer.

Direct Routing OPTIONS and TLS

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 358

Untrusted CA

Handshake fails. Fix the trust anchor.

Direct Routing OPTIONS and TLS

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 359

TLS 1.2+

Teams Direct Routing floor in the OPTIONS troubleshooting page.

Direct Routing OPTIONS and TLS

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 360

FQDN Contact

Required toward Teams. An address literal draws 403.

Direct Routing SIP protocol

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 361

Category

Read it on the header. 3261 is Standards Track. 6881 is BCP.

RFC 3261

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 362

Obsoletes

The new RFC names the one it replaces. 8866 and 4566 are the SDP pair here.

RFC 8866

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 363

Updates

A correction that leaves the base in force. Check 6026's header.

RFC 6026

TROUBLESHOOTING LADDERS, CAPTURES, AND DEBUG · 364

rfc-editor.org

The header you cite. Months in this lesson are not invented.

RFC 5411

TOLL FRAUD, E911, RECORDING, AND QOS · 365

Trusted list

Who may present VoIP signaling. CME and SRST each have a page.

Cisco CME toll-fraud prevention

TOLL FRAUD, E911, RECORDING, AND QOS · 366

401 / 407

UAS and proxy digest challenges. Secrets stay unprinted.

RFC 3261 §22

TOLL FRAUD, E911, RECORDING, AND QOS · 367

Numbering plan

Dial-peers match the plan, including whether international destinations are in it.

Cisco CME toll-fraud prevention

TOLL FRAUD, E911, RECORDING, AND QOS · 368

STIR context

FCC call authentication and RFC 8224. A different question from the source list.

FCC call authentication

TOLL FRAUD, E911, RECORDING, AND QOS · 369

trusted list

Addresses allowed to present inbound VoIP. CME page or SRST page.

Cisco CME toll-fraud prevention

TOLL FRAUD, E911, RECORDING, AND QOS · 370

authenticate

The check that uses the list.

Cisco CME toll-fraud prevention

TOLL FRAUD, E911, RECORDING, AND QOS · 371

Two pages

CME and SRST differ. Quote no shared list size.

Cisco SRST trusted IP authentication

TOLL FRAUD, E911, RECORDING, AND QOS · 372

Border pair

198.51.100.30 and 192.0.2.40 in the teaching snippet.

Cisco CME toll-fraud prevention

TOLL FRAUD, E911, RECORDING, AND QOS · 373

urn:service:sos

RFC 5031 service URN for emergency calling.

RFC 5031

TOLL FRAUD, E911, RECORDING, AND QOS · 374

RFC 6881

BCP for emergency calling services.

RFC 6881

TOLL FRAUD, E911, RECORDING, AND QOS · 375

Geolocation

RFC 6442 location conveyance.

RFC 6442

TOLL FRAUD, E911, RECORDING, AND QOS · 376

fcc-mlts

Kari's Law and RAY BAUM's Act. The page wins over a retelling.

FCC MLTS 911 requirements

TOLL FRAUD, E911, RECORDING, AND QOS · 377

7866

Session recording protocol. SRC forks to an SRS.

RFC 7866

TOLL FRAUD, E911, RECORDING, AND QOS · 378

7865

Recording metadata. Read it for fields.

RFC 7865

TOLL FRAUD, E911, RECORDING, AND QOS · 379

Disclosed

Quality monitoring and compliance, with the parties on notice.

RFC 7866

TOLL FRAUD, E911, RECORDING, AND QOS · 380

Retention

A legal question. Outside the RFC.

RFC 7865

TOLL FRAUD, E911, RECORDING, AND QOS · 381

EF

Expedited Forwarding per-hop behavior. RFC 3246.

RFC 3246

TOLL FRAUD, E911, RECORDING, AND QOS · 382

Telephony

The service class RFC 4594 maps to EF.

RFC 4594

TOLL FRAUD, E911, RECORDING, AND QOS · 383

Codepoint

Use the value RFC 3246 recommends. Do not invent a second one.

RFC 3246

TOLL FRAUD, E911, RECORDING, AND QOS · 384

Not a LAN

Queues and campus policy stay in the approved design.

RFC 4594

TOLL FRAUD, E911, RECORDING, AND QOS · 385

OPTIONS

Liveness. Alarm when the trunk stops answering.

RFC 3261 §11

TOLL FRAUD, E911, RECORDING, AND QOS · 386

503

Service Unavailable. Page the server-side class.

RFC 3261 §21

TOLL FRAUD, E911, RECORDING, AND QOS · 387

TLS floor

Toward Teams, 1.2 or newer, or the handshake never yields SIP.

Direct Routing OPTIONS and TLS

TOLL FRAUD, E911, RECORDING, AND QOS · 388

SRS down

Recording-session alarm. RFC 7866. Retention stays outside the RFC.

RFC 7866

TOLL FRAUD, E911, RECORDING, AND QOS · 389

Baseline

The last good OPTIONS or the current snippet, written down.

RFC 3261 §11

TOLL FRAUD, E911, RECORDING, AND QOS · 390

One variable

A single address, codec, or TLS setting.

RFC 3264

TOLL FRAUD, E911, RECORDING, AND QOS · 391

Verify

One signal. A 200, or the test call to +15551212.

RFC 3261

TOLL FRAUD, E911, RECORDING, AND QOS · 392

Rollback

The previous value of that same variable.

Cisco CUBE basic SIP configuration

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 393

Role

What the box does on the ladder: UA, proxy, registrar, B2BUA.

RFC 3261

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 394

B2BUA

UAS plus UAC. RFC 7092. Typical SBC.

RFC 7092

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 395

Document

The cite you can open. A logo is not a document.

RFC 5411

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 396

SDP row

RFC 8866 now. RFC 4566 is the one it moved from.

RFC 8866

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 397

WFM / QM

Operations systems. No SIP RFC in this library.

RFC 7866

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 398

SIPREC

The recording neighbor that is SIP. RFC 7866 and RFC 7865.

RFC 7865

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 399

CRM

Not a SIP element. No invented vendor features.

RFC 3261

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 400

Above the media

Analytics and agents. SIP and RTP still carry the session.

RFC 3550

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 401

Above RTP

Analytics and agents. The packets remain RTP.

RFC 3550

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 402

Dialog

Still Call-ID, CSeq, To tag. RFC 3261.

RFC 3261 §12

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 403

Disclosed fork

SIPREC when the SBC records. RFC 7866.

RFC 7866

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 404

No invented features

Vendor guides or an honest gap. Not a fake RFC.

RFC 3261

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 405

SSCA

SIP School Certified Associate. 20 CEC credits toward BICSI, per the SSCA page.

SSCA Elite

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 406

CLCOR

350-801. Core for CCNP Collaboration and the Collaboration Core specialist.

350-801 CLCOR

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 407

Concentrations

300-815 CLACC, 300-820 CLHCT, or 300-830 CLCCE. One of them, plus the core.

CCNP Collaboration

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 408

MS-721

Collaboration Communications Systems Engineer Associate. Certifications change. Use the link.

MS-721 certification

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 409

Banner

RFC Editor header beats a blog.

RFC 5411

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 410

Cisco page

Exam topics change. The Cisco page wins.

Cisco exams list

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 411

MS-721 link

Certifications change. Use the certification page.

MS-721 certification

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 412

Checked dates

February 3, 2026. April 28, 2026. October 29, 2026. Source check 2026-10-14.

Cisco certification updates

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 413

CUCM

Registrar and trunk call-control point.

Cisco Unified Communications Manager

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 414

UCCX

Call control through CUCM. Not the carrier trunk.

Cisco Unified Contact Center Express

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 415

CUBE or CUCM

Where PSTN SIP lands.

Cisco CUBE basic SIP configuration

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 416

CVP

SIP among CVP, gateways, and CUCM, in that version's guide.

Cisco Unified Customer Voice Portal

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 417

Local Gateway

Premises PSTN pattern for Webex Calling.

Get started with Local Gateway

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 418

Organization PSTN

Configured on the Webex Calling PSTN page.

Configure Webex Calling PSTN

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 419

Placeholder host

example.com stands in so the lesson does not invent the edge FQDN.

Get started with Local Gateway

ECOSYSTEM, CERTIFICATIONS, AND THE UC BRIDGE · 420

Separate product

Webex Contact Center. Check its current design guide.

Configure Webex Calling PSTN

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 421

Call-ID + To tag

Dialog match. No To tag on a brand-new INVITE.

RFC 3261 §12

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 422

Branch

Transaction hop. z9hG4bK.

RFC 3261 §17

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 423

2xx ACK

End to end. RFC 6026.

RFC 6026

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 424

487

INVITE's final response after CANCEL. ACK is hop by hop.

RFC 3261 §21

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 425

488

This UA. Session description. RFC 3261 and RFC 3264.

RFC 3264

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 426

422

RFC 4028. Raise the session interval to Min-SE.

RFC 4028

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 427

telephone-event

RFC 4733. DTMF in the offer you mean.

RFC 4733

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 428

Keying

RFC 3711 plus either RFC 4568 or RFC 5764. Record which.

RFC 4568

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 429

RFC 7092

B2BUA taxonomy. New Call-ID on the other leg is normal.

RFC 7092

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 430

RFC 5853

SBC deployment requirements.

RFC 5853

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 431

Trunk landing

CUBE or CUCM. Not UCCX.

Cisco CUBE basic SIP configuration

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 432

Teams pair

TLS 1.2+ and an FQDN in Contact.

Direct Routing SIP protocol

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 433

Symptom

Silence after connect, Alice at 203.0.113.10. Written first.

RFC 3261

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 434

Ladder

INVITE, 100, 180, 200, end-to-end ACK. One Call-ID.

RFC 6026

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 435

One packet

200 OK SDP. 203.0.113.20, UDP 19642, PCMU.

RFC 3264

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 436

One variable

Capture that port. Config edits wait, and then they are single.

RFC 3550

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 437

Six rows

TLS, codecs, numbering, trusted addresses, OPTIONS, SRTP keying.

RFC 3264

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 438

telephone-event

On the codec row on purpose. RFC 4733.

RFC 4733

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 439

E.164

Number form. tel URI is RFC 3966.

RFC 3966

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 440

Not a dump

Decisions only. No private key, no full dial-peer list.

Cisco CUBE basic SIP configuration

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 441

Path

CUCM, then a certified SBC, then Teams. No invented SKU.

Plan Direct Routing

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 442

CUBE guide

Basic SIP configuration for the CUBE case.

Cisco CUBE basic SIP configuration

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 443

TLS 1.2+

Teams floor. Handshake failures are not SIP codes.

Direct Routing OPTIONS and TLS

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 444

FQDN Contact

sbc.example.com in the lab. An address literal draws 403.

Direct Routing SIP protocol

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 445

SDP

RFC 4566 moved to RFC 8866.

RFC 8866

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 446

ICE

RFC 5245 moved to RFC 8445. Confirm the banner.

RFC 8445

INTERVIEWS, INCIDENTS, AND DESIGN DRILLS · 447

STUN / TURN

RFC 8489 and RFC 8656 in this library. Predecessors 5389 and 5766.

RFC 8489

Banner

A newer obsoleting RFC that this edition does not cite still wins.

RFC 5411

Independent educational project, not affiliated with or endorsed by any vendor. Trademarks belong to their owners. MIT code, CC BY-NC-SA content.