Bandwidth sketch

G.711 20 ms payload is 160 bytes.
IP, UDP, and RTP add 40 bytes.
Layer 3 is about 80 kbit/s.
An 18-byte Ethernet header makes about 87.2 kbit/s.
Size the priority queue from admitted calls.
Formula: (payload + 40 + L2) x 8 x (1000 / ptime) / 1000.

Independent free learning-only student project. Trademarks belong to their owners. Not affiliated or endorsed. Contact: https://cyphermonkeylabs.com/#contact. Nothing is sold.

Sources and go deeper
Opened 2026-10. A row marked confirm has no link, because that page was not verified.
ITU. ITU-T G.711, pulse code modulation of voice. https://www.itu.int/rec/T-REC-G.711. last checked 2026-10
RFC. RFC 3550, RTP. https://www.rfc-editor.org/rfc/rfc3550. last checked 2026-10
RFC. RFC 4594, DiffServ service classes. https://www.rfc-editor.org/rfc/rfc4594. last checked 2026-10
Community. Cisco Community, Collaboration knowledge base. https://community.cisco.com/t5/collaboration-knowledge-base/tkb-p/4691-docs-collaboration-voice-video. last checked 2026-10
Wikipedia. Quality of service (Wikipedia). https://en.wikipedia.org/wiki/Quality_of_service. last checked 2026-10
Cisco. Enterprise QoS SRND book. confirm. The Enterprise QoS SRND path returned HTTP 404. last checked 2026-10