UC flashcards

Transaction — A request and its matching responses.
Dialog — A peer relationship identified by Call-ID and tags.
SIP transactions and dialogs — A transaction pairs a request with its responses.
A 180 Ringing means the call was answered. — False. False. It means alerting. The 200 accepts the session.
ACK for a 2xx is optional. — False. False. Without ACK the far end retransmits the 200 and can drop the call.
Early offer — SDP in the INVITE.
Delayed offer — SDP offered in the reliable response or the 200.
Offer and answer — SDP is the offer or the answer, not a second signaling protocol you ignore.
The answer may add a codec the offer did not list. — False. False. The answer narrows the offer.
AOR — The address-of-record being registered.
Contact — The device URI to try later.
Registration — REGISTER publishes a Contact. It does not place a call.
REGISTER creates a voice session. — False. False. It stores a Contact binding.
PRACK — Acknowledgement of a reliable provisional response.
100rel — The extension that makes selected 1xx responses reliable.
Early media and PRACK — 183 Session Progress can carry SDP before answer.
Hearing ringback proves the called party answered. — False. False. Ringback can be early media.
Partition — A group of patterns with the same reachability.
CSS — An ordered list of partitions.
Partitions and calling search spaces — A partition is a bucket of patterns.
CUCM searches every partition and picks the longest match across all of them. — False. False. It walks the CSS in order.
Route pattern — Digits in a partition that point at a gateway or route list.
Route list — An ordered set of route groups.
Route patterns, lists, and groups — A route pattern matches digits.
A route group is a list of partitions. — False. False. It is a list of gateways or trunks.
Translation pattern — A pattern that transforms digits and can continue routing.
Mask — A digit rewrite applied to a number field.
Transformations — Called, calling, and redirecting numbers are different fields.
The calling number and the called number are the same field. — False. False.
SIP trunk — CUCM's signaling peer toward a gateway or another call agent.
SIP profile — Timers, OPTIONS, and offer behavior for that trunk.
SIP trunks on CUCM — The trunk, the SIP profile, and the security profile are three objects.
A SIP trunk in service proves the route pattern points at it. — False. False. Routing and

status are separate.
Dial peer — An IOS rule that matches a call and names a target.
Preference — A tie-break after match length.
Dial peers — A dial peer matches an incoming or outgoing call.
Outbound dial-peer preference is consulted before match length. — False. False. Longest match comes first when hunt is the default.
B2BUA — A user agent that sits between two dialogs.
Media anchor — RTP terminates on the SBC.
CUBE as a B2BUA — CUBE terminates one dialog and starts another.
CUBE forwards one SIP dialog unchanged, like a proxy. — False. False. It is a B2BUA.
SRST — Fallback call processing on the branch router.
Re-home — Phones returning to CUCM after the WAN recovers.
SRST — SRST is the fallback when phones cannot reach CUCM.
SRST automatically clones every CUCM hunt pilot. — False. False.
Local gateway — The premises SBC that connects Webex Calling to PSTN or a PBX.
Certificate trunk — A trunk that authenticates with a certificate instead of a registration.
Local gateway toward Webex Calling — The local gateway is how premises PSTN or a PBX meets Webex Calling.
A local gateway registration is the same object as a CUCM phone registration. — False. False. It is the trunk from CUBE toward Calling.
Traversal zone — The zone that joins Expressway-C and Expressway-E.
Expressway-E — The edge server.
Expressway-C and Expressway-E — Expressway-C lives on the inside, next to CUCM.
Every CUCM call must pass through Expressway. — False. False.
MRA — Mobile and Remote Access through Expressway.
SRV — A DNS record the client uses to find the edge.
Mobile and Remote Access — MRA lets a remote Cisco phone or Jabber register to CUCM through the Expressway pair.
MRA replaces CUCM as the registrar. — False. False. CUCM remains the registrar.
Traversal media — The UDP range Expressway uses for remote media.
Signaling — SIP or the HTTPS path used to register.
Firewall and traversal — Open the ports your version's guide lists.
A completed INVITE proves the firewall allows RTP. — False. False.
EF — Expedited Forwarding, DSCP 46.
Trust boundary — The place you decide to keep or rewrite a mark.
DSCP and the trust boundary — Voice RTP is commonly marked EF, DSCP 46.
EF and CS3 are the same mark. — False. False. EF is DSCP 46. CS3 is a different codepoint.
LLQ — A queue that serves a priority class up to a configured rate.
Packetization — The time to fill one RTP payload.
LLQ and the delay budget — Priority queue bandwidth is a limiter for the EF class.
LLQ adds bandwidth to a circuit. — False. False. It schedules the bandwidth you already

have.
Location — A CUCM bandwidth domain for admission control.
CAC — Call admission control, the decision to allow a call.
Locations and call admission control — A CUCM location names a bandwidth budget between sites.
CUCM locations mark RTP as EF. — False. False.
CVP — Customer Voice Portal, the voice browser and call-control front in many designs.
ICM — The routing brain in UCCE.
UCCE from carrier to agent — Ingress, routing, queue treatment, and the agent are different stages.
Queue music means an agent phone is ringing. — False. False. Treatment happens before delivery.
Label — The destination the script returns.
Peripheral gateway — The process that represents CUCM devices to ICM.
The CUCM bridge into UCCE — Agents are CUCM endpoints.
A successful ICM script guarantees CUCM can ring the phone. — False. False.
Flow — The routing document in Webex Contact Center.
Script — The routing document in ICM.
Webex Contact Center beside UCCE — Webex Contact Center and UCCE are different products.
An ICM script runs unchanged inside Webex Contact Center. — False. False.
Dedicated Instance — A hosted CUCM offer inside the Webex cloud contract.
Control Hub — The admin place for Webex Calling locations and numbers.
Webex Calling and Dedicated Instance — Multi-tenant Webex Calling and Dedicated Instance are different offers.
Dedicated Instance uses the same dial-plan objects as multi-tenant Calling. — False. False.
Dual-run — Old and new paths both available for a number during a test.
Rollback — Returning the number to the path you saved.
Dual-run and rollback — Move one number you can give back.
A carrier port can always be undone in five minutes. — False. False. Confirm the porting rules.
Survivability gateway — A local gateway mode that keeps selected Calling users up during a cloud outage.
Fallback test — A planned failure of the primary path.
Survivability during cutover — Cloud calling needs a plan for when the cloud path is down.
SRST protects Webex Calling apps with no extra design. — False. False.
Hypothesis — The single fault you are testing.
Evidence pack — The traces and notes that show the test.
One hypothesis, one change — Say what you think is broken, in one sentence.
Changing the CSS, the codec, and the gateway in one window is a clean test. — False. False.
Ladder — A drawing of messages between named boxes.

Cause — The reason phrase or Q.850 cause on a failure.
Reading a ladder — One leg at a time.
Two Call-IDs mean the trace is corrupt. — False. False. A B2BUA creates two dialogs.
SDP c= line — The address where media should be sent.
One-way audio — Media in a single direction.
One-way audio — Signaling can be perfect while RTP fails in one direction.
A 200 OK with SDP proves two-way audio. — False. False.

Independent free learning-only student project. Trademarks belong to their owners. Not affiliated or endorsed. Contact: https://cyphermonkeylabs.com/#contact. Nothing is sold.