

Just-in-Time Context for Agents

Lukas Domagala



A capable programmer.

Their project knowledge
resets every morning.

Start with a task.

Add a field to a form

VIEW	CONTROLLER	TEST
<code>*_view.clj</code> Existing controls Form conventions	<code>*_controller.clj</code> Coercion schemas Route reloads	<code>*_test.clj</code> Scenario setup Assertions Run the test

A controller change has a catch

```
apps/.../ui/.../thing_controller.clj
```

Reloading routes after a schema change

Reitit compiles routes at startup, so a coercion schema change doesn't affect the running router until routes are recompiled.

`:reload` updates the var but not the compiled router — the symptom is silently dropped form fields, no error, and REPL tests still pass because they bypass routing.

Excerpt from Scarlet's controller rule

A rule makes the connection

.cursor/rules/controller_patterns.mdc

```
---  
description: Controller conventions for this project  
globs: apps/**/ui/**/*_controller.clj  
alwaysApply: false  
---  
@doc/conventions/controller_conventions.md#route-coercion-schemas
```

Reloading routes after a schema change

Reitit compiles routes at startup, so a coercion schema change doesn't affect the running router until routes are recompiled. ``:reload`` updates the var but not the compiled router — the symptom is silently dropped form fields, no error, and REPL tests still pass because they bypass routing.

**Write down what matters.
Say when it matters.**

3.5 KB

Scarlet's CLAUDE.md

~220 KB

15 rules + the documents
they draw on

Whole files. The rules can select individual sections.

How much context is useful here?

What does the agent need to know for the decision it's about to make?



github.com/Cyrik/rule-fairy

