



TB/THB Precision Balance

General Specifications

Display
 16.5mm digit LCD display, with white LED backlight

Capacities 300g~3000g

Pan size Φ120mm, 124mm x 144mm Keyboard 7keys (Membrane keyboard)

Housing ABS plastic

Max. Divisions 30,000d/60,000d

ADC update ≤1/10 second

Operate Temp +5°C~+40°C

Power
 AC adapter (12V/500mA), Rechargeable battery(6V/1.2Ah)

Gross weight 2.9kg(with wind shield), 2.7kg(without wind shield)



- Up to 60,000 resolution
- Standard RS-232 interface
- Rechargeable battery provide up to 40 hours of continuous use (without backlight)
- Optional below weighing
- Application: 1. Percentage weighing 2. Counting 3. Accumulation
 - 4. Weighing units conversion






TB/THB Precision Balance

Model Name	Capacity	Readability	Division	Pan Size	Approx. weight	Approval
TB-300	300g	0.01g	30,000d	Φ120mm	2.3kg	CE
TB-600	600g	0.02g	30,000d	Φ120mm	2.3kg	CE
TB-1500	1500g	0.05g	30,000d	124x144mm	2.2kg	CE
TB-3000	3000g	0.1g	30,000d	124x144mm	2.2kg	CE
THB-300	300g	0.005g	60,000d	Φ120mm	2.3kg	CE
THB-600	600g	0.01g	60,000d	Φ120mm	2.3kg	CE
THB-1500	1500g	0.02g	60,000d	124x144mm	2.2kg	CE
THB-3000	3000g	0.05g	60,000d	124x144mm	2.2kg	CE

Options



Dimensions(mm)



Print formats

2012/03/07	13:38
PERCENT:	100.01%
2012/03/07	13:37
S/N0:	1
WEIGHT:	80.26 g
2012/03/07	13:37
S/NO:	1
TOTAL.WT:	80.26 g
2012/03/07	
PCS:	
UNIT.WT: 0	.40132 g
WEIGHT:	89 84 a