

# Computer Programming 143 – Lecture 21

## Pointers IV

Electrical and Electronic Engineering Department  
University of Stellenbosch

Prof Johan du Preez  
Mr Callen Fisher  
Dr Willem Jordaan  
Dr Hannes Pretorius  
Mr Willem Smit



## **Copyright**

Copyright © 2020 Stellenbosch University  
All rights reserved


## **Disclaimer**

This content is provided without warranty or representation of any kind. The use of the content is entirely at your own risk and Stellenbosch University (SU) will have no liability directly or indirectly as a result of this content.

The content must not be assumed to provide complete coverage of the particular study material. Content may be removed or changed without notice.

The video is of a recording with very limited post-recording editing. The video is intended for use only by SU students enrolled in the particular module.

# Module Overview



# Lecture Overview

- 1 Pointer Expressions and Pointer Arithmetic (7.8)
- 2 The Relationship Between Pointers and Arrays (7.9)
- 3 Dynamic Memory Allocation (12.3)

## 7.8 Pointer Expressions

### Arithmetic operations can be performed on pointers

- Increment/decrement pointer (++ or --)
- Add an integer to a pointer( + or += , - or -=)
- Pointers may be subtracted from each other
- Operations meaningless unless performed on an array


## 7.8 Pointer Expressions (cont...)

### 5-element `int` array on computer with 4-byte ints

```
int v[5];
```

```
int *vPtr = &v[0]; /* or int *vPtr = v; */
```

- `vPtr` points to first element `v[ 0 ]`
  - at address 3000 (`vPtr == 3000`)
- `vPtr ++;` sets `vPtr` to 3004
- `vPtr += 2;` sets `vPtr` to 3008
  - `vPtr` points to `v[ 2 ]` (incremented by 2), but the machine has 4-byte ints, so it points to address 3008



## 7.8 Pointer Expressions (cont...)


### Subtracting pointers

- Returns number of elements from one to the other.

```
int v[5], *vPtr0, *vPtr2; /* correct multi-pointer declaration */  
vPtr0 = &v[0];  
vPtr2 = &v[2];  
vPtr2 - vPtr0 would produce 2
```

### Pointer comparison ( <, == , > )

- See which pointer points to the earlier/later numbered array element
- $(vPtr+1) > vPtr$  will return true
- Also, see if a pointer points to nothing (NULL or 0)



## 7.8 Pointer Expressions (cont...)

### Pointers of the same type can be assigned to each other


- If not the same type, a cast operator must be used

```
int *vPtr0;  
char *vPtr2;  
vPtr2 = (char*)vPtr0;
```

- Exception: pointer to void (**type** void \*)
  - Generic pointer, represents any type
  - No casting needed to convert a pointer to void pointer
  - void pointers cannot be dereferenced



## 7.9 Pointers and Arrays



### Element `v[ 3 ]`

- Can be accessed by `*( vPtr + 3 )`
  - Where 3 is the offset. Called pointer/offset notation
- Can be accessed by `vPtr[ 3 ]`
  - Called pointer/subscript notation
  - `vPtr[ 3 ]` same as `v[ 3 ]`
- Can be accessed by performing pointer arithmetic on the array itself
  - `*( v + 3 )`

```
/* Using subscripting and pointer notations with arrays */
```

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int b[] = { 10, 20, 30, 40 }; /* initialize array b */
```

```
    int *bPtr = b; /* set bPtr to point to array b */
```

```
    int i; /* counter */
```

```
    int offset; /* counter */
```

```
/* output array b using array subscript notation */
```

```
printf( "Array b printed with:\nArray subscript notation\n" );
```

```
/* loop through array b */
```

```
for ( i = 0; i < 4; i++ ) {
```

```
    printf( "b[ %d ] = %d\n", i, b[ i ] );
```

```
} /* end for */
```

```
/* output array b using array name and pointer/offset notation */
```

```
printf( "\nPointer/offset notation where\n"  
        "the pointer is the array name\n" );
```

```

/* loop through array b */
for ( offset = 0; offset < 4; offset++ ) {
    printf( "( b + %d ) = %d\n", offset, *( b + offset ) );
} /* end for */

/* output array b using bPtr and array subscript notation */
printf( "\nPointer subscript notation\n" );
/* loop through array b */
for ( i = 0; i < 4; i++ ) {
    printf( "bPtr[ %d ] = %d\n", i, bPtr[ i ] );
} /* end for */

/* output array b using bPtr and pointer/offset notation */
printf( "\nPointer/offset notation\n" );
/* loop through array b */
for ( offset = 0; offset < 4; offset++ ) {
    printf( "( bPtr + %d ) = %d\n", offset, *( bPtr + offset ) );
} /* end for */

return 0;
}

```

Array b printed with:

Array subscript notation

b[ 0 ] = 10

b[ 1 ] = 20

b[ 2 ] = 30

b[ 3 ] = 40

Pointer/offset notation where the pointer is the array name

\*( b + 0 ) = 10

\*( b + 1 ) = 20

\*( b + 2 ) = 30

\*( b + 3 ) = 40

Pointer subscript notation

bPtr[ 0 ] = 10

bPtr[ 1 ] = 20

bPtr[ 2 ] = 30

bPtr[ 3 ] = 40

Pointer/offset notation

\*( bPtr + 0 ) = 10

\*( bPtr + 1 ) = 20

\*( bPtr + 2 ) = 30

\*( bPtr + 3 ) = 40

## 12.3 Dynamic Memory Allocation I

### malloc()

- Contained in `stdlib.h`
- Allocates memory during execution time
- `newPtr = malloc( numberOfElements * sizeof( int ) );`
  - Allocates memory for an array with `numberOfElements` number of `int` elements
  - Starting address of memory block is stored in `newPtr`

### free()

- Contained in `stdlib.h`
- Frees memory allocated previously
- Always free dynamically allocated memory to prevent memory leaks

```
#include <stdio.h>
#include <stdlib.h>

int main( void )
{
    int size; //number of memory units needed
    int counter;
    float *newPtr; // pointer to a float;
    float *myFloat; // pointer to a float
    float *myArray; // pointer for our "dynamic" array

    /*allocates memory using 'malloc' and set our float
    pointer to newPtr*/
    newPtr = malloc( sizeof( float ) );
    myFloat = newPtr;
    *myFloat = 42.13;

    printf( "Enter the number of array elements: " );
    scanf( "%d", &size );
}
```

```

/*allocates memory for an array with 'size' number of type float
elements and set our array pointer to newPtr*/
newPtr = malloc( size * sizeof( float ) );
myArray = newPtr;

// assigns values to array elements
for ( counter = 0; counter < size; counter++ ) {
    myArray[ counter ] = (float)counter/2;
}
// displays all the array elements
printf( "\nArray is:\n" );
for ( counter = 0; counter < size; counter++ ) {
    printf( "%3.2f ", myArray[ counter ] );
    if ( ( counter + 1 ) % 20 == 0 ) {
        printf( "\n" );
    }
}
free( myFloat ); // frees the memory allocated to 'myFloat'
free( myArray ); // frees the memory allocated to 'myArray'
return 0; // indicates successful termination
} // end main

```

## Today

### Pointers IV

- Pointer expressions and arithmetic
- Pointers and arrays
- Dynamic memory allocation

## Next lecture

### Pointers V



# Homework

- 1 Study Sections 7.8-7.9, 12.3 in Deitel & Deitel
- 2 Do Self Review Exercises 7.2, 7.3 in Deitel & Deitel
- 3 Do Exercises 7.9, 7.21 in Deitel & Deitel