

Computer Programming 143 – Lecture 8

Program Control II

Electrical and Electronic Engineering Department
University of Stellenbosch

Prof Johan du Preez
Mr Callen Fisher
Dr Willem Jordaan
Dr Hannes Pretorius
Mr Willem Smit



Copyright

Copyright © 2020 Stellenbosch University
All rights reserved


Disclaimer

This content is provided without warranty or representation of any kind. The use of the content is entirely at your own risk and Stellenbosch University (SU) will have no liability directly or indirectly as a result of this content.

The content must not be assumed to provide complete coverage of the particular study material. Content may be removed or changed without notice.

The video is of a recording with very limited post-recording editing. The video is intended for use only by SU students enrolled in the particular module.

Module Overview



Lecture Overview

- 1 The do...while Repetition Statement (4.8)
- 2 Logical Operators (4.10)
- 3 Confusing Equality and Assignment Operators (4.11)

4.8 The **do...while** Repetition Statement I

The **do...while** repetition statement

- Similar to the while structure
- Condition for repetition tested after the body of the loop is performed
 - All actions are performed at least once
- Format:

```
do {  
    statement(s);  
} while ( condition );
```


4.8 The **do...while** Repetition Statement II

Example:

```
counter = 1;  
do {  
    printf( "%d ", counter );  
} while (++counter <= 10);
```

- Prints the integers from 1 to 10

4.8 The **do...while** Repetition Statement III



4.10 Logical Operators I

&& (logical AND)

- Returns **true** if both conditions are **true**

|| (logical OR)

- Returns **true** if either of its conditions are **true**

! (logical NOT, logical negation)

- Reverses the truth/falsity of its condition
- Unary operator, has one operand

Useful for conditions in loops

if ((2<x) && (x<7)) *equivalent to* $(2 < x < 7)$

or to calculate a student's final mark:

```
Pass = (0.1*S+0.4*A1+0.5*A2>=50) || (0.1*S+0.4*A1+0.5*A3>=50);
```


4.10 Logical Operators II

&& (logical AND)

0	&&	0	= 0
nonzero	&&	0	= 0
0	&&	nonzero	= 0
nonzero	&&	nonzero	= 1

|| (logical OR)

0		0	= 0
nonzero		0	= 1
0		nonzero	= 1
nonzero		nonzero	= 1

4.10 Logical Operators III

! (logical NOT, logical negation)

!0 = 1

!nonzero = 0

4.10 Example: do...while and logical operators I

Problem statement

As part of a survey, read the user's level of happiness on a scale of 1 to 10 and inform the user whether he/she has a normal (3 to 8) or abnormal (1, 2, 9 or 10) level of happiness. Ensure that the user enters a valid level.

Pseudocode

Do

Read user's level of happiness

Until the user has input a valid level

If the user has a normal level of happiness

Inform the user that his/her happiness level is normal

Else

Inform the user that his/her happiness level is abnormal

4.10 Example: do...while and logical operators II

C code

```
/* HappinessMeter.c
 * Program that measures your level of happiness */
#include <stdio.h>
#include <stdlib.h>
int main( void )
{
    int happiness; // the store of happiness
    // Repeatedly reads happiness level from user until 1 <= level <= 10
    do {
        printf( "Enter your happiness level on a scale of 1 to 10: " );
        scanf( "%d", &happiness ); // reads the user's level of happiness
    } while ( (happiness < 1 ) || (happiness > 10) );
    // repeat if invalid level entered
```

4.10 Example: do...while and logical operators III

C code

```
if ( (happiness >= 3) && (happiness <= 8) ) { // if happiness in [3..8]
    printf( "You are normal - congratulations!");
} // end if
else { // if happiness is not in [3..8]
    printf( "You are either very happy or very sad - seek help!\n");
} // end else

return 0; // indicates program ended successfully
} // end function main
```

4.10 Example: do...while and logical operators IV

Output

```
Enter your level of happiness on a scale of 1 to 10: 0
Enter your level of happiness on a scale of 1 to 10: 11
Enter your level of happiness on a scale of 1 to 10: 1
You are either very happy or very sad - seek help!
```

Output

```
Enter your level of happiness on a scale of 1 to 10: 5
You are normal - congratulations!
```

4.10 Example: nested loops and logical operators I

What does the following code do?

```
int i, j;
for ( i = 1; i <= 7; i++ ) {
    for ( j = 1; j <= 7; j++ ) {
        if ( !( i == 4 || j == 4 ) ) {
            printf( "*" );
        }
        else {
            printf( " ");
        }
    }
    printf( "\n" );
}
```

4.10 Example: nested loops and logical operators II

Output

```
* * *   * * *  
* * *   * * *  
* * *   * * *  
  
* * *   * * *  
* * *   * * *  
* * *   * * *
```


4.11 Confusing Equality and Assignment Operators I

Equality operator

```
if ( payCode == 4 ) {  
    printf( "You get a bonus!" );  
}
```

- Displays "You get a bonus!" if variable payCode has value 4

Assignment operator in stead of equality operator

```
if ( payCode = 4 ) {  
    printf( "You get a bonus!" );  
}
```

- Stores 4 in variable payCode and displays "You get a bonus!"

4.11 Confusing Equality and Assignment Operators II

Equality operator in stead of assignment operator

```
x = 1;
```

- Assigns a value of 1 to variable x

```
x == 1;
```

- Tests if variable x is equal to 1, but does not change its value

Today

Program Control II

- do...while repetition structure
- Logical operators
- Confusing equality and assignment operators

Next lecture

Program Control III

- switch selection structure

Homework

- 1 Study Sections 4.8, 4.10, 4.11 in Deitel & Deitel
- 2 Do Self Review Exercises 4.2(c)&(d) in Deitel & Deitel
- 3 Do Exercises 4.5(f), 4.29, 4.36 in Deitel & Deitel