

# Welcome to My AWS S3 Website

This website is hosted using Amazon S3 Static Website Hosting.

index.html

Info

 Copy S3 URI

 Download

 Open 

Object actions 

Properties

Permissions

Versions

## Object overview

### Owner

34f9769c534780a3f741b7fde270af8721af30ee7ac383d11597cedd62ff060a

### AWS Region

US East (N. Virginia) us-east-1

### Last modified

June 13, 2026, 09:38:40 (UTC+05:30)

### Size

838.0 B

### Type

html

### Key

 index.html

### S3 URI

 s3://gfg-demo4/index.html

### Amazon Resource Name (ARN)

 arn:aws:s3:::gfg-demo4/index.html

### Entity tag (Etag)

 Sae5514b6265ae46d96e3d6ac9645f15

### Object URL

 <https://gfg-demo4.s3.us-east-1.amazonaws.com/index.html>

## Make public [info](#)

The make public action enables public read access in the object access control list (ACL) settings. [Learn more](#).

⚠ When public read access is enabled and not blocked by Block Public Access settings, anyone in the world can access the specified objects.

### Specified objects

🔍 Find objects by name

| Name                                                                                                         | ▲ | Type | ▼ | Last modified                       | ▼ | Size    | ▼ |
|--------------------------------------------------------------------------------------------------------------|---|------|---|-------------------------------------|---|---------|---|
|  <a href="#">index.html</a> |   | html |   | June 13, 2026, 09:32:04 (UTC+05:30) |   | 845.0 B |   |

Cancel

Make public

## Object Ownership

Control ownership of objects written to this bucket from other AWS accounts and the use of access control lists (ACLs). Object ownership determines who can specify access to objects.

### Object Ownership

☐ **ACLs disabled (recommended)**

All objects in this bucket are owned by this account. Access to this bucket and its objects is specified using only policies.

☒ **ACLs enabled**

Objects in this bucket can be owned by other AWS accounts. Access to this bucket and its objects can be specified using ACLs.

 We recommend disabling ACLs, unless you need to control access for each object individually or to have the object writer own the data they upload. Using a bucket policy instead of ACLs to share data with users outside of your account simplifies permissions management and auditing.

 **Enabling ACLs turns off the bucket owner enforced setting for Object Ownership**

Once the bucket owner enforced setting is turned off, access control lists (ACLs) and their associated permissions are restored. Access to objects that you do not own will be based on ACLs and not the bucket policy.

☒ I acknowledge that ACLs will be restored.

### Object Ownership

☒ **Bucket owner preferred**

If new objects written to this bucket specify the bucket-owner-full-control canned ACL, they are owned by the bucket owner. Otherwise, they are owned by the object writer.

☐ **Object writer**

The object writer remains the object owner.

 If you want to enforce object ownership for new objects only, your bucket policy must specify that the bucket-owner-full-control canned ACL is required for object uploads. [Learn more](#) 

Cancel

Save changes

## Edit Block public access (bucket settings) [Info](#)

### Block public access (bucket settings)

Public access is granted to buckets and objects through access control lists (ACLs), bucket policies, access point policies, or all. In order to ensure that public access to all your S3 buckets and objects is blocked, turn on Block all public access. These settings apply only to this bucket and its access points. AWS recommends that you turn on Block all public access, but before applying any of these settings, ensure that your applications will work correctly without public access. If you require some level of public access to your buckets or objects within, you can customize the individual settings below to suit your specific storage use cases. [Learn more](#)

☐ **Block all public access**

Turning this setting on is the same as turning on all four settings below. Each of the following settings are independent of one another.

☐ **Block public access to buckets and objects granted through new access control lists (ACLs)**

S3 will block public access permissions applied to newly added buckets or objects, and prevent the creation of new public access ACLs for existing buckets and objects. This setting doesn't change any existing permissions that allow public access to S3 resources using ACLs.

☐ **Block public access to buckets and objects granted through any access control lists (ACLs)**

S3 will ignore all ACLs that grant public access to buckets and objects.

☐ **Block public access to buckets and objects granted through new public bucket or access point policies**

S3 will block new bucket and access point policies that grant public access to buckets and objects. This setting doesn't change any existing policies that allow public access to S3 resources.

☐ **Block public and cross-account access to buckets and objects through any public bucket or access point policies**

S3 will ignore public and cross-account access for buckets or access points with policies that grant public access to buckets and objects.

[Cancel](#)

**Save changes**

Add the files and folders you want to upload to S3. To upload a file larger than 160GB, use the AWS CLI, AWS SDKs or Amazon S3 REST API. [Learn more](#)

Drag and drop files and folders you want to upload here, or choose **Add files** or **Add folder**.

**Files and folders** (1 total, 845.0 B)

Remove

Add files

Add folder

All files and folders in this table will be uploaded.

< 1 >

| <input type="checkbox"/> | Name       | Folder | Type      | Size    |
|--------------------------|------------|--------|-----------|---------|
| <input type="checkbox"/> | index.html | -      | text/html | 845.0 B |

**Destination** [Info](#)

**Destination**

[s3://gfg-demo4](#)

► **Destination details**

Bucket settings that impact new objects stored in the specified destination.

► **Permissions**

Grant public access and access to other AWS accounts.

► **Properties**

Specify storage class, encryption settings, tags, and more.

Cancel

Upload

☐ Browse

#### Tags - optional

You can use bucket tags to analyze, manage and specify permissions for a bucket. [Learn more](#)

- ① You can use `s3:ListTagsForResource`, `s3:TagResource`, and `s3:UntagResource` APIs to manage tags on S3 general purpose buckets for access control in addition to cost allocation and resource organization. To ensure a seamless transition, please provide permissions to `s3:ListTagsForResource`, `s3:TagResource`, and `s3:UntagResource` actions. [Learn more](#)

No tags associated with this bucket.

[Add new tag](#)

You can add up to 50 tags.

#### Default encryption [info](#)

Server-side encryption is automatically applied to new objects stored in this bucket.

##### Encryption type [info](#)

Secure your objects with two separate layers of encryption. For details on enabling, see [D3SE-KMS getting on the Storage tab of the `awscli` page](#).

- ☒ Server-side encryption with Amazon S3 managed keys (SSE-S3)  
☐ Server-side encryption with AWS Key Management Service keys (SSE-KMS)  
☐ Dual-layer server-side encryption with AWS Key Management Service keys (DSSE-KMS)

##### Bucket Key

Using an S3 Bucket Key for SSE-KMS reduces encryption costs by lowering calls to AWS KMS. S3 bucket keys aren't supported for DSSE-KMS. [Learn more](#)

- ☐ Disable  
☒ Enable

#### ► Advanced settings

① After creating the bucket, you can upload files and folders to the bucket, and configure additional bucket settings.

[Cancel](#)

[Create bucket](#)

Create bucket [Info](#)

Buckets are containers for data stored in S3.

General configuration

**AWS Region**  
US East (N. Virginia) us-east-1

**Bucket type** [Info](#)

- ☒ **General purpose**  
Recommended for most use cases and access patterns. General purpose buckets are the original S3 bucket type. They allow a mix of storage classes that redundantly store objects across multiple Availability Zones.
- ☐ **Directory**  
Recommended for low-latency use cases. These buckets use only the S3 Express One Zone storage class, which provides faster processing of data within a single Availability Zone.

**Bucket namespace**  
Choose the namespace where you want to create your bucket. [Learn more](#)

☒ **Global namespace**  
By default, S3 creates general purpose buckets in the global namespace.

☐ **Account Regional namespace (recommended)**  
General purpose buckets created in your account Regional namespace are unique to your account. These buckets can never be created by another AWS account.

**Bucket name** [Info](#)

gfg-demo4

Bucket names must be 3 to 63 characters and unique within the global namespace. Bucket names must also begin and end with a letter or number. Valid characters are a-z, 0-9, periods (.), and hyphens (-). [Learn more](#)

**Copy settings from existing bucket - optional**  
Only the bucket settings in the following configuration are copied.

Choose bucket

Format: s3://bucket/prefix

Object Ownership [Info](#)

Control ownership of objects written to this bucket from other AWS accounts and the use of access control lists (ACLs). Object ownership determines who can specify access to objects.

Object Ownership

- ☒ **ACLs disabled (recommended)**  
All objects in this bucket are owned by this account. Access to this bucket and its objects is specified using only policies.
- ☐ **ACLs enabled**  
Objects in this bucket can be owned by other AWS accounts. Access to this bucket and its objects can be specified using ACLs.

**Object Ownership**  
Bucket owner enforced