

**Ex. No.: 8**

**Date:**

### **PRODUCER CONSUMER USING SEMAPHORES**

**Aim:** To write a program to implement solution to producer consumer problem using semaphores.

**Algorithm:**

1. Initialize semaphore empty, full and mutex.
2. Create two threads- producer thread and consumer thread.
3. Wait for target thread termination.
4. Call sem\_wait on empty semaphore followed by mutex semaphore before entry into critical section.
5. Produce/Consume the item in critical section.
6. Call sem\_post on mutex semaphore followed by full semaphore
7. before exiting critical section.
8. Allow the other thread to enter its critical section.
9. Terminate after looping ten times in producer and consumer Threads each.

**Program Code:**

```
#include<stdio.h>
#include<stdlib.h>
int mutex=1,full=0,empty=3,x=0;
int main()
{
int n;
void producer();
void consumer();
int wait(int);
int signal(int);
printf("\n1.Producer\n2.Consumer\n3.Exit");
while(1)
{
printf("\nEnter your choice:");
scanf("%d",&n);
switch(n)
{
case 1: if((mutex==1)&&(empty!=0))
producer();
else
printf("Buffer is full!!");
break;
case 2: if((mutex==1)&&(full!=0))
consumer();
else
printf("Buffer is empty!!");
break;
case 3;
exit(0);
break;
}
}
return 0;
}
```

```

int wait(int s)
{
return (--s);
}
int signal(int s)
{
return(++s);
}
void producer()
{
mutex=wait(mutex);
full=signal(full);
empty=wait(empty);
x++;
printf("\nProducer produces the item %d",x);
mutex=signal(mutex);
}
void consumer()
{
mutex=wait(mutex);
full=wait(full);
empty=signal(empty);
printf("\nConsumer consumes item %d",x);
x--;
mutex=signal(mutex);
}

```

**Sample Output:**

```
1. Producer
2.Consumer
3.Exit
Enter your choice:1
Producer produces the item 1
Enter your choice:2
Consumer consumes item
1 Enter your choice:2
Buffer is empty!!
Enter your choice:1
Producer produces the item 1
Enter your choice:1
Producer produces the item 2
Enter your choice:1
Producer produces the item 3
Enter your choice:1
Buffer is full!!
Enter your choice:3
```

**Output:**

```
Producer produces the item 1
Enter your choice:1
```

**Result:**

Program is executed successfully and output is verified.