

# Mini Project Week 4

Now that we've learned how to work with two-dimensional data, let's refactor our app to use dictionaries for both product and courier.

Building upon our use of a courier index within our order, let's create a list of product indexes now for order items.

We'll also need to refactor our storage layer to use `.csv` files rather than `.txt` to bring back our persistence functionality.

Unit-tests from previous weeks will need to be updated.

## Goals

As a user I want to:

- create a product, courier, or order and add it to a list
- view all products, couriers, or orders
- update the status of an order
- persist my data
- *STRETCH* update or delete a product, order, or courier
- *BONUS* list orders by status or courier

## Spec

- A `product` should be a `dict`, i.e:

```
{
  "name": "Coke Zero",
  "price": 0.8 // Float
}
```

- A `courier` should be a `dict`, i.e:

```
{
  "name": "Bob",
  "phone": "0789887889"
}
```

- An `order` should be a `dict`, i.e:

```
{
  "customer_name": "John",
  "customer_address": "Unit 2, 12 Main Street, LONDON, WH1 2ER",
  "customer_phone": "0789887334",
  "courier": 2, // Courier IDX
  "status": "preparing",
  "items": [1, 3, 4] // Product IDs
}
```

- Data should be persisted to a `.csv` file on a new line for each `courier`, `order`, or `product`, ie:

```
# ORDER
John,"Unit 2, 12 Main Street, LONDON, WH1 2ER",2,preparing,"1,3,4"
```

## Pseudo Code

```
LOAD products list from products.csv    # WEEK 4 UPDATE
LOAD couriers list from couriers.csv    # WEEK 4 UPDATE
LOAD orders list from orders.csv        # WEEK 4 UPDATE
CREATE order status list

PRINT main menu options
GET user input for main menu option

IF user input is 0:
    SAVE products list to products.csv
    SAVE couriers list to couriers.csv
```

```

SAVE orders list to order.csv
EXIT app

# products menu
ELSE IF user input is 1:
    PRINT product menu options
    GET user input for product menu option

    IF user inputs 0:
        RETURN to main menu

    ELSE IF user input is 1:
        PRINT products list

# WEEK 4 UPDATE
ELSE IF user input is 2:
    # CREATE new product

    GET user input for product name
    GET user input for product price
    CREATE new product dictionary with above properties
    APPEND product dictionary to products list

# WEEK 4 UPDATE
ELSE IF user input is 3:
    # STRETCH GOAL - UPDATE existing product

    PRINT products with their index values
    GET user input for product index value

    FOR EACH key-value pair in selected product:
        GET user input for updated property
        IF user input is blank:
            do not update this property and skip
        ELSE:
            update the property value with user input

ELSE IF user input is 4:
    # STRETCH GOAL - DELETE product

    PRINT products list
    GET user input for product index value
    DELETE product at index in products list

# couriers menu
ELSE IF user input is 2:
    PRINT courier menu options
    GET user input for courier menu option

    IF user inputs 0:
        RETURN to main menu

    ELIF user inputs 1:
        PRINT couriers list

# WEEK 4 UPDATE
ELSE IF user input is 2:
    # CREATE new courier

    GET user input for courier name
    GET user input for courier phone number
    CREATE new courier dictionary with above properties
    APPEND courier dictionary to courier list

# WEEK 4 UPDATE

```

```

ELSE IF user input is 3:
    # STRETCH GOAL - UPDATE existing courier

    PRINT courier with their index values
    GET user input for courier index value

    FOR EACH key-value pair in selected courier:
        GET user input for updated property
        IF user input is blank:
            do not update this property and skip
        ELSE:
            update the property value with user input

ELSE IF user input is 4:
    # STRETCH GOAL - DELETE courier

    PRINT courier list
    GET user input for courier index value
    DELETE courier at index in courier list

# orders menu
ELSE IF user input is 3:
    IF user input is 0:
        RETURN to main menu

    ELSE IF user input is 1:
        PRINT orders dictionary

# WEEK 4 UPDATE
ELSE IF user input is 2:
    GET user input for customer name
    GET user input for customer address
    GET user input for customer phone number

    PRINT products list with its index values
    GET user inputs for comma-separated list of product index values
    CONVERT above user input to list of integers

    PRINT couriers list with index value for each courier
    GET user input for courier index to select courier
    SET order status to be 'PREPARING'

    CREATE new order dictionary with above properties
    APPEND order to orders list

ELSE IF user input is 3:
    # UPDATE existing order status

    PRINT orders list with its index values
    GET user input for order index value

    PRINT order status list with index values
    GET user input for order status index value
    UPDATE status for order

ELSE IF user input is 4:
    # STRETCH - UPDATE existing order

    PRINT orders list with its index values
    GET user input for order index value

    FOR EACH key-value pair in selected order:
        GET user input for updated property
        IF user input is blank:
            do not update this property
        ELSE:

```

ELSE:

    update the property value with user input

ELSE IF user input is 5:

    # STRETCH GOAL - DELETE courier

    PRINT orders list

    GET user input for order index value

    DELETE order at index in order list