

东莞稳畅电子制品有限公司
物质安全资料表

MATERIAL SAFETY DATA SHEET (MSDS)

一、物品与厂商资料(Product and company information)	编号: WCH002
物品名称 Product name: 105 度 PVC 胶料(各色)	
制造商名称: 稳畅电子制品有限公司(GUANGDONG WENCHANG ELECTRONIC CO.,LTD.)	
联络电话/传真电话: 0769-85521848 FAX: 0769-85500868	
联系人:张应鑫 邮箱:WCH588@DGWCH.CN	
东莞虎门白沙社区连升北	

二、成分辨识资料(Ingredients identification information) 纯物质(Pure material)：			
产品组成部分(The product component):			
一级物质成分(matter composition): PVC 胶料			
二级物质成分(matter composition):			
PVC 胶料	CAS 号		
PVC 树脂(polythene)粉 （聚氯乙烯）	50%	9002-86-2	
增塑剂(plasticize)TOTM （偏苯三酸三辛酯）	23.60%	3319-31-1	
填充剂(loading agent) （CaCO3）	17.5%	471-34-1	
安定剂(stabillize) （钙锌复合稳定剂）	2.8%	1592-23-0	
润滑剂(lubriccants) （油脂酸正丁脂）	2.50%	8002-74-2	
阻燃剂（SB2O3）	2.6%	1309-64-4	
色粉（有机颜料）	1%	红色（980-26-7）黄色（22094-93-5）绿色（永固黄 77804-81-0/钛青蓝 147-14-8）蓝色（147-14-8） 黑色（1333-86-4）白色（7128-64-5）紫色（6358-30-1）棕色（8062-14-4）橙色（21889-27-0） 灰色 （炭黑 0.5%CAS: 1333-86-4 钛白粉 0.5% CAS:13463-67-7）	
主要危害物质成份			
成份名称	化学式	含量（%）	化学文摘社登记号码 CAS NO:
阻燃剂（三氧化二锑）	SBzO3	2. 60	1309-64-4
增塑剂(plasticize) (TOTM)		23.60	3319-31-1

--	--	--	--

（以上资讯供参考）

三、危害辨识资料 (The harm is distinguished knowing datum)

最重要危害 效应 The most important harm effect	健康危害效应(The health harms the effect): 与眼睛接触会有轻微刺激感,引起流泪(Can have the light irritate to feel with the eyes contacts , and cause bursting into tears)。
	环境影响 (Environment impact): 属环保产品
	物理性及化学性危害 (Physics and chemistry harm): 在高温 600℃以上燃烧时会产生一氧化碳及二氧化碳 (Carbon monoxide and carbon dioxide are given rise to to the combustion particular circumstances of the time more than 600 °C's' high temperature)
	特殊危害 (Special harm): N/A
主要症状 (The major symptom): 误食后引发呕吐,腹胀等中毒的现象 (That the mistake initiates after the meal vomits , the appearance that the abdominal distension etc are posioned)	
物品危害分类 (The article harm the classification): 非危害物品 (The non- harm article)	

四、急救措施 (The first aid measure)

不同暴露途径之急救方法 (The difference exposes the first aid method of way): 移入暴露区, 仍有不舒服, 需即刻送医院 (The shift-in exposes the area, still has, and need send the hospital at once) • 吸入 Inhale: 立即到医院治疗 (We should cure to the hospital immediately) • 皮肤接触 The skin contact: 用水或肥皂冲洗 The soap washes with Shui Huo • 眼睛接触 The eyes contacts: 立即用水冲洗直到刺激感退去 Wash feeling and moves back with water immediately until the irritate
最重要症状及危害效应 The most important symptom and harm effect: 窒息 Suffocates
对急救人员之防护 To the protection of the first-aid personnel: N/A
对医师之提示 To doctor points out: N/A

五、滅火措施 Subtract the fire measure

适用滅火剂 Being suitable subtracts the fire agent: 泡沫、二氧化碳、化学干粉、水雾 Foam , carbon dioxide and chemistry dried vermicelli made from bean starch and water smoke

滅火时可能遭遇之特殊危害 Probably special to meet with it harm when subtracting the fire: N/A

特殊滅火程序 It is special: N/A

消防人员之特殊防护设备 The special protection equipment of fire fighting personnel: 一般即可
Generally namely passably

六、洩漏处理方法 Flowing swiftly leaks the handle method

个人应注意事项 Personally should pay attention to the item: N/A

环境注意事项 The environment is paid attention to the item: 保持通风, 移除会与外泄物反应的化学
品 The ventilation keeps , moves the divide out understands with lets out chemistry article of
thing reaction

清理方法 Put in order the method: 由于会放出 HCL, 不可焚化处理 HCL, cannot incinerate the
handle owing to letting out

七、安全处理与储存方法: Safe handle and store method

处置 Processing: 交回收站进行回收处理 Handing over the collection depot retrieves the handle

储存 Store: 避免受潮; 安装排气通风设备, 20-40℃保持产品原包装方式, 保持存放地点通风,
防潮、防晒, 温度 40-75% Avoiding being affected with damp Installing the ventilation equipment
exhausting , 20-40 ℃ keeps primary packing method of product , keeps leaving the place to
ventilate , and it is dampproofing and guards against shining upon , temperature 40-75%

八、暴露预防措施 The preventive measure expose

卫生措施 The hygienic measure: 8 小时,量平均容充浓度/短时间量平均容许浓度/最高容浓度无
8 hours , that consistency the highest appearance consistency of / is not had was equally

tolerateed that to the average Rong Chong's consistency short time quantum of / of capacity .。

九、物理及化学性质 Physics and chemical property

物质状态 The matter state: 固态 Solid the form	常温下特性 The normal temperature down property: N/A
颜色 Colour: N/A	气味 Smell: N/A
PH 值: 9 ± 0.5	分解温度 Decompose the temperature: 绝缘体在 280℃以上分解 The insulator decomposes more than 280 °Cs
挥发性 The nature giving play to: N/A	溶解度 Solubility: N/A

十、安定性及反应性 Stable nature and reaction

安定性 Stable nature: 安定 Stable
特殊状况下可能之危害反应 Possibility the harms reaction under the special condition: 外被绝体缘脆化, 绝缘性能下降, 高温燃烧可能会有 HCL 所产生。Outer by desperate fragileization of aspect reason , the dielectric attribute descends , and gives rise to leaking electricity , and that the high temperature burns probably can have HCL to give rise to .
应避免之状况 The condition that should be avoided: 热及高温 Heat and high temperature
应避免之物质 The matter that should be avoided : 避免类似化学物质长期紧接触, 不可在高于产品所示额定温度环境内长期放置使用, 非特殊产品不可与油类有要类三态物质长期接触 Avoiding the similar chemistry matter long-term tight to contact , and cannot show over a long period of time laying up the use inside the rated temperature environment at the mores than product , the different product of fit cannot and oil having kind tri-state matter contact over a long period of time。
危害分解物 Harming decomposes the thing: HCL、CO、CO ₂

十一、毒性资料 Toxicity datum :

急毒性 Impatient toxicity: N/A
局部效应 The part effect: N/A
致敏感性 Send sensitivity: N/A
慢毒性或长期毒性 Slow toxicity or long-term toxicity: N/A

特殊效应 The special effect: N/A

十二、生态资料 Ecology datum

可能之环境影响/环境流布 The possibility of the environment impact of /'s environment is spreaded: N/A

十三、废弃处置方法 The processing method is discarded :

废弃处置方法 The processing method is discarded : 交回收站进行回收处理 Handing over the collection depot retrieves the handle

十四、运送资料 Transport datum

国际运送规定 The internation transports the regulation: N/A

联合国编号 The United Nations number :N/A

国内运送规定 Internal: N/A

特殊运送方法及注意事项 Special in paying attention to the item : 运送过程中, 不能有碰撞及挤压, 防止绝缘层破裂 In transporting the course can not collide and extruding , and prevent the isolation layer from bursting

十五、法规资料 Regulations datum

法规 The regulations:

1 劳动安全卫生设施规则 Work the safe hygiene installation rules

2 危险物及有害物质通迅规则 Dangerous thing and harmful matter lead to the fast rule

3 高压气体环境空气中有害物质充许浓度标准 Harmful matter fills being permitted the consistency standard in the high-handed gas environment air

4 劳工用业环境空气中有害物质充许浓度标准 Labourer fills with harmful matter in the industry environment air to be permitted the consistency standard

5 道路交通安全规则 The road traffic safety rule

十六、其它资讯 Other are interrogated

制表单位 The reporting unit	名称 Name: 东莞稳畅电子制品有限公司 (GUANGDONG WENCHANG ELECTRONIC CO.,LTD)
	地址/电话 Add/Tel: 东莞市虎门白沙社区连升北路

制 表 人 Tabulator	职称：品管 Title of a technical : 主管	姓 名 (签 章)The name (bamboo slips chapters): 张应鑫 YINGXIN ZHANG
制表日期 date	2023-07-19	