Learning Rewards from Machine State: A Proof of Concept on Game Boy Tetris

Author: D-VSpec · **Date:** November 2026 · **Code:** https://github.com/D-Vspec/TetrisFormer

---

Abstract

Reinforcement learning (RL) agents need a reward function. Hand-writing one takes per-game domain knowledge and is easy to exploit. We test whether the reward can instead be *learned from the machine state of a game console*. An autoregressive transformer is trained on Game Boy work-RAM traces of competent play, and its predictive log-likelihood over the next RAM state is used as a dense reward for an RL agent that also acts purely on RAM. No pixels, no action labels and no hand-written reward code enter the reward.

In a two-day proof of concept on Tetris:

- A 0.9M-parameter byte-token transformer predicts held-out expert RAM at 0.040 nats/byte, 12× better than a copy-last-state baseline, and rates random play about 10× less likely per step than expert play.
- Under this learned reward, the pause exploit that broke both of our hand-written rewards becomes the worst-scoring behaviour.
- The same model with the sign flipped (a curiosity reward) reproduces the known "noisy-TV" failure: the agent pauses on 76% of steps.
- Failure modes can be traced to specific RAM addresses.
- However, no agent learned to clear lines within the 300k-step training budget, and part of our evaluation is circular.

We conclude that the reward signal behaves sensibly and is interpretable, while exploration with button-level PPO is the current bottleneck.

---

1. Problem statement

1.1 Motivation

An RL agent learns to maximise a reward signal. Hand-written rewards have two problems:

1. **Effort and domain knowledge.** Someone has to know which game variables matter (position, score, level flags) and how to weight them. This has to be redone for every game.
2. **Reward hacking.** Agents find behaviours that score well without doing what the designer intended. We hit this twice during this project (§5.5).

Learned rewards avoid hand-writing, but those learned over pixels are hard to debug: when the agent exploits the reward, it is unclear *what* in the image it is exploiting.

1.2 Idea

A game console's work RAM (WRAM, 8 KB on the Game Boy) holds the game's logical state *exactly*: board contents, piece positions, timers, sound-engine state. The state is discrete, compact and fully observable.

We train a sequence model on RAM traces of good play and reward the agent for producing RAM trajectories that the model finds likely:

$$r_t = \log p_\theta(s_{t+1} \mid s_{t-T+1}, \dots, s_t)$$

where s_t is the RAM snapshot at agent step t. This is the idea of VIPER (Escontrela et al., 2023), which uses video frames, applied to exact machine state instead.

1.3 Research questions (for this proof of concept)

- **Q1.** Can a small transformer model Game Boy RAM dynamics of expert play well enough to separate expert from non-expert behaviour?
- **Q2.** Does its likelihood work as an RL reward with no other task information?
- **Q3.** Because RAM is exact, can failure modes and reward hacking be explained at the level of individual memory addresses?
- **Q4.** How does the likelihood reward compare with a hand-engineered reward and with a curiosity reward (the same model with the opposite sign)?

1.4 Scope

The original research plan (`PLAN.md`) targets Super Mario Land and Pokémon over several months. This report covers a **two-day proof of concept on Tetris**: the only suitable ROM available on the machine. The PoC checklist is `phases/poc.md`.

---

2. Background and related work

- **VIPER** (Escontrela et al., NeurIPS 2023) trains an autoregressive video model on expert videos and uses the log-likelihood of the next frame as reward, plus an exploration bonus. Our method is the RAM analogue. VIPER also notes that likelihood alone favours "most-probable" degenerate behaviour (e.g. standing still) and converges early to local optima. We observed both.
- **Observation-only density rewards.** IL-flOw (Chang et al., 2021) uses expert state-transition density as a reward on low-dimensional robot states. So *likelihood as reward* is not new; what is new here is exact, discrete *machine state* with a transformer, and byte-level interpretability.
- **Curiosity** (Schmidhuber 1991; Pathak et al., ICML 2017; Burda et al., ICLR 2019) rewards prediction *error*. Its known failure is the "noisy TV": agents get stuck on unpredictable stimuli. We use it as the opposite-sign baseline.
- **RAM as state.** AtariARI (Anand et al., 2019) and OCAtari (Delfosse et al., 2024) use Atari RAM as ground-truth state for representation learning, not for reward learning.
- **Game Boy RL.** PokeRL (Mudireddy & Patibandla, 2026) uses hand-designed RAM rewards with pixel policies. Rank-Then-Act (Maksyuta et al., 2026) learns a progress reward from expert *video* with a 7B vision-language model, on PyBoy games including Kirby.

A literature sweep (`notes/related-work.md`) found no prior work using likelihood over console RAM as a learned reward.

---

3. Work done

3.1 Process

The work was organised around written phase checklists. Any departure from a checklist needed human approval and was logged. The project has 9 approved deviations (`DEVIATIONS.md`), a catalogue of reward hacks (`notes/reward-hacking.md`), and an event log of every discrepancy (`notes/log.md`). The main steps:

Step	Outcome
Literature sweep	No direct prior work; claims narrowed to "VIPER on exact machine state" (D-003); VIPER-style exploration bonus added (D-002)

Step	Outcome
Scope change	Full plan compressed to a 2-day PoC on Tetris (D-004)
Environment	Deterministic PyBoy Tetris env with RAM observations and a volatile-byte mask
Hand-engineered baseline	Exploited twice through the pause button (H-001, H-002); reward fixed (D-006)
Expert data	PPO could not produce competent play, so a scripted expert was written instead (D-005)
Reward model	0.9M-param transformer; address set widened to all 289 varying bytes (D-007)
RL with learned reward	First run collapsed to one action (H-003); exploration fixed via pilots (D-008)
Final runs	300k steps each for 4 reward variants (D-009); analysis, figure, GIF

3.2 Changes from the original plan, and why

- **Tetris instead of Super Mario Land:** no SML ROM was available.
- **Scripted expert instead of TAS/human/RL data:** a Tetris TAS gives only ~2k agent steps, and our PPO agent never cleared a line. A heuristic player gave 100 competent games in 5 minutes.
- **300k RL steps instead of 3M:** the learned reward costs ~14 GFLOPs per step, so RL ran at only ~126 steps/s, and the report was needed within hours.

---

4. Implementation

All code is in the repository root; each component is a single file.

4.1 Environment (`env.py`)

- **Emulator:** PyBoy 2.9, headless, unthrottled (~6,000 frames/s per instance).
- **Observation:** WRAM 0xC000–0xDFFF (8,192 bytes) as `uint8`, sampled every **24 frames** (one agent step). CPU registers are excluded because they reflect when the snapshot was taken, not game state.
- **Actions:** 8 discrete: ↑ ↓ ← → A B Start, no-op. A button is pressed for one frame, then 24 frames are emulated.
- **Episodes:** start with `reset_game(timer_div)`, where `timer_div` seeds Tetris's piece generator (random per episode). They end at game over or after 2,000 steps.
- **Determinism:** the same seed and actions give byte-identical RAM traces (asserted in `env.py`).
- **Parallelism:** 12 subprocess environments, ~1,000–1,500 agent steps/s.

4.2 Volatile-byte mask

Some bytes change regardless of what the player does (sound engine, stack). A likelihood model would waste capacity on them, and a curiosity agent would chase them. We ran no-op and random rollouts and masked bytes that change on ≥60% of no-op steps.

- **Result:** 8 bytes, the sound driver (0xDF94–0xDFC4) and one stack byte (0xCFED).
- **Discrepancy:** the planned rule, "changes on ≥95% of steps", masked nothing, because Tetris keeps its frame counter and random-number state outside WRAM.
- **Observation:** only 278 of the 8,192 WRAM bytes ever change during play.

4.3 Expert data (`expert.py`, `collect.py`)

A scripted player supplies the "competent play" traces:

- **Perception:** it reads the landed blocks from the background tilemap and the falling piece from the sprites.
- **Planning:** for each new piece it tries every rotation × column, simulates the drop, and scores the resulting board with a standard linear heuristic: −0.51·height + 0.76·lines − 0.36·holes − 0.18·bumpiness.
- **Execution:** it presses buttons through the *same* `env.step`, closed loop (rotate until the on-screen shape matches, shift to the target column, soft-drop). Its RAM traces therefore have exactly the timing the RL agent sees.

Data: 100 games, 183,044 steps, 53.3 lines/game (random play: 0). Only RAM is stored, not actions. Details: `notes/scripted-expert.md`.

4.4 Reward model (`rm.py`)

Tokenisation. Every byte that varies in the expert data, minus the mask, is one token: K = 289 addresses. 180 of them are the 18×10 playfield copy at 0xC800. A token's embedding is

$$e = E_{\text{value}}[\text{byte}] + E_{\text{address}}[k] + E_{\text{time}}[t].$$

Byte values are embedded as categories, not scalars, because map or tile IDs are not ordinal.

Architecture. Decoder-only transformer, d = 128, 4 layers, 4 heads, FFN 512, pre-norm: **897,152 parameters**.

- **Context:** T = 8 steps, so 8 × 289 = 2,312 tokens.
- **Block-causal attention:** every token of step t attends to all tokens of steps ≤ t, and predicts the value of *its own address* at step t+1 (a 256-way softmax).
- **Shared output head:** one small 128→256 head is shared across all addresses. This weight sharing is why the model is small; an equivalent step-level model with a flat output layer would need ~19M parameters for the output alone.

Training.

- **Objective:** cross-entropy over all predicted bytes.
- **Optimiser:** AdamW at 1e-3 with a one-cycle schedule, batch of 32 windows, 3,000 iterations (~220M tokens), bf16.
- **Data split:** by game (90 train, 10 validation), so validation games are entirely unseen.
- **Time:** ~15 minutes on an RTX 5060 laptop GPU.
- **No-mask variant:** an identical model that also includes the 8 volatile bytes (K = 297).

4.5 Learned reward and RL (`rl.py`, `ppo.py`)

Reward.

$$r_t = \text{norm}\Big(\sum_k \log p_\theta(s_{t+1}^{(k)} \mid s_{t-7..t})\Big) + \beta\,\text{norm}(r_t^{\text{RND}})$$

- The sum runs over the unmasked addresses.
- norm is a running mean/std normalisation.
- r^{RND} is a Random Network Distillation novelty bonus with β = 0.5, the exploration term VIPER also uses.
- The reward model is frozen; a checksum is asserted unchanged after each run.
- At the start of an episode, the history is padded with the first state.

Policy.

- An MLP over one-hot RAM (271 bytes that change in no-op/random play, minus the mask): one-hot → 256 → 256 → policy and value heads. That's 17.8M parameters, almost all in the one-hot input layer.
- The policy does not share an encoder with the reward model, so it can't co-adapt with it.

PPO settings. 12 envs, 128-step rollouts, $\gamma = 0.99$, $\lambda = 0.95$, clip 0.2, 4 epochs, 8 minibatches, learning rate 2.5e-4, **entropy coefficient 0.05** (raised from 0.01 after the collapse in §5.4).

Compared reward variants. Policy, PPO config and budget (300k steps, 1 seed) are identical; only the reward differs:

Variant	Reward
Hand-engineered	1.0 per line cleared + 0.1 per piece locked
Ours	likelihood + mask + RND
Ours, no mask	likelihood from the no-mask model + RND
Curiosity	−likelihood + RND (only the sign differs from ours)

4.6 Analysis (`analyze.py`, `plot_training.py`, `make_gif.py`)

- **Evaluation:** 24 episodes per policy with sampled actions; lines cleared and episode length.
- **Scoring:** each policy's states are scored with the (masked) reward model over 8 episodes, excluding the terminal transition.
- **Per-address gap:** the expert's mean log p minus the agent's mean log p, per address.

---

5. Results

5.1 Q1: the reward model separates expert from non-expert play

Evaluation data	NLL (nats/byte) ↓
Expert, 10 held-out games	**0.040**
Copy last state (best ε-smoothing, ε = change rate 0.053)	0.505
Per-address unigram	0.715
Random-play traces	0.417

The model beats the copy baseline by 12× and rates random play ~10× less likely per byte than expert play. The no-mask model reaches the same validation NLL (0.040).

Measured *online*, by running each fixed policy through the environment and reward pipeline on unseen seeds, the per-step log p is:

Expert	Always →	No-op	Always ←	Always ↓	Random	Always Start (pause)
−12.4	−34.5	−41 to −52	−45	−46	−121	**−257**

The expert's online score matches the offline evaluation (−11.7), which confirms that states and rewards are aligned correctly in the RL loop.

5.2 Q2/Q4: RL with the learned reward



Figure 1: Training curves

Figure 1. (A) Raw learned reward per step during training; the hand-engineered run has no log-p curve because it was trained on its own reward. (B) Policy entropy (maximum ln 8 ≈ 2.08). Rolling mean over 5 PPO updates.

Run	Lines/game	Episode length	log p/step (mean)	log p/step (**median**)	Dominant action
Scripted expert	53.3	1830	−13.8	**−5.1**	(rotate → shift → drop)
Random	0.0	448	−109	−106	—
Hand-engineered	0.0	178	−72	−33	↓ 29%
Ours	0.0	159	**−38**	**−12.6**	↓ 59%
Ours, no mask	0.0	822	−81	−107	← 76%
Curiosity	0.04	525	−197	−144	**Start 76%**

Lines and length: 24 evaluation episodes. Log p: masked reward model, 8 episodes, terminal transition excluded.

Observations:

- **No variant clears lines** in 300k steps. The independent task metric does not separate the methods.
- **Ours ranks first under the reward model.** Its median step (−12.6) is close to the expert's per-step level. Its training curve (Fig. 1A) rose from −52 to −30 and was still rising when training stopped.
- **The hand-engineered agent was never trained on log p, yet it scores between random and ours.** This is weak independent evidence that the reward model tracks "reasonable" play.
- **Rewards are heavy-tailed.** Most of our agent's steps look expert-like, but rare, very unlikely steps (e.g. topping out) pull the mean down.
- **The no-mask run changed behaviour abruptly at ~285k steps** (Fig. 1). Its log p, under its own model, fell from ~−40 to ~−235, its entropy fell, and it switched to pressing ← on 76% of steps. We have not explained why an agent would move to a much lower raw likelihood; RND domination or the running-normalisation baseline are candidates.

5.3 Q3: byte-level attribution

Largest per-address gaps between expert and agent (nats, masked model):

Agent	Top addresses	Interpretation
Ours	0xC203 (1.67), 0xC018, 0xC01C, 0xC014, 0xC010 (~1.0)	0xC010–0xC01D is the shadow sprite table, i.e. the falling piece's position. The agent moves pieces unlike the expert. 0xC203 is unidentified.
Hand-engineered	0xC014, 0xC018, 0xC010, 0xC203 (~2.5)	same addresses, larger gaps
Random	0xDFBE, 0xCFF1, 0xDFAE, 0xC018 (~3.5)	sound-engine state, stack, piece
Ours, no mask	0xDFBE, 0xDFAA, 0xDF9E, 0xCFF1 (~3)	sound engine + stack: the bytes the mask removes
Curiosity	0xC014, 0xC018, 0xC210, 0xCFF1 (~7.5)	piece sprites frozen/hidden by the pause screen

Each behaviour maps onto a small, nameable group of addresses. Note that these gaps say *where* an agent's states differ from the expert's, not *why*.

5.4 Exploration failure: the collapse (H-003)

With PPO's default entropy coefficient (0.01), the likelihood-trained policy **collapsed to pressing → on every step within 150k steps** (entropy 1.7e-5; Fig. 1B, pink).

- **Not a bug:** the online measurement in §5.1 shows "always →" is the best *trivial* policy (−34.5/step), far below the expert (−12.4). This is the local optimum VIPER warns about.
- **Pilots:** entropy 0.05 prevented the collapse. Entropy 0.05 *plus a stronger novelty bonus* ($\beta = 2$) collapsed faster, to "always ↓". A stronger exploration bonus made things worse.

5.5 Reward-hacking catalogue

ID	Reward	What the agent did
H-001	Hand v1: lines + 0.01 per step survived	Pressed Start once to pause the game, then farmed the survival reward until the step limit
H-002	Hand v2: lines + 0.1 per piece	The pause screen adds 28 non-empty tiles, which my piece detector counted as locks. Pressed Start on 83% of steps (a bug in my reward code; fixed)
H-003	Likelihood, entropy 0.01	Collapse to "always →" (exploration failure)
H-004	Curiosity (−log p)	Pauses on 76% of steps: the never-seen pause screen is the most surprising state available (noisy TV)

The likelihood reward scores pausing *worst* (−257/step), so the exploit behind H-001 and H-002 does not transfer to it. Curiosity, using the *same* model, makes pausing *best*. So the sign of the reward, not the model, determines this behaviour.




Figure 2: Expert | ours | curiosity

Figure 2. A still frame (step ~100) of the side-by-side gameplay recording, same piece sequence (animated version in the repository: `runs/tetris_agents.gif`). Left: scripted expert. Middle: our agent (drops pieces fast and tops out). Right: curiosity agent (paused).

---

6. Discussion

6.1 What the proof of concept supports

1. **RAM is an easy modelling target.** A sub-1M-parameter model predicts the next RAM state almost perfectly for expert play (0.04 nats/byte), because most bytes are deterministic given recent history.
2. **The learned likelihood ranks behaviour sensibly** (expert $\gg$ ours $>$ hand $>$ random $\approx$ degenerate policies), although it never saw a reward, an action or a pixel.
3. **It resists the exploit that broke our hand-written rewards.** Pausing is far off the expert distribution, so likelihood punishes it. This matches the motivation: an unexpected exploit of the reward becomes an off-distribution state, and off-distribution states are penalised by construction.
4. **Byte-level interpretability is real and cheap.** Every failure was attributed to a few addresses with a simple per-address log-p comparison: falling-piece sprites, sound engine, stack.
5. **The volatile mask matters.** Without it, the agent's states differ from the expert's mainly in sound-engine bytes. That is a small-scale version of curiosity's noisy-TV problem, appearing in the likelihood reward too.

6.2 What it does not show

1. **The agent does not play Tetris.** Zero lines for every variant after 300k steps.
2. **Our headline comparison is partly circular.** "Ours scores best under the reward model" is expected: it was trained on that reward. The only independent metric (lines) shows no difference. The hand-engineered agent's intermediate score is the only non-circular hint.
3. **The expert is hand-engineered.** The reward contains no reward code, but it imitates a heuristic that reads the board from the screen. That's less circular than learning from an RL agent trained on a hand reward, but it is not human play.
4. **Weak statistics.** One seed per variant and 10× fewer steps than planned. Differences between runs are within the run-to-run variation we would expect.

6.3 Why the agent does not learn the task

- **Exploration.** The learned reward is dense, but the behaviour it rewards (rotate, shift, drop to a chosen column) is a coordinated sequence of 5–10 button presses. Random exploration rarely produces it, so PPO first finds easy local optima ("always →", "always ↓").
- **What helped and what didn't:**
  - VIPER faces the same problem and uses an exploration bonus.
  - In our case, a larger entropy bonus helped, but a larger novelty bonus hurt: under RND, fast drops and frequent game overs produce a stream of "new" states.
  - Our agent's main behaviour (fast ↓ drops) moves pieces in ways the expert never did. Fig. 1A shows its reward still rising, so more training may help, but we cannot claim it.
- **Compute.** The reward transformer recomputes a 2,312-token window every step (~14 GFLOPs), so the reward, not the emulator, limits RL to ~126 steps/s. KV caching, a shorter context, a factorised architecture or a recurrent model (~30 MFLOPs per step) would allow 10–100× more RL steps for the same time.

6.4 Threats to validity

- The per-address "interpretations" rely on partial knowledge of Tetris's memory map. The shadow sprite table at 0xC000 and the playfield at 0xC800 are consistent with our observations, but 0xC203 is unidentified.
- The expert topped out in 29 of its 100 games. Topping out is therefore *in* the expert distribution, which may make the reward model tolerate it.
- The hand-engineered baseline is weak (0 lines). A stronger hand reward (e.g. penalising holes and height) would make a better reference point.

---

7. Conclusion and future work

The proof of concept answers Q1 and Q3 positively:

- A small transformer models Game Boy RAM well enough to separate expert from non-expert play.
- Failures can be explained at the level of individual memory addresses.

For Q2 and Q4 the answer is partial:

- The learned reward behaves sensibly: it penalises the pause exploit, and it ranks behaviour correctly.
- RL with button-level PPO has not yet turned it into task performance.

Next steps, in order of expected value:

1. **Longer, multi-seed runs** (3M+ steps, 3 seeds) of ours vs. hand-engineered, to test whether lines cleared separate at all.
2. **Easier action space or warm start:** placement-level actions, or behaviour cloning on a few expert actions followed by RL on the learned reward.
3. **Faster reward model** (KV cache or recurrent variant) to make longer RL affordable.
4. **Independent metrics** (holes, stack height) computed outside the reward model, to break the circularity.
5. **The original target:** Super Mario Land and Pokémon, with human/TAS data, as in `PLAN.md`.

References

- Escontrela, A. et al. *Video Prediction Models as Rewards for Reinforcement Learning.* NeurIPS 2023.

- Chang, W.-D. et al. *IL-flOw: Imitation Learning from Observation using Normalizing Flows.* NeurIPS 2021 Robot Learning Workshop.
- Pathak, D. et al. *Curiosity-driven Exploration by Self-supervised Prediction.* ICML 2017.
- Burda, Y. et al. *Large-Scale Study of Curiosity-Driven Learning.* ICLR 2019.
- Burda, Y. et al. *Exploration by Random Network Distillation.* ICLR 2019.
- Anand, A. et al. *Unsupervised State Representation Learning in Atari.* NeurIPS 2019.
- Delfosse, Q. et al. *OCAtari: Object-Centric Atari 2600 Reinforcement Learning Environments.* RLJ 2024.
- Mudireddy, D. R., Patibandla, S. *PokeRL: Reinforcement Learning for Pokémon Red.* arXiv:2604.10812, 2026.
- Maksyuta, Y. et al. *Rank-Then-Act: Reward-Free Control from Frame-Order Progress.* arXiv:2607.01897, 2026.
- Schulman, J. et al. *Proximal Policy Optimization Algorithms.* arXiv:1707.06347, 2017.
- Lee, Y. *Tetris AI – The (Near) Perfect Bot* (heuristic weights), 2013.

Full bibliography: `notes/refs.bib`.

Appendix A — Reproducibility

Commands are in `README.md`. A legally obtained Tetris ROM is required (SHA-1 in `notes/roms.md`; not included). Reward-model checkpoints are in `runs/rm*/model.pt`; policy checkpoints (71 MB each) are not in the repository. Every run's config, git commit and per-update log are in `runs/<name>/`.

Appendix B — Approved deviations from the plan

ID	Change
D-001	Allow oracle-agent rollouts as a data source
D-002	Add VIPER-style RND bonus; faithful VIPER baseline
D-003	Narrow novelty framing (IL-flOw prior art)
D-004	Compress to a 2-day Tetris PoC
D-005	Scripted expert replaces PPO-oracle data
D-006	Hand reward: drop survival term, add per-piece bonus
D-007	Reward-model address set K = 289 (all varying bytes) instead of 128
D-008	Entropy coefficient 0.05 (chosen by pilot), applied to all runs
D-009	300k RL steps per run instead of 3M