

esrin

European Space Research Institute Largo Galileo Galilei 1 00044 Frascati Italy T +39 06 9418 01 F +39 06 9418 0280 www.esa.int

ESA NEOCC PYTHON INTERFACE

Prepared by C. Álvaro Arroyo Parejo

Document Type Software User Manual
Reference ESA-S2P-PD-MAN-0002

Issue/Revision 1.4.0

Date of Issue 29/10/2021

Status Final



APPROVAL

Title	ESA NEOCC Python Interface		
Issue Number	1	Revision Number	4.0
Author	C. Álvaro Arroyo Parejo	Date	29/10/2021
Approved by		Date of Approval	

CHANGE LOG

Reason for change	Issue Nr.	Revision Number	Date
Initial version	1	0	24/02/2021
Release of version 1.1	1	1	26/03/2021
Release of version 1.2	1	2	17/05/2021
Release of version 1.3	1	3	16/06/2021
Release of version 1.3.1	1	3.1	29/06/2021
Release of version 1.4	1	4	29/10/2021

CHANGE RECORD



Issue Number 1	Revision Nur	mber 4.0	
Reason for change	Date	Pages	Paragraphs(s)
New document	24/02/2021	All	
Adding ESA LATEXtemplate	26/03/2021	All	
Update requirements	17/05/2021	5	2
Update change log tables	17/05/2021	6, 13, 15	Tables
Adding clarification within examples	17/05/2021	9, 12	Examples
Adding note for use of <i>help</i> property in data frames	17/05/2021	10	
Change orbit_elements to orbital_elements	17/05/2021	12	
Change in impacts example	17/05/2021	9	
Adding close_encounter and impacted_objects to query_list method	17/05/2021	10	
Change in requirements and version	16/06/2021	5	
Change name neocc to core	16/06/2021	5	Section
Update change log tables	16/06/2021	6, 14, 17	Tables
Adding section Library Examples	16/06/2021	24-28	New Section
Adding section ESANEOCC Change Log	16/06/2021	28-29	New Section
Adding version 1.3.1 to ESANEOCC Change Log	29/06/2021	28	Bug fixed
Update change log tables	29/06/2021	7, 15, 18	Tables
Update requirements	29/10/2021	6	
Adding catalogues of NEAs to query_list	29/10/2021	8	
Remove note about physical_properties	29/10/2021	13	
Update <i>orbit_properties</i> example adding <i>orb_type</i> as attribute	29/10/2021	14	
Remove function get_dec_year	29/10/2021	13	
Update get_list_url parameters	29/10/2021	16	
Added definition of <i>orb_type</i> parameter	29/10/2021	22	
Update change log tables	29/10/2021	7, 15, 18	Tables
Adding version 1.4 to ESANEOCC Change Log	29/10/2021	30-31	Changes and Bug fixed

DISTRIBUTION

Name/Organisational Unit

Feel Free To Distribute (ESA)



Table of Contents:

1.	Introduction	5
2.	Installation	5
3.	Requirements	6
4.	Modules	6
5.	Library examples	25
6.	ESANFOCC Change Log	30



This is the documentation for the ESA NEOCC Portal Python interface library.

1. INTRODUCTION

ESA NEOCC Portal Python interface library makes the data that ESA NEOCC provides easily accessible through a Python program.

The main functionality of this library is to allow a programmer to easily retrieve:

- · All the NEAs
- Other data that the NEOCC provides (risk list, close approach list, etc.)
- All basic and advanced information regarding a NEA
- An ephemeris service for NEAs

2. INSTALLATION

The library is contained in ESANEOCC folder. In order to install the library:

- 1. Navigate to the proper directory where the *setup.py* is located.
- 2. The installation is doable through *pip install* command:

```
$ pip install .
```

Note: Consider installing **ESANEOCC** library into a virtualenv. This will avoid problems with previous installed dependencies.

The previous installation will install the library and its dependencies, but the dependencies will not be updated in case they are previously installed. In order to asssure that the packages version is the one determined in the **Requirements** the following command must be written:

```
$ pip install -r requirements.txt
```

This can be done in one command line:

```
$ pip install . && pip install -r requirements.txt
```

Warning! The previous command will force to install the package version of the requirements. This will upgrade/downgrade the version of any previous installed package that **ESANEOCC** library depends on.

Another installation method that will install the library and will update the dependencies is the following:



```
$ pip install . -upgrade-strategy eager
```

In this case, dependencies are upgraded regardless of whether the currently installed version satisfies the requirements of the upgraded package(s).

If you want to make sure none of your existing dependencies get upgraded, you can also do:

```
$ pip install . -no-deps
```

Note that, in the latter case, it is possible that some library functionalities will not work if the dependencies do not satisfy the **Requirements**.

3. REQUIREMENTS

ESA NEOCC Portal Python Interface Library works with Python 3.

The following packages are required for the library installation & use:

- astropy = 4.3.1
- beautifulsoup4 = 4.10.0
- |xm| = 4.6.3
- pandas = 1.3.4
- parse = 1.19.0
- requests = 2.26.0
- scipy = 1.7.1

For tests the following packages are required:

- pytest = 6.2.1
- **astroquery** = 0.4.3

4. MODULES

ESANEOCC.core

Main module from ESA NEOCCS library. This module contains the two main methods of the library: *query_list* and *query_object*. The information is obtained from ESA Near-Earth Object Coordination Centres (NEOCC) web portal: https://neo.ssa.esa.int/.

- Project: NEOCC portal Python interface
- Property: European Space Agency (ESA)
- Developed by: Elecnor Deimos



Author: C. Álvaro Arroyo Parejo

• Issue: 1.4.0

· Date: 29-10-2021

• Purpose: Main module which gets NEAs data from https://neo.ssa.esa.int/

• Module: core.py

• History:

Version	Date	Change History
1.0	26-02-2021	Initial version
1.1	24-03-2021	New docstrings
1.2	17-05-2021	Adding new docstrings for help property in dataframes and tab
		specification for obtaining attributes.
		For orbit properties <i>orbit_elements</i> changes to <i>orbital_elements</i> .
		Adding impacted objects lists
		Minor typos changes.
1.3	16-06-2021	Renamed module from neocc to core
		specification for obtaining attributes.
		Define methods as static
1.3.1	29-06-2021	No changes
1.4	29-10-2021	Adding new docstrings.
		Change method for obtaining physical properties

©Copyright [European Space Agency][2021] All rights reserved

class ESANEOCC.core.ESAneoccClass

Class to init ESA NEOCC Python interface library.

static query_list(list_name)

Get requested list data from ESA NEOCC.

Different lists that can be requested are:

All NEA list: nea list

Updated NEA list: updated_nea

Monthly computation date: monthly_update

Risk list (normal): risk_list

Risk list (special): risk_list_special

• Close approaches (upcoming): close_approaches_upcoming



- Close approaches (recent): close approaches recent
- Priority list (normal): priority_list
- Priority list (faint): priority list faint
- Close encounter list: close encounter
- Impacted objects: impacted_objects
- Catalogue of NEAs (current date): neo_catalogue_current
- Catalogue of NEAs (middle arc): neo catalogue middle

These lists are referenced in https://neo.ssa.esa.int/computer-access

Parameters list_name (str) - Name of the requested list. Valid names are: nea_list, risk_list, risk_list_special, close_approaches_upcoming, close_approaches_recent, priority_list, priority_list_faint, close_encounter, impacted_objects, neo_catalogue_current and neo_catalogue_middle.

Returns neocc_lst – Data Frame which contains the information of the requested list

Return type pandas. Series or pandas. DataFrame

Examples

NEA list: The output of this list is a *pandas.Series* which contains the list of all NEAs currently considered in the NEOCC system.

```
>>> from ESANEOCC import neocc
>>> list_data = neocc.query_list(list_name='nea_list')
>>> list data
0
                 433 Eros
1
               719 Albert
2
              887 Alinda
3
             1036 Ganymed
                1221 Amor
25191
                   2021DY
25192
                 2021DY1
25193
                  2021DZ
25194
                  2021DZ1
25195
                 6344P-L
Name: 0, Length: 25196, dtype: object
```

Each asteroid can be accessed using its index. This information can be used as input for *query object* method.

```
>>> list_data[4]
'1221 Amor'
```



Other lists: The output of this list is a *pandas.DataFrame* which contains the information of the requested list.

```
>>> from ESANEOCC import neocc
>>> list_data = neocc.query_list(list_name='close_approaches_upcoming')
>>> list_data
                                     ... Rel. vel in km/s
         Object Name
                              Date
0
              2021DE 2021.156164 ...
                                                        26.0
              2021DM 2021.158904
                                                        10.2
1
2
                                                        13.6
              2011DW 2021.161644
3
            2011EH17 2021.161644
                                                        16.8
4
             2016DV1 2021.164384
                                                        18.6
                                    . . .
                                                         . . .
                                    . . .
                 . . .
              2020DF 2022.120548
141
                                    . . .
                                                         8.6
             2018CW2 2022.131507
                                                        10.8
142
                                    . . .
143
             2020CX1 2022.131507
                                                         8.2
144 455176 1999VF22 2022.142466
                                                        25.1
                                    . . .
145
             2017CX1 2022.145205
                                                         5.0
                                    . . .
[146 rows x 10 columns]
```

The information of the columns can be accessed through (see pandas for further information about data access):

```
>>> list_data['Object Name']
0
                 2021DE
1
                 2021DM
2
                 2011DW
3
               2011EH17
4
                2016DV1
141
                 2020DF
142
                2018CW2
143
                2020CX1
144
       455176 1999VF22
                2017CX1
Name: Object Name, Length: 146, dtype: object
```

And the information of the rows can be accessed using:

```
>>> list data.iloc[2]
Object Name
                          2011DW
Date
                        2021.16
                        5333057
Miss Distance in km
Miss Distance in au
                       0.035649
Miss Distance in LD
                        13.874
Diameter in m
                              90
*=Yes
                              *
                            22.9
Η
```

(continues on next page)



(continued from previous page)

Max Bright	16.4
Rel. vel in km/s	13.6
Name: 2, dtype: object	

Note: If the contents request fails the following message will be printed:

Initial attempt to obtain list failed. Reattempting

Then a second request will be automatically sent to the NEOCC portal.

static query_object (name, tab, **kwargs)
Get requested object data from ESA NEOCC.

Parameters

- name (str) Name of the requested object
- tab (str) Name of the request tab. Valid names are: summary, orbit_properties, physical_properties, observations, ephemerides, close_approaches and impacts.
- **kwargs (str) Tabs orbit_properties and ephemerides tabs required additional arguments to work:
 - orbit_properties: the required additional arguments are:
 - * orbital_elements : str (keplerian or equinoctial)
 - * orbit_epoch : str (present or middle)
 - ephemerides: the required additional arguments are:
 - * *observatory*: str (observatory code, e.g. 500, J04, etc.)
 - * start : str (start date in YYYY-MM-DD HH:MM)
 - * stop: str (end date in YYYY-MM-DD HH:MM)
 - * *step* : str (time step, e.g. 2, 15, etc.)
 - * step unit : str (e.g. days, minutes, etc.)

Returns neocc_obj — Object data which contains different attributes depending on the tab selected.

Return type object



Examples

Impacts, Physical Properties and Observations: This example tries to summarize how to access the data of this tabs and how to use it. Note that this classes only require as inputs the name of the object and the requested tab.

The information can be obtained introducing directly the name of the object, but it can be also added from the output of a *query list* search:

```
>>> from ESANEOCC import neocc
>>> ast_impacts = neocc.query_object(name='1979XB', tab='impacts')
```

or

or

The output provides an object with the different attributes:

```
>>> ast_impacts.<tab>
ast_impacts.additional_note
ast_impacts.arc_end
ast_impacts.arc_start
ast_impacts.computation
ast_impacts.observation_accepted
ast_impacts.computation
```

By adding the attribute its information can be accessed:

```
>>> ast_impacts.impacts
                                      ... Exp. Energy in MT
           date
                       MJD
                           sigma
                                                              PS
→ TS
0 2056-12-12.902 72344.902 0.255
                                                   0.011500 - 3.22
1 2065-12-16.462 75635.463 -1.110
                                                  0.000090 -5.36
                                                   0.002390 - 4.03
2 2086-12-16.663 83305.664 -1.101
                                                   0.000131 -5.36
 2101-12-14.203 88781.204 -0.384
                                       . . .
```

(continues on next page)



(continued from previous page)

4	2105-12-12.764	90240.765	1.003	 0.000574 -4.75
\hookrightarrow	0			
5	2113-12-14.753	93164.753	0.706	 0.018500 -3.25
\hookrightarrow	0			
6	2113-12-14.756	93164.756	0.708	 0.000163 -5.30
\hookrightarrow	0			
7	2117-12-15.496	94626.496	-1.316	 0.000069 -5.68
\hookrightarrow	0			
[8	rows x 11 columns	5]		

Note: Most of the dataframes of the object tabs contain the help property which contains information about the fields of the dataframe.

```
>>> print(ast impacts.impacts.help)
Data frame with possible impacts information:
-Date: date for the potential impact in YYYY-MM-DD.ddd format
-MJD: Modified Julian Day for the potential impact
-sigma: approximate location along the Line Of Variation (LOV)
in sigma space
-sigimp: The lateral distance in sigma-space from the LOV to
the Earth surface. A zero implies that the LOV passes through
the Earth-dist: Minimum Distance in Earth radii. The lateral
distance from the LOV to the centre of the Earth
-width: one-sigma semi-width of the Target Plane confidence
region in Earth radii
-stretch: Stretching factor. It indicates how much the
confidence region at the epoch has been stretched by the time
of the approach. This is a close cousin of the Lyapounov
exponent. Units are in Earth radii divided by sigma (RE/sig)
-p_RE: probability of Earth Impact (IP)
-Exp. Energy in MT: Expected energy. It is the product of the
impact energy and the impact probability
-PS: Palermo Scale
-TS: Torino Scale
```

Another example is shown to obtain the physical properties:

```
>>> from ESANEOCC import neocc
>>> properties = neocc.query_object(name='433', tab='physical_

--properties')
```

Again, the output provides an object with different attributes:

```
>>> properties.<tab>
```

(continues on next page)



(continued from previous page)

```
properties.physical_properties properties.sources
>>> properties.physical properties
                    Property
                                  Values Unit Source
0
            Rotation Period
                                    5.27
                                           h
                                                  「41
1
                     Quality
                                      4
                                                  [4]
2
                   Amplitude 0.04-1.49
                                                  [4]
                                          mag
3
         Rotation Direction
                                   PRO
4
                Spinvector L
                                                  [1]
                                      16
                                          deg
5
                Spinvector B
                                      9
                                          deg
                                                  [1]
6
                                                  [2]
                    Taxonomy
                                      Sq
7
             Taxonomy (all)
                                       S
                                                  [3]
8
                                  10.31
     Absolute Magnitude (H)
                                          maa
                                                  [5]
9
        Slope Parameter (G)
                                  0.46**
                                                  [6]
                                          mag
10
                      Albedo
                                    0.24
                                                 [9]
11
                                   23300
                    Diameter
                                                 [10]
                                           m
12
    Color Index Information
                                    0.39 R-I
                                                 [11]
                               Visual S
13
                   Sightings
                                                 [13]
```

Note: For the case of tab Observations there are objects which contain Roving observer and satellite observations. In the original requested data the information of these observations produces two lines of data, where the second line does not fit the structure of the data frame (https://www.minorplanetcenter.org/iau/info/OpticalObs.html). In order to solve this problem those second lines have been extracted in another attribute (e.g. sat observations or roving observations) to make the data more readable.

Since this information can be requested in pairs, i.e. it is needed to access both lines of data, this can be made using the date of the observations which will be the same for both attributes:

```
>>> ast_observations = neocc.query_object(name='99942',
tab='observations')
>>> sat_obs = ast_observations.sat_observations
>>> sat_obs
    Design.
              Τ
                  N YYYY MM DD.dddddd
                                          ... Obs Code
            K
0
      99942 S s
                      2020 12
                                18.97667
                                                    C51
      99942 S s
                                 19.10732
1
                      2020 12
                                                    C51
                      . . .
                                      . . .
                                           . . .
                                                    . . .
                      2021
10
      99942
            S s
                             1
                                 16.92315
                                                    C53
      99942 S s
                      2021
                                                    C53
11
                            1
                                 19.36233
      99942 S s
                      2021
                             1
12
                                 19.36927
                                                    C53
>>> opt_obs = ast_ast_observations.optical_observations
>>> opt_obs.loc[opt_obs['DD.ddddddd'] == sat_obs['DD.ddddddd'][0]]
        Design.
                K T N YYYY MM
                                   ... Obs Code
                                                  Chi A
                   S
4582
        99942
                 S
                         2020 12
                                             C51 1.13 1
                                  . . .
[1 rows x 33 columns]
```



Close Approaches: This example corresponds to the class close approaches. As for the previous example, the information can be obtained by directly introducing the name of the object or from a previous *query_list* search.

In this particular case, there are no attributes and the data obtained is a DataFrame which contains the information for close approaches:

```
>>> close_appr = neocc.query_object(name='99942', tab='close_approaches
' )
>>> close_appr
   BODY CALENDAR-TIME ...
                                 WIDTH PROBABILITY
  EARTH 1957/04/01.13908 ... 1.318000e-08
                                                    1.000
  EARTH 1964/10/24.90646 ... 1.119000e-08
                                                    1.000
1
                                                    1.000
  EARTH 1965/02/11.51118 ... 4.004000e-09
                                                   0.821
16 EARTH 2080/05/09.23878 ... 1.206000e-06
17 EARTH 2087/04/07.54747 ... 1.254000e-08
                                                    0.327
[18 rows x 10 columns]
```

Orbit Properties: In order to access the orbit properties information, it is necessary to provide two additional inputs to *query_object* method: **orbital_elements** and **orbit_epoch**.

It is mandatory to write these two parameters as: *orbit epoch*= to make the library works.

```
>>> ast_orbit_prop = neocc.query_object(name='99942',
tab='orbit_properties',orbital_elements='keplerian', orbit_epoch=
→'present')
>>> ast_orbit_prop.<tab>
ast_orbit_prop.anode
                             ast_orbit_prop.ngr
ast_orbit_prop.aphelion
                            ast_orbit_prop.orb_type
                            ast_orbit_prop.perihelion
ast_orbit_prop.cor
ast_orbit_prop.cov
                            ast_orbit_prop.period
ast_orbit_prop.dnode
                            ast_orbit_prop.pha
ast_orbit_prop.epoch
                            ast_orbit_prop.rectype
ast_orbit_prop.form
                            ast_orbit_prop.refsys
ast_orbit_prop.kep
                            ast_orbit_prop.rms
ast_orbit_prop.lsp
                            ast_orbit_prop.u_par
                             ast_orbit_prop.vinfty
ast_orbit_prop.mag
ast_orbit_prop.moid
```

Ephemerides: In order to access ephemerides information, it is necessary to provide five additional inputs to *query_object* method: **observatory**, **start**, **stop**, **step** and **step_unit***.

It is mandatory to write these five parameters as: *observatory*= to make the library works.

```
>>> ast_ephemerides = neocc.query_object(name='99942', tab='ephemerides', observatory='500', start='2019-05-08 01:30',
```

(continues on next page)



(continued from previous page)

```
stop='2019-05-23 01:30', step='1', step_unit='days')
>>> ast_ephemerides.
ast_ephemerides.ephemerides ast_ephemerides.tinit
ast_ephemerides.observatory ast_ephemerides.tstep
ast_ephemerides.tfinal
```

ESANEOCC.lists

This module contains all the methods required to request the list data, obtain it from the ESA NEOCC portal and parse it to show it properly.

• Project: NEOCC portal Python interface

Property: European Space Agency (ESA)

• Developed by: Elecnor Deimos

Author: C. Álvaro Arroyo Parejo

• Issue: 1.4

• Date: 29-10-2021

• Purpose: Module which request and parse list data from ESA NEOCC

Module: lists.py

• History:

Version	Date	Change History
1.0	26-02-2021	Initial version
1.1	24-03-2021	New docstrings
1.2	17-05-2021	Adding new docstrings for <i>help</i> property in dataframes.
		Adding timeout of 90 seconds.
		Adding parse_impacted function for new list
1.3	16-06-2021	URL and Timeout from configuration file for astroquery implementation.
		Change dateformat to datetime ISO format.
1.3.1	29-06-2021	Hotfix in Risk list (TS and Velocity)
1.4	29-10-2021	Adding Catalogue of NEAS (current date and middle arc).
		Update docstrings.

©Copyright [European Space Agency][2021] All rights reserved

ESANEOCC.lists.get_list_data(url, list_name)

Get requested parsed list from url.



Parameters

- list_name (str) Name of the requested list.
- url (str) URL of the requested list.

Returns neocc_lst – Data frame which contains the data of the requested list.

Return type pandas. Series or pandas. Data Drame

ESANEOCC.lists.get_list_url(list_name)

Get url from requested list name.

Parameters list_name (str) — Name of the requested list. Valid names are: nea_list, risk_list, risk_list_special, close_appr_upcoming, close_appr_recent, priority_list, priority_list_faint, close_encounter, impacted objects, neo catalogue current and neo catalogue middle.

Returns url – Final URL string.

Return type str

Raises KeyError – If the requested list name is not in the dictionary

ESANEOCC.lists.parse_clo(data_byte_d)

Parse and arrange close approaches lists.

Parameters data_byte_d (object) - Decoded StringIO object.

Returns neocc_lst – Data frame with close approaches list data parsed.

Return type pandas. Series or pandas. DataFrame

ESANEOCC.lists.parse_encounter(data_byte_d)

Parse and arrange close encounter list.

Parameters data_byte_d (object) - Decoded StringIO object.

Returns neocc_lst – Data frame with close encounter list data parsed.

Return type pandas. Series or pandas. DataFrame

ESANEOCC.lists.parse_impacted(data byte d)

Parse and arrange close encounter list.

Parameters data_byte_d (object) - Decoded StringIO object.

Returns neocc_lst – Data frame with impacted objects list data parsed.

Return type pandas. Series or pandas. DataFrame

ESANEOCC.lists.parse_list(list_name, data_byte_d)

Switch function to select parse method.

Parameters

• list_name (str) - Name of the requested list.



• data_byte_d (object) - Decoded StringIO object.

Returns neocc_lst – Data frame with data from the list parsed.

Return type pandas. Series or pandas. DataFrame

ESANEOCC.lists.parse_nea(data_byte_d)

Parse and arrange all NEA list.

Parameters data_byte_d (object) - Decoded StringIO object.

Returns neocc Ist – Data frame with NEA list data parsed.

Return type pandas. Series or pandas. DataFrame

ESANEOCC.lists.parse_neo_catalogue(data_byte_d)

Parse neo catalogues (current or middle arc) lists.

Parameters data_byte_d (object) - Decoded StringIO object.

Returns neocc_lst – Data frame with catalogues of NEAs list data parsed.

Return type pandas. Series or pandas. DataFrame

ESANEOCC.lists.parse_pri(data_byte_d)

Parse and arrange priority lists.

Parameters data_byte_d (object) - Decoded StringIO object.

Returns neocc_lst – Data frame with priority list data parsed.

Return type pandas. Series or pandas. DataFrame

ESANEOCC.lists.parse_risk(data_byte_d)

Parse and arrange risk lists.

Parameters data_byte_d (object) - Decoded StringIO object.

Returns neocc_lst – Data frame with risk list data parsed.

Return type pandas. Series or pandas. DataFrame

ESANEOCC.tabs

This module contains all the methods required to request the data from a particular object, obtain it from the ESA NEOCC portal and parse it to show it properly. The information of the object is shows in the ESA NEOCC in different tabs that correspond to the different classes within this module.

Project: NEOCC portal Python interface

Property: European Space Agency (ESA)

Developed by: Elecnor Deimos

Author: C. Álvaro Arroyo Parejo

• Issue: 1.4



• Date: 29-10-2021

• Purpose: Module which request and parse list data from ESA NEOCC

Module: tabs.py

• History:

Version	Date	Change History
1.0	26-02-2021	Initial version
1.1	24-03-2021	Physical properties functionality added
1.2	17-05-2021	Adding <i>help</i> property for dataframes.
		Parsing of diameter property in summary and physical_properties
		has been modified to add robustness.
		In physical_properties the parsing of properties has been
		modified to include cases with more information.
		Adding timeout of 90 seconds.
1.3	16-06-2021	URLs and timeout from configuration file for astroquery implementation
		Change time format to datetime ISO format
		Change to correct types in attributes (e.g., matrices, etc.)
		Change ephemerides skipfooter to fix bug
		Change get_matrix from orbit_properties for objects
		with 2 non-gravitational parameters
1.3.1	29-06-2021	No changes
1.4	29-10-2021	Tab physical_properties has been recoded to parse the information
		through a request in the portal instead of parsing the html.
		Get URL function now contains the file extension for physical
		properties.
		Parsing of ephemerides has been change to adapt new format.
		orb_type attribute added in tab orbit_properties.
		Bug fix in tab observations.
		Adding redundancy for tab summary parsing.

©Copyright [European Space Agency][2021] All rights reserved

class ESANEOCC.tabs.AsteroidObservations

This class contains information of asteroid observations.

version



File version.

Type int

errmod

Error model for the data.

Type str

rmsast

Root Mean Square for asteroid observations.

Type float

rmsmag

Root Mean Square for magnitude.

Type float

optical_observations

Data frame which contains optical observations (without roving observer and satellite observation).

Type pandas.DataFrame

radar_observations

Data structure which contains radar observations.

Type pandas.DataFrame

roving_observations

Data structure which contains roving observer observations.

Type pandas.DataFrame

sat observations

Data structure which contains satellite observations.

Type pandas.DataFrame

class ESANEOCC.tabs.CloseApproaches

This class contains information of object close approaches.

static clo_appr_parser(data_obj, name)

Parse and arrange the close approaches data.

Parameters data_obj (object) – Object in byte format.

Returns df_close_appr – Data frame with the close approaches information.

Return type pandas. DataFrame

Raises ValueError – If file is empty.

class ESANEOCC.tabs.Ephemerides

This class contains information of object ephemerides.



observatory

Name of the observatory from which ephemerides are obtained.

Type str

tinit

Start date from which ephemerides are obtained.

Type str

tfinal

End date from which ephemerides are obtained.

Type str

tstep

Time step and time unit used during ephemerides calculation.

Type str

ephemerides

Data frame which contains the information of the object ephemerides

Type pandas.DataFrame

class ESANEOCC.tabs.EquinoctialOrbitProperties

This class contains information of equinoctial asteroid orbit properties. This class inherits the attributes from OrbitProperties.

equinoctial

Data frame which contains the equinoctial elements information.

Type pandas.DataFrame

rms

Root Mean Square for equinoctial elements.

Type DataFrame

eiq

Eigenvalues for the covariance matrix.

Type pandas.DataFrame

wea

Eigenvector corresponding to the largest eigenvalue.

Type pandas.DataFrame

cov

Covariance matrix for equinoctial elements.

Type pandas.DataFrame

nor

Normalization matrix for equinoctial elements.



Type pandas.DataFrame

class ESANEOCC.tabs.Impacts

This class contains information of object possible impacts.

impacts

Data frame where are listed all the possible impactors.

Type pandas.DataFrame

arc start

Starting date for optical observations.

Type str

arc end

End date for optical observations.

Type str

observations_accepted

Total number of observations subtracting rejected observations.

Type int

observations_rejected

Number of observations rejected.

Type int

computation

Date of computation (in format YYYYMMDD MJD TimeSys)

Type str

info

Information from the footer of the requested file.

Type str

additional_note

Additional information. Some objects (e.g. 99942 Apophis) have an additional note after the main footer.

Type str

class ESANEOCC.tabs.KeplerianOrbitProperties

This class contains information of keplerian asteroid orbit properties. This class inherits the attributes from OrbitProperties.

kep

Data frame which contains the keplerian elements information.

Type pandas.DataFrame



perihelion

Orbit perihelion in au.

Type int

aphelion

Orbit aphelion in au.

Type int

anode

Ascending node-Earth separation in au.

Type int

dnode

Descending node-Earth separation in au.

Type int

moid

Minimum Orbit Intersection distance in au.

Type int

period

Orbit period in days.

Type int

pha

Potential hazardous asteroid classification.

Type string

vinfty

Infinite velocity.

Type int

u_par

Uncertainty parameter as defined by MPC.

Type int

orb_type

Type of orbit.

Type int

rms

Root mean square for keplerian elements

Type pandas.DataFrame

cov

Covariance matrix for keplerian elements



Type pandas.DataFrame

cor

Correlation matrix for keplerian elements

Type pandas.DataFrame

class ESANEOCC.tabs.OrbitProperties

This class contains information of asteroid orbit properties.

form

File format.

Type str

rectype

Record type.

Type str

refsys

Default reference system.

Type str

epoch

Epoch in MJD format.

Type str

mag

Data frame which contains magnitude values.

Type pandas.DataFrame

lsp

Data structure with information about non-gravitational parameters (model, numer of parameters, dimension, etc.).

Type pandas.DataFrame

ngr

Data frame which contains non-gravitational parameters.

Type pandas.DataFrame

class ESANEOCC.tabs.PhysicalProperties

This class contains information of asteroid physical properties

physical_properties

Data structure containing property, value, units and source from the complete set of physical properties

Type DataFrame



sources

Data structure containing source number, name and additional information

Type DataFrame

Raises ValueError – If the name of the object is not found

class ESANEOCC.tabs.Summary

This class contains the information from the Summary tab.

physical_properties

Data frame which contains the information of the object physical properties, their value and their units.

Type pandas.DataFrame

discovery_date

Provides the object discovery date

Type str

observatory

Provides the name of the observatory where object was discovered

Type str

ESANEOCC.tabs.get_indexes(dfobj, value)

Get a list with location index of a value or string in the DataFrame requested.

Parameters

- **dfobj** (pandas.DataFrame) Data frame where the value will be searched.
- value (str, int, float) String, integer or float to be searched.

Returns listofpos – List which contains the location of the value in the Data frame. The first elements will correspond to the index and the second element to the columns

Return type list

ESANEOCC.tabs.get_object_data(url)

Get object in byte format from requested url.

Parameters url (str) – URL of the requested data.

Returns data_obj – Object in byte format.

Return type object

ESANEOCC.tabs.get_object_url(name, tab, **kwargs)

Get url from requested object and tab name.

Parameters



- name (str) Name of the requested object.
- tab (str) Name of the request tab. Valid names are: summary, orbit_properties, physical_properties, observations, ephemerides, close_approaches and impacts.
- **kwargs (str) orbit_properties and ephemerides tabs required additional arguments to work:
 - orbit_properties: the required additional arguments are:
 - * orbital_elements : str (keplerian or equinoctial)
 - * orbit_epoch : str (present or middle)
 - ephemerides: the required additional arguments are:
 - * observatory: str (observatory code, e.g. 500, J04, etc.)
 - * start : str (start date in YYYY-MM-DD HH:MM)
 - * stop: str (end date in YYYY-MM-DD HH:MM)
 - * *step* : str (time step, e.g. 2, 15, etc.)
 - * step_unit : str (e.g. days, minutes, etc.)

Returns url – Final url from which data is requested.

Return type string

Raises

- **KeyError** If the requested tab is not in the dictionary.
- ValueError If the elements requested are not valid.

5. LIBRARY EXAMPLES

How to export data

To JSON

Most of the data obtained from ESANEOCC Python Interface is collected as *pandas.Series* or *pandas.DataFrame* and, therefore it can be easily converted to JSON format. Here is a template that you may use in Python to export pandas DataFrame to JSON:

```
>>> df.to_json(r'Path to store the exported JSON file/ FileName.json')
```

The complete use of this function can be found in pandas.DataFrame.to_json, where different examples are shown. It also shows how to obtain the different types of JSON files.



```
>>> from ESANEOCC import neocc
>>> from astropy.table import Table
>>> ast = neocc.query_object(name='99942', tab='physical_properties')
>>> ast.physical_properties
                   Property
                                Values Unit Source
0
            Rotation Period
                                 30.56
                                        h
                                              [4]
                                   3
1
                   Quality
                                               [4]
                  Amplitude
2
                                   1.0 mag
3
        Rotation Direction
                                RETRO
                                 250 deg
4
               Spinvector L
                                               [1]
5
               Spinvector B
                              -7.50E1 deg
                                               [1]
6
                   Taxonomy
                                 S/Sq
                                               [2]
7
             Taxonomy (all) Sq,Scomp
                                               [3]
8
    Absolute Magnitude (H)
                               19.09 mag
                                               [5]
9
        Slope Parameter (G)
                                 0.24 mag
                                               [1]
10
                                 0.285
                     Albedo
                                               [8]
11
                                  375 m
                                              [9]
                   Diameter
12 Color Index Information
                                 0.362 R-I
                                              [10]
13
                 Sightings Radar R -
                                             [11]
>>> ast_json = ast.physical_properties.to_json(orient='split')
>>> parsed = json.loads(ast_json)
>>> print(json.dumps(parsed, indent= 4))
{
    'columns': [
        'Property',
        'Values',
        'Unit',
        'Source'
    ],
    'index': [
        Ο,
        1,
        2,
        3,
        4,
        5,
        6,
        7,
        8,
        9,
        10,
        11,
        12,
        13
    'data': [
        [
```

(continues on next page)



(continued from previous page)

```
'Rotation Period',
    '30.56',
    'h',
    '[4]'
],
[
    'Quality',
    131,
    '-',
    '[4]'
],
[
    'Amplitude',
    '1.0',
    'mag',
    '[4]'
],
[
    'Rotation Direction',
    'RETRO',
    '-',
    '[1]'
],
[
    'Spinvector L',
    '250',
    'deg',
    '[1]'
],
[
    'Spinvector B',
    '-7.50E1',
    'deg',
    '[1]'
],
[
    'Taxonomy',
    'S/Sq',
    '-',
    '[2]'
],
    'Taxonomy (all)',
    'Sq, Scomp',
    '-',
    '[3]'
```

(continues on next page)



(continued from previous page)

```
],
         Γ
             'Absolute Magnitude (H)',
             '19.09',
             'mag',
             '[5]'
        ],
         [
             'Slope Parameter (G)',
             '0.24',
             'mag',
             '[1]'
         ],
             'Albedo',
             '0.285',
             '-',
             '[8]'
        ],
         [
             'Diameter',
             '375',
             'm',
             '[9]'
         ],
         [
             'Color Index Information',
             '0.362',
             'R-I',
             '[10]'
        ],
         [
             'Sightings',
             'Radar R',
             '-',
             '[11]'
    ]
}
```



To Tables (VO Tables)

Virtual Observatory (VO) tables are a new format developed by the International Virtual Observatory Alliance to store one or more tables. This format is included within ATpy library. However, most of ATpys functionalities has now been incorporated into Astropy library and the developers recommended to use the Astropy Tables.

Astropy documentation details how to interface with the Pandas library, i.e., how to convert data in pandas. Series or pandas. Data Frame formats into Astropy Tables and vice versa.

```
>>> from ESANEOCC import neocc
>>> from astropy.table import Table
>>> ast = neocc.query_object(name='433', tab='physical_properties')
>>> ast.physical_properties
                  Property
                              Values Unit Source
\cap
           Rotation Period
                               5.27 h [4]
1
                  Quality
                                            [4]
                                  4
2
                 Amplitude 0.04-1.49 mag
                                            Γ41
3
        Rotation Direction
                               PRO
                                            [1]
4
              Spinvector L
                                 16
                                      deg
                                            [1]
5
              Spinvector B
                                  9 deg
                                            [1]
6
                  Taxonomy
                                  Sq
                                            [2]
7
            Taxonomy (all)
                                  S
                                            [3]
                             10.31 mag
8
    Absolute Magnitude (H)
                                            [5]
       Slope Parameter (G)
9
                              0.46** mag
                                            [6]
10
                   Albedo
                               0.24 -
                                            [9]
11
                               23300
                                      m
                 Diameter
                                           [10]
12
  Color Index Information
                                0.39 R-I
                                           [11]
13
                 Sightings Visual S
                                           [13]
>>> ast_astropy = Table.from_pandas(ast.physical_properties)
```



<pre>>>> ast_astropy <table length="14"></table></pre>			
Property	Values	Unit	Source
str23	str8	str3	str4
Rotation Period	5.27	 h	[4]
	4		
Amplitude	0.04-1.49	mag	[4]
Rotation Direction	PRO	_	[1]
Spinvector L	16	deg	[1]
Spinvector B	9	deg	[1]
_	Sq		
Taxonomy (all)			
Absolute Magnitude (H)	10.31	mag	[5]
Slope Parameter (G)	0.46**	mag	[6]
Albedo	0.24	_	[9]
	23300		
Color Index Information	0.39	R-I	[11]
Sightings	Visual S	_	[13]

Visit Interfacing with the Pandas Package for further information.

6. ESANEOCC CHANGE LOG

Version 1.4

Changes

- The type of the orbit is now obtained as attribute in tab *orbit_properties*.
- The format of the ephemerides data has been modified to adapt to the change of format of the ephemerides provided by NEOCC portal. This modification includes new parameters for the columns and also changes the precion of the Magnitude values up to two decimal digits.
- Tab *physical_properties* now contains all the values (if exist) for the different properties.
- There are two new lists implemented: Catalogue of NEAs (current date) and Catalogue of NEAs (middle arc).
- Parsing of tab *summary* is more robust.



Bug Fixes

• Fixed tab *observations* which failed to process the information of some asteroids.

Version 1.3.1

Bug Fixes

• Fixed bug where *risk_list* and *risk_list_special* were not displaying Torino Scale and Velocity.

Version 1.3

Changes

- astropy library has been added as required package.
- neocc.py module has been renamed to core.py in order to be consistent with Astroquery.
- core.py has been modified in order to be consistent with Astroquery (main class and static methods).
- Dates/time columns or data have been converted to datetime ISO format.
- Abbreviations contain now complete expressions (e.g., close_appr_upcoming to close approaches_upcoming)
- The documentation explains how to obtain JSON and Table format from data retrieved from the library.
- Time performance improvement in obtaining physical properties.

Bug Fixes

- Fixed two-points ephemerides generation fails
- Fixed physical properties generation for objects with Area-to-mass ratio and Yarkovsky parameter.
- Fixed orbit properties generation for objects with Area-to-mass ratio and Yarkovsky parameter.