



**esrin**

European Space Research Institute  
Largo Galileo Galilei 1  
00044 Frascati  
Italy  
T +39 06 9418 01  
F +39 06 9418 0280  
[www.esa.int](http://www.esa.int)

## ESA NEOCC PYTHON INTERFACE

Prepared by	C. Álvaro Arroyo Parejo
Document Type	Software User Manual
Reference	
Issue/Revision	1.0
Date of Issue	24/03/2021
Status	Final

## APPROVAL

Title	ESA NEOCC Python Interface		
Issue Number	1	Revision Number	0
Author	C. Álvaro Arroyo Parejo	Date	24/03/2021
Approved by	Date of Approval		

## CHANGE LOG

Reason for change	Issue Nr.	Revision Number	Date
Initial version	0	1	24/02/2021
Published	1	0	24/03/2021

## CHANGE RECORD

Issue Number	1	Revision Number	0
Reason for change	Date	Pages	Paragraphs(s)
New document	24/02/2021	All	
Adding ESA L <sup>A</sup> T <sub>E</sub> Xtemplate	24/03/2021	All	

## DISTRIBUTION

Name/Organisational Unit
Feel Free To Distribute (ESA)



**Table of Contents:**

1. Introduction ..... 4

2. Installation..... 4

3. Requirements ..... 4

4. ESANEOCC.neocc ..... 5

5. ESANEOCC.lists ..... 12

6. ESANEOCC.tabs..... 14

This is the documentation for the ESA NEOCC Portal Python interface library.

## 1. INTRODUCTION

ESA NEOCC Portal Python interface library makes the data that [ESA NEOCC](#) provides easily accessible through a Python program.

The main functionality of this library is to allow a programmer to easily retrieve:

- All the NEAs
- Other data that the NEOCC provides (risk list, close approach list, etc.)
- All basic and advanced information regarding a NEA
- An ephemeris service for NEAs

## 2. INSTALLATION

The library is contained in ESANEOCC folder. In order to install the library:

1. Navigate to the proper directory where the *setup.py* is located.
2. The installation is doable through *pip install* command:

```
$ pip install .
```

## 3. REQUIREMENTS

ESA NEOCC Portal Python Interface Library works with Python 3.

The following packages are required for the library installation & use:

- [beautifulsoup4](#) = 4.9.3
- [lxml](#) = 4.6.2
- [pandas](#) = 1.2.2
- [parse](#) = 1.19.0
- [requests](#) = 2.25.1
- [scipy](#) = 1.6.1

For tests the following packages are required:

- [pytest](#)

## 4. ESANE OCC.NEOCC

Main module from ESA NEOCCS library. This module contains the two main methods of the library: *query\_list* and *query\_object*. The information is obtained from ESA Near-Earth Object Coordination Centres (NEOCC) web portal: <https://neo.ssa.esa.int/>.

- Project: NEOCC portal Python interface
- Property: European Space Agency (ESA)
- Developed by: Elecnor Deimos
- Author: C. Álvaro Arroyo Parejo
- Issue: 1.0
- Date: 26-02-2021
- Purpose: Main module which gets NEAs data from <https://neo.ssa.esa.int/>
- Module: neocc.py
- History:

Version	Date	Change History
1.0	26-02-2021	Initial version

©Copyright [European Space Agency][2021] All rights reserved

`ESANE OCC.neocc.query_list(list_name)`

Get requested list data from ESA NEOCC.

Different lists that can be requested are:

- All NEA list: *nea\_list*
- Risk list (normal): *risk\_list*
- Risk list (special): *risk\_list\_special*
- Close approaches (upcoming): *close\_appr\_upcoming*
- Close approaches (recent): *close\_appr\_recent*
- Priority list (normal): *priority\_list*
- Priority list (faint): *priority\_list\_faint*

These lists are referenced in <https://neo.ssa.esa.int/computer-access>

**Parameters** `list_name` (*str*) – Name of the requested list. Valid names are: *nea\_list*, *risk\_list*, *risk\_list\_special*, *close\_appr\_upcoming*, *close\_appr\_recent*, *priority\_list*, *priority\_list\_faint*.

**Returns neocc\_lst** – Data Frame which contains the information of the requested list

**Return type** *pandas.Series* or *pandas.DataFrame*

## Examples

**NEA list:** The output of this list is a *pandas.Series* which contains the list of all NEAs currently considered in the NEOCC system.

```
>>> from ESANEOCC import neocc
>>> list_data = neocc.query_list(list_name='nea_list')
>>> list_data
0          433 Eros
1          719 Albert
2          887 Alinda
3         1036 Ganymed
4         1221 Amor
...
25191          2021DY
25192         2021DY1
25193         2021DZ
25194         2021DZ1
25195         6344P-L
Name: 0, Length: 25196, dtype: object
```

Each asteroid can be accessed using its index. This information can be used as input for *query\_object* method.

```
>>> list_data[4]
'1221 Amor'
```

**Other lists:** The output of this list is a *pandas.DataFrame* which contains the information of the requested list.

```
>>> from ESANEOCC import neocc
>>> list_data = neocc.query_list(list_name='close_appr_upcoming')
>>> list_data
      Object Name      Date    ...  Rel. vel in km/s
0          2021DE  2021.156164  ...           26.0
1          2021DM  2021.158904  ...           10.2
2          2011DW  2021.161644  ...           13.6
3          2011EH17  2021.161644  ...           16.8
4          2016DV1  2021.164384  ...           18.6
..          ...      ...    ...           ...
141         2020DF  2022.120548  ...            8.6
142         2018CW2  2022.131507  ...           10.8
143         2020CX1  2022.131507  ...            8.2
144  455176 1999VF22  2022.142466  ...           25.1
```

(continues on next page)

(continued from previous page)

```
145          2017CX1  2022.145205  ...          5.0
[146 rows x 10 columns]
```

The information of the columns can be accessed through (see [pandas](#) for further information about data access):

```
>>> list_data['Object Name']
0          2021DE
1          2021DM
2          2011DW
3          2011EH17
4          2016DV1
...
141         2020DF
142         2018CW2
143         2020CX1
144    455176 1999VF22
145         2017CX1
Name: Object Name, Length: 146, dtype: object
```

And the information of the rows can be accessed using:

```
>>> list_data.iloc[2]
Object Name          2011DW
Date              2021.16
Miss Distance in km    5333057
Miss Distance in au    0.035649
Miss Distance in LD     13.874
Diameter in m           90
*=Yes                  *
H                      22.9
Max Bright             16.4
Rel. vel in km/s       13.6
Name: 2, dtype: object
```

---

**Note:** If the contents request fails the following message will be printed:

*Initial attempt to obtain list failed. Reattempting*

Then a second request will be automatically sent to the NEOCC portal.

---

ESANE OCC.neocc.**query\_object** (*name, tab, \*\*kwargs*)

Get requested object data from ESA NEOCC.

### Parameters

- **name** (*str*) – Name of the requested object

- **tab** (*str*) – Name of the request tab. Valid names are: summary, orbit\_properties, physical\_properties, observations, ephemerides, close\_approaches and impacts.
- **\*\*kwargs** (*str*) – Tabs orbit\_properties and ephemerides tabs required additional arguments to work:
  - *orbit\_properties*: the required additional arguments are:
    - \* *orbit\_element* : str (keplerian or equinoctial)
    - \* *orbit\_epoch* : str (present or middle)
  - *ephemerides*: the required additional arguments are:
    - \* *observatory* : str (observatory code, e.g. 500, J04, etc.)
    - \* *start* : str (start date in YYYY-MM-DD HH:MM)
    - \* *stop* : str (end date in YYYY-MM-DD HH:MM)
    - \* *step* : str (time step, e.g. 2, 15, etc.)
    - \* *step\_unit* : str (e.g. days, minutes, etc.)

**Returns neocc\_obj** – Object data which contains different attributes depending on the tab selected.

**Return type** object

## Examples

**Impacts, Physical Properties and Observations:** This example tries to summarize how to access the data of this tabs and how to use it. Note that this classes only require as inputs the name of the object and the requested tab.

The information can be obtained introducing directly the name of the object, but it can be also added from the output of a *query\_list* search:

```
>>> from ESANEOCC import neocc
>>> ast_impacts = neocc.query_object(name='99942 Apophis', tab='impacts'
→')
```

or

```
>>> nea_list = neocc.query_list(list_name='nea_list')
>>> nea_list[403]
'99942 Apophis'
>>> ast_impacts = neocc.query_object(name=nea_list[403], tab='impacts')
```

or



```
>>> risk_list = neocc.query_liss(list_name='risk_list')
>>> risk_list[8]
'99942 Apophis'
>>> ast_impacts = neocc.query_object(name=risk_list[8], tab='impacts')
```

The output provides an object with the different attributes:

```
>>> ast_impacts.
ast.additional_note      ast.impacts
ast.arc_end              ast.info
ast.arc_start            ast.observation_accepted
ast.computation          ast.observation_rejected
```

By adding the attribute its information can be accessed:

```
>>> ast_impacts.impacts
      date      MJD  sigma  ...  Exp. Energy in MT  PS
↪TS
0  2056-04-13.094  72101.094  2.221  ...      0.000129 -4.55
↪0
1  2065-04-13.131  75388.131  2.430  ...      0.000044 -5.10
↪0
2  2068-04-12.634  76483.634  2.723  ...      0.000830 -3.86
↪0
3  2074-04-13.359  78675.359  2.396  ...      0.000022 -5.48
↪0
4  2075-04-13.212  79040.212  1.356  ...      0.000244 -4.44
↪0
5  2077-04-13.112  79771.112  2.714  ...      0.000020 -5.54
↪0
6  2098-10-16.481  87627.481  2.398  ...      0.000058 -5.21
↪0
7  2103-04-14.311  89267.311  2.706  ...      0.000041 -5.38
↪0
[8 rows x 11 columns]
```

Another example is shown to obtain the physical properties:

```
>>> from ESANEOCC import neocc
>>> properties = neocc.query_object(name='433', tab='physical_
↪properties')
```

Again, the output provides an object with different attributes:

```
>>> properties.
properties.physical_properties  properties.sources
>>> properties.physical_properties
```

(continues on next page)

(continued from previous page)

	Property	Values	Unit	Source
0	Rotation Period	5.27	h	[4]
1	Quality	4	-	[4]
2	Amplitude	0.04-1.49	mag	[4]
3	Rotation Direction	PRO	-	[1]
4	Spinvector L	16	deg	[1]
5	Spinvector B	9	deg	[1]
6	Taxonomy	Sq	-	[2]
7	Taxonomy (all)	S	-	[3]
8	Absolute Magnitude (H)	10.31	mag	[5]
9	Slope Parameter (G)	0.46**	mag	[6]
10	Albedo	0.24	-	[9]
11	Diameter	23300	m	[10]
12	Color Index Information	0.39	R-I	[11]
13	Sightings	Visual S	-	[13]

**Note:** Some physical properties (e.g. *Absolute Magnitude (H)*, *Slope Parameter (G)*, etc) may have several values which come from different sources. Currently, the library will only show one value as it is done in the NEOCC portal.

**Note:** For the case of tab Observations there are objects which contain Roving observer and satellite observations. In the original requested data the information of these observations produces two lines of data, where the second line does not fit the structure of the data frame (<https://www.minorplanetcenter.org/iau/info/OpticalObs.html>). In order to solve this problem those second lines have been extracted in another attribute (e.g. `sat_observations` or `roving_observations`) to make the data more readable.

Since this information can be requested in pairs, i.e. it is needed to access both lines of data, this can be made using the date of the observations which will be the same for both attributes:

```
>>> ast_observations = neocc.query_object(name='99942',
tab='observations')
>>> sat_obs = ast_observations.sat_observations
>>> sat_obs
   Design.  K  T  N  YYYY  MM  DD.ddddddd  ...  Obs  Code
0    99942  S  s   2020  12   18.97667  ...      C51
1    99942  S  s   2020  12   19.10732  ...      C51
...      ...
10   99942  S  s   2021   1   16.92315  ...      C53
11   99942  S  s   2021   1   19.36233  ...      C53
12   99942  S  s   2021   1   19.36927  ...      C53
>>> opt_obs = ast_ast_observations.optical_observations
```

(continues on next page)

(continued from previous page)

```
>>> opt_obs.loc[opt_obs['DD.dddddd'] == sat_obs['DD.dddddd'][0]]
      Design.  K  T  N  YYYY  MM  ...  Obs Code  Chi  A  M
4582    99942   S  S   2020  12  ...      C51  1.13  1  1
[1 rows x 33 columns]
```

**Close Approaches:** This example corresponds to the class close approaches. As for the previous example, the information can be obtained by directly introducing the name of the object or from a previous *query\_list* search.

In this particular case, there are no attributes and the data obtained is a DataFrame which contains the information for close approaches:

```
>>> close_appr = neocc.query_object(name='99942', tab='close_approaches
↳ ')
>>> close_appr
      BODY      CALENDAR-TIME  ...      WIDTH  PROBABILITY
0   EARTH  1957/04/01.13908  ...  1.318000e-08      1.000
1   EARTH  1964/10/24.90646  ...  1.119000e-08      1.000
2   EARTH  1965/02/11.51118  ...  4.004000e-09      1.000
...      ...                ...      ...      ...
16  EARTH  2080/05/09.23878  ...  1.206000e-06      0.821
17  EARTH  2087/04/07.54747  ...  1.254000e-08      0.327
[18 rows x 10 columns]
```

**Orbit Properties:** In order to access the orbit properties information, it is necessary to provide two additional inputs to *query\_object* method: **orbit\_elements** and **orbit\_epoch**.

It is mandatory to write these two parameters as: *orbit\_epoch=* to make the library works.

```
>>> ast_orbit_prop = neocc.query_object(name='99942',
tab='orbit_properties', orbit_elements='keplerian', orbit_epoch='present
↳ ')
>>> ast_orbit_prop.
ast_orbit_prop.anode      ast_orbit_prop.moid
ast_orbit_prop.aphelion   ast_orbit_prop.ngr
ast_orbit_prop.cor        ast_orbit_prop.perihelion
ast_orbit_prop.cov        ast_orbit_prop.period
ast_orbit_prop.dnode      ast_orbit_prop.pha
ast_orbit_prop.epoch      ast_orbit_prop.rectype
ast_orbit_prop.form       ast_orbit_prop.refsys
ast_orbit_prop.kep        ast_orbit_prop.rms
ast_orbit_prop.lsp        ast_orbit_prop.u_par
ast_orbit_prop.mag        ast_orbit_prop.vinfty
```

**Ephemerides:** In order to access ephemerides information, it is necessary to provide five additional inputs to *query\_object* method: **observatory**, **start**, **stop**, **step** and **step\_unit\***.

It is mandatory to write these five parameters as: *observatory=* to make the library works.

```
>>> ast_ephemerides = neocc.query_object(name='99942',
tab='ephemerides', observatory='500', start='2019-05-08 01:30',
stop='2019-05-23 01:30', step='1', step_unit='days')
>>> ast_ephemerides.
ast_ephemerides.ephemerides  ast_ephemerides.tinit
ast_ephemerides.observatory  ast_ephemerides.tstep
ast_ephemerides.tfinal
```

## 5. ESANEOCC.LISTS

This module contains all the methods required to request the list data, obtain it from the ESA NEOCC portal and parse it to show it properly.

- Project: NEOCC portal Python interface
- Property: European Space Agency (ESA)
- Developed by: Elecnor Deimos
- Author: C. Álvaro Arroyo Parejo
- Issue: 1.0
- Date: 26-02-2021
- Purpose: Module which request and parse list data from ESA NEOCC
- Module: lists.py
- History:

Version	Date	Change History
1.0	26-02-2021	Initial version

©Copyright [European Space Agency][2021] All rights reserved

`ESANEOCC.lists.get_dec_year(date)`

Get decimal year from a date.

**Parameters** `date` (*datetime*) – Date in YYYY/MM/DD.dddd format.

**Returns** `decimal_year` – Date in decimal year format YYYY.yyyyyy.

**Return type** float64

`ESANEOCC.lists.get_list_data(url, list_name)`

Get requested parsed list from url.

**Parameters**

- **list\_name** (*str*) – Name of the requested list.
- **url** (*str*) – URL of the requested list.

**Returns** **neocc\_lst** – Data frame which contains the data of the requested list.

**Return type** *pandas.Series* or *pandas.DataFrame*

`ESANEOCC.lists.get_list_url(list_name)`

Get url from requested list name.

**Parameters** **list\_name** (*str*) – Name of the requested list. Valid names are: *nea\_list*, *risk\_list*, *risk\_list\_special*, *close\_appr\_upcoming*, *close\_appr\_recent*, *priority\_list*, *priority\_list\_faint*.

**Returns** **url** – Final URL string.

**Return type** *str*

**Raises** **KeyError** – If the requested **list\_name** is not in the dictionary

`ESANEOCC.lists.parse_clo(data_byte_d)`

Parse and arrange close approaches lists.

**Parameters** **data\_byte\_d** (*object*) – Decoded StringIO object.

**Returns** **neocc\_lst** – Data frame with close approaches list data parsed.

**Return type** *pandas.Series* or *pandas.DataFrame*

`ESANEOCC.lists.parse_list(list_name, data_byte_d)`

Switch function to select parse method.

**Parameters**

- **list\_name** (*str*) – Name of the requested list.
- **data\_byte\_d** (*object*) – Decoded StringIO object.

**Returns** **neocc\_lst** – Data frame with data from the list parsed.

**Return type** *pandas.Series* or *pandas.DataFrame*

`ESANEOCC.lists.parse_nea(data_byte_d)`

Parse and arrange all NEA list.

**Parameters** **data\_byte\_d** (*object*) – Decoded StringIO object.

**Returns** **neocc\_lst** – Data frame with NEA list data parsed.

**Return type** *pandas.Series* or *pandas.DataFrame*

`ESANEOCC.lists.parse_pri(data_byte_d)`

Parse and arrange priority lists.

**Parameters** **data\_byte\_d** (*object*) – Decoded StringIO object.

**Returns** **neocc\_lst** – Data frame with priority list data parsed.

**Return type** *pandas.Series* or *pandas.DataFrame*

`ESANEOCC.lists.parse_risk(data_byte_d)`

Parse and arrange risk lists.

**Parameters** `data_byte_d` (*object*) – Decoded StringIO object.

**Returns** `neocc_lst` – Data frame with risk list data parsed.

**Return type** *pandas.Series* or *pandas.DataFrame*

## 6. ESANEOCC.TABS

This module contains all the methods required to request the data from a particular object, obtain it from the ESA NEOCC portal and parse it to show it properly. The information of the object is shown in the ESA NEOCC in different tabs that correspond to the different classes within this module.

- Project: NEOCC portal Python interface
- Property: European Space Agency (ESA)
- Developed by: Elecnor Deimos
- Author: C. Álvaro Arroyo Parejo
- Issue: 1.0
- Date: 26-02-2021
- Purpose: Module which request and parse list data from ESA NEOCC
- Module: tabs.py
- History:

Version	Date	Change History
1.0	26-02-2021	Initial version

©Copyright [European Space Agency][2021] All rights reserved

**class** `ESANEOCC.tabs.AsteroidObservations`

This class contains information of asteroid observations.

**version**

File version.

**Type** `int`

**errmod**

Error model for the data.

**Type** `str`

**rmsast**

Root Mean Square for asteroid observations.

**Type** float

**rmsmag**

Root Mean Square for magnitude.

**Type** float

**optical\_observations**

Data frame which contains optical observations (without roving observer and satellite observation).

**Type** pandas.DataFrame

**radar\_observations**

Data structure which contains radar observations.

**Type** pandas.DataFrame

**roving\_observations**

Data structure which contains roving observer observations.

**Type** pandas.DataFrame

**sat\_observations**

Data structure which contains satellite observations.

**Type** pandas.DataFrame

**class** ESANEOCC.tabs.**CloseApproaches**

This class contains information of object close approaches.

**static** **clo\_appr\_parser** (*data\_obj*, *name*)

Parse and arrange the close approaches data.

**Parameters** **data\_obj** (*object*) – Object in byte format.

**Returns** **df\_close\_appr** – Data frame with the close approaches information.

**Return type** pandas.DataFrame

**Raises** **ValueError** – If file is empty.

**class** ESANEOCC.tabs.**Ephemerides**

This class contains information of object ephemerides.

**observatory**

Name of the observatory from which ephemerides are obtained.

**Type** str

**tinit**

Start date from which ephemerides are obtained.

**Type** str

**tfinal**

End date from which ephemerides are obtained.

**Type** str

**tstep**

Time step and time unit used during ephemerides calculation.

**Type** str

**ephemerides**

Data frame which contains the information of the object ephemerides

**Type** pandas.DataFrame

**class** ESANEOCC.tabs.**EquinoctialOrbitProperties**

This class contains information of equinoctial asteroid orbit properties. This class inherits the attributes from OrbitProperties.

**equinoctial**

Data frame which contains the equinoctial elements information.

**Type** pandas.DataFrame

**rms**

Root Mean Square for equinoctial elements.

**Type** DataFrame

**eig**

Eigenvalues for the covariance matrix.

**Type** pandas.DataFrame

**wea**

Eigenvector corresponding to the largest eigenvalue.

**Type** pandas.DataFrame

**cov**

Covariance matrix for equinoctial elements.

**Type** pandas.DataFrame

**nor**

Normalization matrix for equinoctial elements.

**Type** pandas.DataFrame

**class** ESANEOCC.tabs.**Impacts**

This class contains information of object possible impacts.

**impacts**

Data frame where are listed all the possible impactors.



**Type** pandas.DataFrame

**arc\_start**

Starting date for optical observations.

**Type** str

**arc\_end**

End date for optical observations.

**Type** str

**observations\_accepted**

Total number of observations subtracting rejected observations.

**Type** int

**observations\_rejected**

Number of observations rejected.

**Type** int

**computation**

Date of computation (in format YYYYMMDD MJD TimeSys)

**Type** str

**info**

Information from the footer of the requested file.

**Type** str

**additional\_note**

Additional information. Some objects (e.g. 99942 Apophis) have an additional note after the main footer.

**Type** str

**class** ESANEOCC.tabs.KeplerianOrbitProperties

This class contains information of keplerian asteroid orbit properties. This class inherits the attributes from OrbitProperties.

**kep**

Data frame which contains the keplerian elements information.

**Type** pandas.DataFrame

**perihelion**

Orbit perihelion in au.

**Type** int

**aphelion**

Orbit aphelion in au.

**Type** int

**anode**  
Ascending node-Earth separation in au.

**Type** int

**dnode**  
Descending node-Earth separation in au.

**Type** int

**moid**  
Minimum Orbit Intersection distance in au.

**Type** int

**period**  
Orbit period in days.

**Type** int

**pha**  
Potential hazardous asteroid classification.

**Type** string

**vinfty**  
Infinite velocity.

**Type** int

**u\_par**  
Uncertainty parameter as defined by MPC.

**Type** int

**rms**  
Root mean square for keplerian elements

**Type** pandas.DataFrame

**cov**  
Covariance matrix for keplerian elements

**Type** pandas.DataFrame

**cor**  
Correlation matrix for keplerian elements

**Type** pandas.DataFrame

**class** `ESANEOCC.tabs.OrbitProperties`  
This class contains information of asteroid orbit properties.

**form**  
File format.

**Type** str

**rectype**  
Record type.

**Type** str

**refsys**  
Default reference system.

**Type** str

**epoch**  
Epoch in MJD format.

**Type** str

**mag**  
Data frame which contains magnitude values.

**Type** pandas.DataFrame

**lsp**  
Data structure with information about non-gravitational parameters (model, number of parameters, dimension, etc.).

**Type** pandas.DataFrame

**ngr**  
Data frame which contains non-gravitational parameters.

**Type** pandas.DataFrame

**class** ESANEOCC.tabs.**PhysicalProperties**  
This class contains information of asteroid physical properties

**physical\_properties**  
Data structure containing property, value, units and source from the complete set of physical properties

**Type** DataFrame

**sources**  
Data structure containing source number, name and additional information

**Type** DataFrame

**Raises ValueError** – If the name of the object is not found

**class** ESANEOCC.tabs.**Summary**  
This class contains the information from the Summary tab.

**physical\_properties**  
Data frame which contains the information of the object physical properties, their value and their units.

**Type** pandas.DataFrame

**discovery\_date**

Provides the object discovery date

**Type** str

**observatory**

Provides the name of the observatory where object was discovered

**Type** str

`ESANEOCC.tabs.get_indexes(dfobj, value)`

Get a list with location index of a value or string in the DataFrame requested.

**Parameters**

- **dfobj** (*pandas.DataFrame*) – Data frame where the value will be searched.
- **value** (*str, int, float*) – String, integer or float to be searched.

**Returns listofpos** – List which contains the location of the value in the Data frame. The first elements will correspond to the index and the second element to the columns

**Return type** list

`ESANEOCC.tabs.get_object_data(url)`

Get object in byte format from requested url.

**Parameters url** (*str*) – URL of the requested data.

**Returns data\_obj** – Object in byte format.

**Return type** object

`ESANEOCC.tabs.get_object_url(name, tab, **kwargs)`

Get url from requested object and tab name.

**Parameters**

- **name** (*str*) – Name of the requested object.
- **tab** (*str*) – Name of the request tab. Valid names are: *summary, orbit\_properties, physical\_properties, observations, ephemerides, close\_approaches and impacts*.
- **\*\*kwargs** (*str*) – orbit\_properties and ephemerides tabs required additional arguments to work:
  - *orbit\_properties*: the required additional arguments are:
    - \* *orbit\_element* : str (keplerian or equinoctial)
    - \* *orbit\_epoch* : str (present or middle)
  - *ephemerides*: the required additional arguments are:

- \* *observatory* : str (observatory code, e.g. 500, J04, etc.)
- \* *start* : str (start date in YYYY-MM-DD HH:MM)
- \* *stop* : str (end date in YYYY-MM-DD HH:MM)
- \* *step* : str (time step, e.g. 2, 15, etc.)
- \* *step\_unit* : str (e.g. days, minutes, etc.)

**Returns** *url* – Final url from which data is requested.

**Return type** string

**Raises**

- **KeyError** – If the requested tab is not in the dictionary.
- **ValueError** – If the elements requested are not valid.