

Creating a Kubernetes Cluster with Jenkins X and Importing App

This lesson provides the link to gists that you can use to create a Kubernetes cluster with Jenkins X. Moreover, it also gives some steps to follow before we continue with the chapter.

We'll cover the following

- Create a new cluster and install Jenkins X
 - GKE
 - EKS
 - AKS
- Install Jenkins X in an existing serverless cluster
- Before we get started

You know what comes next. We need a cluster with Jenkins X up-and-running unless you kept the one from before.



All the commands from this chapter are available in the [06-env.sh](#) Gist.

Create a new cluster and install Jenkins X

For your convenience, the Gists from the previous chapter are available below as well.

GKE

Create a new serverless **GKE** cluster:

[gke-jx-serverless.sh](#)



EKS

Create a new serverless **EKS** cluster:


[eks-jx-serverless.sh](#)



AKS

Create a new serverless **AKS** cluster:

[aks-jx-serverless.sh](#)



Install Jenkins X in an existing serverless cluster

Use an **existing** serverless cluster: [install-serverless.sh](#)

Before we get started

We'll continue using the *go-demo-6* application. Please enter the local copy of the repository, unless you're already there.

```
cd go-demo-6
```



The commands that follow will reset your master branch with the contents of the **buildpack** branch that contains all the changes from the previous chapter. Please execute them only if you are unsure whether you did all the exercises correctly.

```
git pull
git checkout buildpack-tekton
git merge -s ours master --no-edit
git checkout master
```



```
git merge buildpack-tekton
```

```
git push
```

If you restored the branch, the chances are that there is a reference to my user (**vfarcic**). We'll change that to Google project since that's what is the expected location of container images.



Please execute the commands that follow only if you restored a branch at the beginning of a chapter (like in the snippet above). Please note the comments within the snippet that follows.

```
# If GKE
export REGISTRY_OWNER=$PROJECT

# If EKS or AKS
# Replace `[...]` with your GitHub user
export REGISTRY_OWNER=[...]

cat charts/go-demo-6/Makefile \
| sed -e \
"s@vfarcic@$REGISTRY_OWNER@g" \
| sed -e \
"s@vfarcic@$REGISTRY_OWNER@g" \
| tee charts/go-demo-6/Makefile

cat charts/preview/Makefile \
| sed -e \
"s@vfarcic@$REGISTRY_OWNER@g" \
| sed -e \
"s@vfarcic@$REGISTRY_OWNER@g" \
| tee charts/preview/Makefile

cat skaffold.yaml \
| sed -e \
"s@vfarcic@$REGISTRY_OWNER@g" \
| sed -e \
"s@vfarcic@$REGISTRY_OWNER@g" \
| tee skaffold.yaml
```



If you destroyed the cluster at the end of the previous chapter, we'll need to import the *go-demo-6* application again. Please execute the commands that follow only if you created a new cluster specifically for the exercises from this chapter.

```
jx import --batch-mode
```



```
jx get activity \  
  --filter go-demo-6 \  
  --watch
```

Please wait until the activity of the application shows that all the steps were executed successfully, and stop the watcher by pressing *ctrl+c*.

Now we can explore GitOps through Jenkins X environments.