

Introduction to Generics

In this lesson, an explanation is provided to get started with Generics Methods (functions) in Java.

We'll cover the following

- 🔍 Definition
- Generic methods
 - Syntax
 - Generic methods with multiple type parameters

🔍 Definition

"Generics allow the reusability of code, where one single method can be used for different **data-types** of variables or objects."

The idea is to allow different types like **Integer**, **String**, ... etc and user-defined types to be a parameter to methods, classes, and interfaces.

For example, classes like **HashSet**, **ArrayList**, **HashMap**, etc use generics very well. We can use them for any type.

The following example illustrates three **non-generic** (type-sensitive) functions for finding maximum out of 3 inputs:

```
class Main {
    public static void main(String[] args) {
        System.out.printf("Max of %d, %d and %d is %d\n\n", 3, 4, 5,
            MaximumTest.maximum(3, 4, 5));
        System.out.printf("Max of %.1f,%.1f and %.1f is %.1f\n\n", 6.6, 8.8, 7.7,
            MaximumTest.maximum(6.6, 8.8, 7.7));
        System.out.printf("Max of %s, %s and %s is %s\n", "pear", "apple", "orange",
            MaximumTest.maximum("pear", "apple", "orange"));
    }
}

class MaximumTest {
    // determines the largest of three Comparable objects
    public static int maximum(int x, int y, int z) {
        int max = x; // assume x is initially the largest
```

```

    if (y > max) {
        max = y; // y is the largest so far
    }

    if (z > max) {
        max = z; // z is the largest now
    }
    return max; // returns the largest object
}

public static double maximum(double x, double y, double z) {
    double max = x; // assume x is initially the largest

    if (y > max) {
        max = y; // y is the largest so far
    }

    if (z > max) {
        max = z; // z is the largest now
    }
    return max; // returns the largest object
}

public static String maximum(String x, String y, String z) {
    String max = x; // assume x is initially the largest

    if (y.compareTo(max) > 0) {
        max = y; // y is the largest so far
    }

    if (z.compareTo(max) > 0) {
        max = z; // z is the largest now
    }
    return max; // returns the largest object
}
}

```



Three *methods* that do exactly the same thing, but cannot be defined as a single method because they use *different* data types. (`int`, `double` & `String`)

Generic methods

To use generic methods, we use the following syntax.

Syntax

```
<T> void MyFirstGenericMethod(T element)
```



`T` is our *generic* data type's name, and when the method is to be called, it would be the same as if `T` was a `typedef` for your datatype.

The following example now illustrates how the `multiply` *method* would be written

using a *template*:

```
class Main {
    public static void main(String[] args) {
        System.out.printf("Max of %d, %d and %d is %d\n\n", 3, 4, 5,
            MaximumTest.maximum(3, 4, 5));
        System.out.printf("Max of %.1f,%.1f and %.1f is %.1f\n\n", 6.6, 8.8, 7.7,
            MaximumTest.maximum(6.6, 8.8, 7.7));
        System.out.printf("Max of %s, %s and %s is %s\n", "pear", "apple", "orange",
            MaximumTest.maximum("pear", "apple", "orange"));
    }
}

class MaximumTest {
    // determines the largest of three Comparable objects
    public static < T extends Comparable < T >> T maximum(T x, T y, T z) {
        T max = x; // assume x is initially the largest

        if (y.compareTo(max) > 0) {
            max = y; // y is the largest so far
        }

        if (z.compareTo(max) > 0) {
            max = z; // z is the largest now
        }
        return max; // returns the largest object
    }
}
```

Generic methods with multiple type parameters

In the above code, all of the arguments to `maximum()` must be the same type. Optionally, a template can have more type options, and the syntax is pretty simple. For a template with **three** types, called `T1`, `T2` and `T3`, we have:

```
class Generics {
    public static < T1, T2, T3 > void temp(T1 x, T2 y, T3 z) {
        System.out.println("This is x =" + x);
        System.out.println("This is y =" + y);
        System.out.println("This is z =" + z);
    }
    public static void main(String args[]) {
        temp(1, 2, 3);
    }
}
```

In the next lesson, we'll take a look at templates in some more detail!