

What Now?

This lesson concludes the discussion regarding this chapter and gives instructions to free up the used resources.

We'll cover the following



- How to free up the resources?

There is at least one crucial **Prow**-related subject we haven't explored yet. We need to figure out how to change the Prow plugins we're using and find out how to modify the rules that govern the pull request process. We'll go through those and a few other Prow and ChatOps related subjects later. For now, we know how to use ChatOps capabilities that Jenkins X provides out of the box. That is a notable improvement by itself, so we'll leave the tweaking for one of the next chapters.

How to free up the resources?

Now you need to decide whether to continue using the cluster or to destroy it. If you choose to destroy it or to uninstall Jenkins X, you'll find the instructions at the bottom of the Gist you chose at the beginning of this chapter.

If you destroyed the cluster or you uninstalled Jenkins X, please remove the repositories and the local files we created. You can use the commands that follow for that.



Please replace [...] with your GitHub user before executing the commands that follow.

```
cd ..  
  
GH_USER=[...]  
  
hub delete -y \  
  $GH_USER/environment-jx-rocks-staging  
  
hub delete -y \  
  $GH_USER/environment-jx-rocks-production
```



```
$GH_USER/environment-jx-rocks-production  
  
hub delete -y $GH_USER/jx-prow  
  
rm -rf jx-prow  
  
rm -rf ~/.jx/environments/$GH_USER/environment-jx-rocks-*
```

In the next lesson, we will take a quiz and review some of the material we covered in this chapter.