

# Creating a Kubernetes Cluster with Jenkins X and Importing App

This lesson provides the link to gists that you can use to create a Kubernetes cluster with Jenkins X. Moreover, it also gives some steps to follow before we continue with the chapter.

## We'll cover the following

- Create a new cluster and install Jenkins X
  - GKE
  - EKS
  - AKS
- Install Jenkins X in an existing serverless cluster
- Before we get started

This part is getting boring, but it might be necessary if you destroyed the cluster or uninstalled Jenkins X at the end of the previous chapter. Long story short, create a new Jenkins X cluster unless you kept the one from before.



All the commands from this chapter are available in the [08-pr.sh](#) Gist.

## Create a new cluster and install Jenkins X #

For your convenience, the Gists from the previous chapter are available below as well.

### GKE #

Create a new serverless **GKE** cluster:

[gke-jx-serverless.sh](#)



## EKS #

Create a new serverless **EKS** cluster:

[eks-jx-serverless.sh](#)



## AKS #

Create a new serverless **AKS** cluster:

[aks-jx-serverless.sh](#)



## Install Jenkins X in an existing serverless cluster #

Use an **existing** serverless cluster: [install-serverless.sh](#)

## Before we get started #

We'll continue using the *go-demo-6* application. Please enter the local copy of the repository, unless you're there already.

```
cd go-demo-6
```



The commands that follow will reset your **master** with the contents of the **dev** branch that contains all the changes we did so far. Please execute them only if you are unsure whether you did all the exercises correctly.

```
git pull
git checkout dev-tekton
git merge -s ours master --no-edit
```




```
git merge --ours master --no-edit

git merge dev-tekton

git push
```


If you have restored a branch at the beginning of a chapter, the chances are that there is a reference to my user ( `vfarcic` ). We'll change that to the Google project since that's what Knative will expect for the location of the container images.

 Please execute the commands that follow only if you are using **GKE** and if you ever restored a branch at the beginning of a chapter (like in the snippet above).

```
cat charts/go-demo-6/Makefile \
| sed -e \
"s@vfarcic@$PROJECT@g" \
| sed -e \
"s@devops-26@$PROJECT@g" \
| tee charts/go-demo-6/Makefile

cat charts/preview/Makefile \
| sed -e \
"s@vfarcic@$PROJECT@g" \
| sed -e \
"s@devops-26@$PROJECT@g" \
| tee charts/preview/Makefile

cat skaffold.yaml \
| sed -e \
"s@vfarcic@$PROJECT@g" \
| sed -e \
"s@devops-26@$PROJECT@g" \
| tee skaffold.yaml
```

 If you destroyed the cluster at the end of the previous chapter, you'll need to import the *go-demo-6* application again. Please execute the commands that follow only if you created a new cluster specifically for the exercises from this chapter.

```
jx import --batch-mode

jx get activities \
--filter go-demo-6 \
--watch
```

Please wait until the activity of the application shows that all the steps were executed successfully, and stop the watcher by pressing *ctrl+c*.

---

Now let's create some pull requests in the next lesson.