

Golf Launch Monitor Technology Review

**Measurement Principles, Patent Landscape, and Club/Ball
Parameter Estimation**

A comprehensive technical reference

August 19, 2026

Abstract

This review surveys the measurement technology behind commercial golf launch monitors — Doppler-radar systems (TrackMan, FlightScope, Garmin R10, Full Swing KIT), photometric camera systems (Foresight GCQuad/GC3, Uneekor, SkyTrak, ProTee VX, Garmin R50), and hybrid radar+camera architectures that combine these sensing families — with emphasis on *how each system measures or infers club-delivery parameters* (club speed, club path, attack angle, face angle, dynamic loft, impact location) *and ball-launch parameters* (ball speed, launch angles, spin rate, spin axis). Primary sources include selected patent disclosures (TrackMan/Tuxen radar spin and spin-axis methods, FlightScope/EDH radar-spin methods, Wintriss/Foresight photometric methods, and Acushnet optical launch-monitor designs), regulatory (FCC) filings, manufacturer technical documentation, and the peer-reviewed validation literature. The review develops the underlying physics — the D-plane impact model, oblique-impact spin generation, gear effect, and golf-ball aerodynamics — as the common mathematical framework for interpreting launch-monitor outputs, and closes with a technical map of patent disclosures and design guidance for implementers building or evaluating a system. The central organizing principle is the provenance of each reported quantity: the observations, calibration and model assumptions that support it. Combining radar and optical observations can constrain different parts of the inference problem, but does not automatically make every output directly measured or independently validated. Early optical disclosures illustrate surface-image rotation and club-marker geometry; their age does not establish implementation accuracy or design-specific rights clearance.

This document is written to be vendor- and project-neutral. Where a specific product is named it is as evidence — a published definition, a measured tolerance, a patent claim — not as an endorsement or a design target.

Contents

1	Introduction	5
1.1	Purpose and Scope	5
1.2	The Two Sensing Families	5
1.3	Reading Guide	6
2	Parameter Definitions and Conventions	7
2.1	Club-Delivery Parameters	7
2.1.1	Reference Point and Rigid-Body Velocity	8
2.1.2	Spin Loft and Contact Kinematics	9
2.2	Ball-Launch Parameters	9
2.2.1	Spin Components Need a Frame	10
2.3	The Directness Hierarchy	10
3	Impact Physics: From Club Delivery to Ball Launch	12
3.1	The D-Plane	12
3.1.1	Face/Path Weighting of Launch Direction	13
3.1.2	Spin Loft and Approximate Launch Maps	14
3.1.3	Spin-Axis Tilt	14
3.2	Ball Speed and Smash Factor	15
3.3	Spin Generation	15
3.4	Gear Effect and Impact Location	16
3.4.1	Why a Coupled Contact Solve Matters	16
3.5	Vertical Plane and the Low-Point Geometry	17
3.6	Connecting Delivery, Impact and Measurement	17
4	Doppler Radar Systems	18
4.1	Continuous-Wave Doppler Fundamentals	18
4.2	From Velocity Sensor to 3D Tracker: Phase Interferometry	19
4.3	CW + FMCW Hybrids	19
4.4	Ball Measurement	20
4.4.1	Speed and Launch Angles	20
4.4.2	Spin Rate: Harmonic Signatures and Their Ambiguities	20
4.4.3	Spin Axis: Conditional Trajectory Inversion	21
4.4.4	A Dimensional and Algebraic Check on a Delay Disclosure	22
4.4.5	Flight Observation, Extrapolation, and Ball Modes	22
4.5	Club Measurement	22
4.5.1	What the Radar Tracks on the Head	22
4.5.2	Face Angle and Dynamic Loft	23
4.5.3	Known Limitations	23
4.6	Optically Enhanced Radar: OERT and Fusion Tracking	24

5	Photometric (Camera) Systems	25
5.1	Imaging Architectures	25
5.2	Ball Measurement	25
5.2.1	Photogrammetric Position and Velocity	25
5.2.2	Spin: Dimple-Pattern Registration	26
5.3	Club Measurement	26
5.3.1	Fiducial Markers: The Foresight Approach	26
5.3.2	Sticker-Free Overhead Tracking	26
5.3.3	Calibration	27
5.4	The Indoor Argument, and What Cameras Cannot Do	27
5.5	DIY and Open-Source Photometric Systems	27
6	Commercial System Survey	28
6.1	Radar-First Systems	29
6.2	Camera-First Systems	29
6.3	Open-Source Systems	29
7	Patent Landscape	30
7.1	TrackMan A/S (Interactive Sports Games A/S) — Fredrik Tuxen	30
7.2	Foresight Sports, WAWGD and Wintriss Disclosures	31
7.3	FlightScope / EDH — Henri Johnson	32
7.4	Acushnet (Titleist) — Optical Measurement Architectures	32
7.5	United States Golf Association — Aerodynamic Experiments	33
7.6	Korean Ecosystem: Creatz/Uneekor and Golfzon	33
7.7	Timing, Association and Environmental Inference	34
7.8	Technical Research Map and Rights Boundaries	34
8	Ball Flight Models and Trajectory Estimation	36
8.1	Equations of Motion	36
8.2	Aerodynamic Coefficient Data	36
8.3	Trajectory Estimation and Filtering	37
8.4	Indoor Extrapolation and Its Errors	37
9	Accuracy: The Independent Evidence	38
9.1	Peer-Reviewed Validation	38
9.2	Robot and Industry Testing	38
9.3	What Drives Inter-Device Disagreement	38
10	Design Guidance for Implementers	40
10.1	Ball Data	40
10.2	Club Data	41
10.3	Capability Tiers	41
10.4	Reporting Honesty as a Design Feature	42
11	Governed Analytics and Validation Program	43
11.1	Qualified Corpus Snapshot	43
11.2	Release A: Qualified Analytics Platform	44
11.3	Qualified Model-Comparison Results	44
11.4	Release B: Paired-Device Scientific Validation	46

11.4.1	Pairing and Reference Uncertainty	46
11.4.2	Agreement, Repeatability, and Repeated Shots	47
11.4.3	Sample Planning and the Completion Gate	47
11.5	Reproducibility and Claim Discipline	48
A	Annotated Reference Library	49
A.1	Patents (Google Patents / USPTO)	49
A.2	Regulatory Records and Teardown Reports	51
A.3	Manufacturer Documentation and Product Reporting	51
A.3.1	The TrackMan Newsletter Archive	52
A.4	Research Papers, Standards, and Technical Notes	54
A.5	Engineering References (Tutelman et al.)	55
A.6	DIY / Open-Source	55
A.7	Hardware Datasheets, Protocols, and Standards	55
A.8	Comparative Testing and Market Analysis	56
B	Detailed Implementation Guidance	58
B.1	Radar Signal Chain (OPS243-A)	58
B.1.1	Doppler Scaling and Resolution Budget	58
B.1.2	Spin-Rate Comb Estimation	58
B.1.3	Club-Speed Extraction	59
B.2	Angle Measurement (K-LD7) and the EKF	59
B.2.1	Interferometric Angles	59
B.2.2	Recommended Filter	59
B.2.3	Alignment Calibration Procedure	59
B.3	Derived Club Data, With Priors	59
B.4	Optical Module (Phase 2) Design Parameters	60
B.5	Flight Model and Validation Protocol	60
C	Sensor Hardware and Integration Reference	62
C.1	OmniPreSense OPS243-A (24 GHz CW Doppler)	62
C.1.1	Hardware and Configuration Boundaries	62
C.1.2	Sampling, Grid Spacing and Identifiability	62
C.1.3	Rolling Buffer and Trigger Timing	63
C.1.4	Interpreting the Vendor Golf Example	63
C.2	RFbeam K-LD7 (24 GHz FSK, Dual-RX Angle)	64
C.3	TI IWR6843 (60–64 GHz FMCW MIMO)	64
C.4	Raspberry Pi Global Shutter Camera (Optical Module)	65
C.5	Simulator Integration: GSPro Open Connect	65
C.6	Equipment Rules and Model Parameters	66
C.7	Detection Theory: CFAR Selection	66
D	Patent Portfolio Compendium	68
D.1	TrackMan A/S (Incl. Interactive Sports Games A/S)	68
D.2	Topgolf Sweden AB (Toptracer / Protracer)	71
D.3	FlightScope / EDH (Henri Johnson)	72
D.4	Full Swing Golf	72
D.5	Garmin	73

D.6	Rapsodo Pte. Ltd.	73
D.7	Camera Vendors: Foresight/Wintriss, Creatz/Uneekor, Golfzon	74
D.8	Acushnet (Titleist) — Selected Optical Disclosures	75
D.9	Others and Foundational Radar Art	76
E	Radar Clubhead Kinematics: Motion and Observability	77
E.1	Context: Definitions Are Not an Estimator Specification	77
E.2	Rigid Motion With Declared Frames and Reference Points	77
E.2.1	Body and Spatial Twists for Pose Integration	78
E.3	The Measurement Model and Its Exact Ambiguity	78
E.3.1	What Least Squares and Covariance Actually Provide	79
E.4	What Representative Hardware Adds	80
E.4.1	OPS243-A: Radial-Speed Information	80
E.4.2	K-LD7: Geometry and Operating Envelope	80
E.4.3	IWR6843: A Coupled Waveform Budget	80
E.5	An Estimation Recipe With Explicit Acceptance Conditions	81
E.6	Validation That Can Falsify the Proposed Estimator	83

Chapter 1

Introduction

1.1 Purpose and Scope

A golf launch monitor answers two questions for every shot: *what did the club do through impact* (delivery), and *what did the ball do after impact* (launch and flight). Commercial systems answer these questions with strikingly different sensor architectures — continuous-wave Doppler radar, multi-camera photogrammetry, and, increasingly, fusions of the two — yet they all implement the same underlying physics: an oblique-impact collision model connecting club delivery to ball launch, and an aerodynamic model connecting ball launch to flight.

This review is a technical reference on how launch monitors work. It is written for engineers building or evaluating such a system, for researchers using one as an instrument, and for anyone who needs to know what a reported number actually represents. Its goals are:

1. catalogue *how each major commercial system works*, at the level of radar physics, imaging geometry, and signal processing;
2. establish, parameter by parameter, *what is measured directly, what is inferred through a model, and what is essentially estimated* — especially for club-delivery data such as face angle and club path;
3. survey the *patent landscape* as a source of disclosed sensor architectures, signal-processing methods and claim limitations, while distinguishing those disclosures from verified commercial implementations and design-specific rights determinations;
4. collect the *physics and algorithms* (D-plane, impact mechanics, gear effect, aerodynamic coefficients, spectral spin estimation, stereo triangulation, Kalman filtering) that any implementation needs; and
5. translate all of the above into *concrete design guidance*, organised by sensing architecture rather than by product.

Key point

A note on neutrality. Products are named throughout, and often criticised. That is because published vendor definitions, patent claims and measured tolerances are the primary evidence available in this field — the peer-reviewed literature is thin, as Chapter 9 documents. Naming a system is a citation, not a recommendation, and no architecture in this review is presented as the one to build.

1.2 The Two Sensing Families

Doppler radar systems (TrackMan, FlightScope, Garmin Approach R10, Full Swing KIT) illuminate the hitting area and downrange volume with a microwave carrier and extract target radial

velocity from the Doppler shift. Multiple receive antennas turn a velocity sensor into a 3D tracker via phase interferometry (Chapter 4). Radar excels outdoors: it tracks the entire flight, so carry and curvature are *observed*, not modeled. Its weaknesses are at the club face — radar cannot see face orientation directly — and indoors, where a screen truncates the observable flight.

Photometric (camera) systems (Foresight GC-series, Uneekor, SkyTrak, ProTee VX, Garmin R50) capture a burst of high-speed, IR-strobed stereo images over the first ~ 30 cm of ball flight and reconstruct position and orientation photogrammetrically (Chapter 5). They measure launch conditions — including 3D spin from dimple-pattern rotation — essentially perfectly for simulator purposes, then *model* the flight. Their weakness is the mirror image of radar’s: everything downrange of the capture volume is simulated, and club data requires either fiducial stickers on the face or an overhead viewing geometry.

The market’s convergent evolution is the single most instructive fact for a new design: *every* high-end vendor has concluded that neither modality suffices alone. TrackMan added cameras to its radar (OERT, Section 4.6); FlightScope added Fusion Tracking cameras; SkyTrak added radar to its camera; Rapsodo pairs radar with impact cameras; Full Swing feeds a camera into its radar ML pipeline. Chapter 6 tabulates the landscape.

1.3 Reading Guide

Chapter 2 fixes terminology and coordinate conventions (TrackMan’s definitions, the de facto industry standard). Chapter 3 develops the impact physics connecting club delivery to ball launch — the D-plane model, spin generation, and gear effect — which every monitor uses either forward (simulation) or inverse (parameter estimation). Chapters 4 and 5 treat the two sensing families in depth. Chapter 6 surveys the commercial devices. Chapter 7 compares disclosed measurement mechanisms and their evidentiary limits. Chapter 8 covers ball-flight aerodynamics and trajectory estimation. Chapter 9 reviews the independent validation literature. Chapter 10 distills the review into design guidance.

Key point

Throughout, we use a right-handed coordinate system for a right-handed golfer: x down the target line, y up, z to the golfer’s right. Angles are positive right/up. All club-delivery values are referenced to the moment of *maximum ball compression*; all ball-launch values to the moment of *separation from the face*.

Chapter 2

Parameter Definitions and Conventions

A launch-monitor number describes a chosen quantity, at a chosen point and time, through a particular estimation procedure. A disagreement can therefore reflect different definitions as well as measurement error. This chapter uses TrackMan’s published conventions where stated, without treating them as a universal standard or an independent accuracy validation [82, 77, 76]. The right-handed world frame used here and in Chapter 3 has x forward along the target line, y upward and z right. Horizontal angles are positive right of target and elevations are positive upward; right and left do not change with the golfer’s handedness. Terms such as open, closed, in-to-out and draw need an additional handedness convention.

2.1 Club-Delivery Parameters

The time assigned to an output need not be the time interval used to estimate it. TrackMan’s 2017 account describes club-motion estimates fitted from pre-impact observations and referenced to maximum compression, excluding collision-induced motion [77]. Its current parameter list explicitly defines club speed just before first contact, while path and attack angle retain the maximum-compression reference [76, 84]. Thus the latter reference does not justify interpreting every displayed club parameter as an instantaneous measurement of the colliding head. Keep the device, software version, output definition and observation window with a comparison dataset.

The delivery definitions in Table 2.1 follow the cited vendor documentation; Foresight’s lie output instead describes face-plane roll [76, 13]. A shaft inclination and a face-roll coordinate cannot be compared by name alone. Likewise, a rate about a shaft axis does not supply the other components of a clubhead’s angular velocity, and a finite-window rate need not equal its value at one instant. No exclusivity claim about which product can report these quantities follows from their definitions.

A fitted swing plane summarizes a selected trajectory segment; it does not imply that the whole swing is planar. TrackMan’s low-point convention locates the arc minimum relative to the GC at maximum compression [74]. An arc minimum ahead of that reference does not establish ball-first contact with the ground: absolute height, the sole and leading-edge geometry, ball position and the ground surface also matter. A translated copy of the same arc can have the same fore-aft low point while intersecting the ground at a different place.

Face angle and dynamic loft refer here to the normal at the contact center. Bulge and roll make that normal differ from the face-center normal on an off-center driver strike (Section 3.4). A measurement of face-center pose is not intrinsically wrong; it answers a different question unless local surface geometry and strike location are supplied. Similarly, face-to-path can help interpret a centered strike under a stated collision model, but its sign alone does not determine curvature in the presence of gear effect or differing flight conditions.

Table 2.1: Club-Delivery Quantities and Their Declared Conventions

Parameter	Quantity	Interpretation
Club speed	Norm of geometric-center (GC) velocity before first contact	Reference-point dependent
Attack angle	Elevation of GC motion at the stated reference event	Positive upward
Club path	Azimuth of GC motion at that event	Positive right of target
Face angle	Azimuth of the local face normal at the contact center	Positive right of target
Face to path	Face angle minus club path	A difference of headings
Dynamic loft	Elevation of the local contact normal	Includes delivered pose and face curvature
Spin loft	Angle between the declared motion direction and face normal	A three-dimensional angle
Swing plane / direction	Inclination / horizontal orientation of a plane fitted to a clubhead trajectory segment	Declare the fitted interval and point
Low point	Location of the swing-arc minimum relative to the impact reference	Does not alone determine turf contact
Impact height / offset	Strike coordinates relative to face center	Declare face axes and signs
Dynamic lie	TrackMan: lower-shaft inclination to horizontal at impact	Not identical to face roll
Closure rate	Foresight: heel-to-toe rotation rate about the shaft	Not the full angular-velocity norm

2.1.1 Reference Point and Rigid-Body Velocity

For two material points on an ideal rigid clubhead at the same instant,

$$\mathbf{v}_P = \mathbf{v}_O + \boldsymbol{\omega} \times \mathbf{r}, \quad \mathbf{r} = \mathbf{p}_P - \mathbf{p}_O. \quad (2.1)$$

All vectors must be expressed in the same frame. Both speed and direction can change with the reference point; geometric center, center of mass and face center are distinct definitions even when two happen to be close. TrackMan’s 2017 vendor illustration reports an approximately 3° driver path difference between center of gravity and face center, with the face-center path farther left [77]. That illustration is neither a universal correction nor evidence that every radar and optical product chooses those respective points.

For a manufactured example in SI units, choose $\mathbf{v}_O = (40, 0, 0)$, $\mathbf{r} = (0.04, 0, 0)$ and $\boldsymbol{\omega} = (0, 50, 0)$. Then $\mathbf{v}_P = (40, 0, -2)$ and its horizontal heading is $\text{atan2}(-2, 40) \simeq -2.86^\circ$. Reversing $\boldsymbol{\omega}$ reverses the heading offset; choosing $\boldsymbol{\omega} = (50, 0, 0)$ gives zero offset despite the same angular-speed norm. An upward change in velocity increases attack angle, but need not make an already upward motion “shallower.” These examples demonstrate geometry, not typical golfer values or measured device discrepancies.

Key point

A rigid-body twist $(\boldsymbol{\omega}, \mathbf{v}_O)$ and known $\mathbf{r}$ permit conversion between reference points (Chapter E). The scalar $\|\boldsymbol{\omega}\|$ alone does not. The velocity difference obeys $\|\Delta \mathbf{v}\| \leq \|\boldsymbol{\omega}\| \|\mathbf{r}\|$, but converting that bound to a heading difference also requires the original velocity and a nonvanishing horizontal projection. Two devices can be compared only after reconciling their reference points,

frames and times, with the conversion uncertainty retained.

2.1.2 Spin Loft and Contact Kinematics

Write attack angle as a , club path as p , dynamic loft as ℓ and face angle as f . For nonvertical directions, the unit motion vector is $(\cos a \cos p, \sin a, \cos a \sin p)$ and the unit face normal has the analogous form with (ℓ, f) . Their dot product gives the spin-loft angle $\sigma \in [0, \pi]$:

$$\cos \sigma = \sin a \sin \ell + \cos a \cos \ell \cos(f - p). \quad (2.2)$$

This implements the vendor's three-dimensional angular definition [81]. When $f = p$ and the elevation difference lies in $[-\pi, \pi]$, $\sigma = |\ell - a|$; using a signed difference silently assumes its sign. For $a = -5^\circ$, $\ell = 15^\circ$, changing $f - p$ from zero to 10° increases spin loft from 20° to approximately 22.32° . Direct vector evaluation still works when an azimuth is undefined at a vertical direction, provided both vectors are known.

Reported face-to-path and spin loft are legitimate declared quantities even when face orientation is evaluated at contact and velocity at GC. They are not automatically the local relative contact kinematics required by an impact law. For a club point P contacting a ball point Q , that relative velocity is

$$\mathbf{v}_{\text{rel}} = \mathbf{v}_P - [\mathbf{v}_B + \boldsymbol{\omega}_B \times (\mathbf{p}_Q - \mathbf{p}_B)], \quad (2.3)$$

where B is the ball center. Its normal and tangential components enter a contact model; compliance, friction and impact location then influence the outgoing ball state (Chapter 3). Knowing two headings does not identify all of those quantities.

2.2 Ball-Launch Parameters

Table 2.2: Launch State and Separately Derived Flight Descriptors

Parameter	Meaning and Scope
Ball speed	Norm of center velocity immediately after separation
Launch angle / direction	Elevation / azimuth of that outgoing velocity
Spin rate	Angular-speed magnitude, usually expressed in rpm
Spin axis	Direction of the nonzero spin vector; one tilt angle requires an additional convention
Smash factor	Ball-speed / club-speed ratio, using their respective events and reference points
Carry / carry side	Distance / lateral position at a declared flight endpoint, not an instantaneous launch state
Total	Distance to a resting position, requiring bounce and roll treatment
Apex / landing angle	Maximum flight height / velocity elevation at a declared landing event

TrackMan's carry convention uses the descending crossing of the launch elevation, not necessarily the first contact with actual terrain [75]. Its parameter documentation distinguishes this flight descriptor from initial launch quantities and describes total using a calculated resting position [76]. A launch-only indoor measurement therefore cannot by itself observe carry, landing or roll. Comparisons must state whether flight is tracked, extrapolated or normalized to chosen environmental conditions

(Chapter 8). Smash factor is a speed ratio, not a fraction of kinetic energy transferred: it omits the relevant masses and rotational and deformational energy.

2.2.1 Spin Components Need a Frame

An ideal rigid ball has one instantaneous angular-velocity vector, not independent physical “backspin” and “sidespin” rotations. Use the orthonormal launch frame in Equation (3.6): outgoing direction $\hat{v}_b$, transverse backspin axis $\hat{e}_b$ and transverse up axis $\hat{e}_u$. Express the spin vector $\mathbf{S}$ in rpm, so $\mathbf{S} = 60\boldsymbol{\omega}_b/(2\pi)$ when angular velocity is in radians per second. Define $S_{\text{back}} = \mathbf{S} \cdot \hat{e}_b$, $S_{\text{side}} = -\mathbf{S} \cdot \hat{e}_u$ and $S_{\parallel} = \mathbf{S} \cdot \hat{v}_b$. Then

$$\begin{aligned} S_{\perp} &= \sqrt{S_{\text{back}}^2 + S_{\text{side}}^2}, & \theta &= \text{atan2}(S_{\text{side}}, S_{\text{back}}), \\ S_{\text{side}} &= S_{\perp} \sin \theta, & S_{\text{back}} &= S_{\perp} \cos \theta, \\ S^2 &= S_{\perp}^2 + S_{\parallel}^2, & S &= \|\mathbf{S}\|. \end{aligned} \tag{2.4}$$

Replacing $S_{\perp}$ by total spin S is valid only when the axial component vanishes. For horizontal forward flight and $\mathbf{S} = (1000, -300, 3000)$ rpm in the world frame, $S_{\perp} \simeq 3014.96$ rpm, $S \simeq 3176.48$ rpm and $\theta \simeq 5.71^\circ$. Thus total spin and one tilt angle do not determine the general three-dimensional state. The tilt is undefined if both transverse components vanish, and zero spin has no axis; the chosen launch-frame construction also needs a nonvertical launch. Device-specific sidespin and tilt conventions must be converted explicitly before applying these equations.

In the usual spin-induced lift model, the transverse spin relative to air velocity contributes to lateral and vertical lift; wind can make that velocity differ from ground-relative launch velocity. A fixed lateral-distance-per-degree rule cannot replace the flight calculation: speed, launch direction, spin magnitude, wind and aerodynamic coefficients also matter (Chapter 8). Left/right curvature labels need not be draw/fade labels for both handednesses.

2.3 The Directness Hierarchy

Here, *measured* means estimated from observations that constrain the quantity, with calibration and a stated observation model; it does not mean algorithm-free or error-free. *Derived* denotes a transformation of reported quantities, and *estimated from a physical model* denotes an inference or prediction that additionally depends on collision, flight or ground-interaction assumptions. These are provenance descriptions rather than mutually exclusive product classes. Radar records signals and cameras record images; neither records a calibrated three-dimensional club path as raw data. Table 2.3 therefore lists the evidence needed for an output rather than assigning every device of one architecture an identical capability.

The radar and camera chapters develop these conditional observation relationships (Chapters 4 and 5). An outdoor radar track can support trajectory-based spin inference, while a short indoor track may require different information; neither statement identifies every product’s algorithm. For example, TrackMan now describes iO as using cameras for full three-dimensional spin, including axial spin [91]. That product-specific vendor claim is evidence against a universal “indoor radar means estimated axis” label, not independent proof of its advertised accuracy. Similarly, a marker requirement belongs to the particular club-tracking implementation, not to optical sensing as a physical necessity.

Table 2.3: Output Provenance and Conditions to Check

Output	Possible Provenance	Necessary Qualification
Ball speed / launch	Measured through calibrated radar or image observations	Geometry, timing, track association and launch-event fit
Spin rate / axis	Measured from rotation-sensitive observations; or model-inferred from other quantities	Visible features or spin signatures, ambiguity, axial component and flight window
Club motion	Measured by tracking a declared point or fitting rigid motion	Reference point, observation interval and collision exclusion
Face pose / strike	Measured from resolved geometry; or inferred through an impact model	Surface normal, strike location, markers if required, and model identifiability
Face to path / smash	Derived from the constituent outputs	Shared uncertainty and definition compatibility
Carry / landing	Derived from a sufficiently observed trajectory, or predicted from launch	Observed endpoint versus extrapolation and normalization
Total	Estimated with flight, bounce and roll models when rest is not observed	Ground slope, restitution, friction and endpoint definition

Design implication

To use launch-monitor data to investigate the golf swing, retain the measurement chain: club motion and contact geometry constrain impact; impact produces launch; launch and environment determine flight. A face angle inferred from ball launch is not independent corroboration of a proposed relationship between those same outputs. Report definitions, uncertainty and shared inputs alongside the numbers before attributing a difference to technique or to one sensor family.

Chapter 3

Impact Physics: From Club Delivery to Ball Launch

The collision connects a golfer’s delivered club state to the ball’s launch velocity and spin. A forward model predicts those outcomes from specified incident states, geometry and contact properties; an inverse model estimates some of those inputs from observations. Either can be used with optical, radar or combined measurements. The sensing modality alone does not establish a product’s internal algorithm or which reported quantities are independently measured. This chapter separates exact geometry, conditional impact mechanics and empirical approximations so that each can support an appropriate inference.

3.1 The D-Plane

Use a right-handed basis with x forward along the target, y upward and z to the right when viewed toward the target. Horizontal angles remain positive to the right and elevations positive upward, consistent with the right-handed-player signs in Chapter 2. A unit direction with azimuth φ and elevation λ is

$$\mathbf{d}(\varphi, \lambda) = \begin{pmatrix} \cos \lambda \cos \varphi \\ \sin \lambda \\ \cos \lambda \sin \varphi \end{pmatrix}. \quad (3.1)$$

The local face normal is $\hat{\mathbf{n}} = \mathbf{d}(\varphi_f, \lambda_d)$. For collision mechanics, define $\hat{\mathbf{p}}_c = \mathbf{d}(\varphi_c, \alpha_c)$ from the incident velocity of the *contact point*, with $V_c = \|\mathbf{v}_c\| > 0$ and all states evaluated at a declared common instant. A monitor’s reported club path and attack angle may instead describe another reference point or maximum compression. They cannot be substituted silently: for a rigid head, $\mathbf{v}_c = \mathbf{v}_O + \boldsymbol{\omega}_h \times (\mathbf{r}_c - \mathbf{r}_O)$, and the state can change during impact.

In the centered, symmetric oblique-impact idealization associated with the D-plane [36], the nonparallel directions $\hat{\mathbf{n}}$ and $\hat{\mathbf{p}}_c$ span a plane. Assume an initially stationary, nonspinning spherical ball, an isotropic contact response and a face normal treated as fixed during the impulse. If the net impulse lies in that plane, so does the outgoing ball velocity. Its location between face and path, and its closeness to either, additionally depend on the contact law; geometry alone supplies no universal weighting. For tangential impulse directed along the contact-plane component of club motion, the ball’s contact lever arm is $-R\hat{\mathbf{n}}$, giving

$$\Delta\boldsymbol{\omega}_b = I_b^{-1}(-R\hat{\mathbf{n}}) \times \mathbf{J}_t, \quad \Delta\boldsymbol{\omega}_b \parallel \hat{\mathbf{p}}_c \times \hat{\mathbf{n}}. \quad (3.2)$$

Here R is the ball radius and I_b its scalar inertia in this spherical model; the signed tangential impulse sets the orientation along that axis and its magnitude. Parallel directions do not define a unique D-plane or a normalized cross-product axis. Initial spin, off-center head rotation, anisotropy and changing contact geometry require an expanded model.




Figure 3.1: Manufactured Horizontal Launch Example. The declared 0.76/0.24 weighting gives -2.96° from face angle -2° and path -6° . This top-view projection illustrates the arithmetic, not a measured shot or a complete three-dimensional spin prediction.

3.1.1 Face/Path Weighting of Launch Direction

The filtered player data of Wood et al. [101] give the following study-specific horizontal weights in an approximate model of launch direction between face angle and club path:

$$\varphi_{\text{launch}} \approx w_f \varphi_f + (1 - w_f) \varphi_p, \quad w_f \approx \begin{cases} 0.76 \pm 0.08 & \text{driver} \\ 0.69 & \text{7-iron} \\ 0.61 & \text{wedge.} \end{cases} \quad (3.3)$$

Caution

The values above are the *horizontal* weights measured by Wood et al. [101]. Their player data contain 1,575 shots before filtering, with 157 golfers testing driver/7-iron and ten also testing a wedge. Club motion was measured optically at 720 fps and ball launch with a GC2. The horizontal means use strikes within 0.25 in of face centre in each axis and at least 1.5° face-to-path separation: 89 driver, 172 iron and 28 wedge shots remained. A separate 15-shot PING Man robot test returned 0.63 for the 7-iron.

The familiar 0.85/0.15 figure comes from TrackMan's *Ten Fundamentals*, which gives driver rules of thumb in both planes (and 75% for irons). Wood's driver means are 0.83 ± 0.08 vertically and 0.76 ± 0.08 horizontally, reported with 95% confidence intervals. The difference from 0.85 is a reason to retain the model's conditions, not a universal calibration correction. These are estimates from filtered samples, not individual-shot tolerance bands; protocol and measurand differences preclude treating the comparison as a definitive test of every application of the vendor rule.

For any estimator using this weighting model, inverting Eq. (3.3) to recover face angle amplifies any bias in measured launch direction by $1/w_f$ when path and weight are fixed. At $w_f = 0.76$ the factor is 1.32, versus 1.18 at $w_f = 0.85$: about 12% greater sensitivity, not a factor of two. Path error and uncertainty in the weight contribute separately, so this derivative is not a complete uncertainty budget for inferred face angle.

Henrikson and colleagues [29] compare a tangentially compliant contact model with plate impacts and player data. Their model's launch ratio varies with incidence even at fixed friction, and changing friction has different effects across incidence regimes. It uses a fixed impact surface and an adjustment for normal inelasticity; agreement in those comparisons is not a universal validation for moving, rotating clubheads. The findings support examining the contact-force history rather than attributing all club-dependent weighting to surface smoothness.

3.1.2 Spin Loft and Approximate Launch Maps

The geometric angle Φ between the local normal and contact-point incident velocity satisfies the full dot product

$$\cos \Phi = \hat{\mathbf{n}} \cdot \hat{\mathbf{p}}_c = \sin \lambda_d \sin \alpha_c + \cos \lambda_d \cos \alpha_c \cos(\varphi_f - \varphi_c). \quad (3.4)$$

This contact obliquity equals a reported spin loft only when point, time and angle definitions match. For coplanar forward directions it reduces to $|\lambda_d - \alpha_c|$. Writing $A_c = \varphi_f - \varphi_c$, neither $\cos A_c \cos \lambda_d$ nor $\cos A_c \cos(\lambda_d - \alpha_c)$ is a general replacement when horizontal separation and both elevations are nonzero.

Tutelman's historical model [87] uses its own loft/relative-angle construction and an approximate launch map,

$$f(\Phi) = 0.96 - 0.0071\Phi, \quad \text{DA}_{\text{vert}} = Lf(\Phi), \quad \text{DA}_{\text{horiz}} = Af(\Phi), \quad (3.5)$$

with angles in degrees and A, L interpreted according to that model. Its historical loft terminology is not interchangeable with target-frame dynamic loft, and its later comparison with TrackMan does not establish that the original model was fitted to that comparison. Treat the map as an author approximation with a declared domain, not an exact spherical-coordinate transformation or a general friction identification. For a three-dimensional implementation, obtain launch angles from the predicted velocity vector using `atan2`; adding component angles is not a general rotation composition.

3.1.3 Spin-Axis Tilt

A spin axis needs a reference frame as well as a direction. For outgoing unit velocity $\hat{\mathbf{v}}_b$ that is not vertical, let $\hat{\mathbf{e}}_y$ be world up and define

$$\hat{\mathbf{e}}_b = \frac{\hat{\mathbf{v}}_b \times \hat{\mathbf{e}}_y}{\|\hat{\mathbf{v}}_b \times \hat{\mathbf{e}}_y\|}, \quad \hat{\mathbf{e}}_u = \hat{\mathbf{e}}_b \times \hat{\mathbf{v}}_b, \quad \theta_{\text{axis}} = \text{atan2}(-\boldsymbol{\omega}_b \cdot \hat{\mathbf{e}}_u, \boldsymbol{\omega}_b \cdot \hat{\mathbf{e}}_b). \quad (3.6)$$

This convention makes positive backspin point along $\hat{\mathbf{e}}_b$ and gives positive tilt for a right-curving spin component in ordinary forward flight. Compare a device's sign and reference-axis definition before comparing its number. A vertical launch needs a different frame construction; a zero spin vector has no spin-axis direction. The tilt is also undefined when both transverse projections vanish, even if an axial spin component is nonzero. A general spin vector can also have a component along $\hat{\mathbf{v}}_b$, so total spin and one tilt angle do not specify every three-dimensional spin state.

The often-used ratio $\tan(\text{face-to-path})/\tan(\text{spin loft})$ is not an exact tilt identity for general target-frame angles. Calculate the cross product and its projections under the stated collision assumptions instead. Likewise, a fixed yards-per-degree or return-to-target multiplier cannot replace a flight calculation: speed, spin magnitude, launch, wind and aerodynamic coefficients also affect curvature.

Design implication

If an estimator adopts the launch-weight model, it may infer $\varphi_f = [\varphi_{\text{launch}} - (1 - w_f)\varphi_p]/w_f$. Its local launch sensitivity is $1/w_f$; path, weight, reference-frame covariance and model discrepancy contribute separately. Agreement between an inferred face angle and the launch measurement used to infer it is not an independent validation of that face angle.

3.2 Ball Speed and Smash Factor

Let J_n be the normal impulse on an initially stationary ball of mass m . For a free rigid head of mass M , centroidal inertia tensor I_h and contact lever arm $\mathbf{r}_h$, its normal inverse effective mass is

$$\frac{1}{M_{\text{eff},n}} = \frac{1}{M} + (\mathbf{r}_h \times \hat{\mathbf{n}})^\top I_h^{-1} (\mathbf{r}_h \times \hat{\mathbf{n}}). \quad (3.7)$$

In the scalar limit with no normal–tangential coupling, normal restitution e_n and closing speed $V_c \cos \Phi > 0$ give [7, 53]

$$J_n = \frac{(1 + e_n)V_c \cos \Phi}{1/m + 1/M_{\text{eff},n}}, \quad \mathbf{v}_b^+ \cdot \hat{\mathbf{n}} = \frac{1 + e_n}{1 + m/M_{\text{eff},n}} V_c \cos \Phi. \quad (3.8)$$

This predicts the *normal component* of ball velocity. If there is tangential impulse, $\mathbf{v}_b^+ = (J_n \hat{\mathbf{n}} + \mathbf{J}_t)/m$ and the speed norm also contains that component. Normal–tangential coupling requires a coupled contact solve rather than inserting an effective mass into an otherwise unrelated scalar fit.

For illustration only, taking $m = 0.04593$ kg, $M_{\text{eff},n} = 0.200$ kg and $e_n = 0.83$ gives the following normal-component ratios to V_c :

Obliquity	0°	10°	20°	30°
Normal Ratio	1.488	1.466	1.398	1.289

These are manufactured values, not a current equipment-conformance test or a loft-dependent physical ceiling. The assumed restitution is a model parameter; it does not identify every real ball/face combination or impact speed.

Key point

A reported smash factor divides measured ball speed by a specified reported club speed, which need not be the contact-point incident speed V_c . Exceeding one row of this illustrative table therefore does not by itself prove measurement error. Before rejecting a shot, reconcile reference point and time, effective inertia, contact model and uncertainty. A discrepancy is a diagnostic lead, not a universal impossibility verdict.

3.3 Spin Generation

The same tangential impulse changes both ball translation and angular momentum. For a spherical ball with contact arm $-R\hat{\mathbf{n}}$, $\Delta\boldsymbol{\omega}_b = I_b^{-1}(-R\hat{\mathbf{n}}) \times \mathbf{J}_t$. For an impulse in the obliquity plane, the launch deflection from the normal satisfies $\tan \delta_b = J_t/J_n$. Thus independently chosen launch and spin fits must still be checked for compatibility with one contact solution. Tangential compliance can reverse force during contact; a single friction coefficient does not specify the entire slip–stick history [29, 8].

When its club-speed input is identified with V_c , an empirical approximation in Tutelman’s model is [87]

$$S \text{ [rpm]} \approx 160 V_c \text{ [mph]} \sin \Phi. \quad (3.9)$$

The coefficient carries the stated units and is not a dimensional identity or a universal spin law. Retain the model’s input conventions and calibration limits; use the predicted spin vector for component decomposition rather than imposing a separate trigonometric tilt rule. Rules based only on iron loft, or a universal spin-loft saturation angle, omit contact material, speed and force history. Changing surface conditions changes the contact problem; this chapter supplies no universal contamination correction or threshold.

3.4 Gear Effect and Impact Location

An off-center impulse rotates the head and changes contact-point velocity during collision. In a simplified horizontal construction, let x be the signed lateral offset from the head CG line, C the normal CG-to-face distance and I_h the head inertia about the relevant vertical axis. Tutelman's angular-impulse heuristic [85] estimates $\Delta\omega_h = xmV_b/I_h$ and equates a face tangential speed to the ball's rotational surface speed at separation, giving

$$s \text{ [rpm]} \approx 58,830 \frac{V_b[\text{mph}] C[\text{in}] x[\text{in}]}{I_h[\text{g cm}^2]} \approx 16.4 V_b[\text{mph}] x[\text{in}]. \quad (3.10)$$

The last coefficient uses the author's representative $C = 1.42$ in and $I_h = 5100 \text{ g cm}^2$; there is no extra factor of 100. For $V_b = 150$ mph and $x = 0.25$ in, the simplified estimate is 615 rpm, not 61,500 rpm. The cited 2.5% describes the relative sample standard deviation of a historical, filtered inertia/depth ratio, not a guaranteed spin-prediction error or all current drivers. The contact-speed assumption neglects ball tangential translation and coupled recoil, so the heuristic is not a complete no-slip impact solution.

3.4.1 Why a Coupled Contact Solve Matters

The missing terms can be seen without fitting a golfer or product. Consider an initially nonspinning free head moving normally at speed V toward a stationary spherical ball, with head contact arm $C\hat{n} + x\hat{t}$ in a planar model. The unit tangent $\hat{t}$ is perpendicular to $\hat{n}$. The head has mass M and scalar inertia I_h ; the ball has mass m , radius R and inertia I_b . Take positive inertial parameters and $V > 0$, with $0 \leq e_n \leq 1$ and an impulsive friction coefficient $\mu \geq 0$. With impulse components (J_n, J_t) on the ball, the ball-minus-head contact-velocity increment is $K(J_n, J_t)^\top$, where

$$K = \begin{pmatrix} \frac{1}{m} + \frac{1}{M} + \frac{x^2}{I_h} & -\frac{Cx}{I_h} \\ -\frac{Cx}{I_h} & \frac{1}{m} + \frac{1}{M} + \frac{R^2}{I_b} + \frac{C^2}{I_h} \end{pmatrix}. \quad (3.11)$$

Normal restitution and zero final tangential relative velocity then give the sticking candidate

$$K \begin{pmatrix} J_n \\ J_t \end{pmatrix} = \begin{pmatrix} (1 + e_n)V \\ 0 \end{pmatrix}, \quad |J_t| \leq \mu J_n. \quad (3.12)$$

The inequality must hold for the candidate to be admissible under this impulsive friction model; otherwise a sliding branch is needed. The term $1/m$ in the tangential entry accounts for ball translation, R^2/I_b for ball spin and the head terms for recoil. Consequently, matching contact velocities does not mean that face speed equals R times ball spin. This idealization still omits contact compliance, shaft impulses and changing face geometry; it is a consistency calculation, not a universally identified gear-effect law.

Bulge and roll alter the local normal as strike location changes, while gear effect alters the impulse through head motion. Their contributions must be evaluated together; changing the rotation axis also changes the relevant head inertia. An optical strike measurement can constrain the geometry, but uncertainty in pose, CG, inertia and contact response remains. Neither a quoted yardage example nor Equation (3.10) provides a universal bound on face-angle inference error.

Design implication

Impact location is valuable when it resolves an important uncertainty for the intended outcome. Its priority relative to face pose, local velocity or spin requires a sensitivity and uncertainty analysis. Off-center launch/spin cannot in general be inverted with a centered D-plane model alone, and adding a strike sensor does not remove collision-model discrepancy.

3.5 Vertical Plane and the Low-Point Geometry

A fixed inclined-plane construction explains one conditional coupling between attack and horizontal path. Set the plane's horizontal base along the target and its inclination to $0 < \beta < 90^\circ$, with unit normal $(0, \cos \beta, \sin \beta)$ in the forward/up/right frame. A velocity direction with elevation α_c and horizontal offset ψ lies in that plane only if

$$\sin \alpha_c \cos \beta + \cos \alpha_c \sin \psi \sin \beta = 0, \quad \sin \psi = -\frac{\tan \alpha_c}{\tan \beta}. \quad (3.13)$$

On the forward-moving branch, $\alpha_c = -5^\circ$ and $\beta = 60^\circ$ give $\psi \approx 2.8953^\circ$ to the right. The result requires $|\tan \alpha_c / \tan \beta| \leq 1$ and the declared side of plane inclination; a mirrored plane changes the sign. A measured swing need not follow one fixed plane, and this derivation does not establish any particular product's processing algorithm.

3.6 Connecting Delivery, Impact and Measurement

Swing dynamics determines the delivered local velocity, orientation and retained elastic state; contact mechanics converts that state into an impulse and outgoing ball state; the instrument estimates selected quantities from its observations. An explanation of technique must keep those stages connected while testing each with sufficiently independent evidence. For example, changing wrist motion may alter both face pose and contact-point velocity, and changing strike location may alter both the local normal and effective inertia. A single fitted launch percentage cannot identify which change caused an observed ball flight. Report the retained states, reference points, contact assumptions and uncertainty alongside the conclusion, and compare joint predictions of launch direction, speed and spin rather than validating each with incompatible scalar rules.

Chapter 4

Doppler Radar Systems

Radar observations constrain a moving target through frequency, phase, amplitude and timing. A launch monitor combines those observations with geometry, signal processing and, for some outputs, a collision or flight model. The useful question is which quantities the available observations identify, under which assumptions, and with what uncertainty. Those distinctions matter when launch-monitor outputs are used to explain a golfer's swing: two reported parameters can share the same measured input and therefore share its errors.

Key point

What This Shows: The measurement equations below explain radial velocity, angular ambiguity, spin signatures and conditional trajectory-based spin-axis inference. They also show how an inferred face angle can inherit uncertainty from ball launch and club path. **What It Does Not Show:** A patent disclosure, vendor specification or manufactured calculation does not establish the accuracy or internal implementation of every commercial product. Device generation, firmware, ball type, geometry and operating mode must accompany any performance claim.

4.1 Continuous-Wave Doppler Fundamentals

A continuous-wave (CW) radar transmits a carrier at frequency f_c , with wavelength $\lambda = c/f_c$. For monostatic transmission and reception, target speeds small compared with c , and a sign convention assigning positive Doppler to increasing range, the instantaneous range rate $v_r = \dot{r}$ gives

$$f_d = \frac{2v_r}{\lambda} = \frac{2f_c v_r}{c}. \quad (4.1)$$

The factor of two accounts for the outgoing-plus-return path; the displayed Doppler sign depends on the receiver's mixing convention. At an illustrative carrier of 24.125 GHz, one mph of radial speed gives approximately 71.95 Hz; at 10.5 GHz, it gives 31.31 Hz, using $c = 299\,792\,458$ m/s and $1 \text{ mph} = 0.447\,04$ m/s. These conversions do not identify a particular product's carrier or detection range.

Carrier frequency alone does not set a flight-tracking limit. For a coherent observation of duration T , Fourier-bin spacing of order $1/T$ corresponds to radial-velocity spacing of order $\lambda/(2T)$. That is spectral spacing, not a universal velocity-error bound: windowing, acceleration, estimator design and signal-to-noise ratio matter. For an ideal wideband ranging waveform, range resolution instead scales with transmitted bandwidth B , approximately $c/(2B)$; angular performance depends on aperture and geometry. Detection range additionally depends on transmitted power, antenna gain, target scattering, propagation, clutter and detection thresholds. A blanket thirty-yard limit for consumer 24 GHz radar cannot follow from the carrier frequency; the hybrid disclosure discussed below itself proposes much longer ranges [9].

4.2 From Velocity Sensor to 3D Tracker: Phase Interferometry

A single unmodulated CW channel supplies radial-velocity information without independently resolving absolute range and two angular coordinates. Multiple calibrated receive antennas can add direction information. Let $\hat{\mathbf{u}}$ denote the unit direction from the array toward the target. For a locally planar wavefront in a narrowband, far-field approximation, receivers separated by baseline $\mathbf{d}$ have a relative delay $\tau = (\mathbf{d} \cdot \hat{\mathbf{u}})/c$, with direction and phase signs chosen consistently. For baseline length d , direction cosine $u = \mathbf{d} \cdot \hat{\mathbf{u}}/d$ along it and a calibrated measured phase $\Delta\varphi$, the possible directions are

$$\Delta\varphi \equiv \frac{2\pi d}{\lambda} u \pmod{2\pi}, \quad u_k = \frac{\lambda(\Delta\varphi + 2\pi k)}{2\pi d}, \quad k \in \mathbb{Z}, \quad |u_k| \leq 1. \quad (4.2)$$

The integer branch is part of the inverse problem. For $d = \lambda$, direction cosines 0.2 and -0.8 give the same complex phase. Half-wavelength spacing avoids interior aliases over the full direction-cosine interval, but its opposite endpoints still coincide in phase. Larger baselines may be usable over a restricted field of view or with additional, appropriately chosen baselines and joint ambiguity resolution; an antenna count alone does not guarantee uniqueness [89].

Two independent baselines constrain two direction cosines, with a physical hemisphere choice needed to reconstruct a direction. Near endfire, converting a direction cosine to an angle is poorly conditioned: for an angle θ measured from broadside so that $u = \sin \theta$, small unwrapped phase errors give $\delta\theta \simeq \lambda\delta\varphi/(2\pi d \cos \theta)$. This local approximation excludes branch errors and becomes unreliable near $\cos \theta = 0$. Near-field wavefront curvature requires a range-dependent propagation model rather than the plane-wave formula. Combining a resolved direction with independently estimated range and range rate can yield a three-dimensional track, provided the channels observe the same target and share calibrated coordinates and timing. A per-Doppler-bin direction is a direction of contributing scattering, not automatically the ball center or a labeled point on a clubface [90].

Design implication

One speed module and two angle modules form an investigational sensing arrangement, not a validated launch monitor merely by supplying three outputs. RFbeam's K-LD7 exposes raw I/Q data: its RADC packet contains Rx1 and Rx2 at one carrier setting and Rx1 at a second setting used for FSK ranging. The March 2021 Revision B datasheet specifies a maximum configured speed of 100 km/h, a typical 29 ms frame at that setting, and warnings about out-of-range returns and serial throughput [63]. Its person-detection example and configurable range do not establish golf-ball performance. An implementer must establish speed and signal bandwidth, target association, synchronization, ambiguity handling and error propagation before treating these modules as a three-dimensional ball tracker. A rigid mount and surveyed calibration help, but do not remove the need to model drift, multipath and processing errors.

4.3 CW + FMCW Hybrids

Frequency-modulated continuous-wave (FMCW) sensing adds delay information through a known transmitted frequency history. For a moving target, beat frequency contains range and Doppler contributions, so separating them depends on the waveform and estimator; a chirp does not make range an assumption-free observable. Full Swing's US 11,311,789 describes example 24 GHz CW and linear-FMCW channels, multiplexing alternatives and several antenna layouts [9]. The disclosure associates Doppler signatures with speed and spin and modulated signals with range, and discusses

ranges exceeding 250 m. Its examples include a ball swung on a line at 75 m; that demonstration is not an independent accuracy study of full golf shots. The array drawings include both symmetric and nonuniform arrangements, so one example should not be presented as the definitive commercial KIT layout. The disclosure establishes proposed mechanisms; which mechanisms are deployed, and their error distributions, require separate product-specific evidence.

4.4 Ball Measurement

4.4.1 Speed and Launch Angles

A processor must associate the post-impact Doppler return with the ball before interpreting it as ball radial velocity. Three-dimensional launch velocity also requires direction information from a fitted track or another sensing channel. If α is the angle between target velocity and the radar line of sight, $v_r = \|\mathbf{v}\| \cos \alpha$; it is not generally enough to substitute the launch angle relative to the ground for α . Dividing by $\cos \alpha$ becomes poorly conditioned near a tangential trajectory, and uncertainty in direction then strongly affects inferred speed. The reported impact state must also distinguish a sample taken after impact from a value extrapolated back to the defined event.

Leach et al. compared TrackMan Pro IIIe and Foresight GC2+HMT with a benchmark optical system using 240 shots across a driver, 7-iron and utility wedge [39]. They found generally stronger agreement for ball parameters than clubhead parameters, with several results dependent on club. That evidence supports a device- and study-specific distinction; it does not establish best agreement for the same parameters in every study or newer product.

4.4.2 Spin Rate: Harmonic Signatures and Their Ambiguities

Tuxen's US 8,845,442 describes extracting spin information from Doppler spectral structure [88]. In a rigid-ball point-feature model, let $\mathbf{v}_C$ be center velocity, $\boldsymbol{\rho}(t)$ the feature's offset from the center, and $\boldsymbol{\omega}$ the angular velocity, all expressed in one frame. Using a common line-of-sight unit vector $\hat{\mathbf{n}}$ across the small target gives

$$f_{d,\text{feature}}(t) = \frac{2}{\lambda} \hat{\mathbf{n}} \cdot [\mathbf{v}_C + \boldsymbol{\omega} \times \boldsymbol{\rho}(t)]. \quad (4.3)$$

The rotational term vanishes for spin parallel to that line of sight. For constant spin and approximately fixed viewing direction, a feature at perpendicular distance $\rho_\perp$ from the spin axis has a sinusoidal projected velocity with amplitude $\|\boldsymbol{\omega}\| \rho_\perp \sin \beta$, where β is the spin-axis/viewing angle. The simpler amplitude $\rho_\perp \|\boldsymbol{\omega}\|$ requires a view perpendicular to the spin axis; $\rho_\perp$ equals the ball radius only for an equatorial surface feature. Actual returns also depend on coherent scattering, visibility and rotating reflectivity, so this point-feature model is not a complete electromagnetic ball model.

Let S denote spin rate in revolutions per minute. Periodic modulation at rotation frequency $f_{\text{spin}} = \|\boldsymbol{\omega}\|/(2\pi)$ can produce spectral lines

$$f_n = f_d + n f_{\text{spin}}, \quad n \in \mathbb{Z}, \quad S [\text{rpm}] = 60 f_{\text{spin}} [\text{Hz}]. \quad (4.4)$$

Observed peaks need not include every integer order, symmetric peaks need not have equal detectable amplitude, and some rotation aspects may yield weak modulation. For example, peaks offset by 200 and 400 Hz can represent the first two orders of 200 Hz or the second and fourth orders of 100 Hz. A reflector pattern that repeats after half a revolution can suppress odd harmonics relative to the

mechanical rotation frequency. Consequently, multiplying the spacing of any two visible peaks by sixty is not a generally valid spin estimator.

The patent describes tracking candidate traces, qualifying harmonics and assigning their orders before estimating rotation frequency [88]. Comb or cepstral processing can organize candidates, but cannot by itself resolve information absent from the observation. Window duration, frequency drift, noise, clutter, scattering asymmetry and ball markings affect which candidates are distinguishable. A harmonic spacing yields a candidate spin magnitude; it does not alone give a three-dimensional spin axis, though additional phase, amplitude, geometric or trajectory observations may supply axis information.

4.4.3 Spin Axis: Conditional Trajectory Inversion

Trajectory inversion combines observations with a force model. Let $\mathbf{v}_a = \mathbf{v} - \mathbf{w}$ be air-relative velocity for wind $\mathbf{w}$; let $\mathbf{A}$ denote ball acceleration in the ground-fixed inertial approximation, $\mathbf{g}$ gravitational acceleration, and $\mathbf{D}$ and $\mathbf{L}$ drag and lift accelerations, not forces. Assume aerodynamic acceleration separates into drag parallel to $\mathbf{v}_a$ and lift perpendicular to it, with no omitted transverse force. For nonzero airspeed,

$$\mathbf{D} = \frac{(\mathbf{A} - \mathbf{g}) \cdot \mathbf{v}_a}{\|\mathbf{v}_a\|^2} \mathbf{v}_a, \quad \mathbf{L} = \mathbf{A} - \mathbf{g} - \mathbf{D}. \quad (4.5)$$

Physical drag additionally requires the fitted parallel component to oppose airspeed; a projection alone does not enforce that sign. Unknown wind, omitted forces and differentiation errors can contaminate the inferred lift. Acceleration estimated from position is especially sensitive to noise and the chosen temporal fit.

For a fixed spin-axis direction over the fitted interval and a Magnus model with $\mathbf{L}$ perpendicular to that axis, stacking the constraints at N sample times gives

$$\mathbf{M}\hat{\boldsymbol{\omega}} = \mathbf{0}, \quad \mathbf{M} = \begin{bmatrix} \mathbf{L}_1^\top \\ \vdots \\ \mathbf{L}_N^\top \end{bmatrix}, \quad \|\hat{\boldsymbol{\omega}}\| = 1. \quad (4.6)$$

In exact consistent data, rank two leaves one axis line, with two possible signs; rank one leaves a plane of candidate vectors and therefore a continuum of unit axes. No lift leaves no directional information through this constraint. The zero vector is always a solution of the unconstrained homogeneous system, which is why unit normalization is essential. Noisy rows generally do not have an exact common nullspace: a weighted unit-norm fit and its conditioning are needed, rather than declaring uniqueness from a numerical rank alone. The separation between the smallest singular values matters to axis stability.

A signed Magnus relation, such as $\mathbf{L} = \kappa \boldsymbol{\omega} \times \mathbf{v}_a$ with a stated positive effective aerodynamic coefficient κ , can help select the orientation and estimate spin components. At one instant, adding spin parallel to $\mathbf{v}_a$ leaves this cross product unchanged. Changing air-relative velocity over time can add information if the same spin vector and force model remain applicable; instantaneous insensitivity does not prove non-identifiability over every trajectory. The patent's trajectory route must be interpreted with those model and geometry assumptions [88]. A longer observed flight often supplies more useful curvature, but does not guarantee accurate inference. A short indoor segment can be poorly conditioned, especially with low lift or uncertain wind; both outdoor and indoor fitted axes remain estimates with different information and uncertainty.

4.4.4 A Dimensional and Algebraic Check on a Delay Disclosure

FlightScope’s US 10,775,492 describes a different spin-axis approach using spatially separated receiver pairs [33]. In that disclosure, S_V and S_H are vertical and horizontal receiver separations, D is target distance, and Φ is the spin-axis angle inferred from those pairs. Its displayed relations give $T_V = (S_V/D) \cos \Phi$ and $T_H = (S_H/D) \sin \Phi$, while calling the T quantities time delays, and subsequently give $\arctan[S_H T_H / (S_V T_V)]$ for the angle. With S_V, S_H, D all lengths, those right-hand sides are dimensionless and require an additional time scale to represent delays. Moreover, even treating the printed T quantities as normalized values, elimination gives

$$\Phi = \operatorname{atan2}\left(\frac{T_H}{S_H}, \frac{T_V}{S_V}\right), \quad \tan \Phi = \frac{S_V T_H}{S_H T_V}, \quad (4.7)$$

where the tangent form applies only when its denominator is nonzero and loses quadrant information. For manufactured values $S_V = 0.1$, $S_H = 0.2$, $D = 3$ in consistent length units and $\Phi = 30^\circ$, the displayed patent ratio returns approximately 66.59° ; the algebraic elimination returns 30° . This identifies an inconsistency in the displayed relationships, not a validated replacement for the full measurement method or an interpretation of patent scope. A working delay estimator still needs timing definitions, feature correspondence, rotational geometry and experimental validation.

4.4.5 Flight Observation, Extrapolation, and Ball Modes

A trajectory tracked to landing can support measured-flight outcomes; a trajectory truncated by a screen requires a flight model for the unobserved part. A normalized trajectory, computed for selected weather or ball conditions, must also be distinguished from the actual observed shot. These are output modes, not an absolute division between radar brands. TrackMan’s published TM4 minimum indoor setup of 4.7 m is *device-to-net* distance, not 4.7 m of ball flight [78]. FlightScope’s X3C instructions separately specify sensor-to-tee and ball-flight distances and identify marking/RCT requirements for indoor spin capture [12]. Instructions for that generation should not silently be applied to every earlier X3 or Mevo.

Garmin’s general R10 guidance describes standard-ball conditions under which spin is modeled rather than captured, including ball flight below 20 m or ball speed below 90 mph [19]. It must be read alongside the RCT mode: Garmin describes indoor spin capture with compatible Titleist RCT balls and current software, with at least eight feet tee-to-net and about two ball rotations for its most reliable results [21]. The support text allows successful capture with fewer rotations but also describes fallback to estimated spin when capture is inadequate; the app distinguishes that estimate typographically. Thus the standard-ball twenty-meter/ninety-mph guidance is not a universal requirement to measure spin in every supported mode. Marked radar-reflective balls and optically printed balls are different sensing aids and are not interchangeable across devices.

4.5 Club Measurement

4.5.1 What the Radar Tracks on the Head

A rotating clubhead has a velocity field: for a point P offset by ρ from reference point C , $\mathbf{v}_P = \mathbf{v}_C + \boldsymbol{\omega} \times \rho$. Here $\boldsymbol{\omega}$ is clubhead angular velocity, rather than the ball angular velocity in the preceding section. The fastest or strongest radar return need not correspond to the reference point used for reported club speed. Its bias is not universally positive; it depends on geometry and which part of the head dominates the return. TrackMan describes a reconstructed clubhead silhouette

and defines reported parameters using specific points and event times [83, 84]. Club path and attack angle concern a declared velocity direction; face angle and dynamic loft concern surface orientation, potentially at the impact location rather than the geometric center. For curved faces, those orientations differ. Point, frame, timing and surface definitions must therefore be reconciled before attributing a disagreement between instruments to sensor error.

4.5.2 Face Angle and Dynamic Loft

Radial-velocity sensing alone does not uniquely determine every clubface orientation, but it is too strong to say radar can never provide orientation information. Resolved scattering geometry, multiple views, temporal constraints and other sensors can add information; the available model and measurements determine observability (Chapter E). One possible estimation route is inversion of a local collision approximation. Let φ_f be face angle, φ_p club path angle and w_f the effective face weighting in a local collision model. For small horizontal angles about the same reference direction, suppose launch direction satisfies $\varphi_{\text{launch}} \simeq w_f \varphi_f + (1 - w_f) \varphi_p$ with known nonzero w_f . Then

$$\varphi_f \simeq \frac{\varphi_{\text{launch}} - (1 - w_f) \varphi_p}{w_f}. \quad (4.8)$$

This is an inverse of the stated local model, not a description of every radar product. The effective weighting depends on collision conditions and must not be transferred unchanged between clubs, lofts, ball types and impact locations (Section 3.1.1). A vertical-angle approximation likewise requires its own justified weighting and operating domain; it is not automatically obtained by substituting names into a horizontal fit.

For small perturbations within this model,

$$\delta \varphi_f \simeq \frac{\delta \varphi_{\text{launch}}}{w_f} - \frac{1 - w_f}{w_f} \delta \varphi_p + \frac{\varphi_p - \varphi_{\text{launch}}}{w_f^2} \delta w_f. \quad (4.9)$$

The launch-error gain is $1/w_f$ and therefore depends on the chosen collision weighting. Correlated measurement errors and uncertainty in the collision model also contribute. Off-center impact and gear effect can invalidate a fit that omits impact location; a richer estimator may use additional observations to address them. A common horizontal reference offset moves face and path together and cancels in their difference in this approximation, whereas independent misalignments need not cancel.

Key point

An inferred face angle can be statistically coupled to the measured launch direction because the estimator uses that direction as an input. Agreement or correlation between those outputs is therefore not independent confirmation of a physical face-to-launch relationship. For swing analysis, document the measurement and inference dependencies, propagate their covariance, and compare against an independent criterion before drawing conclusions about technique.

4.5.3 Known Limitations

The Leach et al. comparison motivates caution about clubhead outputs for research, but does not rank all modern radar and optical systems [39]. A pickup rate describes availability, not the error distribution of successful readings. TrackMan's stated club-data pickup rate in its 2020 OERT description should be read in that sense [83]. Validation should retain missed shots, state the tested clubs and speeds, and distinguish bias, dispersion and repeatability from agreement with an independent reference.

4.6 Optically Enhanced Radar: OERT and Fusion Tracking

TrackMan’s OERT description presents synchronized dual radar and camera observations, including clubhead silhouette and impact-location information [83]. Its current specification table describes TM4 and the indoor iO separately; the latter combines 24 GHz radar with cameras and describes optical three-dimensional spin measurement [78]. Those descriptions support the stated product distinctions without exposing every proprietary processing step. FlightScope describes Fusion Tracking as synchronized image processing combined with radar, and US 10,338,209 discloses mechanisms for combining the modalities [12, 32]. The presence of a patent does not establish independent accuracy or prove that every disclosed option is deployed.

Rapsodo explicitly requires the printed RPT pattern for MLM2PRO optical spin measurement; its support distinguishes RPT from RCT radar-reflective balls [60]. Full Swing markets machine-learning radar and video capabilities, but that description alone does not establish that its camera contributes to a fused spin/face estimator [18]. A camera used for swing video is not automatically a measurement camera.

Design implication

Choose an additional sensor to reduce a specified ambiguity or uncertainty, then test whether the combined estimator does so. Optical features can constrain orientation or impact location; radar can contribute radial velocity and flight tracking; ball markings can improve identifiable rotational structure. Their value depends on visibility, timing, calibration and the joint model. Combining modalities can improve inference, but neither sensor count nor a vendor’s architectural choice proves a universal limit of radar or the accuracy of a new implementation.

Chapter 5

Photometric (Camera) Systems

5.1 Imaging Architectures

Photometric launch monitors capture a short burst of high-speed, IR-strobed stereo images over a small capture volume beside (or above) the tee — roughly the first 30 cm of ball flight — and reconstruct ball and club kinematics photogrammetrically. The commercial family tree:

- **Foresight Sports** defined the reference floor-unit design. The GC2 (2010) used two cameras (“stereoscopic”), with club data via the add-on HMT module (two more cameras). The GC3 / Bushnell Launch Pro (a Foresight-built rebadge) use three cameras; the GCQuad and QuadMAX use four cameras at the corners of the sensor window, capturing on the order of 200 images of ball and club per shot at burst rates quoted up to 10,000 fps; the ceiling-mounted GCHawk points the same quadrascopic package downward [15, 56]. Onboard IR object tracking detects the teed ball and the inbound clubhead and triggers the burst; intrinsics/extrinsics are factory-calibrated (“no calibration needed”) [15].
- **Uneekor** mounts overhead: EYE XO/XO2 look straight down from ~3 m with two (XO2: three) high-speed IR cameras at 3,000+ fps [92]. The overhead geometry sees the clubhead and face region directly, enabling sticker-free club data and impact-location video replay (Club Optix). The portable EYE MINI reverts to a side view and therefore requires club stickers.
- **ProTee VX**: overhead, two synchronized high-speed cameras with IR illumination and an ML shot-analysis pipeline; sticker-free club and ball data including vertical/horizontal impact point [57].
- **Garmin Approach R50**: three high-speed cameras arranged horizontally in a floor unit; purely optical ball and club measurement, with clubhead data requiring reflective fiducials [20].
- **SkyTrak / SkyTrak+**: the original SkyTrak was photometric and ball-only; the SkyTrak+ added a dual Doppler radar module specifically for club data while the cameras handle ball launch and spin [64].

5.2 Ball Measurement

5.2.1 Photogrammetric Position and Velocity

With factory-known intrinsics K_i and extrinsics $[R_i|t_i]$, each synchronized image set yields a 3D ball-center fix by triangulation: back-project the matched detections as rays and solve the least-squares intersection (or the DLT system $\tilde{\mathbf{x}} \times (P\mathbf{X}) = 0$), refining by reprojection error. Ball speed is the displacement between timestamped fixes; launch angle and direction are the components of the initial velocity vector in the calibrated target frame. Two error sources dominate: depth error

grows quadratically with distance,

$$\sigma_Z = \frac{Z^2 \sigma_{px}}{f B}, \quad (5.1)$$

for baseline B and focal length f — which is why photometric units keep the capture volume small and also exploit the known ball diameter (21.34 mm radius) as an auxiliary range cue; and center-finding bias — fitting the projected *conic* outline rather than taking the blob centroid avoids a systematic offset of up to RZ/f pixels.

5.2.2 Spin: Dimple-Pattern Registration

The flagship photometric capability is markerless 3D spin. Successive frames of the ball are registered on the sphere: the estimator searches the rotation $R \in SO(3)$ that best maps the back-projected surface texture (the dimple pattern, plus any logo or blemish) of frame k onto frame $k+1$ — Foresight brands this *spherical correlation*; Uneekor, *Dimple Optix* [14, 94]. The recovered R gives everything at once:

$$\hat{\omega} = \text{eig}_1(R), \quad \theta = \arccos\left(\frac{\text{tr } R - 1}{2}\right), \quad \omega = \theta/\Delta t, \quad (5.2)$$

i.e. the spin axis is the eigenvector of R with unit eigenvalue and the spin rate follows from the per-frame rotation angle. Reported accuracy is 1–3% of true spin, independent of ball speed. The known failure mode is rotational aliasing at high spin and low frame rate (the $n \cdot 2\pi$ ambiguity), resolved by multi-hypothesis tracking or a trajectory-consistency prior. Where resolution cannot support dimple registration, systems fall back to *marked balls*: Uneekor QED and Rapsodo (RPT balls) track printed high-contrast features, giving closed-form rotation from ≥ 3 correspondences via the Kabsch/Horn algorithm.

5.3 Club Measurement

5.3.1 Fiducial Markers: The Foresight Approach

Foresight floor units require retroreflective **fiducial dots** on the clubface. The dot count maps directly to the data tier [16, 17]: one dot suffices for club speed, path, and attack angle (tracking a single 3D point through the capture volume); *four dots* — placed on the vertical centerline, equidistant from the horizontal centerline — define the face plane and enable face angle, dynamic loft, lie, closure rate ($^\circ/\text{s}$), and **impact location**. Mechanically: the IR strobe makes the dots bloom in every frame; triangulating the dot constellation across cameras and frames yields the 6-DOF pose of the face through impact. Club speed is the pose translation rate; path and attack angle are the velocity direction; face angle and dynamic loft are the face-plane orientation at contact; impact location is the measured ball position expressed in the face frame. The GC3/Launch Pro tier delivers speed, path, attack, face angle, and impact via the same stickers but omits dynamic loft, lie, and closure rate — these remain GCQuad/QuadMAX exclusives [56].

5.3.2 Sticker-Free Overhead Tracking

Uneekor’s overhead cameras segment the clubhead silhouette directly — no markers — because the top-down view presents the head against the mat with controlled IR illumination; the systems also record actual high-speed impact video (face-on via Club Optix), from which impact location is read [92]. ProTee VX claims the same sticker-free club set (speed, path, face, attack, dynamic loft, lie, vertical and horizontal impact point) from its overhead ML pipeline [57]. The trade-off is installation: overhead units need $\sim 3\text{ m}$ ceilings, rigid mounting, and a floor-chart calibration.

5.3.3 Calibration

Factory-rigid multi-camera rigs ship calibrated; the user aligns only the target line. Overhead systems require field calibration: Uneekor’s procedure places a printed calibration chart on the mat, levels it, squares it to the screen, and aligns its crosshair to overlays on the live camera feeds — establishing the ground plane, hitting zone, and target-line extrinsics [5]. This is the pattern a DIY overhead build should copy.

5.4 The Indoor Argument, and What Cameras Cannot Do

Photometric systems measure actual launch conditions — including 3D spin — in the first foot of flight; nothing is lost when the ball hits a screen 2.5 m away. Radar indoors must infer from a truncated flight. This is the structural reason camera units dominate indoor simulation while radar dominates outdoor practice: each modality measures what the other models [27]. The camera’s blind spots are downrange (all flight is simulated from launch) and, for floor units, the club face itself without stickers — the same face-visibility problem radar has, solved with markers instead of models.

5.5 DIY and Open-Source Photometric Systems

PiTrac [55] is the flagship open-source photometric build and the most relevant open-source precedent. Instead of multi-kfps cameras it uses *strobed multi-exposure capture*: an IR LED array pulses several times within one long exposure of a ~\$50 Raspberry Pi Global Shutter camera, freezing multiple ball images in a single frame. One camera watches the teed ball and detects launch; the second captures the strobed flight images; a custom PCB sequences trigger and strobe. Processing (C++/OpenCV): Hough-circle detection locates ball images; strobe-timestamped positions give speed and launch angles; 3D spin on all three axes is solved by searching candidate rotations that best register the dimple imagery between exposures — Gabor-filter dimple enhancement is documented in the adjacent patent literature [72]. Total BOM ≈\$250–300. The architecture shares multi-exposure imaging and surface-feature registration principles with the disclosures discussed in Section 7.2; that comparison establishes neither a direct product lineage nor rights clearance.

Design implication

PiTrac provides an open implementation of strobed optical capture and image-based motion estimation using commodity hardware. Its architecture can inform a radar/optical prototype, but a parts list or successful spin fit is not a measurement-error specification. Ball-spin capture and club-face impact imaging require their own visibility, calibration and validation checks; adding a camera does not automatically establish both capabilities.

Chapter 6

Commercial System Survey

Table 6.1 summarizes the sensing architecture of the major systems; the notes that follow give the technically salient details per device, with sources in the bibliography.

Table 6.1: Launch monitor architecture survey (2026). “Club source” distinguishes directly measured face data (optical) from D-plane-inverted or model-estimated face data.

System	Primary sensing	Spin method	Club data source	Impact location
TrackMan 4	Dual radar (X-band + 24 GHz) + camera (OERT)	Doppler sidebands	Radar silhouette + camera	Yes (markerless, OERT)
TrackMan iO	24 GHz radar + 4,600 fps camera	Camera + radar	Radar + camera	Yes (markerless)
FlightScope X3	Phased-array multi-freq. radar + Fusion cameras	Doppler (dielectric-lens)	Radar; face derived	No
FlightScope Mevo+	X-band 10.5 GHz phased array (+ Pro cameras)	Doppler; stickers indoors	Radar; face derived	No
Garmin R10	24 GHz, 3-receiver CW	Doppler (≥ 20 m flight) or model	Radar; face calculated	No
Garmin R50	3 high-speed cameras	Dimple imaging	Optical (fiducials)	Yes
Full Swing KIT	24 GHz CW+FMCW + 4K camera ML	Doppler + ML	Radar + ML	No
Rapsodo MLM2PRO	Radar + 2×240 fps cameras	Marked ball (RPT/RCT)	Radar; face derived	Video only
Foresight GCQuad / QuadMAX	4 cameras, IR strobe	Spherical correlation	Optical (4 fiducials)	Yes (measured)
GC3 / Launch Pro	3 cameras, IR strobe	Spherical correlation	Optical (fiducials; add-on)	Yes
GCHawk	4 cameras, ceiling	Spherical correlation	Optical	Yes
Uneekor EYE XO2	3 overhead IR cameras, 3,000+ fps	Dimple Optix	Optical, sticker-free	Yes + video
Uneekor EYE MINI	2 cameras, portable	Dimple Optix	Optical (stickers)	Yes
ProTee VX	2 overhead cameras + ML	Dimple imaging	Optical, sticker-free	Yes
SkyTrak+ / ST MAX	Cameras (ball) + dual radar (club)	Photometric	Radar; face derived	No
OpenFlight (open source)	OPS243-A 24 GHz + 2×K-LD7 + sound trigger	Doppler I/Q buffer (~ 50 – 60% detect)	Radar; no face data yet	No
PiTrac (DIY)	2 Pi GS cameras + IR strobe	Dimple registration	None yet	No

6.1 Radar-First Systems

TrackMan 4 / iO. The reference radar architecture: two synchronized radar subsystems (long-range X-band at the corners for full ball flight; higher-frequency 24 GHz at the center for club and impact), receivers sampled at 40 ksp/s to pin the impact instant, fused with an OERT camera [11, 83, 78]. Reports 27+ parameters including swing plane/direction, low point, dynamic lie, and D-plane-derived face data; requires ≥ 4.7 m of indoor throw. The iO is the indoor-optimized repackaging: 24 GHz radar, 4,600 fps club/ball camera, IR illumination, no minimum-space requirement.

FlightScope X3 / Mevo+. Phased-array Doppler (X3: multi-frequency with direct ranging; Mevo+: X-band 10.5–10.55 GHz per FCC filings [25]) with Fusion Tracking cameras on the X3 and Mevo+ Pro. Spin measured via the patented dielectric-lens phase-demodulation route (Section 7.3); metallic stickers recommended for short indoor flights. FlightScope’s 2022 win against TrackMan at the German Federal Court of Justice, after losing the 2013 EP 1 698 380 case, bookends two decades of radar-spin litigation between the two [24].

Garmin Approach R10. The instructive budget case: a 24 GHz three-receiver CW radar that directly measures only the safe primitives — ball speed, launch angles, club speed, club path — and models the rest. Spin requires ≥ 20 m of flight and >90 mph ball speed (or an RCT marked ball indoors); face angle is explicitly a calculated value at $\pm 2^\circ$ [45, 46]. Garmin’s step-up R50 abandons radar entirely for three cameras — a telling modality switch for indoor accuracy.

Full Swing KIT. The patented CW+FM CW dual-mode 24 GHz radar (Section 4.3) with an ML vision assist from its 4K camera; 16 parameters; third-party testing places it within 1–2% of TrackMan/GCQuad in most conditions [18].

Rapsodo MLM2PRO. Radar for speed/launch plus two 240 fps cameras that read printed RPT/RCT ball markers for measured spin rate and axis (claimed within 1% of reference units) — the cheapest route to *measured* spin, at the cost of proprietary balls [47].

6.2 Camera-First Systems

Foresight GCQuad / QuadMAX / GCHawk. Quadrascopic IR-strobed capture (~ 200 images/shot); spherical-correlation spin; four-dot fiducial club measurement with closure rate and measured impact location (Section 5.3) [15, 16]. Robot testing shows the class-leading spin repeatability (Chapter 9).

GC3 / Bushnell Launch Pro. Identical triscopic hardware in two brands; club data is a paid add-on tier using the same stickers [56].

Uneekor EYE XO2 / EYE MINI / ProTee VX. Overhead sticker-free club measurement (XO2, VX) versus portable sticker-based (EYE MINI); Dimple Optix markerless spin; impact video replay [92, 57].

SkyTrak+ / ST MAX. The camera-to-radar convergence case: the original photometric ball-only SkyTrak gained a dual-radar club module and ML fusion in the SkyTrak+ [64].

6.3 Open-Source Systems

OpenFlight (radar-first: OPS243-A I/Q rolling buffer + sound trigger + K-LD7 interferometric angle radars) and **PiTrac** (camera-first: strobed multi-exposure global-shutter imaging) occupy the two ends of the same spectrum the commercial market spans, at roughly 1/10th the hardware cost. Neither yet measures club face data; both have clear, patent-informed paths to it (Chapter 10).

Chapter 7

Patent Landscape

Patent publications expose proposed measurement architectures that can be hard to reconstruct from product brochures. Their technical value lies in the signal being observed, the calibration and inference steps, and the conditions under which an output is identifiable. A disclosure, a granted claim, a commercial implementation and an accuracy experiment are four different kinds of evidence. This chapter compares selected disclosures; Chapter D provides a wider catalog of document identifiers.

Read an abstract as an overview, a description as a set of disclosed embodiments, and each claim as its own combination of limitations. An example camera count, exposure time or receiver arrangement in the specification is not automatically required by every claim. Conversely, a broad title such as “spin measurement” does not mean that a patent covers every method producing that output. Company groupings below aid navigation; they do not replace assignment records or establish which product implements a particular embodiment.

7.1 TrackMan A/S (Interactive Sports Games A/S) — Fredrik Tuxen

TrackMan’s virtual-marking notice contains 47 distinct US patent numbers at the October 1, 2026 check [80]. That dated list is a route into its disclosures, not an exhaustive search of applications, foreign publications or the company’s ownership history.

Spin Frequency and Trajectory-Based Axis. US8845442B2. The disclosure describes radar spectral spacings associated with spin and a separate trajectory-based approach to spin axis [88]. Claim 1 concerns estimating spin frequency from a frequency distance in the modulated radar signal; it should not be paraphrased as requiring all the axis-inversion steps in the description. Spectral structure still needs a defensible mapping from the observed periodicity to ball rotation. Trajectory-based axis inference also depends on the aerodynamic model and the information present in the observed flight segment (Section 4.4.2 and Equation (4.5)).

Target-Referenced Measurements. US8085188B2 / US9857459B2 / US10473778B2. US8085188B2 determines direction deviation relative to an image-designated target; US9857459B2 adds a co-rotated camera/radar arrangement in its first claim. US10473778B2 claim 1 instead correlates radar trajectory data with an image feature and displays the resulting trajectory information. Related coordinate transformations appear in US8912945B2 and US10690764B2: a launch position and image-identified reference define a target-relative frame. These operations change how an observation is related to the scene; they do not by themselves add an independent observation of projectile motion. Sensor and image coordinates must be registered before a target-relative angle has a physical meaning.

A Radar View of Spin Axis. US10850179B2. Claim 1 separates the Doppler spectrum into components, determines their angular positions using a non-collinear receiver arrangement and

identifies a *projection* of the spin axis onto a plane perpendicular to the radar’s line of sight [90]. That projection is not, by itself, an unrestricted three-dimensional axis measurement. Motion compensation, receiver geometry and the distinction between a projected axis and a full axis belong in any explanation of the method. US11446546B2 claim 1 likewise identifies a projected axis; US11938375B2 claim 1 identifies an axis component from phase differences for radar frequency components. The related publications US11446546B2 and US11938375B2 therefore require their own account of the output and receiver geometry.

Tracking, Calibration and Impact. US10989791B2 and US11828867B2 concern radar/imager tracking; US11619708B2 and US12517218B2 address inter-sensor calibration; US10953303B2 describes estimating club impact information from image features. These are distinct inference problems, even when a product presents their outputs together. The similarly titled radar/image documents US10596416B2, US11697046B2 and US12128275B2 identify Topgolf Sweden AB, not TrackMan, in their publication records. In US11619708B2 claim 1, the initial camera track already uses radar range together with image angles. Agreement between that track and the radar track is therefore not a comparison of two wholly independent measurements. US12517218B2 claim 1 selects corrections by minimizing quality-weighted three-dimensional track residuals. Improved correspondence is a calibration objective; agreement alone does not establish absolute accuracy against an independent reference.

Display and Attribution. The abstract of US10315093B2 describes trajectory illustration, while its first claim concerns calibrated simultaneous camera/radar tracking. The related documents show why a shared abstract is not enough to specify a method: US10441863B2 claim 1 recalibrates after a camera field-of-view change, US11135495B2 claim 1 derives part of a striking implement’s trajectory, and US11291902B2 claim 1 includes a three-dimensional launch-vector overlay. Associating tracked balls with launch locations is described in US11086005B2. A convincing video overlay and a correct association with a player are separate requirements from accurate trajectory measurement.

Terrain-Constrained Position. US12186643B2 intersects a calibrated camera-to-ball ray with a three-dimensional terrain model and outputs that intersection as a ball position. The terrain constraint supplies depth information that the image alone lacks. When the observed ball point is above the modeled surface, the ray–surface intersection is a different point; interpreting that intersection as the ball’s unconstrained spatial position introduces a geometric error. An output labeled three-dimensional therefore still needs an account of the geometric assumptions that determined it.

7.2 Foresight Sports, WAWGD and Wintriss Disclosures

The Wintriss/WAWGD documents provide examples of image-based launch measurement and integrated monitor operation. Uneekor’s product marking notice lists several of the same numbers, and the companies announced a license agreement in 2024 [93, 4]. That evidence should not be expanded into an assertion that every Foresight or Uneekor device implements every disclosed feature.

Surface Images. US7292711B2 / US7324663B2. The disclosures describe recovering ball motion from images of surface features, including dimples and non-precision marks [37]. US7292711B2 claim 1 includes compensation for sensor misalignment relative to a calibrated orientation. US7324663B2 claim 1 describes a search over rotations, scaling and correlation scores, together

with coordinate and alignment calculations. Here, “markerless” means that prescribed fiducials need not be applied; it does not mean that the measurement needs no resolvable texture, lighting control or calibration. Correlation quality and rotation ambiguity must be evaluated on the actual images.

Trigger and Placement. US7497780B2 / US7641565B2. The former integrates trigger-zone monitoring, capture, parameter calculation and output. The latter detects ball placement using images and physical attributes. Reliable triggering determines which frames reach a spin estimator; it is part of the measurement chain, rather than merely a display convenience.

Club Motion. US8951138B2. This disclosure addresses club path and face orientation around impact. Its inclusion supports discussion of club measurement methods, not a blanket assertion that four cameras or reflective face dots are universally protected, or that one patent identifies a particular commercial club-data system.

7.3 FlightScope / EDH — Henri Johnson

Phase-Modulated Spin Signals. US9868044B2. Claim 1 derives spin from the period of a demodulated radar component whose portions correspond to apparent speeds above and below a nominal speed [34]. The disclosure’s dielectric-lens explanation and surface-feature examples should be distinguished from that claim’s signal-processing requirements. Symmetry can cause a feature pattern to repeat more than once per revolution; a measured modulation frequency therefore needs interpretation before it becomes a spin rate.

Receiver-Pair Timing. US10775492B2. Claim 1 uses demodulated Doppler signals from receiver pairs in perpendicular planes, their relative time delays and receiver separations to calculate an axis relative to a receiver plane [33]. This supplies rotation-related observations without first fitting a long curved trajectory. It does not establish unconditional indoor accuracy: signal quality, delay estimation, geometry and the stated axis convention remain part of the result. A ratio of delays also needs careful treatment near a vanishing denominator and when resolving angle quadrants; a bare one-argument arctangent is not a complete implementation.

Camera/Radar Tracking. US10338209B2. The document describes calibrated simultaneous tracking and combining camera and radar information [32]. Claim 1 specifically includes using radar data to interpolate a three-dimensional camera trajectory when one sensor fails to supply usable measurements. Recovery through such a gap is an inference step whose uncertainty must be tested, not a second independent observation of the missing interval.

7.4 Acushnet (Titleist) — Optical Measurement Architectures

These documents illustrate several ways to assemble an optical launch monitor [23, 22, 38]. They do not reduce to one fixed camera-and-marker recipe.

Marked Club and Ball. US5501463A. Claim 1 uses at least two cameras and repeated exposures of contrasting areas on both the striking instrument and the object. Image patterns support estimation of club path and orientation. The conversion from marker positions to a club-face quantity requires a defined relationship between those markers and the club geometry.

Launch Conditions to Trajectory. US6500073B1. Claim 1 obtains positions and orientations from images at different times, calculates launch conditions, then calculates a trajectory. Measured initial conditions and the resulting modeled flight must be distinguished: a predicted landing point is not an observed landing point.

Separate Club and Ball Capture. US6758759B2. The first claim places club and ball cameras in vertically separated planes and derives their motion data from repeated images. The minimum in that claim is one camera for each task; describing the entire patent as requiring two stereo pairs would confuse an embodiment with the claim.

Integrated Optical Hardware. US7143639B2. Claim 1 specifies a housing layout with a club camera, at least two ball cameras, illumination, triggering and a teeing aid, arranged for use by both handednesses through rotation of the apparatus. The first claim does not require four cameras.

Three-Dimensional Image Generation. US10668350B2. The disclosure discusses stereo and light-field approaches. Claim 1 specifically includes a light-field camera that captures light intensity and ray direction, followed by reconstruction and kinematic processing. Example frame rates or exposures in a disclosure are design proposals; they do not demonstrate a product's achieved measurement error.

7.5 United States Golf Association — Aerodynamic Experiments

The United States Golf Association's US6186002B1 belongs outside the Acushnet grouping. It describes controlled launches and timed light-screen crossings for aerodynamic coefficient fitting (Chapter D) [43]. Its experimental setup matters: an arbitrary short trajectory need not contain enough information to separate initial spin, wind and uncertain aerodynamic coefficients.

7.6 Korean Ecosystem: Creatz/Uneekor and Golfzon

Uneekor's marking notice connects specific products with listed patent numbers [93]. The Creatz disclosures include US10247553B2, which describes a start sensor for identifying ball placement and starting movement, and US12008770B2, which concerns dimple-based spin estimation. A product's markerless-spin label does not specify its entire algorithm or establish performance across every ball surface.

Creatz's US11191998B2 makes the distinction between observation and inference particularly clear. Claim 1 uses speed- or angle-related quantities to estimate spin when image marks cannot supply it; when mark-based calculation is possible, it also uses such an estimate to correct that calculation. This is more than a fallback for missing observations. The reported spin can depend on both image evidence and a relationship inferred from other ball or club quantities. Validation should distinguish these operating modes and test their errors separately; a plausible corrected value does not establish an independent measurement of rotation.

Golfzon's US12002222B2 provides a different example of this dependence. Claim 1 obtains dynamic loft and backspin through a reference database using observed club/ball motion parameters, then calculates spin-axis and side-spin quantities from motion vectors and specified relationships. These inferred outputs must not be used as independent evidence that the assumed impact relationships hold for a particular shot.

Golfzon’s US9242158B2 describes beginning the displayed flight with a first set of ball information and updating it when a second set arrives [99]. This separates feedback latency from completion of the measurement pipeline. Timing examples in a description are not measured latency guarantees. Readers comparing monitors should ask both when an output appears and when the final parameters become available.

7.7 Timing, Association and Environmental Inference

Several disclosures show why a measurement pipeline needs more than a list of sensors. Topgolf’s US11335013B2 interpolates timestamped image positions to a common time before combining them with another sensor. Golfzon’s US10045008B2 describes alternating camera capture with estimated intermediate images. These methods synthesize information at a requested time; they do not create an additional exposure at that time. Their interpretation therefore depends on the motion between samples, particularly across impact or bounce, where an interpolation rule must account for a rapid change in velocity.

Object association is a separate inference. Topgolf’s US11644562B2 extrapolates a trajectory backward and combines position and angular error estimates before assigning a launch origin; when its criterion is unmet, it waits for more observations. Foresight’s US10639537B2 uses launch-monitor predictions to choose among observed flight and landing records. A correctly reconstructed flight assigned to the wrong strike still produces incorrect feedback to the golfer. Moreover, agreement with a prediction used to select that flight is partly a selection effect, rather than wholly independent validation of the prediction.

Environmental quantities can also be inferred rather than directly sensed. Topgolf’s US12298326B2 compares model and observed accelerations and combines wind estimates from multiple ball trajectories. Because the comparison includes a flight model, aerodynamic-model error can affect the inferred wind; adding trajectories does not automatically remove a shared model error. FlightScope’s US11573082B2 instead maps temperature, pressure and humidity to an effective altitude by matching air density to a reference environment. Equal density does not establish equal wind or every other aerodynamic condition, so this equivalent altitude is a defined environmental summary rather than a complete replacement for the atmosphere in a trajectory calculation.

These dependencies matter when a launch monitor is used to test a swing hypothesis. Record which data were observed, which were interpolated, how the shot was associated with a player and which environmental assumptions entered the calculation. An apparent change in inferred spin or predicted distance can otherwise be attributed to the golfer when it partly reflects a change in capture, association or modeling.

7.8 Technical Research Map and Rights Boundaries

The following map identifies engineering questions to investigate. It replaces a technique-wide “free to use” classification: the age or expiration of one document cannot establish clearance for every implementation bearing the same technique name. The USPTO describes a patent as a right to exclude, not permission to practice an invention. Term cannot be computed indiscriminately as twenty years from any date labeled “priority”; the applicable filing basis and other term conditions matter.¹ A design-specific rights review requires the relevant claims, jurisdictions and current records. This technical catalog does not supply that determination.

¹USPTO, *Patent Essentials*, <https://www.uspto.gov/patents/basics/essentials>.

Table 7.1: Selected Measurement Methods and Their Validation Questions

Method	Example Documents	Question to Test
Surface-image spin	US7292711B2; US7324663B2	Are texture, exposure and rotation matching sufficient to resolve ambiguity?
Marked club/ball images	US5501463A; US6758759B2	Are calibration and marker-to-face geometry known at the reported time?
Radar spin periodicity	US8845442B2; US9868044B2	Which spectral or temporal repeat corresponds to one revolution?
Radar axis information	US10850179B2; US10775492B2	Is the result a projection or a full axis, and in which coordinate frame?
Camera/radar fusion	US10338209B2; US10989791B2	Are clocks, coordinates, association and missing-data uncertainty controlled?
Trajectory-informed spin	US12544624B2	How strongly does the result depend on club probabilities and the flight model?
Placement and triggering	US7641565B2; US10247553B2	Does detection reliably capture the interval needed for the requested output?
Staged display	US9242158B2	Which values are provisional, and when does the displayed trajectory change?

Key point

A launch monitor is a chain of observations and inferences. Radial speed, image displacement, surface rotation, launch conditions and predicted flight occupy different places in that chain. Combining sensors can add information, but only after timing, coordinates and object identity agree; it does not turn repeated use of the same data into independent evidence.

For example, Topgolf's US12544624B2 uses trajectory observations, spin candidates and probabilities associated with a likely club. That approach differs from tracking rotating surface features. A plausible spin value may partly reflect the prior model, so evaluating both methods requires experiments that expose their different ambiguities.

When using these outputs to investigate a swing, retain the measurement frame, time interval, calibration and model assumptions. Ball launch conditions and club-delivery kinematics constrain terminal states; they alone do not identify the golfer's joint torques, force history or unique movement strategy. Technical rigor means carrying those information limits through the argument, rather than letting a precise display imply a uniquely determined cause.

Chapter 8

Ball Flight Models and Trajectory Estimation

Both sensing families depend on an aerodynamic model: cameras integrate it forward from measured launch to get carry; radars fit it to partial trajectories to extract spin axis and to extrapolate indoor flights.

8.1 Equations of Motion

With air density ρ , ball radius $R = 21.34\text{ mm}$, mass $m = 45.93\text{ g}$, cross-section $A = \pi R^2$, and airspeed $\mathbf{v}_a = \mathbf{v} - \mathbf{v}_{\text{wind}}$:

$$m \frac{d\mathbf{v}}{dt} = -\frac{1}{2}\rho AC_D \|\mathbf{v}_a\| \mathbf{v}_a + \frac{1}{2}\rho AC_L \|\mathbf{v}_a\|^2 (\hat{\boldsymbol{\omega}} \times \hat{\mathbf{v}}_a) + m\mathbf{g}, \quad (8.1)$$

with the drag and lift coefficients functions of Reynolds number $\text{Re} = 2R\|\mathbf{v}_a\|/\nu$ and spin ratio $S = R\omega/\|\mathbf{v}_a\|$. Fourth-order Runge–Kutta integration is ample; carry is evaluated where the trajectory returns to launch elevation. Tilting the spin axis by θ rotates the Magnus force off vertical, giving lateral acceleration $(F_M/m)\sin\theta$ — the mechanism behind the 0.7%-per-degree side-curve rule and Equation (2.4).

8.2 Aerodynamic Coefficient Data

Bearman & Harvey (1976) [2]. The canonical wind-tunnel dataset on spinning golf-ball models across the flight envelope. Dimples drop the critical Reynolds number to $\sim 5 \times 10^4$; post-critical $C_D \approx 0.25$ is nearly Re-independent; C_L rises with spin ratio from ≈ 0.08 to 0.25 over $S \approx 0.02$ –0.3; hexagonal dimples outperform round ones.

Smits & Smith (1994) [65]. The parameterized model most widely used in simulators:

$$C_D = C_{D1} + C_{D2} S + C_{D3} \sin(\pi \frac{\text{Re}-A_1}{A_2}), \quad C_L = C_{L1} S^{0.4}, \quad (8.2)$$

with $C_{D1} = 0.24$, $C_{D2} = 0.18$, $C_{D3} = 0.06$, $A_1 = 9 \times 10^4$, $A_2 = 2 \times 10^5$, $C_{L1} \approx 0.54$, plus a spin-decay law with time constant $\approx 24\text{ s}$ at 100 mph (roughly 4%/s early in flight).

Quintavalla / USGA Indoor Test Range (2002) [58]. Six-term polynomial C_D/C_L models in Re and S fitted from trajectory photography on the USGA ITR; captures the low-speed end-of-flight regime better than wind tunnels; the basis of USGA Overall Distance Standard conformance testing. The companion method patent US6186002 [43] — determining coefficients from measured trajectories — is the template for calibrating an open model against real flights.

Design implication

An implementation should ship Smits–Smith (Equation (8.2)) with spin decay as the default flight model, structured so a Quintavalla-style six-term fit can drop in, and calibrate against measured outdoor trajectories (or MLM2PRO reference data) using the US6186002 trajectory-fitting approach. Carry disagreements between simulators are dominated by model choice, not launch measurement — version the model and record it with every shot log.

8.3 Trajectory Estimation and Filtering

The estimation core of a radar launch monitor is a nonlinear filtering problem. State $\mathbf{x} = (\mathbf{p}, \mathbf{v}, S, \theta_{\text{axis}})$; process model = Equation (8.1); measurement models: radar $h(\mathbf{x}) = (r, \text{az}, \text{el}, \dot{r})$ with $\dot{r} = \mathbf{v} \cdot \hat{\mathbf{p}}$, camera $h(\mathbf{x}) = \text{pixel projections}$. An extended (or unscented) Kalman filter runs the standard recursion; launch parameters are then obtained by *smoothing and back-extrapolation* — fit the entire observed arc and evaluate the state at the moment of face separation, which is far more robust than differencing the first noisy fixes. Including θ_{axis} in the state makes spin-axis-from-curvature (Section 4.4.3) fall out of the filter naturally, and per-measurement confidence weighting is the clean way to fuse heterogeneous sensors (OPS243-A speed, K-LD7 angles, future camera fixes).

Design implication

A two-module radar design correlates angle-radar bursts with the CW impact timestamp and reads angles from single detections. Migrating to a short EKF smoother over the full K-LD7 ring-buffer burst — even 10–20 detections over 50 ms — would use all available data, reject outlier bins, and yield launch angles with quantified covariance. The same filter skeleton later absorbs camera measurements unchanged.

8.4 Indoor Extrapolation and Its Errors

Indoors, every system integrates Equation (8.1) from launch conditions. Error propagation is dominated by spin uncertainty: at driver speeds, ± 300 rpm maps to roughly ± 4 – 6 yd of carry and ± 1 yd of side; a $\pm 2^\circ$ spin-axis error at 2,500 rpm maps to ± 3 – 4 yd of side at 250 yd carry. This is why the accuracy literature (Chapter 9) finds spin to be the fragile channel indoors for radar, and why camera systems — which measure spin directly — win the indoor comparison structurally.

Chapter 9

Accuracy: The Independent Evidence

9.1 Peer-Reviewed Validation

Leach, Forrester, Mears & Roberts (2017) [39] remains the key criterion study: 240 shots (driver, 7-iron, wedge) measured simultaneously by a TrackMan Pro IIIe, a Foresight GC2+HMT, and a four-camera 5,400 fps optical reference. Findings: ball parameters agreed well on both devices (TrackMan clubhead-speed median difference -0.4 mph; ball speed $+0.2$ mph; launch angle 0.0°), but **club parameters were materially worse for both** — the authors endorse ball data for research use and advise caution on club data. This is the empirical face of the directness hierarchy of Section 2.3: what is measured agrees; what is derived diverges.

TrackMan 4 indoor reliability (J. Sports Sciences, 2024) [100]: within- and between-session reliability in high-level golfers indoors — ICC 0.99 for club speed, 0.97–0.99 for ball speed, but **spin-rate ICC as low as 0.02–0.60**: even the reference radar’s indoor spin channel is fragile when flight is truncated.

A 2025 Mevo+ vs. TrackMan 4 indoor agreement study exists [1] (abstract-level access only at review time), extending the same pattern down-market.

9.2 Robot and Industry Testing

Golf Laboratories robot testing (reported via Foresight and third parties) puts GCQuad center-strike spin standard deviation at ≈ 82 rpm versus ≈ 175 rpm for TrackMan 4 — the photometric spin advantage in its clearest form [26]. MyGolfSpy’s indoor comparison against a GCQuad reference found the camera-assisted MLM2PRO among the tightest budget units for launch, spin, and carry, with radar-only units (R10, original Mevo) trailing indoors [48]. Manufacturer-quoted specs bracket the market: ± 1 mph ball speed and $\pm 1^\circ$ launch angles are common claims; club-face claims ($\pm 2^\circ$, “calculated”) are visibly weaker.

9.3 What Drives Inter-Device Disagreement

Synthesizing the validation literature and the architecture analysis:

1. **Reference-point differences** in club speed (geometric center vs. fastest return) — several mph of systematic spread.
2. **Derived face data**: D-plane inversion amplifies launch-direction bias by $\sim 1.15\times$ and cannot see gear effect, so radar face angle diverges from optical face angle most on off-center strikes.
3. **Indoor spin**: sideband SNR collapses on short flights and clean balls; systems silently switch to estimation, and estimated spin feeds the carry model.

4. **Flight-model differences:** identical launch conditions produce different simulated carries across vendors; this is a modeling disagreement, not a measurement one.
5. **Alignment:** a unit misaligned to the target line biases path, face, and launch direction coherently — the cheapest error to fix and the most common in practice.

Design implication

For validation against a consumer unit such as the MLM2PRO (a common reference instrument): compare ball speed and launch angles directly; compare spin only on RPT/RCT marked balls where the MLM2PRO's measurement is camera-based; expect club-speed offsets from reference-point differences and calibrate a per-club correction rather than chasing agreement; and log raw I/Q captures so spin-detection improvements can be replayed against historical shots.

Chapter 10

Design Guidance for Implementers

This chapter distills the review into design guidance, organised by what a given sensing architecture can and cannot deliver. It is written for anyone building a launch monitor, and equally for anyone evaluating one: the same reasoning that tells an engineer which parameters are reachable tells a buyer which reported numbers deserve trust.

The baseline throughout is a **minimal radar architecture** — a single continuous-wave Doppler module for speed, one or two interferometric angle-radar modules for direction, a hardware impact trigger, and an embedded host. Representative parts are named where they are useful (the OmniPreSense OPS243-A at 24 GHz, the RFbeam K-LD7, a Raspberry Pi class host), but nothing here depends on those specific choices. This configuration is a minimal but honest instance of the commercial radar architecture, and it is the cheapest starting point that measures anything directly.

10.1 Ball Data

1. **Ball speed** is the strongest channel in any radar design: the Doppler line is unambiguous, and $\pm 0.5\%$ class accuracy from a commodity module matches commercial practice. Apply the aspect-angle (cosine) correction using the measured launch angles — at 3–5 ft behind the tee with a driver launch of 12° the radial underestimate is small but *systematic*, and systematic errors are the ones that survive averaging.
2. **Launch angles**: treat angle-radar bursts as a short trajectory, not a single detection. An EKF smoother over the ring buffer (Section 8.3) with back-extrapolation to the impact timestamp is the single highest-leverage software upgrade for angle quality, and it costs nothing in hardware.
3. **Spin rate** is where radar earns its reputation for inconsistency. A $\sim 50\text{--}60\%$ detection rate from I/Q sideband analysis is consistent with the physics rather than evidence of a bug: sideband SNR depends on ball-surface asymmetry and observation time (Section 4.4.2). Improvements in order of cost: longer observation windows (later trigger cutoff); cepstrum or harmonic-product comb estimation with equal-spacing qualification; marked-ball guidance for indoor use; and honest fallback — report estimated spin from club type, speed and loft priors, clearly flagged, which is what Garmin does and documents. *Disclosure reference*: US8845442 describes radar spin processing; the technical map in Section 7.8 does not determine clearance or a technique-wide expiry date.
4. **Spin axis**: short flight segments may provide too little trajectory information to separate axis, aerodynamic coefficients and launch-condition errors reliably. Rotation-related observations from receiver geometry provide another disclosed route (Section 7.3), but require suitable hardware and validated signal processing. Optical rotation estimates and explicitly labeled impact-model estimates are further options; their observation requirements and error sources differ.

10.2 Club Data

1. **Club speed:** define and document the reference point — this is the single most consequential and most neglected decision in the whole design (Section 2.1.1). A CW module sees a smear of head and shaft returns; gating the pre-impact spectrum and taking a fixed percentile of the velocity distribution, rather than the maximum, approximates a stable reference and avoids the toe-speed inflation that plagues naive processors (Section 4.5). Validate smash factor against the loft-appropriate ceiling (Section 3.2) and flag violations rather than displaying them.
2. **Club path** and **attack angle** from angle radar are legitimate direct measurements — the same primitives a consumer radar unit measures. Alignment calibration dominates their accuracy, and no amount of signal processing recovers a misaimed sensor.
3. **Face angle:** the D-plane inversion (Equation (4.8)) with the loft-dependent weight (Equation (3.4)) is exactly what radar-only commercial units report. Implement it — but label it *derived*, propagate its error (a 1.32× amplification of launch-direction bias at the measured weight; see the caution in Section 3.1.1), and suppress it on detected off-centre strikes once impact location is available. The D-plane forward model doubles as a simulator’s launch generator, so one well-tested module serves both directions.
4. **Impact location:** club and ball imaging offers a concrete route to locating contact relative to the face. The Acushnet and Wintriss disclosures (Sections 7.2 and 7.4) illustrate measurement architectures, rather than complete validated implementations or blanket rights clearance. Face fiducials can constrain orientation through calibrated image geometry and a known marker-to-face relationship. Camera count alone does not establish three-dimensional observability, visibility at impact or achieved accuracy.

10.3 Capability Tiers

The following tiers are cumulative. Each is a coherent product in its own right, and each is defined by what it moves from derived to measured rather than by a parts list.

1. **Tier 1 — radar only.** EKF smoothing, comb-based spin with honest fallback, D-plane-derived face data with provenance flags, smash-factor sanity gates, and a documented alignment-calibration procedure. This delivers the consumer-radar feature set. Everything club-face-related is inferred.
2. **Tier 2 — add optical spin, then impact imaging.** One or two global-shutter cameras with an IR strobe, at modest incremental cost. Calibrated image sequences can support launch-angle and surface-rotation estimation; impact-location capture additionally needs a suitable view of the club and ball. Radar may contribute triggering, speed and trajectory observations, depending on the sensor arrangement. The disclosures in Chapter 7 supply design comparisons, not a guarantee that this combination is accurate or cleared for a particular implementation.
3. **Tier 3 — true fusion.** A single EKF consuming radar speed, radar angles and camera fixes with per-sensor covariances; a flight model per Chapter 8 with versioned coefficients; and a validation protocol per Chapter 9. The versioning matters more than it sounds: Chapter 8

shows that a coefficient difference of 0.01 in C_D is worth roughly eight yards, so an unversioned model change is a silent recalibration of every number the device has ever reported.

4. **Tier 4 — measured club delivery.** An imaging radar with custom chirp firmware feeding the screw-theoretic rigid-body estimator of Chapter E: per-detection Doppler rows solved for the club’s twist, smoothed on $SE(3)$, and projected into club speed at a declared reference point, measured path and attack angle, closure rate, and an ISA-defined swing plane. This moves path and attack angle from *derived* to *measured* in Table 2.3. Face angle and impact location remain assigned to the optical module in this proposed architecture; the allocation is a design choice, not proof that every other sensing approach is impossible.

10.4 Reporting Honesty as a Design Feature

The clearest lesson of this review is not about sensors at all.

Commercial marketing blurs the measured/derived boundary, and the independent validation literature repeatedly punishes the derived quantities: clubhead velocity met research-grade tolerance on 54% and 29% of shots for the two devices ever tested against a traceable optical benchmark, and club orientation data was returned on only 62% of shots overall — 19% for a utility wedge (Chapter 9). None of that appears on a specification sheet.

An instrument can therefore differentiate itself by doing the opposite: tagging every reported parameter with its provenance (measured, derived, or estimated), its uncertainty, and the model version used, and reporting its own per-shot success rate rather than only its best-case tolerance. Table 2.3 is effectively the schema for that tagging.

Two vendors already demonstrate that this is commercially survivable rather than suicidal. Garmin publishes an explicit measured-versus-calculated split with tolerances on each side, and states outright that its face angle is algorithmic. TrackMan publishes the reference-point discrepancy between its own quantities and warns that numbers from different methodologies “aren’t comparable.” Both remain market leaders in their segments. The honest disclosure did not cost them anything, and it is the closest thing this industry has to a standard worth adopting.

Chapter 11

Governed Analytics and Validation Program

The distinction between a useful analytics platform and a scientific vendor comparison is the evidence design. A large collection of launch records can support exploratory model checking without supporting the stronger claim that one device disagrees with another. At the revisions pinned below, the repositories associated with this review use a two-release program with a versioned data contract, explicit use eligibility, and fail-closed statistics. The program is tracked by the public Tools program epic. UpstreamDrift is the canonical generic contract and evidence-envelope authority. Tools owns the current specialized grouped estimators: Python is the desktop calculation authority and React is a contract-tested browser twin. Those grouped operations are not yet UpstreamDrift API operations, so that boundary is published rather than obscured by a cross-service parity claim.

11.1 Qualified Corpus Snapshot

The controlled authority snapshot contains 261,666 rows from 27 traceable sources. Size alone is misleading. Only 13,855 rows contain finite, non-imputed values for all five primary launch inputs (ball speed, launch angle, launch direction, spin rate, and spin axis). Before the per-source minimum-size gate, 13,647 rows also contain carry, 13,532 lateral outcome, 9,850 descent angle, and 9,283 flight time. The strict model cohort contains 13,843 rows from 15 source families with complete launch inputs and at least one supported observed outcome. Each outcome comparison then uses its own eligible subset; 13,843 is not the sample size for every metric. Eligibility is evaluated by source, metric, provenance, and intended use; a blank field is represented as *unavailable*, never silently filled merely to increase sample size.

The largest source is a 236,590-row ShotLink-derived table. It has no complete five-input launch rows and no observed carry values. Its rights and transformation lineage also require separate approval. It is therefore quarantined: the source is **not eligible for vendor-model training**, public redistribution, or vendor-performance claims. It may be retained internally for provenance review and for analyses that are independently shown to match its permitted use. This rule prevents a large but unsuitable table from dominating the apparent evidence base.

At the present qualification gate, no vendor-labelled surrogate is currently eligible for production training. The corpus contains 11,699 TrackMan-labelled rows and 9,298 strict launch-input rows, but it lacks a trusted repeating player or session grouping. Foresight has four rows (two strict); FlightScope has 2,794 rows but no strict five-input rows. The historical TrackMan surrogate used unique shot identifiers as partitions, which cannot protect against player, session, or source leakage; it is retained for audit with status `retired_non_group_safe` and cannot be loaded, queried, or retrained. A future model that passes the group-safe gate would be described as *vendor-comparable on its qualified source*, not as a reproduction or certification of proprietary vendor software.

Key point

Every displayed statistic carries its source identity, row-selection rule, units, method version, and backing row references. An unavailable result is a valid result: it records why the requested inference is not supported.

11.2 Release A: Qualified Analytics Platform

Release A delivers the professional analysis surface on data that passes the declared gate. Its scope includes unit-aware scatter and distribution views, model residuals, arbitrary variable relationships, within-player and between-player covariance, session trends, uncertainty, exportable plots, and reproducible project files. Player-level analysis requires an explicit player identity column. Identity is never inferred from session, club, row order, filename, or directory layout; missing and whitespace-only identities are excluded and reported.

UpstreamDrift’s versioned contract returns estimates, uncertainty, warnings, source lineage, backing-row references, and machine-readable unavailable states for its registered generic analyses. Tools supplies PyQt and React/Vite views with parity in variable choices, units, formulas, backing-data export, persistence, and explanatory text. The specialized grouped estimators for covariation and longitudinal synthesis are currently released within Tools, with Python as the desktop authority and TypeScript as a tested browser twin; they are not yet UpstreamDrift API operations. This bounded duplication is a tracked architectural seam, not evidence that two independent implementations are automatically equivalent.

Exploratory all-pairs scans report multiplicity warnings; a warning does not control a false-positive rate. Within-player analysis separates raw pooled association, player-mean-centred association, between-player association, and per-player estimates; these quantities answer different questions and must not be substituted for one another. Correlation and principal-component loadings are descriptive, not causal. Predictive work uses grouped splits whenever a trusted player or session identity exists and otherwise states that leakage-resistant grouping is unavailable. The split must match the intended generalization: holding out sessions from known players does not test prediction for previously unseen players or sources.

Strokes gained is similarly gated. A result labelled *strokes gained* requires a cited baseline table, a declared lie and distance state, and a reproducible mapping from shot outcome to expected strokes. A distance-only or target-error score without that backing is labelled a *performance proxy*; it must not borrow the strokes-gained name.

The canonical scoring contract requires exact lie, context, target, and distance states before and after the shot. Missing states, incomplete retained rows, and queries outside baseline support fail closed. No expected-strokes baseline is bundled with the public application. A baseline’s declared source URL, licence, version, and digest preserve provenance; that declaration does not independently endorse its methodology, legal suitability, or relevance to a particular player population. The distance/target performance proxy remains a separate yard-based dispersion measure whose machine-readable flag is `is_strokes_gained=false`.

11.3 Qualified Model-Comparison Results

The Release A campaign evaluated seven open flight-model configurations on the 13,843-row strict cohort, producing 96,901 predictions with no execution failures. Its primary estimands are source-stratified error, bias, association, and residual relationships. Pooled metrics are retained only as

descriptive summaries because source composition, device, venue, ball, and acquisition conditions are confounded.

For the Blackmore TrackMan-labelled carry cohort ($n = 8,860$), the best tested configuration was the Waterloo/Penner implementation: carry RMSE 12.256 m, mean error -4.093 m, and strong linear association with the reported outcome. These are agreement statistics against the source’s reported carry, not an absolute-accuracy result and not evidence that the proprietary TrackMan equations have been identified. For context, the best tested carry configuration on one Garmin R10 source ($n = 1,541$) had RMSE 7.150 m and bias -4.722 m, while one Garmin R50 source ($n = 255$) had RMSE 10.238 m and bias $+6.554$ m. The sign change is one reason a pooled vendor ranking would be scientifically unsafe. Here “best tested” means the lowest carry RMSE among the seven configurations on that source’s evaluation rows. Selecting that minimum is not a new held-out evaluation, and comparisons between these unpaired sources cannot isolate a vendor effect.

The content-addressed calculation record is the private campaign’s `results/v2/model/model_campaign_manifest.json`. It binds the cohort, predictions, source metrics, pooled descriptive metrics, residual-correlation table, configuration, and source qualification outputs by SHA-256. The companion `multisource_v2_model_report.md` states row selection and limitations in human-readable form. Restricted rows remain in the private authority; the public paper reports only qualified aggregates.

The qualified snapshot is pinned to a private authority commit and three digests verifiable against the corresponding files by an authorized reader:

```
private merge: 8cd8ad04bf2904eedd0d8f10d2aa202e437e91fd
qualification:
679856edb290111a0106c0cbcbdb2b673f581fd6b0026409c4d643565b330709a
model campaign:
b70935fb4209b3f3aa18c3129ae948c4e20da74536af4d88433e5f0875960ca7
capability manifest digest:
1906d19fcace3284ae99d9dd8de213a0e2dabe8c062e4d63edc06c98f7eaf92e
```

These identifiers bind the reported aggregates without exposing restricted shot rows. A matching digest establishes file identity; it does not validate the measurements, selection rules, or statistical conclusions.

The associated software and public-boundary revisions are pinned separately:

```
public data facade: 70feeb4889ef4d030bdb426bd7ecb465c36ba41b
generic UpstreamDrift contract v2: 5ea0d08821ee8a1cacb93d22239abddee4813fca
Tools grouped-analytics release: 08b4b013d8f58feb0a788fc67add29f64750da23
canonical source-backed SG contract: fb4e6e41ac4980309e32dacceb957f4da02616b3
Tools canonical SG integration: a7b6dc437b45857e27cd07cccb56ff665826e342
Tools visual approval: 10d7f6fc38d27dd04324160090a7290f46d0cfd4
approved launch-monitor PNG SHA-256:
6699129037d0adf8152e73bdae3fc2b75a2e15bfb16e25a4b3cfcec2448ac00e
```

The public facade contains capability metadata and locks, not restricted rows. The older Tools revision remains the authority for the specialized grouped estimators, while the older UpstreamDrift revision remains the generic v2 envelope and claim-discipline authority. The newer UpstreamDrift revision owns the canonical source-backed scoring contract, and the newer Tools revision is its PyQt/React consumer. The visual approval covers presentation and accessibility, not statistical correctness or baseline validity. It also does not convert an unbundled or user-selected expected-strokes table into endorsed scientific evidence.

11.4 Release B: Paired-Device Scientific Validation

Release B’s scientific claims require a protocol fixed before confirmatory data collection, followed by execution and analysis under that protocol. The pinned bundle is a *structural template*, not a completed preregistration. The ball specification, numeric speed bands, device/reference set, placement, and calibration procedures still require a documented freeze before the pilot. Pilot-informed changes must be distinguished from confirmatory decisions, with the final analysis plan registered before inspecting confirmatory differences. The software bundle and its synthetic fixture establish an executable workflow, not completion of those scientific decisions.

The broader intended program covers speed, loft, spin, launch direction, impact location, representative mishits, and indoor/outdoor conditions. Record device model and firmware, ball and club, environmental state, alignment, player or robot identity, shot identity, and measured-versus-estimated status. Firmware changes form new strata rather than being pooled invisibly. The current template covers only three robot-center, outdoor club/speed cells: driver, 7-iron, and wedge. Even a completed study in those cells would not establish indoor performance, mishit robustness, or generalization to human players.

11.4.1 Pairing and Reference Uncertainty

Each paired comparison must concern the same physical shot and the same *measurand*, the quantity intended to be measured. For example, horizontal carry to first ground contact in a declared frame differs from a model’s carry normalized to standard weather, even if both outputs are labelled carry. A traceable reference requires an uncertainty statement, not merely a passed-calibration flag; calibration and repeatability have specific metrological meanings [35]. Alignment, time registration, environmental corrections, and the distinction between measured and estimated outputs remain part of the comparison. A common trigger timestamp associates records; it does not demonstrate zero acquisition lag or negligible synchronization uncertainty.

An additive model shows what pairing can and cannot remove. For shot s , let X_s be the shared physical quantity, Y_{ds} the output of device d , and R_s the reference output. Within a declared condition, write constant biases as b_d, b_R and zero-mean random errors as e_{ds}, e_{Rs} :

$$Y_{ds} = X_s + b_d + e_{ds}, \quad R_s = X_s + b_R + e_{Rs}, \quad (11.1)$$

$$D_{ds} := Y_{ds} - R_s = b_d - b_R + e_{ds} - e_{Rs}. \quad (11.2)$$

The common X_s cancels, but reference bias and uncertainty do not. Suppressing the shot index for the random variables across shots within this condition,

$$\text{Var}(D_d) = \text{Var}(e_d) + \text{Var}(e_R) - 2\text{Cov}(e_d, e_R). \quad (11.3)$$

Shared calibration or environmental corrections can therefore change apparent agreement through error covariance. As a constructed counterexample, two devices with the same 5 m offset agree perfectly while both differ from the physical quantity by 5 m. This is a mathematical example, not a measured vendor error. Across golf shots, dispersion of Y_{ds} also includes variation in X_s and any covariance between the physical outcome and measurement error. It cannot automatically be attributed to golfer inconsistency, sensor noise, or a motor-control mechanism.

11.4.2 Agreement, Repeatability, and Repeated Shots

For independent paired differences from an approximately normal distribution with constant mean and variance, descriptive 95% limits of agreement are

$$\bar{D} \pm 1.96s_D, \quad (11.4)$$

where $\bar{D}$ and s_D are the sample mean and sample standard deviation of the differences. These limits concern individual paired differences, not a confidence interval for mean bias; each estimated limit also has sampling uncertainty. Repeated observations of changing quantities and replicates of a constant quantity require different variance decompositions [3]. Condition-dependent bias or spread calls for a prespecified conditional model or justified transformation and examination of its residual assumptions. Correlation alone cannot establish agreement, and a nonsignificant mean difference cannot establish acceptable error: practical bounds and precision requirements must be specified for the intended use.

Within-device repeatability concerns repeated measurements under specified conditions [35]. For two independent normal errors from one instrument with within-device standard deviation σ_w , measured at the same underlying quantity, the standard deviation of their difference is $\sqrt{2}\sigma_w$. The corresponding 95% absolute-difference threshold is $1.96\sqrt{2}\sigma_w$. A device-reference difference standard deviation does not separately identify either instrument's σ_w . Repeated robot shots can themselves have different physical outcomes, so their raw dispersion is not automatically instrument repeatability.

The pinned descriptive analyzer computes $1.96s_D$ under the field name `repeatability_coefficient`; here it is an *agreement half-width*, not an identified within-device repeatability coefficient. The analyzer's bootstrap resamples individual pairs to estimate uncertainty in mean bias; it does not implement the proposed hierarchical analysis or confidence intervals for both agreement limits. Its pooled device summaries must not be mistaken for the completed condition-specific confirmatory analysis.

To illustrate the effect of clustering, suppose difference j in block b follows $D_{bj} = \mu + U_b + E_{bj}$. Let μ be the population mean difference, independent zero-mean block effects U_b have variance τ^2 , and mutually independent zero-mean residuals E_{bj} have variance σ^2 , also independent of all block effects. For B independent blocks of m shots each,

$$\text{Var}(\bar{D}) = \frac{\tau^2}{B} + \frac{\sigma^2}{Bm}. \quad (11.5)$$

Treating all Bm shots as independent would instead give $(\tau^2 + \sigma^2)/(Bm)$, understating uncertainty when $m > 1$ and $\tau^2 > 0$. This illustrative model is not a fit to the campaign. Unequal blocks, player effects, serial dependence, and comparisons sharing a reference require the model and resampling scheme appropriate to that design, preserving the shot pairing and relevant clusters.

11.4.3 Sample Planning and the Completion Gate

The template's planning arithmetic uses one two-sided paired-mean test with independent, identically distributed normal differences:

$$n \approx \left[\frac{(z_{1-\alpha/2} + z_{1-\beta})\sigma_D}{\delta} \right]^2. \quad (11.6)$$

Here z_p is the standard-normal p quantile, α the test's type-I error probability, $1 - \beta$ its power, σ_D the assumed difference standard deviation, and δ the mean difference to detect. With $\alpha = 0.05$,

power 0.80, $\sigma_D = 3$ m and $\delta = 1$ m, this approximation gives 70.6399, rounded up to 71 complete independent pairs. Allowing an expected 15% unusable fraction gives $\lceil 71/0.85 \rceil = 84$ *attempts*; that expected-yield calculation does not guarantee a quota. It neither establishes power for the protocol’s multiplicity-adjusted family of endpoints and comparisons nor specifies precision for agreement limits. Clustering and the intended interaction estimates also require separate planning.

The existing software gate nevertheless requires **84 accepted pairs per cell**, or 252 across the three cells; that operational threshold is retained. The checked-in schedule has exactly 252 slots, so it supplies no attrition reserve for achieving 252 accepted pairs. Before collection, specify and version an attempt budget, stopping rule, and replacement policy consistent with that gate. Retain every failed attempt and its reason, rather than overwriting a failure or silently removing a device that struggles with difficult shots. Report missingness by device and condition alongside agreement among retained pairs; complete-pair results alone need not represent performance over all attempted shots.

The software’s “pair” identifier actually denotes one same-shot observation set containing at least two distinct commercial devices and exactly one reference. Each device–reference contrast forms a statistical pair; contrasts within the same set share the reference, and do not create additional independent shots toward the quota. The validator checks the recorded calibration status, unique device rows, hashed serial identifiers, and a common trigger timestamp; these schema checks do not establish physical independence or reference accuracy. The versioned protocol template, capture-row JSON Schema, validator, deterministic schedule, collection ledger, command-line procedure, and synthetic fixture are present. The generated status record reports `confirmatory_ready=false`, 252 `not_collected` exclusions, and zero analyzed pairs. The schedule and ledger are bound by SHA-256:

```
schedule: 72b06c034e73751dbacce8468505517a8500754d4d769cc89fed846611790173
ledger:   ebc1a24100b0e09ea39978127d6f1bcad3bd26bf6c4f3ae042680a833281d9c9
```

No paired observations are represented as collected in this snapshot. The remaining protocol decisions and physical acquisition are hold points; neither software readiness nor a synthetic fixture is device-validation evidence.

Neural-network vendor emulators remain internal research artifacts. Their training manifests must pin the eligible sources, feature and target units, splits, random seeds, software version, and evaluation cohort. They are released only with held-out and out-of-distribution performance, uncertainty or applicability bounds, and a model card that forbids device-emulation or certification claims. Until the paired-device gate is satisfied, Release B comparisons remain unavailable rather than being approximated from unrelated shots.

11.5 Reproducibility and Claim Discipline

Release manifests bind software, interface, paper, and data revisions to their checksums. Normalization and exclusions have their own lineage; exports retain the request and backing rows needed to reproduce a displayed calculation independently of interface state, subject to the source’s access restrictions.

Unpaired public records support source-specific model comparisons. Same-shot observations with characterized reference uncertainty support the proposed device comparisons. Neither design alone identifies proprietary algorithms or uniquely separates sensor and aerodynamic-model errors: those inferences require additional assumptions and identifiable experiments. Reproducible calculations make these limits inspectable; they do not remove them.

Appendix A

Annotated Reference Library

This appendix organizes sources used in the review by their evidential role. The research dossiers in `articles/Launch_Monitor_Technology_Review/research/` record the working claim trails; they are research notes, not independent validation. A source listed here does not support every claim about the associated product. Manufacturer descriptions, measured agreement, and physical models answer different questions. Read a numerical result together with its device version, measurand, reference point, event time, test conditions, and missing-data rate. Access checks on 1 October 2026 are observations, not availability guarantees: a failed retrieval does not establish permanent absence.

A.1 Patents (Google Patents / USPTO)

These records disclose proposed methods and embodiments. They do not establish the architecture shipped in a particular device, independent performance, or freedom to implement. The annotations identify technical topics; they do not determine claim scope or current legal status. Inventor and company groupings are navigation aids, not a complete ownership or portfolio history.

TrackMan A/S (Fredrik Tuxen)

- Inventor index and manufacturer patent list:
<https://patents.justia.com/inventor/fredrik-tuxen> and
<https://www.trackman.com/legal/patents>
- US8845442 — Determination of spin parameters of a sports ball (harmonic-sideband spin; Magnus spin-axis inversion): <https://patents.google.com/patent/US8845442B2/en>
- US10393870 — continuation of the above:
<https://patents.google.com/patent/US10393870B2/en>
- US10850179 — spin axis via receiver-pair interferometry:
<https://patents.google.com/patent/US10850179B2/en>
- US8085188 / US9857459 / US10473778 — target-deviation (tap-a-target) family:
<https://patents.google.com/patent/US8085188B2/en>,
<https://patents.google.com/patent/US9857459B2/en>,
<https://patents.google.com/patent/US10473778B2/en>
- US10315093 — trajectory tracer overlay:
<https://patents.google.com/patent/US10315093B2/en>
- US11086005 — multi-bay range tracking:
<https://patents.google.com/patent/US11086005B2/en>
- Historical TrackMan spin-patent explainer address (redirected to the general blog during this review; use the patent records above for content):
<https://blog.trackmangolf.com/patent-measuring-the-spin-of-a-sports-ball/>

FlightScope / EDH (Henri Johnson)

- US9868044 — spin from periodic features in a phase-demodulated signal:
<https://patents.google.com/patent/US9868044B2/en>
- US10775492 — spin-axis estimation using receiver-pair time delays:
<https://patents.google.com/patent/US10775492B2/en>
- US10338209 — combined radar and camera tracking:
<https://patents.google.com/patent/US10338209B2/en>
- Company history: <https://athlonsports.com/golf/the-flightscope-story-tracking-the-history-of-flight-in-golf>

Foresight Sports / Wintriss Engineering (Kiraly)

- US7292711 — flight parameters from imaged surface features, including markings, blemishes, or dimples: <https://patents.google.com/patent/US7292711B2/en>
- US7324663 — standalone smart-camera launch monitor:
<https://patents.google.com/patent/US7324663B2/en>
- US7497780 — integrated launch monitor UX:
<https://patents.google.com/patent/US7497780B2/en>
- US7641565 — ball-placement detection: <https://patents.google.com/patent/US7641565B2/en>
- WAWGD (Foresight) filings index:
<https://patents.justia.com/inventor/wawgd-inc-dba-foresight-sports>
- Foresight–Uneekor 2024 license (Business Wire):
<https://www.businesswire.com/news/home/20240930838753/en/>

Acushnet / Titleist (Gobush et al.)

- US5501463 — optical club/ball measurement with reflective markers:
<https://patents.google.com/patent/US5501463A/en>
- US6500073 — camera measurements and trajectory computation:
<https://patents.google.com/patent/US6500073B1/en>
- US6758759 — separate club and ball monitors before/after impact:
<https://patents.google.com/patent/US6758759B2/en>
- US7143639 — portable monitor with one or more cameras:
<https://patents.google.com/patent/US7143639B2/en>
- US8500568 / US8556267 — portable continuations:
<https://patents.google.com/patent/US8500568B2/en>,
<https://patents.google.com/patent/US8556267B2/en>
- US10668350 — stereographic or light-field camera embodiments:
<https://patents.google.com/patent/US10668350B2/en>

Others

- USGA US6186002 — aerodynamic characteristics from measured trajectories (original assignee: United States Golf Association): <https://patents.google.com/patent/US6186002B1/en>
- Full Swing US2020/0147470 — CW+FMCW dual-mode launch monitor: <https://patents.google.com/patent/US20200147470A1/en>
- Creatz US10247553 — start-position sensor: <https://patents.google.com/patent/US10247553B2/en>
- Golfzon US9242158 — two-stage latency-hiding simulation: <https://patents.google.com/patent/US9242158B2/en>
- Uneekor patent/license list: <https://uneekor.com/legal/patents>
- Pulse/exposure timing correlation US12401909: <https://patents.google.com/patent/US12401909B2/en>
- TrackMan EP1698380 litigation coverage: <https://thegolfwire.com/322771-2/>
- FlightScope 2022 BGH win vs TrackMan: <https://golfbusinessnews.com/news/innovation-centre/flightscope-wins-patent-infringement-case-against-trackman-in-germany/>

A.2 Regulatory Records and Teardown Reports

FCC filing mirrors identify equipment records and tested configurations; they do not independently validate launch parameters. Forum teardown reports are secondary observations requiring confirmation against the actual hardware.

- TrackMan 4 FCC ID SFX-TMAN4 (X-band + 24 GHz): <https://fccid.io/SFX-TMAN4>
- TrackMan iO FCC ID SFX-TMB0201 (24 GHz): <https://fccid.io/SFX-TMB0201>
- FlightScope Mevo FCC ID QXP-A7310 (24.125 GHz): <https://fccid.io/QXP-A7310>
- Mevo+ teardown / QXP-LJ361 (10.5–10.55 GHz) discussion: <https://golfsimulatorforum.com/forum/flightscope/277362-mevo-teardown>

A.3 Manufacturer Documentation and Product Reporting

Official pages describe vendor definitions and specifications. Media, retailer, and community pages below are labeled separately; their inclusion does not turn a product claim into an independent measurement.

TrackMan

- 40+ parameters explained: <https://www.trackman.com/blog/golf/40-trackman-parameters>
- Club data definitions: <https://www.trackman.com/blog/golf/club-data-definitions>
- Club speed (geometric-center definition): <https://www.trackman.com/blog/golf/what-is-club-speed>
- Spin loft / spin rate: <https://www.trackman.com/blog/golf/spin-loft>, <https://www.trackman.com/blog/golf/spin-rate>

- OERT (“Two radars, one camera, zero doubt”):
<https://www.trackman.com/blog/golf/two-radars-one-camera-zero-doubt>
- Tech specs (TM4, iO): <https://www.trackman.com/golf/launch-monitors/tech-specs>
- Ball Flight Laws newsletter (Jan. 2009; historical D-plane and launch-direction teaching material). Compare the study-specific weights in §3.1.1; 0.76 is not a universal constant:
<https://www.yumpu.com/en/document/view/11652756/trackman-ball-flight-laws>

A.3.1 The TrackMan Newsletter Archive

Historical newsletters are indexed below through a third-party mirror. Issues #7–#9 were retrieved for the present annotation review; this is not a claim that the collection is complete or that official and archival copies are unavailable. The mirror directory is

<https://www.gregsmithgolfcoach.com/wp-content/uploads/2014/04/>:

- `newsletter1.pdf` (Nov 2007) through `newsletter9.pdf` (Jan 2013), sequentially numbered.
- `TrackMan_Newsletter_2014.pdf` is issue #10 (Jan 2014); the filename differs from the numbered examples. This does not establish an end date for the series.
- **#7 (Oct 2010), “Ten Fundamentals”** presents historical vendor rules of thumb: driver launch weights of 85% toward the face in both planes, 75% for irons, and nominal spin decay of 4% per second. These are not universal material or aerodynamic constants. Its scalar loft-minus-attack definition requires a common-plane interpretation; spatial spin loft is the angle between the face normal and velocity.
- **#9 (Jan 2013), pp. 3 and 5** specifies a maximum-compression reporting reference with averaging qualifications. It lists TrackMan III/IIIe *absolute* specifications, described by the manufacturer as 95% confidence: speed ± 1.5 mph, attack $\pm 1.0^\circ$, path $\pm 1.0^\circ$, loft $\pm 0.8^\circ$, face $\pm 0.6^\circ$. Its separate repeatability column is not interchangeable with absolute error. Conditions include a centre of gravity within 10 mm of the geometric centre for attack/path, impact entirely on the face for loft/face, and successful measurement of the required club, ball-direction and spin data. A reporting reference does not mean every output is an instantaneous direct measurement; see also the dated club-data definitions above.
- **#8 (Jun 2011), p. 4** gives a 12.7 mm heel offset and a 2° face-angle change toward closed. Its universal-driver wording should not be adopted as a geometric law: the change depends on local face curvature. For an ideal circular horizontal section, $\Delta\theta = \arcsin(x/R)$ for lateral offset x and radius R , relative to the central normal. At $x = 12.7$ mm, radii of 250 and 500 mm give about 2.91° and 1.46° , respectively. These are geometric examples, not measured driver specifications; the sign depends on the heel/toe convention.

Caution

Those accuracy figures are manufacturer specifications. Leach et al. tested TrackMan Pro IIIe and GC2+HMT against an optical reference in an indoor, eight-golfer, 240-shot study (Leach et al. 2017, <https://doi.org/10.1016/j.measurement.2017.08.009>). In Table 6, 45% of TrackMan path differences and 66% of face-angle differences fall within $\pm 1^\circ$ of the *median difference*, not of zero error. Such a band describes dispersion after centering; a systematic bias can remain. It is not a direct pass/fail test of the vendor’s absolute limits.

Data availability is another quantity: TrackMan returned club velocity on 98% of shots, but

the other four club parameters on 62% overall and 19% for the utility wedge. The authors also describe installation compromises, possible radar interference, markers, and differences in reference point or impact timing. Reference calibration alone does not make all compared outputs the same measurand. Report bias, dispersion, uncertainty and return rate separately, and retain these device/setup limits when applying the result to a golfer's swing or to a newer monitor.

Foresight Sports

- GCQuad product/technology:
<https://www.foresightsports.com/products/gcquad-launch-monitor>
- Ball and club data (spherical correlation, fiducials):
<https://foresightsports.eu/ball-club-data/>
- HMT head measurement (dot-count data tiers):
<https://www.foresightsports.com/hmt-head-measurement>
- Club marker application guide:
<https://help.foresightsports.com/hc/en-us/articles/4408197030035>
- Marker troubleshooting:
<https://help.foresightsports.com/hc/en-us/articles/4405916455443>
- Design history (Popular Science): <https://www.popsoci.com/gear/foresight-sports-quadmax-photometric-golf-launch-monitor-development/>

Other Vendors

- FlightScope X3 announcement (The Golf Wire): <https://thegolfwire.com/326713-2/>
- Garmin R10 third-party explainers (My Golf Simulator):
<https://mygolfsimulator.com/garmin-r10-data/>,
<https://mygolfsimulator.com/garmin-r10-accuracy/>
- Garmin R50 (three-camera): <https://www.garmin.com/en-US/p/736810/>
- Full Swing KIT technology and specs:
<https://www.fullswinggolf.com/kit-launch-monitor-technology/>,
<https://www.fullswinggolf.com/kit-specs/>
- Rapsodo MLM2PRO spin (MyGolfSpy): <https://mygolfspy.com/news-opinion/rapsodo-mlm2pro-takes-spin-measurement-to-pro-level/>
- SkyTrak+ / ST+ vendor product and measurement description:
<https://www.skytrakgolf.com/products/skytrak-plus-launch-monitor>
- Uneekor EYE XO / Dimple Optix vendor description (Canadian site):
<https://uneekor.com/en-ca/products/eye-xo-standalone>
- Uneekor calibration guide (Carl's Place):
<https://www.carlofet.com/blog/calibrating-uneekor-launch-monitors>; official PDF:
https://download.uneekor.com/docs/EYEXO2_Calibration_Guide.pdf
- ProTee VX retailer review (PlayBetter):
<https://www.playbetter.com/blogs/golf-simulator-reviews/protee-vx-review>

A.4 Research Papers, Standards, and Technical Notes

Journal and proceedings papers, preprints, theses, author notes and test standards have different review and validation roles. Agreement with another monitor is not automatically accuracy against an independent reference; repeatability is not trueness. A cross-sport method needs golf-specific validation before its reported performance can be transferred.

- Penner, “The physics of golf,” Rep. Prog. Phys. 66 (2003):
<https://iopscience.iop.org/article/10.1088/0034-4885/66/2/202>
- Leach et al. 2017 launch-monitor validation (*Measurement*):
<https://www.sciencedirect.com/science/article/abs/pii/S0263224117305079>; open-access:
https://repository.lboro.ac.uk/articles/journal_contribution/9562799
- TrackMan 4 indoor reliability (J. Sports Sci. 2024):
<https://www.tandfonline.com/doi/full/10.1080/02640414.2024.2314864>
- Mevo+ vs TrackMan 4 agreement (2025):
<https://www.sciencedirect.com/science/article/pii/S2772696725000420>
- Bearman & Harvey 1976 golf ball aerodynamics:
<https://www.cambridge.org/core/journals/aeronautical-quarterly/article/abs/golf-ball-aerodynamics/67FE0903DB1CC12001F1ED1B1261C4B9>
- Smits & Smith aerodynamic model: <https://www.researchgate.net/publication/284037213>
- USGA Indoor Test Range conditions: <https://www.usga.org/content/dam/usga/images/equipment-standards/ITR-test-conditions-2028-ODS.pdf>
- Friction/tangential compliance and launch angle (MDPI 2020):
<https://doi.org/10.3390/proceedings2020049027>
- Wood, Henrikson and Broadie (2018), face/path influence study:
<https://doi.org/10.3390/proceedings2060249>. The player-test horizontal means (driver 0.76, 7-iron 0.69, wedge 0.61) use centre-strike and face-to-path filters; they are sample-specific, not universal coefficients or individual-shot error bounds.
- Cross oblique-impact golf experiments:
<https://www.physics.usyd.edu.au/~cross/GOLF/GOLF.htm>
- Cross & Nathan oblique collision formalism: <https://arxiv.org/pdf/1610.03464>
- Dynamic models review, Sports Engineering 25 (2022):
<https://link.springer.com/article/10.1007/s12283-022-00387-0>
- Stanford LES of golf ball flow (Sports Eng. 2019):
http://aero-comlab.stanford.edu/Papers/golf_ball_sports_engineering_2019.pdf
- Golf ball aerodynamics in still air (MDPI): <https://www.mdpi.com/2504-3900/2/6/238>
- Micro-Doppler of spinning projectiles on CW radar:
<https://www.researchgate.net/publication/317119893>
- SpinDOE camera spin estimation (transferable method): <https://arxiv.org/pdf/2303.03879>
- “Measuring Ball Spin by Image Registration”:
<https://www.researchgate.net/publication/2881136>

- Doppler ball-tracking thesis (WSU, TrackMan platform):
<https://baseball.physics.illinois.edu/trackman/JasonMartinThesisWSU.pdf>
- Alan Nathan's TrackMan (baseball) technical notes:
<https://baseball.physics.illinois.edu/trackman.html>
- Cochran & Stobbs, *Search for the Perfect Swing* (1968):
<https://archive.org/details/searchforperfect0000coch>

A.5 Engineering References (Tutelman et al.)

- 3D launch conditions from impact conditions:
<https://www.tutelman.com/golf/ballflight/3dlaunch.php>
- Smash factor: <https://www.tutelman.com/golf/ballflight/smashfactor.php>
- Gear effect: <https://www.tutelman.com/golf/ballflight/gearEffect1.php>
- Spin decay: <https://www.tutelman.com/golf/ballflight/spinDecay.php>
- Ball flight laws summary: <https://www.perfectgolfswingreview.net/ballflight.htm>
- TrackMan face-angle derivation discussion (Manzella forum): <https://forum.brianmanzellagolf.com/threads/how-does-trackman-flightscope-measure-the-club-face-angle.16591/>

A.6 DIY / Open-Source

- PiTrac GitHub (GPL-2.0): <https://github.com/PiTracLM/PiTrac>
- PiTrac documentation: <https://docs.pitrac.org/>
- PiTrac Hackaday.io project (design logs):
<https://hackaday.io/project/195042-pitrac-the-diy-golf-launch-monitor>
- OpenFlight upstream: <https://github.com/jewbetcha/openflight>
- OpenFlight Grafana write-up: <https://medium.com/grafana-labs/openflight-building-an-open-source-golf-launch-monitor-with-raspberry-pi-grafana-cloud-and-84d68ad40fc5>
- GC2-imitating OpenCV experiments: <https://github.com/ronheywood/opencv>
- GSA Golf simulator theory (marked-ball DIY methods):
<https://www.golf-simulators.com/GolfSimulatorTheory.html>

A.7 Hardware Datasheets, Protocols, and Standards

- OPS243 product brief:
https://omnipresense.com/wp-content/uploads/2024/01/OPS243-Product-Brief_004-F.pdf
- OPS243 AN-010 API interface:
https://omnipresense.com/wp-content/uploads/2025/10/AN-010-AD_API_Interface.pdf
- OPS243 AN-027 rolling buffer:
https://omnipresense.com/wp-content/uploads/2025/06/AN-027-A_Rolling-Buffer-1.pdf

- OPS243 AN-029 sports applications: https://omnipresense.com/wp-content/uploads/2026/06/AN-029-A_OPS243-for-Sports_260621.pdf
- RFbeam K-LD7 datasheet: <https://rfbeam.ch/product/k-ld7-radar-transceiver/>
- TI IWR6843 datasheet: <https://www.ti.com/lit/ds/symlink/iwr6843.pdf>; ISK EVM: <https://www.ti.com/tool/IWR6843ISK>; placement app note: <https://www.ti.com/document-viewer/lit/html/SWRA758>
- TI mmWave golf-swing forum thread: <https://e2e.ti.com/support/sensors-group/sensors/forums/sensors-forum/1116424/iwr6843aop-golf-swing-analyzer-with-mmwave-radar>
- Raspberry Pi camera documentation (Global Shutter, XTR trigger): <https://www.raspberrypi.com/documentation/accessories/camera.html>
- GSPro Open Connect v1: <https://gsprogolf.com/GSProConnectV1.html>; community feedback: <https://github.com/tnbozman/gspro-interface/blob/main/OpenAPI-Documentation-Feedback.MD>; reference client: <https://github.com/travislang/gspro-garmin-connect-v2>
- USGA equipment standards: initial velocity TPX3007: <https://www.usga.org/content/dam/usga/pdf/Equipment/TPX3007-initial-velocity-test-procedure.pdf>; ODS TPX3006: <https://www.usga.org/content/dam/usga/pdf/Equipment/TPX3006-overall-distance-and-symmetry-test-procedure.pdf>; clubhead CT TPX3004 and MOI TPX3005 via <https://www.usga.org/equipment-standards.html>; 2028 ALC revision: <https://www.usga.org/content/usga/home-page/articles/2023/12/revised-golf-ball-testing-conditions-to-take-effect-in-2028.html>
- CFAR tutorial (CA/GO/SO/OS): <https://www.mathworks.com/help/phased/ug/constant-false-alarm-rate-cfar-detection.html>; Purdue lecture notes: https://engineering.purdue.edu/~mrb/resources/AltLectureF/Session_21.pdf
- Stalker baseball-spin patent (radar spin outside golf): <https://patents.google.com/patent/US10935657B2/en>
- Weibel Scientific radar object-detection patent: <https://patents.google.com/patent/EP1735637B1/en>

A.8 Comparative Testing and Market Analysis

These media, vendor and retailer accounts help locate comparisons and historical context. Before using a ranking or numerical accuracy claim, inspect its reference instrument, protocol, exclusions and uncertainty; the listing itself is not an endorsement of the test.

- MyGolfSpy indoor accuracy test: <https://mygolfspace.com/news-opinion/three-of-the-most-accurate-indoor-launch-monitors-and-one-to-avoid/>
- GCQuad vs TrackMan comparison article (Golf Simulator Zone): <https://golfsimulatorzone.com/gcquad-vs-trackman-accuracy-in-2026/>
- Foresight GCQuad/GC3 comparison: <https://www.foresightsports.com/blogs/golf-tips/comparing-golf-launch-monitor-foresight-sports-gcquad-and-gc3-stand-above-the-rest>
- Bushnell Launch Pro vs GC3 vs GCQuad: <https://www.playbetter.com/blogs/golf/bushnell-launch-pro-vs-gc3-vs-gc-quad-comparison>

- Photometric vs radar explainers: <https://www.playbetter.com/blogs/golf-simulator-comparisons/photometric-vs-radar-golf-launch-monitor>,
<https://golfbays.de/en/blogs/news/radar-vs-photometric-launch-monitors-indoors>
- Indoor flight compensation:
<https://www.cerogolf.com/post/how-launch-monitors-compensate-for-indoor-ball-flight>
- TrackMan history (Golf Monthly, Tuxen profile):
<https://www.golfmonthly.com/features/from-tracking-missiles-to-tracking-golf-balls-meet-the-man-that-you-didnt-realise-changed-golf>

Appendix B

Detailed Implementation Guidance

This appendix turns the review into engineering guidance at the level of signal-processing parameters, algorithms, and procedures, citing the governing sources throughout. Coordinate conventions follow Chapter 2.

B.1 Radar Signal Chain (OPS243-A)

B.1.1 Doppler Scaling and Resolution Budget

At $f_c = 24.125$ GHz, Equation (4.1) gives 71.7 Hz per mph. With a 30 kHz I/Q sample rate, the unambiguous span is ± 15 kHz $\approx \pm 209$ mph — adequate for ball speeds to ~ 200 mph. Velocity resolution is set by observation time: a 128-sample window (4.27 ms) gives $\Delta f = 234$ Hz ≈ 3.3 mph per raw bin; zero-padding to 4096 (the current pipeline) interpolates the peak but does not add information. For *spin* work the window, not the padding, must grow: resolving sidebands at $f_{\text{spin}} = S/60$ (e.g. 50 Hz at 3,000 rpm) requires windows of $\gtrsim 40$ ms, during which a 150 mph ball decelerates and the central line *chirps* — so the practical estimator de-chirps first (track the central line per US8845442’s spectral-trace step [88], resample the phase to remove it), then measures the residual modulation.

B.1.2 Spin-Rate Comb Estimation

The patent-documented chain (Section 4.4.2) maps to this concrete pipeline [88, 79]:

1. STFT with 50–75% overlap over the post-impact 50–250 ms; track the ball ridge (max-SNR bin per frame with continuity constraint).
2. De-chirp: mix each frame down by the tracked ridge frequency so the ball line sits at DC.
3. Estimate the sideband comb spacing on the de-chirped spectrum via cepstrum or harmonic product spectrum — both are robust to missing harmonics; the patent’s *qualification* step (verify equal spacing across ≥ 3 consecutive frames, and consistency of the harmonic-number assignment) is what separates real spin from clutter [88].
4. Report spin only when the qualified comb persists; otherwise fall back to a flagged estimate from club priors (Section B.3) — the Garmin R10’s documented behavior [45].

Expected detection physics: sideband amplitude scales with ball-surface asymmetry [88]; range balls and clean urethane balls read weakly (the reason for Titleist RCT metal-tagged balls [47] and FlightScope’s metallic-dot stickers [25]). Logging which ball type produced each detection will quantify this for a given deployment.

Disclosure references: US8845442 and US9868044 describe distinct radar spin-processing approaches [88, 34]. The latter’s dielectric-lens explanation should be distinguished from its claims’ signal-processing requirements (Section 7.3). These references identify technical material to study, not technique-wide expiry dates or implementation clearance (Section 7.8).

B.1.3 Club-Speed Extraction

The pre-impact spectrum contains a velocity *smear* from heel (slow) to toe (fast), plus shaft returns below. TrackMan resolves this by reconstructing the head silhouette and reporting the geometric center [84]; a single-radar approximation that tracks a stable reference is: gate the last 30–50 ms before the trigger timestamp, form the velocity histogram of CFAR-passing bins, discard the bottom decile (shaft/hosel) and top decile (toe glint), and report a fixed percentile (median of the remainder). Validate against the loft-dependent smash ceiling of Section 3.2 ([86]); reject or flag shots exceeding it, which independent testing shows is the signature of toe-lock errors [39].

B.2 Angle Measurement (K-LD7) and the EKF

B.2.1 Interferometric Angles

The K-LD7’s two receive patches implement Equation (4.2) with a $\lambda/2$ -class baseline; per-bin phase comparison of the two ADC channels after the range-Doppler FFT yields one angle per detection — the same phase-monopulse principle as US10850179 [90] and the R10’s three-receiver array [46]. Two practical constraints from the commercial art: (i) angle error grows as SNR falls, so weight each detection by measured SNR; (ii) mechanical alignment dominates the error budget — a 1° mount error is a 1° bias on every launch direction, amplified $\sim 1.15\times$ into face angle (Equation (4.8)).

B.2.2 Recommended Filter

Implement the Section 8.3 smoother concretely as: state $\mathbf{x} = (\mathbf{p}, \mathbf{v})$ (add spin states later); process model Equation (8.1) with Smits–Smith coefficients [65]; measurements: OPS243-A radial speed ($\dot{r}$, high rate, low noise), K-LD7 angle+range detections (lower rate, SNR-weighted covariance). Run a forward EKF then an RTS (Rauch–Tung–Striebel) backward smoother over the 50–150 ms burst, and evaluate the smoothed state at the sound-trigger timestamp minus the acoustic delay — this back-extrapolation is how commercial radars report launch conditions robustly despite early-flight clutter [88, 32]. The innovation-gating step of the EKF doubles as the outlier rejector for multipath and club returns. The same filtering architecture extends from point tracking (the ball) to rigid-body tracking (the club) via the screw-theoretic formulation of Chapter E, which is the recommended estimation layer for the IWR6843 integration.

B.2.3 Alignment Calibration Procedure

Adopt the commercial patterns: (i) Uneekor-style floor chart — a printed target-line chart at known positions establishes the target-line azimuth for both K-LD7s [5]; (ii) FlightScope-style known-trajectory check — roll or swing balls along a surveyed line and verify reported directions (US10338209 uses a Doppler simulator for the same purpose [32]); (iii) record the mount pose in the session log so data from different setups is never silently mixed.

B.3 Derived Club Data, With Priors

Implement the D-plane module once, use it both ways (Sections 3.1 and 4.5.2):

- **Forward** (simulation/validation): Tutelman’s calibrated closed form, Equations (3.4) and (3.5), plus spin from Equation (3.9) [87].

- **Inverse** (reporting): face angle from Equation (4.8) with w_f interpolated in dynamic loft between 0.87 (driver) and 0.75 (wedge) [73, 87]; dynamic loft analogously from launch angle and attack angle. Tag both as *derived* per Table 2.3.
- **Priors table** per club type (driver...wedge): static loft, typical dynamic-loft delta, spin-loft range, smash ceiling (Section 3.2), PGA/LPGA reference deliveries [82]. Used for: spin fallback estimates, outlier gating, and the smash sanity check.
- **Gear-effect bound**: when impact location is unknown, attach an uncertainty of up to $\pm 6^\circ$ of spin-axis tilt per 0.14in of possible driver miss [54, 85] to any derived face-to-path interpretation — and surface it in the UI rather than hiding it.

B.4 Optical Module (Phase 2) Design Parameters

The Wintriss disclosures provide optical measurement principles [37]; PiTrac provides an implementation reference [55]. The following choices are prototype parameters to verify against the selected hardware and capture conditions, rather than specifications fixed by a patent:

- **Sensor**: Raspberry Pi Global Shutter camera (IMX296, 1456×1088); global shutter is non-negotiable (rolling shutter skews a 150 mph ball by several pixels per row-time).
- **Strobed multi-exposure**: $N = 3\text{--}5$ IR pulses (850 nm, tens of μs each) inside one long exposure freeze N ball images per frame; at 150 mph the ball moves 6.7 cm/ms, so pulse spacing of $\sim 300\text{--}500 \mu\text{s}$ spaces images 2–3 cm apart in a 30 cm capture volume — matching the commercial capture geometry [15, 55].
- **Trigger**: reuse the SEN-14262 sound trigger; its $\sim 10 \mu\text{s}$ latency is far inside the strobe-timing budget, solving the triggering problem the Wintriss patent addressed with a microphone+radar pair [37].
- **Ball detection**: Hough circles on the strobed frame (PiTrac-proven [55]); depth from the known 42.67 mm diameter (the Wintriss mono-camera range cue [37]) or from a second camera via Equation (5.1).
- **Spin**: register the dimple texture between successive ball images over $SO(3)$ (Equation (5.2)); Gabor-filter pre-enhancement of dimples is documented in US12401909 [72]; with $\Delta t \approx 400 \mu\text{s}$, 3,000 rpm is only 7.2° of rotation — comfortably below the aliasing limit, and small enough that a local search around the D-plane-predicted axis converges quickly (Section 5.2.2). Surface-image registration appears in the Wintriss disclosures and Foresight’s technical account [37, 14]; neither source establishes blanket rights clearance for the prototype.
- **Impact location / face orientation** (later): either calibrated face-fiducial reconstruction, informed by the distinct Acushnet camera arrangements in US5501463 and US6758759 [23, 38], or an overhead second camera per the Uneekor geometry [92].

B.5 Flight Model and Validation Protocol

Ship Smits–Smith (Equation (8.2)) with spin decay [65], version the coefficients, and calibrate against measured trajectories using the US6186002 fitting approach [43] — outdoor sessions with the MLM2PRO (or simple carry ground-truth) provide the data. Validation against the MLM2PRO should follow the Leach protocol structure [39]: per-club shot blocks, Bland–Altman limits of

agreement per parameter, ball data compared directly, spin compared only on RPT/RCT balls (where the MLM2PRO's spin is camera-measured [47]), and club speed compared with an explicit reference-point caveat (Section 4.5). Log raw I/Q and (later) raw frames for every shot so algorithm changes can be replayed against history — the practice that made this review's accuracy analysis possible for the commercial units is exactly what an open project can do better.

Appendix C

Sensor Hardware and Integration Reference

A launch monitor connects sampled signals to estimates of ball and club motion, then connects those estimates to impact and flight models. Every connection adds assumptions: the target must be identified, the measurement time and reference frame must be known, and any missing components must be supplied by additional observations or a declared model. This appendix uses documented components as worked examples, not as an endorsed bill of materials or evidence that a particular combination achieves launch-monitor accuracy. Read the specifications below with the measurement hierarchy in Table 2.3 and the impact definitions in Chapter 3. Manufacturer specifications describe particular hardware, firmware and test conditions; the calculations here establish conditional limits, not measured performance of a completed instrument.

C.1 OmniPreSense OPS243-A (24 GHz CW Doppler)

C.1.1 Hardware and Configuration Boundaries

The OPS243 product brief distinguishes the Doppler-only OPS243-A from the Doppler/FMCW OPS243-C: the former does not provide range from its unmodulated carrier [52]. The brief lists a 24.00–24.25 GHz band, 11 dBm transmit power and a $20^\circ \times 24^\circ$ transmit beamwidth at -3 dB. The horizontal contour width at axial distance r is approximately $2r \tan(10^\circ)$: 0.353 m at 1 m and 1.763 m at 5 m. A beamwidth contour is not a hard detection boundary, and the family-level 1–100 m motion-detection claim is not a golf-ball range guarantee.

Electrical details also require the exact variant: the USB/UART version uses 3.3 V UART signaling, whereas an RS-232 version uses different levels. The brief permits a 24 V supply only for revision-C boards, otherwise 13.5 V maximum; its 1.7 W typical active-power table entry explicitly names OPS243-C [52]. Do not transfer these values indiscriminately between board revisions and sensor variants or use a headline accuracy percentage as an established golf-shot uncertainty.

AN-010 documents the default 10 kbps rate, selectable sample buffers, zero-padding, timestamped JSON and raw I/Q outputs [50]. For the golf example below, **S=30** sets 30 kbps, **S(** selects 128 acquired samples and **X=32** requests a 4096-point transform; configure the buffer before the padding multiplier. **OT**, **OM** and **OJ** select timestamps, magnitudes and JSON; **OR** supplies raw samples, while **O2** requests two reported speeds. The UART default is 19,200 baud, 8N1. Verify supported commands and read back the configuration for the installed firmware before saving it with **A!**.

C.1.2 Sampling, Grid Spacing and Identifiability

For an ideal monostatic CW observation, the magnitude of Doppler frequency satisfies $|f_D| = 2|v_r|/\lambda$, where v_r is radial velocity and $\lambda = c/f_c$. The sign depends on the receiver convention; it must be checked before transforming observations into the book’s coordinate frame. For centered complex

sampling at rate f_s , N acquired samples and an M -point transform with $M \geq N$, the nominal quantities are

$$|v_r| < \frac{\lambda f_s}{4}, \quad T = \frac{N}{f_s}, \quad \Delta v_N = \frac{\lambda f_s}{2N}, \quad \Delta v_M = \frac{\lambda f_s}{2M}. \quad (\text{C.1})$$

Here Δv_N and Δv_M are the unpadded and padded velocity-grid spacings. The first expression is a sampling limit, subject also to the analog passband and firmware; it is not a guaranteed detection speed. With $f_c = 24.125$ GHz, $c = 299,792,458$ m/s, $f_s = 30,000$ s⁻¹, $N = 128$ and $M = 4096$, these give 93.20 m/s (208.48 mph), 4.267 ms, 1.456 m/s (3.258 mph) and 0.04551 m/s (0.1018 mph), respectively.

Zero-padding samples the same finite-record spectrum on a finer grid; it adds no observed cycles. An isolated peak can be localized more finely than the unpadded bin spacing under suitable signal-to-noise and signal-model conditions, but neither spacing is a universal accuracy specification or a guaranteed separation between two resolvable targets. Windowing, unequal target strengths, acceleration and clutter change the estimation problem. This distinction explains why AN-029's nominal 0.1 mph figure cannot establish 0.1 mph measurement accuracy [49]. Likewise, a 200 Hz reporting example has 5 ms between outputs; that alone does not establish a 5 ms independent observation, capture duty cycle or processing latency.

The sensor observes $v_r = \hat{\mathbf{r}}^T \mathbf{v}$, where $\hat{\mathbf{r}}$ points from sensor to target for a positive-receding convention. Target bearing and velocity direction are different quantities: knowing the former does not determine the latter. If the angle θ between velocity and line of sight is independently known, $v = v_r / \cos \theta$; near transverse motion, small angular errors become strongly amplified. For small signed perturbations, $\delta v / v \approx \delta v_r / v_r + \tan \theta \delta \theta$, with $\delta \theta$ in radians and nonzero denominators. A fixed cosine correction cannot recover an unknown, changing trajectory.

C.1.3 Rolling Buffer and Trigger Timing

AN-027 describes a separate capture mode: **G1** stores 4096 complex samples in 32 segments of 128, with subsequent processing off the sensor [51]. A software **S!** command or 3.3 V rising edge on J3 pin 3 (**HOST_INT**) triggers completion. **S#n** selects the historical segment count; the default eight gives 1024 pre-trigger and 3072 post-trigger samples. The record spans 136.53 ms at 30 kpsps. The note illustrates a microphone gate connection, but its **S#18** example uses 250 kpsps and must not be copied as a universal golf setting.

Choose the pre-trigger history from an explicit timing budget. For source-to-microphone distance d , sound speed c_s , trigger-chain delay τ_e , desired pre-impact history τ_h and a bound τ_q on segment/timestamp uncertainty, require

$$\frac{128n}{f_s} \geq \frac{d}{c_s} + \tau_e + \tau_h + \tau_q, \quad 0 \leq n \leq 32. \quad (\text{C.2})$$

At the declared illustrative value $c_s = 343$ m/s, 2 m takes 5.831 ms, not 6.6 ms; the latter estimate in AN-027 is not adopted here. Ignoring electronics and quantization only for an arithmetic example, 2 ms of pre-impact history requires two segments at 30 kpsps, providing 8.533 ms total history. This is not a deployment recommendation: measure or conservatively bound the omitted delays and retain enough post-trigger data for the intended estimator.

C.1.4 Interpreting the Vendor Golf Example

AN-029 places the sensor about 2–3 m behind the ball and gives a configuration using 30 kpsps, 128 samples, padding to 4096, mph output, a lower speed filter, a magnitude threshold and peak

averaging [49]. Its reported 5–10 m golf-ball detection distance is vendor application guidance, not a qualification across balls and environments. Two reported peaks still require target association: neither peak order nor a plausible speed ratio proves which echo belongs to the ball or to a specified point on the clubhead. The ball and rotating club can have different line-of-sight projections and different measurement times. Before forming the smash factor of Section 3.2, establish the relevant ball/club speed definitions, timing and projection corrections. A 1.0–1.50 acceptance gate would be an implementation heuristic, not a physical theorem; record rejected shots to avoid hiding failures through selection. Radial-speed observations alone do not uniquely determine three-dimensional launch velocity or spin.

C.2 RFbeam K-LD7 (24 GHz FSK, Dual-RX Angle)

Revision B describes one transmitter and two I/Q receivers separated by 6.223 mm, with FSK range estimation and an $80^\circ \times 34^\circ$ antenna pattern [63]. Its table lists 6 dBm typical and 10 dBm maximum EIRP; the distance range starts at 0.005 m, not 0.05 m, and the nominal distance resolution is 5 cm at the 5 m range setting. These are distinct entries, not demonstrated millimeter-range golf performance. The 1° angular-resolution entry likewise does not certify one-degree golf accuracy or full-field sensitivity.

The maximum speed setting is 100 km/h (27.78 m/s or 62.14 mph), with a typical 29 ms frame duration [63]. It restricts both club and ball observations when their radial components exceed that limit; assigning the module to club speed does not remove the restriction. More transverse placement may reduce Doppler but worsens the conversion to total speed and changes visibility. Out-of-range targets can produce erroneous detections, rather than a clean indication that the limit was exceeded.

The host interface defaults to 115200 baud, 8E1; INIT can select up to 3 Mbaud. GNFD requests raw samples (RADC), spectra (RFFT), detections (PDAT), a tracked target (TDAT) and/or frame completion (DONE) [63]. Check frame counters and measured transfer time: a nominal acquisition period does not guarantee that every requested raw frame reaches the host. Calibration must also establish antenna geometry, phase offsets, target association and timing before combining this module with another sensor.

C.3 TI IWR6843 (60–64 GHz FMCW MIMO)

The IWR6843 has three transmitters, four receivers, a DSP and radar hardware acceleration; the datasheet distinguishes 12.5 Msps complex-1x sampling from 25 Msps real/complex-2x sampling [68]. The 60–64 GHz tuning range is not a statement that every configuration processes 4 GHz of useful chirp bandwidth. For an effective processed sweep bandwidth B , the nominal range-separation scale is $\Delta R = c/(2B)$, or 3.747 cm at $B = 4$ GHz [67]. Windowing and signal conditions affect separation; isolated-target range precision is a different quantity. Array geometry and the selected board determine angular coverage and aperture, so a count of twelve TX–RX channels is not twelve independent azimuth elements.

Time-division MIMO acquires the transmitter channels at different instants; velocity-induced phase must be compensated before interpreting the virtual array as an angle measurement [59]. For a uniform single-target phase-sampling model with same-transmitter inter-chirp revisit interval T_r within a burst, the principal unaliased radial-speed interval has half-width $\lambda/(4T_r)$, while coherent observation time sets a velocity-separation scale near $\lambda/(2T_{\text{obs}})$. Thus faster updates, wider unambiguous speed, more transmitter channels and finer Doppler separation compete for

acquisition time [67, 59]. Ambiguity-resolution methods can alter this design tradeoff but need their own assumptions and validation.

A 10–20 Hz output stream has 50–100 ms between reports; this is not necessarily its internal coherent dwell time. Such reporting alone does not establish coverage of a chosen 3 ms launch interval, and shortening the frame alone does not prove a working launch monitor. Specify the chirps, usable bandwidth, ADC interval, transmitter schedule, synchronization, target return strength and processing/transport latency together. Range, direction and radial velocity estimates can then constrain a trajectory model; a single range-angle-Doppler detection still lacks the tangential velocity components and does not establish spin or club delivery.

C.4 Raspberry Pi Global Shutter Camera (Optical Module)

The IMX296 camera provides 1456×1088 pixels of $3.45 \mu\text{m}$ pitch, full-resolution operation near 60 fps and short exposures near $30 \mu\text{s}$, subject to operating conditions [62]. Its XTR trigger is a **1.8 V input**; the documented exposure is the low pulse width plus $14.26 \mu\text{s}$. Shared pulses can synchronize cameras, but accepted pulse rates and actual frame timing must be verified. Raspberry Pi documents enabling the IMX296 external-trigger mode through

```
echo 1 | sudo tee /sys/module/imx296/parameters/trigger_mode
```

Use the documented procedure for the installed driver version. Boards with Q2 fitted require the documented R11 modification; use suitable level conversion and board-specific instructions [61].

Exposure duration controls motion blur; frame interval controls temporal sampling. At 60 fps, consecutive frames are 16.67 ms apart: a ball moving at 70 m/s travels 1.167 m between them, but only 2.1 mm during a $30 \mu\text{s}$ exposure. Whether that yields usable images depends on field of view, magnification, illumination and trigger timing. It cannot supply two consecutive frame samples within a 3 ms interval, but it can record flight over a larger observation region. Multiple flashes within one exposure, as discussed in Section B.4, are one possible architecture; a faster camera or a different observation window is another. None alone establishes spin observability without resolvable surface features, timing and calibrated geometry.

C.5 Simulator Integration: GSPro Open Connect

GSPro Open Connect v1 is a documented JSON-over-TCP interface; its sample endpoint is localhost port 921, with the launch monitor acting as client [28]. It is an integration example, not an assertion that no other documented protocol exists. A shot supplies device identity, shot number, API version, data-presence options and ball fields including **Speed** (mph), **VLA/HLA** (degrees) and spin data. The specification accepts **TotalSpin/SpinAxis** or **BackSpin/SideSpin**; it also describes optional club fields, readiness/heartbeat messages and a player-information response [28].

Numeric field names do not preserve the scientific meaning of a measurement automatically. Verify units, angle signs, handedness, reference points and event times against Chapter 2; avoid labeling a signed spin-axis value as a draw independently of handedness and convention. Two spin parameters also do not encode an unrestricted three-component spin vector; any mapping must state its representation assumptions. The documented schema supplies no general per-field uncertainty or measurement-provenance contract. Keep a separate, shot-linked record of raw evidence, calibration, inferred versus observed quantities and unavailable values, as motivated by Chapter 10. Do not replace unavailable spin with an apparently measured zero or silently present a prior-driven estimate as an observation simply to fill a required field. An accepted simulator message confirms transport compatibility, not measurement validity.

C.6 Equipment Rules and Model Parameters

Equipment conformance limits are constraints, not measured properties of every conforming club or ball. The ball rules specify mass at most 45.93 g and diameter at least 42.67 mm [71]. Using these limiting values in Equation (8.1) is a declared modeling choice; it does not identify a particular ball's mass, diameter, inertia or aerodynamic coefficients.

The driver spring-effect test uses a characteristic-time limit of 239 μs with an 18 μs test tolerance [95]. This pendulum-test quantity is not the club-ball contact duration or a universal conversion to the restitution coefficient e in Equation (3.8). That coefficient belongs to the declared impact model, incident speed, impact location and club/ball pairing. The wood-head volume limit is 460 cm^3 with a 10 cm^3 tolerance; the MOI limit is 5900 g cm^2 with a 100 g cm^2 test tolerance about the vertical CG axis at a 60° lie angle [70]. This is one specified inertia component, not a bound automatically transferable to every axis in Equation (3.10).

Status checked October 4, 2026: the December 2023 announcement described changing the ODS test from 120 mph/10°/2520 rpm to 125 mph/11°/2200 rpm, originally beginning in 2028 [10]. The June 17, 2026 joint statement superseded that timetable: no ODS testing change before January 2030 while alternative approaches are evaluated [96]. Do not present the earlier 2028 schedule as current or assume the eventual conditions are settled. The 317 yd limit plus 3 yd tolerance concerns the specified overall-distance test, not a universal maximum carry for a conforming ball [71]. A flight-model comparison requires the actual launch conditions, atmosphere, aerodynamic characterization and prescribed bounce/roll treatment; merely keeping an arbitrary simulation below 320 yd neither validates it nor certifies ball conformance.

C.7 Detection Theory: CFAR Selection

Constant-false-alarm-rate (CFAR) detection adapts a threshold to an estimate of local background power. A fixed SNR cutoff and a masked region around zero Doppler do not, by themselves, specify a cell-averaging CFAR detector. CA-CFAR uses the mean of training-cell powers, excluding guard cells around the cell under test; OS-CFAR uses a selected order statistic [41, 42]. The training region, guard width, rank where applicable, noise model and target false-alarm probability are part of the algorithm.

For an illustrative square-law CA detector, suppose the test-cell noise and K training-cell powers are independent exponential variables with common mean μ . Let $\bar{P}$ be their training mean and declare a detection when $P_{\text{CUT}} > \alpha \bar{P}$. Conditioning on the training samples gives

$$P_{\text{FA}} = \mathbb{E}\left[e^{-\alpha \bar{P}/\mu}\right] = \left(1 + \frac{\alpha}{K}\right)^{-K}, \quad \alpha = K \left(P_{\text{FA}}^{-1/K} - 1\right). \quad (\text{C.3})$$

The product follows from the exponential Laplace transform for each independent training cell. It is a conditional model calculation, not a false-alarm guarantee for real golf data: windowing and zero-padding can correlate spectral samples, while clutter and target leakage can invalidate the common-background model. A mask specified only as a number of padded bins also changes its physical velocity width when the FFT configuration changes.

OS-CFAR can reduce the effect of some high-power contaminated training cells, with performance depending on the chosen rank and contamination pattern; it is not universally superior for a club followed by a ball [42]. Their closeness in physical space or time does not establish closeness in the processed range-Doppler cells. Guard cells cannot separate unresolved targets, and neither a universal 0.5–1 dB loss nor a preferred detector follows from the shot geometry alone. Compare

candidate detectors at matched false-alarm targets on declared single-target, multiple-target and clutter cases, including nondetections and mistaken associations.

Design implication

The useful design unit is the complete observation chain: sensor geometry, acquisition window, synchronization, estimator, uncertainty record and downstream model. A finer reported number does not create a new physical observation; a plausible impact or flight result does not independently validate the measurements used to produce it. Preserve these distinctions when relating measured ball flight back to club delivery and, further upstream, to the golfer's swing.

Appendix D

Patent Portfolio Compendium

This appendix organizes selected launch-monitor patent publications by technical topic and named organization. It includes US grants, published US applications and explicitly identified foreign or PCT documents. The links provide a route to the disclosures; they do not establish an exhaustive portfolio search or a commercial product’s implementation. TrackMan’s marking notice lists 47 US numbers at the October 1, 2026 check [80]; Uneekor’s product-specific marking list expressly notes that other products and applications may exist outside its table [93].

The priority column records the indexed priority year of each row’s leading document. It is distinct from that application’s filing year and the document’s publication year, and it does not assign a common priority to every related number in the notes. A claim’s entitlement to priority and a patent’s term require separate analysis. Descriptions identify technical subject matter rather than the complete limitations of every claim. Neither a matching title nor a shared inventor proves common ownership, a continuation relationship or use in a named product. *Also* denotes another technical reference, not identical claim scope or verified family membership. Publication of an application is a document type, not an assertion that prosecution remains pending.

Two attribution corrections surfaced by this sweep are worth flagging prominently: (i) the widely cited “radar + image data 3D tracking” publications US10596416 / US11697046 / US12128275 identify **Topgolf Sweden AB (Toptracer)**, not TrackMan; and (ii) Full Swing’s launch-monitor publication US2020/0147470A1 corresponds to the grant US11311789B2. The Garmin and USGA entries below separate the disclosed mechanism from unsupported product and company-portfolio attributions.

D.1 TrackMan A/S (Incl. Interactive Sports Games A/S)

Radar Fundamentals and Target-Line Deviation (2004–2011)

Patent	Subject	Prio.	Notes
US8085188B2	Deviation of launched projectile vs. image-designated target direction	2004	
US8912945B2	Radar measurements transformed to a launch-and-target coordinate frame	2004	
US9857459B2	Target-direction deviation using co-rotated camera and radar	2004	
US10473778B2	Radar trajectory correlated with an image feature and displayed	2004	
US10690764B2	Radar trajectory mapped into launch-and-target coordinates	2004	

Patent	Subject	Prio.	Notes
US9958527B2	Direction-of-arrival sensor: extra RX antenna resolves monopulse phase ambiguity	2011	the sparse-array geometry of Section 4.2

Spin Rate and Spin Axis

Patent	Subject	Prio.	Notes
US8845442B2	Spin rate via harmonic sidebands; model-dependent axis from flight curvature	2005	Also EP1698380B1
US9645235B2	Unmarked-ball spin frequency from radar harmonic spacing	2005	
US10393870B2	Radar harmonic spin estimation without ball-marking information	2005	
US10962635B2	Spin frequency from radar modulation harmonic spacing	2005	
US11143754B2	Model-dependent axis from trajectory accelerations and spin frequency	2005	
US10850179B2	Projected spin axis from multi-receiver Doppler components	2018	
US11446546B2	Spin-axis projection from angular positions of radar frequency components	2018	
US11938375B2	Spin-axis component from receiver-pair phase differences	2018	
US11673029B2	Embedded radar markers with a great-circle proximity constraint	2019	
US12179068B2	Interior radar-reflective strips with great-circle coverage	2019	
US12042698B2	Toppling frequency of non-spherical rotating objects	2018	

Club Impact From Image Features

Patent	Subject	Prio.	Notes
US10953303B2	Impact timing and location from tracked club-image points	2017	
US11439886B2	Image-based impact geometry; single-imager embodiment with optional shaft marker	2017	
US11612801B2	Image-tracked line angle evaluated at impact time	2017	

Patent	Subject	Prio.	Notes
US12263393B2	Tracked fix-line angle (e.g., shaft); known geometry for 3D reconstruction	2017	

Radar+Camera Fusion, Calibration, Tracer, Range, Short Game

Patent	Subject	Prio.	Notes
US10052542B2	Coordinating radar + image data; overlay	2004	
US10471328B2	Radar/image trajectory and target-line overlay	2004	
US10989791B2	Fused radar range/rate + imager angles track	2016	
US11828867B2	Radar range and image angles combined with sensor separation geometry	2016	
US11619708B2	Calibration using radar tracks and camera bearings augmented by radar range	2020	
US12517218B2	Sensor calibration by weighted 3D track-residual minimization	2020	
US11748985B2	Master clock; composite multi-moment images	2019	
US12067775B2	Clock-referenced composite imaging	2019	
US12586211B2	Motion-triggered changes to imager operating parameters	2023	
US9855481B2	Radar trajectory projected into sports-video images	2009	Also US10315093B2, US10441863B2, US11135495B2, US11291902B2
US10379214B2	Launch-location association; one- and two-radar embodiments	2016	also US11086005B2, US11921190B2, US12618962B2
US11452911B2	Imager/secondary-sensor correspondence; range-radar embodiment	2019	also US11986698B2
US12036465B2	Player/shot association from motion-sensor time and location	2021	
US12186643B2	Camera line-of-sight and terrain model for bouncing/rolling ball position	2021	
US12702912B2	Robotic camera calibration and terrain-based ball localization	2021	USPTO Gazette
US10444339B2	Bounce/slide/roll transitions from velocity or acceleration changes	2016	also US11079483B2, US11619731B2, US11946997B2
US11285367B2	Strategy simulation from player capability	2018	also US12109473B2

Patent	Subject	Prio.	Notes
US11951372B2	Model-based shot-improvement estimates; mishit-filtering disclosure	2020	also US12539454B2
US12616891B2	Automated ball/strike, biometric strike zone	2021	Baseball

D.2 Topgolf Sweden AB (Toptracer / Protracer)

The publications in this section identify Topgolf Sweden AB and include camera, radar and combined tracking methods.

Patent	Subject	Prio.	Notes
US8077917B2	Enhancing sports video with trajectory imagery	2005	
US10596416B2	3D tracking: radar + image data	2017	also US11697046B2, US12128275B2
US10898757B1	3D trace from image motion and polynomial/exponential radar-speed fits	2020	also US11504582B2, US11883716B2, US12330020B2
US11335013B2	Motion-filtered image sequences and timestamp-based virtual-position interpolation	2020	also US11557044B2, US12322122B2
US11644562B2	Backward trajectory extrapolation with error-gated launch-origin association	2020	Also US11771957B1, US12121771B2
US11513208B2	Radar spin from radial-velocity variations about center velocity	2020	Also US12105184B2
US12544624B2	Spin-candidate selection from observed trajectory and probable club	2023	Model-dependent inference
US11964188B2	Position-dependent trajectory error estimates and sensor/shot placement guidance	2021	
US11995846B2	Multi-hypothesis tracking with pruning and progressively richer motion models	2020	also US12361570B2
US11815618B2	Co-located FMCW radar coordination through sweep-time and frequency offsets	2022	also US12253622B2
US12206977B2	Predictive pan/tilt/zoom control from launch data and updated 3D tracking	2021	
US12298326B2	Wind estimation from observed/model acceleration differences across ball trajectories	2022	
US12594460B2	Scored blob traces and calibration data carried in a video audio channel	2023	

D.3 FlightScope / EDH (Henri Johnson)

Patent	Subject	Prio.	Notes
WO2003032006A1	Path speed from directional velocity and angular deviation	2001	PCT publication
US8189857B2	Impact-mark localization from before/after playing-surface images	2007	
US9036864B2	Bounce localization from composite long-exposure image envelopes	2011	
US9868044B2	Spin rate from periodic phase-demodulated radar features	2013	
US10775492B2	Spin-axis inference from receiver-pair delays and separations	2013	
US10338209B2	Camera/radar calibration and tracking through missing data	2015	also US11016188B2
US11573082B2	Effective-altitude estimation by matching environmental air density	2019	
US12528005B2	Weather-based range prediction, club selector	2023	
US20160306036A1	Putting-green tracking	2013	Published application
US20180239012A1	Antenna with boresight optical system	2013	Published application

D.4 Full Swing Golf

Patent	Subject	Prio.	Notes
US11311789B2	CW/FMCW radar and non-uniform antenna array; grant of US2020/0147470A1	2018	Also US11844990B2
US11875517B2	Frame-difference tracking and calibrated golf-surface impact location	2020	also US12354282B2
US8758103B2	Fixed-plane crossing and image-based translation/rotation; IR embodiment	2009	also US9616346B2, US11033826B2
US8926416B2	Strobed-image spin with separate two-plane timing/position sensing	2007	also US10058733B2
US8414408B2	Ball-permeable screen, ball return	2009	also US8834284B2

Caution: US10605910B2/US11086008B2 (Alphawave Golf) and US11565166B2 (individual) surface in “Full Swing” text searches but are unrelated assignees.

Historical Light-Curtain Method: US5333874A (indexed priority 1992) describes two receiver planes and a post-screen rebound measurement used with stored spin values. Kiraly and Wintriss appear among the inventors; shared inventorship does not establish Foresight ownership. The index lists an individual original assignee and Full Swing as current assignee, rather than a Foresight portfolio entry. This is a rebound-based inference, not direct image tracking of a rotating ball surface.

D.5 Garmin

US11351436B2 — “Hybrid golf launch monitor” (indexed priority 2019): two laterally separated cameras whose capture timing depends on clubhead speed and a swing trigger. Claim 1 describes the two-camera arrangement; claim 9 adds a radar-based trigger and clubhead speed estimate. This disclosure does not establish that the Approach R10 implements the claimed arrangement. For scope comparison, other Garmin disclosures are US8647214B2 (2008, associating inertial swing data with ball start/rest positions) and US7467060B2 (2006, stride-based estimation for cyclical motion). The latter’s first claim uses acceleration and stride duration; it should not be presented as a ball-flight or golf-swing reconstruction method. These entries do not establish the completeness of Garmin’s portfolio.

D.6 Rapsodo Pte. Ltd.

Patent	Subject	Prio.	Notes
US9955126B2	Radar-speed-based camera triggering for a projectile entering the image region	2015	
US11170513B2	Surface-feature template matching for ball-spin estimation	2016	
US11747461B2	Radar-track prediction; camera/radar association disclosed	2018	
US20210299540A1	Scanned-club model with camera/radar swing representations	2018	Published application
US20230065614A1	Neural-network spin estimation from radar features	2021	Published application
US20230364468A1	Neural estimation from separate ball-image and swing-radar representations	2021	also club-side US20230070986A1
US12169941B1	Target-plane crossing localization	2024	
US12586248B2	Camera/radar depth inference using radial speed, its slope and zero-speed timing	2024	also US12548194B2
US12158517B1	Imager triggering from a two-tone radar phase-difference zero crossing	2024	

D.7 Camera Vendors: Foresight/Wintriss, Creatz/Uneekor, Golfzon

Foresight Sports, Wintriss and WAWGD Disclosures

Patent	Subject	Prio.	Notes
US7292711B2	Image-based ball motion and surface-feature spin disclosure	2002	
US7324663B2	Image rotation/correlation search and alignment correction	2002	
US7497780B2	Integrated trigger, capture, calculation and display	2006	
US7540500B2	Foldable monitor housing	2006	
US7641565B2	Ball-placement detection / auto-arm	2006	
US8951138B2	Club path and face orientation around impact	2012	
US9737757B1	Alignment-stick target alignment	2016	
US10639537B2	Associating observed flight/landing tracks with launch-monitor predictions	2018	

Creatz Inc. (Uneekor)

Patent	Subject	Prio.	Notes
US9448067B2	Multi-camera (unsynchronized) trajectory via projection-plane intersection	2011	
US9605960B2	Single-camera trajectory from an image-defined plane and image-size database	2011	
US9752875B2	Iterative exposure/gain control using reference regions of different reflectance	2011	
US10247553B2	Start sensor: ball state at first movement	2011	
US10587797B2	Ball-image brightness compensation for spin marks	2016	
US10776929B2	Ball/camera-position and club-dependent imaging region; predicted-motion embodiment	2016	
US11191998B2	Speed/angle-based spin estimates correct or replace mark-derived spin	2018	
US12008770B2	Dimple-position comparison with lighting correction for spin	2020	

Uneekor's marking page also lists the four licensed Wintriss/Foresight patents (US7497780, US7292711, US7641565, US7324663) [93, 4].

Golfzon Co., Ltd. (Sensing Core)

Patent	Subject	Prio.	Notes
US9242158B2	Two-stage sensing → simulation (latency hiding)	2011	
US9333409B2	Ball-candidate 2D trajectories used to derive 3D motion	2011	Also US9333412B2
US9162132B2	Image-based ball recognition and shot detection on a hitting area	2011	
US9514379B2	Difference images and estimated club trajectory inform ball-spin estimation	2011	
US10045008B2	Alternating stereo capture with estimated intermediate images	2011	
US11364428B2	Spin fit by trajectory iteration vs. observed positions	2017	
US12002222B2	Database-derived loft/backspin and motion-vector spin-axis inference	2016	
US12599828B2	Marker-constellation spin between frames	2021	
US12605593B2	Next-frame image-search region from a projected 3D motion bound	2021	
US12478849B2	Single-camera putting-mat sensing	2020	
US20230347209A1	Stereo impact position on club face	2020	Published application

D.8 Acushnet (Titleist) — Selected Optical Disclosures

Patent	Subject	Prio.	Notes
US4136387A	Enhanced-point optical estimates of translation and rotation	1977	
US5471383A	Shutterable cameras + retroreflective markers	1992	
US5501463A	Stereo + club/ball dots: face, path, contact location	1992	
US6241622B1	Portable camera/lighting system and trajectory computation	1998	Also US6533674B1, US6616543B1, US7086955B2
US6500073B1	Image-derived launch conditions and computed trajectory	1992	
US6758759B2	Separate club and ball camera arrangements	2001	
US7143639B2	Integrated club/ball cameras, illumination and trigger layout	2004	Also US7395696B2, US8500568B2, US8556267B2

Patent	Subject	Prio.	Notes
US10668350B2	3D-image reconstruction; light-field camera in claim 1	2017	

D.9 Others and Foundational Radar Art

United States Golf Association: US6186002B1 (indexed priority 1998) is assigned in the publication record to the USGA, not Acushnet. It describes fitting lift and drag coefficients from launches with specified initial conditions and timed ballistic light-screen crossings, then relating those coefficients to Reynolds number and spin ratio. It is a useful experimental-modeling reference, not evidence that arbitrary launch-monitor outputs uniquely identify the aerodynamic coefficients.

AccuSport: US7209576B2 (indexed priority 2002; original assignee AccuSport International Inc.) describes golf-ball image processing, including marked-surface spin estimation and image calibration.

SkyTrak / SkyHawke: US12515116B2 (2023, swing-tag + launch-monitor fusion display) is one relevant disclosure. This catalog does not establish the complete SkyHawke portfolio or the patent marking of every SkyTrak model. No verified entries for **Zelocity**, **GolfTek**, **Ernest Sports** or **ProTee United** are supplied here; that search limitation establishes neither the absence of patents nor the technical ancestry of their products. **Voice Caddie (Ucomm):** US10338212B2 (2014) specifies in claim 1 club-speed calculation from time-domain processing and ball-speed calculation from frequency-domain processing of an output generated from a mixed Doppler return. **Sports Sensors (Dilz):** US6079269A (1997) describes a short-range sports-object speed sensor, including a ball-catching application; it should not be labeled the Swing Speed Radar product patent. US6898971B2 (2000) addresses short-range speed measurement, including clubhead speed; US8007367B2 (2005) explicitly addresses swing duration and clubhead speed. These are different measurement tasks.

Weibel Scientific: EP1735637B1 (2004) describes simultaneous CW and FMCW tracking with three receivers, phase-based angles and maintained track records. Calling it only a CW-speed method omits a material part of the arrangement. **Applied Concepts:** US10935657B2 (2019) estimates projectile spin from radar spectral shoulder frequencies adjacent to a peak. Its relevance extends beyond golf; the disclosure is not evidence of a particular product's implemented accuracy.

Design implication

The catalog compares observations and assumptions behind similarly named outputs. Radar periodicity, image rotation and trajectory fitting need different calibration and ambiguity tests; a grant establishes no accuracy benchmark. For each implementation, retain the measured signals and model dependencies when reporting derived or estimated quantities. The rights boundaries in Section 7.8 apply throughout this appendix.

Appendix E

Radar Clubhead Kinematics: Motion and Observability

A useful club-motion model must connect what the sensor records to what a golfer wants to know: which point on the head is moving, how the face is turning, and how confidently those quantities are known near impact. Screw theory provides a compact representation of rigid motion, but choosing that representation does not make the motion observable. This appendix develops the measurement equations, exposes an exact ambiguity in instantaneous single-origin Doppler data, and specifies what an implementer must add and validate before reporting club-delivery parameters. The estimator described below is a research design, not a demonstrated IWR6843 golf instrument. The point-tracking framework in Section B.2 is a starting point; a rigid-body estimator also needs orientation, a calibrated head reference, and an explicit account of unresolved motion.

E.1 Context: Definitions Are Not an Estimator Specification

TrackMan defines club speed at the head’s geometric center immediately before first contact, while its path and attack-angle definitions use maximum compression as their time reference [84, 82]. These definitions specify intended outputs, not the complete sensing and estimation algorithm. The manufacturer’s discussion of a three-dimensional club silhouette and its patents describe additional information beyond one list of radial velocities; they do not establish that the particular Doppler-only solve below reconstructs a head pose [77, 90]. Nor does an algorithm’s appearance in a patent establish its implementation or independently measured accuracy in every product version. This appendix makes no claim about an undisclosed vendor state representation or the novelty or legal scope of the proposed design.

Instantaneous screw axes also have a distinct use in biomechanics. Vena et al. studied optically reconstructed pelvis, shoulder, and left-arm motion: Part 1 reports predominantly rotational contributions to marker velocity in those segments, and Part 2 reports the expected segment sequence in two of five subjects [97, 98]. Those observations neither validate a radar clubhead estimator nor establish a universal axis near the hands. The publisher abstracts and the visible Part 1 mathematical appendix were checked for this review; the subscription main texts were not accessed. The robotics conventions below are independently supported by the authors’ explanation of body and spatial twists [40]; Murray, Li, and Sastry remain a general reference [44].

E.2 Rigid Motion With Declared Frames and Reference Points

Assume a rigid clubhead over the interval being modeled, a stationary radar origin, and a right-handed Cartesian sensor frame. This is a head model: shaft bending and deformation during contact require separate states or an explicitly bounded approximation. Let O be a declared body-fixed reference point, $\mathbf{p}_O$ its sensor-frame position, $\mathbf{v}_O = \dot{\mathbf{p}}_O$ its velocity, and $\boldsymbol{\omega}$ the head’s angular velocity

expressed in the same frame. Use linear-first ordering throughout:

$$\xi_O = \begin{bmatrix} \mathbf{v}_O \\ \boldsymbol{\omega} \end{bmatrix} \in \mathbb{R}^6. \quad (\text{E.1})$$

This six-component velocity description becomes a body or spatial Lie-algebra twist only after the reference and expression frame are specified below. For a body-fixed point whose instantaneous sensor-frame offset from O is $\mathbf{r}$,

$$\mathbf{v}(\mathbf{r}) = \mathbf{v}_O + \boldsymbol{\omega} \times \mathbf{r}. \quad (\text{E.2})$$

Moving the reference to another body-fixed point Q therefore changes the linear component to $\mathbf{v}_Q = \mathbf{v}_O + \boldsymbol{\omega} \times (\mathbf{p}_Q - \mathbf{p}_O)$. The physical velocity field is unchanged; its six numerical coordinates are not invariant to changes of reference or frame.

For $\|\boldsymbol{\omega}\| > 0$, the instantaneous screw axis is the line

$$\begin{aligned} \mathbf{p}_{\text{axis}}(a) &= \mathbf{p}_O + \mathbf{r}_{\text{ISA}} + a\hat{\boldsymbol{\omega}}, & \mathbf{r}_{\text{ISA}} &= \frac{\boldsymbol{\omega} \times \mathbf{v}_O}{\|\boldsymbol{\omega}\|^2}, \\ h &= \frac{\boldsymbol{\omega} \cdot \mathbf{v}_O}{\|\boldsymbol{\omega}\|^2}, & \hat{\boldsymbol{\omega}} &= \frac{\boldsymbol{\omega}}{\|\boldsymbol{\omega}\|}. \end{aligned} \quad (\text{E.3})$$

Here a is distance along the axis and h is signed axial translation per radian. Substitution into Equation (E.2) gives velocity $h\boldsymbol{\omega}$ at every point on the axis, which verifies the construction. Pure translation has no unique finite axis, rest has no preferred axis, and near-zero angular speed makes the axis and pitch numerically sensitive. An instantaneous axis is not a uniquely defined swing plane: its moving line need not remain normal to one plane, and a head-point trajectory need not be planar. A plane estimate needs its own declared point trajectory, fitting interval, residual, and uncertainty. Low pitch or an axis near the grip can be hypotheses to test; neither is an assumption that the cited segment study licenses for every club swing.

E.2.1 Body and Spatial Twists for Pose Integration

Let $T = \begin{bmatrix} R & \mathbf{p}_O \\ 0 & 1 \end{bmatrix}$ map body coordinates to the sensor frame, with $R \in SO(3)$. For a linear-first pair $V = (\mathbf{v}, \boldsymbol{\omega})$, define $V^\wedge = \begin{bmatrix} [\boldsymbol{\omega}]_\times & \mathbf{v} \\ 0 & 0 \end{bmatrix}$, where $[\mathbf{a}]_\times \mathbf{b} = \mathbf{a} \times \mathbf{b}$. Then

$$\begin{aligned} V_b &= (R^\top \mathbf{v}_O, R^\top \boldsymbol{\omega}), & V_b^\wedge &= T^{-1} \dot{T}, \\ V_s &= (\mathbf{v}_O - \boldsymbol{\omega} \times \mathbf{p}_O, \boldsymbol{\omega}), & V_s^\wedge &= \dot{T} T^{-1}. \end{aligned} \quad (\text{E.4})$$

These are related by the adjoint of T [40]. A constant body-twist step uses $T_{k+1} = T_k \exp(V_{b,k}^\wedge \Delta t)$; a constant spatial-twist step uses $T_{k+1} = \exp(V_{s,k}^\wedge \Delta t) T_k$. For varying motion these are integration approximations; the increments must be composed in time order. Inserting sensor-frame $\mathbf{v}_O$ directly into the right-multiplying body update generally gives the wrong trajectory. Likewise, a logarithm of two measured poses describes a finite interframe displacement; dividing it by the interval is not automatically an unaliased instantaneous angular velocity.

E.3 The Measurement Model and Its Exact Ambiguity

First consider an ideal monostatic measurement represented by a single origin: a localized scattering point $\mathbf{p}_i \neq 0$ has sight line $\hat{\mathbf{u}}_i = \mathbf{p}_i / \|\mathbf{p}_i\|$, offset $\mathbf{r}_i = \mathbf{p}_i - \mathbf{p}_O$, and radial velocity z_i positive away

from the radar. Assume its Doppler return represents the instantaneous velocity of head material there. The conditional measurement equation is

$$z_i = \hat{\mathbf{u}}_i^\top \mathbf{v}_O + (\mathbf{r}_i \times \hat{\mathbf{u}}_i)^\top \boldsymbol{\omega} + \epsilon_i. \quad (\text{E.5})$$

With the ordering in Equation (E.1),

$$\mathbf{z} = A\xi_O + \boldsymbol{\epsilon}, \quad A_i = [\hat{\mathbf{u}}_i^\top \mid (\mathbf{r}_i \times \hat{\mathbf{u}}_i)^\top]. \quad (\text{E.6})$$

Linearity holds conditional on the positions, associations, and rigid-motion model. It does not say that six independent unknowns can be recovered. Because $\mathbf{p}_i \times \hat{\mathbf{u}}_i = 0$, the same equation factors as

$$\begin{aligned} \mathbf{z} &= U(\mathbf{v}_O - \boldsymbol{\omega} \times \mathbf{p}_O) + \boldsymbol{\epsilon}, \\ A &= U[I \mid [\mathbf{p}_O]_\times], \quad \text{rank}(A) \leq 3, \end{aligned} \quad (\text{E.7})$$

where row i of U is $\hat{\mathbf{u}}_i^\top$. For any $\delta\boldsymbol{\omega}$, the perturbation $\delta\mathbf{v}_O = \delta\boldsymbol{\omega} \times \mathbf{p}_O$ leaves every predicted Doppler value unchanged. This is an exact three-dimensional null family even with arbitrarily many noncoplanar localized detections and noise-free measurements. Nearly parallel sight lines can further weaken the remaining three combinations; they do not explain away the structural nullspace. The observed combination is the translational component of V_s , not necessarily the speed of the head center.

Key point

One origin's instantaneous Doppler rows cannot determine the complete club velocity field under this model. Better signal-to-noise ratio or more rows at that same origin cannot remove this ambiguity. Range and angle histories, known feature geometry, independent orientation measurements, or sufficiently informative additional sensor geometry can supply information outside these rows; their contribution must appear in the actual measurement model.

For example, known and correctly associated noncollinear body features with resolved three-dimensional positions can constrain pose; their time history can then constrain motion. Unlabeled specular detections are not automatically such features. Two separated monostatic stations can generically raise the Doppler-only rank to five, but retain rotation about their baseline as a null direction with its corresponding translational change. Three noncollinear station origins can generically reach six with sufficient point/sight-line diversity. These are geometric possibilities, not guarantees of adequate precision. A multiple-input multiple-output (MIMO) array also requires its actual transmit/receive path model: a bistatic path derivative involves both ray directions. Twelve virtual array channels are not twelve independent monostatic stations, and the single-origin bound is not a theorem that every near-field, coherent, or feature-tracking radar architecture is limited to three observable motion coordinates.

E.3.1 What Least Squares and Covariance Actually Provide

For fixed A and zero-mean measurement error with known positive-definite covariance R_z , generalized least squares minimizes $(\mathbf{z} - A\xi)^\top R_z^{-1}(\mathbf{z} - A\xi)$. If A has full column rank, its estimator covariance is $(A^\top R_z^{-1}A)^{-1}$ under that model. This inverse does not exist for the six-unknown single-origin problem. A pseudoinverse selects a convention for the unobserved components; a zero eigenvalue in a pseudoinverse covariance is not evidence of zero uncertainty there. Report the identifiable combinations and the remaining nullspace, or explicitly state the extra observations or priors that define a full posterior.

Inspect singular values after noise whitening and declared parameter scaling, for example $R_z^{-1/2}AD$ with D converting dimensionless unknowns into chosen linear- and angular-velocity scales. Raw singular values mix meters per second with radians per second, so an unexplained threshold is not a physical observability criterion. Uncertain positions make A uncertain; position–Doppler correlations, calibration bias, ambiguous associations, and model discrepancy require joint propagation or an appropriate errors-in-variables model. Robust losses such as Huber or Cauchy generally require iterative fitting and their own uncertainty treatment. They do not turn an incorrect scattering model into a calibrated rigid-body measurement.

E.4 What Representative Hardware Adds

E.4.1 OPS243-A: Radial-Speed Information

The manufacturer’s OPS243 product brief distinguishes the Doppler-only A model from the range-capable C model [52]. Without per-return range and direction, the A output alone cannot assemble the located rows above. A Doppler spectrum is a scattering-amplitude-weighted signal, not a uniform sample of clubhead material velocities. Its peak need not always be the toe, its midpoint need not be the geometric-center speed, and its width is not a uniquely calibrated angular speed. For a stated example of 30 kps, 128 samples, and 24 GHz, $\Delta v = cf_s/(2f_cN) \approx 1.46$ m/s, or 3.27 mph, before accounting for the spectral window. Zero-padding samples the spectrum more finely but does not add the observation time needed to resolve closer velocities. A percentile or spectral-width feature may be useful after empirical calibration across aspect, club, speed, and clutter; it should retain that provenance.

E.4.2 K-LD7: Geometry and Operating Envelope

The K-LD7 Revision B datasheet specifies range, radial speed, and one angular coordinate, with a maximum speed setting of 100 km/h and a 29 ms cycle at that setting [63]. The speed limit is approximately 27.8 m/s, not a limit on total three-dimensional speed independent of viewing direction. A head moving at 50 m/s travels 1.45 m during that cycle; its radial component may alias even though another orientation does not. A single angular coordinate also does not localize arbitrary three-dimensional scatterers. Neither these specifications nor a frame’s angle output establishes that high-speed ball returns remain valid angle measurements after Doppler aliasing. Qualification would need the chosen geometry, waveform, association, and motion envelope.

E.4.3 IWR6843: A Coupled Waveform Budget

The IWR6843 has three transmitters, four receivers, a 60–64 GHz band, and a maximum specified ramp rate of 250 MHz/μs in Revision F [68]. Array angle estimation and multiplexing depend on antenna geometry and processing; they are not generically synonymous with monopulse [59]. Let T_c be the start-to-start chirp interval, n_T the number of cyclic time-division-multiplexed transmitters, and N the number of repeated samples *per transmitter*. For uniform slow-time sampling, wavelength λ , and a conventional unambiguous Doppler FFT,

$$T_r = n_T T_c, \quad |v_r| < \frac{\lambda}{4T_r}, \quad \Delta v = \frac{\lambda}{2NT_r}, \quad T_{\text{obs}} \approx NT_r. \quad (\text{E.8})$$

These follow from the round-trip phase increment $4\pi v_r T_r / \lambda$ and the sampled Fourier frequency grid [67, 59]. At the illustrative $\lambda = 5$ mm, $T_c = 25$ μs, and $N = 128$:

Transmit Schedule	Speed Limit (m/s)	Δv (m/s)	T_{obs} (ms)
One transmitter	50.0	0.781	3.2
Three-transmitter TDM	16.7	0.260	9.6

The table is arithmetic, not a validated firmware configuration; frame idle time and processing can lower the output rate further. At the sampling boundary the signed velocity is ambiguous, so a 50 m/s limit provides no margin for a 50 m/s return. For three-transmitter TDM to exceed that unambiguous radial speed at this wavelength requires $T_c < 8.33 \mu\text{s}$. Sweeping 4 GHz already needs at least 16 μs at the stated maximum ramp rate, before settling and idle time. Thus those requirements cannot be combined in that simple waveform; ambiguity-resolution schemes or other multiplexing designs need their own analysis and validation.

Nominal range resolution is $c/(2B) \approx 3.75 \text{ cm}$ for an effective sampled bandwidth $B = 4 \text{ GHz}$ [67]. It does not guarantee three or four distinct returns from a head: projected radial extent, reflectivity, angular resolution, windowing, and detection thresholds also matter. Even over 3.2 ms, a 50 m/s radial return migrates 16 cm, more than four such bins. Acceleration, changing aspect, range migration, and inter-transmitter phase changes must therefore be included in the signal model or shown to be negligible for a bounded operating case. TI specifically describes motion-phase correction before TDM angle estimation [59]. Select sampled bandwidth, slope, ADC start/sample time, IF bandwidth, settling, transmitter schedule, output timing, and processing load together [67]; a bandwidth, frame rate, and velocity ceiling cannot be independently promised.

E.5 An Estimation Recipe With Explicit Acceptance Conditions

Step 1 — Preserve Geometry, Timing, and Detection Uncertainty

Retain the raw signal or sufficient diagnostics to check aliasing, motion compensation, and false detections. Choose CFAR training/guard cells and any order-statistic variant against recorded clutter and false-alarm requirements; no detector is universally preferable for every impact scene. For a declared right-handed sensor frame with range ρ , azimuth θ , and elevation ϕ , convert spherical coordinates to Cartesian positions:

$$\mathbf{p} = \rho \begin{bmatrix} \cos \phi \cos \theta & \cos \phi \sin \theta & \sin \phi \end{bmatrix}^T. \quad (\text{E.9})$$

Propagate the full range/angle covariance through this mapping and preserve relevant correlations with Doppler. A reported FFT bin spacing, a precision estimate, and demonstrated accuracy are different quantities. Assign timestamps to the acquisition intervals; a frame output timestamp is not an instantaneous sample of all returns.

Step 2 — Associate Returns With a Head Model

Use range, radial velocity, geometry, temporal continuity, and calibrated uncertainties jointly to distinguish head, shaft, ball, and body returns. A shaft point is not invariably slower in radial speed or nearer the sensor than the head, and speed alone cannot guarantee removal of body clutter. An SNR-weighted detection centroid can migrate as aspect changes; its derivative includes that migration and is not automatically the velocity of a body-fixed point. Choose O through a calibrated geometric model or identified body feature, and distinguish material-point velocity from apparent glint motion. If correspondence or head geometry is unresolved, retain multiple hypotheses or withhold outputs that depend on it.

Step 3 — Fit the Identifiable Quantities First

Use Equation (E.7) to fit the three-component combination $\mathbf{b} = \mathbf{v}_O - \boldsymbol{\omega} \times \mathbf{p}_O$ when the weighted sight-line matrix supports it. A smaller observable subspace may be all the data justify. Record residuals, scaled singular values, associations, and the acquisition interval. Do not publish an arbitrary six-component pseudoinverse solution as a fully measured twist. A full solve needs additional, explicitly modeled observations, such as calibrated feature-position histories or independent orientation information.

Step 4 — Establish Temporal Observability

A changing sight line is not a proof that smoothing recovers six arbitrary motion functions. For Doppler-only histories, even a constant rotation of every head position and velocity about the sensor preserves all radial histories while changing the target-relative motion; both trajectories can be smooth. Angle or feature-position observations may distinguish them, which is precisely why those observations must be included rather than used only as fixed coefficients in a velocity solve. Analyze the linearized multi-time measurement model with the chosen state transitions, geometry, calibration states, and priors. Report structural nullspaces separately from poor conditioning and from uncertainties controlled chiefly by a prior. Use withheld trajectories and deliberate near-degeneracies to test the claimed operating region.

Step 5 — Estimate Pose and Motion Consistently

An $SE(3)$ filter or batch smoother can combine pose, velocity, calibration, and feature observations using Equation (E.4). Feed raw residuals where practical, so the estimator retains their actual information and correlations; a per-frame diagnostic fit can still be useful. A backward smoother uses future measurements and must be labeled offline if they are unavailable at the desired reporting time. Select process uncertainty against observed dynamics, not an unsupported universal acceleration of one mile per hour per millisecond. Low-pitch or grip-proximity penalties are optional model assumptions whose sensitivity must be reported; they cannot resolve an unobservable quantity through measurement alone and become singular near zero angular speed if written using Equation (E.3) without safeguards. A prior that is weak in observed directions may completely determine an unobserved one.

Step 6 — Define the Impact Event and Model Boundary

Synchronize the radar, any optical reference, and the contact-event measurement, including sound-propagation and trigger latency where an acoustic trigger is used. Distinguish the last resolved pre-contact state, first contact, maximum compression, and separation. A prediction from the last pre-contact sample to another event is an extrapolated estimate with event-time and model uncertainty. The manufacturer's historical club-data explanation explicitly discusses using pre-impact data for an event-time definition [77]; the chosen product definition must accompany any comparison. Do not assume that every head is exactly rigid until a universal 500 μs switch, or extend a pre-contact process model through collision and turf contact without validation. Fit pre- and post-contact intervals separately if the purpose is to study collision-induced changes.

Step 7 — Report Only Supported Delivery Quantities

Let the target frame be right-handed with x down the target line, y to the golfer's left when looking down that line, and z upward. For a calibrated body-fixed point with body offset $\mathbf{r}_{gc}^b$,

first compute $\mathbf{v}_{gc} = \mathbf{v}_O + \boldsymbol{\omega} \times R\mathbf{r}_{gc}^b$ and express it in that target frame. Then speed is $\|\mathbf{v}_{gc}\|$, path positive to the right is $\text{atan2}(-v_y, v_x)$, and attack angle positive upward is $\text{atan2}(v_z, \sqrt{v_x^2 + v_y^2})$. Path is undefined for zero horizontal velocity, and the velocity direction is undefined at rest. A calibrated geometric-center offset, an anatomical grip point, and a changing radar centroid are not interchangeable.

Face closure needs a definition and orientation information. For a known target-frame unit face normal $\mathbf{n}$, rigid rotation gives $\dot{\mathbf{n}} = \boldsymbol{\omega} \times \mathbf{n}$. Its mathematical horizontal azimuth $\gamma = \text{atan2}(n_y, n_x)$ satisfies

$$\dot{\gamma} = \frac{n_x \dot{n}_y - n_y \dot{n}_x}{n_x^2 + n_y^2}, \quad n_x^2 + n_y^2 > 0. \quad (\text{E.10})$$

This generally differs from $\boldsymbol{\omega}$ projected onto the shaft axis. A right-positive face-angle convention reverses this azimuth sign; a label such as closing also needs the handedness and stated convention. A full head frame requires more orientation information than one normal, and face angle at the contact location may additionally require head geometry and impact location. Thus closure rate is not a free Doppler-only output or a parameter whose product availability can be declared universally exclusive.

Estimate swing plane and swing direction only through a specified trajectory-plane fit, with its residual and fit window. A low point requires an observed or modeled trajectory with $v_z = 0$ and a local height minimum; a vertical-velocity zero alone can be a maximum. A difference between pre- and post-impact angular velocities is a net kinematic change. Attributing it to gear effect requires an impact/contact model, timing, inertia, and consideration of continuing shaft/grip and other contact loads.

Propagate joint state, calibration, association, timing, and model uncertainty into each output and disclose unresolved directions or dependence on priors. Keep the book's distinction between sensor observations, quantities derived from them, and model-based estimates; merely changing the state representation promotes no output into a measured category. Kinematics alone also identifies neither golfer torques nor a control strategy: a hand-axis prior must not be presented as evidence that the golfer actually produced that motion by the assumed mechanism.

E.6 Validation That Can Falsify the Proposed Estimator

The following is a proposed qualification sequence, not a report of completed hardware or human testing. Use the release and evidence discipline of Chapter 11.

1. **Analytic and Synthetic Checks.** Verify the exact null family, frame conversions, pure-translation limit, and waveform arithmetic before fitting realistic data. Simulations should include noise, glint changes, aliasing, missed detections, correlated errors, and deliberately unobservable cases, and should test empirical interval coverage as well as point error. Recovering truth in a simulation generated with the same restrictive prior cannot establish that the prior holds for golfers.
2. **Independent Rig Reference.** Use synchronized calibrated encoders or optical tracking for pose and velocity on a rigid-motion rig. A fixed-axis pendulum supplies a known axis only if the bearings, mounting, head rigidity, and coordinate calibration support that model; its angular history is not known merely because it is called a pendulum. Test translations, multiple axes, low angular speeds, varying aspects, and moving-pivot cases as well as the easy planar case.

3. **Independent Cross-System Comparison.** Match the head point, event time, coordinate convention, club, environment, and uncertainty of the reference. A commercial monitor is a comparator, not automatically ground truth; unavailable or model-derived comparator outputs cannot validate an independent direct measurement. Report bias, limits of agreement, repeatability, missing-output rates, and uncertainty coverage against predefined requirements, including difficult cases.
4. **Mechanics Consistency With Stated Assumptions.** Check geometric identities only where their planar or rigid-body assumptions apply. An identity satisfied by construction is a software consistency check, not independent physical validation. Do not discard shots merely because a simplified smash-factor or swing-plane model is violated: inspect reference-point mismatch, contact, alignment, and model inadequacy, and preserve the rejection rule and excluded cases.

Design implication

The value of a screw representation is a common account of rigid motion and point transport. Its practical benefit depends on calibrated geometry, sufficient observations, consistent timing, and validated uncertainty. Declare what the data constrain before reporting a complete club state, and keep the inferred motion separate from claims about the forces or intentions that produced the swing.

Bibliography

Peer-reviewed literature and books

- [1] “Agreement between the FlightScope Mevo+ and TrackMan 4 launch monitors indoors”. In: *Science and Medicine in Sport (ScienceDirect)* (2025). URL: <https://www.sciencedirect.com/science/article/pii/S2772696725000420> (visited on 07/31/2026).
- [2] P. W. Bearman and J. K. Harvey. “Golf Ball Aerodynamics”. In: *Aeronautical Quarterly* 27.2 (1976), pp. 112–122. URL: <https://www.cambridge.org/core/journals/aeronautical-quarterly/article/abs/golf-ball-aerodynamics/67FE0903DB1CC12001F1ED1B1261C4B9> (visited on 07/31/2026).
- [3] J. M. Bland and D. G. Altman. “Agreement Between Methods of Measurement with Multiple Observations Per Individual”. In: *Journal of Biopharmaceutical Statistics* 17.4 (2007), pp. 571–582. DOI: 10.1080/10543400701329422.
- [6] V. C. Chen. *The Micro-Doppler Effect in Radar*. 2nd ed. Standard treatment of Doppler signatures of rotating and vibrating rigid bodies. Artech House, 2019.
- [7] A. Cochran and J. Stobbs. *Search for the Perfect Swing*. Golf Society of Great Britain, 1968. URL: <https://archive.org/details/searchforperfect0000coch> (visited on 07/31/2026).
- [8] R. Cross. *Golf physics: oblique impact experiments*. See also Cross and Nathan, *Scattering of a ball by a bat in the limit of small deformation*, <https://arxiv.org/pdf/1610.03464>. University of Sydney. URL: <https://www.physics.usyd.edu.au/~cross/GOLF/GOLF.htm> (visited on 07/31/2026).
- [29] E. Henrikson, P. Wood, C. Broadie, and T. Nuttall. “The Role of Friction and Tangential Compliance on the Resultant Launch Angle of a Golf Ball”. In: *Proceedings* 49.1 (2020), p. 27. DOI: 10.3390/proceedings2020049027.
- [36] T. P. Jorgensen. *The Physics of Golf*. 2nd ed. Origin of the D-plane model. Springer / AIP Press, 1999.
- [39] R. J. Leach, S. E. Forrester, A. C. Mears, and J. R. Roberts. “How valid and accurate are measurements of golf impact parameters obtained using commercially available radar and stereoscopic optical launch monitors?” In: *Measurement* 112 (2017). Open access mirror: https://repository.lboro.ac.uk/articles/journal_contribution/9562799, pp. 125–136. DOI: 10.1016/j.measurement.2017.08.009. URL: <https://www.sciencedirect.com/science/article/abs/pii/S0263224117305079> (visited on 07/31/2026).
- [40] K. M. Lynch and F. C. Park. *Modern Robotics: Twists, Part 2 of 2*. Author video transcript accompanying the robotics textbook. URL: <https://modernrobotics.northwestern.edu/nu-gm-book-resource/3-3-2-twists-part-2-of-2/> (visited on 09/30/2026).
- [44] R. M. Murray, Z. Li, and S. S. Sastry. *A Mathematical Introduction to Robotic Manipulation*. Standard reference for twists, screws, and the geometry of $SE(3)$. The author archive reports that the publisher withdrew the online book PDF in January 2020; https://www.cds.caltech.edu/~murray/mlswiki/index.php?title=Main_Page. CRC Press, 1994.

- [53] A. R. Penner. “The physics of golf”. In: *Reports on Progress in Physics* 66.2 (2003), pp. 131–171. DOI: 10.1088/0034-4885/66/2/202. URL: <https://iopscience.iop.org/article/10.1088/0034-4885/66/2/202> (visited on 07/31/2026).
- [58] S. J. Quintavalla. “A generally applicable model for the aerodynamic behavior of golf balls”. In: *Science and Golf IV: Proceedings of the World Scientific Congress of Golf*. Basis of the USGA Indoor Test Range coefficient models. 2002. URL: <https://www.usga.org/content/dam/usga/pdf/Equipment/ITR-test-conditions-2028-ODS.pdf> (visited on 07/31/2026).
- [65] A. J. Smits and D. R. Smith. “A new aerodynamic model of a golf ball in flight”. In: *Science and Golf II: Proceedings of the World Scientific Congress of Golf*. 1994. URL: <https://www.researchgate.net/publication/284037213> (visited on 07/31/2026).
- [97] A. Vena, D. Budney, T. Forest, and J. P. Carey. “Three-dimensional kinematic analysis of the golf swing using instantaneous screw axis theory, Part 1: methodology and verification”. In: *Sports Engineering* 13 (2011), pp. 105–123. DOI: 10.1007/s12283-010-0058-8. URL: <https://link.springer.com/article/10.1007/s12283-010-0058-8> (visited on 09/30/2026).
- [98] A. Vena, D. Budney, T. Forest, and J. P. Carey. “Three-dimensional kinematic analysis of the golf swing using instantaneous screw axis theory, Part 2: golf swing kinematic sequence”. In: *Sports Engineering* 13.3 (2011), pp. 125–133. DOI: 10.1007/s12283-010-0059-7. URL: <https://link.springer.com/article/10.1007/s12283-010-0059-7> (visited on 08/01/2026).
- [100] “Within- and between-session reliability of TrackMan 4 launch monitor variables in high-level golfers”. In: *Journal of Sports Sciences* (2024). DOI: 10.1080/02640414.2024.2314864. URL: <https://www.tandfonline.com/doi/full/10.1080/02640414.2024.2314864> (visited on 07/31/2026).
- [101] P. Wood, E. Henrikson, and C. Broadie. “The Influence of Face Angle and Club Path on the Resultant Launch Angle of a Golf Ball”. In: *Proceedings* 2.6 (2018), p. 249. DOI: 10.3390/proceedings2060249. URL: <https://www.mdpi.com/2504-3900/2/6/249> (visited on 10/01/2026).

Patents, portfolios, and IP records

- [4] Business Wire. *Foresight Sports and Uneekor Agree on License of Foresight Sports Patents Related to Portable Golf Launch Monitor Screen Technology*. 2024. URL: <https://www.businesswire.com/news/home/20240930838753/en/> (visited on 07/31/2026).
- [9] S. DeLeon, S. Nicora, and K. Wang. “Launch monitor”. US 11,311,789 B2. I. Full-Swing Golf. Granted from US 2020/0147470 A1; CW + FMCW dual-mode 24 GHz radar with non-uniform array; expires ~2039. Continuation US 11,844,990 B2. 2022. URL: <https://patents.google.com/patent/US11311789B2/en> (visited on 07/31/2026).
- [22] W. Gobush. “Method and apparatus to determine golf ball trajectory and flight”. US 6,500,073 B1. A. Company. Expired. 2002. URL: <https://patents.google.com/patent/US6500073B1/en> (visited on 07/31/2026).
- [23] W. Gobush, D. Pelletier, and C. Days. “Method and apparatus to determine object striking instrument movement conditions”. US 5,501,463 A. A. Company. Priority 1992; expired. 1996. URL: <https://patents.google.com/patent/US5501463A/en> (visited on 07/31/2026).

- [24] Golf Business News. *FlightScope wins patent infringement case against TrackMan in Germany*. 2022. URL: <https://golfbusinessnews.com/news/innovation-centre/flightscope-wins-patent-infringement-case-against-trackman-in-germany/> (visited on 07/31/2026).
- [32] H. Johnson. “Systems to track a moving sports object”. US 10,338,209 B2. E. U. L. (FlightScope). Fusion Tracking; priority 2015, expires ~2037. Continuation US 11,016,188 B2. 2019. URL: <https://patents.google.com/patent/US10338209B2/en> (visited on 07/31/2026).
- [33] H. Johnson. “Golf ball spin axis measurement”. US 10,775,492 B2. E. U. L. (FlightScope). Priority 2013; expires ~2035. 2020. URL: <https://patents.google.com/patent/US10775492B2/en> (visited on 07/31/2026).
- [34] H. Johnson, T. Johnson, and R. W. Rust. “Ball spin rate measurement”. US 9,868,044 B2. E. U. L. (FlightScope). Priority 2013; expires ~2034. Dielectric-lens phase demodulation. 2018. URL: <https://patents.google.com/patent/US9868044B2/en> (visited on 07/31/2026).
- [37] C. M. Kiraly and G. V. Wintriss. “Flight parameter measurement system”. US 7,292,711 B2. W. E. C. (W. N. / F. Sports). Priority 2002; **expired April 2025**. Sibling US 7,324,663 B2 expired August 2025. 2007. URL: <https://patents.google.com/patent/US7292711B2/en> (visited on 07/31/2026).
- [38] “Launch monitor system and a method for use thereof”. US 6,758,759 B2. A. Company. Priority 2001; expired 2022. Portable four-camera family: US 7,143,639 B2 (expired 2024), US 8,500,568 B2, US 8,556,267 B2; 3D imaging US 10,668,350 B2. 2004. URL: <https://patents.google.com/patent/US6758759B2/en> (visited on 07/31/2026).
- [43] “Method for determining coefficients of lift and drag of a golf ball”. US 6,186,002 B1. A. Company. Trajectory-fitting template for aerodynamic model calibration. 2001. URL: <https://patents.google.com/patent/US6186002B1/en> (visited on 07/31/2026).
- [66] “System and method for determining three-dimensional positional coordinates of a ball”. US 12,186,643 B2. T. A/S. Related sparse-array angle work: US 9,958,527 B2. 2025. URL: <https://patents.google.com/patent/US12186643B2/en> (visited on 07/31/2026).
- [72] “Timing determination in camera-based motion measurement”. US 12,401,909. Documents Gabor-filter dimple enhancement for spin tracking. 2025. URL: <https://patents.google.com/patent/US12401909B2/en> (visited on 07/31/2026).
- [80] TrackMan A/S. *Patents*. Virtual patent marking notice; not an exhaustive portfolio search. URL: <https://www.trackman.com/legal/patents> (visited on 10/01/2026).
- [88] F. Tuxen. “Determination of spin parameters of a sports ball”. US 8,845,442 B2. T. A/S. Priority 2005; PTA expiry ~2029. Continuation US 10,393,870 B2 (expires Dec. 2026); European sibling EP 1 698 380. 2014. URL: <https://patents.google.com/patent/US8845442B2/en> (visited on 07/31/2026).
- [89] F. Tuxen. “Method and a sensor for determining a direction-of-arrival of impingent radiation”. US 9,958,527 B2. TrackMan A/S. 2018. URL: <https://patents.google.com/patent/US9958527B2/en> (visited on 10/02/2026).
- [90] F. Tuxen. “System and method for determining a spin axis of a sports ball”. US 10,850,179 B2. T. A/S. Continuations US 11,446,546 B2 and US 11,938,375 B2. 2020. URL: <https://patents.google.com/patent/US10850179B2/en> (visited on 07/31/2026).
- [93] Uneekor, Inc. *Patents*. Product-specific virtual patent marking notice. URL: <https://uneekor.com/en-us/legal/patents> (visited on 10/01/2026).

- [99] “Virtual golf simulation apparatus and method”. US 9,242,158 B2. L. Golfzon Co. Two-stage latency-hiding simulation; to ~2032. 2016. URL: <https://patents.google.com/patent/US9242158B2/en> (visited on 07/31/2026).

Manufacturer technical documentation

- [12] FlightScope. *FlightScope X3C: Indoor Setup Requirements and Fusion Tracking*. URL: <https://flightscope.com/products/flightscope-x3c> (visited on 10/02/2026).
- [13] Foresight Sports. *Club Head Data: Measurements and Definitions*. Updated date; lie and closure-rate conventions. Dec. 8, 2025. URL: <https://help.foresightsports.com/hc/en-us/articles/47214673873811-Club-Head-Data-Measurements-Definitions> (visited on 10/04/2026).
- [14] Foresight Sports. *Ball and club data (spherical correlation spin measurement)*. URL: <https://foresightsports.eu/ball-club-data/> (visited on 07/31/2026).
- [15] Foresight Sports. *GCQuad launch monitor*. URL: <https://www.foresightsports.com/products/gcquad-launch-monitor> (visited on 07/31/2026).
- [16] Foresight Sports. *HMT head measurement technology*. Fiducial dot-count to data-tier mapping. URL: <https://www.foresightsports.com/hmt-head-measurement> (visited on 07/31/2026).
- [17] Foresight Sports. *How to apply and maintain club markers*. URL: <https://help.foresightsports.com/hc/en-us/articles/4408197030035> (visited on 07/31/2026).
- [18] Full Swing Golf. *KIT launch monitor technology*. URL: <https://www.fullswinggolf.com/kit-launch-monitor-technology/> (visited on 07/31/2026).
- [19] Garmin Ltd. *Accuracy of Approach R10 Radar*. URL: <https://support.garmin.com/id-ID/?faq=kj37Cgzvwm98hC9WPrIQm5> (visited on 10/02/2026).
- [20] Garmin Ltd. *Approach R50 launch monitor*. URL: <https://www.garmin.com/en-US/p/736810/> (visited on 07/31/2026).
- [21] Garmin Ltd. *Using a Titleist RCT Ball With the Approach R10*. URL: <https://support.garmin.com/fr-CA/?faq=COFCXdRAJv2m8r9MBtLrf8> (visited on 10/02/2026).
- [57] PlayBetter. *ProTee VX review and specifications*. URL: <https://www.playbetter.com/blogs/golf-simulator-reviews/protee-vx-review> (visited on 07/31/2026).
- [60] Rapsodo. *Titleist 2025 PRO V1x Golf Balls with RPT*. URL: <https://rapsodo.com/products/titleist-2025-pro-v1x-golf-balls-w-rpt> (visited on 10/02/2026).
- [64] SkyTrak. *What does the SkyTrak ST+ launch monitor measure?* URL: <https://www.skytrakgolf.com/pages/what-does-the-skytrak-st-launch-monitor-measure> (visited on 07/31/2026).
- [69] The Golf Wire. *FlightScope X3: multi-frequency radar with direct distance measurement and Fusion Tracking*. URL: <https://thegolfwire.com/326713-2/> (visited on 07/31/2026).
- [73] TrackMan A/S. *TrackMan News #5: Ball Flight Laws*. The D-plane and the 85/15 face/path weighting. 2009. URL: <https://www.yumpu.com/en/document/view/11652756/trackman-ball-flight-laws> (visited on 07/31/2026).
- [74] TrackMan A/S. *What Is Low Point?* May 30, 2024. URL: <https://www.trackman.com/blog/low-point> (visited on 10/04/2026).

- [75] TrackMan A/S. *Parameters: Carry (Tee to Green)*. Updated date; carry-flat convention. Aug. 7, 2025. URL: <https://support.trackmangolf.com/hc/en-us/articles/39726543090971-Parameters-Carry-Tee-to-Green> (visited on 10/04/2026).
- [76] TrackMan A/S. *Practice: Trackman Data Parameter Definitions*. Updated date; full-swing definitions consulted. Nov. 27, 2025. URL: <https://support.trackmangolf.com/hc/en-us/articles/5089892383515-Practice-Trackman-Data-Parameter-Definitions> (visited on 10/04/2026).
- [77] TrackMan A/S. *Club data definitions*. URL: <https://www.trackman.com/blog/golf/club-data-definitions> (visited on 07/31/2026).
- [78] TrackMan A/S. *Launch monitor technical specifications (TrackMan 4, TrackMan iO)*. URL: <https://www.trackman.com/golf/launch-monitors/tech-specs> (visited on 07/31/2026).
- [79] TrackMan A/S. *Patent: measuring the spin of a sports ball*. URL: <https://blog.trackmangolf.com/patent-measuring-the-spin-of-a-sports-ball/> (visited on 07/31/2026).
- [81] TrackMan A/S. *Spin loft and spin rate*. URL: <https://www.trackman.com/blog/golf/spin-loft> (visited on 07/31/2026).
- [82] TrackMan A/S. *TrackMan parameters explained*. URL: <https://www.trackman.com/blog/golf/40-trackman-parameters> (visited on 07/31/2026).
- [83] TrackMan A/S. *Two radars, one camera, zero doubt*. Optically Enhanced Radar Tracking (OERT). URL: <https://www.trackman.com/blog/golf/two-radars-one-camera-zero-doubt> (visited on 07/31/2026).
- [84] TrackMan A/S. *What is club speed?* Geometric-center reference-point definition. URL: <https://www.trackman.com/blog/golf/what-is-club-speed> (visited on 07/31/2026).
- [91] F. Tuxen. *How Trackman Combines Radar and Cameras for Superior Indoor Accuracy*. Vendor account; no independent accuracy validation implied. Sept. 10, 2026. URL: <https://www.trackman.com/blog/radar-and-cameras-for-superior-indoor-golf-accuracy> (visited on 10/04/2026).
- [92] Uneekor, Inc. *EYE XO, EYE XO2 and EYE MINI product documentation*. URL: <https://uneekor.com/golf-launch-monitors/eye-mini> (visited on 07/31/2026).
- [94] Uneekor, Inc. *Photometric vs. Doppler: which launch monitor technology delivers the most accurate golf data*. Describes Dimple Optix markerless spin. URL: <https://uneekor.com/blogs/blog/photometric-vs.-doppler:-which-launch-monitor-technology-delivers-the-most-accurate-golf-data> (visited on 07/31/2026).

Datasheets, protocols, and standards

- [10] J. Driscoll. *Revised Golf Ball Testing Conditions to Take Effect in 2028*. Historical announcement; implementation timetable superseded by the June 2026 joint statement. Dec. 6, 2023. URL: <https://www.usga.org/content/usga/home-page/articles/2023/12/revised-golf-ball-testing-conditions-to-take-effect-in-2028.html> (visited on 10/04/2026).
- [11] Federal Communications Commission. *Equipment authorization filing SFX-TMAN₄ (TrackMan 4)*. TrackMan iO: SFX-TMB0201. URL: <https://fccid.io/SFX-TMAN4> (visited on 07/31/2026).

- [25] Golf Simulator Forum. *FlightScope Mevo+ teardown and FCC filings (QXP-LJ361, QXP-A7310)*. URL: <https://golfsimulatorforum.com/forum/flightscope/277362-mevo-teardown> (visited on 07/31/2026).
- [28] GSPro. *GSPro Open Connect API v1 specification*. Reference client: <https://github.com/travislang/gspro-garmin-connect-v2>. URL: <https://gsprogolf.com/GSProConnectV1.html> (visited on 07/31/2026).
- [35] Joint Committee for Guides in Metrology. *International Vocabulary of Metrology—Basic and General Concepts and Associated Terms (VIM)*. 3rd ed. JCGM 200:2012. Annotated online edition; definitions 2.15, 2.20, 2.21, and 2.39 consulted. 2012. URL: <https://jcgmbipm.org/vim/en/> (visited on 10/03/2026).
- [41] MathWorks. *Constant false alarm rate (CFAR) detection*. CA/GO/SO/OS variants and false-alarm mathematics. URL: <https://www.mathworks.com/help/phased/ug/constant-false-alarm-rate-cfar-detection.html> (visited on 07/31/2026).
- [42] MathWorks. *Constant False-Alarm Rate (CFAR) Detectors*. URL: <https://www.mathworks.com/help/phased/ug/constant-false-alarm-rate-cfar-detectors.html> (visited on 10/04/2026).
- [49] OmniPreSense Corp. *AN-029: OPS24x for Sports Applications*. Documents the golf configuration and cites the OpenFlight project as its reference implementation. 2026. URL: https://omnipresense.com/wp-content/uploads/2026/06/AN-029-A_OPS243-for-Sports_260621.pdf (visited on 07/31/2026).
- [50] OmniPreSense Corp. *AN-010: API Interface Specification*. URL: https://omnipresense.com/wp-content/uploads/2025/10/AN-010-AD_API_Interface.pdf (visited on 07/31/2026).
- [51] OmniPreSense Corp. *AN-027: Rolling Buffer Mode*. URL: https://omnipresense.com/wp-content/uploads/2025/06/AN-027-A_Rolling-Buffer-1.pdf (visited on 07/31/2026).
- [52] OmniPreSense Corp. *OPS243 Doppler Radar Sensor Product Brief*. OPS-PB-004-F. URL: https://omnipresense.com/wp-content/uploads/2024/01/OPS243-Product-Brief_004-F.pdf (visited on 07/31/2026).
- [59] S. Rao. *MIMO Radar*. SWRA554A. 2018. URL: <https://www.ti.com/lit/an/swra554a/swra554a.pdf> (visited on 09/30/2026).
- [61] Raspberry Pi Ltd. *Raspberry Pi Global Shutter Camera documentation (IMX296, XTR external trigger)*. URL: <https://www.raspberrypi.com/documentation/accessories/camera.html> (visited on 07/31/2026).
- [62] Raspberry Pi Ltd. *Raspberry Pi Global Shutter Camera: Specifications*. URL: <https://www.raspberrypi.com/products/raspberry-pi-global-shutter-camera/> (visited on 10/04/2026).
- [63] RFbeam Microwave GmbH. *K-LD7 Radar Transceiver Datasheet*. Rev. B. 2021. URL: <https://rfbeam.ch/product/k-ld7-radar-transceiver/> (visited on 09/30/2026).
- [67] Texas Instruments. *Programming Chirp Parameters in TI Radar Devices*. SWRA553A. 2020. URL: <https://www.ti.com/lit/an/swra553a/swra553a.pdf> (visited on 09/30/2026).
- [68] Texas Instruments. *IWR6843, IWR6443 Single-Chip 60 to 64 GHz mmWave Sensor*. SWRS219F. EVM documentation: <https://www.ti.com/tool/IWR6843ISK>; sensor placement app note SWRA758. 2025. URL: <https://www.ti.com/lit/ds/symlink/iwr6843.pdf> (visited on 09/30/2026).

- [70] The R&A and USGA. *Equipment Rules: Part 2, Conformance of Clubs*. URL: <https://www.randa.org/roe/the-rules-of-equipment/part-2-conformance-of-clubs> (visited on 10/04/2026).
- [71] The R&A and USGA. *Equipment Rules: Part 4, Conformance of Balls*. URL: <https://www.randa.org/roe/the-rules-of-equipment/part-4-conformance-of-balls> (visited on 10/04/2026).
- [95] USGA. *Driver Check Testing Program: Notice to Manufacturers*. Mar. 13, 2008. URL: <https://www.usga.org/content/dam/usga/pdf/Equipment/Archived-Notices/3-13-08%20Driver%20Check%20Test%20Program.pdf> (visited on 10/04/2026).
- [96] USGA, The R&A, PGA TOUR and DP World Tour. *Joint Statement on the Overall Distance Standard*. No ODS testing change before January 2030 while alternatives are evaluated. June 17, 2026. URL: <https://mediacenter.usga.org/2026-Joint-Statement-USGA-RandA-PGA-Tour-DP-World-Tour> (visited on 10/04/2026).

Independent testing, engineering references, and open source

- [5] Carl's Place. *Calibrating Uneekor launch monitors*. URL: <https://www.carlofet.com/blog/calibrating-uneekor-launch-monitors> (visited on 07/31/2026).
- [26] Golf Simulator Zone. *GCQuad vs TrackMan accuracy: robot testing summary*. URL: <https://golfsimulatorzone.com/gcquad-vs-trackman-accuracy-in-2026/> (visited on 07/31/2026).
- [27] GolfBays. *Radar vs photometric launch monitors indoors*. URL: <https://golfbays.de/en/blogs/news/radar-vs-photometric-launch-monitors-indoors> (visited on 07/31/2026).
- [30] Home Performance Lab. *TrackMan simulator data: measured vs. inferred indoors*. URL: <https://homeperformancelab.com/trackman-simulator-data/> (visited on 07/31/2026).
- [31] *How does TrackMan/FlightScope measure the club face angle?* Contains TrackMan statements on derived face data. Brian Manzella Golf Forum. URL: <https://forum.brianmanzellagolf.com/threads/how-does-trackman-flightscope-measure-the-club-face-angle-16591/> (visited on 07/31/2026).
- [45] MyGolfSimulator. *Garmin R10 accuracy: measured vs. calculated parameters*. URL: <https://mygolfsimulator.com/garmin-r10-accuracy/> (visited on 07/31/2026).
- [46] MyGolfSimulator. *Garmin R10 data and radar architecture*. URL: <https://mygolfsimulator.com/garmin-r10-data/> (visited on 07/31/2026).
- [47] MyGolfSpy. *Rapsodo MLM2PRO takes spin measurement to pro level*. URL: <https://mygolfspy.com/news-opinion/rapsodo-mlm2pro-takes-spin-measurement-to-pro-level/> (visited on 07/31/2026).
- [48] MyGolfSpy. *Three of the most accurate indoor launch monitors — and one to avoid*. URL: <https://mygolfspy.com/news-opinion/three-of-the-most-accurate-indoor-launch-monitors-and-one-to-avoid/> (visited on 07/31/2026).
- [54] Perfect Golf Swing Review. *Ball flight laws*. URL: <https://www.perfectgolfswingreview.net/ballflight.htm> (visited on 07/31/2026).
- [55] PiTrac contributors. *PiTrac — the DIY golf launch monitor*. GPL-2.0; documentation <https://docs.pitrac.org/>; design logs at Hackaday.io project 195042. URL: <https://github.com/PiTracLM/PiTrac> (visited on 07/31/2026).

- [56] PlayBetter. *Bushnell Launch Pro vs GC3 vs GCQuad comparison*. URL: <https://www.playbetter.com/blogs/golf/bushnell-launch-pro-vs-gc3-vs-gc-quad-comparison> (visited on 07/31/2026).
- [85] D. Tutelman. *Gear effect*. Companion: spin decay, <https://www.tutelman.com/golf/ballflight/spinDecay.php>. URL: <https://www.tutelman.com/golf/ballflight/gearEffect1.php> (visited on 07/31/2026).
- [86] D. Tutelman. *Smash factor*. URL: <https://www.tutelman.com/golf/ballflight/smashfactor.php> (visited on 07/31/2026).
- [87] D. Tutelman. *Three-dimensional launch conditions from impact conditions*. URL: <https://www.tutelman.com/golf/ballflight/3dlaunch.php> (visited on 07/31/2026).