1. Create 'spj' database'. (Database for suppliers, parts and jobs)

```
root>CREATE DATABASE spj;
Query OK, 1 row affected (0.03 sec)

root> SHOW DATABASES;
+--------------------+
| Database           |
+--------------------+
| classwork          |
| dacdb              |
| harry              |
| information_schema |
| mysql              |
| performance_schema |
| sakila             |
| spj                |
| sys                |
+--------------------+
9 rows in set (0.05 sec)

root>SELECT DATBASE();
ERROR 1046 (3D000): No database selected
root>SELECT USER(),DATABASE();
+----------------+------------+
| USER()         | DATABASE() |
+----------------+------------+
| root@localhost | NULL       |
+----------------+------------+
1 row in set (0.00 sec)

root>USE spj;
Database changed
```

2. use spj database;

3. Create following tables in spj database.

Note : S denotes the Suppliers Table. CREATE TABLE S (S# CHAR(5) NOT NULL, Sname CHAR(20), status SMALLINT, city CHAR(15));

```
d2_96390_Shashidhar>DESCRIBE S;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| S#     | char(5)  | NO   |     | NULL    |       |
| Sname  | char(20) | YES  |     | NULL    |       |
| status | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
4 rows in set (0.02 sec)
```

```
d2_96390_Shashidhar>SELECT * FROM S;
+----+--------+--------+--------+
| S# | Sname  | status | city   |
+----+--------+--------+--------+
| S1 | Smith  |     20 | London |
| S2 | Jonas  |     10 | Paris  |
| S3 | Blake  |     30 | Paris  |
| S4 | Clarke |     20 | London |
| S5 | Adams  |     30 | Athens |
+----+--------+--------+--------+
5 rows in set (0.00 sec)
```

CREATE TABLE P (P# CHAR(6) NOT NULL, Pname CHAR(20), color CHAR(6), weight SMALLINT, city CHAR(15));

```
2_96390_Shashidhar>DESCRIBE P;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| P#     | char(6)  | NO   |     | NULL    |       |
| Pname  | char(20) | YES  |     | NULL    |       |
| cplor  | char(6)  | YES  |     | NULL    |       |
| weight | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
 rows in set (0.01 sec)
```

```
d2_96390_Shashidhar>SELECT * FROM P;
+----+-------+-------+--------+--------+
| P# | Pname | cplor | weight | city   |
+----+-------+-------+--------+--------+
| P1 | NUT   | RED   |     12 | LONDON |
| P2 | BOLT  | SCREW |     17 | PARIS  |
| P3 | SCREW | BLUE  |     17 | ROME   |
| P4 | SCREW | RED   |     14 | LONDON |
| P5 | CAM   | BLUE  |     12 | PARIS  |
| P6 | COG   | RED   |     19 | LONDON |
+----+-------+-------+--------+--------+
6 rows in set (0.00 sec)
```

CREATE TABLE J (J# CHAR(4) NOT NULL, Jname CHAR(10), City CHAR(15));

```
d2_96390_Shashidhar>DESCRIBE J;
+-------+----------+------+-----+---------+-------+
| Field | Type     | Null | Key | Default | Extra |
+-------+----------+------+-----+---------+-------+
| J#    | char(4)  | NO   |     | NULL    |       |
| Jname | char(10) | YES  |     | NULL    |       |
| City  | char(15) | YES  |     | NULL    |       |
+-------+----------+------+-----+---------+-------+
```

```
d2_96390_Shashidhar>SELECT* FROM J;
+----+---------+--------+
| J# | Jname   | City   |
+----+---------+--------+
| J1 | Sorter  | Paris  |
| J2 | Punch   | Rome   |
| J3 | Reader  | Atehns |
| J4 | Console | Athens |
+----+---------+--------+
4 rows in set (0.00 sec)
```

CREATE TABLE sp (S# CHAR(4) NOT NULL, P# CHAR(4) NOT NULL, J# CHAR(4) NOT NULL, QTY INT);

```
2_96390_Shashidhar>CREATE TABLE sp (`S#` CHAR(4) NOT NULL, `P#` CHAR(4) NOT NULL, `J#` CHAR(4) NOT NULL, QTY INT);
uery OK, 0 rows affected (0.90 sec)

2_96390_Shashidhar>DESCRIBE SP;
-------+---------+------+-----+---------+-------+
 Field | Type    | Null | Key | Default | Extra |
-------+---------+------+-----+---------+-------+
 S#    | char(4) | NO   |     | NULL    |       |
 P#    | char(4) | NO   |     | NULL    |       |
 J#    | char(4) | NO   |     | NULL    |       |
 QTY   | int     | YES  |     | NULL    |       |
-------+---------+------+-----+---------+-------+
 rows in set (0.00 sec)
```

```
d2_96390_Shashidhar>INSERT INTO sp (`S#`, `P#`, `J#`, QTY) VALUES
    -> ('S1', 'P1', 'J1', 200),
    -> ('S1', 'P1', 'J4', 700),
    -> ('S2', 'P3', 'J1', 400),
    -> ('S2', 'P3', 'J2', 200),
    -> ('S2', 'P3', 'J3', 200),
    -> ('S2', 'P3', 'J4', 500),
    -> ('S2', 'P3', 'J5', 600),
    -> ('S2', 'P3', 'J6', 400),
    -> ('S2', 'P3', 'J7', 800),
    -> ('S2', 'P5', 'J2', 100),
    -> ('S3', 'P3', 'J1', 200),
    -> ('S3', 'P4', 'J2', 500),
    -> ('S4', 'P6', 'J3', 300),
    -> ('S4', 'P6', 'J7', 300),
    -> ('S5', 'P2', 'J2', 200),
    -> ('S5', 'P2', 'J4', 100),
    -> ('S5', 'P5', 'J5', 500),
    -> ('S5', 'P5', 'J7', 100),
    -> ('S5', 'P6', 'J2', 200),
    -> ('S5', 'P1', 'J4', 100),
    -> ('S5', 'P3', 'J4', 200),
    -> ('S5', 'P4', 'J4', 800),
    -> ('S5', 'P5', 'J4', 400),
    -> ('S5', 'P6', 'J4', 500);
Query OK, 24 rows affected (0.01 sec)
Records: 24  Duplicates: 0  Warnings: 0
```

```
d2_96390_Shashidhar>SELECT * FROM sp;
+----+----+----+------+
| S# | P# | J# | QTY  |
+----+----+----+------+
| S1 | P1 | J1 |  200 |
| S1 | P1 | J4 |  700 |
| S2 | P3 | J1 |  400 |
| S2 | P3 | J2 |  200 |
| S2 | P3 | J3 |  200 |
| S2 | P3 | J4 |  500 |
| S2 | P3 | J5 |  600 |
| S2 | P3 | J6 |  400 |
| S2 | P3 | J7 |  800 |
| S2 | P5 | J2 |  100 |
| S3 | P3 | J1 |  200 |
| S3 | P4 | J2 |  500 |
| S4 | P6 | J3 |  300 |
| S4 | P6 | J7 |  300 |
| S5 | P2 | J2 |  200 |
| S5 | P2 | J4 |  100 |
| S5 | P5 | J5 |  500 |
| S5 | P5 | J7 |  100 |
| S5 | P6 | J2 |  200 |
| S5 | P1 | J4 |  100 |
| S5 | P3 | J4 |  200 |
| S5 | P4 | J4 |  800 |
| S5 | P5 | J4 |  400 |
| S5 | P6 | J4 |  500 |
+----+----+----+------+
24 rows in set (0.00 sec)
```

. Create 'hr' database. Import hr-db.sql. 2. Create 'sales' database. Import sales-db.sql. 3. List all tables in hr database. Display contents of all tables (one by one). 4. List all tables in sales database. Display contents of all tables (one by one).

```
2_96390_Shashidhar>SHOW DATABASES;
--------------------+
 Database           |
--------------------+
 classwork          |
 harry              |
 hr                 |
 information_schema |
 performance_schema |
 spj                |
--------------------+
 rows in set (0.01 sec)

2_96390_Shashidhar>use hr;
atabase changed
2_96390_Shashidhar>SELECT USER(), DATABASE();
------------------------------+------------+
 USER()                       | DATABASE() |
------------------------------+------------+
 d2_96390_Shashidhar@localhost | hr         |
------------------------------+------------+
 row in set (0.00 sec)

2_96390_Shashidhar>SHOW TABLES;
--------------+
 Tables_in_hr |
--------------+
 countries    |
 customers    |
 departments  |
 employees    |
 job_history  |
 jobs         |
 locations    |
 orders       |
 regions      |
 salespeople  |
--------------+
```

```
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2001 | Hoffman  | London   |    100 | 1001 |
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2006 | Clemens  | London   |    100 | 1001 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
| 2007 | Pereira  | Rome     |    100 | 1004 |
+------+----------+----------+--------+------+
7 rows in set (0.00 sec)

12_96390_Shashidhar>select* from department;
ERROR 1146 (42S02): Table 'hr.department' doesn't exist
12_96390_Shashidhar>SELECT * FROM  departments;
+---------------+----------------------+------------+-------------+
| DEPARTMENT_ID | DEPARTMENT_NAME      | MANAGER_ID | LOCATION_ID |
+---------------+----------------------+------------+-------------+
|            10 | Administration       |        200 |        1700 |
|            20 | Marketing            |        201 |        1800 |
|            30 | Purchasing           |        114 |        1700 |
|            40 | Human Resources      |        203 |        2400 |
|            50 | Shipping             |        121 |        1500 |
|            60 | IT                   |        103 |        1400 |
|            70 | Public Relations     |        204 |        2700 |
|            80 | Sales                |        145 |        2500 |
|            90 | Executive            |        100 |        1700 |
|           100 | Finance              |        108 |        1700 |
|           110 | Accounting           |        205 |        1700 |
|           120 | Treasury             |       NULL |        1700 |
|           130 | Corporate Tax        |       NULL |        1700 |
|           140 | Control And Credit   |       NULL |        1700 |
|           150 | Shareholder Services |       NULL |        1700 |
|           160 | Benefits             |       NULL |        1700 |
|           170 | Manufacturing        |       NULL |        1700 |
|           180 | Construction         |       NULL |        1700 |
|           190 | Contracting          |       NULL |        1700 |
|           200 | Operations           |       NULL |        1700 |
|           210 | IT Support           |       NULL |        1700 |
|           220 | NOC                  |       NULL |        1700 |
```

```
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

d2_96390_Shashidhar>use sales;
Database changed
d2_96390_Shashidhar>SELECT USER(),DATABASE();
+-------------------------------+------------+
| USER()                        | DATABASE() |
+-------------------------------+------------+
| d2_96390_Shashidhar@localhost | sales      |
+-------------------------------+------------+
1 row in set (0.00 sec)

d2_96390_Shashidhar>SHOW TABLES;
+-----------------+
| Tables_in_sales |
+-----------------+
| customers       |
| orders          |
| salespeople     |
+-----------------+
3 rows in set (0.01 sec)

d2_96390_Shashidhar>SELECT* FROM customers;
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2001 | Hoffman  | London   |    100 | 1001 |
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2006 | Clemens  | London   |    100 | 1001 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
| 2007 | Pereira  | Rome     |    100 | 1004 |
+------+----------+----------+--------+------+
7 rows in set (0.00 sec)

d2_96390_Shashidhar>SELECT* FROM orders;
```

```
+------+----------+----------+--------+------+
| 2001 | Hoffman  | London   |    100 | 1001 |
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2006 | Clemens  | London   |    100 | 1001 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
| 2007 | Pereira  | Rome     |    100 | 1004 |
+------+----------+----------+--------+------+
7 rows in set (0.00 sec)

d2_96390_Shashidhar>SELECT* FROM orders;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
10 rows in set (0.00 sec)

d2_96390_Shashidhar>SELECT* FROM salespeople;
+------+---------+-----------+------+
| snum | sname   | city      | comm |
+------+---------+-----------+------+
| 1001 | Peel    | London    | 0.12 |
| 1002 | Serres  | San Jose  | 0.13 |
| 1004 | Motika  | London    | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York  | 0.10 |
+------+---------+-----------+------+
5 rows in set (0.00 sec)
```