Write a query that uses a subquery to obtain all orders for the customer named Cisneros. Assume you do not know his customer number (cnum).

```
d2_96390_Shashidhar>select * from orders where cnum = (select cnum from cust
omers where cname = 'cisneros');
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
+------+---------+------------+------+------+
2 rows in set (0.00 sec)

d2_96390_Shashidhar>
```

```
d2_96390_Shashidhar>select * from orders where snum = (select snum from sale
speople where sname = 'Motika');
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
+------+---------+------------+------+------+
1 row in set (0.00 sec)
```

```
d2_96390_Shashidhar>select * from orders where snum = all(select snum from c
ustomers where city = 'London');
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
3 rows in set (0.00 sec)

d2_96390_Shashidhar>
```

```
d2_96390_Shashidhar>select * from orders where amt > any (select amt from or
ders where cnum IN(select cnum from customers where city = 'London'));
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
6 rows in set (0.00 sec)
```

```
d2_96390_Shashidhar>select * from customers where rating > any(select  ratin
g from customers where city = 'Rome');
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
+------+----------+----------+--------+------+
4 rows in set (0.01 sec)
```

```
d2_96390_Shashidhar>select * from orders where amt > any(select amt from ord
ers where odate = '1990-10-04');
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
8 rows in set (0.00 sec)
```

```
d2_96390_Shashidhar>select * from orders where amt < any(select amt from ord
ers where cnum IN (select cnum from customers where city = 'san jose'));
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
+------+---------+------------+------+------+
8 rows in set (0.00 sec)
```

```
d2_96390_Shashidhar>select o.amt,c.cname,c.rating from customers c inner joi
n orders o on o.cnum = c.cnum where o.amt> (select avg(amt) from orders);
+---------+---------+--------+
| amt     | cname   | rating |
+---------+---------+--------+
| 5160.45 | Liu     |    200 |
| 9891.88 | Clemens |    100 |
| 4723.00 | Clemens |    100 |
+---------+---------+--------+
3 rows in set (0.01 sec)
```

```
d2_96390_Shashidhar>select * from customers where rating > all (select ratin
g from customers where city = 'London');
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
+------+----------+----------+--------+------+
4 rows in set (0.00 sec)
```

```
d2_96390_Shashidhar>select sname, snum from salespeople where snum IN(select
  snum from customers group by snum having count(snum) > 1);
+--------+------+
| sname  | snum |
+--------+------+
| Peel   | 1001 |
| Serres | 1002 |
+--------+------+
2 rows in set (0.00 sec)
```

```
d2_96390_Shashidhar>select snum, sum(amt) from orders group by snum having s
um(amt) > (select max(amt) from orders);
+------+----------+
| snum | sum(amt) |
+------+----------+
| 1001 | 15382.07 |
+------+----------+
1 row in set (0.00 sec)

d2_96390_Shashidhar>
```

```
d2_96390_Shashidhar>select  c.rating from customers c inner join salespeople
 s on s.snum = c.snum where sname = 'serres';
+--------+
| rating |
+--------+
|    200 |
|    300 |
+--------+
2 rows in set (0.01 sec)
```

```
d2_96390_Shashidhar>SELECT *
    -> FROM salespeople s
    -> WHERE s.city <> ALL (
    ->     SELECT c.city
    ->     FROM customers c
    ->     WHERE c.snum = s.snum
    -> );
+------+---------+-----------+------+
| snum | sname   | city      | comm |
+------+---------+-----------+------+
| 1004 | Motika  | London    | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York  | 0.10 |
+------+---------+-----------+------+
3 rows in set (0.00 sec)

d2_96390_Shashidhar>
d2_96390_Shashidhar>
```