1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.
2.

```
+------+---------+-----------+------+
| snum | sname   | city      | comm |
+------+---------+-----------+------+
| 1001 | Peel    | London    | 0.12 |
| 1002 | Serres  | San Jose  | 0.13 |
| 1004 | Motika  | London    | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York  | 0.10 |
+------+---------+-----------+------+
5 rows in set (0.00 sec)

d2_96390_Shashidhar>USE sales;
Database changed
d2_96390_Shashidhar>SHOW TABLES;
+-----------------+
| Tables_in_sales |
+-----------------+
| customers       |
| orders          |
| salespeople     |
+-----------------+
3 rows in set (0.00 sec)

d2_96390_Shashidhar>SELECT * FROM salespeople;
+------+---------+-----------+------+
| snum | sname   | city      | comm |
+------+---------+-----------+------+
| 1001 | Peel    | London    | 0.12 |
| 1002 | Serres  | San Jose  | 0.13 |
| 1004 | Motika  | London    | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York  | 0.10 |
+------+---------+-----------+------+
5 rows in set (0.00 sec)

d2_96390_Shashidhar>SELECT* FROM salespeople WHERE snum = 1001;
+------+-------+--------+------+
| snum | sname | city   | comm |
+------+-------+--------+------+
| 1001 | Peel  | London | 0.12 |
+------+-------+--------+------+
```

Write a select command that produces the rating followed by the name of each customer in San Jose.

```
d2_96390_Shashidhar>SELECT cname,rating FROM customers WHERE city = 'SAN jos
e';
+----------+--------+
| cname    | rating |
+----------+--------+
| Liu      |    200 |
| Cisneros |    300 |
+----------+--------+
2 rows in set (0.03 sec)

d2_96390_Shashidhar>
```

Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
d2_96390_Shashidhar>SELECT DISTINCT snum FROM ORDERS;
+------+
| snum |
+------+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+------+
5 rows in set (0.01 sec)
```

Write a query that will display all the orders for amount more than Rs. 1,000.

```
d2_96390_Shashidhar>SELECT* FROM ORDERS WHERE amt > 1000;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
6 rows in set (0.01 sec)

d2_96390_Shashidhar>
```

Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
d2_96390_Shashidhar> SELECT sname, city FROM salespeople WHERE city = 'Londo
n' AND comm >0.10;
+--------+--------+
| sname  | city   |
+--------+--------+
| Peel   | London |
| Motika | London |
+--------+--------+
2 rows in set (0.01 sec)
```

. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
d2_96390_Shashidhar>SELECT * FROM customers WHERE rating > 100 OR city = 'Ro
me';
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
| 2007 | Pereira  | Rome     |    100 | 1004 |
+------+----------+----------+--------+------+
5 rows in set (0.00 sec)
```

. What will be the output from the following query? Select * from Orders where (amt < 1000 OR NOT (odate = ‘1990-10- 03’ AND cnum > 2003));

```
d2_96390_Shashidhar>SELECT* FROM orders WHERE (amt <1000 OR NOT(odate = '199
0-10-03' AND cnum > 2003));
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
8 rows in set (0.01 sec)

d2_96390_Shashidhar>SELECT* FROM orders;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
10 rows in set (0.00 sec)
```

8. What will be the output of the following query? Select * from Orders where NOT (odate = ‘1990-10-03’ OR snum >1006) AND amt >= 1500;

```
d2_96390_Shashidhar>SELECT* FROM orders WHERE NOT(odate = '1990-10-03' OR sn
um>1006) AND amt >= 1500;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
3 rows in set (0.00 sec)

d2_96390_Shashidhar>
```

10. Write a query that selects all orders except those with amount less than 100.

```
d2_96390_Shashidhar>SELECT* FROM orders WHERE AMT < 100;
+------+-------+------------+------+------+
| onum | amt   | odate      | cnum | snum |
+------+-------+------------+------+------+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
+------+-------+------------+------+------+
2 rows in set (0.00 sec)

d2_96390_Shashidhar>
```