Exp 4

AIM: Hands on Solidity Programming Assignments for creating Smart Contracts.

Theory:

1. **Primitive Data Types, Variables, Functions – pure, view**

In Solidity, primitive data types form the foundation of smart contract development. Commonly used types include:

- **uint / int**: unsigned and signed integers of different sizes (e.g., uint256, int128).
- **bool**: represents logical values (true or false).
- **address**: holds a 20-byte Ethereum account address, often used for storing user accounts or contract addresses.
- **bytes / string**: store binary data or textual data.

Variables in Solidity can be **state variables** (stored on the blockchain permanently), **local variables** (temporary, created during function execution), or **global variables** (special predefined variables such as msg.sender, msg.value, and block.timestamp).

Functions allow execution of contract logic. Special types of functions include:

- **pure**: cannot read or modify blockchain state; they work only with inputs and internal computations.
- **view**: can read state variables but cannot alter them. This classification helps optimize gas usage and enforces function integrity.

2. **Inputs and Outputs to Functions**

Functions in Solidity can accept input arguments and return one or more output values. Inputs enable users or other contracts to pass data into the contract, while outputs make it possible to return results after computation. For example, a function can accept an amount in Ether and return whether the transfer was successful. Solidity also allows named return variables, which improve readability and debugging.

3. **Visibility, Modifiers and Constructors**

- **Function Visibility** defines who can access a function:
  - public: available both inside and outside the contract.
  - private: only accessible within the same contract.
  - internal: accessible within the contract and its child contracts.
  - external: can be called only by external accounts or other contracts.

- **Modifiers** are reusable code blocks that change the behavior of functions. They are often used for access control, such as restricting sensitive functions to the contract owner (onlyOwner).
- **Constructors** are special functions executed only once during contract deployment. They initialize important values, such as setting the deploying account as the owner of the contract.

3. Control Flow: if-else, loops

Control flow in Solidity is similar to traditional programming languages:

- **if-else** allows conditional decision-making in contract logic, e.g., checking if a balance is sufficient before transferring funds.
- **Loops** (for, while, do-while) enable repeated execution of code. For example, iterating through an array of users. However, loops must be used carefully, as excessive iterations increase gas consumption, potentially making the contract expensive to execute.

5. Data Structures: Arrays, Mappings, Structs, Enums

- **Arrays**: Can be fixed or dynamic and are used to store ordered lists of elements. Example: an array of addresses for registered users.
- **Mappings**: Key-value pairs that allow quick lookups. Example: mapping(address => uint) for storing balances. Unlike arrays, mappings do not support iteration.
- **Structs**: Allow grouping of related properties into a single data type, such as creating a struct Player {string name; uint score;}.
- **Enums**: Used to define a set of predefined constants, making code more readable. Example: enum Status { Pending, Active, Closed }.

6. Data Locations

Solidity uses three primary data locations for storing variables:

- **storage**: Data stored permanently on the blockchain. Examples: state variables.
- **memory**: Temporary data storage that exists only while a function is executing. Used for local variables and function inputs.
- **calldata**: A non-modifiable and non-persistent location used for external function parameters. It is gas-efficient compared to memory. Understanding data locations is essential, as they directly impact gas costs and performance.

7. Transactions: Ether and Wei, Gas and Gas Price, Sending Transactions

- **Ether and Wei**: Ether is the main currency in Ethereum. All values are measured in Wei, the smallest unit (1 Ether = 10^{18} Wei). This ensures high precision in financial transactions.
- **Gas and Gas Price**: Every transaction consumes gas, which represents computational effort. The gas price determines how much Ether is paid per unit of gas. A higher gas price incentivizes miners to prioritize the transaction.
- **Sending Transactions**: Transactions are used for transferring Ether or interacting with contracts. Functions like transfer() and send() are commonly used, while call() provides more flexibility. Each transaction requires gas, making efficiency in contract design very important.

Implementation:

Tutorial - 1 (compile)







Tutorial - 1 (get)



Tutorial - 1 (inc)



Tutorial - 1 (dec)



Tutorial - 2



Tutorial - 3



Tutorial - 4



Tutorial - 5



Tutorial - 6



Tutorial - 7



Tutorial - 8



Tutorial - 9



Tutorial - 10



Tutorial - 11



Tutorial - 12



Tutorial - 13

We can use the delete operator to delete a value associated with a key, which will set it to the default value of 0. As we have seen in the arrays section.

Watch a video tutorial on Mappings.

Assignment

1. Create a public mapping `balances` that associates the key type `address` with the value type `uint`.
2. Change the functions `get` and `remove` to work with the mapping balances.
3. Change the function `set` to create a new entry to the balances mapping, where the key is the address of the parameter and the value is the balance associated with the address of the parameter.

Check Answer | Show answer

Next

Well done! No errors.

```
    mapping(address => uint) public myMap;
// Kunal Punjabi D20A 46ey D20A 37
    mapping(address => uint) public balances;

    function get(address _addr) public view returns (uint) {    2895 gas
        // Mapping always returns a value.
        // If the value was never set, it will return the default value.
        return balances[_addr];
    }

    function set(address _addr) public {    25279 gas
        // Update the value at this address
        balances[_addr] = _addr.balance;
    }

    function remove(address _addr) public {    5588 gas
```

Explain contract

0 Listen on all transactions Filter with transaction hash or ad...

Note: The called function should be payable if you send value and the value you send should be less than yo
If the transaction failed for not having enough gas, try increasing the gas limit gently.

Tutorial - 14

Watch a video tutorial on Structs.

Assignment

Create a function `remove` that takes a `uint` as a parameter and deletes a struct member with the given index in the `todos` mapping.

Check Answer | Show answer

Next

Well done! No errors.

```
    }
// Kunal Punjabi D20A 46
    function remove(uint _index) public {    infinite gas
        delete todos[_index];
    }
```

Explain contract

0 Listen on all transactions Filter with transactio

Note: The called function should be payable if you send value and the value you send sh
If the transaction failed for not having enough gas, try increasing the gas limit gentl

Tutorial 15

15 / 19

name of the enum and its member (line 35).

Removing an enum value

We can use the delete operator to delete the enum value of the variable, which means as for arrays and mappings, to set the default value to 0.

Watch a video tutorial on Enums.

Assignment

1. Define an enum type called `Size` with the members `S`, `M`, and `L`.
2. Initialize the variable `sizes` of the enum type `Size`.
3. Create a getter function `getSize()` that returns the value of the variable `sizes`.

Check Answer | Show answer

Next

Well done! No errors.

```
    S,
    M,
    L
}
// Default value is the first element listed in
// definition of the type, in this case "Pending"
Status public status;
Size public size;
// Returns uint
// Pending  - 0
// Shipped  - 1
// Accepted - 2
// Rejected - 3
// Canceled - 4
function getSize() public view returns(Size){    2655 gas
    return size;
}
```

Explain contract AI copilot

0 Listen on all transactions Filter with transaction hash or ad...

Note: The called function should be payable if you send value and the value you send should be less than your current bi
If the transaction failed for not having enough gas, try increasing the gas limit gently.

Tutorial - 16

Assignment

1. Change the value of the `myStruct` member `foo`, inside the `function f`, to 4.
2. Create a new struct `myMemStruct2` with the data location *memory* inside the `function f` and assign it the value of `myMemStruct`. Change the value of the `myMemStruct2` member `foo` to 1.
3. Create a new struct `myMemStruct3` with the data location *memory* inside the `function f` and assign it the value of `myStruct`. Change the value of the `myMemStruct3` member `foo` to 3.
4. Let the function f return `myStruct`, `myMemStruct2`, and `myMemStruct3`.

Tip: Make sure to create the correct return types for the function `f`.

Check Answer | Show answer

Next

Well done! No errors.

```
    }

    function _f(    undefined gas
        uint[] storage _arr,
        mapping(uint => address) storage _map,
        MyStruct storage _myStruct
    ) internal {
        // do something with storage variables
    }

    // You can return memory variables
    function g(uint[] memory _arr) public returns (uint[] memory) {    infinite gas
        // do something with memory array
        arr[0] = 1;
    }
    //Prajjwal Pandey D20A 37
// Kunal Punjabi D20A 46 calldata _arr) external {    468 gas
        // do something with calldata array
        // _arr[0] = 1;
    }
}
```

Activate Windows
Go to Settings to activate Windows.

Tutorial 17

Tutorials list | Syllabus

10.1 Transactions - Ether and Wei
17 / 19

`gwei`

One `gwei` (giga-wei) is equal to 1,000,000,000 (10^9) `wei`.

`ether`

One `ether` is equal to 1,000,000,000,000,000,000 (10^18) `wei` (line 11).

Watch a video tutorial on Ether and Wei.

Assignment

1. Create a `public` `uint` called `oneGwei` and set it to 1 `gwei`.
2. Create a `public` `bool` called `isOneGwei` and set it to the result of a comparison operation between 1 gwei and 10^9.

Tip: Look at how this is written for `gwei` and `ether` in the contract.

Check Answer | Show answer

Next

Well done! No errors.

```
1  // SPDX-License-Identifier: MIT
2  pragma solidity ^0.8.3;
3
4  contract EtherUnits {
5      uint public oneWei = 1 wei;
6      // 1 wei is equal to 1
7      bool public isOneWei = 1 wei == 1;
8
9      uint public oneEther = 1 ether;
10     // 1 ether is equal to 10^18 wei
11     bool public isOneEther = 1 ether == 1e18;
12
13     uint public oneGwei = 1 gwei;
14     // 1 ether is equal to 10^9 wei
15     bool public isOneGwei = 1 gwei == 1e9;
16 }
17 // Kunal Punjabi D20A 46
```

Tutorial 18



Tutorial 19



Conclusion :

Through this experiment, the fundamentals of Solidity programming were explored by completing practical assignments in the Remix IDE. Concepts such as data types, variables, functions, visibility, modifiers, constructors, control flow, data structures, and transactions were implemented and understood. The hands-on practice helped in designing, compiling, and deploying smart contracts on the Remix VM, thereby strengthening the understanding of blockchain concepts. This experiment provided a strong foundation for developing and managing smart contracts efficiently.