
A short introduction to UML and UML definition

based on **Bernd Bruegge's** book,
UML Reference manual and including some personal
points of view/opinions and examples using **OCLE**

Dan CHIOREAN
Babeş-Bolyai University
`chiorean@cs.ubbcluj.ro`



Introduction to UML

What is modeling?

Modeling consists of building an abstraction of reality

Model – an abstract description of a problem/problem solution

Abstractions are simplifications because:

- They ignore irrelevant details and
- They only represent the relevant details

What is *relevant* or *irrelevant* depends on the purpose of the model

We use modeling to produce software because:

- Software is getting increasingly more complex
- Modeling is a means for dealing with complexity

Introduction to UML

Abstraction as key technique in modeling

Two definitions for abstraction:


- Abstraction is a *thought process* where ideas are distanced from objects
- **Abstraction as activity**
- Abstraction is the *resulting idea* of a thought process where an idea has been distanced from an object
- **Abstraction as entity**
- Ideas can be expressed by models



Abstraction allows us to ignore unessential details

Introduction to UML

Modeling challenges



Introduction to UML

Models must be falsifiable

- **Testing:** The act of disproving a model.

Introduction to UML

Models must be falsifiable

- **Karl Popper** ("Objective Knowledge):
 - There is no absolute truth when trying to understand reality. One can only build theories, that are "true" until somebody finds a counter example
- **Falsification**: The act of disproving a theory or hypothesis
- **The truth of a theory is never certain**. We must use phrases like:
 - "by our best judgement", "using state-of-the-art knowledge"
- **In software engineering any model is a theory**:
 - We build models and try to find counter examples by:
 - Requirements validation, user interface testing, review of the design, source code testing, system testing, etc.

Introduction to UML

Three ways to deal with complexity

- Abstraction and Modeling
- Decomposition
- Hierarchy

UML supports all these three ways/techniques

Introduction to UML


Decomposition

Complex systems are hard to understand

- The **7 +- 2 phenomena**
- Our short-term memory cannot store more than 7+-2 pieces at the same time -> limitation of the brain
- TUM Phone Number: 498928918204

Chunking:

- Group collection of objects to reduce complexity
 - State-code, city-code, TUM-code, Office-Part




Introduction to UML

Object-oriented decomposition - What is this?

Object-oriented decomposition is good. Unfortunately, depending on the purpose of the system, different objects can be found


An Eskimo!



Introduction to UML

Object-oriented decomposition - What is this?

A Face!




Introduction to UML

Object-oriented decomposition - What is this?

An Eskimo!



A Face!



Depending on the purpose of the system, different objects might be found

Identify the purpose of a system is crucial

Introduction to UML

Hierarchy


Another way to deal with complexity is to provide **relationships between these chunks**

One of the most important relationships is hierarchy. There are 2 useful/special hierarchies:

- **"Part-of"** hierarchy
- **"Is-kind-of"** hierarchy


Introduction to UML

Part of Hierarchy - Aggregation



Introduction to UML

Is Kind of Hierarchy - Taxonomy



Introduction to UML


What is UML?

- **UML** (Unified Modeling Language) - 1997
- Nonproprietary standard for modeling software systems, **OMG**
- Convergence of notations used in object-oriented methods:
 - **OMT** (James Rumbaugh and colleagues)
 - **Booch** (Grady Booch)
 - **OOSE** (Ivar Jacobson)
- Information at **the OMG portal** <http://www.uml.org/>
- Commercial tools: Rational Software Modeler (IBM), Rational Rhapsody, Enterprise Architect, Visual Paradigm, MagicDraw

Introduction to UML

History of UML


- the first version of UML- November 1997
- The version 1.5 implemented in OCLE was adopted in March 2003, formal-03-03-01.pdf, 736 pag. – including OCL 47 pag. chap. 6
- The current Version 2.5.1 - formal-17-12-05.pdf, 796 pag. – OCL specified in another doc. 262 pag. - formal-14-02-03.pdf, OCL 2.4, that is aligned with UML 2.4.1



Introduction to UML

Important to know

- You can solve 80% of the modeling problems by using 20 % UML
- We teach you those 20%
- 80-20 rule: Pareto principle



Vilfredo Pareto, 1848-1923

- Introduced the concept of Pareto Efficiency,
- Founder of the field of microeconomics.

Introduction to UML

Most important features of UML

- Apart from "languages" of OMT, OOD/Booch, OOSE methods contributing at UML definition, UML is specified in a more rigorous manner by means of concrete syntax, abstract syntax and semantics
- The abstract syntax is described by means of the UML metamodel and WFRs (invariants on metamodel classes). The language describing the UML metamodel, MOF is a subset of the UML language
- Beginning with the first version, UML included the OCL


Introduction to UML

What is a Model, View, Diagram?

- **UML** is a language supporting model specification
- A **model** is an **abstraction** describing a problem/problem domain, a problem solution/ system or a subsystem:
 - a system that no longer exists,
 - an existing system,
 - a future system to be built.
- A **view** depicts selected aspects of a model
- A **diagram/notation** is a set of graphical/textual rules for depicting views and formal specifications


Introduction to UML

UML Models, Views, Diagrams



Introduction to UML


UML – A better understanding of the problem – the functionality



Use case diagrams represent the functionality of the system from user's point of view

Introduction to UML

UML – the functional view



UCDs are used during requirements elicitation and analysis to represent external behavior (“visible from the outside of the system”)


A **use case** represents a functionality provided by the system

An **Actor** represents a role, that is, a type of user of the system

The set of all use cases that completely describe the functionality of the system form the **Use Case View/Model**

Introduction to UML

UML – the functional view - Actors




Passenger

An **actor** is a model of an external entity which interacts (communicates) with the system:

- User
 - External system (Another system)
 - Physical environment (e.g. Weather)
-
- An **actor** has a **unique name** and an **optional description**
- Examples:
- **Passenger**: A person in the train
 - **GPS satellite**: An external system that provides the system with GPS

Introduction to UML

UML – the functional view – Use Case



PurchaseTicket

A **Use Case** represents a class of functionality provided by the system


Use Cases can be described textually, with a focus on the event flow between actor and system

The textual **Use Case description** consists of 6 parts:

1. Unique name
2. Participating actors
3. Entry conditions
4. Exit conditions
5. Flow of events
6. Special requirements.

Introduction to UML

UML – the functional view – Use Case



1. Name: Purchase ticket

2. Participating actor: Passenger

3. Entry condition: Passenger stands in front of Ticket Distributor

- Passenger has sufficient money to purchase ticket

4. Exit condition: Passenger has ticket

5. Flow of events:

1. Passenger selects the number of zones to be traveled
2. Ticket Distributor displays the amount due
3. Passenger inserts money, at least the amount due
4. Ticket Distributor returns change
5. Ticket Distributor issues Ticket
6. **Special requirements:** None.

Introduction to UML

UML –Use Cases relationships

Inheritance Relationship

- To express specialization/generalization relations

Extends Relationship

- To represent seldom invoked use cases or exceptional functionality

Includes Relationship

- To represent functional behavior common to more than one use case.


<<extends>> relationships model exceptional or seldom invoked cases

- The exceptional event flows are factored out of the main event flow for clarity
- The direction of an <<extends>> relationship is to the extended use case
- Use Cases representing exceptional flows can extend more than one use case.




Introduction to UML

UML –Use Cases relationships



Introduction to UML


UML –Use Cases relationships



- **<<includes>>** relationship represents common functionality needed in more than one use case
- **<<includes>>** behavior is factored out for reuse, not because it is an exception
- The direction of an **<<includes>>** relationship is to the using use case (unlike the direction of the **<<extends>>** relationship).

Introduction to UML


UML – A better understanding of the problem – the structure_2



Class diagram represents the structure of the system

Introduction to UML


UML – A better understanding of the problem – the behavior



Sequence diagrams describe behavior as interactions between objects

Introduction to UML

UML – A better understanding of the problem – the behavior_2



States transitions diagrams describe behavior by means of states and transitions

UML – Advantages of using Class Diagram


context PCMember**inv** apprprPapToReview:

```

self.papersToReview->select(p:Paper | Set{BiddResult::conflict,
BiddResult::refuseToEv}->includes(p.biddingResult->any(br |
br.pCMembers->includes(self)).resBid))->isEmpty and

```

```
self.papersToReview.authors->excludes(self.oclAsType(Author))
```




UML – Object Diagram Snapshot



Introduction to UML

UML – OCLE Customize Evaluation



Introduction to UML

UML – Model Checking using OCLE

ocle 2.0 - OCL Environment

File Model Project Edit Tools Options Help

Project UserModel Metamodel

Object properties

Name	pc1
Namespaces	Collaboration
Visibility	public
Stereotypes	
Tagged Values	
Constraints	
Classifiers	
Owned Instances	
Slots	

```
model CMMModel

context PCMember

  inv appropriapToReview:
    self.papersToReview >select(p:Paper | Set(BiddResult::conflict, BiddResult::refuseToEv) >includes(p.biddingResult >any(br | br.pCMembers >includes(self)).resDid) >isEmpty and
    self.papersToReview.authors->excludes(self.oclasType(Author))

  inv sessionChair:
    not self.pcmSection.isDefined implies self.section.sectionSpeakers->excludes(self.oclasType(Author))

  def selectEvRes:
    let selectEvRes(p:Paper):EvaluationResult = self.evaluationResult->select(er:EvaluationResult | p.evaluationResult = er)->any(true)

context Conference::assignPaperToReview(ptr:Paper, rev:PCMember)

  pre:
    ptr.reviewers->size < 4 and ptr.reviewers->excludes(rev) and
    self.submittedPapers->includes(ptr) and self.pCCommittee->includes(rev) and
    Set(BiddResult::conflict, BiddResult::refuseToEv)->excludes(ptr.biddingResult->select(br | br.pCMembers = rev)->any(true).res3id)

  post:
    ptr.reviewers->includes(rev) and ptr.reviewers->size = ptr.reviewers@pre->size + 1

context Conference
  def allEvalResBorderline:

    let allEvalResBorderline:Set(Paper)=self.authors.submittedPapers->asSet->select(p:Paper | p.evaluationResult.resEv->forall(rE | rE=EvResult::borderlinePaper))

    let acceptedPapersC: Set(Paper) = self.authors.submittedPapers->asSet->select(p:Paper | Set(EvResult::strongAccept, EvResult::accept, EvResult::weakAccept, EvResult::borderlinePaper)->includes(p.evaluationResult.resEv))

    let rejectedPapersC: Set(Paper) = self.authors.submittedPapers->asSet->select(p:Paper | Set(EvResult::strongReject, EvResult::reject, EvResult::weakReject, EvResult::borderlinePaper)->includes(p.evaluationResult.resEv))
```

Insert 7:70 Write enabled


C:\Users\chiorDidactic\LM\AOCL\ConfMan\ConfMan.bcr

Errors

- UML metamodel(uml15)
- User model(CMMModel)
- PCMember
- not self.pcmSection.isDefined implies self.section.sectionSpeakers->excludes(self.oclasType(Author))
- self.papersToReview->select(p:Paper|Set(BiddResult::conflict,BiddResult::refuseToEv)->includes(p.biddingResult->any(br|br.pCMembers->includes(self).resDid))->isEmpty and self.papersToReview.authors->excludes(self.oclasType(Author))
- Rule failed for context "pc1::Object"
- Rule failed for context "pc3::Object"


Introduction to UML

UML – CD qualified associations & constraints




Introduction to UML

UML – Collaboration Diagram




UML – Activity Diagram




Introduction to UML

UML – Component Diagram




Introduction to UML

UML – Deployment Diagram




Introduction to UML

UML – System Architecture



UML – definition; Foundation Packages



Introduction to UML




Figure 2-3 Behavioral Elements Packages

Introduction to UML





Figure 2-5 Core Package - Backbone

Introduction to UML



Introduction to UML





Figure 2-8 Core Package - Classifiers

Introduction to UML



Introduction to UML

At most one AssociationEnd may be an aggregation or composition.

```
self.allConnections->select(aggregation <#none)->size <= 1
```

```
-- [2] At most one AssociationEnd may be an aggregation or composition.
```

```
inv WFR_2_Association:
```

```
self.allConnectionsS->select(aggregation <> #none)->size <= 1
```

Additional operations

[1] The operation allConnections results in the set of all AssociationEnds of the Association.




```
allConnections : Set(AssociationEnd);  
allConnections = self.connection
```

```
-- [1] The operation allConnections results in the set of all AssociationEnds of the Association
```

```
def:
```

```
let allConnectionsS: Set(AssociationEnd) = self.connection->asSet
```

Introduction to UML



Introduction to UML

The operation `allConnections` results in the set of all `AssociationEnds` of the `AssociationClass`, including all connections defined by its parent (transitive closure).

```
allConnections : Set(AssociationEnd);
allConnections = self.connection->union(self.parent->select
    (s | s.oclIsKindOf(Association))>collect (a : Association |
        a.allConnections))>asSet
```

context `AssociationClass`


```
-- [1] The operation allConnections results in the set of all AssociationEnds of the AssociationClass, including all connections defi
-- by its parent (transitive closure). The parents of an associationClass can be a "simple" class or an associationClass. In th
-- first case, (class) the allConnection AO is not defined. The "similar" AO and concept is named oppositeAssociationEnds. This
-- have to be clearly mentioned in the AO textual description and the visibility must be taken into account in inheritance.
```

def `allConnectionsS:`

```
-- let allConnectionsI: Set(AssociationEnd) = self.connection->union(self.parent->select(s | s.oclIsKindOf(Association))>
-- collect (a : Association | a.allConnections))>asSet

let allConnectionsS: Set(AssociationEnd) = (self.connection->union(self.parent->select(s | s.oclIsKindOf(Association))
    .oclAsType(Association)>collect(a: Association |a.allConnections)
    ->asSequence))>asSet
```

Introduction to UML



Introduction to UML

```
C:\Users\Dan\OneDrive\Temporary\Company_Example.xml
</UML:Classifier.feature>
<UML:Namespace.ownedElement>
  <UML:Generalization xmi.id="S.387" parent="S.349" child="S.237" name="Bank_is_a_NamedEntities" namespace="S.237" visibility="public" isSpecification="false"/>
</UML:Namespace.ownedElement>
</UML:Class>
<UML:Class xmi.id="S.12" isActive="false" instance="S.94 S.136" typedParameter="S.397" isRoot="false" isLeaf="true" isAbstract="false" generalization="S.398" name="Company" namespace="S.1" visibility="public" isSpecification="false">
  <UML:Classifier.feature>
    <UML:Attribute xmi.id="S.142" attributeLink="S.253 S.140" type="S.327" ordering="unordered" targetScope="instance" changeability="changeable" owner="S.12" visibility="public" ownerScope="instance">
      <UML:Attribute.initialValue>
        <UML:Expression xmi.id="S.388" body="" language=""/>
      </UML:Attribute.initialValue>
      <UML:StructuralFeature.multiplicity>
        <UML:Multiplicity xmi.id="S.389">
          <UML:Multiplicity.range>
            <UML:MultiplicityRange xmi.id="S.390" multiplicity="S.389" lower="1" upper="1"/>
          </UML:Multiplicity.range>
        </UML:Multiplicity>
      </UML:StructuralFeature.multiplicity>
    </UML:Attribute>
    <UML:Operation xmi.id="S.391" isRoot="false" isLeaf="false" isAbstract="false" concurrency="sequential" isQuery="false" owner="S.12" visibility="public" ownerScope="instance" name="stockPrice">
      <UML:BehavioralFeature.parameter>
        <UML:Parameter xmi.id="S.358" type="S.357" kind="return" behavioralFeature="S.391" name="stockPrice.Return" visibility="public" isSpecification="false"/>
      </UML:BehavioralFeature.parameter>
    </UML:Operation>
    <UML:Operation xmi.id="S.392" isRoot="false" isLeaf="false" isAbstract="false" concurrency="sequential" isQuery="false" owner="S.12" visibility="public" ownerScope="instance" name="hireEmployee">
      <UML:BehavioralFeature.parameter>
        <UML:Parameter xmi.id="S.347" type="S.19" kind="inout" behavioralFeature="S.392" name="p" visibility="public" isSpecification="false">
          <UML:Parameter.defaultValue>
            <UML:Expression xmi.id="S.393" body="" language=""/>
          </UML:Parameter.defaultValue>
        </UML:Parameter>
      </UML:BehavioralFeature.parameter>
    </UML:Operation>
  </UML:Classifier.feature>
</UML:Class>
```

Introduction to UML

Thanks for your patience!